

Package ‘Julia’

February 14, 2012

Type Package

Title Fractal Image Data Generator

Version 1.0

Date 2011-02-11

Author Mehmet Suzen

Maintainer Mehmet Suzen <mehmet.suzen@physics.org>

Description Generates image data for fractals (Julia and Mandelbrot sets) on the complex plane in the given region and resolution.

License GPL-3

LazyLoad yes

Repository CRAN

Date/Publication 2011-02-12 13:30:24

R topics documented:

Julia-package	2
JuliaImage	3
JuliaIterate	4
MandelImage	5
MandelIterate	6

Index	7
--------------	----------

Julia-package

Julia

Description

Generates image data for fractals (Julia and Mandelbrot sets) on the complex plane in the given region and resolution.

Details

Package: Julia
Type: Package
Version: 1.0
Date: 2011-02-11
License: GPL-3
LazyLoad: yes

Author(s)

Mehmet Suzen Maintainer: Mehmet Suzen <mehmet.suzen@physics.org>

Examples

```
# Julia Set
imageN <- 5;
centre <- -1.0
L <- 2.0
file <- "julia1a.png"
C <- 1-1.6180339887;# Golden Ration
image <- JuliaImage(imageN,centre,L,C);
# writePNG(image,file);# possible visulisation
# Mandelbrot Set
imageN <- 5;
centre <- 0.0
L <- 4.0
file <- "mandelbrot1.png"
image<-MandelImage(imageN,centre,L);
# writePNG(image,file);# possible visulisation
```

JuliaImage

Julia Set Generator in a Square Region

Description

'JuliaImage' returns two dimensional array representing escape values from on the square region in complex plane. Escape values (which measures the number of iteration before the length of the complex value reaches to 2).

Usage

```
JuliaImage(imageN, centre, L, C)
```

Arguments

imageN	Number of pixels to equally space division of one side if the square region.
centre	A complex number that determines the centre of the square region
L	A side length of the square region on the complex plane.
C	Complex coefficient

Details

Julia Set is defined as the set of initial complex values where the $z = z^2 + C$ does not diverge to infinity. C is an arbitrary complex constant that does not change during the iteration by definition.

Value

It returns a 2D array of real values from 0 to 1. The array corresponds to image on the complex plane.

Note

Post processing to plot/color mapping of the Julia set for visualisation can be done by using the array generated. See examples to get a png output.

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

References

Gaston Julia (1918) "Memoire sur l'iteration des fonctions rationnelles," Journal de Mathematiques Pures et Appliquees, vol. 8, pages 47-245.

See Also

[MandelImage](#)

Examples

```
#
# Generating png of the Julia set
# C is 1 minus the golden ratio
#
imageN <- 5;
centre <- 0.0
L <- 4.0
C <- 1-1.6180339887;# Golden Ratio
image <- JuliaImage(imageN,centre,L,C);
#library(png)
#file <- "julia1.png"
#writePNG(image,file); # possible visulation
#
# Generating png of the Julia set
# different coefficient.
#
imageN <- 5;
centre <- 0.0
L <- 4.0
C <- -0.70176-0.3842i
image <- JuliaImage(imageN,centre,L,C);
#library(png)
#file <- "julia2.png"
#writePNG(image,file); # possible visulation
```

JuliaIterate

JuliaIterate

Description

'JuliaIterate' returns the number of iteration until a complex value diverges for the Julia map for a give complex number.

Usage

```
JuliaIterate(z, C)
```

Arguments

z A complex coordinate (initial value for the map).
C A complex constant.

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

Examples

```
z<-0+0i
C <- 1-1.6180339887;# Golden Ratio
it<- JuliaIterate(z,C)
```

MandelImage

Mandelbrot Set Generator in a Square Domain

Description

'MandelImage' returns two dimensional array representing escape values from on the square region in complex plane. Escape values (which measures the number of iteration before the length of the complex value reaches to 2.)

Usage

```
MandelImage(imageN, centre, L)
```

Arguments

imageN	Number of pixels to equally space division of one side if the square region.
centre	A complex number that determines the centre of the square region.
L	A side length of the square region on the complex plane.

Details

Mandelbrot set is defined as the set of initial complex values where the $z = z^2 + z_0$ does not diverge to infinity. Initial value for the map is taken to be zero and z_0 is the complex coordinate.

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

See Also

[JuliaImage](#)

Examples

```
# png image
imageN <- 5;
centre <- 0.0
L <- 4.0
image<-MandelImage(imageN,centre,L);
#file <- "mandelbrot1.png"
# writePNG(image,file); # possible visualisation
# Closer lookup to set
imageN <- 5;
```

```
centre <- -0.5
L <- 2.0
image<-MandelImage(imageN,centre,L);
# file <- "mandelbrot.png"
#writePNG(image,file); # possible visualisation
```

MandelIterate

MandelIterate

Description

'MandelIterate' returns the number of iteration until a complex value diverges for the Mandelbrot map for a give complex number.

Usage

```
MandelIterate(z_0)
```

Arguments

`z_0` A complex coordinate (constant coefficient value for the map)

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

Examples

```
z_0<-0-0.5i
it<- MandelIterate(z_0)
```

Index

*Topic **package**

Julia-package, [2](#)

Julia (Julia-package), [2](#)

Julia-package, [2](#)

JuliaImage, [3](#), [5](#)

JuliaIterate, [4](#)

MandelImage, [3](#), [5](#)

MandelIterate, [6](#)