

Package ‘PCS’

June 18, 2009

Type Package

Title Calculate the probability of correct selection (PCS)

Version 1.0

Date 2009-04-15

Depends statmod, multtest

Author Jason Wilson

Maintainer <jason.wilson@biola.edu>

Description Given k populations (can be in thousands), what is the probability that a given subset of size t contains the true top t populations? This package finds this probability and offers three tuning parameters (G , d , L) to relax the definition.

License GPL-3

LazyLoad yes

Repository CRAN

Date/Publication 2009-06-18 07:28:19

R topics documented:

| | |
|--------------------------------|-----------|
| PCS-package | 2 |
| G.H.Quad | 4 |
| PCS.boot.par | 5 |
| PdCSGt.bootstrap.NP2 | 8 |
| PdofCSGt.bootstrap5 | 10 |
| PdofCSt.T1or2 | 11 |
| PofCSLt.bootstrap5 | 12 |
| PofCSt | 13 |
| tindep | 14 |
| Index | 16 |

PCS-package

Probability of Correct Selection (PCS)

Description

These functions calculate the probability of correct selection (PCS) with G-best, d-best, and L-best selection as described in Cui & Wilson (2008) and Cui, Zhao, & Wilson (2008). The specific parameters (G,d,L), distributional assumptions (normal, Student's t, non-parametric), and calculation method (exact, bootstrap) are user-settable.

Details

Package: PCS
Type: Package
Version: 1.0
Date: 2009-04-15
License: What license is it under?
LazyLoad: yes

Probability of Correct Selection (PCS) is the probability of selecting the best t of k populations. This package allows the user to calculate the PCS for a given dataset. When k is large, even if the best t populations are significantly different from the rest, the PCS may be small due to sample variance. To address this issue, Cui & Wilson (2008, 2009) developed three tuning parameters whereby the definition of correct selection is modified (d-best, G-best, L-best) to more realistic and acceptable standards for large k problems. This package is the implementation of these three definitions, using different calculation methods.

The PCS package consists of three primary functions for users: `PCS.boot.par`, `PCS.boot.np`, and `PCS.exact`. `PCS.boot.par` and `PCS.boot.np` use parametric and non-parametric bootstraps, respectively, to calculate d-best, G-best, and L-best PCS. `PCS.boot.par` is the fastest function for large k problems. It is expected to be the most commonly used, as the parametric distributional (normal & Student's t) assumptions are reasonable and moderately robust (Cui & Wilson 2009). When k is large and the distributional assumptions are not met, then `PCS.boot.np` may be used. For information regarding the necessary sample size, see (Cui & Wilson 2009). When k is small to moderate, `PCS.exact` may be used to obtain PCS using the analytic formula.

Note

I would like to thank Xiping Cui for her support while creating this package, Thomas Girke for use of the UCR Bioinformatics Cluster, Bushi Wang for stress testing the code, and God for all the help on the way.

Author(s)

Jason Wilson Maintainer: <jason.wilson@biola.edu>

References

- Cui, X. and Wilson, J. 2007. On How to Calculate the Probability of Correct Selection for Large k Populations. University of California, Riverside Statistics Department Technical Report 297. http://www.bubbs.biola.edu/~jason.wilson/Article2_tech_techreport.pdf
- Cui, X. and Wilson, J. 2008. On the Probability of Correct Selection for Large k Populations, with Application to Microarray Data. *Biometrical Journal*, 50:5, 870-883. http://www.bubbs.biola.edu/~jason.wilson/Article1_Revision.pdf
- Cui, X. and Wilson, J. 2009. A Simulation Study on the Probability of Correct Selection for Large k Populations. *Communications in Statistics - Simulation and Computation*, 38:6. http://www.bubbs.biola.edu/~jason.wilson/Article2_sim_revised02.pdf
- Cui, X.; Zhao, H. and Wilson, J. Optimization of Gene Selection in Microarray Experiments. 2008. Submitted.

Examples

```
##### Small example for PCS.boot.par & PCS.exact
theta = c(4.2, 2.5, 2.3, 1.7, 1.5, 1.0)
theta = sort(theta)
T = c(1,2,3,5); G = 1:3; D = c(0.5,1,1.5); L = 1:2
PCS.boot.par(theta, T, G, D, L, B=100, SDE=1, dist="normal", df=14, trunc=6)
PCS.exact(theta, t=2, g=1, d=NULL, m=20, tol=1e-8)
```

```
##### Small example for PCS.boot.np
k=20 #number of populations
n=10 #sample size
SD=.1 #standard deviation
theta = seq(0,6,length.out=k)
X1 = rnorm(k*n,0,SD) #Sample 1
X1 = matrix(X1,nrow=k,ncol=n,byrow=FALSE)
X2 = rnorm(k*n,theta,SD) #Sample 2, shifted
X2 = matrix(X2,nrow=k,ncol=n,byrow=FALSE)
PCS.boot.np(X1, X2, T, G, D, B=100, trunc=6)
```

```
##### Microarray example of t-statistics with PCS.boot.par
library(multtest)
data(golub) #Load microarray data
ans = tindep(golub[,1:27], golub[,28:38], flag=1) #Obtain t-statistics
golub.T = sort(abs(ans[,1])) #Message t-statistics
T=c(1,5,10,25,50,92); G=c(1,10,25,50,150); D=c(0,1,2) #Set PCS parameters
df=18 #Degrees of freedom from Sat
sde=sqrt((18/(18-2))/19) #Estimate SDE by method of m
PCS.boot.par(golub.T, T, G, D, L=NULL, B=100, SDE=sde, dist="t", df=18) #Small bootstrap sam
```

```
##### Microarray example of Golub's correlation statistics (see reference) with PCS.boot.par
library(multtest)
data(golub) #Load microarray data
Pgc <- function(x,y) { #Function to calculate Golub
  xbar1 = apply(x,1,mean)
  xbar2 = apply(y,1,mean)
  sd1 = apply(x,1,sd)
```

```

sd2 = apply(y,1,sd)
Pgc = abs((xbar1-xbar2))/(sd1+sd2)
return(Pgc)
} #end function
Pgc.gol = Pgc(golub[,1:27],golub[,28:38]) #Calculate correlation stati
T=c(1,5,10,25,50,92); G=c(1,10,25,50,150); D=c(0,1,2) #Set PCS parameters
sde=0.20 #Obtained by simulat
PCS.boot.par(Pgc.gol, T, G, D, L=NULL, B=100, SDE=0.2, dist="t", df=18) #Small bootstrap sam

##### Microarray example using non-parametric bootstrap
library(multtest)
data(golub) #Load microarray data
T=c(1,5,10); G=c(1,3,5); D=c(0,1,2) #Set PCS parameters
PCS.boot.np(golub[,1:27], golub[,28:38], T, G, D, B=10, trunc=6) #Small bootstrap sample siz

```

G.H.Quad

Gauss-Hermite Quadrature function

Description

Performs Gauss-Hermite Quadrature for an arbitrary number of nodes. Function for use in PofCSt.

Usage

```
G.H.Quad(x, m)
```

Arguments

| | |
|---|---|
| x | x is an m-vector upon which Gauss-Hermite Quadrature is to be applied |
| m | m is the number of nodes desired for the Gauss-Hermite Quadrature |

Details

This function uses `gauss.quad.prob` in the `statmod` package to perform Gauss-Hermite Quadrature inside of the `PofCSt` function.

Value

The result of the Gauss-Hermite Quadrature.

Author(s)

Jason Wilson, <jason.wilson@biola.edu>

References

Hildebrand, F.B. 1956. Introduction to Numerical Analysis. McGraw-Hill.

See Also[PofCSt](#)

 PCS.boot.par *Probability of correct selection (PCS) calculator*

Description

These functions calculate the probability of correct selection (PCS) with G-best, d-best, and L-best selection as described in Cui & Wilson (2008) and Cui, Zhao, & Wilson (2008). The specific parameters (G,d,L), distributional assumptions (normal, Student's t, non-parametric), and calculation method (exact, bootstrap) are user-settable.

Usage

```
PCS.boot.par(theta, T = 1:1, G = NULL, D = NULL, L = NULL, B = 100, SDE = 1, dist =
PCS.boot.np(X1, X2, T = 1, G = 1, D = NULL, B, trunc = 6)
PCS.exact(theta, t = 1, g = NULL, d = NULL, m = 20, tol = 1e-08)
```

Arguments

| | |
|-------|--|
| theta | theta Vector of statistics (or parameters) from which it is desired to select the top t of them |
| T | T Vector of the number of statistics (or parameters) desired to be selected |
| t | t The number of statistics (or parameters) desired to be selected (scalar) |
| G | G Vector of G-best selection parameters |
| g | g The G-best selection parameter (scalar) |
| D | D Vector of d-best selection parameters |
| d | d The d-best selection parameter (scalar) |
| L | L Vector of L-best selection parameters |
| X1 | X1 k by n1 matrix of data. k is the number of populations and n1 the sample size of the first treatment. |
| X2 | X2 k by n2 matrix of data. k is the number of populations and n2 the sample size of the second treatment. |
| B | B Bootstrap sample size |
| SDE | SDE Standard error of the statistics theta (row-wise) |
| dist | dist Distributional assumption used for estimating PCS |
| df | df Common degrees of freedom for one of the t-statistics in theta; the parameter is only used if dist="t" |
| trunc | trunc Number of standard errors below the minimum selected population to disregard in the estimation of PCS; it is a truncation parameter to decrease run time |
| m | m Number of nodes employed in the Gauss-Hermite quadrature |
| tol | tol Tolerance parameter to set the cut-off level for the inclusion of additional probability components in PCS |

Details

The probability of correct selection (PCS) is a single statistic calculated on a vector of sample statistics whose interpretation is the probability that the top t populations selected according to the sample rank would be the true top t populations. PCS may be used in addition to, or instead of, multiple comparison procedures. The PCS package is an implementation of the formulas and ideas in Cui & Wilson (2008) and Cui, Zhao, & Wilson (2008).

After a multi-population experiment is conducted, whether with one, two, or more treatments, a vector of one sample statistic for each population is obtained. This vector is θ . Suppose θ has length k . The user will want to know the probability of correctly selecting some number t of the k populations. T is a vector of all such t desired to be checked. When k is large, the resulting probabilities can be uncomfortably small, even if the corresponding multiple-testing p -values are significant. In order to increase the resulting probabilities (PCS), three tuning parameters have been devised.

g is the number of populations which will be selected in addition to t . Thus, $g+t$ populations are selected, only t of which must be the true top t populations in order to be considered correct. (Cui & Wilson 2007). G is a vector of such g 's. Scalar g is used in the exact function (PCS.exact) and vector G is used in the bootstraps (PCS.boot.par & PCS.boot.np).

d does not directly specify a number of additional populations. Rather, d is the number of standard errors above and below the statistic whose rank is t (hereafter the "tth" statistic). The other statistics which fall in this range are considered close enough to the top t statistics which will be considered comparable to the tth population and therefore considered correct (since the tth statistic is an estimate of the tth population parameter). Thus, t populations are selected, but a random subset of the populations determined by d are considered "close enough" to the top t and are also considered correct (Cui & Wilson 2007). D is a vector of such d 's. Scalar d is used in the exact function (PCS.exact) and vector D is used in the bootstraps (PCS.boot.par & PCS.boot.np). The above interpretation holds when the statistics of θ are standardized (SDE=1); when they are not, then d represents the number of units from the tth statistic, where the units are given by the data. Simulation studies suggest $d > 2$ often produces significantly biased PCS when standardized statistics are used. Therefore, it is recommended that $d \leq 2$ be used when θ is standardized and d not greater than two standard errors when θ is not standardized.

l is the number of populations, out of the top t , which need to be included in the selected t to be considered a correct selection. Thus, t populations are selected, only l of which must be in the true top t , in order to be considered correct. (Cui & Wilson & Zahn 2008). L is a vector of such l . The parameter has not been implemented in the exact function (PCS.exact) or the non-parametric bootstrap (PCS.boot.np), only the parametric bootstrap (PCS.boot.par).

The run time of the function is directly proportional to the bootstrap sample size, B , (as well as the number of elements of T , D , G , and L). In practice, it is recommended that preliminary runs use a small B (e.g. $B=100$), in order to obtain estimates of PCS (off by several percent). Then, when the desired parameters for final calculations are known, B should be run at $B=10000$, or more, depending on the application.

The SDE needs to be supplied by the user (this potential inconvenience is balanced by serving to make the code more general). If the statistics in θ are already standardized, as they often will be, then SDE=1. If the statistics in θ are not standardized, then a form of pooled standard error could be used for SDE. As for distributional assumptions, PCS.exact assumes a normal distribution on the elements of θ . PCS.boot.par allows for a "normal" or a "t" (Student's t , with degrees of freedom = df) distribution. PCS.boot.np is non-parametric, and requires significantly larger sample sizes in order to accurately estimate PCS (see Cui & Wilson 2009). In order to reduce run time, PCS.exact implements a tolerance parameter, tol , at four different levels of the calculations. It is

defaulted conservatively to 1e-8 in order to produce answers exact to at least five decimal places of accuracy. PCS.boot.par and PCS.boot.np both implement a truncation parameter that reduces the size of the bootstrapped theta vector. It works by cutting the vector 'trunc' standard errors below the maximum Tth element of theta. trunc=6 produced no loss of accuracy on the runs attempted, while a loss of over 1 and m is the number of nodes employed. It is defaulted to m=20, which produced the same accuracy, to four or more decimal places, as m=1000.

As is customary in the Ranking and Selection literature, the three functions PCS.exact, PCS.boot.par, and PCS.boot.np all assume that the best statistics in theta are the largest. If the best statistics are the smallest, then a simple conversion will allow the functions to work equally well on the data. See the examples.

Value

For PCS.exact, the value is a scalar of the PCS for the parameters entered. For PCS.boot.par and PCS.boot.np, a matrix is returned whose rows are the entries of G, D, or L and whose columns are the entries of T. If more than one of G, D, or L is entered, then a list is returned, where the G element of the list is the G-best matrix, the d element is the d-best matrix, and the L element is the L-best matrix.

Author(s)

Jason Wilson Maintainer: <jason.wilson@biola.edu>

References

- Cui, X. and Wilson, J. 2007. On How to Calculate the Probability of Correct Selection for Large k Populations. University of California, Riverside Statistics Department Technical Report 297. http://www.bubbs.biola.edu/~jason.wilson/Article2_tech_techreport.pdf
- Cui, X. and Wilson, J. 2008. On the Probability of Correct Selection for Large k Populations, with Application to Microarray Data. Biometrical Journal, 50:5, 870-883. http://www.bubbs.biola.edu/~jason.wilson/Article1_Revision.pdf
- Cui, X. and Wilson, J. 2009. A Simulation Study on the Probability of Correct Selection for Large k Populations. Communications in Statistics: Simulation and Computation. 38:6. http://www.bubbs.biola.edu/~jason.wilson/Article2_sim_revised02.pdf
- Cui, X.; Zhao, H. and Wilson, J. 2008. Optimization of Gene Selection in Microarray Experiments. Submitted.
- Golub, T. et al. 1999. Molecular Classification of Cancer Class Discovery and Class Prediction by Gene Expression Monitoring. Science. 286:531-537.

Examples

```
##### Small example for PCS.boot.par & PCS.exact
theta = c(1.0, 1.5, 1.7, 2.3, 2.5, 4.2)
T = c(1,2,3,5); G = 0:3; D = c(0.5,1,1.5); L = 1:2
PCS.boot.par(theta, T, G, D, L, B=1000, SDE=1, dist="normal", trunc=6)
PCS.exact(theta, t=2, g=1, d=NULL, m=20, tol=1e-8)

#The above assumes the largest thetas are best.
#To select the smallest thetas, reverse the order of the indices, e.g.
```

```

theta.new = max(theta) - theta + min(theta)
T = c(1,2,3,5); G = 0:3; D = c(0.5,1,1.5); L = 1:2
PCS.boot.par(theta.new, T, G, D, L, B=1000, SDE=1, dist="normal", trunc=6)
PCS.exact(theta.new, t=2, g=1, d=NULL, m=20, tol=1e-8)

##### Small example for PCS.boot.np
k=20 #number of populations
n=10 #sample size
SD=.1 #standard deviation
theta = seq(0,6,length.out=k)
X1 = rnorm(k*n,0,SD) #Sample 1
X1 = matrix(X1,nrow=k,ncol=n,byrow=FALSE)
X2 = rnorm(k*n,theta,SD) #Sample 2, shifted
X2 = matrix(X2,nrow=k,ncol=n,byrow=FALSE)
T = c(1,2,3,5); G = 0:3; D = c(0.5,1,1.5); L = 1:2
PCS.boot.np(X1, X2, T, G, D, B=1000, trunc=6)

##### Microarray example of t-statistics with PCS.boot.par
library(multttest)
data(golub) #Load microarray data
ans = tindep(golub[,1:27], golub[,28:38], flag=1) #Obtain t-statistics
golub.T = sort(abs(ans[,1])) #Message t-statistics
T=c(1,5,10,25,50,92); G=c(1,10,25,50,150); D=c(0,1,2) #Set PCS parameters
df=18 #Degrees of freedom from Sat
sde=sqrt((18/(18-2))/19) #Estimate SDE by method of m
PCS.boot.par(golub.T, T, G, D, L=NULL, B=100, SDE=sde, dist="t", df=18) #Small bootstrap sam

##### Microarray example of Golub's correlation statistics (see reference) with PCS.boot.par
library(multttest)
data(golub) #Load microarray data
Pgc <- function(x,y) { #Function to calculate Golub
  xbar1 = apply(x,1,mean)
  xbar2 = apply(y,1,mean)
  sd1 = apply(x,1,sd)
  sd2 = apply(y,1,sd)
  Pgc = abs((xbar1-xbar2))/(sd1+sd2)
  return(Pgc)
} #end function
Pgc.gol = Pgc(golub[,1:27],golub[,28:38]) #Calculate correlation stati
T=c(1,5,10,25,50,92); G=c(1,10,25,50,150); D=c(0,1,2) #Set PCS parameters
sde=0.20 #Obtained by simulat
PCS.boot.par(Pgc.gol, T, G, D, L=NULL, B=100, SDE=0.2, dist="t", df=18) #Small bootstrap sam

##### Microarray example using non-parametric bootstrap
library(multttest)
data(golub) #Load microarray data
T=c(1,5,10); G=c(1,3,5); D=c(0,1,2) #Set PCS parameters
PCS.boot.np(golub[,1:27], golub[,28:38], T, G, D, B=10, trunc=6) #Small bootstrap sample siz

```

PdCSGt.bootstrap.NP2

*Non-parametric bootstrap for computing G-best and d-best PCS***Description**

Non-parametric bootstrap for computing G-best and d-best PCS. This function is called by the wrapper PCS.boot.np.

Usage

```
PdCSGt.bootstrap.NP2(X1, X2, T, D, G, N, trunc = 6)
```

Arguments

| | |
|-------|--|
| X1 | X1 k by n1 matrix of data. k is the number of populations and n1 the sample size of the first treatment. |
| X2 | X2 k by n2 matrix of data. k is the number of populations and n2 the sample size of the second treatment. |
| T | T Vector of the number of statistics (or parameters) desired to be selected |
| D | D Vector of d-best selection parameters |
| G | G Vector of G-best selection parameters |
| N | N The bootstrap sample size |
| trunc | trunc Number of standard errors below the minimum selected population to disregard in the estimation of PCS; it is a truncation parameter to decrease run time |

Value

A matrix whose rows are the entries of G or D and whose columns are the entries of T. If both G and D are entered, then a list is returned, where the *GelementistheG – bestmatrix, thed* element is the d-best matrix.

Author(s)

Jason Wilson, <jason.wilson@biola.edu>

References

Cui, X. and Wilson, J. 2009. A Simulation Study on the Probability of Correct Selection for Large k Populations. Communications in Statistics: Simulation and Computation. 38:6. http://www.bubbs.biola.edu/~jason.wilson/Article2_sim_revised02.pdf

See Also

[PCS.boot.np](#)

PdofCSGt.bootstrap5

Parametric bootstrap for computing G-best and d-best PCS

Description

Parametric bootstrap for computing G-best and d-best PCS. This function is called by the wrapper PCS.boot.par.

Usage

```
PdofCSGt.bootstrap5(theta, T, D, G, B, SDE, dist = c("normal", "t"), df = 14, trunc
```

Arguments

| | |
|-----------|--|
| theta | theta Vector of statistics (or parameters) from which it is desired to select the top t of them |
| T | T Vector of the number of statistics (or parameters) desired to be selected |
| D | D Vector of d-best selection parameters |
| G | G Vector of G-best selection parameters |
| B | B Bootstrap sample size |
| SDE | SDE Standard error of the statistics theta (row-wise) |
| dist | dist Distributional assumption used for estimating PCS |
| df | df Common degrees of freedom for one of the t-statistics in theta; the parameter is only used if dist="t" |
| trunc | trunc Number of standard errors below the minimum selected population to disregard in the estimation of PCS; it is a truncation parameter to decrease run time |
| est.names | est.names Kind of shrinkage estimator employed. Default estimator is "O" for the Olkin estimator. Other estimators will be considered for future releases. |

Value

An array, the non-empty part of which is a matrix whose rows are the entries of G or D and whose columns are the entries of T. If both G and D are entered, then a list is returned, where the *Gelement* is the *G – best matrix*, the *d* element is the d-best matrix.

Author(s)

Jason Wilson, <jason.wilson@biola.edu>

References

Cui, X. and Wilson, J. 2007. On How to Calculate the Probability of Correct Selection for Large k Populations. University of California, Riverside Statistics Department Technical Report 297. http://www.bubbs.biola.edu/~jason.wilson/Article2_tech_techreport.pdf

See Also

[PCS.boot.par](#)

PdofCSt.T1or2

Exact PCS, when selecting t=1 or t=2 or more populations

Description

PdofCSt.T1or2 calls PofCSt to implement the d-best PCS formula for the case of t=1 or t=2 populations. It is called by PdofCSt.cyc2, which implements the d-best PCS formula for general t populations. PofCSGt calls PofCSt to implement the G-best formula for general t. These functions are modular and implement the time reduction techniques of Cui and Wilson (2007).

Usage

```
PdofCSt.T1or2(theta, T, d, m = 20, tol = 1e-08)
PdofCSt.cyc2(theta, T, d, m = 20, tol = 1e-08)
PofCSGt(theta, T, Gd, m = 20, tol = 1e-08)
```

Arguments

| | |
|-------|--|
| theta | theta Vector of statistics (or parameters) from which it is desired to select the top t of them |
| T | T The number of statistics (or parameters) desired to be selected |
| d | d The d-best selection parameter (scalar) |
| Gd | Gd The G-best selection parameter (scalar) |
| m | m Number of nodes employed in the Gauss-Hermite quadrature |
| tol | tol Tolerance parameter to set the cut-off level for the inclusion of additional probability components in PCS |

Value

The probability of correct selection.

Author(s)

Jason Wilson, <jason.wilson@biola.edu>

References

Cui, X. and Wilson, J. 2007. On How to Calculate the Probability of Correct Selection for Large k Populations. University of California, Riverside Statistics Department Technical Report 297. http://www.bubbs.biola.edu/~jason.wilson/Article2_tech_techreport.pdf

See Also

[PofCSt](#), [P dofCSt . Tlor2](#), [P dofCSt . cyc2](#), [P ofCSGt](#)

PofCSLt.bootstrap5 *Parametric bootstrap for computing L-best PCS*

Description

Parametric bootstrap for computing L-best PCS. This function is called by the wrapper PCS.boot.np.

Usage

```
PofCSLt.bootstrap5(theta, T, L, B, SDE, dist = c("normal", "t"), df = 14, trunc = 6)
```

Arguments

| | |
|------------------------|---|
| <code>theta</code> | <code>theta</code> Vector of statistics (or parameters) from which it is desired to select the top <code>t</code> of them |
| <code>T</code> | <code>T</code> Vector of the number of statistics (or parameters) desired to be selected |
| <code>L</code> | <code>L</code> Vector of L-best selection parameters |
| <code>B</code> | <code>B</code> Bootstrap sample size |
| <code>SDE</code> | <code>SDE</code> Standard error of the statistics <code>theta</code> (row-wise) |
| <code>dist</code> | <code>dist</code> Distributional assumption used for estimating PCS |
| <code>df</code> | <code>df</code> Common degrees of freedom for one of the t-statistics in <code>theta</code> ; the parameter is only used if <code>dist="t"</code> |
| <code>trunc</code> | <code>trunc</code> Number of standard errors below the minimum selected population to disregard in the estimation of PCS; it is a truncation parameter to decrease run time |
| <code>est.names</code> | <code>est.names</code> Kind of shrinkage estimator employed. Default estimator is "O" for the Olkin estimator. Other estimators will be considered for future releases. |

Value

An array, the non-empty part of which is a matrix whose rows are the entries of `L` and whose columns are the entries of `T`.

Author(s)

Jason Wilson, <jason.wilson@biola.edu>

References

Cui, X.; Zhao, H. and Wilson, J. 2008. Optimization of Gene Selection in Microarray Experiments. Submitted.

See Also

[PCS.boot.par](#)

PofCSt

Probability of correct selection (PCS) for selecting t out of k populations

Description

Implementation of the Gupta & Liang (1998) formula for computing the probability of correct selection (PCS) for selecting t out of k populations. The results are exact up to a user-settable tolerance parameter. This function is modular and is called by PdocSt.T1or2, PdocSt.cyc2, and PofCSGt.

Usage

```
PofCSt(theta, T, m, tol = 1e-07)
```

Arguments

| | | |
|-------|-------|--|
| theta | theta | Vector of statistics (or parameters) from which it is desired to select the top t of them |
| T | T | The number of statistics (or parameters) desired to be selected |
| m | m | Number of nodes employed in the Gauss-Hermite quadrature |
| tol | tol | Tolerance parameter to set the cut-off level for the inclusion of additional probability components in PCS |

Details

The analytic formula for computing PCS for t of k populations is an integral whose integrand is the product of normal densities. This function obtains the appropriate values and computes the integral using a Gauss-Hermite quadrature. See equation 2.4 of Gupta (1998).

Value

The probability of correct selection.

Author(s)

Jason Wilson, <jason.wilson@biola.edu>

References

Cui, X. and Wilson, J. 2007. On How to Calculate the Probability of Correct Selection for Large k Populations. University of California, Riverside Statistics Department Technical Report 297. http://www.bubbs.biola.edu/~jason.wilson/Article2_tech_techreport.pdf

Gupta, S.S. and Liang, T.C. 1998. Simultaneous lower confidence bounds for probabilities of correct selections. *Journal of Statistical Planning and Inference*. 72(1-2), 279-290.

See Also

[PdofCSt.T1or2](#), [PdofCSt.cyc2](#), [PofCSGt](#)

 tindep

Standardized scores for two independent samples

Description

Calculate the independent two-sample Welch t-statistics for k populations simultaneously. This function is used in PCS.bootstrap.np. It may also be used to summarize data from two sample experiments for use in PCS.exact and PCS.bootstrap.par.

Usage

```
tindep(X, Y, flag = 0)
```

Arguments

| | |
|------|--|
| X | X k by n1 matrix of data. k is the number of populations and n1 the sample size of the first treatment. |
| Y | Y k by n2 matrix of data. k is the number of populations and n2 the sample size of the second treatment. |
| flag | flag Determines whether the output is t-statistics (flag=0) or t-statistics with p-values (flag!=0) |

Details

X & Y are the data matrices for input. When called inside of the function PCS.bootstrap.np, or when used to obtain t-statistics for use with PCS.exact and PCS.bootstrap.par, setting 'flag'=0 will return the needed vector of t-statistics. If flag!=0, then the function 'mt.rawp2adjp' from the multtest library is called, producing multiple comparison adjusted p-values ("Bonferroni", "Holm", "Hochberg", "SidakSS", "SidakSD", "BH", "BY"). The t-statistics and p-values are stored in a matrix.

Value

If `flag = 0`, the result is a `k` by 1 vector of t-statistics. If `flag != 0`, the result is a `k` by 7 vector of t-statistics and p-values (see details).

Author(s)

Jason Wilson, <jason.wilson@biola.edu>

See Also

[PCS.boot.np](#)

Examples

```
### Small example
k=20 #number of populations
n=10 #sample size
SD=.1 #standard deviation
theta = seq(0,6,length.out=k)
X1 = rnorm(k*n,0,SD) #Sample 1
X1 = matrix(X1,nrow=k,ncol=n,byrow=FALSE)
X2 = rnorm(k*n,theta,SD) #Sample 2, shifted
X2 = matrix(X2,nrow=k,ncol=n,byrow=FALSE)
tindep(X1,X2, flag=1)

### Microarray example
library(multtest)
data(golub)
golub.Tp = tindep(golub[,1:27], golub[,28:38], flag=0) #Obtain t-statistics + p-values

ans = tindep(golub[,1:27], golub[,28:38], flag=1) #Obtain t-statistics
golub.T = sort(abs(ans[,1]))
```

Index

*Topic **hstest**

- PCS-package, 1
- PCS.boot.par, 5
- PdCSGt.bootstrap.NP2, 9
- PdofCSGt.bootstrap5, 10
- PdofCSt.T1or2, 11
- PofCSLt.bootstrap5, 12
- PofCSt, 13
- tindep, 14

*Topic **math**

- G.H.Quad, 4
- PCS-package, 1

G.H.Quad, 4

PCS (*PCS-package*), 1

PCS-package, 1

PCS.boot.np, 9, 15

PCS.boot.np (*PCS.boot.par*), 5

PCS.boot.par, 5, 11, 13

PCS.exact (*PCS.boot.par*), 5

PdCSGt.bootstrap.NP2, 8

PdofCSGt.bootstrap5, 10

PdofCSt.cyc2, 12, 14

PdofCSt.cyc2 (*PdofCSt.T1or2*), 11

PdofCSt.T1or2, 11, 12, 14

PofCSGt, 12, 14

PofCSGt (*PdofCSt.T1or2*), 11

PofCSLt.bootstrap5, 12

PofCSt, 4, 12, 13

tindep, 14