

# Package ‘RKEA’

January 24, 2012

**Version** 0.0-3

**Date** 2010-01-22

**Title** R/KEA interface

**Author** Ingo Feinerer, Kurt Hornik

**Maintainer** Kurt Hornik <Kurt.Hornik@R-project.org>

**Description** An R interface to KEA (Version 5.0). KEA (for Keyphrase Extraction Algorithm) allows for extracting keyphrases from text documents. It can be either used for free indexing or for indexing with a controlled vocabulary. For more information see <http://www.nzdl.org/Kea/>.

**Imports** rJava (>= 0.6-3), tm

**SystemRequirements** Java (>= 5.0)

**License** GPL-2

**Repository** CRAN

**Date/Publication** 2012-01-24 16:13:45

## R topics documented:

createModel . . . . . 2  
extractKeywords . . . . . 3

**Index** . . . . . 4

---

`createModel`*Create a KEA Model*

---

**Description**

Create a keyphrase extraction model.

**Usage**

```
createModel(corpus, keywords, model, voc = "none", vocformat = "")
```

**Arguments**

<code>corpus</code>	A list of character vectors containing the text documents, e.g., a Corpus object as provided by package <code>tm</code> .
<code>keywords</code>	A list of character vectors containing the keywords for each document in corpus.
<code>model</code>	A character giving the path where the created model should be stored.
<code>voc</code>	A character pointing to a controlled vocabulary.
<code>vocformat</code>	A character giving the format of voc.

**Details**

A tutorial on keyword extraction is located at <http://www.nzdl.org/Kea/Download/Kea-5.0-Readme.txt>. There you can find details on the internals of KEA, including various parameter settings (e.g., valid arguments for `voc` and `vocformat`).

**Value**

Invisibly returns `model`, i.e., the path to the created KEA model.

**Author(s)**

Ingo Feinerer

**References**

<http://www.nzdl.org/Kea/>

**See Also**

[extractKeywords](#)

---

extractKeywords	<i>Extract Keywords</i>
-----------------	-------------------------

---

**Description**

Extract keywords from text documents.

**Usage**

```
extractKeywords(corpus, model, voc = "none", vocformat = "")
```

**Arguments**

corpus	A list of character vectors containing the text documents, e.g., a Corpus object as provided by package <code>tm</code> , used for keyword extraction.
model	A character giving the path to a KEA model.
voc	A character pointing to a controlled vocabulary.
vocformat	A character giving the format of voc.

**Details**

A tutorial on keyword extraction is located at <http://www.nzdl.org/Kea/Download/Kea-5.0-Readme.txt>. There you can find details on the internals of KEA, including various parameter settings (e.g., valid arguments for voc and vocformat).

**Value**

A list of character vectors corresponding to the keywords in corpus.

**Author(s)**

Ingo Feinerer

**References**

<http://www.nzdl.org/Kea/>

**See Also**

[createModel](#)

# Index

## \*Topic **file**

createModel, [2](#)

extractKeywords, [3](#)

createModel, [2](#), [3](#)

extractKeywords, [2](#), [3](#)