

Package ‘Rchoice’

July 23, 2021

Type Package

Title Discrete Choice (Binary, Poisson and Ordered) Models with Random Parameters

Version 0.3-3

Date 2021-07-07

Description

An implementation of simulated maximum likelihood method for the estimation of Binary (Probit and Logit), Ordered (Probit and Logit) and Poisson models with random parameters for cross-sectional and longitudinal data as presented in Sarrias (2016) <[doi:10.18637/jss.v074.i10](https://doi.org/10.18637/jss.v074.i10)>.

Depends R (>= 4.0), Formula, maxLik

Imports sandwich, miscTools, numDeriv, memisc, msm, plm, plotrix, stats, graphics

Suggests car, lmtest, pglm,

License GPL (>= 2)

URL <https://www.msarrias.com/rchoice-package-in-r.html>

LazyData no

RoxygenNote 7.1.1

Encoding UTF-8

NeedsCompilation no

Author Mauricio Sarrias [aut, cre] (<<https://orcid.org/0000-0001-5932-4817>>)

Maintainer Mauricio Sarrias <msarrias86@gmail.com>

Repository CRAN

Date/Publication 2021-07-22 22:40:06 UTC

R topics documented:

AIC.Rchoice	2
Articles	3
Attitudes	4
bread.Rchoice	5

effect.hetprob	6
effect.ivpml	7
effect.Rchoice	8
estfun.Rchoice	9
getSummary.effect.hetprob	10
getSummary.effect.ivpml	10
getSummary.hetprob	11
getSummary.ivpml	12
getSummary.Rchoice	12
Health	13
hetprob	14
ivpml	17
plot.Rchoice	18
Rchoice	20
rFormula	25
vcov.Rchoice	26
Workmroz	27
Index	29

AIC.Rchoice	<i>Akaike's Information Criterion</i>
-------------	---------------------------------------

Description

Calculate Akaike's information Criterion (AIC) or the Bayesian information Criterion (BIC) for a model of class Rchoice.

Usage

```
## S3 method for class 'Rchoice'
AIC(object, ..., k = 2)

## S3 method for class 'Rchoice'
BIC(object, ...)
```

Arguments

object	a fitted model of class Rchoice,
...	additional arguments to be passed to or from other functions,
k	a numeric value, use as penalty coefficient for number of parameters in the fitted model,

Value

a numeric value with the corresponding AIC or BIC value.

See Also[Rchoice](#)**Examples**

```
## Probit model
data("Workmroz")
probit <- Rchoice(lfp ~ k5 + k618 + age + wc + hc + lwg + inc,
                 data = Workmroz , family = binomial('probit'))
summary(probit)

AIC(probit)
BIC(probit)
```

Articles

Doctoral Publications

Description

Data from research by Long(1990) that analyzes the scientist's level of publications.

Usage

```
data(Articles)
```

Format

A data frame with 915 observations on the following 6 variables:

art Articles during last 3 years of Ph.D.,
fem 1 if female scientist; else 0,
mar 1 if married; else 0,
kid5 Number of children 5 or younger,
phd Prestige of Ph.D. department,
ment Articles by mentor during last 3 years,

Source

- Long, J. S. (1990). The origins of sex differences in science. *Social Forces*, 68(4), 1297-1316.
- Long, J. S. (1997). *Regression models for categorical and limited dependent variables* (Vol. 7). Sage.
- Long, J. S., & Freese, J. (2006). *Regression models for categorical and limited dependent variables using Stata*. Stata Press, College Station, TX.

Examples

```
data(Articles)
```

Attitudes

Attituded toward working mothers

Description

In 1997 and 1989, the General Social Survey asked respondents to evaluate the following statement: "A working mother can establish just as warm and secure a relationship with her children as a mother who does not work".

Usage

```
data(Attitudes)
```

Format

A data frame with 2293 observations on the following 10 variables:

warm 1 = Strongly disagree, 2 = disagree, 3 = agree, 4 = strongly agree,

yr89 survey year: 1 = 1989; 0 = 1977,

male 1 = male; 0 = female,

white 1 = white; 0 = nonwhite,

age age in years,

ed years of education,

prst occupational prestige,

Source

- Clogg, C. C., & Shihadeh, E. S. (1994). Statistical models for ordinal variables. Thousand Oaks, CA: Sage Publications.
- Long, J. S. (1997). Regression models for categorical and limited dependent variables (Vol. 7). Sage.
- Long, J. S., & Freese, J. (2006). Regression models for categorical and limited dependent variables using Stata. Stata Press, College Station, TX.

Examples

```
data(Attitudes)
```

bread.Rchoice	<i>Bread for sandwiches</i>
---------------	-----------------------------

Description

Computes the “bread” of the sandwich covariance matrix for a model of class Rchoice

Usage

```
## S3 method for class 'Rchoice'  
bread(x, ...)
```

Arguments

x a fitted model of class Rchoice,
... Other arguments when bread is applied to another class object.

Details

For more information see [bread](#) from the package **sandwich**.

Value

the covariance matrix times observations

References

Zeileis A (2006), Object-oriented Computation of Sandwich Estimators. *Journal of Statistical Software*, 16(9), 1–16.

Examples

```
## Probit model  
data("Workmroz")  
probit <- Rchoice(lfp ~ k5 + k618 + age + wc + hc + lwg + inc,  
                  data = Workmroz , family = binomial('probit'))  
summary(probit)  
  
library("sandwich")  
bread(probit)
```

effect.hetprob *Get average marginal effects for heterokedastic binary models*

Description

Obtain the average marginal effects from hetprob class model.

Usage

```
effect.hetprob(
  object,
  vcov = NULL,
  digits = max(3, getOption("digits") - 2),
  ...
)

## S3 method for class 'effect.hetprob'
summary(object, ...)

## S3 method for class 'summary.effect.hetprob'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

object	an object of class hetprob and effect.hetprob for summary and print method.
vcov	an estimate of the asymptotic variance-covariance matrix of the parameters for a hetprob object.
digits	the number of digits.
...	further arguments. Ignored.
x	an object of class effect.hetprob.

Details

This function allows to obtain the average marginal effects (not the marginal effects at the mean). The standard errors are computed using Delta Method.

Value

An object of class effect.heprob.

Examples

```
## Not run:
# Average marginal effects
data("Health")
het.probit <- hetprob(working ~ factor(female) + factor(year) + educ + age + I(age^2) |
  factor(female) + age + I(age^2),
```

```

                                data = Health,
                                link = "probit")
summary(het.probit)
eff <- effect.hetprob(het.probit)
summary(eff)

## End(Not run)

```

effect.ivpml

Get average marginal effects for IV Probit model.

Description

Obtain the average marginal effects from ivpml class model.

Usage

```

effect.ivpml(
  object,
  vcov = NULL,
  asf = TRUE,
  digits = max(3, getOption("digits") - 2),
  ...
)

## S3 method for class 'effect.ivpml'
summary(object, ...)

## S3 method for class 'summary.effect.ivpml'
print(x, digits = max(3, getOption("digits") - 3), ...)

```

Arguments

object	an object of class ivpml and effect.ivpml for summary and print method.
vcov	an estimate of the asymptotic variance-covariance matrix of the parameters for a ivpml object.
asf	if TRUE, the average structural function is used.
digits	the number of digits.
...	further arguments.Ignored.
x	an object of class effect.ivpml.

Details

This function allows to obtain the average marginal effects (not the marginal effects at the mean). The standard errors are computed using Delta Method.

Value

An object of class `effect.ivpml`.

<code>effect.Rchoice</code>	<i>Get the conditional individual coefficients</i>
-----------------------------	--

Description

This is a helper function to obtain the individuals' conditional estimate of the random parameters or compensating variations.

Usage

```
effect.Rchoice(x, par = NULL, effect = c("cv", "ce"), wrt = NULL, ...)
```

Arguments

<code>x</code>	a object of class <code>Rchoice</code> ,
<code>par</code>	a string giving the name of the variable with random parameter,
<code>effect</code>	a string indicating what should be computed: the conditional expectation of the individual coefficients "ce", or the conditional expectation of the individual compensating variations "cv",
<code>wrt</code>	a string indicating respect to which variable the compensating variation should be computed,
<code>...</code>	further arguments. Ignored.

Value

A named list where "mean" contains the individuals' conditional mean for the random parameter or compensating variation, and where 'sd.est' contains their standard errors.

References

- Greene, W. H. (2012). *Econometric Analysis*, Seventh Edition. Pearson Hall.
- Train, K. (2009). *Discrete Choice Methods with Simulation*. Cambridge university press.

See Also

[Rchoice](#) for the estimation of different discrete choice models with individual parameters.

Examples

```
## Not run:
## Probit Model with Random Effects and Random Parameters
data('Unions', package = 'pglm')
Unions$lwage <- log(Unions$wage)
union.ran <- Rchoice(union ~ age + exper + rural + lwage,
  data = Unions[1:2000, ],
  family = binomial('probit'),
  ranp = c(constant = "n", lwage = "t"),
  R = 10,
  panel = TRUE,
  index = "id",
  print.init = TRUE)

## Get the individuals' conditional mean and their standard errors for lwage
bi.wage <- effect.Rchoice(union.ran, par = "lwage", effect = "ce")
summary(bi.wage$mean)
summary(bi.wage$sd.est)

## End(Not run)
```

 estfun.Rchoice

Gradient for observations

Description

It extracts the gradient for each observations evaluated at the estimated parameters for a model of class Rchoice

Usage

```
## S3 method for class 'Rchoice'
estfun(x, ...)
```

Arguments

x a fitted model of class Rchoice,
 ... Other arguments when estfun is applied to another class object

Details

For more information see [estfun](#) from package **sandwich**.

Value

the gradient matrix of dimension n times k

References

Zeileis A (2006), Object-oriented Computation of Sandwich Estimators. Journal of Statistical Software, 16(9), 1–16.

```
getSummary.effect.hetprob
```

Get Model Summaries for use with "mtable" for objects of class effect.hetprob

Description

A generic function to collect coefficients and summary statistics from a `effect.hetprob` object. It is used in `mtable`

Usage

```
## S3 method for class 'effect.hetprob'
getSummary(obj, alpha = 0.05, ...)
```

Arguments

<code>obj</code>	an <code>effect.hetprob</code> object,
<code>alpha</code>	level of the confidence intervals,
<code>...</code>	further arguments,

Details

For more details see package **memisc**.

```
getSummary.effect.ivpml
```

Get Model Summaries for use with "mtable" for objects of class effect.ivpml

Description

A generic function to collect coefficients and summary statistics from a `effect.ivpml` object. It is used in `mtable`

Usage

```
## S3 method for class 'effect.ivpml'
getSummary(obj, alpha = 0.05, ...)
```

Arguments

obj an effect.ivpml object,
alpha level of the confidence intervals,
... further arguments,

Details

For more details see package **memisc**.

`getSummary.hetprob` *Get Model Summaries for use with "mtable" for objects of class hetprob*

Description

A generic function to collect coefficients and summary statistics from a hetprob object. It is used in mtable

Usage

```
## S3 method for class 'hetprob'  
getSummary(obj, alpha = 0.05, ...)
```

Arguments

obj a hetprob object,
alpha level of the confidence intervals,
... further arguments,

Details

For more details see package **memisc**.

getSummary.ivpml *Get Model Summaries for use with "mtable" for objects of class ivpml*

Description

A generic function to collect coefficients and summary statistics from a ivpml object. It is used in mtable

Usage

```
## S3 method for class 'ivpml'
getSummary(obj, alpha = 0.05, ...)
```

Arguments

obj	a ivpml object,
alpha	level of the confidence intervals,
...	further arguments,

Details

For more details see package **memisc**.

getSummary.Rchoice *Get Model Summaries for use with "mtable" for object of class Rchoice*

Description

A generic function to collect coefficients and summary statistics from a Rchoice object. It is used in mtable

Usage

```
## S3 method for class 'Rchoice'
getSummary(obj, alpha = 0.05, ...)
```

Arguments

obj	a Rchoice object,
alpha	level of the confidence intervals,
...	further arguments,

Details

For more details see package **memisc**.

 Health

 German Health Care Data

Description

German Health Care Data, unbalanced panel.

Usage

```
data(Health)
```

Format

A data frame with 27326 observations on the following 27 variables:

id person identification number
 female female =1, male =0
 year calendar year of the observation
 age age in years
 hsat health satisfaction, 0 (low),...,10 (high)
 handdum handicapped = 1, 0 otherwise
 handper degree of handicap in percent; 0,100
 hhinc household nominal monthly net income in German marks
 hhkids children under age 16 in the household = 1; otherwise = 0
 educ years of schooling
 married married =1, otherwise = 0
 haupts highest schooling degree is Hauptschul degree = 1; otherwise = 0
 reals highest schooling degree is Realschul degree = 1, otherwise = 0
 fachhs highest schooling degree is Polytechnical degree = 1; otherwise = 0
 abitur highest schooling degree is Abitur = 1; otherwise = 0
 univ highest schooling degree is university degree =1; otherwise = 0
 working employed =1; otherwise = 0
 bluec blue-collar employee = 1; otherwise = 0
 whitec white-collar employee =1; otherwise = 0
 self self-employed = 1; otherwise = 0
 beamt civil servant = 1; otherwise = 0
 docvis number of doctor visits in last three months
 hospvis number of hospital visits in last calendar year
 public insured in public health =1; otherwise = 0
 addon insured by add-on insurance =1; otherwise = 0
 hsat2 40 observations on hsat recorded between 6 and 7 were changed to 7
 newhsat recording of hsat, (0-2) = 0, (3-5)=1, (6-8)=2, (9)=3 (10)=4

Source

Riphahn, R. T., Wambach, A., & Million, A. (2003). Incentive effects in the demand for health care: a bivariate panel count data estimation. *Journal of applied econometrics*, 18(4), 387-405.

References

Greene, W. H. (2003). *Econometric analysis*. Pearson Education India.

Examples

```
data(Health)
```

hetprob	<i>Estimate heterokedastic binary (Probit or Logit) model.</i>
---------	--

Description

Estimation of binary dependent variables, either probit or logit, with heteroskedastic error terms for cross-sectional dataset.

Usage

```
hetprob(formula, data, link = c("probit", "logit"), Hes = TRUE, ...)

## S3 method for class 'hetprob'
terms(x, ...)

## S3 method for class 'hetprob'
model.matrix(object, ...)

## S3 method for class 'hetprob'
estfun(x, ...)

## S3 method for class 'hetprob'
bread(x, ...)

## S3 method for class 'hetprob'
AIC(object, k = 2, ...)

## S3 method for class 'hetprob'
BIC(object, ...)

## S3 method for class 'hetprob'
vcov(object, eigentol = 1e-12, ...)

## S3 method for class 'hetprob'
df.residual(object, ...)
```

```

## S3 method for class 'hetprob'
coef(object, ...)

## S3 method for class 'hetprob'
logLik(object, ...)

## S3 method for class 'hetprob'
print(x, ...)

## S3 method for class 'hetprob'
summary(object, eigentol = 1e-12, ...)

## S3 method for class 'summary.hetprob'
print(x, digits = max(3, getOption("digits") - 2), ...)

## S3 method for class 'hetprob'
predict(object, newdata = NULL, type = c("xb", "pr", "sigma"), ...)

```

Arguments

formula	a symbolic description of the model of the form $y \sim x \mid z$ where y is the binary dependent variable and x and z are regressors variables for the mean of the model and $\ln\sigma$.
data	the data of class <code>data.frame</code> .
link	the assumption of the distribution of the error term.
Hes	logical. Should the analytic Hessian to be used? TRUE as default.
...	arguments passed to <code>maxLik</code> .
x, object	an object of class <code>hetprob</code> .
k	a numeric value, use as penalty coefficient for number of parameters in the fitted model
eigentol	the standard errors are only calculated if the ratio of the smallest and largest eigenvalue of the Hessian matrix is less than <code>eigentol</code> . Otherwise the Hessian is treated as singular.
digits	the number of digits.
newdata	optionally, a data frame in which to look for variables with which to predict.
type	the type of prediction required. The default, <code>type = xb</code> , is on the linear prediction without the variance. If <code>type = pr</code> , the predicted probabilities of a positive outcome is returned. Finally, if <code>type = sigma</code> the predictions of σ for each individual is returned.

Details

The heterokedastic binary model for cross-sectional data has the following structure:

$$y_i^* = x_i^\top \beta + \epsilon_i,$$

with

$$\text{var}(\epsilon_i|x_i, z_i) = \sigma_i^2 = [\exp(z_i^\top \delta)]^2,$$

where y_i^* is the latent (unobserved) dependent variable for individual $i = 1, \dots, N$; x_i is a $K \times 1$ vector of independent variables determining the latent variable y_i^* (x variables in formula); and ϵ_i is the error term distributed either normally or logistically with $E(\epsilon_i|z_i, x_i) = 0$ and heterokedastic variance $\text{var}(\epsilon_i|x_i, z_i) = \sigma_i^2, \forall i = 1, \dots, N$. The variance for each individual is modeled parametrically assuming that it depends on a $P \times 1$ vector observed variables z_i (z in formula), whereas δ is the vector of parameters associated with each variable. It is important to emphasize that z_i does not include a constant, otherwise the parameters are not identified.

The models are estimated using the `maxLik` function from `maxLik` package using both analytic gradient and hessian (if `Hess = TRUE`). In particular, the log-likelihood function is:

$$\log L(\theta) = \sum_i^n \log \left\{ \left[1 - F \left(\frac{x_i^\top \beta}{\exp(z_i^\top \delta)} \right) \right]^{1-y_i} \left[F \left(\frac{x_i^\top \beta}{\exp(z_i^\top \delta)} \right) \right]^{y_i} \right\}.$$

Value

An object of class “hetprob”, a list elements:

<code>logLik0</code>	logLik for the homokedastic model,
<code>f1</code>	the formula,
<code>mf</code>	the model framed used,
<code>call</code>	the matched call.

Author(s)

Mauricio Sarrias.

Examples

```
## Not run:
# Estimate a heterokedastic probit and logit model
data("Health")

het.probit <- hetprob(working ~ factor(female) + factor(year) + educ + age + I(age^2) |
                    factor(female) + age + I(age^2),
                    data = Health,
                    link = "probit")
summary(het.probit)

het.logit <- hetprob(working ~ factor(female) + factor(year) + educ + age + I(age^2) |
                    factor(female) + age + I(age^2),
                    data = Health,
                    link = "logit")
summary(het.logit)

## End(Not run)
```

ivpml	<i>Estimate Instrumental Variable Probit model by Maximum Likelihood.</i>
-------	---

Description

Estimation of Probit model with one endogenous and continuous variable by Maximum Likelihood.

Usage

```
ivpml(formula, data, messages = TRUE, ...)
```

```
## S3 method for class 'ivpml'  
terms(x, ...)
```

```
## S3 method for class 'ivpml'  
model.matrix(object, ...)
```

```
## S3 method for class 'ivpml'  
estfun(x, ...)
```

```
## S3 method for class 'ivpml'  
bread(x, ...)
```

```
## S3 method for class 'ivpml'  
AIC(object, k = 2, ...)
```

```
## S3 method for class 'ivpml'  
BIC(object, ...)
```

```
## S3 method for class 'ivpml'  
vcov(object, ...)
```

```
## S3 method for class 'ivpml'  
df.residual(object, ...)
```

```
## S3 method for class 'ivpml'  
coef(object, ...)
```

```
## S3 method for class 'ivpml'  
logLik(object, ...)
```

```
## S3 method for class 'ivpml'  
print(x, ...)
```

```
## S3 method for class 'ivpml'  
summary(object, eigentol = 1e-12, ...)
```

```
## S3 method for class 'summary.ivpml'
print(x, digits = max(3, getOption("digits") - 2), ...)

## S3 method for class 'ivpml'
predict(object, newdata = NULL, type = c("xb", "pr", "stdp"), asf = TRUE, ...)
```

Arguments

formula	a symbolic description of the model of the form $y \sim x \mid z$ where y is the binary dependent variable, x includes the exogenous and the endogenous continuous variable, and z is the complete set of instruments.
data	the data of class <code>data.frame</code> .
messages	if TRUE, then additional messages for the estimation procedure are displayed.
...	arguments passed to <code>maxLik</code> .
x, object	an object of class <code>ivpml</code> .
k	a numeric value, use as penalty coefficient for number of parameters in the fitted model.
eigentol	the standard errors are only calculated if the ratio of the smallest and largest eigenvalue of the Hessian matrix is less than <code>eigentol</code> . Otherwise the Hessian is treated as singular.
digits	the number of digits.
newdata	optionally, a data frame in which to look for variables with which to predict.
type	the type of prediction required. The default, <code>type = xb</code> , is on the linear prediction. If <code>type = pr</code> , the predicted probabilities of a positive outcome is returned. Finally, if <code>type = stdp</code> the standard errors of the linear predictions for each individual is returned.
asf	if TRUE, the average structural function is used. This option is not allowed with <code>xb</code> or <code>stdp</code> .

Author(s)

Mauricio Sarrias.

plot.Rchoice	<i>Plot the distribution of conditional expectation for random parameters.</i>
--------------	--

Description

Plot the distribution of the conditional expectation of the random parameters or compensating variations for objects of class `Rchoice`.

Usage

```
## S3 method for class 'Rchoice'
plot(
  x,
  par = NULL,
  effect = c("ce", "cv"),
  wrt = NULL,
  type = c("density", "histogram"),
  adjust = 1,
  main = NULL,
  col = "indianred1",
  breaks = 10,
  ylab = NULL,
  xlab = NULL,
  ind = FALSE,
  id = NULL,
  ...
)
```

Arguments

x	a object of class Rchoice,
par	a string giving the name of the variable with random parameter,
effect	a string indicating what should be plotted: the conditional expectation of the individual coefficients "ce", or the conditional expectation of the individual compensating variations "cv",
wrt	a string indicating respect to which variable should be computed the compensating variation,
type	a string indicating the type of distribution: it can be a histogram or a density of the conditional expectation,
adjust	bandwidth for the kernel density,
main	an overall title for the plot,
col	color for the graph,
breaks	number of breaks for the histogram if type = "histogram",
ylab	a title for the y axis,
xlab	a title for the x axis,
ind	a boolean. If TRUE, a 95 As default, the conditional expectation of par for the first 10 individual is plotted,
id	only relevant if ind is not NULL. This is a vector indicating the individuals for which the confidence intervals are plotted,
...	further arguments. Ignored.

Author(s)

Mauricio Sarrias

References

- Greene, W. H. (2012). *Econometric analysis*, Seventh Edition. Pearson Hall.
- Train, K. (2009). *Discrete choice methods with simulation*. Cambridge university press.

See Also

[Rchoice](#) for the estimation of different discrete choice models with individual parameters.

Examples

```
## Not run:
## Probit Model with Random Effects and Random Parameters
data('Unions', package = 'pglm')
Unions$lwage <- log(Unions$lwage)
union.ran <- Rchoice(union ~ age + exper + rural + lwage,
                    data = Unions[1:2000, ],
                    family = binomial('probit'),
                    ranp = c(constant = "n", lwage = "t"),
                    R = 10,
                    panel = TRUE,
                    index = "id",
                    print.init = TRUE)

## Plot the distribution of the conditional mean for lwage
plot(union.ran, par = "lwage", type = "density")

## Plot the conditional mean for the first 20 individuals
plot(union.ran, par = "lwage", ind = TRUE, id = 1:20, col = "blue")

## Plot the compensating variation
plot(union.ran, par = "lwage", effect = "cv", wrt = "rural", type = "histogram")

## End(Not run)
```

Rchoice

Estimate discrete choice model with random parameters

Description

Estimation of discrete choice models such as Binary (logit and probit), Poisson and Ordered (logit and probit) model with random coefficients for cross-sectional and panel data using simulated maximum likelihood.

Usage

```
Rchoice(
  formula,
  data,
```

```
subset,
weights,
na.action,
family,
start = NULL,
ranp = NULL,
R = 40,
haltons = NA,
seed = 10,
correlation = FALSE,
panel = FALSE,
index = NULL,
mvar = NULL,
print.init = FALSE,
init.ran = 0.1,
gradient = TRUE,
...
)

## S3 method for class 'Rchoice'
terms(x, ...)

## S3 method for class 'Rchoice'
model.matrix(object, ...)

## S3 method for class 'Rchoice'
coef(object, ...)

## S3 method for class 'Rchoice'
fitted(object, ...)

## S3 method for class 'Rchoice'
residuals(object, ...)

## S3 method for class 'Rchoice'
df.residual(object, ...)

## S3 method for class 'Rchoice'
update(object, new, ...)

## S3 method for class 'Rchoice'
logLik(object, ...)

## S3 method for class 'Rchoice'
print(
  x,
  digits = max(3, getOption("digits") - 3),
  width = getOption("width"),
```

```

    ...
  )

## S3 method for class 'Rchoice'
summary(object, ...)

## S3 method for class 'summary.Rchoice'
print(
  x,
  digits = max(3, getOption("digits") - 3),
  width = getOption("width"),
  ...
)

```

Arguments

formula	a symbolic description of the model to be estimated. The formula consists in two parts. The first one is reserved for standard variables with fixed and random parameters. The second one is reserved for variables that enter in the mean of the random parameters. See for example rFormula ,
data	the data. It may be a <code>pdata.frame</code> object or an ordinary <code>data.frame</code> ,
subset	an optional vector specifying a subset of observations,
weights	an optional vector of weights,
na.action	a function which indicated what should happen when the data contains NA's,
family	the distribution to be used. It might be <code>family = binomial("probit")</code> for a Probit Model, <code>family = binomial("logit")</code> for a Logit model, <code>family = ordinal("probit")</code> for an Ordered Probit Model, <code>family = ordinal("logit")</code> for a Ordered Logit Model for an Ordered Logit Model, and <code>family = "poisson"</code> for a Poisson Model,
start	a vector of starting values,
ranp	a named vector whose names are the random parameters and values the distribution: "n" for normal, "ln" for log-normal, "cn" for truncated normal, "u" for uniform, "t" for triangular, "sb" for Johnson Sb,
R	the number of draws if <code>ranp</code> is not NULL,
haltons	only relevant if <code>ranp</code> is not NULL. If not NULL, halton sequence is used instead of pseudo-random numbers. If <code>haltons=NA</code> , some default values are used for the prime of the sequence and for the number of element dropped. Otherwise, <code>haltons</code> should be a list with elements <code>prime</code> and <code>drop</code> ,
seed	the seed for the pseudo-random draws. This is only relevant if <code>haltons = NULL</code> ,
correlation	only relevant if <code>ranp</code> is not NULL. If TRUE, the correlation between random parameters is taken into account,
panel	if TRUE a panel data model is estimated,
index	a string indicating the 'id' for individuals in the data. This argument is not required if data is a <code>pdata.frame</code> object,

<code>mvar</code>	only valid if <code>ranp</code> is not NULL. This is a named list, where the names correspond to the variables with random parameters, and the values correspond to the variables that enter in the mean of each random parameters,
<code>print.init</code>	if TRUE, the initial values for the optimization procedure are printed,
<code>init.ran</code>	initial values for standard deviation of random parameters. Default is 0.1,
<code>gradient</code>	if FALSE, numerical gradients are used for the optimization procedure of models with random parameters,
<code>...</code>	further arguments passed to <code>maxLik</code> ,
<code>x, object</code>	and object of class <code>Rchoice</code> ,
<code>new</code>	an updated formula for the update method,
<code>digits</code>	number of digits,
<code>width</code>	width,

Details

The models are estimated using the `maxLik` function from `maxLik` package.

If `ranp` is not NULL, the random parameter model is estimated. A random parameter model or random coefficient models permits regression parameter to vary across individuals according to some distribution. A fully parametric random parameter model specifies the latent variable y^* conditional on regressors x and given parameters β_i to have conditional density $f(y|x, \beta_i)$ where β_i are iid with density $g(\beta_i|\theta_i)$. The density is assumed a priori by the user by the argument `ranp`. If the parameters are assumed to be normally distributed $\beta_i \sim N(\beta, \Sigma)$, then the random parameter are constructed as:

$$\beta_{ir} = \beta + L\omega_{ir}$$

where $LL' = \Sigma$ and ω_{ir} is the r -th draw from standard normal distribution for individual i .

Once the model is specified by the argument `family`, the model is estimated using Simulated Maximum Likelihood (SML). The probabilities, given by $f(y|x, \beta_i)$, are simulated using R pseudo-draws if `halton=NULL` or R halton draws if `halton = NA`. The user can also specified the primes and the number of dropped elements for the halton draws. For example, if the model consists of two random parameters, the user can specify `haltons = list("prime" = c(2, 3), "drop" = c(11, 11))`.

A random parameter hierarchical model can be estimated by including heterogeneity in the mean of the random parameters:

$$\beta_{ir} = \beta + \pi' s_i + L\omega_{ir}$$

Rchoice manages the variables in the hierarchical model by the `formula` object: all the hierarchical variables (s_i) are included after the `|` symbol. The argument `mvar` indicate which variables enter in each random parameter. See examples below

Value

An object of class "Rchoice", a list elements:

<code>coefficients</code>	the named vector of coefficients,
<code>family</code>	type of model,
<code>link</code>	distribution of the errors,

logLik	a set of values of the maximum likelihood procedure,
mf	the model framed used,
formula	the formula (a Formula object),
time	proc.time() minus the start time,
freq	frequency of dependent variable,
draws	type of draws used,
R.model	TRUE if a random parameter model is fitted,
R	number of draws used,
bi	an array of dimension $N \times R \times K$ with the individual parameters,
Qir	matrix of dimension $N \times R$ representing $P_{ir} / \sum_r P_{ir}$,
ranp	vector indicating the variables with random parameters and their distribution,
probabilities	the fitted probabilities for each individuals,
residuals	the residuals,
call	the matched call.

Author(s)

Mauricio Sarrias <msarrias86@gmail.com>

References

Greene, W. H. (2012). *Econometric Analysis*. 7 edition. Prentice Hall.

Train, K. (2009). *Discrete Choice Methods with Simulation*. Cambridge university press.

See Also

[plot.Rchoice](#), [effect.Rchoice](#)

Examples

```
## Probit model
data("Workmroz")
probit <- Rchoice(lfp ~ k5 + k618 + age + wc + hc + lwg + inc,
                 data = Workmroz, family = binomial('probit'))
summary(probit)

## Poisson model
data("Articles")
poisson <- Rchoice(art ~ fem + mar + kid5 + phd + ment, data = Articles, family = poisson)
summary(poisson)

## Ordered probit model
data("Health")
oprobit <- Rchoice(newhsat ~ age + educ + hhinc + married + hhkids,
                  data = Health, family = ordinal('probit'), subset = year == 1988)
summary(oprobit)
```



```

## Poisson Model with Random Parameters
## Not run:
poisson.ran <- Rchoice(art ~ fem + mar + kid5 + phd + ment,
                      data = Articles, family = poisson,
                      ranp = c(kid5 = "n", phd = "n", ment = "n"))
summary(poisson.ran)

## Poisson Model with Correlated Random Parameters
poissonc.ran <- Rchoice(art ~ fem + mar + kid5 + phd + ment,
                      data = Articles,
                      ranp = c(kid5 = "n", phd = "n", ment = "n"),
                      family = poisson,
                      correlation = TRUE)
summary(poissonc.ran)

## Hierarchical Poisson Model
poissonH.ran <- Rchoice(art ~ fem + mar + kid5 + phd + ment | fem + phd,
                      data = Articles,
                      ranp = c(kid5 = "n", phd = "n", ment = "n"),
                      mvar = list(phd = c("fem"), ment = c("fem", "phd")),
                      family = poisson,
                      R = 10)
summary(poissonH.ran)

## Ordered Probit Model with Random Effects and Random Parameters
oprobit.ran <- Rchoice(newhsat ~ age + educ + married + hhkids + linc,
                      data = Health[1:2000, ],
                      family = ordinal('probit'),
                      ranp = c(constant = "n", hhkids = "n", linc = "n"),
                      panel = TRUE,
                      index = "id",
                      R = 100,
                      print.init = TRUE)
summary(oprobit.ran)

## End(Not run)

```

Description

Two kind of variables are used in models with individual heterogeneity: the typical variables that enter in the latent process and those variables that enter in the random parameter (Hierarchical Model). rFormula deal with this type of models using suitable methods to extract the elements of the model.

Usage

```

rFormula(object)

is.rFormula(object)

## S3 method for class 'rFormula'
model.frame(formula, data, ..., lhs = NULL, rhs = NULL)

## S3 method for class 'rFormula'
model.matrix(object, data, rhs = NULL, ...)

```

Arguments

object	a formula form the rFormula function, for the model.matrix method, a rFormula object,
formula	a rFormula object,
data	a data.frame,
...	further arguments.
lhs	see Formula ,
rhs	see Formula ,

vcov.Rchoice

vcov method for Rchoice objects

Description

The vcov method for Rchoice objects extracts the covariance matrix of the coefficients or the random parameters. It also allows to get the standard errors for the variance-covariance matrix of the random parameters

Usage

```

## S3 method for class 'Rchoice'
vcov(
  object,
  what = c("coefficient", "ranp"),
  type = c("cov", "cor", "sd"),
  se = FALSE,
  digits = max(3, getOption("digits") - 2),
  ...
)

cov.Rchoice(x)

cor.Rchoice(x)

se.cov.Rchoice(x, sd = FALSE, digits = max(3, getOption("digits") - 2))

```

Arguments

object	a fitted model of class Rchoice,
what	indicates which covariance matrix has to be extracted. The default is coefficient. In this case the vcov behaves as usual. If what = "ranp" the covariance matrix of the random parameters is returned as default,
type	if the model is estimated with random parameters, then this argument indicates what matrix should be returned. If type = "cov", then the covariance matrix of the random parameters is returned; if type = "cor" then the correlation matrix of the random parameters is returned; if type = "sd" then the standard deviation of the random parameters is returned,
se	if TRUE and type = "cov" then the standard error of the covariance matrix of the random parameters is returned; if TRUE and type = "sd" the standard error of the standard deviation of the random parameter is returned. This argument is valid only if the model is estimated using correlated random parameters,
digits	number of digits,
...	further arguments
x	a fitted model of class Rchoice,
sd	if TRUE, then the standard deviation of the random parameters are returned,

Details

This new interface replaces the cor.Rchoice, cov.Rchoice and se.cov.Rchoice functions which are deprecated.

See Also

[Rchoice](#) for the estimation of discrete choice models with random parameters.

 Workmroz

Labor Force Participation

Description

Data extracted by Mroz(1987) from the 1976 Panel Study of Income Dynamics. The sample consists of 753 white, married women between the ages of 30 and 60.

Usage

```
data(Workmroz)
```

Format

A data frame with 753 observations on the following 9 variables:

lfp 1 if wife is in the paid labor force; else 0,
k5 Number of children ages 5 and younger,
k618 Number of children ages 6 to 18,
age Wife's age in years,
wc 1 if wife attended college; else 0,
hc 1 if husband attended college; else 0,
lwg Log of wife's estimated wage rate,
inc Family income excluding wife's wage,
linc Log of Family income excluding wife's wage,

Source

Mroz, T. A. (1987). The sensitivity of an empirical model of married women's hours of work to economic and statistical assumptions. *Econometrica*, 55(4), 765-799

Examples

```
data(Workmroz)
```

Index

* datasets

- Articles, [3](#)
 - Attitudes, [4](#)
 - Health, [13](#)
 - Workmroz, [27](#)
- AIC.hetprob (hetprob), [14](#)
AIC.ivpml (ivpml), [17](#)
AIC.Rchoice, [2](#)
Articles, [3](#)
Attitudes, [4](#)
- BIC.hetprob (hetprob), [14](#)
BIC.ivpml (ivpml), [17](#)
BIC.Rchoice (AIC.Rchoice), [2](#)
bread, [5](#)
bread.hetprob (hetprob), [14](#)
bread.ivpml (ivpml), [17](#)
bread.Rchoice, [5](#)
- coef.hetprob (hetprob), [14](#)
coef.ivpml (ivpml), [17](#)
coef.Rchoice (Rchoice), [20](#)
cor.Rchoice (vcov.Rchoice), [26](#)
cov.Rchoice (vcov.Rchoice), [26](#)
- df.residual.hetprob (hetprob), [14](#)
df.residual.ivpml (ivpml), [17](#)
df.residual.Rchoice (Rchoice), [20](#)
- effect.hetprob, [6](#)
effect.ivpml, [7](#)
effect.Rchoice, [8](#), [24](#)
estfun, [9](#)
estfun.hetprob (hetprob), [14](#)
estfun.ivpml (ivpml), [17](#)
estfun.Rchoice, [9](#)
- fitted.Rchoice (Rchoice), [20](#)
Formula, [26](#)
- getSummary.effect.hetprob, [10](#)
getSummary.effect.ivpml, [10](#)
getSummary.hetprob, [11](#)
getSummary.ivpml, [12](#)
getSummary.Rchoice, [12](#)
- Health, [13](#)
hetprob, [14](#)
- is.rFormula (rFormula), [25](#)
ivpml, [17](#)
- logLik.hetprob (hetprob), [14](#)
logLik.ivpml (ivpml), [17](#)
logLik.Rchoice (Rchoice), [20](#)
- maxLik, [16](#), [23](#)
model.frame.rFormula (rFormula), [25](#)
model.matrix.hetprob (hetprob), [14](#)
model.matrix.ivpml (ivpml), [17](#)
model.matrix.Rchoice (Rchoice), [20](#)
model.matrix.rFormula (rFormula), [25](#)
- ordinal (Rchoice), [20](#)
- plot.Rchoice, [18](#), [24](#)
predict.hetprob (hetprob), [14](#)
predict.ivpml (ivpml), [17](#)
print.hetprob (hetprob), [14](#)
print.ivpml (ivpml), [17](#)
print.Rchoice (Rchoice), [20](#)
print.summary.effect.hetprob
(effect.hetprob), [6](#)
print.summary.effect.ivpml
(effect.ivpml), [7](#)
print.summary.hetprob (hetprob), [14](#)
print.summary.ivpml (ivpml), [17](#)
print.summary.Rchoice (Rchoice), [20](#)
- Rchoice, [3](#), [8](#), [20](#), [20](#), [27](#)
residuals.Rchoice (Rchoice), [20](#)

rFormula, [22](#), [25](#)

se.cov.Rchoice (vcov.Rchoice), [26](#)

summary.effect.hetprob
 (effect.hetprob), [6](#)

summary.effect.ivpml (effect.ivpml), [7](#)

summary.hetprob (hetprob), [14](#)

summary.ivpml (ivpml), [17](#)

summary.Rchoice (Rchoice), [20](#)

terms.hetprob (hetprob), [14](#)

terms.ivpml (ivpml), [17](#)

terms.Rchoice (Rchoice), [20](#)

update.Rchoice (Rchoice), [20](#)

vcov.hetprob (hetprob), [14](#)

vcov.ivpml (ivpml), [17](#)

vcov.Rchoice, [26](#)

Workmroz, [27](#)