

Package ‘Rz’

February 19, 2015

Type Package

Title GUI Tool for Data Management like SPSS or Stata

Version 0.9-1

Date 2013-07-28

Author Masahiro Hayashi

Maintainer Masahiro Hayashi <rinm884@gmail.com>

Description R is very powerful but it lacks some of the functionalities found in Stata or SPSS to manage survey data. The 'memisc' package provides these (variable labels, value labels, definable missing values and so on), but to efficiently work these functions need a graphical interface to allow the user to get an overview of the data. This package provides such a graphical interface, similar in fashion to SPSS's Variable View and data managing system. It uses the 'memisc' package as its backend. Additionally, 'Rz' has a powerful plot assistant interface based on 'ggplot2'.

License GPL (>= 3) + file LICENSE

URL <http://m884.jp/Rz.html>

Depends R (>= 2.14), methods, grid, foreign, memisc, psych, ggplot2 (>= 0.9.2)

Suggests quantreg, Hmisc, cairoDevice, vcd

Imports RGtk2 (>= 2.20), formatR

NeedsCompilation no

Repository CRAN

Date/Publication 2013-07-28 08:24:37

R topics documented:

Rz-package	2
crossTable	2
rzAddData	3
rzAddItem	4
rzReloadData	4
RzThemeEditor	5

Index**6**

Rz-package	<i>GUI Tool for Data Management like SPSS or Stata</i>
------------	--

Description

R is very powerfull but not enough for social science because of lack in some functionality for managing survey data SPSS or Stata provides. Memisc package supplements those, variable labels, value labels, definable missing values and so on, but to efficiently work these functions need graphical interface to overlook data. This package provides such graphical interface similar to SPSS's Variable View and data managing system using memisc package as backend. Additionally, Rz has powerful plot assistant interface based on ggplot2.

Details

Simply excute Rz() to start.

See Also

[RzThemeEditor](#)

crossTable	<i>Cross Tabulation</i>
------------	-------------------------

Description

Output well-formatted cross tabulation. Also can genarate latex syntax of cross tabulation.

Usage

```
crossTable(..., deparse.level = 2)
## S3 method for class 'CrossTable'
summary(object, digits=3, latex=FALSE, ...)
```

Arguments

deparse.level	passed to table
...	passed to table
object	crossTable object
digits	integer, used for number formatting
latex	logical, generate latex syntax if TRUE

Value

crossTable returns a object which belongs to CrossTable class and table class.

Author(s)

Masahiro Hayashi

Examples

```
sex <- factor(rbinom(1:1000, 1, 0.5), labels=c("male" , "female"))
age <- factor(rbinom(1:1000, 2, 0.4), labels=c("young", "middle", "old"))
weight <- factor(rbinom(1:1000, 2, 0.6), labels=c("light", "middle", "heavy"))

cross.table1 <- crossTable(sex, age)
summary(cross.table1)

cross.table2 <- crossTable(sex, age, weight)
summary(cross.table2)

summary(cross.table2, latex = TRUE)
```

rzAddData

Add data.set to Rz

Description

Add data.set to Rz

Usage

```
rzAddData(data.set, name = NULL)
```

Arguments

data.set	data.set or data.frame to be added.
name	data.set.name

Details

Add data.set to Rz

Author(s)

Masahiro Hayashi

See Also

[rzReloadData](#), [rzAddItem](#)

`rzAddItem`*Add a variable to a dataset*

Description

Add a variable to a dataset

Usage

```
rzAddItem(item, name = as.character(substitute(item)),
          data.set.name = NULL, description = name,
          measurement = c("auto", "nominal", "ordinal", "interval", "ratio"),
          overwrite = FALSE, ask = FALSE)
```

Arguments

<code>item</code>	an item object or a variable such as factor or numeric.
<code>name</code>	character: the variable name.
<code>data.set.name</code>	character: a name of a dataset in Rz. NULL means the current dataset.
<code>description</code>	character: the variable label.
<code>measurement</code>	character: measurement of the variable.
<code>overwrite</code>	logical: if TRUE will overwrite an existing variable.
<code>ask</code>	logical: confirm execution if TRUE.

Author(s)

Masahiro Hayashi

See Also

[rzAddData](#), [rzReloadData](#)

`rzReloadData`*Reload data.set from globalenv*

Description

Reload data.set from globalenv

Usage

```
rzReloadData(data.set.name = NULL, ask = TRUE)
```

Arguments

data.set.name character: dataset's name to be reloaded. If NULL, current dataset is reloaded.
ask logical: confirm execution if TRUE

Details

Reload data.set from globalenv

Author(s)

Masahiro Hayashi

See Also

[rzAddData](#), [rzAddItem](#)

RzThemeEditor

Theme Editor for ggplot2

Description

Theme Editor for ggplot2

Usage

```
RzThemeEditor(new = FALSE, ...)
```

Arguments

new logical: rebuild UI
... currently no use

Details

Start RzThemeEditor.

Author(s)

Masahiro Hayashi

See Also

[Rz](#)

Index

*Topic **cross tabulation**

crossTable, [2](#)

*Topic **memisc**

Rz-package, [2](#)

crossTable, [2](#)

Rz, [5](#)

Rz (Rz-package), [2](#)

Rz-package, [2](#)

rzAddData, [3](#), [4](#), [5](#)

rzAddItem, [3](#), [4](#), [5](#)

rzReloadData, [3](#), [4](#), [4](#)

RzThemeEditor, [2](#), [5](#)

summary.CrossTable (crossTable), [2](#)

table, [2](#)