

Package ‘SeerMapper2010Regs’

June 23, 2020

Type Package

Version 1.2.4

Date 2020-6-22

Title Supplemental U.S. 2010 Census Tract Boundaries for 19 States
with Seer Registries for 'SeerMapper'

Author Jim Pearson <jbpearson353@gmail.com> with data provided by U.S. Census Bureau

Maintainer Joe Zou <zouj@imsweb.com>

Depends R (>= 3.6.0)

Imports sp

Suggests

Description Provides supplemental 2010 census tract boundaries of the 19 states
containing Seer Registries for use with the 'SeerMapper' package.
The data contained in this
package is derived from U.S. 2010 Census data and is in public domain.

License GPL (>= 2)

LazyData no

LazyLoad no

BuildResaveData yes

ByteCompile yes

NeedsCompilation no

Repository CRAN

Date/Publication 2020-06-23 05:30:49 UTC

R topics documented:

SeerMapper2010Regs-package	2
trXX_dXX	4
Index	8

SeerMapper2010Regs-package

SeerMapper-Supplemental 2010 Census Tract boundary datasets for states with Seer Registries

Description

The *SeerMapper2010Regs* package provides supplemental 2010 Census Tract boundary datasets for 19 states containing Seer Registries for use with *SeerMapper* package.

The *SeerMapper2010West* supplemental data package contains the 2010 census tract boundary dataset for 13 states west of the Mississippi river that do not contain NCI Seer Registries. The *SeerMapper2010East* data only package contains the 2010 census tract boundary datasets for 20 states, District of Columbia and Puerto Rico that do not have Seer Registries and are east of the Mississippi river.

By loading these packages (via the library function) expands the *SeerMapper* package abilities to map census tract level data in any of the 52 states, the District of Columbia and Puerto Rico.

Details

Package:	SeerMapper2010Regs
Type:	Package
Version:	1.2.4
Date:	2020-06-22
License:	GPL-2
LazyLoad:	no

No special action is required by the user to install this package or load it when running *SeerMapper2010* function in the *SeerMapper* package. The defined interdependencies of the packages automatically install the supplemental census tract boundary packages when *SeerMapper* is install. When the *SeerMapper2010* function is called, it sets the census year to "2010" to instruct *SeerMapper* to use the 2010 boundaries and related information to map the data.

```
library(SeerMapper)

rateDate <- data.frame(FIBS=stateFibs,
                      Rate=stateRateVector,
                      pValue=stateRatePValue)

SeerMapper2010(rateData, Title=c("Test Map"))
```

If the package attachment or dataset load fails, the caller is notified of the problem and mapping is terminated.

The *SeerMapper2010Regs* package contains the 2010 census tract boundary datasets for:

FIPS	Name	# of Registries
02	Alaska	1
04	Arizona	1
06	California	4
09	Connecticut	1
13	Georgia	3
15	Hawaii	1
16	Idaho	1
19	Iowa	1
21	Kentucky	1
22	Louisiana	1
25	Massachusetts	1
26	Michigan	1
34	New Jersey	1
35	New Mexico	1
36	New York	1
40	Oklahoma	1
49	Utah	1
53	Washington	1
55	Wisconsin	1

The *SeerMapper2010East* package contains the 2010 census tract boundary datasets for:

FIPS	Name
01	Alabama
10	Delaware
11	District of Columbia
12	Florida
17	Illinois
18	Indiana
23	Maine
24	Maryland
28	Mississippi
33	New Hampshire
37	North Carolina
39	Ohio
42	Pennsylvania
44	Rhode Island
45	South Carolina
47	Tennessee
50	Vermont
51	Virginia
54	West Virginia
72	Puerto Rico

The *SeerMapper2010West* package contains the 2010 census tract boundary datasets for:

FIPS	Name
------	------

05	Arkansas
08	Colorado
20	Kansas
27	Minnesota
29	Missouri
30	Montana
31	Nebraska
32	Neveda
38	North Dakota
41	Oregon
46	South Dakota
48	Texas
56	Wyoming

Author(s)

Jim Pearson <jbpearson353@gmail.com> with data sourced from U. S. Census Bureau <geo.tiger@census.gov>
 Maintainer: "Joe Zou" <zouj@imsweb.com>

 trXX_dXX

Provides the U.S. 2010 Census Tract Boundary data datasets for 19 States the have Seer Registries for use with SeerMapper Package

Description

There are six supplemental census tract boundary packages for use with *SeerMapper*. The are *SeerMapperRegs*, *SeerMapperEast*, *SeerMapperWest* for the 2000 census and *Seer2010MapperRegs*, *Seer2010MapperEast* and *SeerMapper2010West* for the 2010 census. The combination of the either three provide a set of census tract boundaries for one U. S. census year (either 2000 or 2010). The *SeerMapperRegs* and *Seer2010MapperRegs* packages contains the census tract boundaries for the 19 states the have U. S. Seer Registries. The remaining census tract boundaries are split into two packages for each census year based on whether the state is east or west of the Mississippi river. The census tracts for 20 states, district and territory without registries east of the Mississippi river at contained in the *SeerMapperEast* and *Seer2010MapperEast* packages. The tract boundaries for the 13 states west of the Mississippi river are in the *SeerMapperWest* and *Seer2010MapperWest* packages. The states include the District of Columbia and Puerto Rico. This package contains the 2010 census tract boundaries for the 19 states with Seer Registries.

Usage

data(tr02_d10)

Format

This dataset contains a set of SpatialPolygons structures for the 19 states with Seer Registries. Each state structure is a list of the census tracts boundaries that the state. Refer to the documentation

on the *sp* package for details on the structures. Each list element is a "polygons" class structure containing attributes of the census tract (label point, area, ID, etc.) and a list of "Polygons" class elements that define the boundary polygons.

Details

The *SeerMapperRegs* and *SeerMapper2010Regs* packages contains 19 states with Seer Registries including:

FIPS	Name
02	Alaska
04	Arizona
06	California
09	Connecticut
13	Georgia
15	Hawaii
16	Idaho
19	Iowa
21	Kentucky
22	Louisiana
25	Massachusetts
26	Michigan
34	New Jersey
35	New Mexico
36	New York
40	Oklahoma
49	Utah
53	Washington
55	Wisconsin

The *SeerMapper* package contains the state and county boundary data for all 51 states and DC and the Seer Registry boundary data for the 24 established registries. Due to space limitations, the base packages cannot contain the census tract boundary data.

Three supplemental data packages are used for each census year to provide the census tract boundary data to *SeerMapper* package.

Each state ".rda" file (dataset) contains state's census tract boundary data. The file name structure is trXX_dYY, where tr identifies the file as census tract boundary data, "XX" is the state (2 digits) fips code and "YY" represents the census year (e.g., 00 = 2000 or 10 for 2010)

To conserve disk space and downloading/installation time, the rda files are compressed using the "xy" method.

The U. S. Census Bureau census tract boundary shape file data was pre-processed by "www.MapShaper.org" website version 01.15 using modified Visvalingam method with the intersection repair and prevent shape removal options enabled, the coordinate precision value set to 0.0 and the simplify parameter set to 10 by 85 alignments.

When the *SeerMapper* package is install, the six (6) census tract boundary supplement packages are also install automatically by R. The *SeerMapper* package then manages the loading of the packages to ensure the needed boundary files are available.

Source

The census tract boundary shapefiles were downloaded from the CENSUS.GOV web site for the 2010 Census census tract boundary shapefiles, https://www2.census.gov/geo/tiger/GENZ2010/gz_2010_XX_140_00_500k.z where XX is the state FIPS code.

Examples

```
#
# These examples are a test to ensure each census tract file
# can be read and a plot of the state generated.
#
require("sp")

#
# If you want to save the example output PDF files, change the
# the following "tempDir()" to the path you want to save the output files.
# For Example: outDir <- "c:/RTestPDFs"
outDir <- tempdir()
cat("Output Directory used:",outDir,"\n")

stList <- c("02","04","06","09","13",
            "15","16","19","21","22",
            "25","26","34","35","36",
            "40","49","53","55")
stName <- c("Alaska","Arizona","California","Connecticut","Georgia",
            "Hawaii","Idaho","Iowa","Kentucky","Louisiana",
            "Massachusetts","Michigan","New Jersey","New Mexico","New York",
            "Oklahoma","Utah","Washington","Wisconsin")
cY <- "10"

outfile <- paste0("SeerMapperRegs",cY,"-CT.pdf")
outFN <- file.path(outDir,outfile)
cat("Output example PDF file:",outFN,"\n")

pdf(outFN,width=7,height=10)

for (stN in seq(from=1, to=length(stList), by=7)) { # test draw 3 of 19 states

  stID <- stList[stN]
  stNa <- stName[stN]
  trFN <- paste0("tr",stID,"_d",cY)
  TT_tr <- paste0("U. S. Census Tracts - ",stNa," Fips=",stID," file=",trFN)

  data(list=trFN)

  wrSP <- get(trFN)
  #str(wrSP)

  plot(wrSP,main=TT_tr)
  rm(list=trFN)
}
```

trXX_dXX

7

dev.off()

Index

*Topic **Census2000**

trXX_dXX, [4](#)

*Topic **Census2010**

trXX_dXX, [4](#)

*Topic **SeerMapper**

trXX_dXX, [4](#)

*Topic **datasets**

trXX_dXX, [4](#)

SeerMapper2010Regs-package, [2](#)

tr02_d10 (trXX_dXX), [4](#)

tr04_d10 (trXX_dXX), [4](#)

tr06_d10 (trXX_dXX), [4](#)

tr09_d10 (trXX_dXX), [4](#)

tr13_d10 (trXX_dXX), [4](#)

tr15_d10 (trXX_dXX), [4](#)

tr16_d10 (trXX_dXX), [4](#)

tr19_d10 (trXX_dXX), [4](#)

tr21_d10 (trXX_dXX), [4](#)

tr22_d10 (trXX_dXX), [4](#)

tr25_d10 (trXX_dXX), [4](#)

tr26_d10 (trXX_dXX), [4](#)

tr34_d10 (trXX_dXX), [4](#)

tr35_d10 (trXX_dXX), [4](#)

tr36_d10 (trXX_dXX), [4](#)

tr40_d10 (trXX_dXX), [4](#)

tr49_d10 (trXX_dXX), [4](#)

tr53_d10 (trXX_dXX), [4](#)

tr55_d10 (trXX_dXX), [4](#)

trXX_d10 (trXX_dXX), [4](#)

trXX_dXX, [4](#)