

Package ‘aplpack’

October 13, 2009

Type Package

Title Another Plot PACKage: stem.leaf, bagplot, faces, spin3R, and some slider functions

Version 1.2.2

Date 2009-10-13

Author Peter Wolf, Uni Bielefeld

Maintainer Peter Wolf <pwolf@wiwi.uni-bielefeld.de>

Depends R (>= 2.6.0), tcltk

Description set of functions for drawing some special plots: stem.leaf plots a stem and leaf plot
bagplot plots a bagplot faces plots chernoff faces spin3R for an inspection of a 3-dim point cloud
slider functions for interactive graphics

License GPL (>= 2)

URL <http://www.wiwi.uni-bielefeld.de/statistik/mitarbeiter/wolf/software/aplpack.html>

Repository CRAN

Date/Publication 2009-10-13 17:37:45

R topics documented:

bagplot	2
boxplot2D	4
faces	6
slider	8
slider.bootstrap.lm.plot	11
slider.brush	13
slider.hist	14
slider.lowess.plot	15
slider.smooth.plot.ts	16
slider.split.plot.ts	17
slider.zoom.plot.ts	18
spin3R	19
stem.leaf	20

bagplot *bagplot, a bivariate boxplot*

Description

`compute.bagplot()` computes an object describing a bagplot of a bivariate data set. `plot.bagplot()` plots a bagplot object. `bagplot()` computes and plots a bagplot.

Usage

```
bagplot(x, y, factor = 3, na.rm = FALSE, approx.limit = 300,
        show.outlier = TRUE, show.whiskers = TRUE,
        show.looppoints = TRUE, show.bagpoints = TRUE,
        show.loophull = TRUE, show.baghull = TRUE,
        create.plot = TRUE, add = FALSE, pch = 16, cex = 0.4,
        dkmethod = 2, precision = 1, verbose = FALSE,
        debug.plots = "no", col.loophull="#aaccff",
        col.looppoints="#3355ff", col.baghull="#7799ff",
        col.bagpoints="#000088", transparency=FALSE, ...
)
compute.bagplot(x, y, factor = 3, na.rm = FALSE, approx.limit = 300,
               dkmethod=2,precision=1,verbose=FALSE,debug.plots="no")
plot.bagplot(x,
            show.outlier = TRUE, show.whiskers = TRUE,
            show.looppoints = TRUE, show.bagpoints = TRUE,
            show.loophull = TRUE, show.baghull = TRUE,
            add = FALSE, pch = 16, cex = 0.4, verbose = FALSE,
            col.loophull="#aaccff", col.looppoints="#3355ff",
            col.baghull="#7799ff", col.bagpoints="#000088",
            transparency=FALSE, ...)
```

Arguments

<code>x</code>	<code>x</code> values of a data set; in <code>bagplot</code> : an object of class <code>bagplot</code> computed by <code>compute.bagplot</code>
<code>y</code>	<code>y</code> values of the data set
<code>factor</code>	factor defining the loop
<code>na.rm</code>	if TRUE 'NA' values are removed otherwise exchanged by mean
<code>approx.limit</code>	if the number of data points exceeds <code>approx.limit</code> a sample is used to compute some of the quantities; default: 300
<code>show.outlier</code>	if TRUE outlier are shown
<code>show.whiskers</code>	if TRUE whiskers are shown
<code>show.looppoints</code>	if TRUE loop points are plottet

```

show.bagpoints      if TRUE bag points are plotted
show.loophull       if TRUE the loop is plotted
show.baghull        if TRUE the bag is plotted
create.plot         if FALSE no plot is created
add                 if TRUE the bagplot is added to an existing plot
pch                 sets the plotting character
cex                 sets characters size
dkmethod            1 or 2, there are two method of approximating the bag, method 1 is very rough
precision           precision of approximation, default: 1
verbose             automatic commenting of calculations
debug.plots         if TRUE additional plots describing intermediate results are constructed
col.loophull        color of loop hull
col.looppoints      color of the points of the loop
col.baghull         color of bag hull
col.bagpoints       color of the points of the bag
transparency        see section details
...                 additional graphical parameters

```

Details

A bagplot is a bivariate generalization of the well known boxplot. It has been proposed by Rousseeuw, Ruts, and Tukey. In the bivariate case the box of the boxplot changes to a convex polygon, the bag of bagplot. In the bag are 50 percent of all points. The fence separates points within the fence from points outside. It is computed by increasing the the bag. The loop is defined as the convex hull containing all points inside the fence. If all points are on a straight line you get a classical boxplot. `bagplot()` plots bagplots that are very similar to the one described in Rousseeuw et al. Remarks: The two dimensional median is approximated. For large data sets the error will be very small. On the other hand it is not very wise to make a (graphical) summary of e.g. 10 bivariate data points. In case you want to plot multiple (overlapping) bagplots, you may want plots that are semi-transparent. For this you can use the `transparency` flag. If `transparency==TRUE` the alpha layer is set to '99' (hex). This causes the bagplots to appear semi-transparent, but ONLY if the output device is PDF and opened using: `pdf(file="filename.pdf", version="1.4")`. For this reason, the default is `transparency==FALSE`. This feature as well as the arguments to specify different colors has been proposed by Wouter Meuleman.

Value

`compute.bagplot` returns an object of class `bagplot` that could be plotted by `plot.bagplot()`.

Note

Version of bagplot: 08/2007

Author(s)

Peter Wolf

References

P. J. Rousseeuw, I. Ruts, J. W. Tukey (1999): The bagplot: a bivariate boxplot, *The American Statistician*, vol. 53, no. 4, 382–387

See Also[boxplot](#)**Examples**

```
# example: 100 random points and one outlier
dat<-cbind(rnorm(100)+100,rnorm(100)+300)
dat<-rbind(dat,c(105,295))
bagplot(dat,factor=2.5,create.plot=TRUE,approx.limit=300,
  show.outlier=TRUE,show.looppoints=TRUE,
  show.bagpoints=TRUE,dkmethod=2,
  show.whiskers=TRUE,show.loophull=TRUE,
  show.baghull=TRUE,verbose=FALSE)
# example of Rousseeuw et al., see R-package rpart
cardata <- structure(as.integer( c(2560,2345,1845,2260,2440,
  2285, 2275, 2350, 2295, 1900, 2390, 2075, 2330, 3320, 2885,
  3310, 2695, 2170, 2710, 2775, 2840, 2485, 2670, 2640, 2655,
  3065, 2750, 2920, 2780, 2745, 3110, 2920, 2645, 2575, 2935,
  2920, 2985, 3265, 2880, 2975, 3450, 3145, 3190, 3610, 2885,
  3480, 3200, 2765, 3220, 3480, 3325, 3855, 3850, 3195, 3735,
  3665, 3735, 3415, 3185, 3690, 97, 114, 81, 91, 113, 97, 97,
  98, 109, 73, 97, 89, 109, 305, 153, 302, 133, 97, 125, 146,
  107, 109, 121, 151, 133, 181, 141, 132, 133, 122, 181, 146,
  151, 116, 135, 122, 141, 163, 151, 153, 202, 180, 182, 232,
  143, 180, 180, 151, 189, 180, 231, 305, 302, 151, 202, 182,
  181, 143, 146, 146)), .Dim = as.integer(c(60, 2)),
  .Dimnames = list(NULL, c("Weight", "Disp.")))
bagplot(cardata,factor=3,show.baghull=TRUE,
  show.loophull=TRUE,precision=1,dkmethod=2)
title("car data Chambers/Hastie 1992")
# points of y=x*x
bagplot(x=1:30,y=(1:30)^2,verbose=FALSE,dkmethod=2)
# one dimensional subspace
bagplot(x=1:100,y=1:100)
```

Description

boxplot2D computes summary statistics of a one dimensional projection of a two dimensional data set and plots a sloped boxplot of the statistics into the scatterplot of the two dimensional data set.

Usage

```
boxplot2D(xy, add.to.plot = TRUE, box.size = 10, box.shift = 0,
angle = 0, angle.type = "0", tukey.style = TRUE, coef.out = 1.5,
coef.h.out = 3, design = "s1", na.rm=FALSE, ...)
```

Arguments

xy	(nx2) -matrix, two dimensional data set
add.to.plot	if TRUE the boxplot is added to the actual plot of the graphics device
box.size	height of the box (of the boxplot)
box.shift	shift of boxplot perpendicular to the projection direction
angle	direction of projection in units defined by angle.type
angle.type	"0": angle in $(0, 2\pi)$, "1": clock-like: $\text{angle.type} \cdot 0 \Rightarrow 2\pi \cdot \text{angle.type} / 12$, "2": degrees: $\text{angle.type} \cdot 0 \Rightarrow 2\pi \cdot \text{angle.type} / 360$, "3": by fraction: $\Delta y / \Delta x$
tukey.style	if TRUE outliers are defined as described in Tukey (1977)
coef.out	outliers are values that are more than $\text{coef.out} \cdot \text{boxwidth}$ away from the box, default: $\text{coef.out} = 1.5$
coef.h.out	heavy outliers are values that are more than $\text{coef.h.out} \cdot \text{boxwidth}$ away from the box, default: $\text{coef.h.out} = 3$
design	if s1 then parallelogram else box
na.rm	if TRUE 'NA' values are removed otherwise exchanged by mean
...	additional graphical parameters

Note

version 08/2003

Author(s)

Peter Wolf

References

Tukey, J. *Exploratory Data Analysis*. Addison-Wesley, 1977.

See Also

[boxplot](#)

Examples

```
xy<-cbind(1:100, (1:100)+rnorm(100,,5))
plot(xy,xlim=c(-50,150),ylim=c(-50,150))
boxplot2D(xy,box.shift=-30,angle=3,angle.typ=1)
boxplot2D(xy,box.shift=20,angle=1,angle.typ=1)
boxplot2D(xy,box.shift=50,angle=5,angle.typ=1)
```

faces

Chernoff Faces

Description

faces represent the rows of a data matrix by faces. plot.faces plots faces into a scatterplot.

Usage

```
faces(xy, which.row, fill = FALSE, face.type = 1, nrow.plot,
      ncol.plot, scale = TRUE, byrow = FALSE, main, labels, na.rm = FALSE,
      ncolors = 20, col.nose = rainbow(ncolors), col.eyes = rainbow(ncolors,
        start = 0.6, end = 0.85), col.hair = terrain.colors(ncolors),
      col.face = heat.colors(ncolors), col.lips = rainbow(ncolors,
        start = 0, end = 0.2), col.ears = rainbow(ncolors, start = 0,
        end = 0.2), plot.faces = TRUE)

plot.faces(x, x.pos, y.pos, face.type = 1, width = 1, height = 1, labels,
          ncolors = 20, col.nose = rainbow(ncolors), col.eyes = rainbow(ncolors,
            start = 0.6, end = 0.85), col.hair = terrain.colors(ncolors),
          col.face = heat.colors(ncolors), col.lips = rainbow(ncolors,
            start = 0, end = 0.2), col.ears = rainbow(ncolors, start = 0,
            end = 0.2), ...)
```

Arguments

xy	xy data matrix, rows represent individuals and columns variables
which.row	defines a permutation of the rows of the input matrix
fill	if (fill==TRUE), only the first nc attributes of the faces are transformed, nc is the number of columns of xy
face.type	an integer between 0 and 2 with the meanings: 0 = line drawing faces, 1 = the elements of the faces are painted, 2 = Santa Claus faces are drawn
nrow.plot	number of columns of faces on graphics device
ncol.plot	number of rows of faces
scale	if (scale==TRUE), variables will be normalized
byrow	if (byrow==TRUE), xy will be transposed
main	title

<code>labels</code>	character strings to use as names for the faces
<code>na.rm</code>	if TRUE 'NA' values are removed otherwise exchanged by mean of data
<code>plot.faces</code>	if FALSE no face is plotted
<code>x</code>	an object of class <code>faces</code> computed by <code>faces</code>
<code>x.pos</code>	x coordinates of positions of faces
<code>y.pos</code>	y coordinates of positions of faces
<code>width</code>	width of the faces
<code>height</code>	height of the faces
<code>ncolors</code>	number of colors in the palettes for painting the elements of the faces
<code>col.nose</code>	palette of colors for painting the nose
<code>col.eyes</code>	palette of colors for painting the eyes
<code>col.hair</code>	palette of colors for painting the hair
<code>col.face</code>	palette of colors for painting the face
<code>col.lips</code>	palette of colors for painting the lips
<code>col.ears</code>	palette of colors for painting the ears
<code>...</code>	additional graphical arguments

Details

Explanation of parameters: 1-height of face, 2-width of face, 3-shape of face, 4-height of mouth, 5-width of mouth, 6-curve of smile, 7-height of eyes, 8-width of eyes, 9-height of hair, 10-width of hair, 11-styling of hair, 12-height of nose, 13-width of nose, 14-width of ears, 15-height of ears. For details look at the literate program of `faces`

Value

list of two elements: The first element `out$faces` is a list of standardized faces of class `faces`, this object could be plotted by `plot.faces`; a plot of faces is created on the graphics device if `plot.faces=TRUE`. The second list is short description of the effects of the variables.

Note

version 01/2009

Author(s)

H. P. Wolf

References

Chernoff, H. (1973): The use of faces to represent statistical assoziation, *JASA*, 68, pp 361–368. The smooth curves are computed by an algorithm found in Ralston, A. and Rabinowitz, P. (1985): A first course in numerical analysis, McGraw-Hill, pp 76ff. <http://www.wiwi.uni-bielefeld.de/mitarbeiter/wolf/> : S/R - functions : faces

See Also

—

Examples

```

faces()
faces(face.type=1)

faces(rbind(1:3,5:3,3:5,5:7))

data(longley)
faces(longley[1:9,],face.type=0)
faces(longley[1:9,],face.type=1)

plot(longley[1:16,2:3],btty="n")
a<-faces(longley[1:16,],plot=FALSE)
plot.faces(a,longley[1:16,2],longley[1:16,3],width=35,height=30)

set.seed(17)
faces(matrix(sample(1:1000,128, ),16,8),main="random faces")

a<-faces(rbind(1:3,5:3,3:5,5:7),plot.faces=FALSE)
plot(0:5,0:5,type="n")
plot(a,x.pos=1:4,y.pos=1:4,1.5,0.7)
# during Christmastime
faces(face.type=2)

```

slider*slider / button control widgets*

Description

slider constructs a Tcl/Tk-widget with sliders and buttons automated calculation and plotting. For example slider allows complete all axes rotation of objects in a plot.

Usage

```
slider(sl.functions, sl.names, sl.mins, sl.maxs, sl.deltas, sl.defaults, but.function)
```

Arguments

sl.functions	set of functions or function connected to the slider(s)
sl.names	labels of the sliders
sl.mins	minimum values of the sliders' ranges
sl.maxs	maximum values of the sliders' ranges
sl.deltas	change of step per click

<code>sl.defaults</code>	default values for the sliders
<code>but.functions</code>	function or list of functions that are assigned to the button(s)
<code>but.names</code>	labels of the buttons
<code>no</code>	<code>slider(no=i)</code> requests slider <code>i</code>
<code>set.no.value</code>	<code>slider(set.no.value=c(i, val))</code> sets slider <code>i</code> to value <code>val</code>
<code>obj.name</code>	<code>slider(obj.name=name)</code> requests the value of variable <code>name</code> from environment <code>slider.env</code>
<code>obj.value</code>	<code>slider(obj.name=name, obj.value=value)</code> assigns value to variable <code>name</code> in environment <code>slider.env</code>
<code>reset.function</code>	function that induce a <code>reset.button</code> and contains the commands of it.
<code>title</code>	title of the control window
<code>prompt</code>	if TRUE slider functions are called by moving a slider, if FALSE slider functions are called after releasing the mouse button

Details

With slider you can: a) define (multiple) sliders and buttons, b) request or set slider values, and c) request or set variables in the environment `slider.env`. Slider function management takes place in the environment `slider.env`. If `slider.env` is not found it is generated.

Definition ... of sliders: First of all you have to define sliders, buttons and the attributes of them. Sliders are established by six arguments: `sl.functions`, `sl.names`, `sl.minima`, `sl.maxima`, `sl.deltas`, and `sl.defaults`. The first argument, `sl.functions`, is either a list of functions or a single function that contains the commands for the sliders. If there are three sliders and slider 2 is moved with the mouse the function stored in `sl.functions[[2]]` (or in case of one function for all sliders the function `sl.functions`) is called.

DEFINITION ... of buttons: Buttons are defined by a vector of labels `but.names` and a list of functions: `but.functions`. If button `i` is pressed the function stored in `but.functions[[i]]` is called.

REQUESTING ... a slider: `slider(no=1)` returns the actual value of slider 1, `slider(no=2)` returns the value of slider 2, etc. You are allowed to include expressions of the type `slider(no=i)` in functions describing the effect of sliders or buttons.

SETTING ... a slider: `slider(set.no.value=c(2, 333))` sets slider 2 to value 333. `slider(set.no.value=c(i, value))` can be included in the functions defining the effects of moving sliders or pushing buttons.

VARIABLES ... of the environment `slider.env`: Sometimes information has to be transferred back and forth between functions defining the effects of sliders and buttons. Imagine for example two sliders: one to control p and another one to control q , but they should satisfy: $p+q=1$. Consequently, you have to correct the value of the first slider after the second one was moved. To prevent the creation of global variables store them in the environment `slider.env`. Use `slider(obj.name="p.save", obj.value=1-slider(no=2))` to assign value `1-slider(no=2)` to the variable `p.save`. `slider(obj.name=p.save)` returns the value of variable `p.save`.

Value

Using `slider` in definition mode `slider` returns the value of new created the top level widget. `slider(no=i)` returns the actual value of slider `i`. `slider(obj.name=name)` returns the value of variable `name` in environment `slider.env`.

Author(s)

Hans Peter Wolf

Examples

```
# example 1, sliders only
## Not run:
## This example cannot be run by examples() but should work in an interactive R session
plot.sample.norm<-function(){
  refresh.code<-function(...){
    mu<-slider(no=1); sd<-slider(no=2); n<-slider(no=3)
    x<-rnorm(n,mu,sd)
    plot(x)
  }
  slider(refresh.code,sl.names=c("value of mu","value of sd","n number of observations"),
         sl.mins=c(-10,.01,5),sl.maxs=c(+10,50,100),sl.deltas=c(.01,.01,1),sl.defaults=c(0,1,20))
}
plot.sample.norm()
## End(Not run)

# example 2, sliders and buttons
## Not run:
## This example cannot be run by examples() but should work in an interactive R session
plot.sample.norm.2<-function(){
  refresh.code<-function(...){
    mu<-slider(no=1); sd<-slider(no=2); n<-slider(no=3)
    type= slider(obj.name="type")
    x<-rnorm(n,mu,sd)
    plot(seq(x),x,ylim=c(-20,20),type=type)
  }
  slider(refresh.code,sl.names=c("value of mu","value of sd","n number of observations"),
         sl.mins=c(-10,.01,5),sl.maxs=c(10,10,100),sl.deltas=c(.01,.01,1),sl.defaults=c(0,1,20),
         but.functions=list(
           function(...){slider(obj.name="type",obj.value="l");refresh.code()},
           function(...){slider(obj.name="type",obj.value="p");refresh.code()},
           function(...){slider(obj.name="type",obj.value="b");refresh.code()}
         ),
         but.names=c("lines","points","both"))
  slider(obj.name="type",obj.value="l")
}
plot.sample.norm.2()
## End(Not run)

# example 3, dependent sliders
## Not run:
```

```

## This example cannot be run by examples() but should work in an interactive R session
print.of.p.and.q<-function(){
  refresh.code<-function(...){
    p.old<-slider(obj.name="p.old")
    p<-slider(no=1); if(abs(p-p.old)>0.001) {slider(set.no.value=c(2,1-p))}
    q<-slider(no=2); if(abs(q-(1-p))>0.001) {slider(set.no.value=c(1,1-q))}
    slider(obj.name="p.old",obj.value=p)
    cat("p=",p,"q=",1-p,"\n")
  }
  slider(refresh.code,sl.names=c("value of p","value of q"),
         sl.mins=c(0,0),sl.maxs=c(1,1),sl.deltas=c(.01,.01),sl.defaults=c(.2,.8))
  slider(obj.name="p.old",obj.value=slider(no=1))
}
print.of.p.and.q()
## End(Not run)

# example 4, rotating a surface
## Not run:
## This example cannot be run by examples() but should work in an interactive R session
R.veil.in.the.wind<-function(){
  # Mark Hempelmann / Peter Wolf
  par(bg="blue4", col="white", col.main="white",
      col.sub="white", font.sub=2, fg="white") # set colors and fonts
  samp <- function(N,D) N*(1/4+D)/(1/4+D*N)
  z<-outer(seq(1, 800, by=10), seq(.0025, 0.2, .0025)^2/1.96^2, samp) # create 3d matrix
  h<-100
  z[10:70,20:25]<-z[10:70,20:25]+h; z[65:70,26:45]<-z[65:70,26:45]+h
  z[64:45,43:48]<-z[64:45,43:48]+h; z[44:39,26:45]<-z[44:39,26:45]+h
  x<-26:59; y<-11:38; zz<-outer(x,y,"+"); zz<-zz*(65<zz)*(zz<73)
  cz<-10+col(zz)[zz>0];rz<-25+row(zz)[zz>0]; z[cbind(cz,rz)]<-z[cbind(cz,rz)]+h
  refresh.code<-function(...){
    theta<-slider(no=1); phi<-slider(no=2)
    persp(x=seq(1,800,by=10),y=seq(.0025,0.2,.0025),z=z,theta=theta,phi=phi,
          scale=T, shade=.9, box=F, ltheta = 45,
          lphi = 45, col="aquamarine", border="NA",ticktype="detailed")
  }
  slider(refresh.code, c("theta", "phi"), c(0, 0),c(360, 360),c(.2, .2),c(85, 270) )
}
R.veil.in.the.wind()
## End(Not run)

```

slider.bootstrap.lm.plot

interactive bootstrapping for lm

Description

slider.bootstrap.lm.plot computes a scatterplot and adds regression curves of samples of the data points. The number of samples and the degree of the model are controlled by sliders.

Usage

```
slider.bootstrap.lm.plot(x, y, ...)
```

Arguments

x	two column matrix or vector of x values if y is used
y	y values if x is not a matrix
...	additional graphics parameters

Details

slider.bootstrap.lm.plot draws a scatterplot of the data points and fits a linear model to the data set. Regression curves of samples of the data are then added to the plot. Within a Tcl/Tk control widget the degree of the model, the repetitions and the start of the random seed are set. After modification of a parameter the plot is updated.

Value

a message about the usage

Author(s)

Hans Peter Wolf

References

~~

See Also

[plot](#)

Examples

```
## Not run:  
## This example cannot be run by examples() but should be work in an interactive R session  
  daten<-iris[,2:3]  
  slider.bootstrap.lm.plot(daten)  
## End(Not run)
```

slider.brush *interactive brushing functions*

Description

These functions compute a pairs plot or a simple xy-plot and open a slider control widget for brushing.

`slider.brush.pairs` computes a pairs plot; the user defines an interval for one of the variables and in effect all data points in this interval will be recolored.

`slider.brush.plot.xy` computes an xy-plot; the user defines a interval for a third variable z and all points (x, y) will be recolored red if the z value is in the interval.

Usage

```
slider.brush.pairs(x, ...)  
slider.brush.plot.xy(x, y, z, ...)
```

Arguments

<code>...</code>	new settings for global graphics parameters
<code>x</code>	matrix or data frame or vector
<code>y</code>	vector of y values if <code>x</code> is not a matrix
<code>z</code>	vector of z values if <code>x</code> is not a matrix

Details

`slider.brush.pairs` draws a pairs plot of the data set `x`. The first slider defines the lower limit of the interval and the second its width. By the third slider a variable is selected. All data points for which the selected variable is in the interval are recolored red.

`slider.brush.plot.xy` draws an xy-plot of the data set `x`. The first slider defines the lower limit of the interval of z values and the second one its width. All data points for which the variable z is in the interval are recolored red.

Value

a message about the usage

Author(s)

Hans Peter Wolf

References

W. S. Cleveland, R. A. Becker, and G. Weil. The Use of Brushing and Rotation for Data Analysis. In W. S. Cleveland and M. E. McGill, editors, *Dynamic Graphics for Statistics*. Wadsworth and Brooks/Cole, Pacific Grove, CA, 1988.

See Also[pairs](#), [plot](#)**Examples**

```
## Not run:
## This example cannot be run by examples() but should be work in an interactive R session
  slider.brush.pairs(iris)
## End(Not run)
## Not run:
## This example cannot be run by examples() but should be work in an interactive R session
  slider.brush.plot.xy(iris[,1:3])
## End(Not run)
```

`slider.hist`*interactive histogram and density traces*

Description

The functions `slider.hist` and `slider.density` compute histograms and density traces whereas some parameter are controlled by sliders.

`slider.hist` computes a histogram; the number of classes is defined by a slider.

`slider.density` computes a density trace; width and type of the kernel are defined by sliders.

Usage

```
slider.hist(x, panel, ...)
slider.density(x, panel, ...)
```

Arguments

<code>x</code>	data set to be used for plotting
<code>panel</code>	function constructing additional graphical elements to the plot
<code>...</code>	additional (graphics) parameters which are passed to the invoked high level plotting function

Details

`slider.hist` draws a histogram of the data set `x` by calling `hist` and opens a Tcl/Tk widget with one slider. The slider defines the number of classes of the histogram. Changing the slider results in redrawing of the plot. For further details see the help page of `hist`. `rug` is used as the default panel function.

`slider.density` draws a density trace of the data set `x` by `plot(density(...))` and opens a Tcl/Tk-widget with two sliders. The first slider defines the width of the density trace and the second one the kernel function: "1-gaussian", "2-epanechnikov", "3-rectangular", "4-triangular", "5-biweight", "6-cosine", "7-optcosine" Changing one of the sliders results in a redrawing of the plot. For further details see the help page of `density`. `rug` is used as the default panel function.

Value

a message about the usage

Author(s)

Hans Peter Wolf

References

~~

See Also

[hist](#), [slider](#)

Examples

```
## Not run:
## This example cannot be run by examples() but should be work in an interactive R session
  slider.hist(log(islands))
## End(Not run)
## Not run:
## This example cannot be run by examples() but should be work in an interactive R session
  slider.density(rivers,xlab="rivers",col="red")
## End(Not run)
## Not run:
## This example cannot be run by examples() but should be work in an interactive R session
  slider.density(log(rivers),xlab="rivers",col="red",
    panel=function(x) {
      xx<-seq(min(x),max(x),length=100)
      yy<-dnorm(xx,mean(x),sd(x))
      lines(xx,yy)
      rug(x)
      print(summary(yy))
    }
  )
## End(Not run)
```

slider.lowess.plot *interactive lowess smoothing*

Description

slider.lowess.plot computes an xy-plot of the data and adds LOWESS lines. The smoother span and the number of iterations are selected by sliders.

Usage

```
slider.lowess.plot(x, y, ...)
```

Arguments

x	data set to be used for plotting or vector of x values
y	vector of y values in case x is not a matrix
...	additional (graphics) parameter settings

Details

`slider.lowess.plot` computes a scatterplot of the data. Then a LOWESS smoother line is added to the plot. For more details about the lowess parameters `f` and `iter` take a look at the help page of `lowess`. The parameters are set by moving sliders of the control widget. The first slider defines the smoother span `f` and the second one the number of iterations.

Value

a message about the usage

Author(s)

Hans Peter Wolf

References

for references see help file of `lowess`

See Also

[lowess](#), [slider](#)

Examples

```
## Not run:  
## This example cannot be run by examples() but should be work in an interactive R session  
  slider.lowess.plot(cars)  
## End(Not run)
```

`slider.smooth.plot.ts`
interactive Tukey smoothing

Description

`slider.smooth.plot.ts` computes smooth curves of a time series plot by Tukey's smoothers. The kind of smoothing is controlled by a Tcl/Tk widget.

Usage

```
slider.smooth.plot.ts(x, ...)
```

Arguments

x time series
... additional graphical parameters

Details

slider.smooth.plot.ts draws the time series x. The user selects a filter of the set c("3RS3R", "3RSS", "3RSR", "3R", "3", "S") step by step and the resulting curve is added to the plot. The selection is performed by pressing a button of the control widget of slider.smooth.plot.ts. The button `reset` restarts the smoothing process.

Value

a message about the usage

Author(s)

Hans Peter Wolf

References

Tukey, J. W. (1977). Exploratory Data Analysis, Reading Massachusetts: Addison-Wesley.

See Also

[plot, smooth](#)

Examples

```
## Not run:  
## This example cannot be run by examples() but should be work in an interactive R session  
  slider.smooth.plot.ts(rnorm(100))  
## End(Not run)
```

slider.split.plot.ts

interactive splitting of time series

Description

slider.split.plot.ts plots linear fitted lines or summary statistics in sections of a time series. The sections are controlled by sliders.

Usage

```
slider.split.plot.ts(x, type="l", ...)
```

Arguments

<code>x</code>	time series or vector
<code>type</code>	plotting type: <code>type</code> will be forwarded to function <code>plot</code>
<code>...</code>	additional graphics parameters

Details

`slider.split.plot.ts` draws a time series plot and let you define sections of the series by fixing a limit on the time scale as well as a window width. The whole range of the series is partitioned in pieces of the same length in a way that the fixed limit will be one of the section limits. Then linear models are fitted and plotted in the sections. Alternatively – by pressing the button `fivenum summary` – summary statistics are drawn instead of the model lines.

The first slider fixes the width of the sections and the second one the limit between two of them.

By clicking on button `linear model` or `fivenum summary` the user switches between drawing model curves and five number summary.

Value

a message about the usage

Author(s)

Hans Peter Wolf

See Also

[plot](#)

Examples

```
## Not run:  
## This example cannot be run by examples() but should be work in an interactive R session  
  slider.split.plot.ts(as.vector(sunspots)[1:100])  
## End(Not run)
```

`slider.zoom.plot.ts`

interactive zooming of time series

Description

This function shows one or two sections of a time series. The window(s) is (are) controlled by sliders.

Usage

```
slider.zoom.plot.ts(x, n.windows, ...)
```

Arguments

x time series
n.windows if (n.windows>1 two sections are defined
... additional graphical parameters

Details

`slider.zoom.plot.ts` plots the original time series and it lets you select one or two sections of the series by fixing the width(s) and the starting point(s) of the region(s). Then the section(s) of the series is (are) plotted separately one below the other.

The first slider defines the width of the section(s). The second (third) one sets the start of the first (second) section.

Value

a message about the usage

Author(s)

Hans Peter Wolf

See Also

[plot](#)

Examples

```
## Not run:  
## This example cannot be run by examples() but should be work in an interactive R session  
  slider.zoom.plot.ts(co2,2)  
## End(Not run)
```

spin3R

spin3R

Description

Simple spin function to rotate and to inspect a 3-dimensional cloud of points

Usage

```
spin3R(x, alpha = 1, delay = 0.015, na.rm=FALSE)
```

Arguments

x (n×3) -matrix of points
 alpha angle between successive projections
 delay delay in seconds between two plots
 na.rm if TRUE 'NA' values are removed otherwise exchanged by mean

Details

spin3R computes two-dimensional projections of (n×3) -matrix x and plots them on the graphics device. The cloud of points is rotated step by step. The rotation is defined by a tcl/tk control widget. spin3R requires tcl/tk package of R.

Note

version 01/2003

Author(s)

Peter Wolf

References

Cleveland, W. S. / McGill, M. E. (1988): Dynamic Graphics for Statistics. Wadsworth & Brooks/Cole, Belmont, California.

See Also

spin of S-Plus

Examples

```
xyz<-matrix(rnorm(300),100,3)
# now start: spin3R(xyz)
```

stem.leaf

Stem-and-Leaf Display

Description

Creates a classical ("Tukey-style") stem-and-leaf display.

Usage

```
stem.leaf(data, unit, m, Min, Max, rule.line = c("Dixon", "Velleman", "Sturges"),
  style = c("Tukey", "bare"), trim.outliers = TRUE, depths = TRUE,
  reverse.negative.leaves = TRUE, na.rm = FALSE)
```

Arguments

<code>data</code>	a numeric vector.
<code>unit</code>	leaf unit, as a power of 10 (e.g., 100, .01); if <code>unit</code> is missing <code>unit</code> is chosen by <code>stem.leaf</code> .
<code>m</code>	number of parts (1, 2, or 5) into which each stem will be separated; if <code>m</code> is missing the number of parts/stem (<code>m</code>) is chosen by <code>stem.leaf</code> .
<code>Min</code>	smallest non-outlying value; omit for automatic choice.
<code>Max</code>	largest non-outlying value; omit for automatic choice.
<code>rule.line</code>	the rule to use for choosing the desired number of lines in the display; "Dixon" = $10 \cdot \log_{10}(n)$; "Velleman" = $2 \cdot \sqrt{n}$; "Sturges" = $1 + \log_2(n)$; the default is "Dixon".
<code>style</code>	"Tukey" (the default) for "Tukey-style" divided stems; "bare" for divided stems that simply repeat the stem digits.
<code>trim.outliers</code>	if TRUE (the default), outliers are placed on LO and HI stems.
<code>depths</code>	if TRUE (the default), print a column of "depths" to the left of the stems; the depth of the stem containing the median is the stem-count enclosed in parentheses.
<code>reverse.negative.leaves</code>	if TRUE (the default), reverse direction the leaves on negative stems (so, e.g., the leaf 9 comes before the leaf 8, etc.).
<code>na.rm</code>	if TRUE 'NA' values are removed otherwise the number of NA's are counted

Details

Unlike the `stem` function in the `base` package, this function produces classic stem-and-leaf displays, as described in Tukey's *Exploratory Data Analysis*.

Value

The computed stem and leaf display is printed out. Invisibly `stem.leaf` returns the stem and leaf display as a list containing the elements `info` (legend), `stem` (display as character vector), `lower` (very small values), and `upper` (very large values).

Author(s)

Peter Wolf, the code has been slightly modified by John Fox (jfox@mcmaster.ca) with the original author's permission, help page written by John Fox, the help page has been slightly modified by Peter Wolf.

References

Tukey, J. *Exploratory Data Analysis*. Addison-Wesley, 1977.

See Also

[stem](#)

Examples

```
stem.leaf(co2)
```

Index

*Topic **dynamic**

slider, 8

*Topic **iplot**

slider, 8

slider.bootstrap.lm.plot, 11

slider.brush, 13

slider.hist, 14

slider.lowess.plot, 15

slider.smooth.plot.ts, 16

slider.split.plot.ts, 17

slider.zoom.plot.ts, 18

*Topic **misc**

bagplot, 2

boxplot2D, 4

faces, 6

spin3R, 19

stem.leaf, 20

*Topic **univar**

slider.hist, 14

bagplot, 2

boxplot, 4, 5

boxplot2D, 4

compute.bagplot (*bagplot*), 2

faces, 6

hist, 15

lowess, 16

pairs, 14

plot, 12, 14, 17–19

plot.bagplot (*bagplot*), 2

plot.faces (*faces*), 6

slider, 8

slider.bootstrap.lm.plot, 11

slider.brush, 13

slider.brush.plot.xy

(*slider.brush*), 13

slider.density (*slider.hist*), 14

slider.hist, 14

slider.lowess.plot, 15

slider.smooth.plot.ts, 16

slider.split.plot.ts, 17

slider.zoom.plot.ts, 18

smooth, 17

spin3R, 19

stem, 21

stem.leaf, 20