

Package ‘apsimx’

January 14, 2021

Title Inspect, Read, Edit and Run 'APSIM' ``Next Generation" and 'APSIM' Classic

Version 1.971

Description The functions in this package inspect, read, edit and run files for 'APSIM' ``Next Generation" ('JSON') and 'APSIM' ``Classic" ('XML'). The files with an 'apsim' extension correspond to 'APSIM' Classic (7.x) - Windows only - and the ones with an 'apsimx' extension correspond to 'APSIM' ``Next Generation". For more information about 'APSIM' see (<<https://www.apsim.info/>>) and for 'APSIM' next generation (<<https://apsimnextgeneration.netlify.app/>>).

Depends R (>= 3.5.0)

License GPL-3

Encoding UTF-8

VignetteBuilder knitr

BugReports <https://github.com/femiguez/apsimx/issues>

Imports DBI, jsonlite, knitr, RSQLite, tools, utils, xml2

Suggests BayesianTools, datasets, FedData, ggplot2, GSODR, listviewer, mvtnorm, nasapower, nloptr, raster, reactR, rmarkdown, sp, spData, sf

LazyData true

RoxygenNote 7.1.1

NeedsCompilation no

Author Fernando Miguez [aut, cre] (<<https://orcid.org/0000-0002-4627-8329>>)

Maintainer Fernando Miguez <femiguez@iastate.edu>

Repository CRAN

Date/Publication 2021-01-14 21:20:07 UTC

R topics documented:

apsim	3
apsim.options	4
apsimx	5
apsimx.options	6
apsimx_example	6
apsimx_filetype	7
apsimx_options	8
apsimx_soil_profile	9
apsim_example	12
apsim_options	13
apsim_version	14
auto_detect_apsimx_examples	14
auto_detect_apsim_examples	15
check_apsim_met	16
compare_apsim	16
compare_apsim_met	18
doy2date	19
edit_apsim	20
edit_apsimx	22
edit_apsimx_batch	24
edit_apsimx_replacement	26
edit_apsimx_replace_soil_profile	27
edit_apsim_replace_soil_profile	29
edit_apsim_xml	30
extract_values_apsimx	32
get_daymet_apsim_met	32
get_gsod_apsim_met	34
get_iemre_apsim_met	35
get_iem_apsim_met	36
get_power_apsim_met	37
impute_apsim_met	38
inspect_apsim	38
inspect_apsimx	41
inspect_apsimx_replacement	43
inspect_apsim_xml	45
mcmc.apsim.env	46
mcmc.apsimx.env	46
napad_apsim_met	47
obsWheat	47
optim_apsim	48
optim_apsimx	50
print.met	51
read_apsim	52
read_apsimx	52
read_apsimx_all	53
read_apsim_all	54

read_apsim_met	54
soilwat_parms	55
ssurgo2sp	56
swim_parms	58
unit_conv	60
view_apsim	61
view_apsimx	62
view_apsim_xml	62
wop	63
wop.h	64
write_apsim_met	64

Index	66
--------------	-----------

apsim	<i>Run an APSIM (7.x) 'Classic' simulation</i>
-------	--

Description

Run apsim from R. It's for Windows only. It uses 'shell'.

Usage

```
apsim(
  file = "",
  src.dir = ".",
  silent = FALSE,
  value = c("all", "report", "none"),
  cleanup = FALSE,
  simplify = TRUE
)
```

Arguments

file	file name to be run (the extension .apsim is optional)
src.dir	directory containing the .apsim file to be run (defaults to the current directory)
silent	whether to print messages from apsim simulation
value	how much output to return: option 'all' returns all components of the simulation; option 'report' returns only the 'main' report component;
cleanup	logical. Whether to delete the .out file generated by APSIM. Default is FALSE.
simplify	whether to return a single data frame when multiple simulations are present. If FALSE it will return a list.

Details

Run an APSIM (7.x) 'Classic' Simulation

A valid apsim file can be run from within R. The main goal is to make running APSIM-X simple, especially for large scale simulations or parameter optimization

Examples

```
## Not run:  
## See function 'apsim_example'  
  
## End(Not run)
```

apsim.options

Environment which stores APSIM options

Description

Environment which can store the path to the executable and where examples are located. Creating an environment avoids the use of global variables or other similar practices which would have possible undesirable consequences.

Usage

```
apsim.options
```

Format

An object of class environment of length 3.

Details

Environment which stores APSIM options

Examples

```
## Not run:  
names(apsim.options)  
apsim_options(exe.path = "some-new-path-to-executable")  
apsim.options$exe.path  
  
## End(Not run)
```

apsimx *Run an APSIM-X simulation*

Description

Run apsimx from R. It uses ‘system’ (unix) or ‘shell’ (windows) and it attempts to be platform independent.

Usage

```
apsimx(
  file = "",
  src.dir = ".",
  silent = FALSE,
  value = c("all", "report", "none"),
  cleanup = FALSE
)
```

Arguments

file	file name to be run (the extension .apsimx is optional)
src.dir	directory containing the .apsimx file to be run (defaults to the current directory)
silent	whether to print messages from apsim simulation
value	how much output to return: option ‘all’ returns all components of the simulation; option ‘report’ returns only the ‘main’ report component; option ‘none’ does not create a data.frame but it generates the databases from APSIM-X
cleanup	logical. Whether to delete the .db file generated by APSIM-X. Default is FALSE

Details

Run an APSIM-X Simulation

A valid apsimx file can be run from within R. The main goal is to make running APSIM-X simple, especially for large scale simulations or parameter optimization

Value

a data frame with the ‘Report’ from the APSIM-X simulation. To change the variables being reported use the GUI.

Examples

```
## Not run:
## See function 'apsimx_example' and vignette 'apsimx'

## End(Not run)
```

apsimx.options *Environment which stores APSIM-X options*

Description

Environment which can store the path to the executable, warning settings and where examples are located. Creating an environment avoids the use of global variables or other similar practices which would have possible undesirable consequences.

Usage

```
apsimx.options
```

Format

An object of class environment of length 5.

Details

Environment which stores APSIM-X options

Examples

```
## Not run:
names(apsimx.options)
apsimx_options(exe.path = "some-new-path-to-executable")
apsimx.options$exe.path

## End(Not run)
```

apsimx_example *Access Example APSIM-X Simulations*

Description

simple function to run some of the built-in APSIM-X examples

Usage

```
apsimx_example(example = "Wheat", silent = FALSE)
```

Arguments

example	run an example from built-in APSIM-X. Options are all of the ones included with the APSIM-X distribution, except 'Graph'.
silent	whether to print standard output from the APSIM-X execution

Details

This function creates a temporary copy of the example file distributed with APSIM-X to avoid writing a .db file to the directory where the ‘Examples’ are located. It is not a good practice and there is no guarantee that the user has read/write permissions in that directory.

Note

This function creates a new column ‘Date’ which is in the R ‘Date’ format which is convenient for graphics.

Examples

```
## Not run:
wheat <- apsimx_example("Wheat")
maize <- apsimx_example("Maize")
barley <- apsimx_example("Barley")
## The 'Date' column is created by this function, based on apsim output.
require(ggplot2)
ggplot(data = wheat , aes(x = Date, y = Yield)) +
  geom_point()

## End(Not run)
```

apsimx_filetype *Test file format for .apsimx files*

Description

Test whether an .apsimx file is XML or json

Usage

```
apsimx_filetype(file = "", src.dir = ".")
```

Arguments

file	file ending in .apsimx to be tested
src.dir	directory containing the .apsimx file to be tested; defaults to the current working directory

Value

‘xml’, ‘json’ or ‘unknown’

Note

Minimal function which reads only the first line in a file and tries to guess whether it is an ‘xml’ or ‘json’ file type.

Examples

```
## Not run:
ex.dir <- auto_detect_apsimx_examples()
apsimx_filetype("Barley", src.dir = ex.dir)
apsimx_filetype("Chicory", src.dir = ex.dir)
apsimx_filetype("Oats", src.dir = ex.dir)
apsimx_filetype("Maize", src.dir = ex.dir)
apsimx_filetype("Sugarcane", src.dir = ex.dir)

## End(Not run)
```

apsimx_options

Setting some options for the package

Description

Set the path to the APSIM-X executable, examples and warning suppression.

Usage

```
apsimx_options(
  exe.path = NA,
  examples.path = NA,
  warn.versions = TRUE,
  warn.find.apsimx = TRUE
)
```

Arguments

`exe.path` path to apsim executable. White spaces are not allowed.

`examples.path` path to apsim examples

`warn.versions` logical. warning if multiple versions of APSIM-X are detected.

`warn.find.apsimx` logical. By default a warning will be thrown if APSIM-X is not found. If 'exe.path' is 'NA' an error will be thrown instead.

Details

Set apsimx options

Note

It is possible that APSIM-X is installed in some alternative location other than the defaults ones. Guessing this can be difficult and then the `auto_detect` functions might fail. Also, if multiple versions of APSIM-X are installed `apsimx` will choose the newest one but it will issue a warning. Suppress the warning by setting `warn.versions = FALSE`.

Examples

```
## Not run:
names(apsimx.options)
apsimx_options(exe.path = "some-new-path-to-executable")
apsimx.options$exe.path

## End(Not run)
```

apsimx_soil_profile *Create APSIM-X Soil Profiles*

Description

Generates a soil profile that can then replace the existing one in an '.apsimx' or '.apsim' simulation file

plotting function for a soil profile, it requires 'ggplot2'

checking an apsimx soil profile for reasonable values

Usage

```
apsimx_soil_profile(
  nlayers = 10,
  Depth = NULL,
  Thickness = NULL,
  BD = NULL,
  AirDry = NULL,
  LL15 = NULL,
  DUL = NULL,
  SAT = NULL,
  KS = NULL,
  crop.LL = NULL,
  crop.KL = NULL,
  crop.XF = NULL,
  Carbon = NULL,
  SoilCNRatio = NULL,
  FOM = NULL,
  FOM.CN = NULL,
  FBiom = NULL,
  FInert = NULL,
  NO3N = NULL,
  NH4N = NULL,
  PH = NULL,
  soil.bottom = 150,
  water.table = 200,
  soil.type = 0,
  crops = c("Maize", "Soybean", "Wheat"),
```

```

    metadata = NULL,
    soilwat = NA,
    swim = NA,
    dist.parms = list(a = 0, b = 0.2)
)

## S3 method for class 'soil_profile'
plot(
  x,
  ...,
  property = c("all", "water", "BD", "AirDry", "LL15", "DUL", "SAT", "KS", "crop.XF",
    "crop.KL", "crop.LL", "Carbon", "SoilCNRatio", "FOM", "FOM.CN", "FBiom", "FInert",
    "NO3N", "NH4N", "PH")
)

check_apsimx_soil_profile(x)

```

Arguments

nlayers	Number of soil layers (default = 10)
Depth	specific depths for each soil layer (cm)
Thickness	thickness for each soil layer (mm)
BD	bulk density for each soil layer (g/cc) – ‘cc’ is cubic cm
AirDry	air dry for each soil layer (mm/mm)
LL15	lower limit (15 bar) for each soil layer (mm/mm)
DUL	drainage upper limit (0.33 bar) for each soil layer (mm/mm)
SAT	saturation (0 bar) for each soil layer (mm/mm)
KS	saturated hydraulic conductivity (mm/day)
crop.LL	lower limit for a specific crop
crop.KL	root ability to extract water for a specific crop
crop.XF	soil root exploration for a specific crop
Carbon	organic carbon (percent)
SoilCNRatio	organic carbon C:N ratio
FOM	fresh organic matter (kg/ha)
FOM.CN	fresh organic matter C:N ratio
FBiom	Fraction of microbial biomass (0-1)
FInert	Fraction of inert carbon (0-1)
NO3N	nitrate nitrogen (Chemical) (ppm)
NH4N	ammonium nitrogen (Chemical) (ppm)
PH	soil pH
soil.bottom	bottom of the soil profile (cm)
water.table	water table level (not used at the moment) (cm)

soil.type	might use it in the future for auto filling missing information
crops	name of crops being grown
metadata	list with soil metadata. For possible parameters and values see an example of inspect_apsimx with soil.child = "Metadata".
soilwat	optional 'list' of class 'soilwat_parms'
swim	optional 'list' of class 'swim_parms'
dist.parms	parameter values for creating a profile. If a == 0 and b == 0 then a constant value of 1 is used. If a == 0 and b != 0, then an exponential decay is used. If a != 0 and b != 0 then the equation is $a * \text{soil.layer} * \exp(-b * \text{soil.layer})$.
x	object of class 'soil_profile' or the 'soil' component within an object of class 'soil_profile'.
...	additional plotting arguments (none use at the moment).
property	"all" for plotting all soil properties, "water" for just SAT, DUL and LL15

Details

Soil Profiles

Real soils might have discontinuities, but for APSIM it might be beneficial to be able to create a soil profile with an arbitrary number of layers and have flexibility in the distribution of soil physical and chemical properties. Steps:

1. [apsimx_soil_profile](#) is a function which can create a soil matrix with many layers
2. It allows for creating a smooth distribution for Physical (or Water), Chemical, InitialWater, Analysis, InitialN, Organic or SoilOrganicMatter
3. The distribution can be specified with the 'a' and 'c' parameter of an exponential decay function, using a list. E.g. DUL = list(0.35, 0, -0.1). This means that the top value for DUL will be 0.35 and it will decay with a rate of -0.1.
4. If an increase and then a decay is needed the Ricker function can be used. See 'SSricker' in the 'nlraa' package.

Value

a soil profile with class 'soil_profile' with elements 'soil' and 'crops' (for now)

Examples

```
## Not run:
sp <- apsimx_soil_profile()
require(ggplot2)
plot(sp)

## End(Not run)
```

`apsim_example`*Access Example APSIM Simulations*

Description

simple function to run some of the built-in APSIM examples

Usage

```
apsim_example(example = "Millet", silent = FALSE, tmp.dir = NULL)
```

Arguments

<code>example</code>	run an example from built-in APSIM. Options are all of the ones included with the APSIM distribution, except 'Graph'.
<code>silent</code>	whether to print standard output from the APSIM execution
<code>tmp.dir</code>	temporary directory where to write files

Details

This function creates a temporary copy of the example file distributed with APSIM to avoid writing a .out file to the directory where the 'Examples' are located. It is not a good practice and there is no guarantee that the user has read/write permissions in that directory.

Note

This function creates a new column 'Date' which is in the R 'Date' format which is convenient for graphics.

Examples

```
## Not run:
## Only run these if you have APSIM 'Classic' installed (Windows only)
millet <- apsim_example("Millet")
potato <- apsim_example("Potato")
sugar <- apsim_example("Sugar")
## The 'Date' column is created by this function, based on apsim output.
require(ggplot2)
ggplot(data = millet , aes(x = Date, y = millet_biomass)) +
  geom_line()

## End(Not run)
```

apsim_options	<i>Setting some options specific to APSIM (7.x) 'Classic'</i>
---------------	---

Description

Set the path to the APSIM executable, examples and warning suppression.

Usage

```
apsim_options(exe.path = NA, examples.path = NA, warn.versions = TRUE)
```

Arguments

exe.path	path to apsim executable
examples.path	path to apsim examples
warn.versions	logical. warning if multiple versions of APSIM are detected.

Details

Set apsim options

Note

It is possible that APSIM 7.x 'Classic' is installed in some alternative location other than the defaults ones. Guessing this can be difficult and then the auto_detect functions might fail. Also, if multiple versions of APSIM are installed apsim will choose the newest one but it will issue a warning. Suppress the warning by setting warn.versions = FALSE.

Examples

```
## Not run:  
names(apsim.options)  
apsim_options(exe.path = "some-new-path-to-executable")  
apsim.options$exe.path  
  
## End(Not run)
```

apsim_version	<i>Display available APSIM 'Classic' and APSIM-X versions</i>
---------------	---

Description

Display available APSIM 'Classic' and APSIM-X versions

Usage

```
apsim_version(which = c("all", "inuse"), verbose = TRUE)
```

Arguments

which	either 'all' or 'inuse'
verbose	whether to print the information to standard output

Value

a data frame (all) or a vector (inuse) with APSIM-X and/or APSIM versions

Examples

```
## Not run:  
## Check which apsim version are available  
ava <- apsim_version(verbose = TRUE)  
  
## End(Not run)
```

auto_detect_apsimx_examples	<i>Auto detect where apsimx examples are located</i>
-----------------------------	--

Description

simple function to detect where APSIM-X examples are located

Usage

```
auto_detect_apsimx_examples()
```

Details

Auto detect where apsimx examples are located

Value

will create a directory pointing to APSIM-X distributed examples

Examples

```
## Not run:  
ex.dir <- auto_detect_apsimx_examples()  
  
## End(Not run)
```

auto_detect_apsim_examples

Auto detect where apsim examples are located

Description

simple function to detect where APSIM ‘Classic’ examples are located

Usage

```
auto_detect_apsim_examples()
```

Details

Auto detect where APSIM (7.x) ‘Classic’ examples are located

Value

will create a directory pointing to APSIM ‘Classic’ distributed examples

Examples

```
## Not run:  
ex.dir <- auto_detect_apsim_examples()  
  
## End(Not run)
```

check_apsim_met	<i>Check a met file for possible errors</i>
-----------------	---

Description

Takes in an object of class 'met' and checks for missing/valid/reasonable values

Usage

```
check_apsim_met(met)
```

Arguments

met	object of class 'met'
-----	-----------------------

Details

It will only check for missing values and reasonable (within range) values for: 'year': range (1500 to 3000);

'day': range (1 to 366);

'maxt': range (-60 to 60) – units (C);

'mint': range (-60 to 40) – units (C);

'radn': range (0 to 40) – units (MJ/m²/day);

'rain': range (0 to 100) – units (mm/day)

Value

does not return anything unless possible errors are found

compare_apsim	<i>Compare two or more apsim output objects</i>
---------------	---

Description

Function which allows for a simple comparison between APSIM output objects
plotting function for compare_apsim, it requires ggplot2

Usage

```
compare_apsim(..., variable, index = "Date", by, labels)
```

```
## S3 method for class 'out_mrg'
```

```
plot(
  x,
  ...,
```



```

plot.type = c("vs", "diff", "ts", "density"),
pairs = c(1, 2),
cummulative = FALSE,
variable,
id,
span = 0.75
)

```

Arguments

...	additional arguments, can be passed to certain ggplot2 functions
variable	variable to plot
index	index for merging objects. Default is 'Date'
by	factor for splitting the comparison, such as a treatment effect.
labels	labels for plotting and identification of objects.
x	object of class 'out_mrg'
plot.type	either 'vs', 'diff', 'ts' - for time series or 'density'
pairs	pair of objects to compare, defaults to 1 and 2 but others are possible
cummulative	whether to plot cummulative values (default FALSE)
id	identification (not implemented yet)
span	argument passed to 'geom_smooth'

Value

object of class 'out_mrg', which can be used for further plotting

Examples

```

## Directory with files
extd.dir <- system.file("extdata", package = "apsimx")
## Comparing observed and simulated for Wheat
data(obsWheat)
sim.opt <- read.csv(file.path(extd.dir, "wheat-sim-opt.csv"))
sim.opt$Date <- as.Date(sim.opt$Date)

cap <- compare_apsim(obsWheat, sim.opt, labels = c("obs", "sim"))

plot(cap)
plot(cap, plot.type = "diff")
plot(cap, plot.type = "ts")

plot(cap, variable = "AboveGround")
plot(cap, variable = "AboveGround", plot.type = "diff")
plot(cap, variable = "AboveGround", plot.type = "ts")

```

compare_apsim_met *Compare two or more metfiles*

Description

Helper function which allows for a simple comparison among help files
plotting function for compare_apsim_met, it requires ggplot2

Usage

```
compare_apsim_met(
  ...,
  met.var = c("all", "radn", "maxt", "mint", "rain", "rh", "wind_speed", "vp"),
  labels,
  check = FALSE
)

## S3 method for class 'met_mrg'
plot(
  x,
  ...,
  plot.type = c("vs", "diff", "ts", "density"),
  pairs = c(1, 2),
  cumulative = FALSE,
  met.var = c("radn", "maxt", "mint", "rain"),
  id,
  span = 0.75
)
```

Arguments

...	additional arguments, can be passed to certain ggplot2 functions
met.var	meteorological variable to plot
labels	labels for plotting and identification of 'met' objects.
check	whether to check met files using 'check_apsim_met'.
x	object of class 'met_mrg'
plot.type	either 'vs', 'diff', 'ts' - for time series or 'density'
pairs	pair of objects to compare, defaults to 1 and 2 but others are possible
cumulative	whether to plot cumulative values (default FALSE)
id	identification (not implemented yet)
span	argument to be passed to 'geom_smooth'

Value

object of class 'cmet', which can be used for further plotting

Note

I have only tested this for 2 or 3 objects. The code is set up to be able to compare more, but I'm not sure that would be all that useful.

Examples

```
## Not run:
require(nasapower)
## Specify the location
lonlat <- c(-93, 42)
## dates
dts <- c("2017-01-01", "2017-12-31")
## Get pwr
pwr <- get_power_apsim_met(lonlat = lonlat, dates = dts)
## Get data from IEM
iem <- get_iem_apsim_met(lonlat = lonlat, dates = dts)
## Compare them
cmet <- compare_apsim_met(pwr[,1:6], iem, labels = c("pwr", "iem"))
## Visualize radiation
plot(cmet, met.var = "radn")
plot(cmet, plot.type = "diff")
plot(cmet, plot.type = "ts")
## Visualize maxt
plot(cmet, met.var = "maxt")
plot(cmet, met.var = "maxt", plot.type = "diff")
plot(cmet, met.var = "maxt", plot.type = "ts")
## Cumulative rain
plot(cmet, met.var = "rain", plot.type = "ts", cumulative = TRUE)

## End(Not run)
```

doy2date

Converts from doy to date

Description

Given a day of the year as julian (1-366) it converts to 'Date'

Given a 'Date' it converts to julian day (1-366) or day of the year

Usage

```
doy2date(x, year = 2001, inverse = FALSE)
```

```
date2doy(x, year = 2001, inverse = FALSE)
```

Arguments

x	either an integer 1-366 or a 'Date'
year	year
inverse	if TRUE it goes from doyr to 'Date'

Examples

```
doy2date(120)
date2doy("04-30")
```

edit_apsim

Edit an APSIM (Classic) Simulation

Description

This function allows editing of an APSIM (Classic) simulation file.

Usage

```
edit_apsim(
  file,
  src.dir = ".",
  wrt.dir = NULL,
  node = c("Clock", "Weather", "Soil", "SurfaceOrganicMatter", "MicroClimate", "Crop",
    "Manager", "Other"),
  soil.child = c("Metadata", "Water", "OrganicMatter", "Chemical", "Analysis",
    "InitialWater", "Sample", "SWIM"),
  manager.child = NULL,
  parm = NULL,
  value = NULL,
  overwrite = FALSE,
  edit.tag = "-edited",
  parm.path = NULL,
  root,
  verbose = TRUE,
  check.length = TRUE
)
```

Arguments

file	file ending in .apsim to be edited
src.dir	directory containing the .apsim file to be edited; defaults to the current working directory
wrt.dir	should be used if the destination directory is different from the src.dir

node	either 'Clock', 'Weather', 'Soil', 'SurfaceOrganicMatter', 'MicroClimate', 'Crop', 'Manager' or 'Other'
soil.child	specific soil component to be edited
manager.child	specific manager component to be edited (not implemented yet)
parm	parameter to be edited
value	new values for the parameter to be edited
overwrite	logical; if TRUE the old file is overwritten, a new file is written otherwise
edit.tag	if the file is edited a different tag from the default '-edited' can be used.
parm.path	path to the attribute to edit when node is 'Other'
root	supply the node position in the case of multiple simulations such as factorials.
verbose	whether to print information about successful edit
check.length	check whether vectors are of the correct length

Details

The variables specified by parm within the .apsim file specified by file in the source directory src.dir are edited. The old values are replaced with value, which is a list that has the same number of elements as the length of the vector parm. The current .apsim file will be overwritten if overwrite is set to TRUE; otherwise the file 'file' -*edited.apsim* will be created. If (verbose = TRUE) then the name of the written file is returned. The function is similar to the edit_apsim functin in the 'apsimr' package, but with the difference that only some variables (parameters) can be modified.

The function inspect_apsim is for a quick look from within R. The APSIM GUI provides a more complete examination of the .apsim file

Value

(when verbose=TRUE) complete file path to edited .apsimx file is returned as a character string. As a side effect this function creates a new (XML) .apsimx file.

Note

The components that can be edited are restricted because this is better in preventing errors of editing unintended parts of the file. The disadvantage is that there is less flexibility compared to the similar function in the 'apsimr' package.

Examples

```
## This example will read one of the examples distributed with APSIM
## but write to a temporary directory

tmp.dir <- tempdir()

extd.dir <- system.file("extdata", package = "apsimx")
edit_apsim("Millet", src.dir = extd.dir, wrt.dir = tmp.dir,
           node = "Clock",
```

```
parm = "start_date", value = "01/02/1940")
```

edit_apsimx

Edit an APSIM-X (JSON) Simulation

Description

This function allows editing of an APSIM-X (JSON) simulation file.

Usage

```
edit_apsimx(
  file,
  src.dir = ".",
  wrt.dir = NULL,
  node = c("Clock", "Weather", "Soil", "SurfaceOrganicMatter", "MicroClimate", "Crop",
           "Manager", "Other"),
  soil.child = c("Metadata", "Water", "Organic", "Physical", "Analysis", "Chemical",
                 "InitialWater", "Sample"),
  manager.child = NULL,
  parm = NULL,
  value = NULL,
  overwrite = FALSE,
  edit.tag = "-edited",
  parm.path = NULL,
  root,
  verbose = TRUE
)
```

Arguments

file	file ending in .apsimx to be edited (JSON)
src.dir	directory containing the .apsimx file to be edited; defaults to the current working directory
wrt.dir	should be used if the destination directory is different from the src.dir
node	either 'Clock', 'Weather', 'Soil', 'SurfaceOrganicMatter', 'MicroClimate', 'Crop', 'Manager' or 'Other'
soil.child	specific soil component to be edited
manager.child	specific manager component to be edited
parm	parameter to be edited
value	new values for the parameter to be edited
overwrite	logical; if TRUE the old file is overwritten, a new file is written otherwise
edit.tag	if the file is edited a different tag from the default '-edited' can be used.

parm.path	path to the attribute to edit when node is 'Other'
root	supply the node position in the case of multiple simulations such as factorials.
verbose	whether to print information about successful edit

Details

The variables specified by `parm` within the `.apsimx` file specified by `file` in the source directory `src.dir` are edited. The old values are replaced with `value`, which is a list that has the same number of elements as the length of the vector `parm`. The current `.apsimx` file will be overwritten if `overwrite` is set to `TRUE`; otherwise the file `'file' -edited.apsimx` will be created. If (`verbose = TRUE`) then the name of the written file is returned. The function is similar to the `edit_apsim` function in the `'apsimr'` package, but with the difference that only some variables (parameters) can be modified.

The function `inspect_apsimx` is for a quick look from within R. The APSIM GUI provides a more complete examination of the `.apsimx` file

Value

(when `verbose=TRUE`) complete file path to edited `.apsimx` file is returned as a character string. As a side effect this function creates a new (JSON) `.apsimx` file.

Note

The components that can be edited are restricted because this is better in preventing errors of editing unintended parts of the file. The disadvantage is that there is less flexibility compared to the similar function in the `'apsimr'` package.

Examples

```
## Not run:
## This example will read one of the examples distributed with APSIM-X
## but write to a temporary directory
tmp.dir <- tempdir()

## Edit Bulk density
ex.dir <- auto_detect_apsimx_examples()
bds <- c(1.02, 1.03, 1.09, 1.16, 1.18, 1.19, 1.20)
edit_apsimx("Barley.apsimx", src.dir = ex.dir,
            wrt.dir = tmp.dir,
            node = "Soil",
            soil.child = "Water",
            parm = "BD", value = bds,
            verbose = FALSE)

## Inspect file
inspect_apsimx("Barley-edited.apsimx", src.dir = tmp.dir,
              node = "Soil", soil.child = "Water")

## To delete the file...
file.remove(paste0(tmp.dir, "/Barley-edited.apsimx"))

## Edit the fertilizer amount in 'Maize.apsimx'
```

```

edit_apsimx("Maize.apsimx", src.dir = ex.dir,
            wrt.dir = tmp.dir, node = "Manager",
            manager.child = "SowingFertiliser",
            parm = "Amount", value = 200, verbose = TRUE)

## Make sure it worked
inspect_apsimx("Maize-edited.apsimx", src.dir = tmp.dir, node = "Manager")

## Remove the file
file.remove(paste0(tmp.dir, "/Maize-edited.apsimx"))

## End(Not run)

```

edit_apsimx_batch

Edit an APSIM-X (JSON) Simulation in Batch mode

Description

This function allows editing of an APSIM-X (JSON) simulation file in batch mode.

Usage

```

edit_apsimx_batch(
  file,
  src.dir = ".",
  wrt.dir = NULL,
  parms = NULL,
  silent = FALSE,
  verbose = TRUE
)

```

Arguments

file	file ending in .apsimx to be edited (JSON)
src.dir	directory containing the .apsimx file to be edited; defaults to the current working directory
wrt.dir	should be used if the destination directory is different from the src.dir
parms	parameter to be edited in the for of 'key = value'
silent	controls the output of running APSIM at the command line
verbose	whether to print information about successful edit

Details

from hol430

This allows the user to specify an .apsimx file and a config file when running Models.exe. The .apsimx file will not be run but instead, the changes listed in the config file will be applied to the .apsimx file, which will then be written to disk under the same filename.

The config file should contain lines of the form 'path = value'

e.g.

```
[Clock].StartDate = 2019-1-20 .Simulations.Sim1.Name = SimulationVariant35 .Simulations.Sim2.Enabled
= false .Simulations.Sim1.Paddock.Soil.Thickness[1] = 50 Notes:
```

Command line arguments should look like: Models.exe file.apsimx /Edit /path/to/config/file.conf

Relative paths will be resolved to the first match. ie [Clock].StartDate will match the first clock found in the file.

Dates can be specified as yyyy-mm-dd or mm/dd/yyyy.

Strings should not be quoted

Array indices will be interpreted as 1-indexed (mad face). So the first element in the array should have index 1 in the config file.

The file will be upgraded to the latest file version as part of this process.

Value

(when verbose=TRUE) complete file path to edited .apsimx file is returned as a character string. As a side effect this function creates a new (JSON) .apsimx file.

Examples

```
## Not run:
## This example will read one of the examples distributed with APSIM-X
## but write to a temporary directory

tmp.dir <- tempdir()

## Edit InitialResidueMass
extd.dir <- system.file("extdata", package = "apsimx")
parms <- list(`.Simulations.Simulation.Field.SurfaceOrganicMatter.InitialResidueMass` = 600)
edit_apsimx_batch("Wheat.apsimx", src.dir = extd.dir, wrt.dir = tmp.dir, parms = parms)

## End(Not run)
```

 edit_apsimx_replacement

Edit a replacement component in an .apsimx (JSON) file

Description

edit the replacement componenet of an JSON apsimx file. It does not replace the GUI, but it can save time by quickly editing parameters and values.

Usage

```
edit_apsimx_replacement(
  file = "",
  src.dir = ".",
  wrt.dir = ".",
  node = NULL,
  node.child = NULL,
  node.subchild = NULL,
  node.subsubchild = NULL,
  node.sub3child = NULL,
  node.string = NULL,
  root = list("Models.Core.Replacements", NA),
  parm = NULL,
  value = NULL,
  overwrite = FALSE,
  edit.tag = "-edited",
  verbose = TRUE
)
```

Arguments

file	file ending in .apsimx to edit (JSON)
src.dir	directory containing the .apsimx file; defaults to the current working directory
wrt.dir	should be used if the destination directory is different from the src.dir
node	specific node to edit
node.child	specific node child component to edit.
node.subchild	specific node sub-child to edit.
node.subsubchild	specific node sub-subchild to edit.
node.sub3child	specific node sub-sub-subchild to be inspected.
node.string	passing of a string instead of the node hierarchy.
root	'root' node to explore (default = "Models.Core.Replacements")
parm	specific parameter to edit
value	new values for the parameter

overwrite	logical; if TRUE the old file is overwritten, a new file is written otherwise
edit.tag	if the file is edited a different tag from the default '-edited' can be used.
verbose	whether to print information about successful edit

Details

This is simply a script that prints the relevant parameters which are likely to need editing. It does not print all information from an .apsimx file.

Value

(when verbose=TRUE) complete file path to edited .apsimx file is returned as a character string. As a side effect this function creates a new (JSON) .apsimx file.

Note

The components that can be edited are restricted because this is better in preventing errors of editing unintended parts of the file.

Examples

```
extd.dir <- system.file("extdata", package = "apsimx")
## Writing to a temp directory, but change as needed
tmp.dir <- tempdir()

edit_apsimx_replacement("MaizeSoybean.apsimx",
                        src.dir = extd.dir, wrt.dir = tmp.dir,
                        node = "Maize", node.child = "Phenology",
                        node.subchild = "ThermalTime", parm = "X",
                        value = c(1,2,3,4,5))
```

```
edit_apsimx_replace_soil_profile
```

Edit APSIM-X file with a replaced soil profile

Description

Edits an APSIM-X simulation by replacing the soil profile

Usage

```
edit_apsimx_replace_soil_profile(
  file = "",
  src.dir = ".",
  wrt.dir = NULL,
  soil.profile = NULL,
  edit.tag = "-edited",
  overwrite = FALSE,
  verbose = TRUE
)
```

Arguments

file	name of the .apsimx file to be edited
src.dir	source directory
wrt.dir	writing directory
soil.profile	a soil profile object with class 'soil_profile'
edit.tag	default edit tag '-edited'
overwrite	default FALSE
verbose	default TRUE and it will print messages to console

Details

This function is designed to batch replace the whole soil in an APSIM simulation file.

Value

writes a file to disk with the supplied soil profile

Note

There is no such thing as a default soil, carefully build the profile for each simulation.

Examples

```
sp <- apsimx_soil_profile()
extd.dir <- system.file("extdata", package = "apsimx")

## I write to a temp directory but replace as needed
tmp.dir <- tempdir()

edit_apsimx_replace_soil_profile("Maize.apsimx", soil.profile = sp,
                                src.dir = extd.dir, wrt.dir = tmp.dir)
inspect_apsimx("Maize-edited.apsimx", src.dir = tmp.dir,
              node = "Soil")
```

`edit_apsim_replace_soil_profile`*Edit APSIM 'Classic' file with a replaced soil profile*

Description

Edits an APSIM Classic simulation by replacing the soil profile

Usage

```
edit_apsim_replace_soil_profile(  
  file = "",  
  src.dir = ".",  
  wrt.dir = NULL,  
  soil.profile = NULL,  
  swim = NULL,  
  soilwat = NULL,  
  edit.tag = "-edited",  
  overwrite = FALSE,  
  verbose = TRUE  
)
```

Arguments

<code>file</code>	name of the .apsim file to be edited
<code>src.dir</code>	source directory
<code>wrt.dir</code>	writing directory
<code>soil.profile</code>	a soil profile object with class 'soil_profile'
<code>swim</code>	list with SWIM specific parameters
<code>soilwat</code>	list with SoilWat specific parameters
<code>edit.tag</code>	default edit tag '-edited'
<code>overwrite</code>	default FALSE
<code>verbose</code>	default TRUE. Will print messages indicating what was done.

Details

This function is designed to batch replace the whole soil in an APSIM simulation.

Value

writes a file to disk with the supplied soil profile

Note

There is no such thing as a default soil, carefully build the profile for each simulation. This function replaces values and it can grow an XML node, but it cannot edit a property which is not present in the original file.

Examples

```
sp <- apsimx_soil_profile(nlayers = 20,
                        crops = c("Barley", "Chickpea", "Lucerne",
                                "Maize", "Perennial Grass", "Sorghum",
                                "Wheat", "Millet"))

extd.dir <- system.file("extdata", package = "apsimx")

## Writing to a temp directory
tmp.dir <- tempdir()
edit_apsim_replace_soil_profile("Millet.apsim", soil.profile = sp,
                              edit.tag = "-newsoil",
                              src.dir = extd.dir,
                              wrt.dir = tmp.dir)

inspect_apsim("Millet-newsoil.apsim", src.dir = tmp.dir,
             node = "Soil", soil.child = "Water")
```

`edit_apsim_xml`*Edit an APSIM (Classic) Simulation auxiliary xml file*

Description

This function allows editing of an APSIM (Classic) simulation xml file.

Usage

```
edit_apsim_xml(
  file,
  src.dir = ".",
  wrt.dir = NULL,
  parm.path = NULL,
  value = NULL,
  overwrite = FALSE,
  edit.tag = "-edited",
  verbose = TRUE
)
```

Arguments

file	file ending in .xml to be edited
src.dir	directory containing the .xml file to be edited; defaults to the current working directory
wrt.dir	should be used if the destination directory is different from the src.dir
parm.path	parameter path to be edited (see example)
value	new values for the parameter to be edited
overwrite	logical; if TRUE the old file is overwritten, a new file is written otherwise
edit.tag	if the file is edited a different tag from the default '-edited' can be used.
verbose	whether to print information about successful edit

Details

The variables specified by parm within the .apsim file specified by file in the source directory src.dir are edited. The old values are replaced with value, which is a list that has the same number of elements as the length of the vector parm. The current .xml file will be overwritten if overwrite is set to TRUE; otherwise the file 'file' *-edited.xml* will be created. If (verbose = TRUE) then the name of the written file is returned. The function is similar to the edit_sim_file function in the 'apsimr' package, but with the difference that here the xml2 package is used instead.

Value

(when verbose=TRUE) complete file path to edited .xml file is returned as a character string. As a side effect this function creates a new XML file.

Note

This function cannot check whether replacement is of the correct length. Also, there is an inspect equivalent. It is more flexible than 'edit_apsim' and (perhaps) similar to 'apsimr::edit_sim_file'.

Examples

```
## This example changes the RUE values

extd.dir <- system.file("extdata", package = "apsimx")

values <- paste(rep(1.7, 12), collapse = " ")

## Writing to a temp directory, but replace as needed
tmp.dir <- tempdir()

edit_apsim_xml("Maize75.xml",
              src.dir = extd.dir,
              wrt.dir = tmp.dir,
              parm.path = "../Model/rue",
              value = values)
```

extract_values_apsimx *Extract values from a parameter path*

Description

Extract initial values from a parameter path

Usage

```
extract_values_apsimx(file, src.dir, parm.path)
```

Arguments

file	file name to be run (the extension .apsimx is optional)
src.dir	directory containing the .apsimx file to be run (defaults to the current directory)
parm.path	parameter path either use inspect_apsimx or see example below

Examples

```
## Find examples
ex.dir <- auto_detect_apsimx_examples()
## Extract parameter path
pp <- inspect_apsimx("Barley.apsimx", src.dir = ex.dir,
                    node = "Manager", parm = list("Fert", 1))
ppa <- paste0(pp, ".Amount")
## Extract value
extract_values_apsimx("Barley.apsimx", src.dir = ex.dir, parm.path = ppa)
```

get_daymet_apsim_met *Get DAYMET data for an APSIM met file*

Description

Uses [get_daymet](#) from the **FedData** package to download data to create an APSIM met file.

Usage

```
get_daymet_apsim_met(
  lonlat,
  years,
  wrt.dir = ".",
  filename = NULL,
  width.height = c(0.001, 0.001),
  template,
```



```

    label = NULL,
    elements = NULL,
    raw.dir = "./RAW/DAYMET",
    extraction.dir = paste0("./EXTRACTIONS/", label, "/DAYMET"),
    force.redo = FALSE,
    cleanup = FALSE
  )

```

Arguments

lonlat	Longitude and latitude vector
years	a numeric vector of years to extract
wrt.dir	write directory
filename	file name for writing out to disk
width.height	width and height of the cropped area (default 0.001, 0.001)
template	A Raster or Spatial object to serve as a template for cropping (see get_daymet).
label	a character string naming the area (see get_daymet)
elements	see get_daymet
raw.dir	see get_daymet
extraction.dir	see get_daymet
force.redo	see get_daymet
cleanup	whether to delete download directories (default is FALSE). If the intention is for cleanup to delete all the files, 'raw.dir' and 'extraction.dir' should be supplied, supplying a single name, such as 'RAW' and 'EXTRACTION'.

Details

This function requires the **FedData** package.

If the filename is not provided it will not write the file to disk, but it will return an object of class 'met'. This is useful in case manipulation is required before writing to disk. The variable 'srad' as downloaded from daymet is average solar radiation, so it is converted to total. Daily total radiation (MJ/m²/day) can be calculated as follows: $((\text{srad (W/m}^2) * \text{dayl (s/day)}) / 1,000,000)$
 Vapor Pressure Deficit (vp) should be in hecto Pascals

Source

The data is retrieved using the **FedData** package. For the original source see: <https://daymet.ornl.gov/>

Examples

```

## Not run:
require(FedData)
## I write to a temp directory but replace as needed
tmp.dir <- tempdir()
dmet12 <- get_daymet_apsim_met(lonlat = c(-93,42),
                              raw.dir = paste0(tmp.dir, "/RAW/DAYMET"),

```

```

                                extraction.dir = paste0(tmp.dir, "/EXTRACTIONS/CIA/DAYMET"),
                                years = 2012, label = "CIA")
summary(dmet12)
## Check for reasonable ranges
check_apsim_met(dmet12)

## End(Not run)

```

```
get_gsod_apsim_met    Get GSOD data for an APSIM met file
```

Description

Uses `get_GSOD` from the **GSODR** package to download data to create an APSIM met file.

Usage

```

get_gsod_apsim_met(
  lonlat,
  dates,
  wrt.dir = ".",
  filename = NULL,
  distance = 100,
  fillin.radn = FALSE
)

```

Arguments

lonlat	Longitude and latitude vector
dates	date ranges
wrt.dir	write directory
filename	file name for writing out to disk
distance	distance in kilometers for the nearest station
fillin.radn	whether to fill in radiation data using the nasapower package. Default is FALSE.

Details

This function requires the **GSODR** package.

If the filename is not provided it will not write the file to disk, but it will return an object of class 'met'. This is useful in case manipulation is required before writing to disk.

Note

This source of data does not provide solar radiation. If 'fillin.radn' is TRUE it fill in radiation data using the nasapower package.

Examples

```
## Not run:
require(GSODR)
## This will not write a file to disk
gsd <- get_gsod_apsim_met(lonlat = c(-93,42), dates = c("2012-01-01", "2012-12-31"))
summary(gsd)
## Check for reasonable ranges
## Radiation is not included by default
check_apsim_met(gsd)

## End(Not run)
```

```
get_iemre_apsim_met     Get weather data from Iowa Environmental Mesonet Reanalysis
```

Description

Retrieves weather data from Iowa Environmental Mesonet Reanalysis into an APSIM met file

Usage

```
get_iemre_apsim_met(lonlat, dates, wrt.dir = ".", filename = NULL)
```

Arguments

lonlat	Longitude and latitude vector
dates	date ranges
wrt.dir	write directory
filename	file name for writing out to disk

Details

The original data can be obtained from: <https://mesonet.agron.iastate.edu/iemre/>

If the filename is not provided it will not write the file to disk, but it will return an object of class 'met'. This is useful in case manipulation is required before writing to disk.

Examples

```
## Not run:
## This will not write a file to disk
iemre <- get_iemre_apsim_met(lonlat = c(-93,42), dates = c("2012-01-01", "2012-12-31"))
## Note that solar radiation is not available
summary(iemre)

## End(Not run)
```

get_iem_apsim_met *Get weather data from Iowa Environmental Ag Weather Stations*

Description

Retrieves weather data from Iowa Environmental Mesonet (AgWeather) into an APSIM met file

Usage

```
get_iem_apsim_met(lonlat, dates, wrt.dir = ".", state, station, filename)
```

Arguments

lonlat	Longitude and latitude vector (optional)
dates	date ranges
wrt.dir	write directory
state	state which you choose climate data from
station	station which you choose climate data from
filename	file name for writing out to disk

Details

The original data can be obtained from: <https://mesonet.agron.iastate.edu/request/coop/fe.phtml>

If the filename is not provided it will not write the file to disk, but it will return an object of class 'met'. This is useful in case manipulation is required before writing to disk. For this function either provide the longitude and latitude or the state and station, but not both. In fact, 'state' and 'station' will be ignored if 'lonlat' is supplied.

Examples

```
## Not run:
## This will not write a file to disk
iem.met <- get_iem_apsim_met(state = "IA",
                           station = "IA5198",
                           dates = c("2012-01-01", "2012-12-31"))

summary(iem.met)

## Alternatively, coordinates can be used
## This should be equivalent to the previous request
iem.met2 <- get_iem_apsim_met(lonlat = c(-93, 42),
                             dates = c("2012-01-01", "2012-12-31"))

summary(iem.met2)

## End(Not run)
```

get_power_apsim_met *Get NASA-POWER data for an APSIM met file*

Description

Uses `get_power` from the **nasapower** package to download data to create an APSIM met file.

Usage

```
get_power_apsim_met(lonlat, dates, wrt.dir = ".", filename = NULL)
```

Arguments

lonlat	Longitude and latitude vector
dates	date ranges
wrt.dir	write directory
filename	file name for writing out to disk

Details

This function requires the **nasapower** package.

If the filename is not provided it will not write the file to disk, but it will return an object of class 'met'. This is useful in case manipulation is required before writing to disk.

Examples

```
## Not run:
require(nasapower)
## This will not write a file to disk
pwr <- get_power_apsim_met(lonlat = c(-93,42), dates = c("2012-01-01","2012-12-31"))
## Note that missing data is coded as -99
summary(pwr)
## Check for reasonable ranges
check_apsim_met(pwr)
## replace -99 with NA
pwr$radn <- ifelse(pwr$radn == -99, NA, pwr$radn)
## Impute using linear interpolation
pwr.imptd <- impute_apsim_met(pwr, verbose = TRUE)
summary(pwr.imptd)

## End(Not run)
```

impute_apsim_met	<i>Perform imputation for missing data in a met file</i>
------------------	--

Description

Takes in an object of class 'met' and imputes values

Usage

```
impute_apsim_met(
  met,
  method = c("approx", "spline", "mean"),
  verbose = FALSE,
  ...
)
```

Arguments

met	object of class 'met'
method	method for imputation, 'approx' (approxfun), 'spline' (splinefun) or 'mean' (mean).
verbose	whether to print missing data to the console, default = FALSE
...	additional arguments to be passed to imputation method

Value

an object of class 'met' with attributes

inspect_apsim	<i>Inspect an .apsim (XML) file</i>
---------------	-------------------------------------

Description

inspect an XML apsim file. It does not replace the GUI, but it can save time by quickly checking parameters and values.

Usage

```
inspect_apsim(
  file = "",
  src.dir = ".",
  node = c("Clock", "Weather", "Soil", "SurfaceOrganicMatter", "Crop", "Manager",
    "Other"),
  soil.child = c("Metadata", "Water", "OrganicMatter", "Nitrogen", "Analysis",
    "InitialWater", "Sample", "SWIM"),
```

```

    parm = NULL,
    digits = 3,
    print.path = FALSE,
    root
  )

```

Arguments

file	file ending in .apsim (Classic) to be inspected (XML)
src.dir	directory containing the .apsim file to be inspected; defaults to the current working directory
node	either 'Weather', 'Soil', 'SurfaceOrganicMatter', 'MicroClimate', 'Crop', 'Manager' or 'Other'
soil.child	specific soil component to be inspected
parm	parameter to inspect when node = 'Crop', 'Manager' or 'Other'
digits	number of decimals to print (default 3)
print.path	whether to print the parameter path (default = FALSE)
root	root node label. In simulation structures such as factorials there will be multiple possible nodes. This can be specified by supplying an appropriate character.

Details

This is simply a script that prints the relevant parameters which are likely to need editing. It does not print all information from an .apsim file. For 'Crop', 'Manager' and 'Other', 'parm' should be indicated with a first element to look for and a second with the relative position in case there are multiple results.

Value

table with inspected parameters and values

Note

When multiple folders are present as it is the case when there are factorials. Inspect will find the instance in the first folder unless 'root' is supplied. By providing the name of the folder to root (or a regular expression), the appropriate node can be selected. In this case the printed path will be absolute instead of relative.

Examples

```

extd.dir <- system.file("extdata", package = "apsimx")
## Testing using 'Millet'
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Clock")
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Weather")
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil", soil.child = "Metadata")
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil", soil.child = "OrganicMatter")
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil", soil.child = "Analysis")

```

```

inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil", soil.child = "InitialWater")
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil", soil.child = "Sample")
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "SurfaceOrganicMatter")
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Crop", parm = list("sow",NA))
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Crop", parm = list("sow",7))

## when soil.child = "Water" there are potentially many crops to chose from
## This selects LL, KL and XF for Barley
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "Water", parm = "Barley")
## This selects LL for all the crops
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "Water", parm = "LL")
## To print the parm.path the selection needs to be unique
## but still there will be multiple soil layers
## 'parm' can be a list or a character vector of length equal to two
inspect_apsim("Millet.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "Water", parm = list("Barley", "LL"),
             print.path = TRUE)

## Testing with maize-soybean-rotation.apsim
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Clock")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Weather")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "Metadata")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "OrganicMatter")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "Analysis")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "InitialWater")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Soil",
             soil.child = "Sample")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir,
             node = "SurfaceOrganicMatter")
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir, node = "Crop")
## This has many options and a complex structure
## It is possible to select unique managements, but not non-unique ones
## The first element in parm can be a regular expression
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir,
             node = "Manager", parm = list("rotat",NA))
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir,
             node = "Manager",
             parm = list("sow on a fixed date - maize",NA))
## Select an individual row by position
inspect_apsim("maize-soybean-rotation.apsim", src.dir = extd.dir,
             node = "Manager",
             parm = list("sow on a fixed date - maize",7))

## Illustrating the 'print.path' feature.
inspect_apsim("Millet.apsim", src.dir = extd.dir,
             node = "Soil", soil.child = "Water",
             parm = "DUL", print.path = TRUE)

```



```

## But the path can also be returned as a string
## Which is useful for later editing
pp <- inspect_apsim("Millet.apsim", src.dir = extd.dir,
                   node = "Soil", soil.child = "Water",
                   parm = "DUL", print.path = TRUE)

## Inspecting a factorial
## (or simply a simulation with multiple folders)
## No cover
inspect_apsim("maize-factorial.apsim", src.dir = extd.dir,
             root = "IA-CC_Canisteo_No-Cover")

## Cover
inspect_apsim("maize-factorial.apsim", src.dir = extd.dir,
             root = "IA-CC_Canisteo_Cover")

```

inspect_apsimx	<i>Inspect an .apsimx (JSON) file</i>
----------------	---------------------------------------

Description

inspect a JSON apsimx file. It does not replace the GUI, but it can save time by quickly checking parameters and values.

Usage

```

inspect_apsimx(
  file = "",
  src.dir = ".",
  node = c("Clock", "Weather", "Soil", "SurfaceOrganicMatter", "MicroClimate", "Crop",
           "Manager", "Other"),
  soil.child = c("Metadata", "Water", "InitialWater", "Chemical", "Physical",
                 "Analysis", "SoilWater", "InitialN", "CERESSoilTemperature", "Sample", "Nutrient",
                 "Organic"),
  parm = NULL,
  digits = 3,
  print.path = FALSE,
  root
)

```

Arguments

file	file ending in .apsimx to be inspected (JSON)
src.dir	directory containing the .apsimx file to be inspected; defaults to the current working directory

node	specific node to be inspected either 'Clock', 'Weather', 'Soil', 'SurfaceOrganicMatter', 'MicroClimate', 'Crop', 'Manager' or 'Other'
soil.child	specific soil component to be inspected. The options vary depending on what is available (see details)
parm	parameter to refine the inspection of the 'manager' list('parm', 'position'), use 'NA' for all the positions. 'parm' can be a regular expression for partial matching.
digits	number of decimals to print (default 3). Not used now because everything is a character.
print.path	whether to print the path to the specific parameter. Useful to give the later editing. (Also returned as 'invisible')
root	root node label. In simulation structures such as factorials there will be multiple possible nodes. This can be specified by supplying an appropriate character.

Details

This is simply a script that prints the relevant parameters which are likely to need editing. It does not print all information from an .apsimx file. To investigate the available 'soil.childs' specify 'Soil' for 'node' and do not specify the 'soil.child'.

Value

prints a table with inspected parameters and values (and 'parm path' when 'print.path' = TRUE).

Examples

```
## Not run:
ex.dir <- auto_detect_apsimx_examples()
inspect_apsimx("Barley", src.dir = ex.dir, node = "Clock")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Weather")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Soil", soil.child = "Metadata")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Soil", soil.child = "Water")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Soil", soil.child = "SoilWater")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Soil", soil.child = "Organic")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Soil", soil.child = "Chemical")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Soil", soil.child = "InitialWater")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Soil", soil.child = "InitialN")
inspect_apsimx("Barley", src.dir = ex.dir, node = "SurfaceOrganicMatter")
inspect_apsimx("Barley", src.dir = ex.dir, node = "MicroClimate")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Crop")
inspect_apsimx("Barley", src.dir = ex.dir, node = "Manager")

## Manager folder present
extd.dir <- system.file("extdata", package = "apsimx")
inspect_apsimx("maize-manager-folder.apsimx", node = "Other", src.dir = extd.dir,
  parm = list("Manager", "Fertiliser", "Amount"))

## End(Not run)
```

`inspect_apsimx_replacement`*Inspect a replacement component in an .apsimx (JSON) file*

Description

inspect the replacement component of an JSON apsimx file. It does not replace the GUI, but it can save time by quickly checking parameters and values.

Usage

```
inspect_apsimx_replacement(  
    file = "",  
    src.dir = ".",  
    node = NULL,  
    node.child = NULL,  
    node.subchild = NULL,  
    node.subsubchild = NULL,  
    node.sub3child = NULL,  
    node.sub4child = NULL,  
    node.string = NULL,  
    root = list("Models.Core.Replacements", NA),  
    parm = NULL,  
    display.available = FALSE,  
    digits = 3,  
    print.path = FALSE,  
    verbose = TRUE  
)
```

Arguments

<code>file</code>	file ending in .apsimx to be inspected (JSON)
<code>src.dir</code>	directory containing the .apsimx file to be inspected; defaults to the current working directory
<code>node</code>	specific node to be inspected
<code>node.child</code>	specific node child component to be inspected.
<code>node.subchild</code>	specific node sub-child to be inspected.
<code>node.subsubchild</code>	specific node sub-subchild to be inspected.
<code>node.sub3child</code>	specific node sub3child to be inspected.
<code>node.sub4child</code>	specific node sub4child to be inspected.
<code>node.string</code>	passing of a string instead of the node hierarchy. Do not use this and also the other node arguments. This argument will overwrite the other node specifications.

root	'root' for the inspection of a replacement file (it gives flexibility to inspect other types of files).
parm	specific parameter to display
display.available	logical. Whether to display available components to be inspected (default = FALSE)
digits	number of decimals to print (default 3)
print.path	print the path to the inspected parameter (default FALSE)
verbose	whether to print additional information, default: TRUE

Details

This is simply a script that prints the relevant parameters which are likely to need editing. It does not print all information from an .apsimx file.

Value

table with inspected parameters and values

Note

I need to make some changes in order to be able to handle multiple parameters. At this point, it might work but it will generate warnings.

Examples

```

extd.dir <- system.file("extdata", package = "apsimx")
inspect_apsimx_replacement("MaizeSoybean.apsimx", src.dir = extd.dir,
                           node = "Maize", node.child = "Phenology",
                           node.subchild = "ThermalTime",
                           node.subsubchild = "BaseThermalTime",
                           node.sub3child = "Response")

## For Wheat
## In this case, I can't dig deep enough
## Would need to add an argument 'node.sub4child'
inspect_apsimx_replacement("WheatRye.apsimx",
                           src.dir = extd.dir,
                           node = "Wheat",
                           node.child = "Structure",
                           node.subchild = "BranchingRate",
                           node.subsubchild = "PotentialBranchingRate",
                           node.sub3child = "Vegetative")

## Not run:
## This function can also be used to inspect more complex APSIM-X files
## For example the 'Factorial' example
ex.dir <- auto_detect_apsimx_examples()
inspect_apsimx_replacement("Factorial", src.dir = ex.dir,
                           root = list("Experiment", 1), node = "Base", node.child = "Weather")

```

```
## End(Not run)
```

inspect_apsim_xml *Inspect an APSIM Classic auxiliary (XML) file*

Description

inspect an auxiliary XML apsim file.

Usage

```
inspect_apsim_xml(  
  file = "",  
  src.dir = ".",  
  parm,  
  verbose = TRUE,  
  print.path = TRUE  
)
```

Arguments

file	file ending in .xml to be inspected.
src.dir	directory containing the .xml file to be inspected; defaults to the current working directory
parm	parameter to inspect.
verbose	Whether to print to standard output
print.path	Whether to print the parameter path

Value

absolute parameter path

Examples

```
extd.dir <- system.file("extdata", package = "apsimx")  
  
inspect_apsim_xml("Maize75.xml", src.dir = extd.dir,  
  parm = "leaf_no_rate_change")  
  
pp <- inspect_apsim_xml("Maize75.xml", src.dir = extd.dir,  
  parm = "leaf_no_rate_change",  
  verbose = FALSE,  
  print.path = FALSE)
```

mcmc.apsim.env *Environment to store data for apsim MCMC*

Description

Environment which stores data for MCMC

Usage

mcmc.apsim.env

Format

An object of class environment of length 0.

Details

Create an apsim environment for MCMC

mcmc.apsimx.env *Environment to store data for apsimx MCMC*

Description

Environment which stores data for MCMC

Usage

mcmc.apsimx.env

Format

An object of class environment of length 0.

Details

Create an apsimx environment for MCMC

napad_apsim_met	<i>Pad a met file with NAs when there are date discontinuities</i>
-----------------	--

Description

It will fill in or 'pad' a met object with NAs

Usage

```
napad_apsim_met(met)
```

Arguments

met object of class 'met'

Details

Fill in with missing data date discontinuities in a met file

Note

The purpose of this function is to allow for imputation using [impute_apsim_met](#)

obsWheat	<i>Observed wheat phenology, LAI and biomass</i>
----------	--

Description

Artificial observed data for Wheat

Usage

```
obsWheat
```

Format

A data frame with 10 rows and 4 variables:

Date -date- date starting Oct 1 2016 and ending June 6 2017

Wheat.Phenology.Stage -numeric- phenology stage of wheat

Wheat.Leaf.LAI -numeric- Leaf Area Index

Wheat.AboveGround.Wt -numeric- above ground biomass (g/m2)

Details

A dataset containing the Date, phenology stage, LAI and above ground biomass for Wheat

Source

These are simulated data. For details see the APSIM documentation

optim_apsim	<i>Optimize parameters in an APSIM simulation</i>
-------------	---

Description

It is a wrapper for running APSIM and optimizing parameters using [optim](#)

Friendly printing of optim_apsim

Variance-Covariance for an 'optim_apsim' object

Parameter estimates for an 'optim_apsim' object

Usage

```
optim_apsim(
  file,
  src.dir = ".",
  crop.file,
  parm.paths,
  data,
  type = c("optim", "nloptr", "mcmc"),
  weights,
  index = "Date",
  parm.vector.index,
  ...
)

## S3 method for class 'optim_apsim'
print(x, ..., digits = 3, level = 0.95)

## S3 method for class 'optim_apsim'
vcov(object, ..., scaled = TRUE)

## S3 method for class 'optim_apsim'
coef(object, ..., scaled = FALSE)
```

Arguments

file	file name to be run (the extension .apsim is optional)
src.dir	directory containing the .apsim file to be run (defaults to the current directory)
crop.file	name of auxiliary xml file where parameters are stored. If this is missing, it is assumed that the parameters to be edited are in the main simulation file.
parm.paths	absolute paths of the coefficients to be optimized. It is recommended that you use inspect_apsim or inspect_apsim_xml for this.

data	data frame with the observed data. By default is assumes there is a 'Date' column for the index.
type	Type of optimization. For now, <code>optim</code> and, if available, <code>nloptr</code> or 'mcmc' through <code>runMCMC</code> .
weights	Weighting method or values for computing the residual sum of squares (see Note).
index	Index for filtering APSIM output. 'Date' is currently used. (I have not tested how well it works using anything other than Date).
parm.vector.index	Index to optimize a specific element of a parameter vector. At the moment it is possible to only edit one element at a time. This is because there is a conflict when generating multiple elements in the candidate vector for the same parameter.
...	additional arguments (none used at the moment)
x	object of class 'optim_apsim'
digits	number of digits to round up the output
level	confidence level (default 0.95)
object	object of class 'optim_apsim'
scaled	whether to return the scaled or unscaled estimates (TRUE in the optimized scale, FALSE in the original scale)

Details

Simple optimization for APSIM Classic

* This function assumes that you want to optimize parameters which are stored in an auxiliary XML file. These are typically crop or cultivar specific parameters. However, it is possible to optimize parameters present in the main simulation file.

* Only one observation per day is allowed in the data.

* Given how APSIM Classic works, this can only be run when the main simulation file is in the current directory and the crop file (or XML) should be in the same directory as the main simulation.

* The initial values for the optimization should be the ones in the stored crop parameter file.

* It is suggested that you keep a backup of the original file. This function will edit and overwrite the file during the optimization.

* When you use the `parm.vector.index` you cannot edit two separate elements of a vector at the same time. This should be used to target a single element of a vector only.

Value

object of class 'optim_apsim', but really just a list with results from `optim` and additional information.

Note

When computing the objective function (residual sum-of-squares) different variables are combined. It is common to weight them since they are in different units. If the argument weights is not supplied no weighting is applied. It can be 'mean', 'var' or a numeric vector of appropriate length.

This in the scale of the optimized parameters which are scaled to be around 1.

 optim_apsimx

Optimize parameters in an APSIM Next Generation simulation

Description

It is a wrapper for running APSIM-X and optimizing parameters using [optim](#)

Usage

```
optim_apsimx(
  file,
  src.dir = ".",
  parm.paths,
  data,
  type = c("optim", "nloptr", "mcmc"),
  weights,
  index = "Date",
  parm.vector.index,
  replacement,
  root,
  initial.values,
  ...
)
```

Arguments

file	file name to be run (the extension .apsimx is optional)
src.dir	directory containing the .apsimx file to be run (defaults to the current directory)
parm.paths	absolute paths of the coefficients to be optimized. It is recommended that you use inspect_apsimx for this
data	data frame with the observed data. By default is assumes there is a 'Date' column for the index.
type	Type of optimization. For now, optim and, if available, nloptr or 'mcmc' through runMCMC .
weights	Weighting method or values for computing the residual sum of squares.
index	Index for filtering APSIM output

`parm.vector.index` Index to optimize a specific element of a parameter vector. At the moment it is possible to only edit one element at a time. This is because there is a conflict when generating multiple elements in the candidate vector for the same parameter.

`replacement` TRUE or FALSE for each parameter. Indicating whether it is part of the 'replacement' component. Its length should be equal to the length of 'parm.paths'.

`root` root argument for [edit_apsimx_replacement](#)

`initial.values` (required) supply the initial values of the parameters. (Working on fixing this...)

`...` additional arguments to be passed to the optimization algorithm. See [optim](#)

Details

Simple optimization for APSIM Next Generation

* At the moment it is required to provide starting values for the parameters of interest.

* It is suggested that you keep a backup of the original file. This function will edit and overwrite the file during the optimization.

* When you use the `parm.vector.index` you cannot edit two separate elements of a vector at the same time. This should be used to target a single element of a vector only. (I can add this feature in the future if it is justified.)

Value

vector of optimized coefficients

Note

When computing the objective function (residual sum-of-squares) different variables are combined. It is common to weight them since they are in different units. If the argument `weights` is not supplied no weighting is applied. It can be 'mean', 'variance' or a numeric vector of appropriate length.

print.met

Printer-friendly version of a metfile

Description

Print a met file in a friendly way

Usage

```
## S3 method for class 'met'
print(x, ...)
```

Arguments

`x` an R object of class 'met'

`...` additional printing arguments

read_apsim	<i>Read APSIM generated .out files</i>
------------	--

Description

read 'output' databases created by APSIM runs (.out and .sim). One file at a time.

Usage

```
read_apsim(
  file = "",
  src.dir = ".",
  value = c("report", "all"),
  date.format = "%d/%m/%Y"
)
```

Arguments

file	file name
src.dir	source directory where file is located
value	either 'report' (data.frame) or 'all' (list)
date.format	format for adding 'Date' column

Details

Read APSIM generated .out files

Examples

```
## Not run:
extd.dir <- system.file("extdata", package = "apsimx")
maize.out <- read_apsim("Maize", src.dir = extd.dir, value = "report")
millet.out <- read_apsim("Millet", src.dir = extd.dir, value = "report")

## End(Not run)
```

read_apsimx	<i>Read APSIM-X generated .db files</i>
-------------	---

Description

read SQLite databases created by APSIM-X runs. One file at a time.

Usage

```
read_apsimx(file = "", src.dir = ".", value = c("report", "all"))
```

Arguments

file	file name
src.dir	source directory where file is located
value	either 'report' (data.frame) or 'all' (list)

Details

Read APSIM-X generated .db files

read_apsimx_all	<i>Read all APSIM-X generated .db files in a directory</i>
-----------------	--

Description

Like [read_apsimx](#), but it reads all .db files in a directory.

Usage

```
read_apsimx_all(src.dir = ".", value = c("report", "all"))
```

Arguments

src.dir	source directory where files are located
value	either 'report' or 'all' (only 'report' implemented at the moment)

Details

Read all APSIM-X generated .db files in a directory

Note

Warning: very simple function at the moment, not optimized for memory or speed.

read_apsim_all	<i>Read all APSIM generated .out files in a directory</i>
----------------	---

Description

Like [read_apsim](#), but it reads all .out files in a directory.

Usage

```
read_apsim_all(  
  filenames,  
  src.dir = ".",  
  value = c("report", "all"),  
  date.format = "%d/%m/%Y",  
  simplify = TRUE  
)
```

Arguments

filenames	names of files to be read
src.dir	source directory where files are located
value	either 'report' or 'all' (only 'report' implemented at the moment)
date.format	format for adding 'Date' column
simplify	whether to return a single data frame or a list.

Details

Read all APSIM generated .out files in a directory

Note

Warning: very simple function at the moment, not optimized for memory or speed.

read_apsim_met	<i>Read in an APSIM met file</i>
----------------	----------------------------------

Description

Read into R a met file and return an object of class 'met'

Usage

```
read_apsim_met(file, src.dir = ".", verbose = TRUE)
```

Arguments

file	path to met file
src.dir	optional source directory
verbose	whether to suppress all messages and warnings

Details

Read a met file into R

This function uses S3 classes and stores the additional information as attributes. I use a more strict format than APSIM and reading and writing will not preserve all the details. For example, at this moment comments are lost through the process of read and write unless they are added back in manually. Also, empty lines are ignored so these will be lost as well in the read and write process.

Value

an object of class 'met' with attributes

Examples

```
## Not run:
extd.dir <- system.file("extdata", package = "apsimx")
ames.met <- read_apsim_met("Ames.met", src.dir = extd.dir)
ames.met

## End(Not run)
```

soilwat_parms

Helper function to supply SoilWat parameters

Description

Creates a list with specific components for the SoilWat model

Usage

```
soilwat_parms(
  SummerCona = NA,
  SummerU = NA,
  SummerDate = NA,
  WinterCona = NA,
  WinterU = NA,
  WinterDate = NA,
  DiffusConst = NA,
  DiffusSlope = NA,
  Salb = NA,
```

```

    CN2Bare = NA,
    CNRed = NA,
    CNCov = NA
)

```

Arguments

SummerCona	see APSIM documentation
SummerU	see APSIM documentation
SummerDate	see APSIM documentation
WinterCona	see APSIM documentation
WinterU	see APSIM documentation
WinterDate	see APSIM documentation
DiffusConst	see APSIM documentation
DiffusSlope	see APSIM documentation
Salb	soil albedo (see APSIM documentation)
CN2Bare	see APSIM documentation
CNRed	see APSIM documentation
CNCov	see APSIM documentation

Details

current documentation for APSIM 7.10 <https://www.apsim.info/documentation/model-documentation/soil-modules-documentation/soilwat/>

Value

a 'list' with class 'soilwat_parms'

ssurgo2sp

Take in SSURGO csv files and create a soil profile

Description

Utility function to convert SSURGO data to soil profile

Usage

```

ssurgo2sp(
  mapunit = NULL,
  component = NULL,
  chorizon = NULL,
  mapunit.shp = NULL,
  nmapunit = 1,

```



```

nsoil = 1,
xout = NULL,
soil.bottom = 200,
method = c("constant", "linear"),
nlayers = 10,
verbose = FALSE
)

```

Arguments

mapunit	mapunit SSURGO file
component	component SSURGO file
chorizon	chorizon SSURGO file
mapunit.shp	mapunit shapefile for creating metadata
nmapunit	number of mapunits to select
nsoil	number of soil components (within a mapunit) to consider
xout	vector for interpolation and extrapolation
soil.bottom	bottom of the soil profile
method	method used for interpolation (see approx)
nlayers	number of soil layers to generate
verbose	whether to print details of the process

Details

Download the data from SSURGO using the 'FedData' package
 This will generate csv files 'chorizon', 'component' and 'mapunit',
 but also many other files which are not needed for creating a soil profile.

Value

a list with soil profile matrices with length equal to nsoil

Examples

```

require(ggplot2)
require(sf)
extd.dir <- system.file("extdata", package = "apsimx")

chorizon <- read.csv(paste0(extd.dir, "/ISUAG/SSURGO/ISUAG_SSURGO_chorizon.csv"))
component <- read.csv(paste0(extd.dir, "/ISUAG/SSURGO/ISUAG_SSURGO_component.csv"))
mapunit <- read.csv(paste0(extd.dir, "/ISUAG/SSURGO/ISUAG_SSURGO_mapunit.csv"))
mapunit.shp <- st_read(paste0(extd.dir, "/ISUAG/SSURGO/ISUAG_SSURGO_Mapunits.shp"), quiet = TRUE)

## Using default 'constant' method
sp.c <- ssurgo2sp(mapunit = mapunit,
                  component = component,

```

```

        chorizon = chorizon,
        mapunit.shp = mapunit.shp)

sp.c <- sp.c[[1]]

ggplot(data = sp.c, aes(y = -Depth, x = Carbon)) +
  geom_point() +
  geom_path() +
  ylab("Soil Depth (cm)") + xlab("Organic Matter (percent)") +
  ggtitle("method = constant")

## Using 'linear' method
sp.l <- ssurgo2sp(mapunit = mapunit,
                  component = component,
                  chorizon = chorizon,
                  mapunit.shp = mapunit.shp,
                  method = "linear")

sp.l <- sp.l[[1]]

ggplot(data = sp.l, aes(y = -Depth, x = Carbon)) +
  geom_point() +
  geom_path() +
  ylab("Soil Depth (cm)") + xlab("Organic Matter (percent)") +
  ggtitle("Method linear")

```

swim_parms

Helper function to supply SWIM parameters

Description

Creates a list with specific components for the SWIM model

Usage

```

swim_parms(
  Salb = NA,
  CN2Bare = NA,
  CNRed = NA,
  CNCov = NA,
  KDul = NA,
  PSIDul = NA,
  VC = NA,
  DTmin = NA,
  DTmax = NA,
  MaxWaterIncrement = NA,

```

```

SpaceWeightingFactor = NA,
SoluteSpaceWeightingFactor = NA,
Diagnostics = NA,
SwimWaterTable_WaterTableDepth = NA,
SwimSubsurfaceDrain_DrainDepth = NA,
SwimSubsurfaceDrain_DrainSpacing = NA,
SwimSubsurfaceDrain_DrainRadius = NA,
SwimSubsurfaceDrain_Klat = NA,
SwimSubsurfaceDrain_ImpermDepth = NA
)

```

Arguments

Salb	see APSIM documentation
CN2Bare	see APSIM documentation
CNRed	see APSIM documentation
CNCov	see APSIM documentation
KDu1	see APSIM documentation
PSIDu1	see APSIM documentation
VC	see APSIM documentation
DTmin	see APSIM documentation
DTmax	see APSIM documentation
MaxWaterIncrement	see APSIM documentation
SpaceWeightingFactor	see APSIM documentation
SoluteSpaceWeightingFactor	see APSIM documentation
Diagnostics	see APSIM documentation
SwimWaterTable_WaterTableDepth	see APSIM documentation
SwimSubsurfaceDrain_DrainDepth	see APSIM documentation
SwimSubsurfaceDrain_DrainSpacing	see APSIM documentation
SwimSubsurfaceDrain_DrainRadius	see APSIM documentation
SwimSubsurfaceDrain_Klat	see APSIM documentation
SwimSubsurfaceDrain_ImpermDepth	see APSIM documentation

Details

current documentation for APSIM 7.10 <https://www.apsim.info/documentation/model-documentation/soil-modules-documentation/swim3/>

Value

a 'list' with class 'swim_parms'

unit_conv	<i>performs common unit conversions</i>
-----------	---

Description

It does not do much at the moment, but I will develop it as I have increasing needs for unit conversions.

Usage

```
unit_conv(x, from, to)
```

Arguments

x	input variable
from	original units
to	target units

Details

Function which performs common unit conversions

At the moment possible conversions are:

- 'g/m2' to 'kg/ha'
- 'kg/ha' to 'g/m2'
- 'lb' to 'kg'
- 'kg' to 'lb'
- 'maize bu' to 'kg'
- 'kg' to 'maize bu'
- 'soy bu' to 'kg'
- 'kg' to 'soy bu'
- 'maize bu/ac' to 'kg/ha'
- 'kg/ha' to 'maize bu/ac'
- 'soy bu/ac' to 'kg/ha'
- 'kg/ha' to 'soy bu/ac'

This is for metric and Imperial conversions Source: <https://www.extension.iastate.edu/agdm/wholefarm/html/c6-80.html>

Value

value of the input variable with new units

Examples

```
grain.yield.gm2 <- 600
grain.yield.kgha <- unit_conv(grain.yield.gm2, from = "g/m2", to = "kg/ha")
grain.yield.kgha
```

 view_apsim

Viewing an APSIM Classic file interactively

Description

Generate an interactive viewer for an APSIM file

Usage

```
view_apsim(file, src.dir, viewer = c("json", "react"), ...)
```

Arguments

file	a file ending in .apsim to be inspected (XML)
src.dir	directory containing the .apsim file to be inspected; defaults to the current working directory
viewer	either "json" or "react".
...	additional arguments passed to either 'jsonedit' or 'reactjson'. These are functions in package listviewer .

Note

I do not know how to edit an APSIM file using this method yet.

Examples

```
## Not run:
extd.dir <- system.file("extdata", package = "apsimx")
## View the structure of the APSIM-X simulation file
view_apsim("Millet.apsim", src.dir = extd.dir)

## End(Not run)
```

view_apsimx	<i>Viewing an APSIM-X file interactively</i>
-------------	--

Description

Generate an interactive viewer for an APSIM-X file

Usage

```
view_apsimx(file, src.dir, viewer = c("json", "react"), ...)
```

Arguments

file	a file ending in .apsimx to be inspected (JSON)
src.dir	directory containing the .apsimx file to be inspected; defaults to the current working directory
viewer	either "json" or "react".
...	additional arguments passed to either 'jsonedit' or 'reactjson'. These are functions in package listviewer .

Note

I do not know how to edit an APSIM-X file using this method yet.

Examples

```
## Not run:
extd.dir <- system.file("extdata", package = "apsimx")
## View the structure of the APSIM-X simulation file
view_apsimx("Wheat.apsimx", src.dir = extd.dir)

## End(Not run)
```

view_apsim_xml	<i>View an APSIM Classic auxiliary (XML) file</i>
----------------	---

Description

view an auxilliary XML apsim file.

Usage

```
view_apsim_xml(file, src.dir, viewer = c("json", "react"), ...)
```

Arguments

file	file ending in .xml to be viewed.
src.dir	directory containing the .xml file to be viewed; defaults to the current working directory
viewer	either "json" or "react".
...	additional arguments passed to either 'jsonedit' or 'reactjson'.

Details

view APSIM XML file

Value

nothing

Examples

```
## Not run:
extd.dir <- system.file("extdata", package = "apsimx")
view_apsim_xml("Maize75.xml", src.dir = extd.dir)

## End(Not run)
```

wop

Wheat example optimization results

Description

Results from Wheat optimization example

Usage

wop

Format

An object of class 'optim_apsim'

wop wheat optimization results

Source

Result of running the examples in Parameter Optimization vignette

wop.h	<i>Wheat example optimization results plus Hessian</i>
-------	--

Description

Results from Wheat optimization example plus the Hessian

Usage

wop.h

Format

An object of class 'optim_apsim'

wop.h wheat optimization results plus Hessian

Source

Result of running the examples in Parameter Optimization vignette with the added Hessian

write_apsim_met	<i>Write an APSIM met file</i>
-----------------	--------------------------------

Description

Write an object of class 'met' to disk

Usage

```
write_apsim_met(met, wrt.dir = NULL, filename = NULL)
```

Arguments

met	object of class 'met'
wrt.dir	directory where the file will be written
filename	optional alternative filename

Details

Write a met file to disk. It takes an object of class 'met' at the moment the read-write cycle will strip comments

Value

does not create an R object, it only writes to disk

Examples

```
## Not run:
extd.dir <- system.file("extdata", package = "apsimx")
ames.met <- read_apsim_met("Ames.met", src.dir = extd.dir)
ames.met
tmp.dir <- tempdir()
write_apsim_met(ames.met, wrt.dir = tmp.dir, filename = "Ames.met")
## Here I write to a temporary directory, but change this to where
## you want to write to

## End(Not run)
```

Index

* datasets

- apsim.options, 4
 - apsimx.options, 6
 - mcmc.apsim.env, 46
 - mcmc.apsimx.env, 46
 - obsWheat, 47
 - wop, 63
 - wop.h, 64
- approx, 57
- approxfun, 38
- apsim, 3
- apsim.options, 4
- apsim_example, 12
- apsim_options, 13
- apsim_version, 14
- apsimx, 5
- apsimx.options, 6
- apsimx_example, 6
- apsimx_filetype, 7
- apsimx_options, 8
- apsimx_soil_profile, 9, 11
- auto_detect_apsim_examples, 15
- auto_detect_apsimx_examples, 14
- check_apsim_met, 16
- check_apsimx_soil_profile
(apsimx_soil_profile), 9
- coef.optim_apsim (optim_apsim), 48
- compare_apsim, 16
- compare_apsim_met, 18
- date2doy (doy2date), 19
- doy2date, 19
- edit_apsim, 20
- edit_apsim_replace_soil_profile, 29
- edit_apsim_xml, 30
- edit_apsimx, 22
- edit_apsimx_batch, 24
- edit_apsimx_replace_soil_profile, 27
- edit_apsimx_replacement, 26, 51
- extract_values_apsimx, 32
- get_daymet, 32, 33
- get_daymet_apsim_met, 32
- get_GSOD, 34
- get_gsod_apsim_met, 34
- get_iem_apsim_met, 36
- get_iemre_apsim_met, 35
- get_power, 37
- get_power_apsim_met, 37
- impute_apsim_met, 38, 47
- inspect_apsim, 38, 48
- inspect_apsim_xml, 45, 48
- inspect_apsimx, 11, 41, 50
- inspect_apsimx_replacement, 43
- mcmc.apsim.env, 46
- mcmc.apsimx.env, 46
- mean, 38
- napad_apsim_met, 47
- nloptr, 49, 50
- obsWheat, 47
- optim, 48–51
- optim_apsim, 48
- optim_apsimx, 50
- plot.met_mrg (compare_apsim_met), 18
- plot.out_mrg (compare_apsim), 16
- plot.soil_profile
(apsimx_soil_profile), 9
- print.met, 51
- print.optim_apsim (optim_apsim), 48
- read_apsim, 52, 54
- read_apsim_all, 54
- read_apsim_met, 54

read_apsimx, [52](#), [53](#)
read_apsimx_all, [53](#)
runMCMC, [49](#), [50](#)

soilwat_parms, [55](#)
splinefun, [38](#)
ssurgo2sp, [56](#)
swim_parms, [58](#)

unit_conv, [60](#)

vcov.optim_apsim(optim_apsim), [48](#)
view_apsim, [61](#)
view_apsim_xml, [62](#)
view_apsimx, [62](#)

wop, [63](#)
wop.h, [64](#)
write_apsim_met, [64](#)