

Package ‘assertive.dattetimes’

February 2, 2017

Type Package

Title Assertions to Check Properties of Dates and Times

Version 0.0-2

Date 2016-05-08

Author Richard Cotton [aut, cre]

Maintainer Richard Cotton <richierocks@gmail.com>

Description A set of predicates and assertions for checking the properties of dates and times. This is mainly for use by other package developers who want to include run-time testing features in their own packages. End-users will usually want to use assertive directly.

URL <https://bitbucket.org/richierocks/assertive.dattetimes>

BugReports <https://bitbucket.org/richierocks/assertive.dattetimes/issues>

Depends R (>= 3.0.0)

Imports assertive.base (>= 0.0-2), assertive.types

Suggests testthat

License GPL (>= 3)

LazyLoad yes

LazyData yes

Acknowledgments Development of this package was partially funded by the Proteomics Core at Weill Cornell Medical College in Qatar <<http://qatar-weill.cornell.edu>>. The Core is supported by 'Biomedical Research Program' funds, a program funded by Qatar Foundation.

RoxygenNote 5.0.1

Collate 'assert-is-date-string.R' 'imports.R' 'assert-is-time.R' 'is-date-string.R' 'workaround.R' 'is-time.R'

NeedsCompilation no

Repository CRAN

Date/Publication 2016-05-10 10:30:32

R topics documented:

| | |
|---------------------------------------|---|
| assert_all_are_after | 2 |
| assert_all_are_date_strings | 4 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

assert_all_are_after *Is the input in the past/future?*

Description

Checks to see if the input is a time in the past/future, or before/after some time point.

Usage

```
assert_all_are_after(x, y, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_any_are_after(x, y, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_all_are_before(x, y, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_any_are_before(x, y, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_all_are_in_future(x, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_any_are_in_future(x, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_all_are_in_past(x, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_any_are_in_past(x, na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
is_after(x, y, .xname = get_name_in_parent(x),
  .yname = get_name_in_parent(y))
```

```
is_before(x, y, .xname = get_name_in_parent(x),
  .yname = get_name_in_parent(y))
```

```
is_in_future(x, .xname = get_name_in_parent(x))
```

```
is_in_past(x, .xname = get_name_in_parent(x))
```

Arguments

| | |
|-----------|--|
| x | Date or POSIXt input to check. |
| y | Another date-time object to compare against. |
| na_ignore | A logical value. If FALSE, NA values cause an error; otherwise they do not. Like <code>na.rm</code> in many stats package functions, except that the position of the failing values does not change. |
| severity | How severe should the consequences of the assertion be? Either "stop", "warning", "message", or "none". |
| .xname | Not intended to be used directly. |
| .yname | Not intended to be used directly. |

Details

The current time is determined by `Sys.time`, and the input is coerced to POSIXct format if necessary.

Value

The `is_*` function return TRUE if the input is a time in the future/past. The `assert_*` functions return nothing but throw an error if the corresponding `is_*` function returns FALSE.

Note

Note that the print method for POSIXct objects means that the cause attribute (in the event of failures) is not shown. You can still access it via, e.g., `cause(is_in_past(x))`.

See Also

[Sys.time](#).

Examples

```
x <- Sys.time() + c(-1, 100)
is_in_past(x)
is_in_future(x)

# more generally, compare against any date-time
is_before(x, as.POSIXct("9999-12-31"))
is_after(x, as.POSIXct("0001-01-01"))
```

 assert_all_are_date_strings

Does the character vector contain dates?

Description

Checks that the input contains dates or times.

Usage

```
assert_all_are_date_strings(x, format = "%F %T", na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
assert_any_are_date_strings(x, format = "%F %T", na_ignore = FALSE,
  severity = getOption("assertive.severity", "stop"))
```

```
is_date_string(x, format = "%F %T", .xname = get_name_in_parent(x))
```

Arguments

| | |
|-----------|--|
| x | Input to check. |
| format | Expected format of the dates. See strptime . |
| na_ignore | A logical value. If FALSE, NA values cause an error; otherwise they do not. Like <code>na.rm</code> in many stats package functions, except that the position of the failing values does not change. |
| severity | How severe should the consequences of the assertion be? Either "stop", "warning", "message", or "none". |
| .xname | Not intended to be used directly. |

Value

A logical vector that is TRUE when the input contains valid dates or times.

See Also

[strptime](#) for specifying formats, and the `lubridate` package for automatic guessing of date formats (and other date manipulation functions).

Examples

```
x <- c("9999-12-31 23:59:59", "wednesday", NA)
is_date_string(x)
assert_all_are_date_strings("01Aug1979", format = "%d%b%Y") #My DOB!
```

Index

`assert_all_are_after`, 2
`assert_all_are_before`
 (`assert_all_are_after`), 2
`assert_all_are_date_strings`, 4
`assert_all_are_in_future`
 (`assert_all_are_after`), 2
`assert_all_are_in_past`
 (`assert_all_are_after`), 2
`assert_any_are_after`
 (`assert_all_are_after`), 2
`assert_any_are_before`
 (`assert_all_are_after`), 2
`assert_any_are_date_strings`
 (`assert_all_are_date_strings`),
 4
`assert_any_are_in_future`
 (`assert_all_are_after`), 2
`assert_any_are_in_past`
 (`assert_all_are_after`), 2

`is_after` (`assert_all_are_after`), 2
`is_before` (`assert_all_are_after`), 2
`is_date_string`
 (`assert_all_are_date_strings`),
 4
`is_in_future` (`assert_all_are_after`), 2
`is_in_past` (`assert_all_are_after`), 2

`strptime`, 4
`Sys.time`, 3