

Package ‘calibrate’

April 17, 2009

Version 1.5

Date 2009-02-23

Title Calibration of Biplot Axes

Author Jan Graffelman <jan.graffelman@upc.edu>

Maintainer Jan Graffelman <jan.graffelman@upc.edu>

Depends R (>= 1.8.0)

Description Package for drawing calibrated scales with tick marks on (non-orthogonal) variable vectors in scatterplots and biplots.

License GPL-2

Repository CRAN

Date/Publication 2009-02-23 12:58:58

R topics documented:

calibrate	2
calves	4
canocor	5
circle	6
dlines	7
goblets	8
heads	8
linnerud	9
ones	9
origin	10
rda	11
storks	12
textxy	13
Index	14

calibrate

*Calibration of Biplot and Scatterplot Axis***Description**

Routine for the calibration of any axis (variable vector) in a biplot or a scatterplot

Usage

```
calibrate(g, y, tm, Fr, tmlab=tm, tl=0.05, dt=TRUE, dp=FALSE, lm=TRUE,
verb=TRUE, axislab="", reverse=FALSE, shift=0, alpha=NULL, labpos=1,
weights=diag(rep(1, length(y))), axiscol="blue", cex.axislab=0.75,
graphics=TRUE, where=3, laboffset=c(0, 0), m=matrix(c(0, 0), nrow=1),
markerpos=3, showlabel=TRUE, lwd=1)
```

Arguments

<code>g</code>	the vector to be calibrated (2 x 1).
<code>y</code>	the data vector corresponding to <code>g</code> , appropriately centred and/or standardized.
<code>tm</code>	the vector of tick marks, appropriately centred and/or scaled.
<code>Fr</code>	the coordinates of the rows markers in the biplot.
<code>tmlab</code>	a list or vector of tick mark labels.
<code>tl</code>	the tick length. By default, the tick markers have length 0.05.
<code>dt</code>	draw ticks. By default, ticks markers are drawn. Set <code>dt=F</code> in order to compute calibration results without actually drawing the calibrated scale.
<code>dp</code>	drop perpendiculars. With <code>dp=T</code> perpendicular lines will be drawn from the row markers specified by <code>Fr</code> onto the calibrated axis. This is a graphical aid to read off the values in the corresponding scale.
<code>lm</code>	label markers. By default, all tick marks are labelled. Setting <code>lm=F</code> turns off the labelling of the tick marks. This allows for creating tick marks without labels. It is particularly useful for creating finer scales of tickmarks without labels.
<code>verb</code>	verbose parameter (F=be quiet, T=show results).
<code>axislab</code>	a label for the calibrated axis.
<code>reverse</code>	puts the tick marks and tick mark labels on the other side of the axis.
<code>shift</code>	a scalar that shifts the calibrated axis by a fixed distance.
<code>alpha</code>	a value for the calibration factor. This parameter should only be specified if a calibration is required that is different from the one that is optimal for data recovery.
<code>labpos</code>	position of the label for the calibrated axis (1,2,3 or 4).
<code>laboffset</code>	offset vector for the axis label. If specified, shifts the label by the specified amounts with respect to the current position.
<code>weights</code>	a matrix of weights (optional).

<code>axiscol</code>	color of the calibrated axis.
<code>cex.axislab</code>	character expansion factor for axis label and tick mark labels.
<code>graphics</code>	do graphics or not (F=no graphical output, T=draws calibrated scale).
<code>where</code>	label placement (1=beginning,2=middle,3=end).
<code>m</code>	vector of means.
<code>markerpos</code>	position specifier for the tick mark labels (1,2,3 or 4).
<code>showlabel</code>	show axis label in graph (T) or not (F).
<code>lwd</code>	line width for the calibrated axis

Details

This program calibrates variable vectors in biplots and scatterplots, by drawing tick marks along a given the vector and labelling the tick marks with specified values. The optimal calibration is found by (generalized) least squares. Non-optimal calibrations are possible by specifying a calibration factor (α).

Value

Returns a list with calibration results

<code>useralpha</code>	calibration factor specified by the user
<code>optalpha</code>	optimal calibration factor
<code>lengthoneunit</code>	length in the plot of one unit in the scale of the calibrated variable
<code>gof</code>	goodness of fit (as in regression)
<code>gos</code>	goodness of scale
<code>M</code>	coordinates of the tick markers
<code>ang</code>	angle in degrees of the biplot axis with the positive x-axis
<code>yt</code>	fitted values for the variable according to the calibration
<code>e</code>	errors according to the calibration
<code>Fpr</code>	coordinates of the projections of the row markers onto the calibrated axis
<code>Mn</code>	coordinates of the tick marker end points

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

References

- Gower, J.C. and Hand, D.J., (1996) Biplots. Chapman & Hall, London
- Graffelman, J. and van Eeuwijk, F.A. (2005) Calibration of multivariate scatter plots for exploratory analysis of relations within and between sets of variables in genomic research *Biometrical Journal*, 47(6) pp. 863-879.
- Graffelman, J. (2006) A guide to biplot calibration.

See Also

`biplot`

Examples

```
x <- rnorm(20,1)
y <- rnorm(20,1)
x <- x - mean(x)
y <- y - mean(y)
z <- x + y
b <- c(1,1)
plot(x,y,asp=1,pch=19)
tm<-seq(-2,2,by=0.5)
Calibrate.z <- calibrate(b,z,tm,cbind(x,y),axislab="Z",graphics=TRUE)
```

calves

Delivery of Dutch Calves

Description

This data set gives a cross classification of 7275 calves born in the late nineties according to type of production and type of delivery.

Usage

```
data(calves)
```

Format

A data frame containing a contingency table of 7275 observations.

Source

Holland Genetics. <http://www.hg.nl>

References

Graffelman, J. (2005) *A guide to scatterplot and biplot calibration*.

canocor *Canonical correlation analysis*

Description

canocor performs canonical correlation analysis on the basis of the standardized variables and stores extensive output in a list object.

Usage

```
canocor(X, Y)
```

Arguments

X	a matrix containing the X variables
Y	a matrix containing the Y variables

Details

canocor computes the solution by a singular value decomposition of the transformed between set correlation matrix.

Value

Returns a list with the following results

ccor	the canonical correlations
A	canonical weights of the x variables
B	canonical weights of the y variables
U	canonical x variates
V	canonical y variates
Fs	biplot markers for x variables (standard coordinates)
Gs	biplot markers for y variables (standard coordinates)
Fp	biplot markers for x variables (principal coordinates)
Gp	biplot markers for y variables (principal coordinates)
fitRxy	goodness of fit of the between-set correlation matrix
fitXs	adequacy coefficients of x variables
fitXp	redundancy coefficients of x variables
fitYs	adequacy coefficients of y variables
fitYp	redundancy coefficients of y variables

Author(s)

Jan Graffelman <jan.graffelman@upc.edu>

References

Hotelling, H. (1935) The most predictable criterion. *Journal of Educational Psychology* (26) pp. 139-142.

Hotelling, H. (1936) Relations between two sets of variates. *Biometrika* (28) pp. 321-377.

Johnson, R. A. and Wichern, D. W. (2002) *Applied Multivariate Statistical Analysis*. New Jersey: Prentice Hall.

See Also

[cancor](#)

Examples

```
set.seed(123)
X <- matrix(runif(75), ncol=3)
Y <- matrix(runif(75), ncol=3)
cca.results <- canocor(X, Y)
```

circle

Draw a circle

Description

circle draws a circle in an existing plot.

Usage

```
circle(radius)
```

Arguments

radius the radius of the circle

Value

NULL

Author(s)

Jan Graffelman <jan.graffelman@upc.edu>

Examples

```
set.seed(123)
X <- matrix(rnorm(20), ncol=2)
plot(X[,1], X[,2])
circle()
```

dlines *Connect two sets of points by lines*

Description

dlines connects two sets of points by lines in a rowwise manner.

Usage

```
dlines(SetA, SetB, lin = "dotted")
```

Arguments

SetA	matrix with the first set of points
SetB	matrix with teh second set of points
lin	linestyle for the connecting lines

Value

NULL

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

See Also

[lines](#)

Examples

```
X <- matrix(runif(20), ncol=2)
Y <- matrix(runif(20), ncol=2)
plot(rbind(X, Y))
text(X[, 1], X[, 2], paste("X", 1:10, sep=""))
text(Y[, 1], Y[, 2], paste("Y", 1:10, sep=""))
dlines(X, Y)
```

goblets

Size measurements of archeological goblets

Description

This data set gives 6 different size measurements of 25 goblets

Usage

```
data(goblets)
```

Format

A data frame containing 25 observations.

Source

Manly, 1989

References

Manly, B. F. J. (1989) *Multivariate statistical methods: a primer*. London: Chapman and Hall, London

heads

Dimensions of heads of first and second sons for 25 families

Description

Variables X1 and X2 are the head length and head breadth of the first son and Y1 and Y2 are the same variables for the second son.

Usage

```
data(heads)
```

Format

A data frame containing 25 observations.

Source

Mardia, 1979, p. 121

References

- Frets, G. P. (1921) *Heredity of head form in man*, *Genetica* 3, pp. 193-384.
- Mardia, K. V. and Kent, J. T. and Bibby, J. M. (1979) *Multivariate Analysis*. Academic Press London.
- Anderson, T. W. (1984) *An Introduction to Multivariate Statistical Analysis*. New York: John Wiley, Second edition.

`linnerud`*Linnerud's exercise and body measurements*

Description

The data set consist of 3 exercise variables (Tractions a la barre fixe, Flexions, Sauts) and 3 body measurements (Poids, Tour de taille, Pouls) of 20 individuals.

Usage

```
data(linnerud)
```

Format

A data frame containing 20 observations.

Source

Tenenhaus, 1998, table 1, page 15

References

- Tenenhaus, M. (1998) *La Regression PLS*. Paris: Editions Technip.

`ones`*Generates a matrix of ones*

Description

`ones` generates a matrix of ones.

Usage

```
ones(n, p = n)
```

Arguments

`n` number of rows
`p` number of columns

Details

if only `n` is specified, the resulting matrix will be square.

Value

a matrix filled with ones.

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

See Also

[matrix](#)

Examples

```
Id <- ones(3)
print(Id)
```

origin

Origin

Description

Draws coordinate axes in a plot.

Usage

```
origin(m=c(0,0))
```

Arguments

`m` the coordinates of the means (2 x 1).

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

Examples

```
X <- matrix(runif(40), ncol=2)
plot(X[,1], X[,2])
origin(m=c(mean(X[,1]), mean(X[,2])))
```

rda *Redundancy analysis*

Description

rda performs redundancy analysis and stores extensive output in a list object.

Usage

```
rda(X, Y, scaling = 1)
```

Arguments

X	a matrix of x variables
Y	a matrix of y variables
scaling	scaling used for x and y variables. 0: x and y only centered. 1: x and y standardized

Details

Results are computed by doing a principal component analysis of the fitted values of the regression of y on x.

Plotting the first two columns of Gxs and Gyp, or of Gxp and Gys provides a biplots of the matrix of regression coefficients.

Plotting the first two columns of Fs and Gp or of Fp and Gs provides a biplot of the matrix of fitted values.

Value

Returns a list with the following results

Yh	fitted values of the regression of y on x
B	regression coefficients of the regression of y on x
decom	variance decomposition/goodness of fit of the fitted values AND of the regression coefficients
Fs	biplot markers of the rows of Yh (standard coordinates)
Fp	biplot markers of the rows of Yh (principal coordinates)
Gys	biplot markers for the y variables (standard coordinates)
Gyp	biplot markers for the y variables (principal coordinates)
Gxs	biplot markers for the x variables (standard coordinates)
Gxp	biplot markers for the x variables (principal coordinates)

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

References

Van den Wollenberg, A.L. (1977) Redundancy Analysis, an alternative for canonical correlation analysis. *Psychometrika* 42(2): pp. 207-219.

Ter Braak, C. J. F. and Looman, C. W. N. (1994) Biplots in Reduced-Rank Regression. *Biometrical Journal* 36(8): pp. 983-1003.

See Also

[princomp](#), [canocor](#), [biplot](#)

Examples

```
X <- matrix(rnorm(75), ncol=3)
Y <- matrix(rnorm(75), ncol=3)
rda.results <- rda(X, Y)
```

storks

Frequencies of nesting storks in Denmark

Description

Danish data from 1953-1977 giving the frequency of nesting storks, the human birth rate and the per capita electricity consumption.

Usage

```
data(storks)
```

Format

A data frame containing 25 observations.

Source

Gabriel and Odoroff, Table 1.

References

Gabriel, K. R. and Odoroff, C. L. (1990) Biplots in biomedical research. *Statistics in Medicine* 9(5): pp. 469-485.

textxy *Label points in a plot*

Description

Function textxy calls function text in order to add text to points in a graph. textxy chooses a different position for the text depending on the quadrant. This tends to produce better readable plots.

Usage

```
textxy(X, Y, labs, cx = 0.5, dcol = "black", m = c(0, 0))
```

Arguments

X	x coordinates of a set of points
Y	y coordinates of a set of points
labs	labels to be placed next to the points
cx	character expansion factor
dcol	colour for the labels
m	coordinates of the origin of the plot (default (0,0))

Value

NULL

Author(s)

Jan Graffelman (jan.graffelman@upc.edu)

References

Graffelman, J. (2006) A guide to biplot calibration.

See Also

[text](#)

Examples

```
x <- runif(50)
y <- runif(50)
plot(x, y)
textxy(x, y, 1:50, m=c(mean(x), mean(y)))
```

Index

*Topic **aplot**

circle, 6
dlines, 6
textxy, 12

*Topic **datasets**

calves, 4
goblets, 7
heads, 8
linnerud, 8
storks, 12

*Topic **multivariate**

calibrate, 1
canocor, 4
ones, 9
origin, 10
rda, 10

biplot, 3, 11

calibrate, 1
calves, 4
cancor, 5
canocor, 4, 11
circle, 6

dlines, 6

goblets, 7

heads, 8

lines, 7
linnerud, 8

matrix, 9

ones, 9
origin, 10

princomp, 11

rda, 10

storks, 12

text, 13
textxy, 12