

Package ‘distrTeach’

November 3, 2009

Version 2.2

Date 2009-10-16

Title Extensions of package distr for teaching Stochastics/Statistics in secondary school

Description Extensions of package distr and some additional functionality

Depends R(>= 2.2.0), methods, distr(>= 2.2), distrEx(>= 2.2), startupmsg

Suggests tcltk

Author Peter Ruckdeschel, Matthias Kohl, Anja Hueller, Eleonara Feist

Maintainer Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>

LazyLoad yes

License LGPL-3

Encoding latin1

URL <http://distr.r-forge.r-project.org/>

LastChangedDate {`$(LastChangedDate: 2009-10-16 06:07:57 +0200 (Fr, 16. Okt 2009) $`}

LastChangedRevision {`$(LastChangedRevision: 619 $`}

Repository CRAN

Date/Publication 2009-11-03 13:50:28

R topics documented:

distrTeach-package	2
illustrateCLT	4
illustrateLLN	5

Index	8
--------------	----------

distrTeach-package *distrTeach – Teaching Extensions of package distr*

Description

distrTeach provides some illustrations based on package **distr** for teaching Stochastics / Statistics in secondary school; so far the following has been implemented

- `illustrateLLT`: function for the generation of LLN - visualizations
- `illustrateCLT`: function for the generation of CLT - visualizations
- `plotCLT`: Generic function for the plotting of CLT-approximations

as well as a Tcl/Tk based demo for `illustrateCLT`

Details

```

Package:    distrTeach
Version:    2.2
Date:       2009-09-04
Depends:    R(>= 2.2.0), methods, distr(>= 2.0), distrEx(>= 2.0), startupmsg
LazyLoad:   yes
License:    LGPL-3
URL:        http://distr.r-forge.r-project.org/

```

Classes

Teaching Classes

Methods

```

illustration:
illustrateLLT      function for the generation of LLN - visualizations
illustrateCLT      function for the generation of CLT - visualizations
plotCLT            Generic function for the plotting of CLT-approximations

```

Demos

Demos are available — see `demo(package="distrTeach")`.

Start-up-Banner

You may suppress the start-up banner/message completely by setting `options("StartupBanner"="off")` somewhere before loading this package by `library` or `require` in your R-code / R-session.

If option "StartupBanner" is not defined (default) or setting `options("StartupBanner"=NULL)` or `options("StartupBanner"="complete")` the complete start-up banner is displayed.

For any other value of option "StartupBanner" (i.e., not in `c(NULL, "off", "complete")`) only the version information is displayed.

The same can be achieved by wrapping the `library` or `require` call into either `suppressStartupMessages()` or `onlytypeStartupMessages(., atypes="version")`.

As for general packageStartupMessage's, you may also suppress all the start-up banner by wrapping the `library` or `require` call into `suppressPackageStartupMessages()` from **startupmsg**-version 0.5 on.

Package versions

Note: The first two numbers of package versions do not necessarily reflect package-individual development, but rather are chosen for the distrXXX family as a whole in order to ease updating "depends" information.

Author(s)

Matthias Kohl <Matthias.Kohl@stamats.de> and
 Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>,
 Eleonara Feist <eleonoragerber@gmx.de>, and,
 Anja Hueller <anja_h86@web.de>

Maintainer: Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>

References

P. Ruckdeschel, M. Kohl, T. Stabla, F. Camphausen (2006): S4 Classes for Distributions, *R News*, 6(2), 2-6. http://CRAN.R-project.org/doc/Rnews/Rnews_2006-2.pdf

a vignette for packages **distr**, **distrSim**, **distrTEst**, and **distrTeach** is included into the mere documentation package **distrDoc** and may be called by `require("distrDoc"); vignette("distr")`

a homepage to this package is available under <http://distr.r-forge.r-project.org/> and the pages ...

M. Kohl (2005): *Numerical Contributions to the Asymptotic Theory of Robustness*. PhD Thesis. Bayreuth. Available as <http://www.stamats.de/ThesisMKohl.pdf>

See Also

[distr-package](#) [distrEx-package](#)

Description

Functions for generating a sequence of plots of the density and cdf of the consecutive standardized and centered sums of iid r.v. distributed according to a prescribed discrete or absolutely continuous distribution compared to the standard normal — uses the generic function `plotCLT`.

Usage

```
illustrateCLT(Distr, len, sleep = 0)
illustrateCLT.tcl(Distr, k, Distrname)
```

Arguments

<code>Distr</code>	object of class "AbscontDistribution", "LatticeDistribution" or "DiscreteDistribution": distribution of the summands
<code>len</code>	integer: up to which number of summands plots are generated
<code>k</code>	integer: number of summands for which a plot is to be generated
<code>Distrname</code>	character: name of the summand distribution to be used as title in the plot
<code>sleep</code>	numeric: pause in seconds between subsequent plots

Details

`illustrateCLT` generates a sequence of plots, while `illustrateCLT.tcl` may be used with Tcl/Tk-widgets as in demo `illustCLT_tcl.R`.

Value

void

Author(s)

Matthias Kohl (Matthias.Kohl@stamats.de)
Peter Ruckdeschel (Peter.Ruckdeschel@itwm.fraunhofer.de)

See Also

[plotCLT](#)

Examples

```

distrptions("DefaultNrFFTGridPointsExponent" = 13)
illustrateCLT(Distr = Unif(), len = 20)
distrptions("DefaultNrFFTGridPointsExponent" = 12)
illustrateCLT(Distr = Pois(lambda = 2), len = 20)
distrptions("DefaultNrFFTGridPointsExponent" = 13)
illustrateCLT(Distr = Pois(lambda = 2)+Unif(), len = 20)
illustrateCLT.tcl(Distr = Unif(), k = 4, "Unif()")

```

illustrateLLN

Functions for Illustrating the LLN

Description

Functions for generating a sequence of plots of randomly generated replicates of $\bar{X}_n = \frac{1}{n} \sum_{i=1}^n X_i$ for sums of iid r.v. distributed according to a prescribed discrete or absolutely continuous distribution. A line for the expectation and CLT based (pointwise) 95%-confidence bands are also plotted and the empirical coverage of this band by the replicated plotted so far is indicated.

Usage

```

illustrateLLN(Distr = Norm(), n = c(1, 3, 5, 10, 25, 50, 100, 500, 1000, 10000),
             m = 50, step = 1, sleep = 0, withConf = TRUE,
             withCover = (length(n) <= 12), withEline = TRUE, withLegend = TRUE,
             CLTorCheb = "CLT", coverage = 0.95, ..., col.Eline = "blue",
             lwd.Eline = par("lwd"), lty.Eline = par("lty"), col.Conf = "red",
             lwd.Conf = par("lwd"), lty.Conf = 2, cex.Cover = 0.7,
             cex.legend = 0.8)

```

Arguments

Distr	object of class "UnivariateDistribution": distribution of the summands
n	vector of integers: sample sizes to be considered
m	integer: (total) number of replicates to be plotted subsequently
step	integer: number of replicates to be drawn at once
sleep	numeric: pause in seconds between subsequent plots
withEline	logical: shall a line for the limiting expectation (in case of class Cauchy instead: median) be drawn?
withConf	logical: shall (CLT-based) confidence bands be plotted?
withCover	logical: shall empirical coverage of (CLT-based) confidence bands be printed?
withLegend	logical: shall a legend be included?
CLTorCheb	character: type of confidence interval — "CLT" or "Chebyshev"; partial matching is used; if this fails "CLT" is used.

<code>coverage</code>	numerical: nominal coverage of the confidence bands —to be in (0,1)
<code>col.Eline</code>	character or integer code; color for confidence bands
<code>lwd.Eline</code>	integer code (see par); line width of the confidence bands
<code>lty.Eline</code>	integer code (see par); line type of the confidence bands
<code>col.Conf</code>	character or integer code; color for confidence bands
<code>lwd.Conf</code>	integer code (see par); line width of the confidence bands
<code>lty.Conf</code>	integer code (see par); line type of the confidence bands
<code>cex.Cover</code>	magnification w.r.t. the current setting of <code>cex</code> to be used for empirical coverages; as in par
<code>cex.legend</code>	magnification w.r.t. the current setting of <code>cex</code> to be used for the legend as in par
<code>...</code>	further arguments to be passed to <code>matplot</code> , <code>matlines</code> , <code>abline</code>

Details

`illustrateLLN` generates a sequence of plots. Any parameters of `plot.default` may be passed on to this particular `plot` method.

There are default `main` titles as well as `xlab` and `ylab` annotations.

In all title arguments, the following patterns are substituted:

"%C" class of argument `x`

"%P" parameters of `x` in form of a comma-separated list of `<value>`'s coerced to character

"%Q" parameters of `x` in form of a comma-separated list of `<value>`'s coerced to character and in parenthesis — unless empty; then ""

"%N" parameters of `x` in form of a comma-separated list `<name> = <value>` coerced to character

"%A" deparsed argument `x`

"%D" time/date-string when the plot was generated

"%X" the expression $\bar{X}_n = \sum_{i=1}^n X_i/n$

If not explicitly set, `col.Eline`, `col.Conf` are set to `col` if this arg is given and else to their default values as given above. Similarly for `cex`, `lwd` and `lty`.

Value

void

Author(s)

Peter Ruckdeschel (Peter.Ruckdeschel@itwm.fraunhofer.de)

Examples

```
illustrateLLN(Distr = Unif())
illustrateLLN(Distr = Pois(lambda = 2))
illustrateLLN(Distr = Pois(lambda = 2)+Unif())
illustrateLLN(Td(3), m = 50, col.Eline = "green", lwd = 2, cex = 0.6, main =
  "My LLN %C%Q", sub = "generated %D")
illustrateLLN(Td(3), m = 50, CLTorCheb = "Chebyshev")
illustrateLLN(Td(3), m = 50, CLTorCheb = "Chebyshev", coverage = 0.75)
```

Index

*Topic **distribution**

illustrateCLT, 4

illustrateLLN, 5

*Topic **dynamic**

illustrateCLT, 4

illustrateLLN, 5

*Topic **methods**

illustrateCLT, 4

illustrateLLN, 5

*Topic **package**

distrTeach-package, 2

distr-package, 3

distrEx-package, 3

distrTeach (*distrTeach-package*), 2

distrTeach-package, 2

illustrateCLT, 4

illustrateLLN, 5

par, 6

plotCLT, 4