

# Package ‘dplR’

May 23, 2018

**Encoding** UTF-8

**Type** Package

**Title** Dendrochronology Program Library in R

**Version** 1.6.8

**Date** 2018-05-22

**Author** Andy Bunn [aut, cph, cre, trl],  
Mikko Korpela [aut, cph, trl],  
Franco Biondi [aut, cph],  
Filipe Campelo [aut, cph],  
Pierre Mérian [aut, cph],  
Fares Qeadan [aut, cph],  
Christian Zang [aut, cph],  
Allan Buras [ctb],  
Jacob Cecile [ctb],  
Manfred Mudelsee [ctb],  
Michael Schulz [ctb],  
Darwin Pucha-Cofrep [aut, cph],  
Jakob Wernicke [aut, cph]

**Copyright** Authors and file inst/COPYRIGHTS

**Maintainer** Andy Bunn <andy.bunn@wwu.edu>

**Depends** R (>= 2.15.2)

**Imports** graphics, grDevices, grid, stats, utils, lattice (>= 0.13-6),  
Matrix (>= 1.0-3), digest (>= 0.2.3), matrixStats (>= 0.50.2),  
png (>= 0.1-2), R.utils (>= 1.32.1), stringi (>= 0.2-3),  
stringr (>= 0.4), XML (>= 2.1-0), plyr (>= 1.8), animation (>= 2.0-2)

**Suggests** Biobase, Cairo (>= 1.5-0), dichromat (>= 1.2-3), foreach,  
forecast (>= 3.6), gmp (>= 0.5-5), iterators, knitr,  
RColorBrewer, testthat (>= 0.8), tikzDevice, waveslim

**Description** Perform tree-ring analyses such as detrending, chronology building, and cross dating. Read and write standard file formats used in dendrochronology.

**LazyData** no

**License** GPL (>= 2)

**URL** <https://r-forge.r-project.org/projects/dplr/>

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2018-05-23 21:57:55 UTC

## R topics documented:

dpIR-package	4
anos1	4
bai.in	5
bai.out	7
ca533	9
cana157	9
ccf.series.rwl	10
chron	12
cms	13
co021	15
combine.rwl	16
common.interval	17
corr.rwl.seg	18
corr.series.seg	20
crn.plot	22
csv2rwl	24
detrend	26
detrend.series	28
ffcsaps	31
fill.internal.NA	33
gini.coef	35
glk	36
gp.d2pith	37
gp.dbh	38
gp.po	38
gp.rwl	39
hanning	40
i.detrend	41
i.detrend.series	42
insert.ring	43
interseries.cor	44
latexDate	45
latexify	46
morlet	48
net	50
plot.rwl	51
plotRings	52
po.to.wc	55

pointer . . . . .	56
powt . . . . .	58
print.redfit . . . . .	59
print.rwl.report . . . . .	60
rasterPlot . . . . .	61
rcs . . . . .	64
read.compact . . . . .	66
read.crn . . . . .	67
read.fh . . . . .	68
read.ids . . . . .	69
read.rwl . . . . .	72
read.tridas . . . . .	73
read.tucson . . . . .	80
redfit . . . . .	81
rwi.stats.running . . . . .	87
rwl.report . . . . .	91
rwl.stats . . . . .	92
sea . . . . .	94
seg.plot . . . . .	95
sens1 . . . . .	96
sens2 . . . . .	97
series.rwl.plot . . . . .	98
skel.plot . . . . .	100
spag.plot . . . . .	102
strip.rwl . . . . .	103
tbrm . . . . .	105
time.rwl . . . . .	106
treeMean . . . . .	107
tridas.vocabulary . . . . .	108
uuid.gen . . . . .	110
wa082 . . . . .	112
wavelet.plot . . . . .	112
wc.to.po . . . . .	115
write.compact . . . . .	116
write.crn . . . . .	117
write.rwl . . . . .	119
write.tridas . . . . .	120
write.tucson . . . . .	126
xskel.ccf.plot . . . . .	128
xskel.plot . . . . .	130

---

dpLR-package

*Dendrochronology Program Library in R*

---

### Description

This package contains functions for performing some standard tree-ring analyses.

### Details

Package: dpLR  
Type: Package  
License: GPL (>= 2)

#### *Main Functions*

[read.rwl](#) reads rwl files  
[detrend](#) detrends raw ring widths  
[chron](#) builds chronologies  
[corr.rwl.seg](#) crossdating function

### Author(s)

Andy Bunn <[andy.bunn@wwu.edu](mailto:andy.bunn@wwu.edu)> with major additions from Mikko Korpela and other significant contributions from Franco Biondi, Filipe Campelo, Pierre Mérian, Fares Qeadan and Christian Zang. Function [redfit](#) is an improved translation of program REDFIT which is original work of Manfred Mudelsee and Michael Schulz. Jacob Cecile contributed a bug fix to [detrend.series](#). Allan Buras came up with the revised formula of [glk](#) in dpLR >= 1.6.1.

### References

Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.  
Fritts, H. C. (2001) *Tree Rings and Climate*. Blackburn. ISBN-13: 978-1-930665-39-2.

---

anos1

*Rothenburg Tree Ring Widths*

---

### Description

This data set gives the raw ring widths for Norway spruce *Picea abies* at Rothenburg ob der Tauber, Bavaria, Germany. There are 20 series from 10 trees. Data set was created using [read.rwl](#) and saved to an `.rda` file using [save](#).

**Usage**

```
data(anos1)
```

**Format**

A `data.frame` containing 20 tree-ring series from 10 trees in columns and 98 years in rows. The correct `stc` mask for use with `read.ids` is `c(5, 2, 1)`.

**References**

Zang, C. (2010) *Growth reaction of temperate forest tree species to summer drought – a multispecies tree-ring network approach*. Ph.D. thesis, Technische Universität München.

---

bai.in	<i>Basal Area Increment (Inside Out)</i>
--------	--

---

**Description**

Convert multiple ring-width series to basal area increment (i.e., ring area) going from the pith to the bark.

**Usage**

```
bai.in(rwl, d2pith = NULL)
```

**Arguments**

rwl	a <code>data.frame</code> with series as columns and years as rows such as that produced by <code>read.rwl</code>
d2pith	an optional vector containing two variables. If present, then variable one (series in the example below) gives the series ID as either characters or factors. These must exactly match <code>colnames(rwl)</code> . Variable two ( <code>d2pith</code> in the example below) gives the distance from the innermost measured ring to the pith of the tree in mm. If <code>d2pith</code> is <code>NULL</code> then the distance to pith is assumed to be zero for each series (column) in <code>rwl</code> .

**Details**

This converts ring-width series (mm) to ring-area series (mm squared) (aka basal area increments) based on the distance between the innermost measured ring and the pith of the tree. It is related to `bai.out`, which calculates each ring area starting from the outside of the tree and working inward. Both methods assume a circular cross section (Biondi 1999). See the references below for further details.

**Value**

A `data.frame` containing the ring areas for each series with column names, row names and dimensions of `rwl`.

**Note**

DendroLab website: <http://dendrolab.org/>

**Author(s)**

Code by Andy Bunn based on work from DendroLab, University of Nevada Reno, USA. Patched and improved by Mikko Korpela.

**References**

Biondi, F. (1999) Comparing tree-ring chronologies and repeated timber inventories as forest monitoring tools. *Ecological Applications*, **9**(1), 216–227.

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

**See Also**

[bai.out](#)

**Examples**

```
library(graphics)
library(stats)
library(utils)
## Toy
n <- 100
## Make three fake tree-ring series to show that these funcs work on rwl objects
base.series <- 0.75 + exp(-0.2 * 1:n)
rwl <- data.frame(x1 = base.series + abs(rnorm(n, 0, 0.05)),
                 x2 = base.series + abs(rnorm(n, 0, 0.05)),
                 x3 = base.series + abs(rnorm(n, 0, 0.05)))

## The inside out method
foo <- bai.in(rwl = rwl)
## The outside in method
bar <- bai.out(rwl = rwl)

## Identical
head(bar)
head(foo)

## Use gp data
data(gp.rwl)
data(gp.d2pith)
foo <- bai.in(rwl = gp.rwl, d2pith = gp.d2pith)
foo.crn <- chron(foo)
yrs <- time(foo.crn)
plot(yrs, foo.crn[, 1], type = "n",
     xlab = "Year", ylab = expression(mm^2))
lines(yrs, foo.crn[, 1], col = "grey", lty = "dashed")
lines(yrs, ffcaps(foo.crn[, 1], nyrs = 32), col = "red", lwd = 2)
```

---

bai.out	<i>Basal Area Increment (Outside In)</i>
---------	--

---

### Description

Convert multiple ring-width series to basal area increment (i.e., ring area) going from the bark to the pith.

### Usage

```
bai.out(rwl, diam = NULL)
```

### Arguments

<code>rwl</code>	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a>
<code>diam</code>	an optional data.frame containing two variables. If present, variable one ( <i>series</i> in the example below) gives the series ID as either characters or factors. These must exactly match <code>colnames(rwl)</code> . Variable two ( <i>diam</i> in the example below) gives the diameter of the tree (in mm) up to the outermost ring (e.g., the diameter of the tree where the core was taken minus the thickness of the bark). If <i>diam</i> is NULL then the diameter is taken as twice the sum of the widths for each series (column) in <i>rwl</i> .

### Details

This converts ring-width series (mm) to ring-area series (mm squared) (aka basal area increments) based on the diameter of the tree and the width of each ring moving towards the pith of the tree. It is related to [bai.in](#), which calculates each ring area starting from the inside of the tree and working outward. Both methods assume a circular cross section (Biondi 1999). See the references below for further details.

### Value

A data.frame containing the ring areas for each series with column names, row names and dimensions of *rwl*.

### Note

DendroLab website: <http://dendrolab.org/>

### Author(s)

Code by Andy Bunn based on work from DendroLab, University of Nevada Reno, USA. Patched and improved by Mikko Korpela.

## References

Biondi, F. (1999) Comparing tree-ring chronologies and repeated timber inventories as forest monitoring tools. *Ecological Applications*, **9**(1), 216–227.

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

## See Also

[bai.in](#)

## Examples

```
library(graphics)
library(utils)
## Not run:
library(stats)
## Toy
n <- 100
## Make three fake tree-ring series to show that these funcs work on rwl objects
base.series <- 0.75 + exp(-0.2 * 1:n)
rwl <- data.frame(x1 = base.series + abs(rnorm(n, 0, 0.05)),
                 x2 = base.series + abs(rnorm(n, 0, 0.05)),
                 x3 = base.series + abs(rnorm(n, 0, 0.05)))

## The inside out method
foo <- bai.in(rwl = rwl)
## The outside in method
bar <- bai.out(rwl = rwl)

## Identical
head(bar)
head(foo)

## End(Not run)
## Use gp data
data(gp.rwl)
data(gp.dbh)
## dbh (minus the bark) from cm to mm
gp.dbh2 <- gp.dbh[, 1:2]
gp.dbh2[, 2] <- (gp.dbh[, 2] - gp.dbh[, 3]) * 10
bar <- bai.out(rwl = gp.rwl, diam = gp.dbh2)
bar.crn <- chron(bar)
yrs <- time(bar.crn)
plot(yrs, bar.crn[, 1], type = "n",
     xlab = "Year", ylab = expression(mm^2))
lines(yrs, bar.crn[, 1], col = "grey", lty = "dashed")
lines(yrs, ffcaps(bar.crn[, 1], nyrs = 32), col = "red", lwd = 2)
```



---

ca533

*Campito Mountain Tree Ring Widths*

---

### Description

This data set gives the raw ring widths for bristlecone pine *Pinus longaeva* at Campito Mountain in California, USA. There are 34 series. Data set was created using [read.rwl](#) and saved to an .rda file using [save](#).

### Usage

```
data(ca533)
```

### Format

A data.frame containing 34 tree-ring series in columns and 1358 years in rows.

### Source

International tree-ring data bank, Accessed on 27-August-2007 at <ftp://ftp.ncdc.noaa.gov/pub/data/paleo/treering/measurements/northamerica/usa/ca533.rwl>

### References

Graybill, D. A. and LaMarche, Jr., V. C. (1983) Campito Mountain Data Set. IGBP PAGES/World Data Center for Paleoclimatology Data Contribution Series 1983-CA533.RWL. NOAA/NCDC Paleoclimatology Program, Boulder, Colorado, USA.

---

cana157

*Twisted Tree Heartrot Hill Standard Chronology*

---

### Description

This data set gives the standard chronology for white spruce *Picea glauca* at Twisted Tree Heartrot Hill in Yukon, Canada. Data set was created using [read.crn](#) and saved to an .rda file using [save](#).

### Usage

```
data(cana157)
```

### Format

A data.frame containing the standard chronology in column one and the sample depth in column two. There are 463 years (1530–1992) in the rows.

**Source**

International tree-ring data bank, Accessed on 27-August-2007 at <ftp://ftp.ncdc.noaa.gov/pub/data/paleo/treering/chronologies/northamerica/canada/cana157.crn>

**References**

Jacoby, G., D'Arrigo, R. and Buckley, B. (1992) Twisted Tree Heartrot Hill Data Set. IGBP PAGES/World Data Center for Paleoclimatology Data Contribution Series 1992-CANA157.CRN. NOAA/NCDC Paleoclimatology Program, Boulder, Colorado, USA.

---

ccf.series.rwl	<i>Cross-Correlation between a Series and a Master Chronology</i>
----------------	---

---

**Description**

Computes cross-correlations between a tree-ring series and a master chronology built from a `rwl` object at user-specified lags and segments.

**Usage**

```
ccf.series.rwl(rwl, series, series.yrs = as.numeric(names(series)),
               seg.length = 50, bin.floor = 100, n = NULL,
               prewhiten = TRUE, biweight = TRUE, pcrit = 0.05,
               lag.max = 5, make.plot = TRUE,
               floor.plus1 = FALSE, ...)
```

**Arguments**

<code>rwl</code>	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
<code>series</code>	a numeric or character vector. Usually a tree-ring series. If the length of the value is 1, the corresponding column of <code>rwl</code> is selected (by name or position) as the series and ignored when building the master chronology. Otherwise, the value must be numeric.
<code>series.yrs</code>	a numeric vector giving the years of <code>series</code> . Defaults to <code>as.numeric(names(series))</code> . Ignored if <code>series</code> is an index to a column of <code>rwl</code> .
<code>seg.length</code>	an even integral value giving length of segments in years (e.g., 20, 50, 100 years).
<code>bin.floor</code>	a non-negative integral value giving the base for locating the first segment (e.g., 1600, 1700, 1800 AD). Typically 0, 10, 50, 100, etc.
<code>n</code>	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
<code>prewhiten</code>	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .
<code>biweight</code>	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .

<code>pcrit</code>	a number between 0 and 1 giving the critical value for the correlation test.
<code>lag.max</code>	an integral value giving the maximum lag at which to calculate the <code>ccf</code> .
<code>make.plot</code>	logical flag indicating whether to make a plot.
<code>floor.plus1</code>	logical flag. If TRUE, one year is added to the base location of the first segment (e.g., 1601, 1701, 1801 AD).
<code>...</code>	other arguments passed to plot.

## Details

This function calculates the cross-correlation function between a tree-ring series and a master chronology built from `rwl` looking at correlations lagged positively and negatively using `ccf` at overlapping segments set by `seg.length`. For instance, with `lag.max` set to 5, cross-correlations would be calculated at for each segment with the master lagged at  $k = -5:5$  years.

The cross correlations are calculated calling `ccf` as `ccf(x=series, y=master, lag.max=lag.max, plot=FALSE)`. Note that prior to `dplR` version 1.60, the master was set as `x` and the series as `y`. This was changed to be more in line with user expectations so that a missing ring in a series produces a positive lag in the plot rather than a negative lag. This structure of this call does put the plots at odds with Figure 3 in Bunn (2010) which is unfortunate.

Correlations are calculated for the first segment, then the second segment and so on. Correlations are only calculated for segments with complete overlap with the master chronology.

Each series (including those in the `rwl` object) is optionally detrended as the residuals from a `hanning` filter with weight `n`. The filter is not applied if `n` is NULL. Detrending can also be done via prewhitening where the residuals of an `ar` model are added to each series mean. This is the default. The master chronology is computed as the mean of the `rwl` object using `tbrm` if `biweight` is TRUE and `rowMeans` if not. Note that detrending typically changes the length of the series. E.g., a `hanning` filter will shorten the series on either end by `floor(n/2)`. The prewhitening default will change the series length based on the `ar` model fit. The effects of detrending can be seen with `series.rwl.plot`.

## Value

A list containing matrices `ccf` and `bins`. Matrix `ccf` contains the correlations between the series and the master chronology at the lags window given by `lag.max`. Matrix `bins` contains the years encapsulated by each bin.

## Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

## References

Bunn, A. G. (2010) Statistical and visual crossdating in R using the `dplR` library. *Dendrochronologia*, **28**(4), 251–258.

## See Also

`corr.rwl.seg`, `corr.series.seg`, `skel.plot`, `series.rwl.plot`

## Examples

```

library(utils)
data(co021)
dat <- co021
## Create a missing ring by deleting a year of growth in a random series
flagged <- dat$"641143"
flagged <- c(NA, flagged[-325])
names(flagged) <- rownames(dat)
dat$"641143" <- NULL
ccf.100 <- ccf.series.rwl(rwl = dat, series = flagged, seg.length = 100)
## Not run:
flagged2 <- co021$"641143"
names(flagged2) <- rownames(dat)
ccf.100.1 <- ccf.series.rwl(rwl = dat, seg.length = 100,
                           series = flagged2)
## Select series by name or column position
ccf.100.2 <- ccf.series.rwl(rwl = co021, seg.length = 100,
                           series = "641143")
ccf.100.3 <- ccf.series.rwl(rwl = co021, seg.length = 100,
                           series = which(colnames(co021) == "641143"))
identical(ccf.100.1, ccf.100.2) # TRUE
identical(ccf.100.2, ccf.100.3) # TRUE

## End(Not run)

```

---

chron

*Build Mean Value Chronology*

---

## Description

This function builds a mean value chronology, typically from a `data.frame` of detrended ring widths as produced by [detrend](#).

## Usage

```
chron(x, prefix = "xxx", biweight = TRUE, prewhiten = FALSE, ...)
```

## Arguments

<code>x</code>	a <code>data.frame</code> of ring widths with <code>rownames(x)</code> containing years and <code>colnames(x)</code> containing each series ID such as produced by <a href="#">read.rwl</a>
<code>prefix</code>	a character string with less than 4 characters. Defaults to "xxx"
<code>biweight</code>	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .
<code>prewhiten</code>	logical flag. If TRUE each series is whitened using <a href="#">ar</a> prior to averaging.
<code>...</code>	Arguments passed to <a href="#">ar</a> when <code>prewhiten</code> is TRUE. For example, use <code>aic</code> and <code>order.max</code> to control the order of the AR model.

**Details**

This either averages the rows of the `data.frame` using a mean or a robust mean (the so-called standard chronology) or can do so from the residuals of an AR process (the residual chronology).

**Value**

A `data.frame` with the standard chronology, residual chronology (if prewhitening was performed), and the sample depth.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**References**

Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.

Fritts, H. C. (2001) *Tree Rings and Climate*. Blackburn. ISBN-13: 978-1-930665-39-2.

**See Also**

[read.rwl](#), [detrend](#), [ar](#), [crn.plot](#)

**Examples**

```
library(graphics)
library(utils)
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
ca533.crn <- chron(ca533.rwi, prefix = "CAM")
plot(ca533.crn, xlab="Year", ylab="RWI")
## With residual chron
ca533.crn <- chron(ca533.rwi, prefix = "CAM", prewhiten = TRUE)
```

---

cms

*C-Method Standardization*

---

**Description**

Detrend multiple ring-width series simultaneously using the C-method.

**Usage**

```
cms(rwl, po, c.hat.t = FALSE, c.hat.i = FALSE)
```

## Arguments

<code>rw1</code>	a <code>data.frame</code> with series as columns and years as rows such as that produced by <code>read.rw1</code>
<code>po</code>	a <code>data.frame</code> containing two variables. Variable one ( <i>series</i> in the example below) gives the series ID as either characters or factors. These must exactly match <code>colnames(rw1)</code> . Variable two ( <i>pith.offset</i> in the example below) must be integral values and give the years from the beginning of the core to the pith (or center) of the tree.
<code>c.hat.t</code>	a logical indicating whether to export the C-curves for each tree by biological age.
<code>c.hat.i</code>	a logical indicating whether to export the expected ring widths for each series.

## Details

This method detrends and standardizes tree-ring series by calculating a growth curve based on constant annual basal area increment. The method is based on the “assumption that constant growth is expressed by a constant basal area increment distributed over a growing surface” (Biondi and Qeadan 2008). The detrending is the estimation and removal of the tree’s natural biological growth trend. The standardization is done by dividing each series by the growth trend to produce units in the dimensionless ring-width index (RWI).

This attempts to remove the low frequency variability that is due to biological or stand effects.

See the reference below for further details.

## Value

A `data.frame` containing the dimensionless and detrended ring-width indices with column names, row names and dimensions of `rw1` if `c.hat.t` is FALSE and `c.hat.i` is FALSE.

Otherwise a list of length 2 or 3 containing the RWI `data.frame`, a `data.frame` containing the C-curves for each tree (`c.hat.t`), and/or a vector containing the C-values for each tree (`c.hat.i`) depending on the output flags. See Eq. 12 in Biondi and Qeadan (2008) for more detail on `c.hat.t`, and `c.hat.i`.

## Note

DendroLab website: <http://dendrolab.org/>

## Author(s)

Code provided by DendroLab based on programming by F. Qeadan and F. Biondi, University of Nevada Reno, USA and adapted for `dplr` by Andy Bunn. Patched and improved by Mikko Korpela.

## References

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

**See Also**

[detrrend](#), [chron](#), [rccs](#)

**Examples**

```
library(graphics)
library(utils)
data(gp.rwl)
data(gp.po)
gp.rwi <- cms(rwl = gp.rwl, po = gp.po)
gp.crn <- chron(gp.rwi)
crn.plot(gp.crn, add.spline = TRUE)
## c.hat
gp.rwi <- cms(rwl = gp.rwl, po = gp.po, c.hat.t = TRUE, c.hat.i = TRUE)
dotchart(gp.rwi$c.hat.i, ylab = "Series", xlab = expression(hat(c)[i]))
tmp <- gp.rwi$c.hat.t
plot(tmp[, 1], type = "n", ylim = range(tmp, na.rm = TRUE),
      xlab = "Cambial Age", ylab = expression(hat(c)[t]))
apply(tmp, 2, lines)
```

---

co021

*Schulman Old Tree No. 1, Mesa Verde*


---

**Description**

This data set gives the raw ring widths for Douglas fir *Pseudotsuga menziesii* at Mesa Verde in Colorado, USA. There are 35 series. Data set was created using [read.rwl](#) and saved to an .rda file using [save](#).

**Usage**

```
data(co021)
```

**Format**

A data.frame containing 35 tree-ring series in columns and 788 years in rows.

**Source**

International tree-ring data bank, Accessed on 12-September-2011 at <ftp://ftp.ncdc.noaa.gov/pub/data/paleo/treering/measurements/northamerica/usa/co021.rwl>

**References**

Schulman, E. (1963) Schulman Old Tree No. 1 Data Set. IGBP PAGES/World Data Center for Paleoclimatology Data Contribution Series 1983-CO021.RWL. NOAA/NCDC Paleoclimatology Program, Boulder, Colorado, USA.

---

`combine.rwl`*Combine Tree-Ring Data Sets*

---

### Description

This function combines any number of `data.frames` of tree-ring data into one `data.frame`.

### Usage

```
combine.rwl(x, y = NULL)
```

### Arguments

<code>x</code>	either a <code>data.frame</code> to be combined with <code>y</code> , or a list of <code>data.frames</code> to be combined.
<code>y</code>	a <code>data.frame</code> to be combined with <code>data.frame x</code> .

### Details

The sequence of years in each `data.frame` must be increasing and continuous. The output produced by the function also fulfills this condition. If the input is differently formatted, the result will be wrong.

### Value

An object of class `c("rwl", "data.frame")` with the series in columns and the years as rows. The keycodes are the column names and the years are the row names.

### Author(s)

Christian Zang. Patched by Mikko Korpela.

### Examples

```
library(utils)
data(ca533)
data(co021)
combi1 <- combine.rwl(list(ca533, co021))
## or alternatively for data.frames to combine
combi2 <- combine.rwl(ca533, co021)
identical(combi1, combi2) # TRUE
```



---

common.interval	<i>Common Interval</i>
-----------------	------------------------

---

### Description

This function finds the common interval on a set of tree-ring widths such as that produced by [read.rwl](#).

### Usage

```
common.interval(rwl, type=c("series", "years", "both"),
               make.plot=TRUE)
```

### Arguments

rwl	a data.frame of ring widths with rownames(x) containing years and colnames(x) containing each series ID such as produced by <a href="#">read.rwl</a>
type	a character string of "series", "years", or "both". Argument matching is performed.
make.plot	a logical indicating if a plot should be drawn

### Details

This trims an rwl object to a common interval that maximizes the number of series (type="series"), the number of years (type="years"), or a compromise between the two (type="both"). A modified [seg.plot](#) can be drawn as well.

### Value

A data.frame with colnames(x) and rownames(x).

### Author(s)

Filipe Campelo, Andy Bunn and Mikko Korpela

### See Also

[seg.plot](#)

### Examples

```
library(utils)
data(co021)
co021.s <- common.interval(co021, type="series", make.plot=TRUE)
co021.y <- common.interval(co021, type="years", make.plot=TRUE)
co021.b <- common.interval(co021, type="both", make.plot=TRUE)

dim(co021)
```

```

dim.s <- dim(co021.s)
dim.s      # the highest number of series
prod(dim.s) # (33 series x 288 years = 9504)
dim.y <- dim(co021.y)
dim.y      # the highest number of years
prod(dim.y) # (27 series x 458 years = 12366)
dim.b <- dim(co021.b)
dim.b      # compromise solution
prod(dim.b) # (28 series x 435 years = 12180)

```

---

corr.rwl.seg

*Compute Correlations between Series*


---

### Description

Computes the correlation between each tree-ring series in a `rwl` object.

### Usage

```

corr.rwl.seg(rwl, seg.length = 50, bin.floor = 100, n = NULL,
             prewhiten = TRUE, pcrit = 0.05, biweight = TRUE,
             method = c("spearman", "pearson", "kendall"),
             make.plot = TRUE, label.cex = 1, floor.plus1 = FALSE,
             master = NULL,
             master.yrs = as.numeric(if (is.null(dim(master))) {
                                     names(master)
                                   } else {
                                     rownames(master)
                                   }
             )),
             ...)

```

### Arguments

<code>rwl</code>	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
<code>seg.length</code>	an even integral value giving length of segments in years (e.g., 20, 50, 100 years).
<code>bin.floor</code>	a non-negative integral value giving the base for locating the first segment (e.g., 1600, 1700, 1800 AD). Typically 0, 10, 50, 100, etc.
<code>n</code>	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
<code>prewhiten</code>	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .
<code>pcrit</code>	a number between 0 and 1 giving the critical value for the correlation test.
<code>biweight</code>	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .
<code>method</code>	Can be either "pearson", "kendall", or "spearman" which indicates the correlation coefficient to be used. Defaults to "spearman". See <a href="#">cor.test</a> .

<code>make.plot</code>	logical flag indicating whether to make a plot.
<code>label.cex</code>	numeric scalar for the series labels on the plot. Passed to <code>axis.cex</code> in <a href="#">axis</a> .
<code>floor.plus1</code>	logical flag. If TRUE, one year is added to the base location of the first segment (e.g., 1601, 1701, 1801 AD).
<code>master</code>	NULL, a numeric vector or a matrix-like object of numeric values, including a <code>data.frame</code> . If NULL, a number of master chronologies, one for each series in <code>rwl</code> , is built from <code>rwl</code> using the leave-one-out principle. If a vector, the function uses this as the master chronology. If a <code>matrix</code> or <code>data.frame</code> , this object is used for building the master chronology (no leave-one-out).
<code>master.yrs</code>	a numeric vector giving the years of <code>series</code> . Defaults to names or rownames of <code>master</code> coerced to numeric type.
<code>...</code>	other arguments passed to <code>plot</code> .

## Details

This function calculates correlation serially between each tree-ring series and a master chronology built from all the other series in the `rwl` object (leave-one-out principle). Optionally, the user may give a `master` chronology (a vector) as an argument. In the latter case, the same master chronology is used for all the series in the `rwl` object. The user can also choose to give a `master data.frame` (series as columns, years as rows), from which a single master chronology is built.

Correlations are done for each segment of the series where segments are lagged by half the segment length (e.g., 100-year segments would be overlapped by 50-years). The first segment is placed according to `bin.floor`. The minimum bin year is calculated as  $\text{ceiling}(\text{min.yr}/\text{bin.floor}) * \text{bin.floor}$  where `min.yr` is the first year in either the `rwl` object or the user-specified `master` chronology, whichever is smaller. For example if the first year is 626 and `bin.floor` is 100 then the first bin would start in 700. If `bin.floor` is 10 then the first bin would start in 630.

Correlations are calculated for the first segment, then the second segment and so on. Correlations are only calculated for segments with complete overlap with the master chronology. For now, correlations are Spearman's rho calculated via `cor.test` using `method = "spearman"`.

Each series (including those in the `rwl` object) is optionally detrended as the residuals from a [hanning](#) filter with weight `n`. The filter is not applied if `n` is NULL. Detrending can also be done via prewhitening where the residuals of an `ar` model are added to each series mean. This is the default. The master chronology is computed as the mean of the `rwl` object using `tbrm` if `biweight` is TRUE and `rowMeans` if not. Note that detrending can change the length of the series. E.g., a [hanning](#) filter will shorten the series on either end by  $\text{floor}(n/2)$ . The prewhitening default will change the series length based on the `ar` model fit. The effects of detrending can be seen with [series.rwl.plot](#).

The function is typically invoked to produce a plot where each segment for each series is colored by its correlation to the master chronology. Green segments are those that do not overlap completely with the width of the bin. Blue segments are those that correlate above the user-specified critical value. Red segments are those that correlate below the user-specified critical value and might indicate a dating problem.

## Value

A list containing matrices `spearman.rho`, `p.val`, `overall`, `bins`, vector `avg.seg.rho`. An additional character `flags` is also returned if any segments fall below the critical value. Matrix `spearman.rho`

contains the correlations for each series by bin. Matrix *p.val* contains the p-values on the correlation for each series by bin. Matrix *overall* contains the average correlation and p-value for each series. Matrix *bins* contains the years encapsulated by each bin. The vector *avg.seg.rho* contains the average correlation for each bin.

### Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

### See Also

[corr.series.seg](#), [skel.plot](#), [series.rwl.plot](#), [ccf.series.rwl](#)

### Examples

```
library(utils)
data(co021)
crs <- corr.rwl.seg(co021, seg.length = 100, label.cex = 1.25)
names(crs)
## Average correlation and p-value for the first few series
head(crs$overall)
## Average correlation for each bin
crs$avg.seg.rho
```

---

corr.series.seg	<i>Compute Correlation between a Series and a Master Chronology</i>
-----------------	---

---

### Description

Compute correlation between a tree-ring series and a master chronology by segment.

### Usage

```
corr.series.seg(rwl, series, series.yrs = as.numeric(names(series)),
               seg.length = 50, bin.floor = 100, n = NULL,
               prewhiten = TRUE, biweight = TRUE,
               method = c("spearman", "pearson", "kendall"),
               pcrit = 0.05,
               make.plot = TRUE, floor.plus1 = FALSE, ...)
```

### Arguments

<code>rwl</code>	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
<code>series</code>	a numeric or character vector. Usually a tree-ring series. If the length of the value is 1, the corresponding column of <code>rwl</code> is selected (by name or position) as the series and ignored when building the master chronology. Otherwise, the value must be numeric.

series.yrs	a numeric vector giving the years of <i>series</i> . Defaults to <code>as.numeric(names(series))</code> . Ignored if <i>series</i> is an index to a column of <i>rwl</i> .
seg.length	an even integral value giving length of segments in years (e.g., 20, 50, 100 years).
bin.floor	a non-negative integral value giving the base for locating the first segment (e.g., 1600, 1700, 1800 AD). Typically 0, 10, 50, 100, etc.
n	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
prewhiten	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .
biweight	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .
method	Can be either "pearson", "kendall", or "spearman" which indicates the correlation coefficient to be used. Defaults to "spearman". See <a href="#">cor.test</a> .
pcrit	a number between 0 and 1 giving the critical value for the correlation test.
make.plot	logical flag indicating whether to make a plot.
floor.plus1	logical flag. If TRUE, one year is added to the base location of the first segment (e.g., 1601, 1701, 1801 AD).
...	other arguments passed to plot.

### Details

This function calculates the correlation between a tree-ring series and a master chronology built from a *rwl* object. Correlations are done by segment (see below) and with a moving correlation with length equal to the *seg.length*. The function is typically invoked to produce a plot.

### Value

A list containing matrices *bins*, *moving.rho*, and vectors *spearman.rho*, *p.val*, and *overall*.

Matrix *bins* contains the years encapsulated by each bin (segments). Matrix *moving.rho* contains the moving correlation and p-value for a moving average equal to *seg.length*. Vector *spearman.rho* contains the correlations by bin and *p.val* contains the p-values. Vector *overall* contains the average correlation and p-value.

### Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

### See Also

[corr.series.seg](#), [skel.plot](#), [series.rwl.plot](#), [ccf.series.rwl](#)

### Examples

```
library(utils)
data(co021)
dat <- co021
## Create a missing ring by deleting a year of growth in a random series
flagged <- dat$"641143"
```

```

flagged <- c(NA, flagged[-325])
names(flagged) <- rownames(dat)
dat$"641143" <- NULL
seg.100 <- corr.series.seg(rwl = dat, series = flagged,
                          seg.length = 100, biweight = FALSE)

## Not run:
flagged2 <- co021$"641143"
names(flagged2) <- rownames(dat)
seg.100.1 <- corr.series.seg(rwl=dat, seg.length=100, biweight=FALSE,
                             series = flagged2)
## Select series by name or column position
seg.100.2 <- corr.series.seg(rwl=co021, seg.length=100, biweight=FALSE,
                             series = "641143")
seg.100.3 <- corr.series.seg(rwl=co021, seg.length=100, biweight=FALSE,
                             series = which(colnames(co021) == "641143"))
identical(seg.100.1, seg.100.2) # TRUE
identical(seg.100.2, seg.100.3) # TRUE

## End(Not run)

```

---

crn.plot

*Plot a Tree-Ring Chronology*


---

## Description

This function makes a default plot of a tree-ring chronology from a data.frame of the type produced by [chron](#).

## Usage

```

crn.plot(crn, add.spline = FALSE, nyrs = NULL, f = 0.5,
         crn.line.col='grey50', spline.line.col='red',
         samp.depth.col='grey90',
         samp.depth.border.col='grey80',
         crn.lwd=1, spline.lwd=1.5,
         abline.pos=1, abline.col='black',
         abline.lty=1, abline.lwd=1,
         xlab="Time", ylab="RWI", ...)

```

```

## S3 method for class 'crn'
plot(x, ...)

```

## Arguments

**x**, **crn** a data.frame e.g., as produced by [chron](#). The data.frame should have the years in `rownames(crn)`, the chronologies in the columns. Optionally, the last column can contain the sample depth named "samp.depth". If the data are produced via [chron](#) the object will be of class "crn" and the generic plot method can be used

<code>add.spline</code>	a logical flag. Will add a line with a smoothing spline using <a href="#">ffcsaps</a>
<code>nyrs</code>	a number giving the rigidity of the smoothing spline. Defaults to 0.33 times the length of the first chronology if <code>nyrs</code> is NULL
<code>f</code>	a number between 0 and 1 giving the frequency response or wavelength cutoff. Defaults to 0.5
<code>crn.line.col</code>	color for the x line
<code>spline.line.col</code>	color for the spline (if added)
<code>samp.depth.col</code>	color for the sample depth polygon (if present)
<code>samp.depth.border.col</code>	border color for the sample depth polygon (if present)
<code>crn.lwd</code>	line width for the x line
<code>spline.lwd</code>	line width for the spline (if added)
<code>abline.pos</code>	position for a reference abline on the y-axis. No line added if NULL
<code>abline.col</code>	color for the reference abline (if added)
<code>abline.lty</code>	line type the reference abline (if added)
<code>abline.lwd</code>	line width for the reference abline (if added)
<code>xlab</code>	default label for x axis
<code>ylab</code>	default label for y axis
<code>...</code>	Additional arguments to pass to <a href="#">plot</a> . The scale of the secondary y axis (sample depth) can be controlled with argument <code>ylim2</code> .

### Details

This makes a plot of one or more tree-ring chronologies.

### Value

None. Invoked for side effect (plot).

### Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

### See Also

[chron](#)

### Examples

```
library(graphics)
library(utils)
data(cana157)
crn.plot(cana157)
plot(cana157, main='Twisted Tree Heartrot Hill')
# with added spline
```

```

crn.plot(cana157,add.spline=TRUE, nyrs=32)
## Without sample depth
cana157.mod <- cana157
cana157.mod$samp.depth <- NULL
crn.plot(cana157.mod, add.spline = TRUE)
## A raw ring-width chronology
data(ca533)
ca533.raw.crn <- chron(ca533, prefix = "CAM", prewhiten=TRUE)
plot(ca533.raw.crn,abline.pos=NULL,ylab='mm')

## Not run:
# not pretty - but illustrates the coloring options
my.cols <- c("#3182BD", "#9ECAE1", "#DEEBF7", "#31A354", "#A1D99B", "#E5F5E0")
crn.plot(cana157,add.spline=TRUE,nyrs=32,
         crn.line.col=my.cols[5],
         spline.line.col=my.cols[4],
         samp.depth.col=my.cols[3],
         samp.depth.border.col=my.cols[2],
         abline.col=my.cols[1],
         crn.lwd=1.5,spline.lwd=3,
         abline.lwd=1,
         xlab="Year", ylab="RWI")

## End(Not run)

```

---

csv2rwl

*Read Ring Width File from CSV*


---

## Description

This function reads in a file of ring widths (.rwl) from a text file with comma separated values (csv).

## Usage

```
csv2rwl(fname, ...)
```

## Arguments

fname	a character vector giving the file name of the csv file.
...	other arguments passed to <a href="#">read.table</a> .

## Details

This is a simple wrapper to [read.table](#) that reads in a text file with ring-width data in "spreadsheet" format. I.e., with series in columns and the the years as rows. The first column should contain the years and each subsequent column should contain a tree-ring series. The series names should be in the first row of the file. The default for NA values are empty cells or as the character string "NA" but can also be set using the na.strings argument passed to [read.table](#). E.g.,:



Year	Ser1A	Ser1B	Ser2A	Ser2B
1901	NA	0.45	0.43	0.24
1902	NA	0.05	0.00	0.07
1903	0.17	0.46	0.03	0.21
1904	0.28	0.21	0.54	0.41
1905	0.29	0.85	0.17	0.76
1906	0.56	0.64	0.56	0.31
1907	1.12	1.06	0.99	0.83
etc...				

Note that this is a rudimentary convenience function that isn't doing anything sophisticated. It reads in a file, assigns the years to the row names and sets the class of the object to `c("rwl", "data.frame")` which allows `dp1R` to recognize it.

Although arguments can be passed to `read.table`, this is not designed to be a flexible function. As is the philosophy with `dp1R`, modifying the code is easy should the user wish to read in a different style of text file (e.g., tab delimited). Typing `csv2rwl` at the R prompt will get the user started.

### Value

Function returns an object of class `c("rwl", "data.frame")` with the series in columns and the years as rows. The series IDs are the column names and the years are the row names.

### Author(s)

Andy Bunn

### See Also

[read.rwl](#), [read.table](#)

### Examples

```
library(utils)
data(ca533)
# write out a rwl file in a format that csv2rwl will understand
tm <- time(ca533)
foo <- data.frame(tm,ca533)
# this is the temp file where foo will be written
tmpName <- tempfile()
write.csv(foo,file=tmpName,row.names=FALSE)
# read it back in using csv2rwl
bar <- csv2rwl(tmpName)
# check to see if identical
identical(ca533,bar)
# delete temp file
unlink(tmpName)
```

detrend

*Detrend Multiple Ring-Width Series Simultaneously***Description**

This is a wrapper for [detrend.series](#) to detrend many ring-width series at once.

**Usage**

```
detrend(rwl, y.name = names(rwl), make.plot = FALSE,
        method = c("Spline", "ModNegExp", "Mean", "Ar", "Friedman"),
        nyrs = NULL, f = 0.5, pos.slope = FALSE,
        constrain.modnegexp = c("never", "when.fail", "always"),
        verbose = FALSE, return.info = FALSE,
        wt, span = "cv", bass = 0)
```

**Arguments**

<code>rwl</code>	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a>
<code>y.name</code>	a character vector of length(ncol( <i>rwl</i> )) that gives the ID of each series. Defaults to the column names of <i>rwl</i> .
<code>make.plot</code>	a logical flag. Makes plots of the raw data and detrended data if TRUE. See details below.
<code>method</code>	a character vector to determine the detrending methods. See details below. Possible values are all subsets of c("Spline", "ModNegExp", "Mean", "Ar", "Friedman"). Defaults to using all the available methods.
<code>nyrs</code>	a number giving the rigidity of the smoothing spline, defaults to 0.67 of series length if <i>nyrs</i> is NULL.
<code>f</code>	a number between 0 and 1 giving the frequency response or wavelength cutoff. Defaults to 0.5.
<code>pos.slope</code>	a logical flag. Will allow for a positive slope to be used in method "ModNegExp". If FALSE the line will be horizontal.
<code>constrain.modnegexp</code>	a character string which controls the constraints of the "ModNegExp" model. See <a href="#">detrend.series</a> for further details.
<code>verbose</code>	logical. Write out details?
<code>return.info</code>	a logical flag. If TRUE, details about models and data will be added to the return value. See 'Value'.
<code>wt</code>	a numeric vector of case weights for method "Friedman". The default means equals weights.
<code>span</code>	a numeric value controlling method "Friedman", or "cv" (default) for automatic choice by cross-validation. See <a href="#">supsmu</a> .
<code>bass</code>	a numeric value controlling the smoothness of the fitted curve in method "Friedman". See <a href="#">supsmu</a> .

**Details**

See [detrend.series](#) for details on detrending methods. Setting `make.plot = TRUE` will cause plots of each series to be produced. These could be saved using [Devices](#) if desired.

**Value**

If one detrending method is used, a `data.frame` containing the dimensionless detrended ring widths with column names, row names and dimensions of `rwl`. If more methods are used, a list with `ncol(rwl)` elements each containing a `data.frame` with the detrended ring widths in each column.

If `return.info` is `TRUE`, the return value is a list with three parts:

<code>series</code>	the main result described above ( <code>data.frame</code> or list of <code>data.frames</code> )
<code>model.info</code>	Information about the models corresponding to each output series. A list with one element for each column of <code>rwl</code> . See <a href="#">detrend.series</a> ('Value', <code>model.info</code> ) for a description of the contents.
<code>data.info</code>	Information about the input series. A list with one element for each column of <code>rwl</code> . See <a href="#">detrend.series</a> ('Value', <code>data.info</code> ).

**Note**

This function uses the [foreach](#) looping construct with the `%dopar%` operator. For parallel computing and a potential speedup, a parallel backend must be registered before running the function. If `verbose` is `TRUE`, parallel computation is disabled.

**Author(s)**

Andy Bunn. Improved by Mikko Korpela.

**See Also**

[detrend.series](#)

**Examples**

```
library(utils)
data(ca533)
## Detrend using modified exponential decay. Returns a data.frame
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")

## Not run:
library(grDevices)
## Detrend using all methods. Returns a list
ca533.rwi <- detrend(rwl = ca533)
## Save a pdf of all series
fname <- tempfile(fileext=".pdf")
print(fname) # tempfile used for output
pdf(fname)
ca533.rwi <- detrend(rwl = ca533, method = c("Spline", "ModNegExp"),
                    make.plot = TRUE)
dev.off()
```

```

unlink(fname) # remove the file

## End(Not run)

```

---

detrend.series      *Detrend a Ring-Width Series*

---

## Description

Detrend a tree-ring series by one of two methods, a smoothing spline or a statistical model. The series and fits are plotted by default.

## Usage

```

detrend.series(y, y.name = "", make.plot = TRUE,
               method = c("Spline", "ModNegExp", "Mean", "Ar", "Friedman"),
               nyrs = NULL, f = 0.5, pos.slope = FALSE,
               constrain.modnegexp = c("never", "when.fail", "always"),
               verbose = FALSE, return.info = FALSE,
               wt, span = "cv", bass = 0)

```

## Arguments

y	a numeric vector. Usually a tree-ring series.
y.name	an optional character vector to name the series for plotting purposes.
make.plot	a logical flag. Makes plots of the raw data and detrended data if TRUE.
method	a character vector to determine the detrending methods. See details below. Possible values are all subsets of c("Spline", "ModNegExp", "Mean", "Ar", "Friedman"). Defaults to using all the available methods.
nyrs	a number controlling the smoothness of the fitted curve in method "Spline", defaults to 0.67 of series length if nyrs is NULL. See <a href="#">ffcsaps</a> .
f	a number between 0 and 1 giving the frequency response or wavelength cutoff in method "Spline". Defaults to 0.5. See <a href="#">ffcsaps</a> .
pos.slope	a logical flag. Will allow for a positive slope to be used in method "ModNegExp". If FALSE the line will be horizontal.
constrain.modnegexp	a character string which controls the constraints of the "ModNegExp" model. The value is an answer to the question: When should the parameters of the modified negative exponential function be constrained? The options are "never": do not constrain (the default), "when.fail": only compute the constrained solution if the unconstrained fit contains other than positive values, and "always": return the constrained solution, even if the unconstrained one would have been valid. See 'Details'.
verbose	a logical flag. Write out details?

return.info	a logical flag. If TRUE, details about models and data will be added to the return value. See ‘Value’.
wt	a numeric vector of case weights for method "Friedman". The default means equals weights.
span	a numeric value controlling method "Friedman", or "cv" (default) for automatic choice by cross-validation. See <a href="#">supsmu</a> .
bass	a numeric value controlling the smoothness of the fitted curve in method "Friedman". See <a href="#">supsmu</a> .

## Details

This detrends and standardizes a tree-ring series. The detrending is the estimation and removal of the tree’s natural biological growth trend. The standardization is done by dividing each series by the growth trend to produce units in the dimensionless ring-width index (RWI). There are currently three methods available for detrending although more are certainly possible. The methods implemented are a smoothing spline via [ffcsaps](#) (*method* = "Spline"), a modified negative exponential curve (*method* = "ModNegExp"), or a simple horizontal line (*method* = "Mean").

The "Spline" approach uses a spline where the frequency response is 0.50 at a wavelength of 0.67 \* "series length in years", unless specified differently using *nyrs* and *f* in the function [ffcsaps](#). This attempts to remove the low frequency variability that is due to biological or stand effects.

The "ModNegExp" approach attempts to fit a classic nonlinear model of biological growth of the form  $f(t) = ae^{bt} + k$ , where the argument of the function is time, using [nls](#). See Fritts (2001) for details about the parameters. Option *constrain.modnegexp* gives a possibility to constrain the parameters of the modified negative exponential function. If the constraints are enabled, the nonlinear optimization algorithm is instructed to keep the parameters in the following ranges:  $a \geq 0$ ,  $b \leq 0$  and  $k \geq 0$ . The default is to not constrain the parameters (*constrain.modnegexp* = "never") for [nls](#) but warn the user when the parameters go out of range.

If a suitable nonlinear model cannot be fit (function is non-decreasing or some values are not positive) then a linear model is fit. That linear model can have a positive slope unless *pos.slope* is FALSE in which case method "Mean" is used.

The "Mean" approach fits a horizontal line using the mean of the series. This method is the fallback solution in cases where the "Spline" or the linear fit (also a fallback solution itself) contains zeros or negative values, which would lead to invalid ring-width indices.

The "Ar" approach is also known as prewhitening where the detrended series is the residuals of an [ar](#) model divided by the mean of those residuals to yield a series with white noise and a mean of one. This method removes all but the high frequency variation in the series and should only be used as such.

These methods are chosen because they are commonly used in dendrochronology. There is a rich literature on detrending and many researchers are particularly skeptical of the use of the classic nonlinear model of biological growth ( $f(t) = ae^{bt} + k$ ) for detrending. It is, of course, up to the user to determine the best detrending method for their data.

See the references below for further details on detrending.

The "Friedman" approach uses Friedman’s ‘super smoother’ as implemented in [supsmu](#). The parameters *wt*, *span* and *bass* can be adjusted, but *periodic* is always set to FALSE.

**Value**

If several methods are used, returns a `data.frame` containing the detrended series ( $y$ ) according to the methods used. The columns are named and ordered to match `method`. If only one method is selected, returns a vector.

If `return.info` is TRUE, the return value is a list with three parts:

<code>series</code>	the main result described above ( <code>data.frame</code> or vector)
<code>model.info</code>	Information about the models corresponding to each output series. Whereas <code>series</code> may return a vector, <code>model.info</code> is always a list where each top level element corresponds to one selected method. Also these elements are named and arranged according to the methods selected. Each element is a list with some of the following sub-elements, depending on which detrending method was actually used: <b>n.zeros</b> See "data.info" below. Always present. <b>zero.years</b> See "data.info". Always present. <b>method</b> The method actually used for detrending. One of "Mean", "Line", "ModNegExp", "Spline" or "Ar". Always present. <b>mean</b> Mean of the input series, missing values removed. Only for method "Mean". <b>coefs</b> Coefficients of the model. Methods "Line" and "ModNegExp". <b>formula</b> The "ModNegExp" <a href="#">formula</a> . <b>is.constrained</b> A logical flag indicating whether the parameters of the "ModNegExp" model were constrained. Only interesting when argument <code>constrain.modnegexp</code> is set to "when.fail". <b>nyrs</b> The value of <code>nyrs</code> used for <code>ffcsaps</code> . Only for method "Spline". <b>order</b> The order of the autoregressive model, selected by AIC (Akaike information criterion). Only for method "Ar". <b>ar</b> The autoregressive coefficients used by method "Ar". A numeric vector ordered by increasing lag.
<code>data.info</code>	Information about the input series: number ("n.zeros") and location ("zero.years") of zero values. If the locations are in a character vector, they are years. Otherwise they are indices to the input series.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela. A bug fix related to negative output values is based on work by Jacob Cecile.

**References**

Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.

Fritts, H. C. (2001) *Tree Rings and Climate*. Blackburn. ISBN-13: 978-1-930665-39-2.

**See Also**

[detrend](#)

**Examples**

```

library(stats)
library(utils)
## Using a plausible representation of a tree-ring series
gt <- 0.5 * exp (-0.05 * 1:200) + 0.2
noise <- c(arima.sim(model = list(ar = 0.7), n = 200, sd = 0.5))+2
series <- gt * noise
series.rwi <- detrend.series(y = series, y.name = "Foo", verbose=TRUE)
## Use series CAM011 from the Campito data set
data(ca533)
series <- ca533[, "CAM011"]
names(series) <- rownames(ca533)
# defaults to all five methods
series.rwi <- detrend.series(y = series, y.name = "CAM011", verbose=TRUE)
# see plot with three methods
series.rwi <- detrend.series(y = series, y.name = "CAM011",
                             method=c("Spline", "ModNegExp", "Friedman"))
# see plot with two methods
# interesting to note difference from ~200 to 250 years
# in terms of what happens to low frequency growth
series.rwi <- detrend.series(y = series, y.name = "CAM011",
                             method=c("Spline", "ModNegExp"))
# see plot with just one method and change the spline
# stiffness to 50 years (which is not necessarily a good choice!)
series.rwi <- detrend.series(y = series, y.name = "CAM011",
                             method="Spline",nyrs=50)
# note that method "Ar" doesn't get plotted in first panel
# since this approach doesn't approximate a growth curve.
series.rwi <- detrend.series(y = series, y.name = "CAM011",
                             method="Ar")

```

ffcsaps

*Smoothing Spline with User-Specified Rigidity and Frequency Cutoff***Description**

Applies a smoothing spline to  $y$  with rigidity determined by two parameters: frequency response  $f$  at a wavelength of  $nyrs$  years.

**Usage**

```
ffcsaps(y, x = seq_along(y), nyrs = length(y)/2, f = 0.5)
```

**Arguments**

$y$	a numeric vector, typically a tree-ring series.
$x$	a numeric vector with the same length as $y$ , typically giving the years of $y$ .
$nyrs$	a number greater than 1, affecting the rigidity of the spline. When $f$ is kept constant, a larger $nyrs$ produces a more rigid spline. Defaults to $\text{length}(y)/2$ .

$f$  a number between 0 and 1 giving the frequency response at a wavelength of  $nyrs$  years. When  $nyrs$  is kept constant, a smaller  $f$  produces a more rigid spline: At one extreme,  $f = 0$  causes the function to return the least-squares straight line fit to the data. At the other extreme,  $f = 1$  results in the natural spline, i.e. the function outputs  $y$ . The default value is 0.5.

### Details

This applies a smoothing spline similar to the spline applied in most dendrochronological software. See references for more information. See ‘Examples’ for a pointer to a PDF document including mathematical details about the function.

### Value

A filtered vector.

### Note

DendroLab website: <http://dendrolab.org/>

### Author(s)

Code provided by DendroLab based on programming by F. Qeadan and F. Biondi, University of Nevada Reno, USA and adapted for dplR by Andy Bunn. Patched and improved by Mikko Korpela.

### References

Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.

### See Also

[hanning](#), [detrrend](#)

### Examples

```
library(graphics)
library(utils)
docFile <- system.file("doc", "math-dplR.pdf", package="dplR")
cat("See the following PDF for mathematical details:\n")
cat(docFile, sep="\n")
## Not run:
if (interactive() && requireNamespace("Biobase")) {
  Biobase::openPDF(docFile)
}
## Use series CAM011 from the Campito data set
data(ca533)
series <- ca533[, "CAM011"]
series <- series[!is.na(series)]
plot(series, type = "l", ylab = "Ring Width (mm)", col = "grey")
lines(ffcsaps(series, nyrs = 32), col = "red", lwd = 2)
```



```

lines(ffcsaps(series, nyrs = 64), col = "green", lwd = 2)
lines(ffcsaps(series, nyrs = 128), col = "blue", lwd = 2)

## End(Not run)
## Use first series from the Mesa Verde data set
data(co021)
series <- co021[, 1]
series <- series[!is.na(series)]
plot(series, type = "l", ylab = "Ring Width (mm)", col = "grey")
lines(ffcsaps(series, nyrs = 32), col = "red", lwd = 2)
lines(ffcsaps(series, nyrs = 64), col = "green", lwd = 2)
## nyrs defaults to 0.5*length(series) == 347
lines(ffcsaps(series), col = "blue", lwd = 2)
legend("topright",
      c("Series", "nyrs=32", "nyrs=64",
        paste("Default nyrs (", length(series) / 2, ")", sep="")),
      fill=c("grey", "red", "green", "blue"))

```

---

fill.internal.NA

*Fill Internal NA*


---

## Description

This function fills internal NA values (i.e., those with numeric data above and below a small data gap) in each column of a data.frame such as a data set of ring widths as produced by [read.rwl](#).

## Usage

```
fill.internal.NA(x, fill = c("Mean", "Spline", "Linear"))
```

## Arguments

x	a data.frame of ring widths with row.names(x) containing years and names(x) containing each series ID such as produced by <a href="#">read.rwl</a>
fill	a numeric value (e.g., 0) or a character string of "Mean", "Spline", or "Linear". Defaults to "Mean".

## Details

There are occasionally data gaps within a tree-ring series. Some of the functions in `dpLR` will fail when an internal NA is encountered (e.g. [ffcsaps](#)). This function fills internal NA values with either a given numeric value (e.g., 0) or through crude imputation. The latter can be calculated as the mean of the series (`fill="Mean"`) or calculated by fitting a cubic spline (`fill="Spline"`) using the [spline](#) function or calculated by linear approximation (`fill="Linear"`) using the function [approx](#).

Editorial: Having internal NA in a tree-ring series is often bad practice and filling those values should be done with caution. For instance, some users code missing rings as NA instead of 0. And missing values (i.e., NA) are sometimes present in maximum latewood density data when the rings are small.

A common, but not recommended, practice is to leave stretches of NA values in places where it has been impossible to accurately measure rings (perhaps because of a break in the core). It is often better to treat that core as two separate series (e.g., "01A" and "01B" rather than have internal NA values. As with all processing, the analyst should make a decision based on their experience with the wood and not rely on software to make a choice for them!

### Value

A data.frame with `colnames(x)` and `rownames(x)`. Internal NAs filled as above.

### Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

### See Also

[spline](#), [approx](#)

### Examples

```
library(graphics)
library(stats)
foo <- data.frame(x1=c(rnorm(5), NA, NA, rnorm(3)),
                 x2=c(rnorm(10)),
                 x3=c(NA, NA, rnorm(3), NA, rnorm(4)),
                 x4=c(NA, NA, rnorm(3), NA, rnorm(3), NA),
                 x5=c(NA, NA, rnorm(8)),
                 x6=c(NA, rnorm(9)),
                 x7=c(NA, rnorm(5), NA, rnorm(3)),
                 x8=c(rnorm(8), NA, NA),
                 x9=c(rnorm(5), NA, rnorm(3), NA))
row.names(foo) <- 1901:1910
class(foo) <- c("rwl", "data.frame")
fill.internal.NA(foo, fill=0)

bar <- fill.internal.NA(foo, fill="Spline")
baz <- fill.internal.NA(foo, fill="Linear")

## note differences in method "Spline" vs. "Linear"
yrs <- time(foo)
plot(yrs, foo$x7, type="b", lwd=3)
lines(yrs, bar$x7, col="red", lwd=2)
lines(yrs, baz$x7, col="green", lwd=1)
```

---

gini.coef	<i>Calculate the Gini Coefficient</i>
-----------	---------------------------------------

---

**Description**

This function calculates the Gini coefficient on raw or detrended ring-width series.

**Usage**

```
gini.coef(x)
```

**Arguments**

x                    a numeric vector

**Details**

This calculates the Gini coefficient of inequality which is used as an all-lag measure of diversity in tree-ring records – typically detrended series. Lower values indicate lower diversity. The use of the Gini coefficient in dendrochronology is described by Biondi and Qeadan (2008). See Hancock and Morris (1999) for more information. See ‘Examples’ for a pointer to a PDF document including mathematical details about the function.

**Value**

the Gini coefficient.

**Author(s)**

Mikko Korpela, based on original by Andy Bunn

**References**

- Biondi, F. and Qeadan, F. (2008) Inequality in Paleorecords. *Ecology*, **89**(4), 1056–1067.
- Hancock, M. S. and Morris, M. (1999) *Relative Distribution Methods in the Social Sciences*. Springer. ISBN: 0-387-98778-9.

**See Also**

[rwl.stats](#)

**Examples**

```

docFile <- system.file("doc", "math-dplR.pdf", package="dplR")
cat("See the following PDF for mathematical details:\n")
cat(docFile, sep="\n")
## Not run:
if (interactive() && requireNamespace("Biobase")) {
  Biobase::openPDF(docFile)
}
## End(Not run)
library(utils)
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
ca533.crn <- chron(ca533.rwi, prefix = "CAM")
gini.coef(ca533.crn)

```

glk

*Calculate Gleichläufigkeit***Description**

This function calculates the matrix of Gleichläufigkeit for a given set of tree-ring records.

**Usage**

```
glk(x)
```

**Arguments**

`x` a data.frame of tree-ring data with records in columns, and years as rows.

**Details**

Gleichläufigkeit is a classical agreement test based on sign tests (Eckstein and Bauch, 1969). This function implements Gleichläufigkeit as the pairwise comparison of all records in data set, and thus returns a matrix whose upper triangle reports the Gleichläufigkeit of each possible combination of records. The global Gleichläufigkeit can be calculated as `mean(glk(x), na.rm = TRUE)`. This implementation improves the original formulation inasmuch as the case of neighbouring identical measurements in the same years is accounted for. Here, it is treated as full agreement, in contrast to only partial agreement in the original formulation.

**Value**

A matrix with the Gleichläufigkeit for all possible combinations of records. If two curves have less than 3 years of overlap, Gleichläufigkeit cannot be computed, and NA is returned.

**Author(s)**

Christian Zang. Patched and improved by Mikko Korpela. Improved by Allan Buras.

## References

Eckstein, D. and Bauch, J. (1969) Beitrag zur Rationalisierung eines dendrochronologischen Verfahrens und zur Analyse seiner Aussagesicherheit. *Forstwissenschaftliches Centralblatt*, **88**(1), 230–250.

Schweingruber, F. H. (1988) *Tree rings: basics and applications of dendrochronology*. Kluwer Academic Publishers, Dordrecht, Netherlands, 276 p.

## Examples

```
library(utils)
data(ca533)
ca533.glk <- glk(ca533)
mean(ca533.glk, na.rm = TRUE)
```

---

gp.d2pith

*Ponderosa Pine Distance to Pith Corresponding to [gp.rwl](#)*

---

## Description

This data set gives the distance to pith for each series (in mm) that matches the ring widths for [gp.rwl](#) – a data set of ponderosa pine (*Pinus ponderosa*) from the Gus Pearson Natural Area (GPNA) in northern Arizona, USA. Data are further described by Biondi and Qeadan (2008) and references therein.

## Usage

```
data(gp.d2pith)
```

## Format

A data frame containing series IDs in column 1 (*series*) and the distance (in mm) from the innermost ring to the pith of the tree (*d2pith*). This can be used together with the ring widths to calculate the area of each ring.

## Source

DendroLab, University of Nevada Reno, USA. <http://dendrolab.org/>

## References

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

---

gp.dbh

*Ponderosa Pine Stem Diameters and Bark Thickness* ([gp.rwl](#))

---

### Description

This data set gives the diameter at breast height for each series that matches the series in [gp.rwl](#) – a data set of ponderosa pine (*Pinus ponderosa*) from the Gus Pearson Natural Area (GPNA) in northern Arizona, USA. Data are further described by Biondi and Qeadan (2008) and references therein.

### Usage

```
data(gp.dbh)
```

### Format

A data.frame containing series IDs in column 1 (*series*), tree diameter (in cm) at breast height (*dbh*), and the bark thickness (in cm). This can be used together with the ring widths to calculate the area of each ring.

### Source

DendroLab, University of Nevada Reno, USA. <http://dendrolab.org/>

### References

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

---

gp.po

*Ponderosa Pine Pith Offsets Corresponding to* [gp.rwl](#)

---

### Description

This data set gives the pith offsets that match the ring widths for [gp.rwl](#) – a data set of ponderosa pine (*Pinus ponderosa*) from the Gus Pearson Natural Area (GPNA) in northern Arizona, USA. Data are further described by Biondi and Qeadan (2008) and references therein.

### Usage

```
data(gp.po)
```

### Format

A data.frame containing series IDs in column 1 (*series*) and the number of years between the beginning of that series in [gp.rwl](#) and the pith of the tree (*pith.offset*). This can be used together with the ring widths to calculate the cambial age of each ring.

**Source**

DendroLab, University of Nevada Reno, USA. <http://dendrolab.org/>

**References**

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

---

gp.rwl

*Ponderosa Pine Ring Widths from Gus Pearson Natural Area*

---

**Description**

This data set includes ring-width measurements for ponderosa pine (*Pinus ponderosa*) increment cores collected at the Gus Pearson Natural Area (GPNA) in northern Arizona, USA. There are 58 series from 29 trees (2 cores per tree). Data are further described by Biondi and Qeadan (2008) and references therein.

**Usage**

```
data(gp.rwl)
```

**Format**

A data.frame containing 58 ring-width series in columns and 421 years in rows.

**Source**

DendroLab, University of Nevada Reno, USA. <http://dendrolab.org/>

**References**

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

---

hanning	<i>Hanning Filter</i>
---------	-----------------------

---

**Description**

Applies a Hanning filter of length  $n$  to  $x$ .

**Usage**

```
hanning(x, n = 7)
```

**Arguments**

$x$	a vector
$n$	length of the Hanning filter, defaults to 7

**Details**

This applies a low frequency Hanning (a.k.a. Hann) filter to  $x$  with weight set to  $n$ .

**Value**

A filtered vector.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**References**

Oppenheim, A. V., Schafer, R. W., and Buck, J. R. (1999) *Discrete-Time Signal Processing*. Prentice-Hall, 2nd edition. ISBN-13: 978-0-13-754920-7.

**See Also**

[filter](#)

**Examples**

```
library(graphics)
library(utils)
data(ca533)
yrs <- time(ca533)
y <- ca533[, 1]
not.na <- !is.na(y)
yrs <- yrs[not.na]
y <- y[not.na]
plot(yrs, y, xlab = "Years", ylab = "Series1 (mm)",
     type = "l", col = "grey")
```



```

lines(yrs, hanning(y, n = 9), col = "red", lwd = 2)
lines(yrs, hanning(y, n = 21), col = "blue", lwd = 2)
legend("topright", c("Series", "n=9", "n=21"),
      fill=c("grey", "red", "blue"))

```

i.detrend

*Interactively Detrend Multiple Ring-Width Series***Description**

Interactively detrend multiple tree-ring series by one of two methods, a smoothing spline or a statistical model. This is a wrapper for [detrend.series](#).

**Usage**

```

i.detrend(rwl, y.name = names(rwl), nyrs = NULL, f = 0.5,
          pos.slope = FALSE)

```

**Arguments**

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> or <a href="#">ca533</a>
y.name	a character vector of length <code>ncol(rwl)</code> that gives the ID of each series. Defaults to the column names of <code>rwl</code> .
nyrs	a number giving the rigidity of the smoothing spline, defaults to 0.67 of series length if <code>nyrs</code> is NULL.
f	a number between 0 and 1 giving the frequency response or wavelength cutoff. Defaults to 0.5.
pos.slope	a logical flag. Will allow for a positive slope to be used in method "ModNegExp". If FALSE the line will be horizontal.

**Details**

This function allows a user to choose detrending curves based on plots that are produced by [detrend.series](#) for which it is essentially a wrapper. The user enters their choice of detrended method via keyboard at a prompt for each ring width series in `rwl`. See [detrend.series](#) for examples and details on the detrending methods.

**Value**

A data.frame containing each detrended series according to the method used as columns and rownames set to `colnames(y)`. These are typically years. Plots are also produced as the user chooses the detrending methods through keyboard input.

**Author(s)**

Andy Bunn

**See Also**[detrend.series](#)


---

<i>i.detrend.series</i>	<i>Interactively Detrend a Ring-Width Series</i>
-------------------------	--

---

**Description**

Interactively detrend a tree-ring series by one of three methods, a smoothing spline, a linear model, or the mean. This is a wrapper for [detrend.series](#).

**Usage**

```
i.detrend.series(y, y.name = NULL, nyrs = NULL, f = 0.5,
                 pos.slope = FALSE)
```

**Arguments**

<code>y</code>	a numeric vector. Usually a tree-ring series.
<code>y.name</code>	an optional character vector to name the series for plotting purposes.
<code>nyrs</code>	a number giving the rigidity of the smoothing spline, defaults to 0.67 of series length if <code>nyrs</code> is NULL.
<code>f</code>	a number between 0 and 1 giving the frequency response or wavelength cutoff. Defaults to 0.5.
<code>pos.slope</code>	a logical flag. Will allow for a positive slope to be used in method "ModNegExp". If FALSE the line will be horizontal.

**Details**

This function allows a user to choose a detrending method based on a plot that is produced by [detrend.series](#) for which it is essentially a wrapper. The user enters their choice of detrended method via keyboard at a prompt. See [detrend.series](#) for examples and details on the detrending methods.

**Value**

A vector containing the detrended series (`y`) according to the method used with names set to `colnames(y)`. These are typically years. A plot is also produced and the user chooses a method through keyboard input.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**[detrend.series](#)

---

`insert.ring`*Edit a Ring-Width Series*

---

**Description**

Insert or delete rings from a ring-width series

**Usage**

```
insert.ring(rw.vec, rw.vec.yrs=as.numeric(names(rw.vec)),
            year, ring.value=mean(rw.vec, na.rm=TRUE),
            fix.last=TRUE)
delete.ring(rw.vec, rw.vec.yrs=as.numeric(names(rw.vec)),
            year, fix.last=TRUE)
```

**Arguments**

<code>rw.vec</code>	a vector of data
<code>rw.vec.yrs</code>	the years for <code>rw.vec</code> as names
<code>year</code>	the year to add or delete
<code>ring.value</code>	the value to add
<code>fix.last</code>	logical. If TRUE the last year of the series is fixed and the first year changes.

**Details**

Simple editing of ring widths.

**Value**

A named vector.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**

[dpLR](#)

**Examples**

```
library(utils)
data(gp.rwl)
series <- gp.rwl$"50A"
names(series) <- rownames(gp.rwl)
series <- series[!is.na(series)]
series
```

```
insert.ring(rw.vec=series,year=1950,ring.value=0)
insert.ring(rw.vec=series,year=1950,ring.value=0,fix.last=FALSE)
delete.ring(rw.vec=series,year=1900)
delete.ring(rw.vec=series,year=1900,fix.last=FALSE)
```

interseries.cor

*Individual Series Correlation Against a Master Chronology***Description**

This function calculates the correlation between a series and a master chronology.

**Usage**

```
interseries.cor(rwl,n=NULL,prewhiten=TRUE,biweight=TRUE,
  method = c("spearman", "pearson", "kendall"))
```

**Arguments**

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
n	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
prewhiten	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .
biweight	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .
method	Can be either "pearson", "kendall", or "spearman" which indicates the correlation coefficient to be used. Defaults to "spearman". See <a href="#">cor.test</a> .

**Details**

This function calculates correlation serially between each tree-ring series and a master chronology built from all the other series in the *rwl* object (leave-one-out principle).

Each series in the *rwl* object is optionally detrended as the residuals from a [hanning](#) filter with weight *n*. The filter is not applied if *n* is NULL. Detrending can also be done via prewhitening where the residuals of an [ar](#) model are added to each series mean. This is the default. The master chronology is computed as the mean of the *rwl* object using [tbrm](#) if *biweight* is TRUE and `rowMeans` if not. Note that detrending can change the length of the series. E.g., a [hanning](#) filter will shorten the series on either end by `floor(n/2)`. The prewhitening default will change the series length based on the [ar](#) model fit. The effects of detrending can be seen with [series.rwl.plot](#).

This function produces the same output of the *overall* portion of [corr.rwl.seg](#). The mean correlation value given is sometimes referred to as the "overall interseries correlation" or the "COFECHA interseries correlation". This output differs from the *rbar* statistics given by [rwl.stats](#) in that *rbar* is the average pairwise correlation between series where this is the correlation between a series and a master chronology.

**Value**

a data.frame with correlation values and p-values given from `cor.test`

**Author(s)**

Andy Bunn, patched and improved by Mikko Korpela

**See Also**

`rwl.stats`, `rwi.stats`

**Examples**

```
library(utils)
data(gp.rwl)
foo <- interseries.cor(gp.rwl)
# compare to:
# corr.rwl.seg(rwl=gp.rwl,make.plot=FALSE)$overall
# using pearson's r
foo <- interseries.cor(gp.rwl,method="pearson")

# two measures of interseries correlation
# compare interseries.cor to rbar from rwi.stats
gp.ids <- read.ids(gp.rwl, stc = c(0, 2, 1))
bar <- rwi.stats(gp.rwl, gp.ids, prewhiten=TRUE)
bar$rbar.eff
mean(foo[,1])
```

---

latexDate

*Date Conversion to Character in LaTeX Format*

---

**Description**

This is a simple convenience function that returns a date in the format used by ‘\today’ in LaTeX. A possible use case is fixing the date shown in a vignette at weaving time.

**Usage**

```
latexDate(x = Sys.Date(), ...)
```

**Arguments**

`x` any object for which an `as.POSIXlt` method exists. Defaults to the current date.  
`...` other arguments to `as.POSIXlt`

**Value**

A character vector

**Author(s)**

Mikko Korpela

**Examples**

```

latexDate() # today
latexDate(Sys.Date() + 5) # today + 5 days
latexDate(c("2013-12-06", "2014-09-19")) # fixed dates
## [1] "December 6, 2013" "September 19, 2014"
latexDate(5*60*60*24, origin=Sys.Date()) # today + 5 days

```

---

 latexify

---

*Convert Character Strings for Use with LaTeX*


---

**Description**

Some characters cannot be entered directly into a LaTeX document. This function converts the input character vector to a form suitable for inclusion in a LaTeX document in text mode. It can be used together with ‘\Sexpr’ in vignettes.

**Usage**

```

latexify(x, doublebackslash = TRUE, dashdash = TRUE,
        quotes = c("straight", "curved"),
        packages = c("fontenc", "textcomp"))

```

**Arguments**

x	a character vector
doublebackslash	a logical flag. If TRUE, backslashes in the output are doubled. It seems that Sweave needs TRUE and knitr FALSE.
dashdash	a logical flag. If TRUE (the default), consecutive dashes (“-”) in the input will be rendered as separate characters. If FALSE, they will not be given any special treatment, which will usually mean that two dashes are rendered as an en dash and three dashes make an em dash.
quotes	a character string specifying how single and double quotes (ASCII codes 39 and 34) and stand-alone grave accents (ASCII code 96) in the input are treated. The default is to use straight quotes and the proper symbol for the grave accent. The other option is to use curved right side (closing) quotes, and let LaTeX convert the grave accent to opening curved quotes. Straight double quotes are not available in the default OT1 font encoding of LaTeX. Straight single quotes and the grave accent symbol require the “textcomp” package. See <i>packages</i> .

`packages` a character vector specifying the LaTeX packages allowed. The use of some symbols in LaTeX requires commands or characters made available by an add-on package. If a package required for a given character is not marked as available, a fallback solution is silently used. For example, curved quotes may be used instead of straight quotes. The supported packages are "eurosym" (not used by default), "fontenc" and "textcomp". Including "fontenc" in the vector means that some other encoding than OT1 is going to be used. Note that straight quotes are an exception in the sense that a reasonable substitute (curved quotes) is available. In many other cases, "textcomp" and "fontenc" are silently assumed.

### Details

The function is intended for use with unformatted inline text. Newlines, tabs and other whitespace characters ("`[:space:]`" in [regex](#)) are converted to spaces. Control characters ("`[:cntrl:]`") that are not whitespace are removed. Other more or less special characters in the ASCII set are '{', '}', '\', '#', '\$', '%', '^', '&', '\_', '~', double quote, '/', single quote, '<', '>', '|', grave and '-'. They are converted to the corresponding LaTeX commands. Some of the conversions are affected by user options, e.g. *dashdash*.

Before applying the substitutions described above, input elements with `Encoding` set to "bytes" are printed and the output is stored using `captureOutput`. The result of this intermediate stage is ASCII text where some characters are shown as their byte codes using a hexadecimal pair prefixed with "\x". This set includes tabs, newlines and control characters. The substitutions are then applied to the intermediate result.

The quoting functions `sQuote` and `dQuote` may use non-ASCII quote characters, depending on the locale. Also these quotes are converted to LaTeX commands. This means that the quoting functions are safe to use with any LaTeX input encoding. Similarly, some other non-ASCII characters, e.g. letters, currency symbols, punctuation marks and diacritics, are converted to commands.

Adding "eurosym" to `packages` enables the use of the euro sign as provided by the "eurosym" package (`\euro`).

The result is converted to UTF-8 encoding, Normalization Form C (NFC). Note that this function will not add any non-ASCII characters that were not already present in the input. On the contrary, some non-ASCII characters, e.g. all characters in the "latin1" (ISO-8859-1) `Encoding` (character set), are removed when converted to LaTeX commands. Any remaining non-ASCII character has a good chance of working when the document is processed with XeTeX or LuaTeX, but the Unicode support available with pdfTeX is limited.

Assuming that 'pdflatex' is used for compilation, suggested package loading commands in the document preamble are:

```
\usepackage[T1]{fontenc}    % no ''' in OT1 font encoding
\usepackage{textcomp}      % some symbols e.g. straight single quote
\usepackage[utf8]{inputenx} % UTF-8 input encoding
\input{ix-utf8enc.dfu}      % more supported characters
```

### Value

A character vector

**Author(s)**

Mikko Korpela

**References**

INRIA. Tralics: a LaTeX to XML translator, HTML documentation of all TeX commands. <http://www-sop.inria.fr/marelle/tralics/>.

Levitt, N., Persch, C., and Unicode, Inc. (2013) GNOME Character Map, application version 3.10.1.

Mittelbach, F., Goossens, M., Braams, J., Carlisle, D., and Rowley, C. (2004) *The LaTeX Companion*. Addison-Wesley, second edition. ISBN-13: 978-0-201-36299-2.

Pakin, S. (2009) The Comprehensive LaTeX Symbol List. <http://www.ctan.org/tex-archive/info/symbols/comprehensive>.

The Unicode Consortium. The Unicode Standard. <http://www.unicode.org/versions/latest/>.

**Examples**

```
x1 <- "clich\xe9\nma\xflana"
Encoding(x1) <- "latin1"
x1
x2 <- x1
Encoding(x2) <- "bytes"
x2
x3 <- enc2utf8(x1)
testStrings <-
  c("different kinds\nof\tspace",
    "control\a characters \ftoo",
    "{braces} and \\backslash",
    '#various$ %other^ &characters_ ~escaped'/coded',
    x1,
    x2,
    x3)
latexStrings <- latexify(testStrings, doublebackslash = FALSE)
## All should be "unknown"
Encoding(latexStrings)
cat(latexStrings, sep="\n")
## Input encoding does not matter
identical(latexStrings[5], latexStrings[7])
```

---

morlet

*Perform a Continuous Morlet Wavelet Transform*

---

**Description**

This function performs a continuous wavelet transform on a time series.



**Usage**

```
morlet(y1, x1 = seq_along(y1), p2 = NULL, dj = 0.25, siglvl = 0.95)
```

**Arguments**

y1	numeric vector. Series to be transformed.
x1	numeric. A vector of values giving the years for the plot. Must be the same length as length(y1).
p2	numeric. The number of power of two to be computed for the wavelet transform. Calculated from length of y1 if NULL.
dj	numeric. Sub-octaves per octave calculated.
siglvl	numeric. Level for the significance test.

**Details**

This performs a continuous wavelet transform of a time series. This function is typically invoked with [wavelet.plot](#).

**Value**

A list containing:

y	numeric. The original time series.
x	numeric. The time values.
wave	complex. The wavelet transform.
coi	numeric. The cone of influence.
period	numeric. The period.
Scale	numeric. The scale.
Signif	numeric. The significant values.
Power	numeric. The squared power.

**Note**

This is a port of Torrence's IDL code, which can be accessed through the [Internet Archive Wayback Machine](#).

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**References**

Torrence, C. and Compo, G. P. (1998) A practical guide to wavelet analysis. *Bulletin of the American Meteorological Society*, **79**(1), 61–78.

**See Also**[wavelet.plot](#)**Examples**

```
library(utils)
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
ca533.crn <- chron(ca533.rwi, prefix = "CAM", prewhiten = FALSE)
Years <- time(ca533.crn)
CAMstd <- ca533.crn[, 1]
out.wave <- morlet(y1 = CAMstd, x1 = Years, dj = 0.1, siglvl = 0.99)
```

net

*Calculate NET***Description**

Computes the *NET* parameter for a set of tree-ring records or other time-series data.

**Usage**

```
net(x, weights = c(v = 1, g = 1))
```

**Arguments**

x	A matrix or data.frame with at least two rows and two columns containing numeric data. The rows should represent a sequence of sampling points with uniform intervals (e.g. a range of years), but this is not checked. Each column is a time-series spanning either the whole time range or a part of it.
weights	A numeric vector with two elements. Normally, variation ("v") and Gegenläufigkeit ("g") contribute to NET with equal weight. It is possible to use different weights by setting them here. The names of the vector are matched to c("v", "g") (see 'Examples'). If no names are given, the first element is the weight of variation.

**Details**

This function computes the *NET* parameter (Esper et al., 2001). The overall *NET* is an average of all (non-NA) yearly values  $NET_j$ , which are computed as follows:

$$NET_j = v_j + (1 - G_j)$$

The yearly variation  $v_j$  is the standard deviation of the measurements of a single year divided by their mean. Gegenläufigkeit  $1 - G_j$  is based on one definition of Gleichläufigkeit  $G_j$ , similar to but not the same as what [glk](#) computes. Particularly, in the formula used by this function (Esper et al., 2001), simultaneous zero differences in two series are not counted as a synchronous change.

The weights of  $v_j$  and  $1 - G_j$  in the sum can be adjusted with the argument *weights* (see above). As a rather extreme example, it is possible to isolate variation or Gegenläufigkeit by setting one of the weights to zero (see ‘Examples’).

### Value

A list with the following components, in the same order as described here:

`all`                    a numeric vector containing  $NET_j$ . Row names of  $x$  (if any) are copied here.  
`average`                a numeric value  $NET$ , the average of the "all" vector (NA values removed).

### Author(s)

Mikko Korpela

### References

Esper, J., Neuwirth, B., and Treydte, K. (2001) A new parameter to evaluate temporal signal strength of tree-ring chronologies. *Dendrochronologia*, **19**(1), 93–102.

### Examples

```
library(utils)
data(ca533)
ca533.rwl <- detrend(rwl = ca533, method = "ModNegExp")
ca533.net <- net(ca533.rwl)
tail(ca533.net$all)
ca533.net$average
## Not run:
## Isolate the components of NET
ca533.v <- net(ca533.rwl, weights=c(v=1,0))
ca533.g <- net(ca533.rwl, weights=c(g=1,0))

## End(Not run)
```

---

plot.rwl

*Plotting Rwl Objects*

---

### Description

Plots rwl objects.

### Usage

```
## S3 method for class 'rwl'
plot(x, plot.type=c("seg", "spag"), ...)
```

**Arguments**

x                    An object of class "rwl".  
 plot.type          Character. Type "seg" calls [seg.plot](#) while "spag" calls [spag.plot](#)  
 ...                Additional arguments for each type

**Value**

None. A plot is produced.

**Author(s)**

Andy Bunn

**See Also**

[read.rwl](#)

**Examples**

```
library(graphics)
library(utils)
data(co021)
plot(co021, plot.type="seg")
plot(co021, plot.type="spag")
plot(co021, plot.type="spag", zfac=2)
```

---

plotRings

*Plot Rings*

---

**Description**

Make a plot and/or animation of a cross section based on up to four ring-width series. Gives basic summary statistics (e.g. annual basal area, mean ring width) of an approximated stem disc.

**Usage**

```
plotRings(year, trwN, trwS = NA_real_,
           trwE = NA_real_, trwW = NA_real_, length.unit = "mm",
           animation = FALSE, sys.sleep = 0.2, year.labels = FALSE,
           d2pith = NA, col.inrings = "grey", col.outring = "black",
           x.rings = "none", col.x.rings = "red", xy.lim = NULL,
           species.name = NA, saveGIF = FALSE, fname = "GIF_plotRings.gif")
```

**Arguments**

year	a numeric vector giving the years of the tree-ring records
trwN	a numeric vector giving the first tree-ring series to make the plot. It will be arbitrarily defined as North.
trwS	an optional numeric vector giving a tree-ring series to make the plot. It will be arbitrarily defined as South or 180 degrees from <i>trwN</i> .
trwE	an optional numeric vector giving a tree-ring series to make the plot. It will be arbitrarily defined as East or 90 degrees from <i>trwN</i> .
trwW	an optional numeric vector giving a tree-ring series to make the plot. It will be arbitrarily defined as West or 270 degrees from <i>trwN</i> .
animation	logical flag. If TRUE then each ring will be individually plotted as an animation within the R-GUI. A working copy of "ImageMagick" is required. See 'Details'.
length.unit	a character string to to set the length unit of ring measurement. Possible values are "mm", "1/10 mm", "1/100 mm" and "1/10 mm".
sys.sleep	a numeric value defining the sleep pause in between rings during animation.
year.labels	logical flag. If TRUE the year labels will be shown at the bottom of the plot.
d2pith	numeric. The distance from the innermost ring to the pith of the tree. It is computed in the same unit as in the "length.unit" argument. If a value is assigned, a new row in the output table will be added at the first year
col.inrings	The color to be used for the interior rings. See section 'Color Specification' for suitable values.
col.outring	The color to be used for the outer ring. See section 'Color Specification' for suitable values.
x.rings	a character string to color narrow and wider rings of the series. Possible values are "none", "narrow.rings" to highlight the rings $\leq$ quantile 25%, and "wider.rings" to highlight the rings $\geq$ quantile 75%.
col.x.rings	The color to be used for the <i>x.rings</i> . See section 'Color Specification' for suitable values.
xy.lim	a numeric giving a single positive value for the axis limits. If NULL limits are calculated automatically. See examples.
species.name	an optional character string that defines the species name in the plot.
saveGIF	logical. If TRUE a GIF will be saved. A working copy of "ImageMagic" is required. See 'Details' and examples.
fname	character. Filename for GIF.

**Details**

This makes a plot, drawing all rings from tree-ring series on a Cartesian plane of up to four cardinal directions (N, S, E, W) defining the eccentricity of the stem. It can be plotted using only data from one ratio, or up to four different radii from same tree. This function can plot each individual ring as an animation within the R-GUI, as a GIF-file, or it can plot all rings at once.

Animations require a functional installation of ImageMagick [<https://www.imagemagick.org>] where the ImageMagick program convert is configured correctly in the PATH. At the moment, the saveGIF

option in plotRings is stable but occasionally fails. Should users encounter issues saving a GIF, the problem might be related to the installation of ImageMagick the details of which depend on platform. See [saveGIF](#) for details.

### Value

A data.frame giving the original data of each tree-ring series ("trwN", "trwS", "trwE", "trwW"), a mean of all tree-ring series ("trw.means"), cumulative values from "trw.means" ("trw.acc"), the difference of North - South and East - West tree-ring series ("N\_S", "E\_W"), the basal area increment of "trw.acc" ("bai.acc"), and the bai for each individual tree ring ("bai.ind").

### Author(s)

Code by Darwin Pucha-Cofrep and Jakob Wernicke. Patched and improved by Andy Bunn and Mikko Korpela.

### Examples

```
# with tree-ring series from Rothenburg data
data("anos1")

yrs <- time(anos1)
# Plot rings with data of two radii from same individual tree
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5],
                species.name = "Cedreia odorata")

# change plot limits
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5],
                xy.lim = 100)

# Playing with colors
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5],
                col.inrings = "tan", col.outring = "blue")
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5],
                col.inrings = terrain.colors(nrow(anos1)))

#Setting the length.unit
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5], sp="Cedreia odorata", length.unit = "mm")
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5], sp="Cedreia odorata", length.unit = "1/100 mm")

# Specifying x.rings highlighting only narrow rings
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5],
                x.rings = "narrow.rings")

# Highlight and color wide rings
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5],
                x.rings = "wider.rings", col.x.rings = "green")

## Not run:
# Plot rings and animate. Requires ImageMagick to be installed.
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5], year.labels = TRUE,
                animation = TRUE, sys.sleep = 0.1)
```

```

# Plot rings, animate, save as GIF. Requires ImageMagick to be installed.
res <- plotRings(yrs, anos1[,4], trwW = anos1[,5],
                saveGIF = TRUE, fname="GIF_plotRings.gif",sys.sleep = 0.1)

## End(Not run)

# with four fake tree-ring series
trw <- data.frame(trw01.n = abs(rnorm(100, 10, 4)), # North direction
                 trw01.s = abs(rnorm(100, 10, 2)), # South direction
                 trw01.w = abs(rnorm(100, 10, 2)), # West direction
                 trw01.e = abs(rnorm(100, 10, 2)), # East direction
                 row.names = 1918:2017)
class(trw) <- c("rwl","data.frame")

yrs <- time(trw)

# Default plot with 2, 3 and 4 radii
res <- plotRings(yrs, trw[,1], trw[,2], trw[,3], trw[,4])

# with d2pith values (see the hole before the first rings in the plot)
res <- plotRings(yrs, trw[,1], trw[,2], trw[,3], trw[,4],
                d2pith = 100)

```

---

po.to.wc

---

*Convert Pith Offset to Wood Completeness*


---

## Description

This function creates a partial wood completeness data structure based on pith offset data.

## Usage

```
po.to.wc(po)
```

## Arguments

po	A data frame containing two variables. Variable one ( <i>series</i> ) gives the series ID as either characters or factors. Variable two ( <i>pith.offset</i> ) contains integral values and gives the years from the beginning of the core to the pith (or center) of the tree. The minimum value is 1.
----	---

## Details

Uses *pith.offset* - 1 as the number of missing heartwood rings.

**Value**

A `data.frame` containing one variable of wood completeness data: `n.missing.heartwood` (integer type). This can be used as input to `write.tridas`.

**Author(s)**

Mikko Korpela

**See Also**

`wc.to.po`, `rcs`, `write.tridas`

**Examples**

```
## Not run:
library(utils)
data(gp.po)
all(wc.to.po(po.to.wc(gp.po)) == gp.po)

## End(Not run)
```

---

pointer

*Calculates Pointer Years from a Group of Ring-Width Series*

---

**Description**

This function calculates pointer years on a `data.frame` of ring-width series using the Becker algorithm. The pointer years are computed with adjustable thresholds of relative radial growth variation and number of series displaying similar growth pattern (i.e. positive or negative variations).

**Usage**

```
pointer(rwl, rgv.thresh = 10, nseries.thresh = 75, round.decimals = 2)
```

**Arguments**

<code>rwl</code>	a <code>data.frame</code> with ring-width series as columns and years as rows such as that produced by <code>read.rwl</code> .
<code>rgv.thresh</code>	a numeric giving the minimum absolute relative radial growth variation (in percentage) above which the growth change from the year $t-1$ to $t$ is considered as significant. Must be $> 0$ . Values $> 100$ are possible but highly unusual. See references. Defaults to 10.
<code>nseries.thresh</code>	a numeric giving the minimum percentage of series displaying significant relative radial growth variations of a same sign above which the year $t$ is considered as a pointer year. Positive significant variations will results in a positive pointer year, negative ones in a negative pointer year. This number ranges from 1 to 100. Defaults to 75.
<code>round.decimals</code>	an integer indicating the number of decimal places to be used for outputs. This number must be positive. Defaults to 2.



## Details

This calculates pointer years from ring-width series for each year  $t$  of the time period covered by the series using the Becker algorithm. This algorithm is based on, first, the calculation of the individual relative radial growth variation by comparison of ring-width of year  $t$  to that of year  $t-1$  for each series, and second, the inter-series comparison of both sign and magnitude of these variations.

For example, if *rgv.thresh* and *nseries.thresh* are set at 10 and 75 respectively, pointer years will be defined as those years when at least 75% of the series present an absolute relative radial growth variation higher than 10%.

Users unfamiliar with the Becker algorithm should refer to Becker et al. (1994) and Mérian and Lebourgeois (2011) for further details.

## Value

A data.frame containing the following columns (each row corresponds to one position of the window):

Year	Considered year (t).
Nb.series	Number of available series.
Perc.pos	Percentage of series displaying a significant positive radial growth variation.
Perc.neg	Percentage of series displaying a significant negative radial growth variation.
Nature	Number indicating whether the year is a positive pointer year (1), a negative pointer year (-1) or a regular year (0).
RGV_mean	Mean radial growth variations over the available series.
RGV_sd	Standard deviation of the radial growth variations over the available series.

## Author(s)

Pierre Mérian. Improved by Mikko Korpela and Andy Bunn.

## References

Becker, M., Nieminen, T. M., and Géréma, F. (1994) Short-term variations and long-term changes in oak productivity in northeastern France – the role of climate and atmospheric CO<sub>2</sub>. *Annals of Forest Science*, **51**(5), 477–492.

Mérian, P. and Lebourgeois, F. (2011) Size-mediated climate–growth relationships in temperate forests: A multi-species analysis. *Forest Ecology and Management*, **261**(8), 1382–1391.

## See Also

[skel.plot](#)

**Examples**

```
## Pointer years calculation on ring-width series. Returns a data.frame.
library(utils)
data(gp.rwl)
py <- pointer(rwl=gp.rwl, rgv.thresh=10, nseries.thresh=75,
              round.decimals=2)
tail(py)
```

---

 powt

*Power Transformation of Tree-Ring Data*


---

**Description**

Perform power transformation simultaneously for a data.frame of raw tree-ring width series.

**Usage**

```
powt(rwl)
```

**Arguments**

rwl a data.frame of raw tree-ring widths series, such as that produced by [read.rwl](#) or [read.fh](#)

**Details**

This procedure is a variance stabilization technique implemented after Cook & Peters (1997): for each series a linear model is fitted on the logs of level and spread, where level is defined as the local mean  $M_t = (R_t + R_{t-1})/2$  with ring widths R, and spread S is the local standard deviation defined as  $S_t = |R_t - R_{t-1}|$ . The regression coefficient b from  $\log S = k + b \log M$  is then used for the power transform  $\star R_t = R_t^{1-b}$ .

**Value**

A data.frame containing the power transformed ring width series.

**Author(s)**

Christian Zang. Patched and improved by Mikko Korpela.

**References**

Cook, E. R. and Peters, K. (1997) Calculating unbiased tree-ring indices for the study of climatic and environmental change. *The Holocene*, 7(3), 361–370.

**See Also**

[rcs](#)

**Examples**

```
library(utils)
data(gp.rwl)
gp.pt <- powt(gp.rwl)
```

---

```
print.redfit          Printing Redfit Results
```

---

**Description**

Print information contained in or derived from a redfit object.

**Usage**

```
## S3 method for class 'redfit'
print(x, digits = NULL, csv.out = FALSE, do.table = FALSE,
      prefix = "", row.names = FALSE, file = "", ...)
```

**Arguments**

x	An object of class "redfit".
digits	Specifies the desired number of significant digits in the output. The argument is passed to <code>format</code> and <code>print.data.frame</code> . A positive integral value or NULL. If NULL, the value in <code>options("digits")</code> is used.
csv.out	A logical flag. If TRUE, writes a large, comma-separated table of information. The table contains one row for each frequency. If FALSE, writes a few summary numbers instead. See 'Details'.
do.table	A logical flag. If TRUE, the large information table is also printed when <code>csv.out</code> is FALSE, although not in a comma-separated format but with <code>print.data.frame</code> .
prefix	A prefix to be used on every output line except the large information table. REDFIT (see References) uses "# ".
row.names	A logical flag enabling or disabling automatic row names from the large information table, or a character vector of names. In any case, the table will contain frequency as the first column.
file	A writable connection or a character string naming a file. Used for setting the output destination when <code>csv.out</code> is TRUE. The default is to write the comma-separated table to the console.
...	Arguments to <code>write.csv</code> . Used when <code>csv.out</code> is TRUE.

**Value**

Invisibly returns `x`.

**Author(s)**

Mikko Korpela

## References

This function is based on the Fortran program **REDFIT**, which is in the public domain.

Schulz, M. and Mudelsee, M. (2002) REDFIT: estimating red-noise spectra directly from unevenly spaced paleoclimatic time series. *Computers & Geosciences*, **28**(3), 421–426.

## See Also

[redfit](#)

## Examples

```
library(utils)
data(ca533)
tm <- time(ca533)
x <- ca533[[1]]
idx <- which(!is.na(x))
redf <- redfit(x[idx], tm[idx], "time",
              nsim = 100, iwin = 0, ofac = 1, n50 = 1)
print(redf)
fname <- tempfile(fileext=".csv")
print(fname) # tempfile used for output
print(redf, csv.out = TRUE, file = fname)
redftable <- read.csv(fname)
unlink(fname) # remove the file
```

---

print.rwl.report      *Do some reporting on a RWL object*

---

## Description

This function prints the results of [rwl.report](#)

## Usage

```
## S3 method for class 'rwl.report'
print(x, ...)
```

## Arguments

x	a list from <a href="#">rwl.report</a>
...	not implemented

## Details

This function formats the list from [rwl.report](#) for the user to have a summary report of the number of series, the mean length of all the series, the first year, last year, the mean first-order autocorrelation (via [summary.rwl](#)), the mean interseries correlation (via [interseries.cor](#)), the years where a series has a missing ring (zero), internal NA, or a very small ring (<0.005).

**Value**

Invisible

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**

[rwl.report](#), [summary.rwl](#), [interseries.cor](#)

**Examples**

```
data("gp.rwl")
rwl.report(gp.rwl)
foo <- gp.rwl
foo[177,1] <- NA
foo[177:180,3] <- NA
foo[185,4] <- 0.001
rwl.report(foo)
```

---

rasterPlot

*Add Raster Elements to Plot*


---

**Description**

This function takes plotting commands and uses a temporary bitmap graphics device to capture their output. The resulting raster image is drawn in the plot or figure region of the active high-level plot. A new plot is started if one does not exist.

**Usage**

```
rasterPlot(expr, res = 150, region = c("plot", "figure"), antialias,
           bg = "transparent", interpolate = TRUE, draw = TRUE,
           Cairo = FALSE, ...)
```

**Arguments**

<code>expr</code>	Low-level plotting commands (lines, points, text, ...) representing elements to be added to the current plot. A <a href="#">call</a> or an <a href="#">expression</a> .
<code>res</code>	Resolution in points per inch (ppi). A numeric value. Suggested values for different types of display media are given in <a href="#">compactPDF</a> . For example, the default 150 ppi corresponds to "ebook" quality.
<code>region</code>	The function can draw in the "plot" region or the "figure" region which also includes "mar" margins (see <a href="#">par</a> ). If the drawing commands in <code>expr</code> contain no material for the margins, the default "plot" is optimal. Plotting in the outer margins ("oma" in <a href="#">par</a> ) is not supported.

<code>antialias</code>	Antialiasing argument passed to <code>png</code> . The default (missing argument) is probably good for line plots but "none" is preferred for images in which color signifies value of data. Unused if a <code>Cairo</code> device is used instead of <code>png</code> .
<code>bg</code>	Background color of the raster plot, an argument passed to the bitmap device. If the default "transparent" does not work, try "white" or another color. Note that a non-transparent background will mask any previous content in the figure or plot region, depending on the value of <code>region</code> .
<code>interpolate</code>	Argument passed to <code>rasterImage</code> . A logical flag. The default is TRUE: use linear interpolation. Analogously to <code>antialias</code> , FALSE is preferred when color maps to value.
<code>draw</code>	A logical flag. Draw the results (TRUE, the default) or return an image object (FALSE)?
<code>Cairo</code>	A logical flag. TRUE for preferring a <code>Cairo</code> to <code>png</code> as the bitmap device, FALSE (the default) for the opposite. If the preferred device cannot be used, the other one will be tried.
<code>...</code>	Other arguments to <code>png</code> or <code>Cairo</code> .

### Details

The appropriate graphical parameters of the current graphics device are copied to the temporary bitmap device. Therefore the appearance of the raster contents should be almost the same as when directly drawn.

The call or expression `expr` is evaluated in the environment of the caller.

It is possible that the raster contents will maintain a constant size when the graphics device is resized. If resizing works, however, the image may become distorted. For example, circle symbols will turn into ellipses if the width to height ratio is not maintained (see 'Examples'). This is in contrast to a standard plot in a display graphics device, e.g. `x11`, where text and symbols maintain their size when the device is resized.

### Value

If `draw` is TRUE, there is no return value. The function is used for the side effects.

If `draw` is FALSE, an object of class "nativeRaster" is returned. The object can be used as input for `rasterImage` or `grid.raster`. See `readPNG`. If no bitmap device is available (see 'Note'), NULL is returned.

### Note

- The graphics device used for the output must have support for including raster images. See "rasterImage" in `dev.capabilities`.
- The R build must have a functional `png` device, which requires one of the following `capabilities`: "png", "aqua" or "cairo". Alternatively, a `Cairo` device from package `Cairo` must be available with `Cairo.capabilities` "raster" or "png".

If either of these requirements is not met, at least one `message` is generated and the function reverts to regular plotting. The `bg` argument is then handled by drawing a filled rectangle. Also `region` is honored, but the other settings do not apply.

**Author(s)**

Mikko Korpela

**Examples**

```

library(graphics)
library(stats)

## Picture with various graphical elements
x <- 1:100
y0 <- quote(sin(pi * x / 20) + x / 100 + rnorm(100, 0, 0.2))
y <- eval(y0)
ylab <- deparse(y0)
spl <- smooth.spline(y)
plot(x, y, type = "n", axes = FALSE, ylab = ylab)
usr <- par("usr")
xrange <- usr[2] - usr[1]
xsize <- xrange * 0.4
nsteps <- 8
xmar <- xsize / 20
yrange <- usr[4] - usr[3]
ysize <- yrange / 20
ymar <- 0.5 * ysize
X <- seq(usr[1] + xmar, by = xsize / nsteps, length.out = nsteps + 1)
xleft <- X[-(nsteps + 1)]
xright <- X[-1]
pin <- par("pin")
maxrad <- xsize / 3 * min(1, pin[2] / pin[1])
nrad <- 16
minrad <- maxrad / nrad
Rad <- seq(maxrad, by = (minrad - maxrad) / (nrad - 1), length.out=nrad)
xmar2 <- xmar + maxrad
ymar2 <- (xmar2 / xrange) * pin[1] / pin[2] * yrange
expr <- quote({
  rect(xleft, usr[4] - 1.5 * ysize, xright, usr[4] - ymar,
       col = rainbow(8), border = NA)
  symbols(rep(usr[2] - xmar2, nrad), rep(usr[3] + ymar2, nrad),
         circles = Rad, inches = FALSE, add = TRUE, fg = NA,
         bg = gray.colors(nrad + 1, 1, 0)[-1])
  points(y)
  lines(spl)
})
rasterPlot(expr, res = 50)
box()
axis(1)
axis(2)

## The same picture with higher resolution but no antialiasing
plot(y, type = "n", axes = FALSE, ann = FALSE)
## No content in margin, but region = "figure" and bg = "white"
## paints margin white
rasterPlot(expr, antialias = "none", interpolate = FALSE,

```

```

        region = "figure", bg = "white")
## Draw box, axes, labels
parnew <- par(new = TRUE)
plot(x, y, type = "n", ylab = ylab)
par(parnew)

## Draw plot(1:5) with adjusted margins and additional axes. Some parts
## are drawn with rasterPlot, others normally. Resize to see stretching.
op <- par(no.readonly = TRUE)
par(mar = c(5.1, 4.1, 2.1, 2.1))
plot(1:5, type = "n", axes = FALSE, ann = FALSE)
expr2 <- quote({
  points(c(2, 4), c(2, 4))
  axis(2)
  axis(3)
})
rasterPlot(expr2, region = "figure", bg = "white")
points(c(1, 3, 5), c(1, 3, 5))
box()
axis(1)
axis(4)
title(xlab = "Index", ylab = "1:5")
par(op)

```

---

rCS

*Regional Curve Standardization*


---

## Description

Detrend multiple ring-width series simultaneously using a regional curve.

## Usage

```
rCS(rwl, po, nyrs = NULL, f = 0.5, biweight = TRUE, ratios = TRUE,
    rc.out = FALSE, make.plot = TRUE, ..., rc.in = NULL, check = TRUE)
```

## Arguments

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a>
po	a data.frame containing two variables. Variable one ( <i>series</i> in the example below) gives the series ID as either characters or factors. These must exactly match <code>colnames(rwl)</code> . Variable two ( <i>pith.offset</i> in the example below) must be integral values and give the years from the beginning of the core to the pith (or center) of the tree. The minimum value is 1.
nyrs	a number giving the rigidity of the smoothing spline, defaults to 0.1 of length of the maximum cambial age (i.e., the length of the regional curve) if <i>nyrs</i> is NULL.



<code>f</code>	a number between 0 and 1 giving the frequency response or wavelength cutoff. Defaults to 0.5.
<code>biweight</code>	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .
<code>ratios</code>	logical flag. If TRUE (the default) then indices are calculated by division, if FALSE indices are calculated by subtraction.
<code>rc.out</code>	logical flag. Returns the regional curve along with the ring-width indices if TRUE.
<code>make.plot</code>	logical flag. Makes plots of the raw data and regional curve if TRUE.
<code>...</code>	other arguments passed to <a href="#">plot</a> .
<code>rc.in</code>	for internal use.
<code>check</code>	a logical flag. Bypass input checks by setting this to FALSE.

### Details

This method detrends and standardizes tree-ring series by calculating an age-related growth curve specific to the *rwI*. The detrending is the estimation and removal of the tree's natural biological growth trend. The standardization is done by either dividing each series by the growth trend or subtracting the growth trend from each series to produce units in the dimensionless ring-width index (RWI). The option to produce indices by subtraction is intended to be used on series that have been subject to variance stabilization (e.g., using [powt](#)).

The spline approach uses an n-year spline where the frequency response is 0.50 at a wavelength of 10 percent of the maximum cambial age unless specified differently using *nyrs* and *f* in the function [ffcsaps](#).

This attempts to remove the low frequency variability that is due to biological or stand effects. See the references below for further details on detrending in general, and Biondi and Qeadan (2008) for an explanation of RCS.

### Value

A `data.frame` containing the dimensionless and detrended ring-width indices with column names, row names and dimensions of *rwI*. If *rc.out* is TRUE then a `list` will be returned with a `data.frame` containing the detrended ring widths as above and a vector containing the regional curve.

### Note

DendroLab website: <http://dendrolab.org/>

### Author(s)

Code provided by DendroLab based on programming by F. Qeadan and F. Biondi, University of Nevada Reno, USA and adapted for `dplR` by Andy Bunn. Patched and improved by Mikko Korpela.

## References

Biondi, F. and Qeadan, F. (2008) A theory-driven approach to tree-ring standardization: Defining the biological trend from expected basal area increment. *Tree-Ring Research*, **64**(2), 81–96.

Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.

Fritts, H. C. (2001) *Tree Rings and Climate*. Blackburn. ISBN-13: 978-1-930665-39-2.

## See Also

[detrrend](#), [chron](#), [cms](#), [ffcsaps](#)

## Examples

```
library(utils)
data(gp.rwl)
data(gp.po)
gp.rwi <- rcs(rwl = gp.rwl, po = gp.po, biweight = TRUE,
             rc.out = TRUE, make.plot = FALSE)
str(gp.rwi)
gp.rwi <- rcs(rwl = gp.rwl, po = gp.po, biweight = TRUE,
             make.plot = TRUE, main = "Regional Curve")
```

---

read.compact

*Read DPL Compact Format Ring Width File*

---

## Description

This function reads in a DPL compact format file of ring widths.

## Usage

```
read.compact(fname)
```

## Arguments

fname            a character vector giving the file name of the rwl file.

## Details

This function should be able to read files written by the Dendrochronology Program Library (DPL) in its compact format.

## Value

An object of class `c("rwl", "data.frame")` with the series in columns and the years as rows. The series IDs are the column names and the years are the row names.

**Author(s)**

Mikko Korpela

**See Also**[read.rwl](#), [read.tucson](#), [read.tridas](#), [read.fh](#), [write.compact](#)

read.crn

*Read Tucson Format Chronology File***Description**

This function reads in a Tucson (decadal) format file of tree-ring chronologies (.crn).

**Usage**

```
read.crn(fname, header = NULL, encoding = getOption("encoding"),
         long = TRUE)
```

**Arguments**

fname	a character vector giving the file name of the crn file.
header	logical flag indicating whether the file has a header. If NULL then the function will attempt to determine if a header exists
encoding	the name of the encoding to be used when reading the crn file. Usually the default value will work, but a crn file written in a non-default encoding may crash the function. In that case, identifying the encoding and specifying it here should fix the problem. Examples of popular encodings available on many systems are "ASCII", "UTF-8", and "latin1" alias "ISO-8859-1". See the help of <a href="#">file</a> .
long	logical flag indicating whether to automatically detect when an input file uses more than 4 characters for the decade. If FALSE, the function assumes 6 characters are used for the site ID and 4 characters for the decade, which is the standard. If TRUE (the default), long records may work.

**Details**

This reads in a standard crn file as defined according to the standards of the ITRDB at <http://www1.ncdc.noaa.gov/pub/data/paleo/treering/treeinfo.txt>. Despite the standards at the ITRDB, this occasionally fails due to formatting problems.

**Value**

A data.frame with each chronology in columns and the years as rows. The chronology IDs are the column names and the years are the row names. If the file includes sample depth that is included as the last column (*samp.depth*). The output class is class "crn" and "data.frame"

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

---

read.fh

*Read Heidelberg Format Ring Width File*

---

**Description**

This function reads in a Heidelberg (block or column) format file of ring widths (.fh).

**Usage**

```
read.fh(fname)
```

**Arguments**

fname            a character vector giving the file name of the fh file.

**Details**

This reads in a fh-file with ring widths in blocks (decadal format) or in columns (e.g., as with comment flags) as used by TSAP program. Chronologies or half-chronos in fh-format are not supported.

**Value**

An object of class c("rwl", "data.frame") with the series in columns and the years as rows. The keycodes are the column names and the years are the row names. Depending on metadata available in the input file, the following attributes may be present in the data.frame:

ids            A data.frame identifying the series. Always contains columns "tree" and "core", may contain columns "site", "radius", and "stemDisk". All columns are numeric.

po            A data.frame containing pith offsets, formatted for use in [rcs](#).

**Author(s)**

Christian Zang. New features and patches by Mikko Korpela.

**References**

Rinn, F. (2003) *TSAP-Win User Reference Manual*. Rinntech, Heidelberg. <http://www.rinntech.com/>.

**See Also**

[read.rwl](#)

---

read.ids	<i>Read Site-Tree-Core IDs</i>
----------	--------------------------------

---

### Description

These functions try to read site, tree, and core IDs from a `rw1` data frame.

### Usage

```
read.ids(rw1, stc = c(3, 2, 3), ignore.site.case = FALSE,
         ignore.case = FALSE, fix.typos = FALSE, typo.ratio = 5,
         use.cor = TRUE)
```

```
autoread.ids(rw1, ignore.site.case = TRUE, ignore.case = "auto",
             fix.typos = TRUE, typo.ratio = 5, use.cor = TRUE)
```

### Arguments

<code>rw1</code>	a data frame with series as columns and years as rows such as that produced by <a href="#">read.rw1</a> or <a href="#">ca533</a>
<code>stc</code>	a vector of three integral values or character string "auto". The numbers indicate the number of characters to split the site code ( <code>stc[1]</code> ), the tree IDs ( <code>stc[2]</code> ), and the core IDs ( <code>stc[3]</code> ). Defaults to <code>c(3, 2, 3)</code> . If "auto", tries to automatically determine the split locations. See Details for further information.
<code>use.cor</code>	a logical flag. If TRUE and <code>stc</code> is "auto", correlation clustering may be used for determining the length of the tree and core parts. See Details.  The following parameters affect the handling of suspected typing errors. Some have different default values in <code>read.ids</code> and <code>autoread.ids</code> .
<code>ignore.site.case</code>	a logical flag. If TRUE, the function does not distinguish between upper case and lower case letters in the site part of the series names.
<code>ignore.case</code>	a logical flag or "auto". If TRUE, the function does not distinguish between upper case and lower case letters in the tree / core part of the series names. The default in <code>read.ids</code> is FALSE, i.e. the difference matters. The default in <code>read.ids</code> is "auto", which means that the function tries to be smart with respect to case sensitivity. In "auto" mode, the function generally ignores case differences, unless doing so would result in additional duplicate combinations of tree and core IDs. Also, when in "auto" mode and <code>stc</code> is "auto", case sensitivity is used in highly heuristic ways when deciding the boundary between the site part and the tree part in uncertain cases.
<code>fix.typos</code>	a logical flag. If TRUE, the function will try to detect and fix typing errors.
<code>typo.ratio</code>	a numeric value larger than 1, affecting the eagerness of the function to fix typing errors. The default is 5. See Details.

## Details

Because dendrochronologists often take more than one core per tree, it is occasionally useful to calculate within vs. between tree variance. The International Tree Ring Data Bank (ITRDB) allows the first eight characters in an *rwl* file for series IDs but these are often shorter. Typically the creators of *rwl* files use a logical labeling method that can allow the user to determine the tree and core ID from the label.

Argument *stc* tells how each series separate into site, tree, and core IDs. For instance a series code might be "ABC011" indicating site "ABC", tree 1, core 1. If this format is consistent then the *stc* mask would be `c(3, 2, 3)` allowing up to three characters for the core ID (i.e., pad to the right). If it is not possible to define the scheme (and often it is not possible to machine read IDs), then the output data frame can be built manually. See Value for format.

The function `autoread.ids` is a wrapper to `read.ids` with `stc="auto"`, i.e. automatic detection of the site / tree / core scheme, and different default values of some parameters. In automatic mode, the names in the same *rwl* can even follow different site / tree / core schemes. As there are numerous possible encoding schemes for naming measurement series, the function cannot always produce the correct result.

With `stc="auto"`, the site part can be one of the following.

- In names mostly consisting of numbers, the longest common prefix is the site part
- Alphanumeric site part ending with alphabet, when followed by numbers and alphabets
- Alphabetic site part (quite complicated actual definition). Setting `ignore.case` to "auto" allows the function to try to guess when a case change in the middle of a sequence of alphabets signifies a boundary between the site part and the tree part.
- The characters before the first sequence of space / punctuation characters in a name that contains at least two such sequences

These descriptions are somewhat general, and the details can be found in regular expressions inside the function. If a name does not match any of the descriptions, it is matched against a previously found site part, starting from the longest.

The following ID schemes are detected and supported in the tree / core part. The detection is done per site.

- Numbers in tree part, core part starts with something else
- Alphabets in tree part, core part starts with something else
- Alphabets, either tree part all lower case and core part all upper case or vice versa. For this to work, `ignore.case` must be set to "auto" or FALSE.
- All digits. In this case, the number of characters belonging to the tree and core parts is detected with one of the following methods.
  - If numeric tree parts were found before, it is assumed that the core part is missing (one core per tree).
  - If the series are numbered continuously, one core per tree is assumed.
  - Otherwise, try to find a core part as the suffix so that the cores are numbered continuously.

If none of the above fits, the tree / core split of the all-digit names will be decided with the methods described further down the list, or finally with the fallback mechanism.

- The combined tree / core part is empty or one character. In this case, the core part is assumed to be missing.
- Tree and core parts separated by a punctuation or white space character

If the split of a tree / core part cannot be found with any of the methods described above, the prefix of the string is matched against a previously found tree part, starting from the longest. The fallback mechanism for the still undecided tree / core parts is one of the following. The first one is used if *use.cor* is TRUE, number two if it is FALSE.

1. Pairwise correlation coefficients are computed between all remaining series. Pairs of series with above median correlation are flagged as similar, and the other pairs are flagged as dissimilar. Each possible number of characters (minimum 1) is considered for the share of the tree ID. The corresponding unique would-be tree IDs determine a set of clusterings where one cluster is formed by all the measurement series of a single tree. For each clustering (allocation of characters), an agreement score is computed. The agreement score is defined as the sum of the number of similar pairs with matching cluster number and the number of dissimilar pairs with non-matching cluster number. The number of characters with the maximum agreement is chosen.
2. If the majority of the names in the site use *k* characters for the tree part, that number is chosen. Otherwise, one core per tree is assumed. Parameter *typo.ratio* has a double meaning as it also defines what is meant by majority here: at least  $\text{typo.ratio} / (\text{typo.ratio} + 1) * n.tot$ , where *n.tot* is the number of names in the site.

In both fallback mechanisms, the number of characters allocated for the tree part will be increased until all trees have a non-zero ID or there are no more characters.

Suspected typing errors will be fixed by the function if *fix.typos* is TRUE. The parameter *typo.ratio* affects the eagerness to fix typos, i.e. the number of counterexamples required to declare a typo. The following main typo fixing mechanisms are implemented:

**Site IDs.** If a rare site string resembles an at least *typo.ratio* times more frequent alternative, and if fixing it would not create any name collisions, make the fix. The alternative string must be unique, or if there is more than one alternative, it is enough if only one of them is a look-alike string. Any kind of substitution in one character place is allowed if the alternative string has the same length as the original string. The alternative string can be one character longer or one character shorter than the original string, but only if it involves interpreting one digit as the look-alike alphabet or vice versa. There are requirements to how long a site string must be in order to be eligible for replacement / typo fixing, i.e. cannot be shortened to zero length, cannot change the only character of a site string. The parameters *ignore.case* and *ignore.site.case* have some effect on this typo fixing mechanism.

**Tree and core IDs.** If all tree / core parts of a site have the same length, each character position is inspected individually. If the characters in the *i*:th position are predominantly digits (alphabets), any alphabets (digits) are changed to the corresponding look-alike digit (alphabet) if there is one. The look-alike groups are {0, O, o}, {1, I, i}, {5, S, s} and {6, G}. The parameter *typo.ratio* determines the decision threshold of interpreting the type of each character position as alphabet (digit): the ratio of alphabets (digits) to the total number of characters must be at least  $\text{typo.ratio} / (\text{typo.ratio} + 1)$ . If a name differs from the majority type in more than one character position, it is not fixed. Also, no fixes are performed if any of them would cause a possible monotonic order of numeric prefixes to break.

The function attempts to convert the tree and core substrings to integral values. When this succeeds, the converted values are copied to the output without modification. When non-integral substrings are observed, each unique tree is assigned a unique integral value. The same applies to cores within a tree, but there are some subtleties with respect to the handling of duplicates. Substrings are sorted before assigning the numeric IDs.

The order of columns in *rwl*, in most cases, does not affect the tree and core IDs assigned to each series.

### Value

A data.frame with column one named "tree" giving an ID for each tree and column two named "core" giving an ID for each core. The original series IDs are copied from *rwl* as rownames. The order of the rows in the output matches the order of the series in *rwl*. If more than one site is detected, an additional third column named "site" will contain a site ID. All columns have integral valued numeric values.

### Author(s)

Andy Bunn (original version) and Mikko Korpela (patches, *stc*="auto", *fix.typos*, etc.).

### See Also

[rwi.stats](#), [read.rwl](#)

### Examples

```
library(utils)
data(ca533)
read.ids(ca533, stc = c(3, 2, 3))
autoread.ids(ca533)
```

---

read.rwl

*Read Ring Width File*

---

### Description

This function reads in a file of ring widths (.rwl) in one of the available formats.

### Usage

```
read.rwl(fname,
          format = c("auto", "tucson", "compact", "tridas", "heidelberg", "csv"),
          ...)
```



**Arguments**

fname	a character vector giving the file name of the rwl file.
format	a character vector giving the format. This must be "auto" (rough automatic detection), "tucson", "compact", "tridas", "heidelberg" or "csv". Automatic format detection is the default but failable.
...	arguments specific to the function implementing the operation for the chosen format.

**Details**

This is a simple wrapper to the functions actually implementing the read operation.

**Value**

If a "tucson", "compact", "heidelberg", "csv" file is read (even through "auto"), returns an object of class c("rwl", "data.frame") with the series in columns and the years as rows. The series IDs are the column names and the years are the row names.

If a "tridas" file is read (even through "auto"), returns a list of results. See [read.tridas](#) for more information.

**Author(s)**

Mikko Korpela

**See Also**

[read.tucson](#), [read.compact](#), [read.tridas](#), [read.fh](#), [csv2rwl](#), [write.rwl](#)

---

read.tridas

*Read Tree Ring Data Standard (TRiDaS) File*

---

**Description**

This function reads in a TRiDaS format XML file. Measurements, derived series and various kinds of metadata are supported.

**Usage**

```
read.tridas(fname, ids.from.titles = FALSE,
             ids.from.identifiers = TRUE, combine.series = TRUE,
             trim.whitespace = TRUE, warn.units = TRUE)
```

## Arguments

<code>fname</code>	character vector giving the file name of the TRiDaS file.
<code>ids.from.titles</code>	logical flag indicating whether to override the (tree, core, radius, measurement) structure imposed by the element hierarchy (element, sample, radius, measurementSeries) of the file. If TRUE, measurement series will be rearranged by matching titles in the file at the aforementioned four levels of the hierarchy. Defaults to FALSE, i.e. the element hierarchy of the file will be used.
<code>ids.from.identifiers</code>	logical flag indicating whether to (partially) override the element hierarchy of the file. If TRUE, measurement series will be grouped according to matching identifiers at the measurementSeries level, where identifiers are available. The changes caused by this option are applied on top of the structure imposed by the file or computed from matching titles if <code>ids.from.titles == TRUE</code> . Defaults to TRUE.
<code>combine.series</code>	logical flag indicating whether to combine two or more measurement series with the same set of (tree, core, radius, measurement) ID numbers. Each set of combined measurement series will be represented by one column of a resulting <code>data.frame</code> . Overlapping years of combined series do not produce a warning. If several data points are available for a given year, the function chooses one in a rather arbitrary manner. This option can only have effect when <code>ids.from.titles    ids.from.identifiers</code> .
<code>trim.whitespace</code>	logical flag indicating whether to replace repeated white spaces in the text content of the file with only one space. Defaults to TRUE, i.e. excess white space will be trimmed from the text.
<code>warn.units</code>	logical flag indicating whether to warn about unitless measurements and “strange” units. The function expects measurements in units that can be converted to millimetres. Defaults to TRUE: warnings will be given. For example, density measurements will trigger warnings, which can be disabled by setting this option to FALSE.

## Details

The Tree Ring Data Standard (TRiDaS) is described in Jansma et. al (2010). Information about the current version of the standard can be found from [TRiDaS website](#).

The parameters used for rearranging (`ids.from.titles`, `ids.from.identifiers`) and combining (`combine.series`) measurement series only affect the four lowest levels of document structure: element, sample, radius, measurementSeries. Series are not reorganized or combined at the upper structural levels (project, object).

## Value

A list with a variable number of components according to the contents of the input file. The possible list components are:

<code>measurements</code>	A <code>data.frame</code> or a list of <code>data.frames</code> with the series in columns and the years as rows. Contains measurements ( <code>&lt;measurementSeries&gt;</code> ) with known years.
---------------------------	--

The series IDs are the column names and the years are the row names. The series IDs are derived from '<title>' elements in the input file. Each unique combination of '<project>', '<object>', '<unit>', '<taxon>', and '<variable>' gets a separate data.frame.

ids	A data.frame or a list of data.frames with columns named "tree", "core", "radius", and "measurement", together giving a unique numeric ID for each column of the data.frame(s) in <i>measurements</i> . If <code>!combine.series &amp;&amp; (ids.from.titles    ids.from.identifiers)</code> , some rows may be non-unique.
titles	A data.frame or a list of data.frames with columns named "tree", "core", "radius", and "measurement", containing the '<title>' hierarchy of each column of the data.frame(s) in <i>measurements</i> .
wood.completeness	A data.frame or a list of data.frames containing wood completeness information. Column names are a subset of the following, almost self-explanatory set: "pith.presence", "heartwood.presence", "sapwood.presence", "last.ring.presence", "last.ring.details", "bark.presence", "n.sapwood", "n.missing.heartwood", "n.missing.sapwood", "missing.heartwood.foundation", "missing.sapwood.foundation", "n.unmeasured.inner", "n.unmeasured.outer".
unit	A character vector giving the unit of the measurements. Length equals the number of data.frames in <i>measurements</i> .
project.id	A numeric vector giving the project ID, i.e. the position of the corresponding '<project>' element), of the measurements in each data.frame in <i>measurements</i> . Length equals the number of data.frames.
project.title	A character vector giving the title of the project of each data.frame in <i>measurements</i> . Length equals the number of data.frames.
site.id	A data.frame giving the site ID (position of '<object>' element(s) within a '<project>') of each data.frame in <i>measurements</i> . May have several columns to reflect the possibly nested '<object>' elements.
site.title	A data.frame giving the site ('<object>') title of each data.frame in <i>measurements</i> . May have several columns to reflect the possibly nested '<object>' elements.
taxon	A data.frame showing the taxonomic name for each data.frame in <i>measurements</i> . Contains some of the following columns: "text", "lang", "normal", "normalId", "normalStd". The first two are a free-form name and its language, and the rest are related to a normalized name.
variable	A data.frame showing the measured variable of each data.frame in <i>measurements</i> . Contains some of the following columns: "text", "lang", "normal", "normalId", "normalStd", "normalTridas". The first two are a free-form name and its language, and the rest are related to a normalized name.
undated	A list of measurements with unknown years, together with metadata. Elements are a subset of the following: <b>data</b> A numeric vector or a list of such vectors containing measurement series

- unit** A character vector giving the unit of the measurements. Length equals the number of measurement series in *undated\$data*
- ids** A data.frame with columns named "tree", "core", "radius", and "measurement", together giving a numeric ID for each measurement series in *undated\$data*. The rows are guaranteed to be unique only when comparing measurement series with the same *project.id* and *site.id*, but not if *ids.from.titles* || *ids.from.identifiers*.
- titles** A data.frame with columns named "tree", "core", "radius", and "measurement", containing the '<title>' hierarchy of each measurement series in *undated\$data*
- project.id** A numeric vector giving the project ID of each measurement series in *undated\$data*
- project.title** A character vector giving the project title of each measurement series in *undated\$data*
- site.id** A data.frame giving the site ID of each measurement series in *undated\$data*
- site.title** A data.frame giving the site title of each measurement series in *undated\$data*
- variable** A data.frame containing the variable of each measurement series in *undated\$data*
- taxon** A data.frame containing taxonomic names of each measurement series in *undated\$data*
- wood.completeness** A data.frame containing wood completeness information of each measurement series in *undated\$data*
- derived A list of calculated series of values, together with metadata. Elements are a subset of the following:
- data** A numeric vector or a list of such vectors containing calculated series of values.
- link** A list of data.frames, one for each series in *derived\$data*, giving links to the measurements used to form the corresponding derived series. Each data.frame has a subset of the following columns: "idRef" (reference to a series in the same file), "xLink" (URI), "identifier", and "domain" (identifier and its domain, not necessarily in the same file).
- project.id** A numeric vector giving the project ID of each derived series in *derived\$data*
- id** A numeric vector giving the ID (order of appearance in the project) of each derived series in *derived\$data*
- title** A character vector giving the title of each derived series in *derived\$data*
- project.title** A character vector giving the project title of each derived series in *derived\$data*
- unit** A character vector giving the unit of the derived series. Length equals the number of series in *derived\$data*.
- standardizing.method** A character vector giving the standardizing method of the derived series. Length equals the number of series in *derived\$data*.
- variable** A data.frame containing the variable of each series in *derived\$data*

type	<p>A data.frame containing the type of various entities, and metadata related to each 'type' element. Contents are NA where the metadata is not applicable (e.g., no <i>tree.id</i> when the 'type' element refers to a project). Columns are a subset of the following:</p> <p><b>text</b> The text of the 'type' element</p> <p><b>lang</b> The language of the text</p> <p><b>normal</b> The normalized name of the type</p> <p><b>normalId</b> The ID value of the type in the standard dictionary</p> <p><b>normalStd</b> The name of the standard</p> <p><b>project.id</b> The ID of the project</p> <p><b>site.id</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the ID of the site where the '&lt;type&gt;' element appeared.</p> <p><b>tree.id</b> The ID of the tree</p> <p><b>core.id</b> The ID of the core</p> <p><b>derived.id</b> The ID of the derived series</p> <p><b>project.title</b> The title of the project</p> <p><b>site.title</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the title of the site where the '&lt;type&gt;' element appeared.</p> <p><b>tree.title</b> The title of the tree</p> <p><b>core.title</b> The title of the core</p> <p><b>derived.title</b> The title of the derived series</p>
comments	<p>A data.frame containing comments to various entities, and metadata related to each 'comments' element. Contents are NA where the metadata is not applicable. Columns are a subset of the following:</p> <p><b>text</b> The text of the 'comments' element</p> <p><b>project.id</b> The ID of the project</p> <p><b>site.id</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the ID of the site.</p> <p><b>tree.id</b> The ID of the tree</p> <p><b>core.id</b> The ID of the core</p> <p><b>radius.id</b> The ID of the radius</p> <p><b>measurement.id</b> The ID of the measurement series</p> <p><b>derived.id</b> The ID of the derived series</p> <p><b>project.title</b> The title of the project</p> <p><b>site.title</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the title of the site.</p> <p><b>tree.title</b> The title of the tree</p> <p><b>core.title</b> The title of the core</p> <p><b>radius.title</b> The title of the radius</p> <p><b>measurement.title</b> The title of the measurement series</p> <p><b>derived.title</b> The title of the derived series</p>

identifier	<p>A <code>data.frame</code> containing identifiers of various entities, and metadata related to each 'identifier' element. Contents are NA where the metadata is not applicable. Columns are a subset of the following:</p> <p><b>text</b> The text of the 'identifier' element</p> <p><b>domain</b> The domain which the identifier is applicable to</p> <p><b>project.id</b> The ID of the project</p> <p><b>site.id</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the ID of the site.</p> <p><b>tree.id</b> The ID of the tree</p> <p><b>core.id</b> The ID of the core</p> <p><b>radius.id</b> The ID of the radius</p> <p><b>measurement.id</b> The ID of the measurement series</p> <p><b>derived.id</b> The ID of the derived series</p> <p><b>project.title</b> The title of the project</p> <p><b>site.title</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the title of the site.</p> <p><b>tree.title</b> The title of the tree</p> <p><b>core.title</b> The title of the core</p> <p><b>radius.title</b> The title of the radius</p> <p><b>measurement.title</b> The title of the measurement series</p> <p><b>derived.title</b> The title of the derived series</p>
remark	<p>A list of remarks concerning individual measured or derived values, with some of the following items:</p> <p><b>measurements</b> Remarks related to measurements with a known year. A <code>data.frame</code> with the following columns:</p> <p><b>text</b> The remark</p> <p><b>frame</b> Index to a <code>data.frame</code> in <i>measurements</i></p> <p><b>row</b> Index to a row of the <code>data.frame</code></p> <p><b>col</b> Index to a column of the <code>data.frame</code></p> <p><b>undated</b> Remarks related to measurements without a known year. A <code>data.frame</code> with the following columns:</p> <p><b>text</b> The remark</p> <p><b>series</b> Index to a series in <i>undated\$data</i></p> <p><b>idx</b> Index to a value in the series</p> <p><b>derived</b> Remarks related to derived values. A <code>data.frame</code> with the following columns:</p> <p><b>text</b> The remark</p> <p><b>series</b> Index to a series in <i>derived\$data</i></p> <p><b>idx</b> Index to a value in the series</p>
laboratory	<p>A <code>data.frame</code> or a list of <code>data.frames</code> with one item per project. Each <code>data.frame</code> contains information about the research laboratories involved in the project. Columns are a subset of the following:</p>

	<p><b>name</b> Name of the laboratory</p> <p><b>acronym</b> Acronym of the name</p> <p><b>identifier</b> Identifier</p> <p><b>domain</b> Domain which the identifier is applicable to</p> <p><b>addressLine1</b> Address</p> <p><b>addressLine2</b> Another address line</p> <p><b>cityOrTown</b> City or town</p> <p><b>stateProvinceRegion</b> State, province or region</p> <p><b>postalCode</b> Postal code</p> <p><b>country</b> Country</p>
research	<p>A data.frame or a list of data.frames with one item per project. Each data.frame contains information about the systems in which the research project is registered. Columns are the following:</p> <p><b>identifier</b> Identifier</p> <p><b>domain</b> Domain which the identifier is applicable to</p> <p><b>description</b> General description</p>
altitude	<p>A data.frame containing the altitude of trees. Columns are the following:</p> <p><b>metres</b> The altitude in metres</p> <p><b>project.id</b> The ID of the project</p> <p><b>site.id</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the ID of the site.</p> <p><b>tree.id</b> The ID of the tree</p> <p><b>project.title</b> The title of the project</p> <p><b>site.title</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the title of the site.</p> <p><b>tree.title</b> The title of the tree</p>
preferred	<p>A data.frame containing links to preferred measurement series. Columns are a subset of the following:</p> <p><b>idRef</b> Reference to a series in the same file</p> <p><b>xLink</b> URI</p> <p><b>identifier</b> Identifier of a series not necessarily in the same file</p> <p><b>domain</b> Domain which the identifier is applicable to</p> <p><b>project.id</b> The ID of the project</p> <p><b>site.id</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the ID of the site.</p> <p><b>tree.id</b> The ID of the tree</p> <p><b>project.title</b> The title of the project</p> <p><b>site.title</b> One or more columns with this prefix, depending on the maximum depth of the '&lt;object&gt;' hierarchy. Gives the title of the site.</p> <p><b>tree.title</b> The title of the tree</p>

**Note**

This is an early version of the function. Bugs are likely to exist, and parameters and return values are subject to change. Not all metadata defined in the TRiDaS specification is supported – unsupported elements are quietly ignored.

**Author(s)**

Mikko Korpela

**References**

Jansma, E., Brewer, P. W., and Zandhuis, I. (2010) TRiDaS 1.1: The tree-ring data standard. *Dendrochronologia*, **28**(2), 99–130.

TRiDaS – The Tree Ring Data Standard. <http://www.tridas.org/>.

**See Also**

[read.rwl](#), [read.tucson](#), [read.compact](#), [read.fh](#), [write.tridas](#)

---

read.tucson

*Read Tucson Format Ring Width File*

---

**Description**

This function reads in a Tucson (decadal) format file of ring widths (.rwl).

**Usage**

```
read.tucson(fname, header = NULL, long = FALSE,
            encoding = getOption("encoding"), edge.zeros = TRUE)
```

**Arguments**

fname	a character vector giving the file name of the rwl file.
header	logical flag indicating whether the file has a header. If NULL then the function will attempt to determine if a header exists.
long	logical flag indicating whether dates in file span 0 CE and therefore use negative numbers. If TRUE only the first 7 characters can be used for series IDs. If FALSE then series IDs can be up to 8 characters.
encoding	the name of the encoding to be used when reading the rwl file. Usually the default value will work, but an rwl file written in a non-default encoding may crash the function. In that case, identifying the encoding and specifying it here should fix the problem. Examples of popular encodings available on many systems are "ASCII", "UTF-8", and "latin1" alias "ISO-8859-1". See the help of <a href="#">file</a> .
edge.zeros	logical flag indicating whether leading or trailing zeros in series will be preserved (when the flag is TRUE, the default) or discarded, i.e. marked as NA (when FALSE).



**Details**

This reads in a standard rwl file as defined according to the standards of the ITRDB at <http://www1.ncdc.noaa.gov/pub/data/paleo/treering/treeinfo.txt>. Despite the standards at the ITRDB, this occasionally fails due to formatting problems.

**Value**

An object of class `c("rwl", "data.frame")` with the series in columns and the years as rows. The series IDs are the column names and the years are the row names.

**Author(s)**

Andy Bunn. Patched and greatly improved by Mikko Korpela.

**See Also**

[read.rwl](#), [read.compact](#), [read.tridas](#), [read.fh](#), [write.tucson](#)

---

redfit

*Red-Noise Spectra of Time-Series*


---

**Description**

Estimate red-noise spectra from a possibly unevenly spaced time-series.

**Usage**

```
redfit(x, t, tType = c("time", "age"), nsim = 1000, mctest = TRUE,
      ofac = 4, hifac = 1, n50 = 3, rhopre = NULL,
      p = c(0.10, 0.05, 0.02), iwin = 2,
      txOrdered = FALSE, verbose = FALSE, seed = NULL,
      maxTime = 10, nLimit = 10000)
```

```
runcrit(n, p = c(0.10, 0.05, 0.02), maxTime = 10, nLimit = 10000)
```

**Arguments**

<code>x</code>	a numeric vector representing a possibly unevenly spaced time-series.
<code>t</code>	a numeric vector of times or ages corresponding to <code>x</code> . If missing, this is set to an evenly spaced increasing integer sequence (1, 2, ...) along <code>x</code> . See <code>txOrdered</code> .
<code>tType</code>	a character string indicating the type of the <code>t</code> vector: either times or ages.
<code>nsim</code>	a numeric value giving the number of simulated AR1 spectra to compute.
<code>mctest</code>	a logical flag. If TRUE, performs a Monte Carlo test for computing red noise false-alarm levels. In that case, the result list will contain non-NULL elements "ci80", "ci90", "ci95" and "ci99".
<code>ofac</code>	oversampling factor for Lomb-Scargle Fourier transform. A numeric value.

hifac	maximum frequency to analyze relative to the Nyquist frequency. A numeric value.
n50	number of segments. The segments overlap by about 50 percent.
rhopr	a numeric value giving the prescribed autocorrelation coefficient. If NULL or negative, the autocorrelation coefficient will be estimated from the data.
p	a numeric or <code>bigq</code> (if package "gmp" is installed) vector of significance levels for a statistical test considering the number of runs in a sequence. See 'Details'.
iwin	the type of window used for scaling the values of each segment of data. A numeric value or one of "rectangular", "welch i", "hanning", "triangular" and "blackman-harris". Integers 0:4 correspond to the character values, in this order. The default <code>iwin = 2</code> corresponds to the "hanning" window.
txOrdered	a logical flag. If TRUE, it is assumed that <code>t</code> is in ascending order without duplicates. If FALSE (the default), <code>t</code> will be sorted and <code>x</code> reordered accordingly. Values of <code>x</code> at identical values of <code>t</code> are averaged. If duplicates are found, the non-duplicated <code>t</code> and averaged <code>x</code> will be included in the return value of the function.
verbose	a logical flag. If TRUE, the function prints some information while operating.
seed	a value to be given to <code>set.seed</code> at the start of the function. The value is also recorded in the list returned. If not NULL, this can be used for reproducible results.
maxTime	a numeric value giving the approximate maximum time in seconds to use for computing the exact acceptance regions of the number of runs test. See also <code>nLimit</code> .
nLimit	a numeric value giving the maximum <code>n</code> for which <code>runcrit</code> will try to compute an exact solution to the acceptance regions of the number of runs test. Precomputed solutions may exist for larger <code>n</code> ). This limit is in place because a part of the exact solution always needs to be computed in order to roughly estimate the total time and whether it would exceed <code>maxTime</code> . If <code>nLimit</code> is very large, <code>maxTime</code> may be (greatly) exceeded while computing the aforementioned part of the exact solution.
n	an integral value giving the length of the sequence in the number of runs test.

## Details

Function `redfit` computes the spectrum of a possibly unevenly sampled time-series by using the Lomb-Scargle Fourier transform. The spectrum is bias-corrected using spectra computed from simulated AR1 series and the theoretical AR1 spectrum.

The function duplicates the functionality of program REDFIT by Schulz and Mudelsee. See the manual of that program for more information. The results of this function should be very close to REDFIT. However, some changes have been made:

- More precision is used in some constants and computations.
- All the data are used: the last segment always contains the last pair of  $(t, x)$ . There may be small differences between `redfit` and REDFIT with respect to the number of points per segment and the overlap of consecutive segments.

- The critical values of the runs test (see the description of `runcrit` below) differ between `redfit` and `REDFIT`. The approximate equations in `REDFIT` produce values quite far off from the exact values when the number of frequencies is large.
- The user can select the significance levels of the runs test.
- Most of the window functions have been adjusted.
- 6 dB bandwidths have been computed for discrete-time windows.

Function `runcrit` computes the limits of the acceptance region of a number of runs test: assuming a sequence of  $n$  i.i.d. discrete random variables with two possible values  $a$  and  $b$  of equal probability (0.5), we are examining the distribution of the number of runs. A run is an uninterrupted sequence of only  $a$  or only  $b$ . The minimum number of runs is 1 (a sequence with only  $a$  or only  $b$ ) while the maximum number is  $n$  (alternating  $a$  and  $b$ ). See Bradley, p. 253–254, 259–263. The function is also called from `redfit`; see `rcnt` in ‘Value’ for the interpretation. In this case the arguments  $p$ , `maxTime` and `nLimit` are passed from `redfit` to `runcrit`, and  $n$  is the number of output frequencies.

The results of `runcrit` have been essentially precomputed for some values of  $p$  and  $n$ . If a precomputed result is not found and  $n$  is not too large (`nLimit`, `maxTime`), the exact results are computed on-demand. Otherwise, or if package “`gmp`” is not installed, the normal distribution is used for approximation.

### Value

Function `runcrit` returns a list containing `rcritlo`, `rcrithi` and `rcritexact` (see below). Function `redfit` returns a list with the following elements:

<code>varx</code>	variance of $x$ estimated from its spectrum. A numeric value.
<code>rho</code>	average autocorrelation coefficient, either estimated from the data or prescribed ( <code>rhopre</code> ). A numeric value.
<code>tau</code>	the time scale of an AR1 process corresponding to <code>rho</code> . A numeric value.
<code>rcnt</code>	a numeric value giving the number of runs to be used for a statistical test studying the difference between a theoretical AR1 spectrum and the bias-corrected spectrum estimated from the data. Null hypothesis: the two spectra agree, i.e. the probability of either being larger than the other is 0.5 at every point. Requires that <code>iwin == 0</code> (“rectangular”), <code>ofac == 1</code> and <code>n50 == 1</code> . Otherwise the test is not performed and <code>rcnt</code> is NULL.
<code>rcritlo</code>	a numeric vector of critical low values for the number of runs, i.e. the lowest value for accepting the null hypothesis at each level of significance $p$ . When returned from <code>redfit</code> , NULL when <code>rcnt</code> is NULL.
<code>rcrithi</code>	a numeric vector of critical high values for the number of runs, i.e. the highest value for accepting the null hypothesis at each level of significance $p$ . When returned from <code>redfit</code> , NULL when <code>rcnt</code> is NULL.
<code>rcritexact</code>	a logical vector specifying whether each pair of <code>rcritlo</code> and <code>rcrithi</code> are exact values (TRUE) or approximated from a normal distribution (FALSE). When returned from <code>redfit</code> , NULL when <code>rcnt</code> is NULL.
<code>freq</code>	the frequencies used. A numeric vector. The other numeric vectors have the same length, i.e. one value for each frequency studied.

<code>gxx</code>	estimated spectrum of the data ( $t, x$ ). A numeric vector.
<code>gxxc</code>	red noise corrected spectrum of the data. A numeric vector.
<code>grravg</code>	average AR1 spectrum over <i>nsim</i> simulations. A numeric vector.
<code>gredth</code>	theoretical AR1 spectrum. A numeric vector.
<code>corr</code>	a numeric vector containing the by-frequency correction: <i>gxxc</i> equals <i>gxx</i> divided by <i>corr</i> (or multiplied by the inverse correction). Also used for computing <i>ci80</i> , <i>ci90</i> , <i>ci95</i> and <i>ci99</i> .
<code>ci80</code>	a numeric vector containing the bias-corrected 80th percentile (by frequency) red noise spectrum. Only if <i>mctest</i> is TRUE.
<code>ci90</code>	a numeric vector containing the 90th percentile red noise spectrum.
<code>ci95</code>	95th percentile red noise spectrum.
<code>ci99</code>	99th percentile red noise spectrum.
<code>call</code>	the call to the function. See <a href="#">match.call</a> .
<code>params</code>	A list with the following items: <b>np</b> number of points in the data. <b>nseg</b> number of points in each segment. <b>nfreq</b> number of frequencies in the results. <b>avgdt</b> average sampling interval. <b>df</b> difference between consecutive frequencies. <b>fnyq</b> average Nyquist frequency. <b>n50</b> value of the <i>n50</i> argument. <b>ofac</b> value of the <i>ofac</i> argument. <b>hifac</b> value of the <i>hifac</i> argument. <b>segskip</b> the ideal, non-rounded difference between starting indices of consecutive segments. <b>iwin</b> value of the <i>iwin</i> argument. If a character value was used, this contains the corresponding number used internally. <b>nsim</b> value of the <i>nsim</i> argument. <b>mctest</b> value of the <i>mctest</i> argument. <b>rhopre</b> value of the <i>rhopre</i> argument.
<code>vers</code>	version of dplr. See <a href="#">packageVersion</a> .
<code>seed</code>	value of the <i>seed</i> argument.
<code>t</code>	if duplicated values of <i>t</i> are given, the non-duplicated numeric time or age vector (see <i>tType</i> ) is returned here. Otherwise NULL. See <i>txOrdered</i> .
<code>x</code>	if duplicated values of <i>t</i> are given, the averaged numeric data vector is returned here. Otherwise NULL.

**Author(s)**

Mikko Korpela. Examples by Andy Bunn.

## References

Function `redfit` is based on the Fortran program **REDFIT** (version 3.8e), which is in the public domain.

Bradley, J. V. (1968) *Distribution-Free Statistical Tests*. Prentice-Hall.

Schulz, M. and Mudelsee, M. (2002) REDFIT: estimating red-noise spectra directly from unevenly spaced paleoclimatic time series. *Computers & Geosciences*, **28**(3), 421–426.

## See Also

[print.redfit](#)

## Examples

```
# Create a simulated tree-ring width series that has a red-noise
# background ar1=phi and sd=sigma and an embedded signal with
# a period of 10 and an amplitude of have the rednoise sd.
library(graphics)
library(stats)
runif(1)
rs <- .Random.seed
set.seed(123)
nyrs <- 500
yrs <- 1:nyrs

# Here is an ar1 time series with a mean of 2mm,
# an ar1 of phi, and sd of sigma
phi <- 0.7
sigma <- 0.3
sigma0 <- sqrt((1 - phi^2) * sigma^2)
x <- arima.sim(list(ar = phi), n = nyrs, sd = sigma0) + 2

# Here is a sine wave at f=0.1 to add in with an amplitude
# equal to half the sd of the red noise background
per <- 10
amp <- sigma0 / 2
wav <- amp * sin(2 * pi / per * yrs)

# Add them together so we have signal and noise
x <- x + wav

# Here is the redfit spec
redf.x <- redfit(x, nsim = 500)

# Acceptance region of number of runs test
# (not useful with default arguments of redfit())
runcrit(length(redf.x[["freq"]]))

op <- par(no.readonly = TRUE) # Save to reset on exit
par(tcl = 0.5, mar = rep(2.2, 4), mgp = c(1.1, 0.1, 0))

plot(redf.x[["freq"]], redf.x[["gxxc"]],
```

```

        ylim = range(redf.x[["ci99"]], redf.x[["gxxc"]]),
        type = "n", ylab = "Spectrum (dB)", xlab = "Frequency (1/yr)",
        axes = FALSE)
grid()
lines(redf.x[["freq"]], redf.x[["gxxc"]], col = "#1B9E77")
lines(redf.x[["freq"]], redf.x[["ci99"]], col = "#D95F02")
lines(redf.x[["freq"]], redf.x[["ci95"]], col = "#7570B3")
lines(redf.x[["freq"]], redf.x[["ci90"]], col = "#E7298A")
freqs <- pretty(redf.x[["freq"]])
pers <- round(1 / freqs, 2)
axis(1, at = freqs, labels = TRUE)
axis(3, at = freqs, labels = pers)
mtext(text = "Period (yr)", side = 3, line = 1.1)
axis(2); axis(4)
legend("topright", c("x", "CI99", "CI95", "CI90"), lwd = 2,
      col = c("#1B9E77", "#D95F02", "#7570B3", "#E7298A"),
      bg = "white")
box()

## Not run:
# Second example with tree-ring data
# Note the long-term low-freq signal in the data. E.g.,
# crn.plot(cana157)

library(utils)
data(cana157)
yrs <- time(cana157)
x <- cana157[, 1]
redf.x <- redfit(x, nsim = 1000)

plot(redf.x[["freq"]], redf.x[["gxxc"]],
     ylim = range(redf.x[["ci99"]], redf.x[["gxxc"]]),
     type = "n", ylab = "Spectrum (dB)", xlab = "Frequency (1/yr)",
     axes = FALSE)
grid()
lines(redf.x[["freq"]], redf.x[["gxxc"]], col = "#1B9E77")
lines(redf.x[["freq"]], redf.x[["ci99"]], col = "#D95F02")
lines(redf.x[["freq"]], redf.x[["ci95"]], col = "#7570B3")
lines(redf.x[["freq"]], redf.x[["ci90"]], col = "#E7298A")
freqs <- pretty(redf.x[["freq"]])
pers <- round(1 / freqs, 2)
axis(1, at = freqs, labels = TRUE)
axis(3, at = freqs, labels = pers)
mtext(text = "Period (yr)", side = 3, line = 1.1)
axis(2); axis(4)
legend("topright", c("x", "CI99", "CI95", "CI90"), lwd = 2,
      col = c("#1B9E77", "#D95F02", "#7570B3", "#E7298A"),
      bg = "white")
box()
par(op)

## End(Not run)
.Random.seed <- rs

```

---

rwi.stats.running      *(Running Window) Statistics on Detrended Ring-Width Series*

---

## Description

These functions calculate descriptive statistics on a data.frame of (usually) ring-width indices. The statistics are optionally computed in a running window with adjustable length and overlap. The data can be filtered so that the comparisons are made to on just high-frequency data.

## Usage

```
rwi.stats.running(rwi, ids = NULL, period = c("max", "common"),
                 method = c("spearman", "pearson", "kendall"),
                 prewhiten=FALSE, n=NULL,
                 running.window = TRUE,
                 window.length = min(50, nrow(rwi)),
                 window.overlap = floor(window.length / 2),
                 first.start = NULL,
                 min.corr.overlap = min(30, window.length),
                 round.decimals = 3,
                 zero.is.missing = TRUE)
```

```
rwi.stats(rwi, ids=NULL, period=c("max", "common"),
          method = c("spearman", "pearson", "kendall"), ...)
```

```
rwi.stats.legacy(rwi, ids=NULL, period=c("max", "common"))
```

## Arguments

rwi	a data.frame with detrended and standardized ring width indices as columns and years as rows such as that produced by <a href="#">detrend</a> .
ids	an optional data.frame with column one named "tree" giving a numeric ID for each tree and column two named "core" giving a numeric ID for each core. Defaults to one core per tree as <code>data.frame(tree=1:ncol(rwi), core=rep(1, ncol(rwi)))</code> .
period	a character string, either "common" or "max" indicating whether correlations should be limited to complete observations over the period common to all cores (i.e. rows common to all samples) or the maximum pairwise overlap. Defaults to "max".
method	Can be either "pearson", "kendall", or "spearman" which indicates the correlation coefficient to be used. Defaults to "spearman". See <a href="#">cor</a> .
n	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
prewhiten	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .

<code>running.window</code>	logical flag indicating whether to use a running window (TRUE, the default) or to ignore the other window parameters and effectively use one window covering all years (FALSE).
<code>window.length</code>	numeric value indicating the length of the running window in years. The default is 50 years or the number of years (rows) in <code>rwi</code> , whichever is smaller.
<code>window.overlap</code>	numeric value indicating the overlap of consecutive window positions, i.e. the number of common years. The default is half of the window length, rounded down.
<code>first.start</code>	an optional numeric value setting the position of the first window. Must be a value between 1 and $n.years - window.length + 1$ , where $n.years$ is the number of years in <code>rwi</code> . The default value NULL lets the function make the decision using some heuristic rules.
<code>min.corr.overlap</code>	numeric value setting the minimum number of common years in any pair of ring-width series required for their correlation to be included in the calculations. Smaller overlaps are considered to yield unreliable correlation values which are ignored. Defaults to the minimum of 30 and the length of the window. One way to lift the restriction and include all correlations is to set <code>min.corr.overlap = 0</code> .
<code>round.decimals</code>	non-negative integer numeric value setting the desired number of decimal places in the results. Use NA, NULL or a negative number for no rounding.
<code>zero.is.missing</code>	logical flag indicating whether to treat zeros as missing values (TRUE, the default) or to include them in computation (FALSE).
<code>...</code>	arguments passed on to <code>rwi.stats.running</code>

## Details

This calculates a variety of descriptive statistics commonly used in dendrochronology.

The function `rwi.stats` is a wrapper that calls `rwi.stats.running` with `running.window = FALSE`. The results may differ from those prior to `dpIR 1.5.3`, where the former `rwi.stats` (now renamed to `rwi.stats.legacy`) was replaced with a call to `rwi.stats.running`.

For correctly calculating the statistics on within and between series variability, an appropriate mask (parameter `ids`) must be provided that identifies each series with a tree as it is common for dendrochronologists to take more than one core per tree. The function `read.ids` is helpful for creating a mask based on the series ID.

If `ids` has duplicate tree/core combinations, the corresponding series are averaged before any statistics are computed. The value of the parameter `zero.is.missing` is relevant in the averaging: TRUE ensures that zeros don't contribute to the average. The default value of `zero.is.missing` is TRUE. The default prior to `dpIR 1.5.3` was FALSE. If the parameter is set to FALSE, the user will be warned in case zeros are present. Duplicate tree/core combinations are not detected by `rwi.stats.legacy`.

Row names of `ids` may be used for matching the IDs with series in `rwi`. In this case, the number of rows in `ids` is allowed to exceed the number of series. If some names of `rwi` are missing from the row names of `ids`, the rows of `ids` are assumed to be in the same order as the columns of `rwi`, and the dimensions must match. The latter is also the way that `rwi.stats.legacy` handles `ids`, i.e. names are ignored and dimensions must match.



Note that `period = "common"` can produce NaN for many of the stats if there is no common overlap period among the cores. This happens especially in chronologies with floating subfossil samples (e.g., [ca533](#)).

Some of the statistics are specific to dendrochronology (e.g., the effective number of cores or the expressed population signal). Users unfamiliar with these should see Cook and Kairiukstis (1990) and Fritts (2001) for further details for computational details on the output. The signal-to-noise ratio is calculated following Cook and Pederson (2011).

If desired, the `rwi` can be filtered in the same manner as the family of cross-dating functions using `prewhiten` and `n`. See the help page for [corr.rwl.seg](#) for more details.

### Value

A data.frame containing the following columns (each row corresponds to one position of the window):

<code>start.year</code>	the first year in the window. Not returned if <code>running.window</code> is FALSE or called as <code>rwi.stats</code> or <code>rwi.stats.legacy</code> .
<code>mid.year</code>	the middle year in the window, rounded down. Not returned if <code>running.window</code> is FALSE or called as <code>rwi.stats</code> or <code>rwi.stats.legacy</code> .
<code>end.year</code>	the last year in the window. Not returned if <code>running.window</code> is FALSE or called as <code>rwi.stats</code> or <code>rwi.stats.legacy</code> .
<code>n.cores</code>	the number of cores
<code>n.trees</code>	the number of trees
<code>n</code>	the average number of trees (for each year, a tree needs at least one non-NA core in order to be counted). Not returned in the results of <code>rwi.stats.legacy</code>
<code>n.tot</code>	total number of correlations calculated as $n.wt + n.bt$ . Equal to $n.cores * (n.cores - 1) / 2$ if there is overlap between all samples
<code>n.wt</code>	number of within-tree correlations computed
<code>n.bt</code>	number of between-tree correlations computed
<code>rbar.tot</code>	the mean of all the correlations between different cores
<code>rbar.wt</code>	the mean of the correlations between series from the same tree over all trees
<code>rbar.bt</code>	the mean interseries correlation between all series from different trees
<code>c.eff</code>	the effective number of cores (takes into account the number of within-tree correlations in each tree)
<code>rbar.eff</code>	the effective signal calculated as $rbar.bt / (rbar.wt + (1 - rbar.wt) / c.eff)$
<code>eps</code>	the expressed population signal calculated using the average number of trees as $n * rbar.eff / ((n - 1) * rbar.eff + 1)$
<code>snr</code>	the signal to noise ratio calculated using the average number of trees as $n * rbar.eff / (1 - rbar.eff)$

### Note

This function uses the `foreach` looping construct with the `%dopar%` operator. For parallel computing and a potential speedup, a parallel backend must be registered before running the function.

**Author(s)**

Mikko Korpela, based on [rwi.stats.legacy](#) by Andy Bunn

**References**

Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.

Cook, E. R. and Pederson, N. (2011) Uncertainty, Emergence, and Statistics in Dendrochronology. In Hughes, M. K., Swetnam, T. W., and Diaz, H. F., editors, *Dendroclimatology: Progress and Prospects*, pages 77–112. Springer. ISBN-13: 978-1-4020-4010-8.

Fritts, H. C. (2001) *Tree Rings and Climate*. Blackburn. ISBN-13: 978-1-930665-39-2.

**See Also**

[detrend](#), [cor](#), [read.ids](#), [rwi.stats](#), [corr.rwl.seg](#)

**Examples**

```
library(utils)
data(gp.rwl)
data(gp.po)
gp.rwi <- cms(rwl = gp.rwl, po = gp.po)
gp.ids <- read.ids(gp.rwl, stc = c(0, 2, 1))
# On a running window
rwi.stats.running(gp.rwi, gp.ids)
## With no running window (i.e. running.window = FALSE)
rwi.stats(gp.rwi, gp.ids)
## Restrict to common overlap (in this case 1899 to 1987)
rwi.stats(gp.rwi, gp.ids, period="common")
rwi.stats.legacy(gp.rwi, gp.ids) # rwi.stats prior to dp1R 1.5.3

## Not run:
library(graphics)
def.par <- par(no.readonly=TRUE)
## Plot the chronology showing a potential cutoff year based on EPS
eps.cut <- 0.92 # An arbitrary EPS cutoff for demonstration
gp.crn <- chron(gp.rwi)
## Running stats on the rwi with an window
foo <- rwi.stats.running(gp.rwi, gp.ids, window.length = 80)
yrs <- time(gp.crn)
bar <- data.frame(yrs = c(min(yrs), foo$mid.year, max(yrs)),
                  eps = c(NA, foo$eps, NA))
par(mar = c(2, 2, 2, 2), mgp = c(1.1, 0.1, 0), tcl = 0.25,
     mfcol = c(2, 1), xaxs='i')
plot(yrs, gp.crn[, 1], type = "n", xlab = "Year",
      ylab = "RWI", axes=FALSE)
cutoff <- max(bar$yrs[bar$eps < eps.cut], na.rm = TRUE)
xx <- c(500, 500, cutoff, cutoff)
yy <- c(-1, 3, 3, -1)
polygon(xx, yy, col = "grey80")
abline(h = 1, lwd = 1.5)
```

```

lines(yrs, gp.crn[, 1], col = "grey50")
lines(yrs, ffcaps(gp.crn[, 1], nyrs = 32), col = "red", lwd = 2)
axis(1); axis(2); axis(3);
par(new = TRUE)
## Add EPS
plot(bar$yrs, bar$eps, type = "b", xlab = "", ylab = "",
      axes = FALSE, pch = 20, col = "blue")
axis(4, at = pretty(foo$eps))
mtext("EPS", side = 4, line = 1.1)
box()
## Second plot is the chronology after the cutoff only
## Chronology is rebuilt using just years after cutoff but
## that difference is essentially nil.
yr.mask <- yrs > cutoff
yrs2 <- yrs[yr.mask]
gp.crn2 <- chron(gp.rwi[yr.mask, ])
plot(yrs2, gp.crn2[, 1], type = "n",
      xlab = "Year", ylab = "RWI", axes=FALSE)
abline(h = 1, lwd = 1.5)
lines(yrs2, gp.crn2[, 1], col = "grey50")
lines(yrs2, ffcaps(gp.crn2[, 1], nyrs = 32),
      col = "red", lwd = 2)
axis(1); axis(2); axis(3); axis(4)
box()
par(def.par)

## End(Not run)

```

---

rwl.report

*Do some reporting on a RWL object*


---

## Description

This function generates a small report on a `rwl` (or `rwi`) object that gives the user some basic information on the data including the number of series, the span of the data, the mean interseries correlation, the number of missing rings (zeros), internal NA values, and rings that are very small, or very large.

## Usage

```
rwl.report(rwl, small.thresh=NA, big.thresh=NA)
```

## Arguments

<code>rwl</code>	a data.frame of ring widths with <code>rownames(x)</code> containing years and <code>colnames(x)</code> containing each series ID such as produced by <code>read.rwl</code>
<code>small.thresh</code>	a numeric value for the threshold value that will cause small rings to be listed. If values is NA this will be omitted.
<code>big.thresh</code>	a numeric value for the threshold value that will cause large rings to be listed. If values is NA this will be omitted.

**Details**

This report is a list containing the number of series, the mean length of all the series, the first year, last year, the mean first-order autocorrelation (via [summary.rwl](#)), the mean interseries correlation (via [interseries.cor](#)), the years where a series has a missing ring (zero), internal NA, very small ring, and very large rings.

This output of this function is not typically meant for the user to access but has a `print` method that formats that data for the user.

**Value**

A list with elements containing descriptive information on the `rwl` object.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**

[read.rwl](#), [summary.rwl](#), [interseries.cor](#)

**Examples**

```
data("gp.rwl")
rwl.report(rwl = gp.rwl)
# list very small (smallest 1pct) of rings as well
one.pct <- quantile(gp.rwl[gp.rwl != 0], na.rm=TRUE, probs=0.01)
rwl.report(rwl = gp.rwl, small.thresh = one.pct)
```

---

rwl.stats

*Calculate Descriptive Summary Statistics on Ring-Width Series*

---

**Description**

This function calculates descriptive statistics on a `rwl` object of raw or detrended ring-width series.

**Usage**

```
rwl.stats(rwl)

## S3 method for class 'rwl'
summary(object, ...)
```

**Arguments**

`rwl`, `object` a `rwl` object with (usually) raw ring-width series as columns and years as rows such as that produced by [read.rwl](#). It is sometimes desirable to run this on detrended (e.g., `rwi`) data.

`...` Additional arguments from the generic function. These are silently ignored.

## Details

This calculates a variety of descriptive statistics commonly used in dendrochronology (see below). Users unfamiliar with these should see Cook and Kairiukstis (1990) and Fritts (2001) for further details.

The [summary](#) method for class "rwl" is a wrapper for `rwl.stats`.

## Value

A data.frame containing descriptive stats on each "series". These are the first and last year of the series as well as the length of the series ("first", "last", "year"). The mean, median, standard deviation are given ("mean", "median", "stdev") as are the skewness, two measures of sensitivity, the Gini coefficient, and first order autocorrelation ("skew", "sens1", "sens2", "gini.coef", "ar1").

Note that mean sensitivity is not a robust statistic that should rarely, if ever, be used (Bunn et al. 2013).

## Author(s)

Andy Bunn. Slightly improved by Mikko Korpela.

## References

Bunn, A. G., Jansma, E., Korpela, M., Westfall, R. D., and Baldwin, J. (2013) Using simulations and data to evaluate mean sensitivity ( $\zeta$ ) as a useful statistic in dendrochronology. *Dendrochronologia*, **31**(3), 250–254.

Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.

Fritts, H. C. (2001) *Tree Rings and Climate*. Blackburn. ISBN-13: 978-1-930665-39-2.

## See Also

[rwi.stats](#), [read.rwl](#)

## Examples

```
library(utils)
data(ca533)
rwl.stats(ca533)
summary(ca533)
```

---

 sea

---

*Superposed Epoch Analysis*


---

**Description**

This function calculates the significance of the departure from the mean for a given set of key event years and lagged years.

**Usage**

```
sea(x, key, lag = 5, resample = 1000)
```

**Arguments**

x	a chronology data.frame of ring-width indices (such as produced by <a href="#">chron</a> )
key	a vector specifying the key event years for the superposed epoch
lag	an integral value defining the number of lagged years
resample	an integral value specifying the number of bootstrap sample for calculation of confidence intervals

**Details**

Superposed epoch analysis (SEA) is used to test the significance of a mean tree growth response to certain events (such as droughts). Departures from the mean RWI values for the specified years prior to each event year, the event year, and the specified years immediately after each event are averaged to a superposed epoch. To determine if RWI for these years was significantly different from randomly selected sets of  $lag+1$  other years, bootstrap resampling is used to randomly select sets of  $lag+1$  years from the data set and to estimate significances for the departures from the mean RWI.

SEA computation is based on scaled RWI values, and 95%-confidence intervals are computed for the scaled values for each year in the superposed epoch.

**Value**

A data.frame with

lag	the lagged years,
se	the superposed epoch, i.e. the scaled mean RWI for the event years,
se.unscaled	the unscaled superposed epoch, i.e. the mean RWI for the event years,
p	significance of the departure from the chrono's mean RWI,
ci.95.lower	lower 95% confidence band,
ci.95.upper	upper 95% confidence band,
ci.99.lower	lower 99% confidence band,
ci.99.upper	upper 99% confidence band.

**Author(s)**

Christian Zang. Patched and improved by Mikko Korpela.

**References**

Lough, J. M. and Fritts, H. C. (1987) An assessment of the possible effects of volcanic eruptions on North American climate using tree-ring data, 1602 to 1900 AD. *Climatic Change*, **10**(3), 219–239.

**Examples**

```
library(graphics)
library(utils)
data(cana157)
event.years <- c(1631, 1742, 1845)
cana157.sea <- sea(cana157, event.years)
foo <- cana157.sea$se.unscaled
names(foo) <- cana157.sea$lag
barplot(foo, col = ifelse(cana157.sea$p < 0.05, "grey30", "grey75"),
        ylab = "RWI", xlab = "Superposed Epoch")
```

---

seg.plot

*Segment Plot*

---

**Description**

Makes a segment plot of tree-ring data.

**Usage**

```
seg.plot(rwl, ...)
```

**Arguments**

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
...	arguments to be passed to plot.

**Details**

This makes a simple plot of the length of each series in a tree-ring data set.

**Value**

None. This function is invoked for its side effect, which is to produce a plot.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**[spag.plot](#)**Examples**

```
library(utils)
data(co021)
seg.plot(co021)
```

---

sens1	<i>Calculate Mean Sensitivity</i>
-------	-----------------------------------

---

**Description**

This function calculates mean sensitivity of a detrended ring-width series.

**Usage**

```
sens1(x)
```

**Arguments**

x                    a numeric vector containing the series

**Details**

This calculates mean sensitivity according to Eq. 1 in Biondi and Qeadan (2008). This is the standard measure of sensitivity in dendrochronology and is typically calculated on detrended series. However, note that mean sensitivity is not a robust statistic and should rarely, if ever, be used (Bunn et al. 2013).

**Value**

the mean sensitivity.

**Author(s)**

Mikko Korpela, based on original by Andy Bunn

**References**

- Biondi, F. and Qeadan, F. (2008) Inequality in Paleorecords. *Ecology*, **89**(4), 1056–1067.
- Bunn, A. G., Jansma, E., Korpela, M., Westfall, R. D., and Baldwin, J. (2013) Using simulations and data to evaluate mean sensitivity ( $\zeta$ ) as a useful statistic in dendrochronology. *Dendrochronologia*, **31**(3), 250–254.



**See Also**[sens2](#), [rwl.stats](#)**Examples**

```
library(utils)
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
sens1(ca533.rwi[, 1])
```

---

**sens2***Calculate Mean Sensitivity on Series with a Trend*

---

**Description**

This function calculates mean sensitivity of a raw or detrended ring-width series.

**Usage**

```
sens2(x)
```

**Arguments**

**x** a numeric vector containing the series

**Details**

This calculates mean sensitivity according to Eq. 2 in Biondi and Qeadan (2008). This is a measure of sensitivity in dendrochronology that is typically used in the presence of a trend. However, note that mean sensitivity is not a robust statistic and should rarely, if ever, be used (Bunn et al. 2013).

**Value**

the mean sensitivity.

**Author(s)**

Mikko Korpela, based on original by Andy Bunn

**References**

- Biondi, F. and Qeadan, F. (2008) Inequality in Paleorecords. *Ecology*, **89**(4), 1056–1067.
- Bunn, A. G., Jansma, E., Korpela, M., Westfall, R. D., and Baldwin, J. (2013) Using simulations and data to evaluate mean sensitivity ( $\zeta$ ) as a useful statistic in dendrochronology. *Dendrochronologia*, **31**(3), 250–254.

**See Also**

[sens1, rwl.stats](#)

**Examples**

```
library(utils)
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
sens2(ca533.rwi[, 1])
```

---

series.rwl.plot      *Plot Series and a Master*

---

**Description**

Plots a tree-ring series with a master chronology and displays their fit, segments, and detrending options in support of the cross-dating functions.

**Usage**

```
series.rwl.plot(rwl, series, series.yrs = as.numeric(names(series)),
               seg.length = 100, bin.floor = 100, n = NULL,
               prewhiten = TRUE, biweight = TRUE, floor.plus1 = FALSE)
```

**Arguments**

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
series	a numeric or character vector. Usually a tree-ring series. If the length of the value is 1, the corresponding column of <i>rwl</i> is selected (by name or position) as the series and ignored when building the master chronology. Otherwise, the value must be numeric.
series.yrs	a numeric vector giving the years of <i>series</i> . Defaults to <code>as.numeric(names(series))</code> . Ignored if <i>series</i> is an index to a column of <i>rwl</i> .
seg.length	an even integral value giving length of segments in years (e.g., 20, 50, 100 years).
bin.floor	a non-negative integral value giving the base for locating the first segment (e.g., 1600, 1700, 1800 AD). Typically 0, 10, 50, 100, etc.
n	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
prewhiten	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .
biweight	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .
floor.plus1	logical flag. If TRUE, one year is added to the base location of the first segment (e.g., 1601, 1701, 1801 AD).

## Details

The function is typically invoked to produce four plots showing the effect of the detrending options *n* and *prewhiten* and the binning options *seg.length* and *bin.floor*.

**Plot 1** Time series plot of the filtered series and the master

**Plot 2** Scatterplot of series vs. master

**Plot 3** Segments that would be used in the other cross-dating functions (e.g., [corr.series.seg](#))

**Plot 4** Text giving the detrending options and the time span of the raw and filtered series and master

The series and master are returned as well.

See help pages for [corr.rwl.seg](#), [corr.series.seg](#), and [ccf.series.rwl](#) for more information on these arguments.

## Value

A list containing the filtered vectors *series* and *master*.

## Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

## See Also

[corr.rwl.seg](#), [corr.series.seg](#), [ccf.series.rwl](#)

## Examples

```
library(utils)
data(co021)
foo <- series.rwl.plot(rwl = co021, series = "646244", seg.length = 100,
                     n = 5)
## note effect of n on first year in the series
foo <- series.rwl.plot(rwl = co021, series = "646244", seg.length = 100,
                     n = 13, prewhiten = FALSE)
bar <- series.rwl.plot(rwl = co021, series = "646244", seg.length = 100,
                     n = 7, prewhiten = FALSE)

head(foo$series)
head(bar$series)
```

skel.plot

*Skeleton Plot***Description**

Automatically generates a skeleton plot of tree-ring data.

**Usage**

```
skel.plot(rw.vec, yr.vec = NULL, sname = "", filt.weight = 9,
          dat.out = FALSE, master = FALSE, plot = TRUE)
```

**Arguments**

rw.vec	a numeric vector of a tree-ring chronology or series
yr.vec	optional numeric vector giving years for the tree-ring data
sname	an optional character string giving the ID for the data. The width of the string, often identical to the number of characters, must be less than 8.
filt.weight	filter length for the Hanning filter, defaults to 9
dat.out	logical flag indicating whether to return a data.frame containing the data.
master	logical flag indicating whether to make the plot with the segments inverted to ease pattern matching. If TRUE the segments will be plotted from the top down and the labels on the x axes will be on the bottom.
plot	logical flag indicating whether to make a plot.

**Details**

This makes a skeleton plot – a plot that gives the relative growth for year  $t$  relative to years  $t-1$  and  $t+1$ . Note that this plot is a standard plot in dendrochronology and typically made by hand for visually cross-dating series. This type of plot might be confusing to those not accustomed to visual cross-dating. See references for more information. The implementation is based on Meko's (2002) skeleton plotting approach.

The skeleton plot is made by calculating departures from high frequency growth for each year by comparing year  $t$  to the surrounding three years ( $t-1, t, t+1$ ). Low frequency variation is removed using a [hanning](#) filter. Relative growth is scaled from one to ten but only values greater than three are plotted. This function's primary effect is to create plot with absolute units that can be printed and compared to other plots. Here, anomalous growth is plotted on a 2mm grid and up to 120 years are plotted on a single row with a maximum of 7 rows (840 years). These plots are designed to be plotted on standard paper using an appropriate device, e.g., postscript with defaults or to pdf with plot width and height to accommodate a landscape plot, e.g., `width = 10`, `height = 7.5`, `paper = "USr"`. These plots are designed to be printable and cut into strips to align long series. Statistical cross-dating is possible if the data are output.

**Value**

This function is invoked primarily for its side effect, which is to produce a plot. If *dat.out* is TRUE then a data.frame is returned with the years and height of the skeleton plot segments as columns.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**References**

- Stokes, M. A. and Smiley, T. L. (1968) *An Introduction to Tree-Ring Dating*. The University of Arizona Press. ISBN-13: 978-0-8165-1680-3.
- Sheppard, P. R. (2002) Crossdating Tree Rings Using Skeleton Plotting. <http://www.ltrr.arizona.edu/skeletonplot/introcrossdate.htm>.
- Meko, D. (2002) Tree-Ring MATLAB Toolbox. <http://www.mathworks.com/matlabcentral/>.

**See Also**

[Devices, hanning](#)

**Examples**

```
library(utils)
data(co021)
x <- co021[,33]
x.yrs <- time(co021)
x.name <- colnames(co021)[33]
## On a raw ring width series - undated
skel.plot(x)
## On a raw ring width series - dated with names
skel.plot(x, yr.vec = x.yrs, sname = x.name, master = TRUE)
## Not run:
library(grDevices)
## Try cross-dating
y <- co021[, 11]
y.yrs <- time(co021)
y.name <- colnames(co021)[11]

## send to postscript - 3 pages total
fname1 <- tempfile(fileext=".ps")
print(fname1) # tempfile used for PS output
postscript(fname1)
## "Master series" with correct calendar dates
skel.plot(x, yr.vec = x.yrs, sname = x.name, master = TRUE)
## Undated series, try to align with last plot
skel.plot(y)
## Here's the answer...
skel.plot(y, yr.vec = y.yrs, sname = y.name)
dev.off()

unlink(fname1) # remove the PS file
```

```
## alternatively send to pdf
fname2 <- tempfile(fileext=".pdf")
print(fname2) # tempfile used for PDF output
pdf(fname2, width = 10, height = 7.5, paper = "USr")
skel.plot(x, yr.vec = x.yrs, sname = x.name, master = TRUE)
skel.plot(y)
skel.plot(y, yr.vec = y.yrs, sname = y.name)
dev.off()

unlink(fname2) # remove the PDF file

## End(Not run)
```

---

spag.plot

*Spaghetti Plot*


---

### Description

Makes a spaghetti plot of tree-ring data.

### Usage

```
spag.plot(rwl, zfac = 1, useRaster = FALSE, res = 150, ...)
```

### Arguments

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
zfac	a multiplier for <i>rwl</i> to enhance clarity when plotting.
useRaster	A logical flag. If TRUE, the tree-ring series are drawn as a raster image. Other parts of the plot are not affected. Other choices are NA (automatic) and FALSE (use vector graphics, the default). See <a href="#">wavelet.plot</a> .
res	A numeric vector of length 1. The resolution (pixels per inch) of the tree-ring series when a raster image is used.
...	arguments to be passed to <a href="#">lines</a> .

### Details

This makes a simple plot of each series in a tree-ring data set. Each series is centered first by subtracting the column mean using [scale](#). The plot can be grossly tuned with *zfac* which is a multiplier to *rwl* before plotting and centering.

### Value

None. This function is invoked for its side effect, which is to produce a plot.

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**

[seg.plot](#)

**Examples**

```
library(utils)
data(co021)
spag.plot(co021)
spag.plot(co021, zfac = 2)
```

---

strip.rwl

*Chronology Stripping by EPS*

---

**Description**

EPS-based chronology stripping after Fowler & Boswijk 2003.

**Usage**

```
strip.rwl(rwl, ids = NULL, verbose = FALSE, comp.plot = FALSE,
          legacy.eps = FALSE)
```

**Arguments**

rwl	a <code>data.frame</code> of raw tree-ring widths series, such as that produced by <a href="#">read.rwl</a> or <a href="#">read.fh</a>
ids	an optional <code>data.frame</code> with column one named "tree" giving a numeric ID for each tree and column two named "core" giving a numeric ID for each core. This is passed on to <a href="#">rwi.stats</a> . See its manual for the meaning of the default value NULL and more information.
verbose	logical flag, indicating if the EPS calculated at each step and other details should be printed on the console during the chronology stripping process
comp.plot	logical flag, indicating if a diagnostic plot with year-wise stripped and unstripped EPS should be drawn (see details below)
legacy.eps	logical flag, indicating if the EPS will be calculated with <code>rwi.stats</code> (FALSE, the default) or <code>rwi.stats.legacy</code> (TRUE)

## Details

The EPS-based chronology stripping is implemented after Fowler & Boswijk 2003: First, all series are standardized using a double detrending procedure with splines and frequency cutoffs of 50% at 20 and 200 years. Then, EPS is calculated for the chronology including all (remaining) series. In each iteration, the algorithm calculates leave-one-out EPS values, and the series whose removal increases overall EPS the most is discarded. This is repeated until no further increase in EPS is gained by discarding a single series. The procedure is then repeated in the opposite direction, i.e., the reinsertion of each previously removed series into the `data.frame` is considered. In each iteration, the series (if any) whose reinsertion increases EPS the most is reinserted. As a last step, EPS is calculated for each year of the stripped and original chronology including all series. If `comp.plot` is set to `TRUE`, a diagnostic plot is shown for the year-wise comparison.

When verbose output is chosen, the EPS values for all leave-one-out (or back-in) chronologies are reported. If discarding or re-inserting a single series leads to an improvement in EPS, this series is marked with an asterisk.

## Value

The functions returns a `data.frame` of raw tree-ring widths, where series that do not contribute to an overall improvement in EPS are left out.

## Author(s)

Christian Zang. Patched and improved by Mikko Korpela.

## References

Fowler, A. and Boswijk, G. (2003) Chronology stripping as a tool for enhancing the statistical quality of tree-ring chronologies. *Tree-Ring Research*, **59**(2), 53–62.

## See Also

[rwi.stats](#)

## Examples

```
library(utils)
data(anos1)
anos1.ids <- read.ids(anos1, stc = c(4, 3, 1))
srwl <- strip.rwl(anos1, ids = anos1.ids, verbose = TRUE)
tail(srwl)
```



---

`tbrm`*Calculate Tukey's Biweight Robust Mean*

---

### Description

This calculates a robust average that is unaffected by outliers.

### Usage

```
tbrm(x, C = 9)
```

### Arguments

<code>x</code>	a numeric vector
<code>C</code>	a constant. <code>C</code> is preassigned a value of 9 according to the Cook reference below but other values are possible.

### Details

This is a one step computation that follows the Affy whitepaper below, see page 22. This function is called by `chron` to calculate a robust mean. `C` determines the point at which outliers are given a weight of 0 and therefore do not contribute to the calculation of the mean. `C = 9` sets values roughly +/-6 standard deviations to 0. `C = 6` is also used in tree-ring chronology development. Cook and Kairiukstis (1990) have further details.

An exact summation algorithm (Shewchuk 1997) is used. When some assumptions about the rounding of floating point numbers and conservative compiler optimizations hold, summation error is completely avoided. Whether the assumptions hold depends on the platform, i.e. compiler and CPU.

### Value

A numeric mean.

### Author(s)

Mikko Korpela

### References

- Statistical Algorithms Description Document, 2002, Affymetrix.
- Cook, E. R. and Kairiukstis, L. A., editors (1990) *Methods of Dendrochronology: Applications in the Environmental Sciences*. Springer. ISBN-13: 978-0-7923-0586-6.
- Mosteller, F. and Tukey, J. W. (1977) *Data Analysis and Regression: a second course in statistics*. Addison-Wesley. ISBN-13: 978-0-201-04854-4.
- Shewchuk, J. R. (1997) Adaptive precision floating-point arithmetic and fast robust geometric predicates. *Discrete and Computational Geometry*, **18**(3), 305–363.

**See Also**[chron](#)**Examples**

```

library(stats)
library(utils)
foo <- rnorm(100)
tbrm(foo)
mean(foo)

## Compare
data(co021)
co021.rwi <- detrend(co021, method = "ModNegExp")
crn1 <- apply(co021.rwi, 1, tbrm)
crn2 <- chron(co021.rwi)
cor(crn1, crn2[, 1])

```

---

`time.rwl`*Return time values for rwl and crn objects*

---

**Description**

Returns the time values for rwl and crn objects.

**Usage**

```

## S3 method for class 'rwl'
time(x, ...)
## S3 method for class 'crn'
time(x, ...)

```

**Arguments**

`x` An object of class "rwl" or an abobject of class "crn".

`...` Not used.

**Value**

A numeric vector of time (typically in years) for the object. This is done via `as.numeric(rownames(x))` but has been asked for by users so many times that it is being included as a function.

**Author(s)**

Andy Bunn

**See Also**

[read.rwl](#) [read.crn](#)

## Examples

```
library(utils)
data(co021)
co021.yrs <- time(co021)
```

---

treeMean	<i>Calculate mean across cores in a tree</i>
----------	--

---

## Description

This function calculates the mean value for each tree in a `rwl` or `rwi` object.

## Usage

```
treeMean(rwl, ids, na.rm=FALSE)
```

## Arguments

<code>rwl</code>	a <code>data.frame</code> of ring widths with <code>rownames(rwl)</code> containing years and <code>colnames(rwl)</code> containing each series ID such as produced by <a href="#">read.rwl</a>
<code>ids</code>	a <code>data.frame</code> with column one named "tree" giving a numeric ID for each tree and column two named "core" giving a numeric ID for each core.
<code>na.rm</code>	logical passed to <a href="#">rowMeans</a> . Should missing values be removed?

## Details

This function averages together multiple cores to give a mean value of growth. It is very common in dendrochronology to take more than one core per tree. In those cases it is occasionally desirable to have an average of the cores. This function merely loops through the `rwl` object and calculates the [rowMeans](#) for each tree. If `na.rm=TRUE` trees with >1 sample will be averaged only over the period where the samples overlap. If `FALSE` the output can vary in the number of samples. See examples.

## Value

An object of class `c("rwl", "data.frame")` with the mean annual value for each tree.

## Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

## See Also

[read.rwl](#), [read.ids](#)

**Examples**

```

data(gp.rwl)
gp.ids <- read.ids(gp.rwl, stc = c(0, 2, 1))

gp.treeMean <- treeMean(gp.rwl, gp.ids)
gp.treeMean2 <- treeMean(gp.rwl, gp.ids, na.rm=TRUE)

# look at an example of a single tree with different averaging periods
tree40 <- data.frame(gp.rwl[, c("40A", "40B")],
                    gp.treeMean[, "40", drop=FALSE],
                    gp.treeMean2[, "40", drop=FALSE])
names(tree40) <- c("coreA", "coreB", "treeMean1", "treeMean2")
head(tree40, 50)

data(ca533)
ca533.treeMean <- treeMean(ca533, autoread.ids(ca533))
# plot using S3method for class "rwl"
plot(ca533.treeMean, plot.type="spag")

```

---

tridas.vocabulary

*Browse and Check Standard TRiDaS Vocabulary*


---

**Description**

This function can be used to browse the TRiDaS vocabulary by category.

**Usage**

```

tridas.vocabulary(category = c("dating type", "measuring method",
                              "shape", "location type", "variable", "unit",
                              "remark", "dating suffix", "presence / absence",
                              "complex presence / absence", "certainty"),
                  idx = NA, term = NA, match.exact = FALSE)

```

**Arguments**

category	Vocabulary category as a character vector of length one. One of "dating type", "measuring method", "shape", "location type", "variable", "unit", "remark", "dating suffix", "presence / absence", "complex presence / absence", "certainty". Partial matches are allowed.
idx	A numeric vector. Index to the character vector containing the vocabulary of the given category.
term	A character vector. One or more (partial) terms to look for in the given category.
match.exact	A logical value. If TRUE, partial matching of <i>term</i> is not used. Defaults to FALSE.

## Details

The Tree Ring Data Standard (TRiDaS) is described in Jansma et. al (2010). Information about the current version of the standard can be found from [TRiDaS website](http://www.tridas.org/).

The function has four usage modes:

1. When *idx* is given, returns item number *idx* in the given *category*. There may be several numbers in *idx*, in which case multiple items are returned.
2. When *term* contains one or more items and *match.exact* is TRUE, checks whether any of the terms is an exact match in the given *category*
3. When *term* contains one or more items and *match.exact* is FALSE, expands partial matches of the terms in the vocabulary of the given *category*
4. When only *category* is given, returns the complete vocabulary in the given *category*

## Value

In mode 1	A character vector, same length as in <i>idx</i>
In mode 2	A logical value
In mode 3	A character vector, same length as in <i>term</i>
In mode 4	A character vector

## Author(s)

Mikko Korpela

## References

Jansma, E., Brewer, P. W., and Zandhuis, I. (2010) TRiDaS 1.1: The tree-ring data standard. *Dendrochronologia*, **28**(2), 99–130.

TRiDaS – The Tree Ring Data Standard. <http://www.tridas.org/>.

## See Also

[read.tridas](#), [write.tridas](#)

## Examples

```
## Show all entries in category "measuring method"
tridas.vocabulary(category = "measuring")

## Show item number one in category "complex presence / absence"
tridas.vocabulary(category = "complex", idx = 1)

## Check whether "half section" exists in category "shape"
tridas.vocabulary(category = "shape", term = "half section",
                  match.exact = TRUE)

## Return unabbreviated matches to several queries in category "remark"
tridas.vocabulary(category = "remark",
                  term = c("trauma", "fire", "diffuse"))
```

---

 uuid.gen

 UUID Generator
 

---

### Description

Initializes and returns a generator of universally unique identifiers. Use the returned function repeatedly for creating one or more UUIDs, one per function call.

### Usage

```
uuid.gen(more.state = "")
```

### Arguments

`more.state`      A character string for altering the state of the generator

### Details

This function returns a function (closure) which generates UUIDs. The state of that anonymous function is set when `uuid.gen` is called. The state consists of the following:

- System and user information ([Sys.info](#))
- R version ([R.version](#))
- Platform information ([.Platform](#))
- Working directory
- Process ID of the R session
- Time when `uuid.gen` was called (precision of seconds or finer)
- The text in parameter `more.state`

The Pseudo Random Number Generator of R (see [.Random.seed](#)) is used in the generation of UUIDs. No initialization of the PRNG is done. Tampering with the state of the R PRNG while using a given UUID generator causes a risk of non-unique identifiers. Particularly, setting the state of the PRNG to the same value before two calls to the UUID generator guarantees two identical identifiers. If two UUID generators have a different state, it is *not* a problem to have the PRNG going through or starting from the same state with both generators.

The user is responsible for selecting a PRNG with a reasonable number of randomness. Usually, this doesn't require any action. For example, any PRNG algorithm available in R works fine. However, the uniqueness of UUIDs can be destroyed by using a bad user-supplied PRNG.

The UUIDs produced by `uuid.gen` generators are Version 4 (random) with 122 random bits and 6 fixed bits. The UUID is presented as a character string of 32 hexadecimal digits and 4 hyphens:

```
'xxxxxxxx-xxxx-4xxx-yxxx-xxxxxxxxxxxx'
```

where `x` is any hexadecimal digit and `y` is one of "8", "9", "a", or "b". Each `x` and `y` in the example is an independent variables (for all practical purposes); subscripts are omitted for clarity. The UUID generator gets 32 hex digits from the MD5 message digest algorithm by feeding it a string consisting of the constant generator state and 5 (pseudo) random numbers. After that, the 6 bits are fixed and the hyphens are added to form the final UUID.

**Value**

A parameterless function which returns a single UUID (character string)

**Author(s)**

Mikko Korpela

**References**

Leach, P., Mealling, M., and Salz, R. (2005) A Universally Unique Identifier (UUID) URN namespace. RFC 4122, RFC Editor. <http://www.rfc-editor.org/rfc/rfc4122.txt>.

**See Also**

[digest](#), [Random](#)

**Examples**

```
## Normal use
ug <- uuid.gen()
uuids <- character(100)
for(i in 1:100){
  uuids[i] <- ug()
}
length(unique(uuids)) == 100 # TRUE, UUIDs are unique with high probability

## Do NOT do the following unless you want non-unique IDs
rs <- .Random.seed
set.seed(0L)
id1 <- ug()
set.seed(0L)
id2 <- ug()
id1 != id2 # FALSE, The UUIDs are the same
.Random.seed <- rs

## Strange usage pattern, but will probably produce unique IDs
ug1 <- uuid.gen("1")
set.seed(0L)
id1 <- ug1()
ug2 <- uuid.gen("2")
set.seed(0L)
id2 <- ug2()
id1 != id2 # TRUE, The UUIDs are different with high probability
.Random.seed <- rs
```

wa082

*Hurricane Ridge, Pacific silver fir***Description**

This data set gives the raw ring widths for Pacific silver fir *Abies amabilis* at Hurricane Ridge in Washington, USA. There are 23 series. Data set was created using [read.rwl](#) and saved to an .rda file using [save](#).

**Usage**

```
data(wa082)
```

**Format**

A data.frame containing 23 tree-ring series in columns and 286 years in rows.

**Source**

International tree-ring data bank, Accessed on 06-March-2016 at <ftp://ftp.ncdc.noaa.gov/pub/data/paleo/treering/measurements/northamerica/usa/wa082.rwl>

**References**

Schweingruber, F. (1983) Hurricane Ridge Data Set. IGBP PAGES/World Data Center for Paleoclimatology Data Contribution Series 1983-wa082.RWL. NOAA/NCDC Paleoclimatology Program, Boulder, Colorado, USA.

wavelet.plot

*Plot a Continuous Wavelet Transform***Description**

This function creates a filled.contour plot of a continuous wavelet transform as output from [morlet](#).

**Usage**

```
wavelet.plot(wave.list,
             wavelet.levels = quantile(wave.list$Power,
                                       probs = (0:10)/10),
             add.coi = TRUE, add.sig = TRUE,
             x.lab = gettext("Time", domain = "R-dplR"),
             period.lab = gettext("Period", domain = "R-dplR"),
             crn.lab = gettext("RWI", domain = "R-dplR"),
             key.cols = rev(rainbow(length(wavelet.levels)-1)),
```



```

key.lab = parse(text=paste0("\",
                           gettext("Power",
                                   domain="R-dplR"),
                           "\"^2")),
add.spline = FALSE, f = 0.5, nyrs = NULL,
crn.col = "black", crn.lwd = 1, coi.col='black',
crn.ylim = range(wave.list$y) * c(0.95, 1.05),
side.by.side = FALSE,
useRaster = FALSE, res = 150, reverse.y = FALSE, ...)

```

## Arguments

<code>wave.list</code>	A list. Output from <a href="#">morlet</a> .
<code>wavelet.levels</code>	A numeric vector. Values for levels of the filled contours for the wavelet plot.
<code>add.coi</code>	A logical flag. Add cone of influence?
<code>add.sig</code>	A logical flag. Add contour lines for significance?
<code>x.lab</code>	X-axis label.
<code>period.lab</code>	Y-axis label for the wavelet plot.
<code>crn.lab</code>	Y-axis label for the time-series plot.
<code>key.cols</code>	A vector of colors for the wavelets and the key.
<code>key.lab</code>	Label for key.
<code>add.spline</code>	A logical flag. Add a spline to the time-series plot using <a href="#">ffcsaps?</a> .
<code>nyrs</code>	A number giving the rigidity of the smoothing spline, defaults to 0.33 of series length if <code>nyrs</code> is NULL.
<code>f</code>	A number between 0 and 1 giving the frequency response or wavelength cutoff for the smoothing spline. Defaults to 0.5.
<code>crn.col</code>	Line color for the time-series plot.
<code>crn.lwd</code>	Line width for the time-series plot.
<code>coi.col</code>	Color for the COI if <code>add.coi</code> is TRUE.
<code>crn.ylim</code>	Axis limits for the time-series plot.
<code>side.by.side</code>	A logical flag. Plots will be in one row if TRUE.
<code>useRaster</code>	A logical flag. If TRUE, the filled contours are drawn as a raster image. Other parts of the plot are not affected. <code>useRaster=TRUE</code> can be especially useful when a pdf device is used: the size and complexity of the PDF file will probably be greatly reduced. Setting this to TRUE has negative effects when used with a bitmap device such as png. If NA, plotting of a raster image will be attempted if and only if the name of the graphics device is "pdf" or "postscript". The default is FALSE: draw directly to the graphics device without using an intermediate raster image.
<code>res</code>	A numeric vector of length 1. The resolution (pixels per inch) of the filled contours when a raster image is used. See <code>useRaster</code> .
<code>reverse.y</code>	A logical flag. If TRUE, the Y-axis will be reversed, i.e. period increasing towards the bottom. The default is FALSE.
<code>...</code>	Arguments passed to <a href="#">rasterPlot</a> . Only relevant when the filled contours are drawn as a raster image. See <code>useRaster</code> .

**Details**

This produces a plot of a continuous wavelet transform and plots the original time series. Contours are added for significance and a cone of influence polygon can be added as well. Anything within the cone of influence should not be interpreted.

The time series can be plotted with a smoothing spline as well.

**Value**

None. This function is invoked for its side effect, which is to produce a plot.

**Note**

The function `morlet` is a port of Torrence's IDL code, which can be accessed through the [Internet Archive Wayback Machine](#).

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**References**

Torrence, C. and Compo, G. P. (1998) A practical guide to wavelet analysis. *Bulletin of the American Meteorological Society*, **79**(1), 61–78.

**See Also**

[morlet](#), [ffcsaps](#)

**Examples**

```
library(stats)
library(utils)
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
ca533.crn <- chron(ca533.rwi, prefix = "CAM", prewhiten = FALSE)
Years <- time(ca533.crn)
CAMstd <- ca533.crn[, 1]
out.wave <- morlet(y1 = CAMstd, x1 = Years, p2 = 9, dj = 0.1,
                 siglvl = 0.99)
wavelet.plot(out.wave, useRaster = NA)
## Not run:
## Alternative palette with better separation of colors
if (require(RColorBrewer)) {
  ## RColorBrewer (1.1.2) uses but does not import rgb()
  library(grDevices)
  wavelet.plot(out.wave, key.cols=rev(brewer.pal(10, "Spectral")),
              useRaster = NA)
}

## End(Not run)
levs <- quantile(out.wave$Power, probs = c(0, 0.5, 0.75, 0.9, 0.99))
```

```
wavelet.plot(out.wave, wavelet.levels = levs, add.sig = FALSE,  
             key.cols = c("white", "green", "blue", "red"),  
             useRaster = NA)
```

---

wc.to.po

*Convert Wood Completeness to Pith Offset*

---

## Description

This function creates a pith offset data structure based on wood completeness data.

## Usage

```
wc.to.po(wc)
```

## Arguments

wc                    A data.frame containing wood completeness data, as returned by [read.tridas](#).

## Details

Computes the sum of the variables *n.missing.heartwood* and *n.unmeasured.inner* in *wc*.

## Value

A data.frame containing two variables. Variable one (*series*) gives the series ID as either characters or factors. These match `rownames(wc)`. Variable two (*pith.offset*) is of integer type and gives the years from the beginning of the core to the pith (or center) of the tree. The minimum value is 1.

## Author(s)

Mikko Korpela

## See Also

[po.to.wc](#), [rcs](#), [read.tridas](#)

## Examples

```
library(utils)  
data(gp.po)  
all(wc.to.po(po.to.wc(gp.po)) == gp.po)
```

---

write.compact

---

*Write DPL Compact Format Ring Width File*


---

### Description

This function writes a chronology to a DPL compact format file.

### Usage

```
write.compact(rwl.df, fname, append = FALSE, prec = 0.01,
             mapping.fname = "", mapping.append = FALSE, ...)
```

### Arguments

rwl.df	a data.frame containing tree-ring ring widths with the series in columns and the years as rows. The series IDs are the column names and the years are the row names. This type of data.frame is produced by <a href="#">read.rwl</a> and <a href="#">read.compact</a> .
fname	a character vector giving the file name of the rwl file.
append	logical flag indicating whether to append this chronology to an existing file.
prec	numeric indicating the precision of the output file. This must be equal to either 0.01 or 0.001 (units are in mm).
mapping.fname	a character vector of length one giving the file name of an optional output file showing the mapping between input and output series IDs. The mapping is only printed for those IDs that are transformed. An empty name (the default) disables output.
mapping.append	logical flag indicating whether to append the description of the altered series IDs to an existing file. The default is to create a new file.
...	Unknown arguments are accepted but not used.

### Details

The output should be readable by the Dendrochronology Program Library (DPL) as a compact format file.

In series IDs, letters of the English alphabet and numbers are allowed. Other characters will be removed. The length of the IDs is limited to about 50 characters, depending on the length of the other items to be placed on the header lines of the output file. Longer IDs will be truncated. Also any duplicate IDs will be automatically edited so that only unique IDs exist. If series IDs are changed, one or more warnings are shown. In that case, the user may wish to print a list of the renamings (see Arguments).

### Value

*fname*

**Author(s)**

Mikko Korpela, based on write.tucson by Andy Bunn

**See Also**

[write.rwl](#), [write.tucson](#), [write.tridas](#), [read.compact](#)

**Examples**

```
library(utils)
data(co021)
fname <- write.compact(rwl.df = co021,
                      fname = tempfile(fileext=".rwl"),
                      append = FALSE, prec = 0.001)
print(fname) # tempfile used for output

unlink(fname) # remove the file
```

---

write.crn

*Write Tucson Format Chronology File*

---

**Description**

This function writes a chronology to a Tucson (decadal) format file.

**Usage**

```
write.crn(crn, fname, header = NULL, append = FALSE)
```

**Arguments**

crn	a <code>data.frame</code> containing a tree-ring chronology with two columns of the type produced by <a href="#">chron</a> . The first column contains the mean value chronology, the second column gives the sample depth. Years for the chronology are determined from the row names. The chronology ID is determined from the first column name.
fname	a character vector giving the file name of the crn file.
header	a list giving information for the header of the file. If <code>NULL</code> then no header information will be written.
append	logical flag indicating whether to append this chronology to an existing file.

## Details

This writes a standard crn file as defined according to the standards of the ITRDB at <http://www.ncdc.noaa.gov/paleo/treeinfo.html>. This is the decadal or Tucson format. It is an ASCII file and machine readable by the standard dendrochronology programs. Header information for the chronology can be written according to the International Tree Ring Data Bank (ITRDB) standard. The header standard is not very reliable however and should be thought of as experimental here. Do not try to write headers using dplR to submit to the ITRDB. When submitting to the ITRDB, you can enter the metadata via their website. If you insist however, the header information is given as a list and must be formatted with the following:

<i>Description</i>	<i>Name</i>	<i>Class</i>	<i>Max Width</i>
Site ID	<i>site.id</i>	character	6
Site Name	<i>site.name</i>	character	52
Species Code	<i>spp.code</i>	character	4
State or Country	<i>state.country</i>	character	13
Species	<i>spp</i>	character	18
Elevation	<i>elev</i>	character	5
Latitude	<i>lat</i>	character or numeric	5
Longitude	<i>long</i>	character or numeric	5
First Year	<i>first.yr</i>	character or numeric	4
Last Year	<i>last.yr</i>	character or numeric	4
Lead Investigator	<i>lead.invs</i>	character	63
Completion Date	<i>comp.date</i>	character	8

See examples for a correctly formatted header list. If the width of the fields is less than the max width, then the fields will be padded to the right length when written. Note that *lat* and *long* are really *lat\*100* or *long\*100* and given as integral values. E.g., 37 degrees 30 minutes would be given as 3750.

This function takes a single chronology with sample depth as input. This means that it will fail if given output from `chron` where `prewhiten == TRUE`. However, more than one chronology can be appended to the bottom of an existing file (e.g., standard and residual) with a second call to `write.crn`. However, the ITRDB recommends saving and publishing only one chronology per file. The examples section shows how to circumvent this. The output from this function might be suitable for publication on the ITRDB although the header writing is clunky (see above) and rwl files are much better than crn files in terms of usefulness on the ITRDB.

## Value

*fname*

## Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

## See Also

`chron`, `read.crn`

**Examples**

```

library(utils)
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
ca533.crn <- chron(ca533.rwi, prefix = "CAM")
fname1 <- write.crn(ca533.crn, tempfile(fileext=".crn"))
print(fname1) # tempfile used for output

## Put the standard and residual chronologies in a single file
## with ITRDB header info on top. Not recommended.
ca533.crn <- chron(ca533.rwi, prefix = "CAM", prewhiten = TRUE)
ca533.hdr <- list(site.id = "CAM", site.name = "Campito Mountain",
  spp.code = "PIL0", state.country = "California",
  spp = "Bristlecone Pine", elev = "3400M", lat = 3730,
  long = -11813, first.yr = 626, last.yr = 1983,
  lead.invs = "Donald A. Graybill, V.C. LaMarche, Jr.",
  comp.date = "Nov1983")
fname2 <- write.crn(ca533.crn[, -2], tempfile(fileext=".crn"),
  header = ca533.hdr)
write.crn(ca533.crn[, -1], fname2, append = TRUE)
print(fname2) # tempfile used for output

unlink(c(fname1, fname2)) # remove the files

```

write.rwl

*Write Chronology File***Description**

This function writes a chronology to a file in one of the available formats.

**Usage**

```
write.rwl(rwl.df, fname, format = c("tucson", "compact", "tridas"), ...)
```

**Arguments**

rwl.df	a data.frame containing tree-ring ring widths with the series in columns and the years as rows. The series IDs are the column names and the years are the row names. This type of data.frame is produced by <a href="#">read.rwl</a> .
fname	a character vector giving the file name of the rwl file.
format	a character vector giving the format. This must be "tucson", "compact", or "tridas". Tucson format is the default.
...	arguments specific to the function implementing the operation for the chosen format.

**Details**

This is a simple wrapper to the functions actually implementing the write operation.

**Value***fname***Author(s)**

Mikko Korpela

**See Also**[write.crn](#), [write.tucson](#), [write.compact](#), [write.tridas](#), [read.rwl](#)**Examples**

```
library(utils)
data(co021)
co021.hdr <- list(site.id = "CO021",
                 site.name = "SCHULMAN OLD TREE NO. 1, MESA VERDE",
                 spp.code = "PSME", state.country = "COLORADO",
                 spp = "DOUGLAS FIR", elev = 2103, lat = 3712,
                 long = -10830, first.yr = 1400, last.yr = 1963,
                 lead.invs = "E. SCHULMAN", comp.date = "")
fname <- write.rwl(rwl.df = co021, fname = tempfile(fileext=".rwl"),
                 format = "tucson", header = co021.hdr,
                 append = FALSE, prec = 0.001)
print(fname) # tempfile used for output

unlink(fname) # remove the file
```

write.tridas

*Write Tree Ring Data Standard (TRiDaS) file***Description**

This function writes measured or derived (standardized, averaged) series of values to a TRiDaS format file. Some metadata are also supported.

**Usage**

```
write.tridas(rwl.df = NULL, fname, crn = NULL, prec = NULL, ids = NULL,
            titles = NULL, crn.types = NULL, crn.titles = NULL,
            crn.units = NULL, tridas.measuring.method = NA,
            other.measuring.method = "unknown", sample.type = "core",
            wood.completeness = NULL, taxon = "",
            tridas.variable = "ring width", other.variable = NA,
            project.info = list(type = c("unknown"), description = NULL,
                               title = "", category = "", investigator = "",
                               period = ""),
            lab.info = data.frame(name = "", acronym = NA, identifier = NA,
```



```

        domain = "", addressLine1 = NA,
        addressLine2 = NA, cityOrTown = NA,
        stateProvinceRegion = NA, postalCode = NA,
        country = NA),
research.info = data.frame(identifier = NULL, domain = NULL,
        description = NULL),
site.info = list(type = "unknown", description = NULL, title = ""),
random.identifiers = FALSE, identifier.domain = lab.info$name[1],
...)
```

## Arguments

<code>rwl.df</code>	data.frame containing tree-ring ring widths in millimetres with the series in columns and the years as rows. The series IDs are the column names and the years are the row names. This type of data.frame is produced by <code>read.tucson</code> , <code>read.compact</code> and <code>read.tridas</code> . Defaults to NULL: no measurement series are written.
<code>fname</code>	character vector giving the file name of the <code>rwl</code> file
<code>crn</code>	data.frame or a list of data.frames containing tree-ring chronologies. Accepts data.frames of the type produced by <code>chron</code> . Additionally, allows several chronologies per data.frame. Any column of the data.frame(s) with a name starting with "samp.depth" is interpreted as a sample depth. The rest of the columns are interpreted as chronologies whose titles are determined from the column names (optionally from parameter <code>crn.titles</code> ). Chronology columns and sample depth columns are paired in order so that the first chronology gets the first sample depth column, second chronology gets the second set of sample depths, etc. If there are less sample depth columns than chronologies, the sample depths are recycled. Defaults to NULL: no chronologies are written.
<code>prec</code>	optional numeric indicating the rounding precision of the output file when writing the data contained in <code>rwl.df</code> . Defaults to NULL: no rounding is done and the measurements are written in (non-integer) millimetres. Possible numeric values are 0.001, 0.01, 0.05, 0.1, 1, 10, 100 and 1000, which cause the data to be transformed to micrometres, 1/100th millimetres, 1/20th millimetres, 1/10 millimetres, (millimetres), centimetres, decimetres or metres, respectively, and then rounded to integral values. Data rounded to decimetres are written in centimetres (values always ending in zero). Otherwise, the matching unit is used in the file.
<code>ids</code>	optional data.frame with column one named "tree" giving the numeric ID of the tree, column two named "core" giving the numeric ID of the core, optional column three named "radius" giving the numeric ID of the radius, and optional column four named "measurement" giving the numeric ID of the measurement. If column "measurement" exists, column "radius" must also exist. Defaults to one core, radius and measurement per tree:

```

data.frame(tree=1:n.col, core=rep(1,n.col),
           radius=rep(1,n.col), measurement=rep(1,n.col))
```

where `n.col` is the number of columns in `rwl.df`.

titles	optional data.frame with column one named "tree" giving the title of the tree, column two named "core" giving the title of the core, column three named "radius" giving the title of the radius, and column four named "measurement" giving the title of the measurement. By default, <i>titles</i> is NULL, and the title hierarchy is automatically created out of the column names of <i>rwl.df</i> , taking <i>ids</i> into account.
crn.types	character vector or a list of character vectors giving the types of the derived series in <i>crn</i> . A single vector is interpreted as one type per data.frame in <i>crn</i> , recycled if not long enough. A list of vectors is interpreted as one list element per data.frame. In this case, the list is recycled to the correct length. After that, the vectors inside the list are recycled to match the number of derived series in each data.frame of <i>crn</i> . The default is to write empty '<type>' elements.
crn.titles	optional character vector or a list of character vectors giving the titles of the derived series in <i>crn</i> . The interpretation is the same as with <i>crn.types</i> , except that the default is to derive the titles from the column names of <i>crn</i> . Also NA means that the column name is used.
crn.units	optional character vector or a list of character vectors giving the units of the derived series in <i>crn</i> . The interpretation is the same as with <i>crn.types</i> , except that the default is to mark the series as '<unitless>'. Also NA means '<unitless>'.
tridas.measuring.method	character vector giving the measuring method used to acquire each series of <i>rwl.df</i> . Partial matching is used to replace these with the complete terms in <a href="#">tridas.vocabulary</a> . If the vector is shorter than the number of columns in <i>rwl.df</i> , it is recycled to the correct length. The default is to use the information in <i>other.measuring.method</i> instead. Also, NA in any position of the vector means that the measuring method information for that series is looked up in <i>other.measuring.method</i> .
other.measuring.method	character vector giving the measuring method used to acquire each series of <i>rwl.df</i> . In contrast to <i>tridas.measuring.method</i> , these are free-form strings in English. If the vector is shorter than the number of columns in <i>rwl.df</i> , it is recycled to the correct length. The default value is "unknown".
sample.type	optional character vector giving the type of the samples, corresponding to "core" in <i>ids</i> . The length of the vector, however, must match the number of columns in <i>rwl.df</i> , or it is recycled to the correct length. If there are several measurements per sample, some elements of <i>sample.type</i> are redundant. The default is to use "core" for all series.
wood.completeness	optional data.frame giving wood completeness information for the measurement series in <i>rwl.df</i> . The number of rows must match the number of columns in <i>rwl.df</i> . The columns are expected to be a subset of the following (descriptions almost directly quoted from TRiDaS specification): <b>n.unmeasured.inner</b> Field for recording whether there are any rings at the inner (i.e. towards pith) edge of the sample that have not been measured. Typically used to note when rings are too damaged to measure. Non-negative integral value.

	<p><b>n.unmeasured.outer</b> Field for recording whether there are any rings at the outer (i.e. towards bark) edge of the sample that have not been measured. Typically used to note when rings are too damaged to measure. Non-negative integral value.</p> <p><b>pith.presence</b> Whether the pith is present or absent. Each element must be a partial match with the contents of category "complex presence / absence" in <a href="#">tridas.vocabulary</a>.</p> <p><b>heartwood.presence</b> Whether the outer (youngest) heartwood is present and if so whether it is complete. Category "complex presence / absence" in <a href="#">tridas.vocabulary</a>.</p> <p><b>n.missing.heartwood</b> Estimated number of missing heartwood rings to the pith. Non-negative integral value.</p> <p><b>missing.heartwood.foundation</b> Description of the way the estimation of how many heartwood rings are missing was made and what the certainty is. Free-form string.</p> <p><b>sapwood.presence</b> Whether the sapwood is present or not. Category "complex presence / absence".</p> <p><b>n.sapwood</b> Number of sapwood rings measured. Non-negative integral value.</p> <p><b>last.ring.presence</b> Last ring under the bark is present or absent. Category "presence / absence".</p> <p><b>last.ring.details</b> If the last ring under the bark is present, include information about the completeness of this ring and/or season of felling. Free-form string.</p> <p><b>n.missing.sapwood</b> Estimated number of missing sapwood rings to the bark. Non-negative integral value.</p> <p><b>missing.sapwood.foundation</b> Description of the way the estimation of how many sapwood rings are missing was made and what the certainty is. Free-form string.</p> <p><b>bark.presence</b> Bark is present or absent. Category "presence / absence" in <a href="#">tridas.vocabulary</a>.</p>
taxon	character string. The most detailed taxonomic name known for this element (species, genus, family etc). Preferably from the <a href="#">Catalogue of Life</a> controlled vocabulary. The same string is used for all of <i>rw1.df</i> . The default value is an empty string, but a proper value should really be given.
tridas.variable	character string. Measured variable (ring width, earlywood, latewood etc) taken from the TRiDaS controlled vocabulary ( <a href="#">tridas.vocabulary</a> , category "variable"). The same string is used for all of <i>rw1.df</i> . Defaults to "ring width".
other.variable	character string. Measured variable as a free-form string. The same string is used for all of <i>rw1.df</i> . This is only used if <i>tridas.variable</i> is NA.
project.info	list containing information about the project. Elements are the following (includes quotes from the TRiDaS specification):  <p><b>type</b> character vector. The type(s) of the project. Defaults to "unknown".</p> <p><b>description</b> character string. A description of the project. Defaults to NULL: no description.</p>

	<p><b>title</b> character string. The title of the project. Defaults to an empty string.</p> <p><b>category</b> character string. Category of research this project falls into. Defaults to an empty string.</p> <p><b>investigator</b> character string. Principal investigator of this project. Defaults to an empty string.</p> <p><b>period</b> character string. When the dendrochronological project took place. Could consist of a start- and end-date. If unknown it should be estimated. Defaults to an empty string.</p>
lab.info	<p>data.frame. Information about the dendrochronological research laboratories where this work was done. One row per laboratory. Defaults to one laboratory with an empty name and no other information. The columns are expected to be a subset of the following:</p> <p><b>name</b> Name of the laboratory</p> <p><b>acronym</b> Optional acronym of the laboratory</p> <p><b>identifier</b> Optional identifier of the laboratory</p> <p><b>domain</b> The domain which the identifier of the laboratory is applicable to. Could be the URL of the organization's server or the name of the organization as long as it is not ambiguous.</p> <p><b>addressLine1</b> First address line</p> <p><b>addressLine2</b> Second address line</p> <p><b>cityOrTown</b> City or town</p> <p><b>stateProvinceRegion</b> State, province or region</p> <p><b>postalCode</b> Postal code. Beware of ignored leading zeros if these are given in numeric or integer type values. It is always safe to use character values.</p> <p><b>country</b> Country</p>
research.info	<p>optional data.frame with information about the systems in which the research project is registered. Columns are the following:</p> <p><b>identifier</b> Identifier</p> <p><b>domain</b> Domain which the identifier is applicable to</p> <p><b>description</b> General description</p>
site.info	<p>list containing information about the site ('&lt;object&gt;'). Elements are the following, and all are character strings:</p> <p><b>type</b> Type of the site. Defaults to "unknown".</p> <p><b>description</b> Description. Defaults to no description.</p> <p><b>title</b> Title of the site. Defaults to an empty string.</p>
random.identifiers	<p>logical flag. If TRUE, unique random identifiers are created with <a href="#">uuid.gen</a> and attached to each '&lt;project&gt;' (one in the file), '&lt;object&gt;' (site, one in the file), '&lt;element&gt;' (tree), '&lt;sample&gt;' (core), '&lt;radius&gt;', '&lt;measurementSeries&gt;' (measurement) and '&lt;derivedSeries&gt;' element in the resulting TRiDaS file.</p>
identifier.domain	<p>character string. The domain which the random identifiers are applicable to. Could be the URL of the organization's server or the name of the organization as long as it is not ambiguous. Defaults to the name of the first laboratory in <i>lab.info</i>.</p>
...	<p>Unknown arguments are accepted but not used.</p>

**Details**

The Tree Ring Data Standard (TRiDaS) is described in Jansma et. al (2010). Information about the current version of the standard can be found from [TRiDaS website](http://www.tridas.org/).

**Value**

*fname*

**Note**

This is an early version of the function. Bugs are likely to exist, and parameters are subject to change.

**Author(s)**

Mikko Korpela

**References**

Jansma, E., Brewer, P. W., and Zandhuis, I. (2010) TRiDaS 1.1: The tree-ring data standard. *Dendrochronologia*, **28**(2), 99–130.

TRiDaS – The Tree Ring Data Standard. <http://www.tridas.org/>.

**See Also**

[write.rwl](#), [write.tucson](#), [write.compact](#), [write.crn](#), [read.tridas](#)

**Examples**

```
library(utils)
## Write raw ring widths
data(co021)
fname1 <- write.tridas(rwl.df = co021,
  fname = tempfile(fileext=".xml"), prec = 0.01,
  site.info = list(title = "Schulman old tree no. 1, Mesa Verde",
    type = "unknown"),
  taxon = "Pseudotsuga menziesii var. menziesii (Mirb.) Franco",
  project.info = list(investigator = "E. Schulman",
    title = "", category = "",
    period = "", type = "unknown"))
print(fname1) # tempfile used for output

## Write mean value chronology of detrended ring widths
data(ca533)
ca533.rwi <- detrend(rwl = ca533, method = "ModNegExp")
ca533.crn <- chron(ca533.rwi, prefix = "CAM", prewhiten = TRUE)
fname2 <- write.tridas(crn = ca533.crn,
  fname = tempfile(fileext=".xml"),
  taxon = "Pinus longaeva D.K. Bailey",
  project.info =
    list(investigator = "Donald A. Graybill, V.C. LaMarche, Jr.",
```

```

        title = "Campito Mountain", category = "",
        period = "", type = "unknown"))
print(fname2) # tempfile used for output

unlink(c(fname1, fname2)) # remove the files

```

---

write.tucson

---

*Write Tucson Format Chronology File*


---

## Description

This function writes a chronology to a Tucson (decadal) format file.

## Usage

```

write.tucson(rwl.df, fname, header = NULL, append = FALSE,
             prec = 0.01, mapping.fname = "", mapping.append = FALSE,
             long.names = FALSE, ...)

```

## Arguments

rwl.df	a data.frame containing tree-ring ring widths with the series in columns and the years as rows. The series IDs are the column names and the years are the row names. This type of data.frame is produced by <a href="#">read.rwl</a> and <a href="#">read.compact</a> .
fname	a character vector giving the file name of the rwl file.
header	a list giving information for the header of the file. If NULL then no header information will be written.
append	logical flag indicating whether to append this chronology to an existing file. The default is to create a new file.
prec	numeric indicating the precision of the output file. This must be equal to either 0.01 or 0.001 (units are in mm).
mapping.fname	a character vector of length one giving the file name of an optional output file showing the mapping between input and output series IDs. The mapping is only printed for those IDs that are transformed. An empty name (the default) disables output.
mapping.append	logical flag indicating whether to append the description of the altered series IDs to an existing file. The default is to create a new file.
long.names	logical flag indicating whether to allow long series IDs (7 or 8 characters) to be written to the output. The default is to only allow 6 characters.
...	Unknown arguments are accepted but not used.

## Details

This writes a standard rwl file as defined according to the standards of the ITRDB at <http://www.ncdc.noaa.gov/paleo/treeinfo.html>. This is the decadal or Tucson format. It is an ASCII file and machine readable by the standard dendrochronology programs. Header information for the rwl can be written according to the International Tree Ring Data Bank (ITRDB) standard. The header standard is not very reliable however and should be thought of as experimental here. Do not try to write headers using dplR to submit to the ITRDB. When submitting to the ITRDB, you can enter the metadata via their website. If you insist however, the header information is given as a list and must be formatted with the following:

<i>Description</i>	<i>Name</i>	<i>Class</i>	<i>Max Width</i>
Site ID	<i>site.id</i>	character	5
Site Name	<i>site.name</i>	character	52
Species Code	<i>spp.code</i>	character	4
State or Country	<i>state.country</i>	character	13
Species	<i>spp</i>	character	18
Elevation	<i>elev</i>	character	5
Latitude	<i>lat</i>	character or numeric	5
Longitude	<i>long</i>	character or numeric	5
First Year	<i>first.yr</i>	character or numeric	4
Last Year	<i>last.yr</i>	character or numeric	4
Lead Investigator	<i>lead.invs</i>	character	63
Completion Date	<i>comp.date</i>	character	8

See examples for a correctly formatted header list. If the width of the fields is less than the max width, then the fields will be padded to the right length when written. Note that *lat* and *long* are really  $lat * 100$  or  $long * 100$  and given as integral values. E.g., 37 degrees 30 minutes would be given as 3750.

Series can be appended to the bottom of an existing file with a second call to `write.tucson`. The output from this file is suitable for publication on the ITRDB.

The function is capable of altering excessively long and/or duplicate series IDs to fit the Tucson specification. Additionally, characters other than numbers or English letters will be removed. If series IDs are changed, one or more warnings are shown. In that case, the user may wish to print a list of the renamings (see Arguments).

Setting `long.names = TRUE` allows series IDs to be 8 characters long, or 7 in case there are year numbers using 5 characters. Note that in the latter case the limit of 7 characters applies to all IDs, not just the one corresponding to the series with long year numbers. The default (`long.names = FALSE`) is to allow 6 characters. Long IDs may cause incompatibility with other software.

## Value

*fname*

## Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**

[write.crn](#), [read.tucson](#), [write.rwl](#), [write.compact](#), [write.tridas](#)

**Examples**

```
library(utils)
data(co021)
co021.hdr <- list(site.id = "C0021",
                 site.name = "SCHULMAN OLD TREE NO. 1, MESA VERDE",
                 spp.code = "PSME", state.country = "COLORADO",
                 spp = "DOUGLAS FIR", elev = "2103M", lat = 3712,
                 long = -10830, first.yr = 1400, last.yr = 1963,
                 lead.invs = "E. SCHULMAN", comp.date = "")
fname <- write.tucson(rwl.df = co021, fname = tempfile(fileext=".rwl"),
                    header = co021.hdr, append = FALSE, prec = 0.001)
print(fname) # tempfile used for output

unlink(fname) # remove the file
```

---

xskel.ccf.plot

*Skeleton Plot for Series and Master with Cross Correlation*


---

**Description**

...

**Usage**

```
xskel.ccf.plot(rwl, series, series.yrs = as.numeric(names(series)),
              win.start, win.width = 50, n = NULL,
              prewhiten = TRUE, biweight = TRUE)
```

**Arguments**

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
series	a numeric or character vector. Usually a tree-ring series. If the length of the value is 1, the corresponding column of <i>rwl</i> is selected (by name or position) as the series and ignored when building the master chronology. Otherwise, the value must be numeric.
series.yrs	a numeric vector giving the years of <i>series</i> . Defaults to <code>as.numeric(names(series))</code> .
win.start	year to start window
win.width	an even integral value
n	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
prewhiten	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .
biweight	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .



## Details

This function produces a plot that is a mix of a skeleton plot and a cross-correlation plot. It's used in crossdating.

The top panel shows the normalized values for the master chronology (bottom half) and the series (top half) in green. The values are the detrended and standardized data (e.g., RWI).

Similarly, the black lines are a skeleton plot for the master and series with the marker years annotated for the master on the bottom axis and series on the top. The text at the top of the figure gives the correlation between the series and master (green bars) as well as the percentage of agreement between the years of skeleton bars for the series and master. I.e., if all the black lines occur in the same years the percentage would be 100%.

The bottom panels show cross correlations for the first half (left) and second half of the time series using function `ccf` as `ccf(x=series,y=master,lag.max=5)`.

The plot is built using the `Grid` package which allows for great flexibility in building complicated plots. However, these plots look best when they don't cover too wide a range of years (unless the plotting device is wider than is typical). For that reason the user will get a warning if `win.width` is greater than 100 years.

## Value

None. Invoked for side effect (plot).

## Author(s)

Andy Bunn. Patched and improved by Mikko Korpela.

## See Also

`ccf`

## Examples

```
library(utils)
data(co021)
dat <- co021
#corrupt a series
bad.series <- dat$"641143"
names(bad.series) <- rownames(dat)
bad.series <- delete.ring(bad.series,year=1825)
# good match
xskel.ccf.plot(rwl=dat,series=bad.series,win.start=1900,win.width=50)
# overlap missing ring
xskel.ccf.plot(rwl=dat,series=bad.series,win.start=1800,win.width=50)
```

xskel.plot

*Skeleton Plot for Series and Master***Description**

...

**Usage**

```
xskel.plot(rwl, series, series.yrs = as.numeric(names(series)),
           win.start, win.end = win.start+100, n = NULL,
           prewhiten = TRUE, biweight = TRUE)
```

**Arguments**

rwl	a data.frame with series as columns and years as rows such as that produced by <a href="#">read.rwl</a> .
series	a numeric or character vector. Usually a tree-ring series. If the length of the value is 1, the corresponding column of <i>rwl</i> is selected (by name or position) as the series and ignored when building the master chronology. Otherwise, the value must be numeric.
series.yrs	a numeric vector giving the years of <i>series</i> . Defaults to <code>as.numeric(names(series))</code> .
win.start	year to start window
win.end	year to end window
n	NULL or an integral value giving the filter length for the <a href="#">hanning</a> filter used for removal of low frequency variation.
prewhiten	logical flag. If TRUE each series is whitened using <a href="#">ar</a> .
biweight	logical flag. If TRUE then a robust mean is calculated using <a href="#">tbrm</a> .

**Details**

This function produces a plot that is a mix of a skeleton plot and a cross-correlation plot. It's used in [crossdating](#).

The top panel shows the normalized values for the master chronology (bottom half) and the series (top half) in green. The values are the detrended and standardized data (e.g., RWI).

Similarly, the black lines are a skeleton plot for the master and series with the marker years annotated for the master on the bottom axis and series on the top. The text at the top of the figure gives the correlation between the series and master (green bars) as well as the percentage of agreement between the years of skeleton bars for the series and master. I.e., if all the black lines occur in the same years the percentage would be 100%.

The bottom panels show cross correlations for the first half (left) and second half of the time series using function [ccf](#) as `ccf(x=series,y=master,lag.max=5)`.

The plot is built using the [Grid](#) package which allows for great flexibility in building complicated plots. However, these plots look best when they don't cover too wide a range of years (unless the

plotting device is wider than is typical). For that reason the user will get a warning if *win.width* is greater than 100 years.

**Value**

None. Invoked for side effect (plot).

**Author(s)**

Andy Bunn. Patched and improved by Mikko Korpela.

**See Also**

[ccf](#)

**Examples**

```
library(utils)
data(co021)
dat <- co021
#corrupt a series
bad.series <- dat$"641143"
names(bad.series) <- rownames(dat)
bad.series <- delete.ring(bad.series,year=1825)
# good match
xskel.plot(rwl=dat,series=bad.series,win.start=1850)
# overlap missing ring
xskel.plot(rwl=dat,series=bad.series,win.start=1800)
```

# Index

## \*Topic **IO**

- csv2rwl, 24
- read.compact, 66
- read.crn, 67
- read.fh, 68
- read.rwl, 72
- read.tridas, 73
- read.tucson, 80
- write.compact, 116
- write.crn, 117
- write.rwl, 119
- write.tridas, 120
- write.tucson, 126

## \*Topic **aplot**

- rasterPlot, 61

## \*Topic **datasets**

- anos1, 4
- ca533, 9
- cana157, 9
- co021, 15
- gp.d2pith, 37
- gp.dbh, 38
- gp.po, 38
- gp.rwl, 39
- wa082, 112

## \*Topic **hplot**

- crn.plot, 22
- morlet, 48
- plot.rwl, 51
- plotRings, 52
- seg.plot, 95
- skel.plot, 100
- spag.plot, 102
- wavelet.plot, 112
- xskel.ccf.plot, 128
- xskel.plot, 130

## \*Topic **htest**

- redfit, 81

## \*Topic **iplot**

- i.detrend, 41

- i.detrend.series, 42

## \*Topic **manip**

- bai.in, 5
- bai.out, 7
- ccf.series.rwl, 10
- chron, 12
- cms, 13
- combine.rwl, 16
- common.interval, 17
- corr.rwl.seg, 18
- corr.series.seg, 20
- detrend, 26
- detrend.series, 28
- fill.internal.NA, 33
- insert.ring, 43
- interseries.cor, 44
- po.to.wc, 55
- powt, 58
- print.rwl.report, 60
- rcs, 64
- rwl.report, 91
- series.rwl.plot, 98
- strip.rwl, 103
- time.rwl, 106
- treeMean, 107
- wc.to.po, 115

## \*Topic **misc**

- read.ids, 69
- rwi.stats.running, 87
- rwl.stats, 92

## \*Topic **package**

- dplR-package, 4

## \*Topic **print**

- print.redfit, 59

## \*Topic **robust**

- tbrm, 105

## \*Topic **smooth**

- ffcsaps, 31

- \*Topic **ts**
  - glk, 36
  - hanning, 40
  - net, 50
  - redfit, 81
  - sea, 94
- \*Topic **univar**
  - gini.coef, 35
  - sens1, 96
  - sens2, 97
  - tbrm, 105
- \*Topic **utilities**
  - latexDate, 45
  - latexify, 46
  - rasterPlot, 61
  - tridas.vocabulary, 108
  - uuid.gen, 110
- .Platform, 110
- .Random.seed, 110
- %dopar%, 27, 89
- anos1, 4
- approx, 33, 34
- ar, 10–13, 18, 19, 21, 29, 44, 87, 98, 128, 130
- autoread.ids (read.ids), 69
- axis, 19
- bai.in, 5, 7, 8
- bai.out, 5, 6, 7
- bigq, 82
- ca533, 9, 41, 69, 89
- Cairo, 62
- Cairo.capabilities, 62
- call, 61
- cana157, 9
- capabilities, 62
- captureOutput, 47
- ccf, 11, 129–131
- ccf.series.rwl, 10, 20, 21, 99
- chron, 4, 12, 15, 22, 23, 66, 94, 105, 106, 117, 118, 121
- cms, 13, 66
- co021, 15
- combine.rwl, 16
- common.interval, 17
- compactPDF, 61
- cor, 87, 90
- cor.test, 18, 19, 21, 44, 45
- corr.rwl.seg, 4, 11, 18, 44, 89, 90, 99
- corr.series.seg, 11, 20, 20, 21, 99
- crn.plot, 13, 22
- csv2rwl, 24, 73
- delete.ring (insert.ring), 43
- detrend, 4, 12, 13, 15, 26, 30, 32, 66, 87, 90
- detrend.series, 4, 26, 27, 28, 41, 42
- dev.capabilities, 62
- Devices, 27, 101
- digest, 111
- dplR, 43
- dplR (dplR-package), 4
- dplR-package, 4
- dQuote, 47
- Encoding, 47
- expression, 61
- ffcsaps, 23, 28–30, 31, 33, 65, 66, 113, 114
- file, 67, 80
- fill.internal.NA, 33
- filter, 40
- foreach, 27, 89
- format, 59
- formula, 30
- gini.coef, 35, 93
- glk, 4, 36, 50
- gp.d2pith, 37
- gp.dbh, 38
- gp.po, 38
- gp.rwl, 37, 38, 39
- Grid, 129, 130
- grid.raster, 62
- hanning, 10, 11, 18, 19, 21, 32, 40, 44, 87, 98, 100, 101, 128, 130
- i.detrend, 41
- i.detrend.series, 42
- insert.ring, 43
- interseries.cor, 44, 60, 61, 92
- latexDate, 45
- latexify, 46
- lines, 102
- match.call, 84
- message, 62

- morlet, [48](#), [112–114](#)
- NA, [24](#)
- net, [50](#)
- nls, [29](#)
- packageVersion, [84](#)
- par, [61](#)
- plot, [23](#), [65](#)
- plot.crn (crn.plot), [22](#)
- plot.rwl, [51](#)
- plotRings, [52](#)
- png, [62](#)
- po.to.wc, [55](#), [115](#)
- pointer, [56](#)
- powt, [58](#), [65](#)
- print.data.frame, [59](#)
- print.redfit, [59](#), [85](#)
- print.rwl.report, [60](#)
- R.version, [110](#)
- Random, [111](#)
- rasterImage, [62](#)
- rasterPlot, [61](#), [113](#)
- rcs, [15](#), [56](#), [58](#), [64](#), [68](#), [115](#)
- read.compact, [66](#), [73](#), [80](#), [81](#), [116](#), [117](#), [121](#), [126](#)
- read.crn, [9](#), [67](#), [106](#), [118](#)
- read.fh, [58](#), [67](#), [68](#), [73](#), [80](#), [81](#), [103](#)
- read.ids, [5](#), [69](#), [88](#), [90](#), [107](#)
- read.rwl, [4](#), [5](#), [7](#), [9](#), [10](#), [12–15](#), [17](#), [18](#), [20](#), [25](#), [26](#), [33](#), [41](#), [44](#), [52](#), [56](#), [58](#), [64](#), [67–69](#), [72](#), [72](#), [80](#), [81](#), [91–93](#), [95](#), [98](#), [102](#), [103](#), [106](#), [107](#), [112](#), [116](#), [119](#), [120](#), [126](#), [128](#), [130](#)
- read.table, [24](#), [25](#)
- read.tridas, [67](#), [73](#), [73](#), [81](#), [109](#), [115](#), [121](#), [125](#)
- read.tucson, [67](#), [73](#), [80](#), [80](#), [121](#), [128](#)
- readPNG, [62](#)
- redfit, [4](#), [60](#), [81](#)
- regex, [47](#)
- rowMeans, [107](#)
- runcrit (redfit), [81](#)
- rwi.stats, [44](#), [45](#), [72](#), [90](#), [93](#), [103](#), [104](#)
- rwi.stats (rwi.stats.running), [87](#)
- rwi.stats.legacy, [90](#)
- rwi.stats.running, [87](#)
- rwl.report, [60](#), [61](#), [91](#)
- rwl.stats, [35](#), [45](#), [92](#), [97](#), [98](#)
- save, [4](#), [9](#), [15](#), [112](#)
- saveGIF, [54](#)
- scale, [102](#)
- sea, [94](#)
- seg.plot, [17](#), [52](#), [95](#), [103](#)
- sens1, [93](#), [96](#), [98](#)
- sens2, [93](#), [97](#), [97](#)
- series.rwl.plot, [11](#), [19–21](#), [44](#), [98](#)
- skel.plot, [11](#), [20](#), [21](#), [57](#), [100](#)
- spag.plot, [52](#), [96](#), [102](#)
- spline, [33](#), [34](#)
- sQuote, [47](#)
- strip.rwl, [103](#)
- summary, [93](#)
- summary.rwl, [60](#), [61](#), [92](#)
- summary.rwl (rwl.stats), [92](#)
- supsmu, [26](#), [29](#)
- Sys.info, [110](#)
- tbrm, [10–12](#), [18](#), [19](#), [21](#), [44](#), [65](#), [98](#), [105](#), [128](#), [130](#)
- time.crn (time.rwl), [106](#)
- time.rwl, [106](#)
- treeMean, [107](#)
- tridas.vocabulary, [108](#), [122](#), [123](#)
- uuid.gen, [110](#), [124](#)
- wa082, [112](#)
- wavelet.plot, [49](#), [50](#), [102](#), [112](#)
- wc.to.po, [56](#), [115](#)
- write.compact, [67](#), [116](#), [120](#), [125](#), [128](#)
- write.crn, [117](#), [118](#), [120](#), [125](#), [128](#)
- write.rwl, [73](#), [117](#), [119](#), [125](#), [128](#)
- write.tridas, [56](#), [80](#), [109](#), [117](#), [120](#), [120](#), [128](#)
- write.tucson, [81](#), [117](#), [120](#), [125](#), [126](#)
- x11, [62](#)
- xskel.ccf.plot, [128](#)
- xskel.plot, [130](#)