

Package ‘etm’

January 2, 2012

Title Empirical Transition Matrix

Version 0.5-2

Author Arthur Allignol

Description Matrix of transition probabilities for any
time-inhomogeneous multistate model with finite state space

Maintainer Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>

License GPL (>= 2)

Depends lattice,survival

Suggests changeLOS

date 2010/12/6

Repository CRAN

Date/Publication 2011-01-03 12:53:49

R topics documented:

abortion	2
clos	3
etm	5
etmCIF	8
etmprep	10
fourD	12
lines.etm	13
plot.clos.etm	14
plot.etm	15
plot.etmCIF	17
print.clos.etm	18
print.etm	19
print.etmCIF	20
sir.cont	21

summary.etm	22
summary.etmCIF	23
trprob.etm	24
xyplot.etm	25

Index	27
--------------	-----------

abortion	<i>Pregnancies exposed to coumarin derivatives</i>
----------	--

Description

Outcomes of pregnancies exposed to coumarin derivatives. The aim is to investigate whether exposure to coumarin derivatives increases the probability of spontaneous abortions. Apart from spontaneous abortion, pregnancy may end in induced abortion or live birth, leading to a competing risks situation. Moreover, data are left-truncated as women usually enter the study several weeks after conception.

Usage

```
data(abortion)
```

Format

A data frame with 1186 observations on the following 5 variables.

`id` Identification number

`entry` Entry times into the cohort

`exit` Event times

`group` Group. 0: control, 1: exposed to coumarin derivatives

`cause` Cause of failure. 1: induced abortion, 2: life birth, 3: spontaneous abortion

Source

Meiester, R. and Schaefer, C (2008). Statistical methods for estimating the probability of spontaneous abortion in observational studies – Analyzing pregnancies exposed to coumarin derivatives. *Reproductive Toxicology*, 26, 31–35

Examples

```
data(abortion)
```

clos *Change in Length of Stay*

Description

The function estimates the expected change in length of stay (LOS) associated with an intermediate event in the same way as does the `clos` function in the **changeLOS** package. The difference between the 2 implementations is that this function can handle left-truncated data, and does not require a competing outcome.

Usage

```
clos(x, aw = FALSE)
```

Arguments

x	An object of class <code>etm</code> . Argument <code>delta.na</code> in <code>etm</code> must be set to <code>TRUE</code> in order to use this function.
aw	Logical. Whether to compute the expected change of LOS using alternative weighting. Default is <code>FALSE</code> .

Details

See `clos` for more details on the method

Value

An object of class `clos.etm` with the following components:

e.phi	Change in length of stay
phi.case	Estimates of $E(\text{LOS} X_s = \text{intermediate event})$ for all observed transition times s , where X_s denotes the state by time s
phi.control	Estimates of $E(\text{LOS} X_s = \text{initial state})$ for all observed transition times s .
e.phi2	Weighted average of the difference between <code>phi2.case</code> and <code>phi2.control</code> .
phi2.case	Estimates of $E(\text{LOS1}(X_{\text{LOS}} = \text{discharge}) X_s = \text{intermediate event})$, where <code>1</code> denotes the indicator function.
phi2.control	$E(\text{LOS1}(X_{\text{LOS}} = \text{discharge}) X_s = \text{initial state})$.
e.phi3	Weighted average of the difference between <code>phi3.case</code> and <code>phi3.control</code> .
phi3.case	Estimates of $E(\text{LOS1}(X_{\text{LOS}} = \text{death}) X_s = \text{intermediate event})$.
phi3.control	$E(\text{LOS1}(X_{\text{LOS}} = \text{death}) X_s = \text{initial state})$.
weights	Weights used to compute the weighted averages.
w.time	Times at which the weights are computed.
time	All transition times.

e.phi.weights.1	Expected change in LOS using weights.1
e.phi.weights.other	Expected change in LOS using weights.other
weights.1	Weights corresponding to the conditional waiting time in the initial state given one experiences the intermediate event.
weights.other	Weights corresponding to the conditional waiting time given one does not experience the intermediate event.

Author(s)

Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>, Matthias Wangler, Jan Beyersmann

See Also

[clos](#), [etm](#)

Examples

```
require(changeLOS)
data(los.data) # in package changeLOS

## putting los.data in the long format (see changeLOS)
my.observ <- prepare.los.data(x=los.data)

tra <- matrix(FALSE, 4, 4)
tra[1, 2:4] <- TRUE
tra[2, 3:4] <- TRUE

tr.prob <- etm(my.observ, c("0","1","2","3"), tra, NULL, 0)

cLOS <- etm::clos(tr.prob)
plot(cLOS)

### Compute bootstrapped SE

## function that performs the bootstrap
## nboot: number of bootstrap samples. Other arguments are as in etm()
boot.clos <- function(data, state.names, tra, cens.name, s = 0, nboot) {
  res <- double(nboot)
  for (i in seq_len(nboot)) {
    index <- sample(unique(data$id), replace = TRUE)
    inds <- new.id <- NULL
    for (j in seq_along(index)){
      ind <- which(data$id == index[j])
      new.id <- c(new.id, rep(j, length(ind)))
      inds <- c(inds, ind)
    }
    dboot <- cbind(data[inds, ], new.id)
    dboot[, which(names(dboot) == "id")]
  }
}
```

```

      dboot$id <- dboot$new.id
      tr.prob <- etm(dboot, state.names, tra, cens.name, s, cova = FALSE)
      res[i] <- etm::clos(tr.prob)$e.phi
    }
  res
}

## bootstrap
se <- sqrt(var(boot.clos(my.observ, c("0","1","2","3"), tra, NULL, 0,
                           nboot = 10)))

```

etm

Computation of the empirical transition matrix

Description

This function computes the empirical transition matrix, also called Aalen-Johansen estimator, of the transition probability matrix of any multistate model. The covariance matrix is also computed.

Usage

```

etm(data, state.names, tra, cens.name, s, t = "last",
     covariance = TRUE, delta.na = TRUE)

```

Arguments

data	data.frame of the form data.frame(id,from,to,time) or (id,from,to,entry,exit) id: patient id from: the state from where the transition occurs to: the state to which a transition occurs time: time when a transition occurs entry: entry time in a state exit: exit time from a state This data.frame is transition-oriented, <i>i.e.</i> it contains one row per transition, and possibly several rows per patient. Specifying an entry and exit time permits to take into account left-truncation.
state.names	A vector of characters giving the states names.
tra	A quadratic matrix of logical values describing the possible transitions within the multistate model.
cens.name	A character giving the code for censored observations in the column 'to' of data. If there is no censored observations in your data, put 'NULL'.
s	Starting value for computing the transition probabilities.
t	Ending value. Default is "last", meaning that the transition probabilities are computed over $(s, t]$, t being the last time in the data set.

covariance	Logical. Decide whether or not computing the covariance matrix. May be useful for, say, simulations, as the variance computation is a bit long. Default is TRUE.
delta.na	Logical. Whether to export the array containing the increments of the Nelson-Aalen estimator. Default is TRUE.

Details

Data are considered to arise from a time-inhomogeneous Markovian multistate model with finite state space, and possibly subject to independent right-censoring and left-truncation.

The matrix of the transition probabilities is estimated by the Aalen-Johansen estimator / empirical transition matrix (Andersen et al., 1993), which is the product integral over the time period $(s, t]$ of $I +$ the matrix of the increments of the Nelson-Aalen estimates of the cumulative transition hazards. The (i, j) - *th* entry of the empirical transition matrix estimates the transition probability of being in state j at time t given that one has been in state j at time s .

The covariance matrix is computed using the recursion formula (4.4.19) in Anderson et al. (1993, p. 295). This estimator of the covariance matrix is an estimator of the Greenwood type.

If the multistate model is not Markov, but censorship is entirely random, the Aalen-Johansen estimator still consistently estimates the state occupation probabilities of being in state i at time t (Datta & Satten, 2001; Glidden, 2002)

Value

est	Transition probability estimates. This is a 3 dimension array with the first dimension being the state from where transitions occur, the second the state to which transitions occur, and the last one being the event times.
cov	Estimated covariance matrix. Each cell of the matrix gives the covariance between the transition probabilities given by the rownames and the colnames, respectively.
time	Event times at which the transition probabilities are computed. That is all the observed times between $(s, t]$.
s	Start of the time interval.
t	End of the time interval.
trans	A data.frame giving the possible transitions.
state.names	A vector of character giving the state names.
cens.name	How the censored observation are coded in the data set.
n.risk	Matrix indicating the number of individuals at risk just before an event
n.event	Array containing the number of transitions at each times
delta.na	A 3d array containing the increments of the Nelson-Aalen estimator.

Note

Transitions into a same state, mathematically superfluous, are not allowed. If transitions into the same state are detected in the data, the function will stop. Equally, `diag(tra)` must be set to FALSE, see the example below.

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

References

- Allignol, A., Schumacher, M. and Beyersmann, J. (2011). Empirical Transition Matrix of Multi-State Models: The etm Package. *Journal of Statistical Software*, 38.
- Andersen, P.K., Borgan, O., Gill, R.D. and Keiding, N. (1993). *Statistical models based on counting processes*. Springer Series in Statistics. New York, NY: Springer.
- Aalen, O. and Johansen, S. (1978). An empirical transition matrix for non-homogeneous Markov chains based on censored observations. *Scandinavian Journal of Statistics*, 5: 141-150.
- Gill, R.D. and Johansen, S. (1990). A survey of product-integration with a view towards application in survival analysis. *Annals of statistics*, 18(4): 1501-1555.
- Datta, S. and Satten G.A. (2001). Validity of the Aalen-Johansen estimators of stage occupation probabilities and Nelson-Aalen estimators of integrated transition hazards for non-Markov models. *Statistics and Probability Letters*, 55(4): 403-411.
- Glidden, D. (2002). Robust inference for event probabilities with non-Markov data. *Biometrics*, 58: 361-368.

See Also

[print.etm](#), [summary.etm](#), [sir.cont](#), [xyplot.etm](#)

Examples

```
data(sir.cont)

# Modification for patients entering and leaving a state
# at the same date
# Change on ventilation status is considered
# to happen before end of hospital stay
sir.cont <- sir.cont[order(sir.cont$id, sir.cont$time), ]
for (i in 2:nrow(sir.cont)) {
  if (sir.cont$id[i]==sir.cont$id[i-1]) {
    if (sir.cont$time[i]==sir.cont$time[i-1]) {
      sir.cont$time[i-1] <- sir.cont$time[i-1] - 0.5
    }
  }
}

### Computation of the transition probabilities
# Possible transitions.
tra <- matrix(ncol=3,nrow=3,FALSE)
tra[1, 2:3] <- TRUE
tra[2, c(1, 3)] <- TRUE

# etm
tr.prob <- etm(sir.cont, c("0", "1", "2"), tra, "cens", 1)
```

```

tr.prob
summary(tr.prob)

# plotting
xyplot(tr.prob, tr.choice=c("0 0", "1 1", "0 1", "0 2", "1 0", "1 2"),
       layout=c(2, 3), strip=strip.custom(bg="white",
       factor.levels=
       c("0 to 0", "1 to 1", "0 to 1", "0 to 2", "1 to 0", "1 to 2")))

### example with left-truncation

data(abortion)

# Data set modification in order to be used by etm
names(abortion) <- c("id", "entry", "exit", "from", "to")
abortion$to <- abortion$to + 1

## computation of the matrix giving the possible transitions
tra <- matrix(FALSE, nrow = 5, ncol = 5)
tra[1:2, 3:5] <- TRUE

## etm
fit <- etm(abortion, as.character(0:4), tra, NULL, s = 0)

## plot
xyplot(fit, tr.choice = c("0 0", "1 1", "0 4", "1 4"),
       ci.fun = c("log-log", "log-log", "cloglog", "cloglog"),
       strip = strip.custom(factor.levels = c("P(T > t) -- control",
       "P(T > t) -- exposed",
       "CIF spontaneous abortion -- control",
       "CIF spontaneous abortion -- exposed")))

```

etmCIF

Cumulative incidence functions of competing risks

Description

etmCIF is a wrapper around the etm function for facilitating the computation of the cumulative incidence functions in the competing risks framework.

Usage

```
etmCIF(formula, data, etype, subset, na.action, failcode = 1)
```

Arguments

formula	A formula object, that must have a Surv object on the left of ~ operator, and a discrete covariate (or 1) on the right. The status indicator should be 1 (or TRUE) for an event (whatever the type of this event, 0 (or FALSE) for censored observations.)
---------	--

data	A data.frame in which to interpret the terms of the formula
etype	Competing risks event indicator. When the status indicator is 1 (or TRUE) in the formula, etype describes the type of event, otherwise, for censored observation, the value of etype is ignored
subset	Expression saying that only a subset of the data should be used.
na.action	Missing-data filter function. Default is options()\$na.action.
failcode	Indicates the failure type of interest. Default is one. This option is only relevant for some options of the plot function.

Details

This function computes the cumulative incidence functions in a competing risks setting using the etm machinery, without having to specify the matrix of possible transitions and using the more usual formula specification with Surv

Value

Returns a list of etm objects (1 per covariate level) plus additional informations:

failcode	As in function call
call	Function call
X	A matrix giving the name of the covariate (if present) and the levels of this covariate.

Author(s)

Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etm](#), [print.etmCIF](#), [summary.etmCIF](#), [plot.etmCIF](#)

Examples

```
data(abortion)

cif.ab <- etmCIF(Surv(entry, exit, cause != 0) ~ group, abortion,
                etype = cause, failcode = 3)

cif.ab

plot(cif.ab, ci.type = "bars", pos.ci = 24,
     col = c(1, 2), lty = 1, curvlab = c("Control", "Exposed"))
```

 etmprep

Data transformation function for using etm

Description

The function transforms a data set in the wide format (i.e., one row per subject) into the long format (i.e., one row per transition, and possibly several rows per subjects) in a suitable way for using the `etm` function

Usage

```
etmprep(time, status, data, tra, state.names, cens.name = NULL,
        start = NULL, id = NULL, keep)
```

Arguments

<code>time</code>	A character vector giving the name of the columns containing the transition times or last follow-up times. The length of <code>time</code> have to be equal to the number of states, some elements may be NA. See Details.
<code>status</code>	A character vector giving the name of the columns indicating whether a state has been visited (0 if not, 1 otherwise).
<code>data</code>	A data frame in which to look for the columns specified in <code>time</code> and <code>status</code> .
<code>tra</code>	A quadratic matrix of logical values describing the possible transitions within the multistate model. The (i, j) th element of <code>tra</code> is TRUE if a transition from state i to state j is possible, FALSE otherwise. The diagonal must be set to FALSE.
<code>state.names</code>	A vector of characters giving the states names. If missing, state names are set to be 0:(number of states).
<code>cens.name</code>	A character string specifying how censored observations will be indicated in the new data set. Default is NULL, i.e., no censored observation.
<code>start</code>	A list containing two elements, <code>state</code> and <code>time</code> , giving the starting states and times for all individuals. Default is NULL, in which case all individuals are considered to start in the initial state at time 0.
<code>id</code>	A character string specifying in which column of <code>data</code> the user ids are. Default is NULL, and the ids will be 1:n.
<code>keep</code>	A character vector indicating the column names of the covariate one might want to keep in the new data.frame.

Details

This function only works for irreversible acyclic Markov processes. Therefore, the multistate model will have initial states, into which no transition are possible. For these, NAs are allowed in `time` and `status`.

Value

The function returns a data.frame suitable for using the `etm` function. The data frame contains the following components:

<code>id</code>	Individual id number
<code>entry</code>	Entry time into a state
<code>exit</code>	Exit time from a state
<code>from</code>	State from which a transition occurs
<code>to</code>	State into which a transition occurs
<code>...</code>	Further columns specified in <code>keep</code>

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etm](#)

Examples

```
### creation of fake data in the wild format, following an illness-death model
## transition times
tdisease <- c(3, 4, 3, 6, 8, 9)
tdeath <- c(6, 9, 8, 6, 8, 9)

## transition status
stat.disease <- c(1, 1, 1, 0, 0, 0)
stat.death <- c(1, 1, 1, 1, 1, 0)

## a covariate that we want to keep in the new data
cova <- rbinom(6, 1, 0.5)

dat <- data.frame(tdisease, tdeath,
                 stat.disease, stat.death,
                 cova)

## Possible transitions
tra <- matrix(FALSE, 3, 3)
tra[1, 2:3] <- TRUE
tra[2, 3] <- TRUE

## data preparation
newdat <- etmprep(c(NA, "tdisease", "tdeath"),
                 c(NA, "stat.disease", "stat.death"),
                 data = dat, tra = tra, cens.name = "cens")
```

`fourD`*Placebo data from the 4D study*

Description

Data from the placebo group of the 4D study. This study aimed at comparing atorvastatin to placebo for patients with type 2 diabetes and receiving hemodialysis in terms of cardiovascular events. The primary endpoint was a composite of death from cardiac causes, stroke and non-fatal myocardial infarction. Competing event was death from other causes.

Usage`data(fourD)`**Format**

A data frame with 636 observations on the following 7 variables.

`id` Patients' id number

`sex` Patients' gender

`age` Patients' age

`medication` Character vector indicating treatment affiliation. Here only equal to "Placebo"

`status` Status at the end of the follow-up. 1 for the event of interest, 2 for death from other causes and 0 for censored observations

`time` Survival time

`treated` Numeric vector indicated whether patients are treated or not. Here always equal to zero

Source

Wanner, C., Krane, V., Maerz, W., Olschewski, M., Mann, J., Ruf, G., Ritz, E (2005). Atorvastatin in patients with type 2 diabetes mellitus undergoing hemodialysis. *New England Journal of Medicine*, 353(3), 238–248.

References

Allignol, A., Schumacher, M., Wanner, C., Dreschler, C. and Beyersmann, J. (2010). Understanding competing risks: a simulation point of view. Research report.

Examples`data(fourD)`

lines.etm *Lines method for 'etm' objects*

Description

Lines method for etm objects

Usage

```
## S3 method for class 'etm'
lines(x, tr.choice, col = 1, lty,
      conf.int = FALSE, level = 0.95, ci.fun = "linear",
      ci.col = col, ci.lty = 3, ...)
```

Arguments

x	An object of class etm.
tr.choice	character vector of the form c("from to", "from to") specifying which transitions should be plotted. By default, all the direct transition probabilities are plotted
col	Vector of colours. Default is black.
lty	Vector of line type. Default is 1:number of transitions
conf.int	Logical specifying whether to plot confidence intervals. Default is FALSE.
level	Level of the confidence interval. Default is 0.95.
ci.fun	Transformation applied to the confidence intervals. It could be different for all transition probabilities, though if length(ci.fun) != number of transitions, only ci.fun[1] will be used. Possible choices are "linear", "log", "log-log" and "cloglog". Default is "linear".
ci.col	Colours of the confidence intervals. Default value is the same as col.
ci.lty	Line types for the confidence intervals. Default is 3.
...	Further arguments for lines.

Value

No value returned.

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etm](#), [plot.etm](#), [xyplot.etm](#)

plot.clos.etm

Plot method for 'clos.etm' objects

Description

Plot method for objects of class `clos.etm`.

Usage

```
## S3 method for class 'clos.etm'
plot(x, xlab = "Time", ylab.e = "Expected LOS",
     ylab.w = "Weights", xlim, ylim.e, ylim.w, col.e = c(1, 2), col.w = 1,
     lty.e = c(1, 1), lty.w = 1, legend = TRUE, legend.pos, curvlab,
     legend.bty = "n", ...)
```

Arguments

<code>x</code>	An object of class <code>clos.etm</code>
<code>xlab</code>	Label for the x-axis
<code>ylab.e</code>	Label for the y-axis in the plot of the expected LOS
<code>ylab.w</code>	Label for the y-axis in the plot of the weights
<code>xlim</code>	Limits of x-axis for the plots
<code>ylim.e</code>	Limits of the y-axis for the expected LOS plot
<code>ylim.w</code>	Limits of the y-axis for the weights plot
<code>col.e</code>	Vector of colours for the plot of expected LOS
<code>col.w</code>	Vector of colours for the plot of the weights
<code>lty.e</code>	Vector of line type for the plot of expected LOS
<code>lty.w</code>	Vector of line type for the plot of the weights
<code>legend</code>	Logical. Whether to draw a legend for the plot of expected LOS
<code>legend.pos</code>	A vector giving the legend's position. See legend for details
<code>curvlab</code>	Character or expression vector to appear in the legend. Default is <code>c("Intermediate event by time t", "No intermediate event by time t")</code>
<code>legend.bty</code>	Box type for the legend
<code>...</code>	Further arguments for plot

Details

Two graphs are drawn. The lower graph displays the expected LOS for patients who have experienced the intermediate event and for those who have not. The upper graph displays the weights used to compute the weighted average.

Value

No value returned

Author(s)

Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>, Matthias Wangler

See Also

[clos](#)

plot.etm

Plot method for an etm object

Description

Plot method for an object of class 'etm'. It draws the estimated transition probabilities in a basic scatterplot.

Usage

```
## S3 method for class 'etm'
plot(x, tr.choice, xlab = "Time",
      ylab = "Transition Probability", col = 1, lty, xlim, ylim,
      conf.int = FALSE, level = 0.95, ci.fun = "linear",
      ci.col = col, ci.lty = 3,
      legend = TRUE, legend.pos, curvlab, legend.bty = "n", ...)
```

Arguments

x	An object of class 'etm'
tr.choice	character vector of the form 'c("from to","from to")' specifying which transitions should be plotted. Default, all the transition probabilities are plotted
xlab	x-axis label. Default is "Time"
ylab	y-axis label. Default is "Transition Probability"
col	Vector of colour. Default is black
lty	Vector of line type. Default is 1:number of transitions
xlim	Limits of x-axis for the plot
ylim	Limits of y-axis for the plot
conf.int	Logical. Whether to display pointwise confidence intervals. Default is FALSE.
level	Level of the confidence intervals. Default is 0.95.
ci.fun	Transformation applied to the confidence intervals. It could be different for all transition probabilities, though if <code>length(ci.fun) != number of transitions</code> , only <code>ci.fun[1]</code> will be used. Possible choices are "linear", "log", "log-log" and "cloglog". Default is "linear".

<code>ci.col</code>	Colour of the confidence intervals. Default is <code>col</code> .
<code>ci.lty</code>	Line type of the confidence intervals. Default is 3.
<code>legend</code>	A logical specifying if a legend should be added
<code>legend.pos</code>	A vector giving the legend's position. See legend for further details
<code>curvlab</code>	A character or expression vector to appear in the legend. Default is the name of the transitions
<code>legend.bty</code>	Box type for the legend
<code>...</code>	Further arguments for <code>plot</code>

Value

No value returned

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

See Also

[plot.default](#), [legend](#), [etm](#)

Examples

```
data(sir.cont)

# Modification for patients entering and leaving a state
# at the same date
sir.cont <- sir.cont[order(sir.cont$id, sir.cont$time), ]
for (i in 2:nrow(sir.cont)) {
  if (sir.cont$id[i]==sir.cont$id[i-1]) {
    if (sir.cont$time[i]==sir.cont$time[i-1]) {
      sir.cont$time[i-1] <- sir.cont$time[i-1] - 0.5
    }
  }
}

tra <- matrix(ncol=3,nrow=3,FALSE)
tra[1, 2:3] <- TRUE
tra[2, c(1, 3)] <- TRUE

my.etm <- etm(sir.cont,c("0","1","2"),tra,"cens", s = 0)

plot(my.etm, tr.choice = c("0 0"))
```

plot.etmCIF

*Plot cumulative incidence functions***Description**

Plot function for etmCIF objects. The function plots cumulative incidence curves, possibly with pointwise confidence intervals.

Usage

```
## S3 method for class 'etmCIF'
plot(x, which.cif, xlim, ylim,
     ylab = "Cumulative Incidence", xlab = "Time", col = 1, lty, lwd = 1,
     ci.type = c("none", "bars", "pointwise"), ci.fun = "cloglog",
     ci.col = col, ci.lty = 3, legend = TRUE, legend.pos, curvlab,
     legend.bty = "n", pos.ci = 27, ci.lwd = 3, ...)
```

Arguments

x	A etmCIF object
which.cif	A numeric vector indicating which CIFs should be plotted. When missing, only the CIF of interest is plotted (determined through the failcode argument in etmCIF .)
xlim	x-axis limits for the plot. By default, c(0, max(time))
ylim	y-axis limits. Default is c(0, 1)
ylab	Label for y-axis. Default is "Cumulative Incidence"
xlab	Label for x-axis. Default is "Time"
col	Vector describing colours used for the CIF curves. Default is black
lty	Vector of line type
lwd	Thickness of the lines
ci.type	One of c("none", "bars", "pointwise"). none plots no confidence interval, bars plots the confidence intervals in the form of a segment for one time point, and pointwise draws pointwise confidence intervals for the whole follow-up period.
ci.fun	Transformation used for the confidence intervals. Default is "cloglog", and is a better choice for cumulative incidences. Other choices are "log" and "log-log"
ci.col	Colour for the pointwise confidence interval curves. Default is same as the CIF curves
ci.lty	Line type for the confidence intervals. Default is 3
legend	Logical. Whether to draw a legend. Default is TRUE
legend.pos	A vector giving the legend's position. See legend for further details
curvlab	A character or expression vector to appear in the legend. Default is CIF + event label

legend.bty	Box type for the legend. Default is none ("n")
pos.ci	If ci.type = "bars", vector of integers indicating at which time point to put the confidence interval bars. Default is 27
ci.lwd	Thickness of the confidence interval segment (for ci.type = "bars")
...	Further graphical arguments

Details

The function relies on `plot.etm` and `lines.etm` with more or less the same options. Exception is the drawing of the confidence intervals, for which several displays are possible.

Value

No value returned

Author(s)

Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etmCIF](#), [plot.etm](#), [lines.etm](#)

Examples

```
data(abortion)

cif.ab <- etmCIF(Surv(entry, exit, cause != 0) ~ group, abortion,
                etype = cause, failcode = 3)

cif.ab

plot(cif.ab, ci.type = "bars", pos.ci = 24,
      col = c(1, 2), lty = 1, curvlab = c("Control", "Exposed"))

plot(cif.ab, which = c(1, 2))
```

print.clos.etm

Print function for 'clos.etm' objects

Description

Print method for object of class `clos.etm`

Usage

```
## S3 method for class 'clos.etm'
print(x, ...)
```

Arguments

x	An object of class <code>clos.etm</code>
...	Further arguments

Value

No value returned

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

See Also

[clos](#)

print.etm

Print method for object of class 'etm'

Description

Print method for objects of class `etm`.

Usage

```
## S3 method for class 'etm'
print(x, covariance = TRUE, whole = TRUE, ...)
```

Arguments

x	An object of class <code>etm</code> .
covariance	Whether print the covariance matrix. Default is <code>TRUE</code>
whole	Whether to plot the entire covariance matrix. If set to <code>FALSE</code> , rows and columns containing only 0 will be removed for printing.
...	Further arguments for <code>print</code> or <code>summary</code> .

Details

The function prints a matrix giving the possible transitions, along with the estimates of $P(s, t)$ and $cov(P(s, t))$.

Value

No value returned

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etm](#)

print.etmCIF	<i>Print function for cifETM objects</i>
--------------	--

Description

Print method for cifETM objects

Usage

```
## S3 method for class 'etmCIF'  
print(x, ...)
```

Arguments

x	An object of class etmCIF
...	Further arguments

Value

No value returned

Author(s)

Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etmCIF](#)

`sir.cont`*Ventilation status in intensive care unit patients*

Description

Time-dependent ventilation status for intensive care unit (ICU) patients, a random sample from the SIR-3 study.

Usage

```
data(sir.cont)
```

Format

A data frame with 1141 rows and 6 columns:

id: Randomly generated patient id

from: State from which a transition occurs

to: State to which a transition occurs

time: Time when a transition occurs

age: Age at inclusion

sex: Sex. F for female and M for male

The possible states are:

0: No ventilation

1: Ventilation

2: End of stay

And cens stands for censored observations.

Details

This data frame consists in a random sample of the SIR-3 cohort data. It focuses on the effect of ventilation on the length of stay (combined endpoint discharge/death). Ventilation status is considered as a transient state in an illness-death model.

The data frame is directly formatted to be used with the `etm` function, i.e. it is transition-oriented with one row per transition.

References

Beyersmann, J., Gastmeier, P., Grundmann, H., Baerwolff, S., Geffers, C., Behnke, M., Rueden, H., and Schumacher, M. Use of multistate models to assess prolongation of intensive care unit stay due to nosocomial infection. *Infection Control and Hospital Epidemiology*, 27:493-499, 2006.

Examples

```
data(sir.cont)
```

summary.etm

*Summary methods for an 'etm' object***Description**

Summary method for objects of class etm

Usage

```
## S3 method for class 'etm'
summary(object, all = FALSE,
        ci.fun = "linear", level = 0.95, ...)
## S3 method for class 'summary.etm'
print(x, ...)
```

Arguments

object	An object of class etm.
all	If set to TRUE, a data.frame will be computed for all transitions that are not 0 in the empirical transition matrix.
ci.fun	A character vector specifying the transformation to be applied to the pointwise confidence intervals. It could be different for each transition probability, though if <code>length(ci.fun) != number of transitions</code> , only <code>ci.fun[1]</code> will be used. The function displays the transition probabilities in the following order: first the direct transitions in alphabetical order, e.g., 0 to 1, 0 to 2, 1 to 2, ..., then the state occupation probabilities in alphabetical order, e.g., 0 to 0, 1 to 1, ... The possible transformations are "linear", "log", "log-log" and "cloglog". Default is "linear".
level	Level of the two-sided confidence intervals. Default is 0.95.
x	A summary.cpf object
...	Further arguments

Value

A list of data.frames giving the transition probability and stage occupation probability estimates. List items are named after the possible transition.

P	Transition probability estimates
var	Variance estimates
lower	Lower confidence limit
upper	Upper confidence limit
time	Transition times
n.risk	Number of individuals at risk of experiencing a transition just before time t
n.event	Number of events at time t

Author(s)

Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etm](#)

summary.etmCIF

Summary function for cifETM

Description

Summary function for objects of class cifETM

Usage

```
## S3 method for class 'etmCIF'
summary(object, ci.fun = "cloglog",
        level = 0.95, ...)
## S3 method for class 'summary.etmCIF'
print(x, ...)
```

Arguments

object	An object of class etmCIF
ci.fun	Transformation applied to the pointwise confidence intervals. On of "linear", "log", "log-log", "cloglog". Default is "cloglog".
level	Level of the confidence intervals. Default is 0.95.
x	An object of class cifETM.
...	Further arguments

Value

A data.frame per covariate level and competing event

P	Transition probability estimates
var	Variance estimates
lower	Lower confidence limit
upper	Upper confidence limit
time	Transition times
n.risk	Number of individuals at risk of experiencing a transition just before time t
n.event	Number of events at time t

Author(s)

Arthur Allignol <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etmCIF](#)

trprob.etm

Function to extract transition probabilities and (co)variance

Description

The trprob method is used to extract transition probabilities, while trcov is used to obtain the (co)variance.

Usage

```
## S3 method for class 'etm'  
trprob(x, tr.choice, timepoints, ...)  
## S3 method for class 'etm'  
trcov(x, tr.choice, timepoints, ...)
```

Arguments

x	An object of class etm.
tr.choice	A character vector of the form "from to" describing for which transition one wishes to obtain the transition probabilities or covariance estimates. For trprob, tr.choice must be of length 1, while it can be of length 2 for trcov.
timepoints	Time points at which one want the estimates. When missing, estimates are obtained for all event times.
...	Further arguments.

Value

A vector containing the transition probabilities or covariance estimates either at the time specified in timepoints or at all transition times.

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etm](#)

Examples

```

data(sir.cont)

# Modification for patients entering and leaving a state
# at the same date
# Change on ventilation status is considered
# to happen before end of hospital stay
sir.cont <- sir.cont[order(sir.cont$id, sir.cont$time), ]
for (i in 2:nrow(sir.cont)) {
  if (sir.cont$id[i]==sir.cont$id[i-1]) {
    if (sir.cont$time[i]==sir.cont$time[i-1]) {
      sir.cont$time[i-1] <- sir.cont$time[i-1] - 0.5
    }
  }
}

### Computation of the transition probabilities
# Possible transitions.
tra <- matrix(ncol=3,nrow=3,FALSE)
tra[1, 2:3] <- TRUE
tra[2, c(1, 3)] <- TRUE

# etm
fit.etm <- etm(sir.cont, c("0", "1", "2"), tra, "cens", 0)

## extract P_01(0, t) and variance
p01 <- trprob(fit.etm, "0 1")
var.p01 <- trcov(fit.etm, "0 1")

## covariance between P_00 and P_01
cov.00.01 <- trcov(fit.etm, c("0 0", "0 1"))

## P_01 at some time points
trprob(fit.etm, "0 1", c(0, 15, 50, 100))

```

xyplot.etm

*xyplot method for object of class 'etm'***Description**

xyplot function for objects of class etm. Estimates of the transition probabilities are plotted as a function of time for all the transitions specified by the user.

Usage

```

## S3 method for class 'etm'
xyplot(x, data = NULL, tr.choice, col = c(1, 1, 1),
       lty = c(1, 3, 3), xlab = "Time",
       ylab = "Transition probability",
       conf.int = TRUE, ci.fun = "linear", level = 0.95, ...)

```

Arguments

<code>x</code>	An object of class <code>etm</code> .
<code>data</code>	<i>Useless.</i>
<code>tr.choice</code>	A character vector of the form <code>c("from to", "from to", ...)</code> specifying the transition probabilities to be plotted. By default, all the direct transition probabilities are displayed.
<code>col</code>	Vector of colours for the curves.
<code>lty</code>	Vector of line types.
<code>xlab</code>	x-axis label. Default is "Time".
<code>ylab</code>	y-axis label. Default is "Estimated transition probability".
<code>conf.int</code>	Logical. Whether to draw pointwise confidence intervals. Default is TRUE.
<code>ci.fun</code>	A character vector specifying the transformation to be applied to the pointwise confidence intervals. It could be different for each transition probability, though if <code>length(ci.fun) != length(tr.choice)</code> , only <code>ci.fun[1]</code> will be used. The possible transformations are "linear", "log", "log-log" and "cloglog". Default is "linear".
<code>level</code>	Level of the two-sided confidence intervals. Default is 0.95.
<code>...</code>	Further arguments for <code>xyplot</code> .

Value

An object of class `trellis`.

Author(s)

Arthur Allignol, <arthur.allignol@fdm.uni-freiburg.de>

See Also

[etm](#), [xyplot](#)

Index

- *Topic **datagen**
 - etmprep, 10
 - *Topic **datasets**
 - abortion, 2
 - fourD, 12
 - sir.cont, 21
 - *Topic **hplot**
 - lines.etm, 13
 - plot.clos.etm, 14
 - plot.etm, 15
 - plot.etmCIF, 17
 - xyplot.etm, 25
 - *Topic **manip**
 - etmprep, 10
 - *Topic **methods**
 - summary.etm, 22
 - trprob.etm, 24
 - *Topic **method**
 - summary.etmCIF, 23
 - *Topic **print**
 - print.clos.etm, 18
 - print.etm, 19
 - print.etmCIF, 20
 - summary.etm, 22
 - summary.etmCIF, 23
 - *Topic **survival**
 - clos, 3
 - etm, 5
 - etmCIF, 8
 - lines.etm, 13
 - plot.etmCIF, 17
 - print.etmCIF, 20
 - summary.etmCIF, 23
- abortion, 2
- clos, 3, 3, 4, 15, 19
- etm, 3, 4, 5, 9, 11, 13, 16, 20, 23, 24, 26
- etmCIF, 8, 17, 18, 20, 24
- etmprep, 10
- fourD, 12
- legend, 14, 16, 17
- lines.etm, 13, 18
- plot.clos.etm, 14
- plot.default, 16
- plot.etm, 13, 15, 18
- plot.etmCIF, 9, 17
- print.clos.etm, 18
- print.etm, 7, 19
- print.etmCIF, 9, 20
- print.summary.etm (summary.etm), 22
- print.summary.etmCIF (summary.etmCIF), 23
- sir.cont, 7, 21
- summary.etm, 7, 22
- summary.etmCIF, 9, 23
- trcov (trprob.etm), 24
- trprob (trprob.etm), 24
- trprob.etm, 24
- xyplot, 26
- xyplot.etm, 7, 13, 25