

Package ‘fmsb’

April 27, 2012

Version 0.3.4

Date 2012/4/27

Title Functions for medical statistics book with some demographic data

Author Minato Nakazawa <minato-nakazawa@umin.net>

Maintainer Minato Nakazawa <minato-nakazawa@umin.net>

Depends R (>= 2.2.0)

Description Several utility functions for the book entitled ‘‘Practices of Medical and Health Data Analysis using R’’ (Pearson Education Japan, 2007) with Japanese demographic data and some demographic analysis related functions.

License GPL (>= 2)

URL <http://minato.sip21c.org/msb/>

Repository CRAN

Date/Publication 2012-04-27 06:17:25

R topics documented:

CronbachAlpha	2
CT	3
Denny	4
geary.test	5
GompertzMakeham	6
gstem	7
Hadwiger	8
JASM	9
Jfert	10
Jlife	12
Jpop	13
Jpopl	15
Jvital	17

Kappa.test	19
lifetable	20
mhchart	22
NagelkerkeR2	23
oddsratio	23
pairwise.fisher.test	24
percentile	25
pvalueplot	26
radarchart	27
riskratio	28
roc	29
S60MPJ	30
Siler	31
SIQR	32
truemedian	33
VIF	34
Index	35

CronbachAlpha	<i>Calculate Cronbach's alpha coefficient.</i>
---------------	--

Description

Calculate Cronbach's alpha coefficient from a matrix or data.frame with more than 2 columns.

Usage

```
CronbachAlpha(X)
```

Arguments

X A matrix or data.frame with more than 2 columns.

Value

Single numeric value of Cronbach's alpha.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

References

Bland JM, Altman DG (1997) Statistics notes: Cronbach's alpha. *BMJ*, 314: 572.

Examples

```

QUEST <- data.frame(
  Q1=c(1,5,2,3,4,2,3,4,3,2),
  Q2=c(2,4,1,2,4,1,2,5,2,1),
  Q3=c(2,5,1,3,3,2,2,4,2,2))
CronbachAlpha(QUEST)

```

CT

*Coale and Trussell's model marital fertility and its fitting***Description**

Implementing Coale and Trussell's model of age-specific marital fertility rates and fitting the model to actual ASMFR.

Usage

```

CT(M=1, m=0)
fitCT(initialpar=c(1.0, 1.0), data, Method="Nelder-Mead", ...)

```

Arguments

M	The parameter M of the CT model, the scale (peak height) parameter of fertility
m	The parameter m of the CT model, the strength of downward discordance from natural fertility with aging
initialpar	Initial value for the parameters to be estimated. If not given, c(1.0, 1.0) is used.
data	Actual vector of ASMFR (which must be given for from age 12 to age 49 for each age) to be used to obtain the best-fit parameters of the CT's model.
Method	The method to be used in optim() function. Default is "Nelder-Mead".
...	Other options to be passed to optim().

Value

CT() returns model ASMFR for ages from 12 to 49. fitCT() returns the numeric vector of fitted parameters M and m, RMSE for those values, and the flag of convergence.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

See Also

[Jfert](#)

Examples

```

ASMFR <- c(0,0,0,Jfert$ASMFR2000[1:35]) # Jfert gives ASMFR for ages 15:54, so that it should be rearranged to 12:4
res <- fitCT(ASMFR)
FLAG <- res[4]
while (FLAG>0) {
  res <- fitCT(res[1:2],ASMFR)
  FLAG <- res[4]
}
print(res)

```

Denny

Denny's model mortality for lx and its fitting

Description

Implementing Denny's model mortality function of lx and fitting the model to actual lx of given lifetable.

Usage

```

Denny(a, b, c, t)
fitDenny(initialpar=rep(0.1, 3), data, mode=3, Method="Nelder-Mead", ...)

```

Arguments

a	The parameter a of the Denny model, $l(t)=1/(1+a*(t/(105-t))^3+b*\sqrt{\exp(t/(105-t))-1}+c*(1-\exp(-2*t)))$.
b	The parameter b of the Denny model, $l(t)=1/(1+a*(t/(105-t))^3+b*\sqrt{\exp(t/(105-t))-1}+c*(1-\exp(-2*t)))$.
c	The parameter c of the Denny model, $l(t)=1/(1+a*(t/(105-t))^3+b*\sqrt{\exp(t/(105-t))-1}+c*(1-\exp(-2*t)))$.
t	Age (vector OK) in years. The t must be less than 105, otherwise the value by Denny() become 0.
initialpar	Initial value for the parameters to be estimated. If not given, rep(0.1, 3) is used.
data	Actual vector of qx in the lifetable to be used to obtain the best-fit parameters of the Denny's model. If the ages for qx are equal or elder than 105 years old, those will be ignored in fitting.
mode	Which of lifetable functions should be used to calculate the RMSE: 1 qx, 2 dx, otherwise lx. Default is 3.
Method	The method to be used in optim() function. Default is "Nelder-Mead".
...	Other options to be passed to optim().

Value

Denny() returns model lx for the same length with t. fitDenny() returns the numeric vector of fitted parameters a, b, and c, RMSE for those values, and the flag of convergence.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

See Also

[Jlife](#)

Examples

```
res <- fitDenny(,qxtolx(Jlife$qx2005M))
FLAG <- res[5]
while (FLAG>0) {
  res <- fitDenny(res[1:3],qxtolx(Jlife$qx2005M))
  FLAG <- res[5]
}
print(res)
```

geary.test

Geary's test for normality about kurtosis.

Description

Geary's test for normality. Null hypothesis is that the data obeys to normal distribution.

Usage

```
geary.test(X)
```

Arguments

X A numeric vector.

Value

statistic Geary's test statistic G
p.value The significant probability of the null-hypothesis testing.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
geary.test(rnorm(100))
geary.test(20:50)
```

GompertzMakeham

Gompertz-Makeham's model mortality for $u(x)$ and its fitting

Description

Implementing Gompertz-Makeham's model mortality function of the force of mortality $u(x)$ with conversion into q_x and fitting the model to actual q_x of given lifetable.

Usage

```
GompertzMakeham(A, B, C, t)
fitGM(initialpar=c(0.01, 0.0003, 0.07), data, mode=1, Method="Nelder-Mead", ...)
```

Arguments

A	The parameter A of the Gompertz-Makeham model $u(t)=A*\exp B*t+C$.
B	The parameter B of the Gompertz-Makeham model $u(t)=A*\exp B*t+C$.
C	The parameter C of the Gompertz-Makeham model $u(t)=A*\exp B*t+C$.
t	Age (vector OK) in years
initialpar	Initial value for the parameters to be estimated. If not given, c(0.01, 0.0003, 0.07) is used.
data	Actual vector of q_x in the lifetable to be used to obtain the best-fit parameters of the Gompertz-Makeham model.
mode	Which of lifetable functions should be used to calculate the RMSE, which is to be minimized in <code>optim()</code> function: 1 q_x , 2 dx , otherwise lx . Default is 1.
Method	The method to be used in <code>optim()</code> function. Default is "Nelder-Mead".
...	Other options to be passed to <code>optim()</code> .

Value

`GompertzMakeham()` returns model q_x for the same length with t , where $u(x)$ is internally converted into q_x . `fitGM()` returns the numeric vector of fitted parameters of A, B and C, RMSE for those values, and the flag of convergence.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

See Also

[Jlife](#)

Examples

```
res <- fitGM(,Jlife$qx2005M)
FLAG <- res[5]
while (FLAG>0) {
  res <- fitGM(res[1:3],Jlife$qx2005M)
  FLAG <- res[5]
}
print(res)
```

gstem

Draw the stem and leaf plot in a graphic device.

Description

Capture the output of stem() function and plot them into graphic devices. However, the result of setting scale parameter as 2 may be controversial.

Usage

```
gstem(X, scale)
```

Arguments

X	A numeric vector.
scale	Parameter to control plot length of graph. Default is 1.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
x <- rnorm(100,10,1)
stem(x)
stem(x,2)
layout(t(1:2))
gstem(x)
gstem(x,2)
```

 Hadwiger

Hadwiger's model fertility and its fitting

Description

Implementing Hadwiger's model of age-specific fertility rates and fitting the model to actual ASFR.

Usage

```
Hadwiger(a=3.4, b=2.5, c=22.2)
fitHad(initialpar=c(3.4, 2.5, 22.2), data, Method="Nelder-Mead", ...)
```

Arguments

a	The parameter a of the Hadwiger model, $ASFR(x) = a*b/c*(c/x)^{1.5}*exp(-b^2*(c/x+x/c-2))$ for age x from 15 to 54.
b	The parameter b of the Hadwiger model, $ASFR(x) = a*b/c*(c/x)^{1.5}*exp(-b^2*(c/x+x/c-2))$ for age x from 15 to 54.
c	The parameter c of the Hadwiger model, $ASFR(x) = a*b/c*(c/x)^{1.5}*exp(-b^2*(c/x+x/c-2))$ for age x from 15 to 54.
initialpar	Initial value for the parameters to be estimated. If not given, c(3.4, 2.5, 22.2) is used.
data	Actual vector of ASFR (which must be given for from ages from 15 to 54 for each age) to be used to obtain the best-fit parameters of the Hadwiger's model.
Method	The method to be used in optim() function. Default is "Nelder-Mead".
...	Other options to be passed to optim().

Value

Hadwiger() returns model ASFR for ages from 15 to 54. fitHad() returns the numeric vector of fitted parameters a, b and c, RMSE for those values, and the flag of convergence.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

See Also

[Jfert](#)

Examples

```

res <- fitHad(,Jfert$ASFR2000)
FLAG <- res[5]
while (FLAG>0) {
  res <- fitHad(res[1:3],Jfert$ASFR2000)
  FLAG <- res[5]
}
print(res)

```

JASM

Japanese mortality data

Description

The data gives the sex and age-class (by five) specific numbers of death in Showa 60 (S60 = 1985), Heisei 2 (H02 = 1990), Heisei 7 (H07 = 1995), Heisei 12 (H12 = 2000), Heisei 17 (H17 = 2005) and Heisei 22 (H22 = 2010), and corresponding populations.

Usage

JASM

Format

A data frame with 18 observations on 26 variables.

[, 1]	AGECLASS	Factor w/18 levels	Age class (years old)
[, 2]	S60MODEL	numeric	Model population in 1985
[, 3]	S60M	numeric	Number of males' death by age classes in 1985
[, 4]	H02M	numeric	Number of males' death by age classes in 1990
[, 5]	H07M	numeric	Number of males' death by age classes in 1995
[, 6]	H12M	numeric	Number of males' death by age classes in 2000
[, 7]	H17M	numeric	Number of males' death by age classes in 2005
[, 8]	H22M	numeric	Number of males' death by age classes in 2010
[, 9]	S60F	numeric	Number of females' death by age classes in 1985
[, 10]	H02F	numeric	Number of females' death by age classes in 1990
[, 11]	H07F	numeric	Number of females' death by age classes in 1995
[, 12]	H12F	numeric	Number of females' death by age classes in 2000
[, 13]	H17F	numeric	Number of females' death by age classes in 2005
[, 14]	H22F	numeric	Number of females' death by age classes in 2010
[, 15]	S60MP	numeric	Number of males' population by age classes in 1985
[, 16]	H02MP	numeric	Number of males' population by age classes in 1990
[, 17]	H07MP	numeric	Number of males' population by age classes in 1995
[, 18]	H12MP	numeric	Number of males' population by age classes in 2000
[, 19]	H17MP	numeric	Number of males' population by age classes in 2005
[, 20]	H22MP	numeric	Number of males' population by age classes in 2010
[, 21]	S60FP	numeric	Number of females' population by age classes in 1985

[, 22]	H02FP	numeric	Number of females' population by age classes in 1990
[, 23]	H07FP	numeric	Number of females' population by age classes in 1995
[, 24]	H12FP	numeric	Number of females' population by age classes in 2000
[, 25]	H17FP	numeric	Number of females' population by age classes in 2005
[, 26]	H22FP	numeric	Number of females' population by age classes in 2010

Details

Japanese mortality data by sex and age-class (by five) given as national official vital statistics from 1985 to 2010, every 5 years.

- AGECLASS: Labels for age classes. [0-4] to [85-].
- S60MODEL: Age class specific model population of Japan in 1985.
- S60M-H22M: Age class specific number of death of males in 1985-2010.
- S60F-H22F: Age class specific number of death of females in 1985-2010.
- S60MP-H22MP: Age class specific number of males' population in 1985-2010.
- S60FP-H22FP: Age class specific number of females' population in 1985-2010.

Source

<http://www.stat.go.jp/data/nenkan/02.htm> <http://www.e-stat.go.jp/SG1/estat/List.do?bid=000001025191&cycode=0>

References

Ministry of Health, Labor and Welfare of Japan: Vital Statistics.

Jfert *Age-specific fertility rates and age-specific marital fertility rates in Japan.*

Description

Age-specific fertility and marital fertility rates for aged 15-54 Japanese women in Japan, from 1950 to 2010, every five years.

Usage

Jfert

Format

A data frame with 40 observations on 27 variables.

[, 1]	Age	integer	Ages of women
[, 2]	ASFR1950	numeric	Age-specific fertility rates of Japanese women in 1950.
[, 3]	ASFR1955	numeric	Age-specific fertility rates of Japanese women in 1955.
[, 4]	ASFR1960	numeric	Age-specific fertility rates of Japanese women in 1960.
[, 5]	ASFR1965	numeric	Age-specific fertility rates of Japanese women in 1965.
[, 6]	ASFR1970	numeric	Age-specific fertility rates of Japanese women in 1970.
[, 7]	ASFR1975	numeric	Age-specific fertility rates of Japanese women in 1975.
[, 8]	ASFR1980	numeric	Age-specific fertility rates of Japanese women in 1980.
[, 9]	ASFR1985	numeric	Age-specific fertility rates of Japanese women in 1985.
[, 10]	ASFR1990	numeric	Age-specific fertility rates of Japanese women in 1990.
[, 11]	ASFR1995	numeric	Age-specific fertility rates of Japanese women in 1995.
[, 12]	ASFR2000	numeric	Age-specific fertility rates of Japanese women in 2000.
[, 13]	ASFR2005	numeric	Age-specific fertility rates of Japanese women in 2005.
[, 14]	ASFR2010	numeric	Age-specific fertility rates of Japanese women in 2010.
[, 15]	ASMFR1950	numeric	Age-specific marital fertility rates of Japanese married women in 1950.
[, 16]	ASMFR1955	numeric	Age-specific marital fertility rates of Japanese married women in 1955.
[, 17]	ASMFR1960	numeric	Age-specific marital fertility rates of Japanese married women in 1960.
[, 18]	ASMFR1965	numeric	Age-specific marital fertility rates of Japanese married women in 1965.
[, 19]	ASMFR1970	numeric	Age-specific marital fertility rates of Japanese married women in 1970.
[, 20]	ASMFR1975	numeric	Age-specific marital fertility rates of Japanese married women in 1975.
[, 21]	ASMFR1980	numeric	Age-specific marital fertility rates of Japanese married women in 1980.
[, 22]	ASMFR1985	numeric	Age-specific marital fertility rates of Japanese married women in 1985.
[, 23]	ASMFR1990	numeric	Age-specific marital fertility rates of Japanese married women in 1990.
[, 24]	ASMFR1995	numeric	Age-specific marital fertility rates of Japanese married women in 1995.
[, 25]	ASMFR2000	numeric	Age-specific marital fertility rates of Japanese married women in 2000.
[, 26]	ASMFR2005	numeric	Age-specific marital fertility rates of Japanese married women in 2005.
[, 27]	ASMFR2010	numeric	Age-specific marital fertility rates of Japanese married women in 2010.

Details

The calculations were the numbers of live births divided by the numbers of women for ASFR (15-54), and the numbers of legitimate live births divided by the numbers of married women for ASMFR (15-54). Data sources are all official publication as vital statistics and national population census, so that the data are given with 5 years intervals.

- Age: Ages of women, from 15 to 54.
- ASFR1950-ASFR2010: Age-specific fertility rates for all women aged 15-54 for 1950-2010, every 5 years.
- ASMFR1950-ASMFR2010: Age-specific marital fertility rates for married women aged 15-54 for 1950-2010, every 5 years.

Source

<http://www.stat.go.jp/english/data/chouki/02.htm> <http://www.e-stat.go.jp/SG1/estat/List.do?bid=000001025191&cycode=0>

References

Ministry of Health, Labor and Welfare of Japan: Vital Statistics. / Ministry of Internal Affairs and Communications, Statistics Bureau: Population Census.

Jlife *Completed lifetables in Japan.*

Description

The qx column of the completed lifetables in Japan, from "1891-1898" to "2005", mostly every 5 years.

Usage

Jlife

Format

A data frame with 117 observations (NAs are filled for the ages with no survivors) on 39 variables.

[, 1]	Age	integer	Ages of women
[, 2]	qx1895M	numeric	qx of completed lifetable functions of Japanese men in 1891-1898.
[, 3]	qx1895F	numeric	qx of completed lifetable functions of Japanese women in 1891-1898.
[, 4]	qx1901M	numeric	qx of completed lifetable functions of Japanese men in 1899-1903.
[, 5]	qx1901F	numeric	qx of completed lifetable functions of Japanese women in 1899-1903.
[, 6]	qx1911M	numeric	qx of completed lifetable functions of Japanese men in 1909-1913.
[, 7]	qx1911F	numeric	qx of completed lifetable functions of Japanese women in 1909-1913.
[, 8]	qx1923M	numeric	qx of completed lifetable functions of Japanese men in 1921-1925.
[, 9]	qx1923F	numeric	qx of completed lifetable functions of Japanese women in 1921-1925.
[,10]	qx1928M	numeric	qx of completed lifetable functions of Japanese men in 1926-1930.
[,11]	qx1928F	numeric	qx of completed lifetable functions of Japanese women in 1926-1930.
[,12]	qx1935M	numeric	qx of completed lifetable functions of Japanese men in 1935-1936.
[,13]	qx1935F	numeric	qx of completed lifetable functions of Japanese women in 1935-1936.
[,14]	qx1947M	numeric	qx of completed lifetable functions of Japanese men in 1947.
[,15]	qx1947F	numeric	qx of completed lifetable functions of Japanese women in 1947.
[,16]	qx1951M	numeric	qx of completed lifetable functions of Japanese men in 1950-1952.
[,17]	qx1951F	numeric	qx of completed lifetable functions of Japanese women in 1950-1952.
[,18]	qx1955M	numeric	qx of completed lifetable functions of Japanese men in 1955.
[,19]	qx1955F	numeric	qx of completed lifetable functions of Japanese women in 1955.
[,20]	qx1960M	numeric	qx of completed lifetable functions of Japanese men in 1960.
[,21]	qx1960F	numeric	qx of completed lifetable functions of Japanese women in 1960.
[,22]	qx1965M	numeric	qx of completed lifetable functions of Japanese men in 1965.
[,23]	qx1965F	numeric	qx of completed lifetable functions of Japanese women in 1965.
[,24]	qx1970M	numeric	qx of completed lifetable functions of Japanese men in 1970.
[,25]	qx1970F	numeric	qx of completed lifetable functions of Japanese women in 1970.
[,26]	qx1975M	numeric	qx of completed lifetable functions of Japanese men in 1975.
[,27]	qx1975F	numeric	qx of completed lifetable functions of Japanese women in 1975.

[, 28]	qx1980M	numeric	qx of completed lifetable functions of Japanese men in 1980.
[, 29]	qx1980F	numeric	qx of completed lifetable functions of Japanese women in 1980.
[, 30]	qx1985M	numeric	qx of completed lifetable functions of Japanese men in 1985.
[, 31]	qx1985F	numeric	qx of completed lifetable functions of Japanese women in 1985.
[, 32]	qx1990M	numeric	qx of completed lifetable functions of Japanese men in 1990.
[, 33]	qx1990F	numeric	qx of completed lifetable functions of Japanese women in 1990.
[, 34]	qx1995M	numeric	qx of completed lifetable functions of Japanese men in 1995.
[, 35]	qx1995F	numeric	qx of completed lifetable functions of Japanese women in 1995.
[, 36]	qx2000M	numeric	qx of completed lifetable functions of Japanese men in 2000.
[, 37]	qx2000F	numeric	qx of completed lifetable functions of Japanese women in 2000.
[, 38]	qx2005M	numeric	qx of completed lifetable functions of Japanese men in 2005.
[, 39]	qx2005F	numeric	qx of completed lifetable functions of Japanese women in 2005.

Details

qx columns were cited from the completed life tables in Japan for the 1st to 20th one (7th one was not made, so that it is missing).

- Age: Ages from 0 to 116.
- qx1895M-qx2005M: qx of 1st to 20th completed lifetables for Japanese men.
- qx1895F-qx2005F: qx of 1st to 20th completed lifetables for Japanese women.

Source

<http://www.stat.go.jp/english/data/chouki/02.htm> <http://www.stat.go.jp/data/chouki/zuhyou/02-35.xls> <http://www.mhlw.go.jp/toukei/saikin/hw/life/20th/index.html>

References

Ministry of Health, Labor and Welfare of Japan: Completed lifetables. / Ministry of Internal Affairs and Communications, Statistics Bureau: Historical Statistics of Japan.

Jpop

Japanese population data

Description

The data gives the sex and age specific population for the all census results in Japan.

Usage

Jpop

Format

A data frame with 86 observations on 53 variables.

[, 1]	Age	Factor w/86 levels	Ages (years old, combined for 85+)
[, 2]	M1888	numeric	Age specific population of males in 1888
[, 3]	F1888	numeric	Age specific population of females in 1888
[, 4]	M1893	numeric	Age specific population of males in 1893
[, 5]	F1893	numeric	Age specific population of females in 1893
[, 6]	M1898	numeric	Age specific population of males in 1898
[, 7]	F1898	numeric	Age specific population of females in 1898
[, 8]	M1903	numeric	Age specific population of males in 1903
[, 9]	F1903	numeric	Age specific population of females in 1903
[, 10]	M1908	numeric	Age specific population of males in 1908
[, 11]	F1908	numeric	Age specific population of females in 1908
[, 12]	M1913	numeric	Age specific population of males in 1913
[, 13]	F1913	numeric	Age specific population of females in 1913
[, 14]	M1918	numeric	Age specific population of males in 1918
[, 15]	F1918	numeric	Age specific population of females in 1918
[, 16]	M1920	numeric	Age specific population of males in 1920
[, 17]	F1920	numeric	Age specific population of females in 1920
[, 18]	M1925	numeric	Age specific population of males in 1925
[, 19]	F1925	numeric	Age specific population of females in 1925
[, 20]	M1930	numeric	Age specific population of males in 1930
[, 21]	F1930	numeric	Age specific population of females in 1930
[, 22]	M1935	numeric	Age specific population of males in 1935
[, 23]	F1935	numeric	Age specific population of females in 1935
[, 24]	M1940	numeric	Age specific population of males in 1940
[, 25]	F1940	numeric	Age specific population of females in 1940
[, 26]	M1947	numeric	Age specific population of males in 1947
[, 27]	F1947	numeric	Age specific population of females in 1947
[, 28]	M1950	numeric	Age specific population of males in 1950
[, 29]	F1950	numeric	Age specific population of females in 1950
[, 30]	M1955	numeric	Age specific population of males in 1955
[, 31]	F1955	numeric	Age specific population of females in 1955
[, 32]	M1960	numeric	Age specific population of males in 1960
[, 33]	F1960	numeric	Age specific population of females in 1960
[, 34]	M1965	numeric	Age specific population of males in 1965
[, 35]	F1965	numeric	Age specific population of females in 1965
[, 36]	M1970	numeric	Age specific population of males in 1970
[, 37]	F1970	numeric	Age specific population of females in 1970
[, 38]	M1975	numeric	Age specific population of males in 1975
[, 39]	F1975	numeric	Age specific population of females in 1975
[, 40]	M1980	numeric	Age specific population of males in 1980
[, 41]	F1980	numeric	Age specific population of females in 1980
[, 42]	M1985	numeric	Age specific population of males in 1985
[, 43]	F1985	numeric	Age specific population of females in 1985
[, 44]	M1990	numeric	Age specific population of males in 1990
[, 45]	F1990	numeric	Age specific population of females in 1990
[, 46]	M1995	numeric	Age specific population of males in 1995
[, 47]	F1995	numeric	Age specific population of females in 1995
[, 48]	M2000	numeric	Age specific population of males in 2000

[, 49]	F2000	numeric	Age specific population of females in 2000
[, 50]	M2005	numeric	Age specific population of males in 2005
[, 51]	F2005	numeric	Age specific population of females in 2005
[, 52]	M2010	numeric	Age specific population of males in 2010
[, 53]	F2010	numeric	Age specific population of females in 2010

Details

Japanese population data by sex and age given as national official census record.

- Age: Ages, combined for 85+.
- M1888-M2010: Age specific number of males' population in 1988-2010.
- F1888-F2010: Age specific number of females' population in 1988-2010.

Source

<http://www.stat.go.jp/english/data/kokusei/index.htm>
<http://www.stat.go.jp/english/data/chouki/02.htm>

References

Statistics Bureau, Ministry of Internal Affairs and Communications: Population Census, 1888-2010.

Jpopl *Japanese population data (unshrunk version)*

Description

The data gives the sex and age specific population for the all census results in Japan.

Usage

Jpopl

Format

A data frame with 111 observations on 59 variables.

[, 1]	Age	Factor w/111 levels	Ages (years old, combined for 110+)
[, 2]	M1888	numeric	Age specific population of males in 1888
[, 3]	F1888	numeric	Age specific population of females in 1888
[, 4]	M1893	numeric	Age specific population of males in 1893
[, 5]	F1893	numeric	Age specific population of females in 1893
[, 6]	M1898	numeric	Age specific population of males in 1898
[, 7]	F1898	numeric	Age specific population of females in 1898

[, 8]	M1903	numeric	Age specific population of males in 1903
[, 9]	F1903	numeric	Age specific population of females in 1903
[, 10]	M1908	numeric	Age specific population of males in 1908
[, 11]	F1908	numeric	Age specific population of females in 1908
[, 12]	M1913	numeric	Age specific population of males in 1913
[, 13]	F1913	numeric	Age specific population of females in 1913
[, 14]	M1918	numeric	Age specific population of males in 1918
[, 15]	F1918	numeric	Age specific population of females in 1918
[, 16]	M1920	numeric	Age specific population of males in 1920
[, 17]	F1920	numeric	Age specific population of females in 1920
[, 18]	M1925	numeric	Age specific population of males in 1925
[, 19]	F1925	numeric	Age specific population of females in 1925
[, 20]	M1930	numeric	Age specific population of males in 1930
[, 21]	F1930	numeric	Age specific population of females in 1930
[, 22]	M1935	numeric	Age specific population of males in 1935
[, 23]	F1935	numeric	Age specific population of females in 1935
[, 24]	M1940	numeric	Age specific population of males in 1940
[, 25]	F1940	numeric	Age specific population of females in 1940
[, 26]	M1947	numeric	Age specific population of males in 1947
[, 27]	F1947	numeric	Age specific population of females in 1947
[, 28]	M1950	numeric	Age specific population of males in 1950
[, 29]	F1950	numeric	Age specific population of females in 1950
[, 30]	M1955	numeric	Age specific population of males in 1955
[, 31]	F1955	numeric	Age specific population of females in 1955
[, 32]	M1960	numeric	Age specific population of males in 1960
[, 33]	F1960	numeric	Age specific population of females in 1960
[, 34]	M1965	numeric	Age specific population of males in 1965
[, 35]	F1965	numeric	Age specific population of females in 1965
[, 36]	M1970	numeric	Age specific population of males in 1970
[, 37]	F1970	numeric	Age specific population of females in 1970
[, 38]	M1975	numeric	Age specific population of males in 1975
[, 39]	F1975	numeric	Age specific population of females in 1975
[, 40]	M1980	numeric	Age specific population of males in 1980
[, 41]	F1980	numeric	Age specific population of females in 1980
[, 42]	M1985	numeric	Age specific population of males in 1985
[, 43]	F1985	numeric	Age specific population of females in 1985
[, 44]	M1990	numeric	Age specific population of males in 1990
[, 45]	F1990	numeric	Age specific population of females in 1990
[, 46]	M1995	numeric	Age specific population of males in 1995
[, 47]	F1995	numeric	Age specific population of females in 1995
[, 48]	M2000	numeric	Age specific population of males in 2000
[, 49]	F2000	numeric	Age specific population of females in 2000
[, 50]	M2000J	numeric	Age specific population of Japanese males in 2000
[, 51]	F2000J	numeric	Age specific population of Japanese females in 2000
[, 52]	M2005	numeric	Age specific population of males in 2005
[, 53]	F2005	numeric	Age specific population of females in 2005
[, 54]	M2005J	numeric	Age specific population of Japanese males in 2005
[, 55]	F2005J	numeric	Age specific population of Japanese females in 2005

[,56]	M2010	numeric	Age specific population of males in 2010
[,57]	F2010	numeric	Age specific population of females in 2010
[,58]	M2010J	numeric	Age specific population of Japanese males in 2010
[,59]	F2010J	numeric	Age specific population of Japanese females in 2010

Details

Japanese population data by sex and age given as national official census record.

- Age: Ages, combined for 110+.
- M1888-M2010: Age specific number of males' population in Japan for 1888-2010.
- F1888-F2010: Age specific number of females' population in Japan for 1888-2010.
- M2000J-M2010J: Age specific number of Japanese males' population in Japan for 2000-2010 by every 5 years.
- F2000J-F2010J: Age specific number of Japanese females' population in Japan for 2000-2010 by every 5 years.

Source

<http://www.stat.go.jp/english/data/kokusei/index.htm> <http://www.stat.go.jp/english/data/chouki/02.htm>

References

Statistics Bureau, Ministry of Internal Affairs and Communications: Population Census, 1888-2010.

Jvital

Longitudinal data of several vital statistics in Japan

Description

The data gives longitudinal data of several vital statistics in Japan. Included indices are crude birth rates, crude death rates, infant mortality rates, and so on.

Usage

Jvital

Format

A data frame with 109 observations on 16 variables.

[, 1]	YEAR	numeric	Year
[, 2]	CBR	numeric	Crude birth rates of Japan
[, 3]	CDR	numeric	Crude death rates of Japan
[, 4]	IMR	numeric	Infant mortality rates of Japan
[, 5]	NMR	numeric	Neonatal mortality rates of Japan
[, 6]	NIR	numeric	Natural increase rates of Japan
[, 7]	SBRPB	numeric	Stillbirth rates of Japan
[, 8]	SARPB	numeric	Spontaneous abortion rates of Japan
[, 9]	ACRPB	numeric	Artificial contraception rates of Japan
[, 10]	PNMPB	numeric	Perinatal mortalities per birth of Japan
[, 11]	MR	numeric	Marriage rates of Japan
[, 12]	DR	numeric	Divorce rates of Japan
[, 13]	TFR	numeric	Total fertility rates of Japan
[, 14]	ASMRM	numeric	Age-standardized mortality rates of males in Japan
[, 15]	ASMRF	numeric	Age-standardized mortality rates of females in Japan
[, 16]	PNMPLB	numeric	Perinatal mortalities per live births of Japan

Details

Longitudinal vital statistics in Japan provided as national official vital statistics every year from 1899 to 2010, except for 1944-1946.

- YEAR: Calendar year.
- CBR: Crude birth rate. Number of all live birth / mid-year population 1000.
- CDR: Crude death rate. Number of death / mid-year population 1000.
- IMR: Infant mortality rate. Number of death at age 0 / 1000 live births.
- NMR: Neonatal mortality rate. Number of death within 4 weeks after birth / 1000 live births.
- NIR: Natural increase rate. CBR-CDR.
- SBRPB: Stillbirth rate per birth. Number of stillbirths / 1000 births.
- SARPB: Spontaneous abortion rate per birth. Number of spontaneous abortions / 1000 births.
- ACRPB: Artificial contraception (= induced abortion) rate per birth. Number of induced abortions / 1000 births.
- PNMPB: Perinatal mortality per birth. [(Number of stillbirths after gestational age 22 weeks) + (Number of early neonatal deaths within a week after birth)] per 1000 births. The denominator is the sum of the number of stillbirths after gestational age 22 weeks and the number of live births. This definition was established in 1995, but PNMPB also includes some values before 1995.
- MR: Marital rate. The number of marriages / mid-year population 1000.
- DR: Divorce rate. The number of divorces / mid-year population 1000.
- TFR: Total fertility rate. The sum of age-specific fertility rates, which is the number of births divided by the number of women's population for each age.

- ASMRM: Age-standardized mortality rate of males, per mid-year population 1000, where the standard population is the model population in 1985.
- ASMRF: Age-standardized mortality rate of females, per mid-year population 1000, where the standard population is the model population in 1985.
- PNMPBLB: Perinatal mortality per live birth. [(Number of stillbirths after gestational age 28 weeks) + (Number of early neonatal deaths within a week after birth)] per 1000 live births. This definition stood until 1994, but PNMPBLB also includes values after 1995, for comparison.

Source

<http://www.stat.go.jp/english/data/chouki/02.htm> <http://www.e-stat.go.jp/SG1/estat/List.do?bid=000001025191&cycode=0>

References

Ministry of Health, Labor and Welfare of Japan: Vital Statistics.

Kappa.test

Calculate Cohen's kappa statistics for agreement

Description

Calculate Cohen's kappa statistics for agreement and its confidence intervals followed by testing null-hypothesis that the extent of agreement is same as random, kappa statistic equals zero.

Usage

```
Kappa.test(x, y=NULL, conf.level=0.95)
```

Arguments

- | | |
|------------|--|
| x | If y is not given, x must be the square matrix that the rows and columns show the ratings of different rater (or repeated measure) and the values indicate the numbers of data having that combination. If y is given, x must be the result of ratings by the first rater (or first time measurement). |
| y | If given, y must be the result of ratings by the second rater (or second time measurement). As default, it is not given. |
| conf.level | Probability for confidence intervals for kappa statistics. Default is 0.95. |

Value

- | | |
|-------------------|---|
| Result\$statistic | Z score to test null-hypothesis. |
| Result\$estimate | Calculated point estimate of Cohen's kappa statistic. |
| Result\$conf.int | A numeric vector of length 2 to give upper/lower limit of confidence intervals. |

Result\$p.value The significant probability as the result of null-hypothesis testing.

Judgement The judgement for the estimated kappa about the extent of agreement, given by Landis JR, Koch GG (1977) *Biometrics*, 33: 159-174: If kappa is less than 0, "No agreement", if 0-0.2, "Slight agreement", if 0.2-0.4, "Fair agreement", if 0.4-0.6, "Moderate agreement", if 0.6-0.8, "Substantial agreement", if 0.8-1.0, "Almost perfect agreement".

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

References

Landis JR, Koch GG (1977) The measurement of observer agreement for categorical data. *Biometrics*, 33: 159-174.

See Also

[Kappa](#)

Examples

```
res <- Kappa.test(matrix(c(20,10,5,15),2,2))
str(res)
print(res)
Kappa.test(c(1,1,3,1,1,2,1,2,1,1),c(2,1,3,1,3,2,1,3,3,3))
```

lifetable

Lifetable functions with mutual conversions

Description

Lifetable related functions.

Usage

```
lifetable(mx, class=5, mode=1)
clifetable(qx)
lxtodx(lx)
dxtolx(dx)
qxtodx(qx)
dxtoqx(dx)
qxtomx(qx)
mxtoqx(mx)
qxtolx(qx)
lxtoqx(lx)
uxtoqx(ux)
```

 mhchart

Draw maternity history charts.

Description

To compare the maternity histories among several human populations, this kind of graph is useful, inspired by Wood JW (1994) "Dynamics of Human Reproduction", Aldine de Gruyter, New York.

Usage

```
mhchart(LIST, XLIM=c(15,45), COL="black", FILL="white", BWD=1, ...)
```

Arguments

LIST	The list of groups with their maternity histories from first birth to the last birth. Usually the first childbirth age is estimated as median by Kaplan-Meier method, the second childbirth age was given by adding the median of first birth intervals to the first childbirth age by Kaplan-Meier method, and so on.
XLIM	The limit of x axis, which means the range of reproductive ages. Default is 15 and 45.
COL	The border color. Default is black.
FILL	The painting color. Default is white.
BWD	The line width of the boxes. Default is 1.
...	Other parameters handed to <code>barplot()</code> to draw axes and background.

Value

No value is returned.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
Developing <- c(18,21,24,27,30,33.5,37)
Hutterite <- c(23,25,27,29,31,33,35,37,39)
Gainj <- c(27,31,35,39)
Japan <- c(29,34)
x <- list(
  Developing=Developing,
  Hutterite=Hutterite,
  Gainj=Gainj,
  Japan=Japan)
mhchart(rev(x), COL="blue", FILL="pink", BWD=2, XLIM=c(15, 45),
  main="Maternity histories for selected populations",
  xlab="Maternal age (years)")
```

NagelkerkeR2	<i>Calculate Nagelkerke's R squared.</i>
--------------	--

Description

To evaluate the goodness of fit of the logistic regression model, calculating Nagelkerke's R squared from the result of `glm()`. The Nagelkerke's R squared means the power of explanation of the model.

Usage

```
NagelkerkeR2(rr)
```

Arguments

`rr` The object with class "glm" and "lm", which would be generated by `glm()`.

Value

`N` The number of observations in which the model were fitted.
`R2` Nagelkerke's R squared.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
res <- glm(cbind(ncases,ncontrols) ~ agegp+alcgp+tobgp, data=esoph, family=binomial())
summary(res)
NagelkerkeR2(res)
```

oddsratio	<i>Calculate odds ratio and its confidence intervals</i>
-----------	--

Description

Calculate odds ratio and its confidence intervals based on approximation, followed by null-hypothesis (odds ratio equals to 1) testing.

Usage

```
oddsratio(a, b, c, d, conf.level=0.95)
```

Arguments

a	The number of individuals who both suffer from exposure and disease.
b	The number of individuals who suffer from disease but not exposed.
c	The number of individuals who suffer from exposure but are healthy.
d	The number of individuals who neither suffered from exposure nor disease.
conf.level	Probability for confidence intervals. Default is 0.95.

Value

estimate	Calculated point estimate of odds ratio.
conf.int	A numeric vector of length 2 to give upper/lower limit of confidence intervals.
p.value	The significant probability as the result of null-hypothesis testing.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
res <- oddsratio(5,10,85,80)
str(res)
print(res)
```

`pairwise.fisher.test` *Exact version of pairwise.prop.test*

Description

By conducting repeatedly Fisher's exact tests instead of chi-square tests, this function can test the null-hypothesis of no difference in any pair of proportions for more than 2 groups, with adjustment of type I error for multiple comparison.

Usage

```
pairwise.fisher.test(x, n, p.adjust.method, ...)
```

Arguments

x	A integer vector of event occurrences
n	A integer vector of trials
p.adjust.method	A name in p.adjust.methods to specify the method to adjust type I error for multiple comparisons. Default is "holm".
...	Miscellaneous arguments to be given for fisher.test().

Value

An object of adjusted p-values for all possible comparisons of pairs with class pairwise.htest.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>. The code of this function was provided by Dr. Shigenobu AOKI (Gunma Univ.).

See Also

pairwise.prop.test, p.adjust.methods

Examples

```
pairwise.fisher.test(c(2,4,5), c(10,14,17), p.adjust.method="bonferroni")
smoker <- c(2,1,7)
total <- c(11,14,10)
names(total) <- c("A","B","C")
pairwise.fisher.test(smoker, total)
```

percentile

Convert numeric vector into its percentile

Description

Convert numeric vector into its percentile. For example, 1:5 will become c(0,25,50,75,100).

Usage

```
percentile(dat)
```

Arguments

dat A numeric vector, which will be converted into percentile value.

Value

A integer vector in [0,100]. Minimum value always becomes 0 and maximum always becomes 100.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
percentile(1:5)
X <- runif(1000,10,20)
percentile(X)
```

pvalueplot

Drawing p-value function plot by a cross table

Description

Drawing the p-value function plot using a 2 by 2 cross table, which is strongly recommended by Rothman KJ "Epidemiology: An introduction." Oxford Univ. Press.

Usage

```
pvalueplot(XTAB, plot.OR, xrange, scale, plot.log)
```

Arguments

XTAB	A 2 by 2 matrix to draw p-value function.
plot.OR	Logical. If draw odds ratio, it's TRUE, otherwise FALSE. Default FALSE.
xrange	A numeric vector includes 2 elements for minimum and maximum of x axis. Default is c(0.01, 5).
scale	A numeric value indicates the drawing density. If 10, p-values are calculated for all possible XTAB counts when the peripheral counts were fixed and 9 in-between values for each possible counts (I'm sorry for such bad explanation). Default is 1.
plot.log	Logical. Default FALSE.

Value

No value is returned.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
pvalueplot(matrix(c(321,411,686-321,689-411),2,2),xrange=c(0.7,0.9))
pvalueplot(matrix(c(4,386,4,1250),2,2),xrange=c(0.1,20),scale=10,plot.log=TRUE)
pvalueplot(matrix(c(468,480,229,205),2,2),plot.OR=TRUE,xrange=c(0.7,1.0))
```

radarchart	<i>Drawing radar chart (a.k.a. spider plot)</i>
------------	---

Description

Drawing the radar chart with several lines from a data frame, which must be composed of more than 3 variables as axes and the rows indicate cases as series.

Usage

```
radarchart(df, axistype, seg, pty, pcol, plty, plwd,
           cglty, cglwd, cglcol, axislabcol, title, maxmin, na.itp, ...)
```

Arguments

df	The data frame to be used to draw radarchart. If maxmin is TRUE, this must include maximum values as row 1 and minimum values as row 2 for each variables, and actual data should be given as row 3 and lower rows. The number of columns (variables) must be more than 2.
axistype	The type of axes, specified by any of 0:5. 0 means no axis label. 1 means center axis label only. 2 means around-the-chart label only. 3 means both center and around-the-chart labels. 4 is *.* format of 1, 5 is *.* format of 3. Default is 0.
seg	The number of segments for each axis (default 4).
pty	A vector to specify point symbol: Default 16 (closed circle), if you don't plot data points, it should be 32. This is repeatedly used for data series.
pcol	A vector of color codes for plot data: Default 1:8, which are repeatedly used.
plty	A vector of line types for plot data: Default 1:6, which are repeatedly used.
plwd	A vector of line widths for plot data: Default 1, which is repeatedly used.
cglty	Line type for radar grids: Default 3, which means dotted line.
cglwd	Line width for radar grids: Default 1, which means thinnest line.
cglcol	Line color for radar grids: Default "navy"
axislabcol	Color of axis label and numbers: Default "blue"
title	if any, title should be typed.
maxmin	Logical. If true, data frame includes possible maximum values as row 1 and possible minimum values as row 2. If false, the maximum and minimum values for each axis will be calculated as actual maximum and minimum of the data. Default TRUE.
na.itp	Logical. If true, items with NA values are interpolated from nearest neighbor items and connect them. If false, items with NA are treated as the origin (but not pointed, only connected with lines). Default FALSE.
...	Miscellaneous arguments to be given for plot.default().

Value

No value is returned.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
# Data must be given as the data frame, where the first cases show maximum.
maxmin <- data.frame(
  total=c(5,1),
  phys=c(15,3),
  psycho=c(3,0),
  social=c(5,1),
  env=c(5,1))
# data for radar chart function version 1 series, minimum value must be omitted from above.
RNGkind("Mersenne-Twister")
set.seed(123)
dat <- data.frame(
  total=runif(3,1,5),
  phys=rnorm(3,10,2),
  psycho=c(0.5,NA,3),
  social=runif(3,1,5),
  env=c(5,2.5,4))
dat <- rbind(maxmin,dat)
op <- par(mar=c(1,2,2,1),mfrow=c(2,2))
radarchart(dat,axistype=1,seg=5,plty=1,title="(axis=1, 5 segments)")
radarchart(dat,axistype=2,pcol=topo.colors(3),plty=1,title="(topo.colors, axis=2)")
radarchart(dat,axistype=3,pty=32,plty=1,axislabcol="grey",na.itp=FALSE,title="(no points, axis=3, na.itp=FALSE)")
radarchart(dat,axistype=0,plwd=1:5,pcol=1,title="(use lty and lwd but b/w, axis=0)")
par(op)
```

riskratio

Calculate risk ratio and its confidence intervals

Description

Calculate risk ratio (a kind of relative risk) and its confidence intervals based on approximation, followed by null hypothesis (risk ratio equals to 1) testing.

Usage

```
riskratio(X, Y, m1, m2, conf.level=0.95)
```

Arguments

X	The number of disease occurrence among exposed cohort.
Y	The number of disease occurrence among non-exposed cohort.
m1	The number of individuals in exposed cohort group.
m2	The number of individuals in non-exposed cohort group.
conf.level	Probability for confidence intervals. Default is 0.95.

Value

estimate	Calculated point estimate of risk ratio.
conf.int	A numeric vector of length 2 to give upper/lower limit of confidence intervals.
p.value	The significant probability of the result of null-hypothesis testing.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
res <- riskratio(5,10,90,90)
str(res)
print(res)
```

roc

Calculate Receiver Operating Characteristic (ROC) curve

Description

Calculate Receiver Operating Characteristic (ROC) curve's each performance set of [sensitivity, 1-specificity], each distance of the performance from the worst performance [0, 1], and each piece of area under the curve, for each cutoff point, as list.

Usage

```
roc(values, iscase)
```

Arguments

values	A numeric vector of measured values.
iscase	A logical (or 0/1) vector of diagnostics. Negative result must be given by FALSE or 0.

Value

cutoff	The numeric vector of cutoff points, which are composed of the all unique values among the given measurements and the maximum cutoff is maximum measurement plus 1. Therefore, the minimum cutoff gives [1, 1] and the maximum cutoff gives [0, 0] as the performance set of [sensitivity, 1-specificity], respectively.
sens	The numeric vector of sensitivities for all cutoff points.
falsepos	The numeric vector of 1-specificities (false positiveness) for all cutoff points.
distance	The numeric vector of distance between actual performance set and the worst performance.
aucpiece	The numeric vector of the pieces of areas under the curve.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

See Also

[ROC](#)

Examples

```
scores <- c(15,20,19,28,26,17,13,22,23,24)
diagno <- c(0,0,0,1,1,1,0,1,1,1)
res <- roc(scores, diagno)
print(res)
plot(res)
```

S60MPJ

Model population of Japan in Showa 60 (1985)

Description

The data gives the age-class (by five) specific model population of Japan in Showa 60 (1985) to calculate directly adjusted mortality rate.

Usage

S60MPJ

Format

A vector containing 18 observations.

Source

<http://www.mhlw.go.jp/toukei/list/dl/81-1b1.pdf>, page 55.

References

Tamura K. (2008) How do we die?: death date from vital statistics of the Japanese population. *The Waseda study of politics and public law*, 87: 27-57.

Siler

Siler's model mortality for qx and its fitting

Description

Implementing Siler's model mortality function of qx and fitting the model to actual qx of given lifetable.

Usage

```
Siler(a1, b1, a2, a3, b3, t)
fitSiler(initialpar=c(0.01,3,1e-4,1e-5,0.1), data, mode=1, Method="Nelder-Mead", ...)
```

Arguments

a1	The parameter a1 of the Siler model, $q(t)=a1*\exp(-b1*t)+a2+a3*\exp(b3*t)$.
b1	The parameter b1 of the Siler model, $q(t)=a1*\exp(-b1*t)+a2+a3*\exp(b3*t)$.
a2	The parameter a2 of the Siler model, $q(t)=a1*\exp(-b1*t)+a2+a3*\exp(b3*t)$.
a3	The parameter a3 of the Siler model, $q(t)=a1*\exp(-b1*t)+a2+a3*\exp(b3*t)$.
b3	The parameter b3 of the Siler model, $q(t)=a1*\exp(-b1*t)+a2+a3*\exp(b3*t)$.
t	Age (vector OK) in years
initialpar	Initial value for the parameters to be estimated. If not given, c(0.01, 0.0003, 0.07) is used.
data	Actual vector of qx in the lifetable to be used to obtain the best-fit parameters of the Gompertz-Makeham model.
mode	Which of lifetable functions should be used to calculate the RMSE: 1 qx, 2 dx, otherwise lx. Default is 1.
Method	The method to be used in optim() function. Default is "Nelder-Mead".
...	Other options to be passed to optim().

Value

Siler() returns model qx for the same length with t. fitSiler() returns the numeric vector of fitted parameters a1, b1, a2, a3 and b3, RMSE for those values, and the flag of convergence.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

See Also[Jlife](#)**Examples**

```
res <- fitSiler(Jlife$qx2005M)
FLAG <- res[7]
while (FLAG>0) {
  res <- fitSiler(res[1:5],Jlife$qx2005M)
  FLAG <- res[7]
}
print(res)
```

SIQR*Calculate semi-interquartile range*

Description

Calculate semi-interquartile range, using IQR or fivenum.

Usage

```
SIQR(X, mode)
```

Arguments

X a numeric vector.
mode If 1, using fivenum, otherwise using IQR function. Default is 1.

Value

A numeric vector of length 1, giving the semi-interquartile range.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
data <- rnorm(100,10,1)
SIQR(data)
SIQR(data, 2)
sd(data)
idata <- sample(50:80,100,replace=TRUE)
SIQR(idata)
SIQR(idata, 2)
sd(idata)
```

truemedian	<i>Calculate true median for data with ties.</i>
------------	--

Description

Usually median for data with ties, tied values are treated as exactly same. For example, median of 3, 3, 4, 4, 4 will be 4. However, the measured values are usually rounded, so that we can assume evenly distributed true values for tied values. For example, the previous data can be treated as rounded values of 2.75, 3.25, 11/3, 4, 13/3. From this viewpoint, true median of 3, 3, 4, 4, 4 could be 11/3 (=3.66...). This function calculates this.

Usage

```
truemedian(X, h)
```

Arguments

X	A numeric vector. Usually integer.
h	Width of measurement unit. Default is 1.

Value

A numeric vector of length 1, giving "true" median estimate.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

References

Grimm LG (1993) Statistical Applications for the Behavioral Sciences. John Wiley and Sons.

Examples

```
median(c(3, 3, 4, 4, 4))  
truemedian(c(3, 3, 4, 4, 4))
```

VIF*Calculate variance inflation factor (VIF) from the result of lm.*

Description

To evaluate multicollinearity of multiple regression model, calculating the variance inflation factor (VIF) from the result of `lm()`. If VIF is more than 10, multicollinearity is strongly suggested.

Usage

```
VIF(X)
```

Arguments

`X` The object with class "lm", which would be generated by `lm()`.

Value

A variance inflation factor is returned.

Author(s)

Minato Nakazawa <minato-nakazawa@umin.net> <http://minato.sip21c.org/>

Examples

```
# the target multiple regression model
res <- lm(Ozone ~ Wind+Temp+Solar.R, data=airquality)
summary(res)
# checking multicollinearity for independent variables.
VIF(lm(Wind ~ Temp+Solar.R, data=airquality))
VIF(lm(Temp ~ Wind+Solar.R, data=airquality))
VIF(lm(Solar.R ~ Wind+Temp, data=airquality))
```

Index

*Topic **datasets**

- JASM, 9
 - Jfert, 10
 - Jlife, 12
 - Jpop, 13
 - Jpop1, 15
 - Jvital, 17
 - S60MPJ, 30
- clifetable (lifetable), 20
- CronbachAlpha, 2
- CT, 3
- Denny, 4
- dxtolx (lifetable), 20
- dxtoqx (lifetable), 20
- fitCT (CT), 3
- fitDenny (Denny), 4
- fitGM (GompertzMakeham), 6
- fitHad (Hadwiger), 8
- fitSiler (Siler), 31
- geary.test, 5
- GompertzMakeham, 6
- gstem, 7
- Hadwiger, 8
- JASM, 9
- Jfert, 3, 8, 10
- Jlife, 5, 6, 12, 21, 32
- Jpop, 13
- Jpop1, 15
- Jvital, 17
- Kappa, 20
- Kappa.test, 19
- lifetable, 20
- lxtodx (lifetable), 20
- lxtoqx (lifetable), 20
- mhchart, 22
- mxtoqx (lifetable), 20
- NagelkerkeR2, 23
- oddsratio, 23
- pairwise.fisher.test, 24
- percentile, 25
- plot.roc (roc), 29
- print.roc (roc), 29
- pvalueplot, 26
- qxtodx (lifetable), 20
- qxtolx (lifetable), 20
- qxtomx (lifetable), 20
- radarchart, 27
- riskratio, 28
- ROC, 30
- roc, 29
- S60MPJ, 30
- Siler, 31
- SIQR, 32
- truemedian, 33
- uxtoqx (lifetable), 20
- VIF, 34