

# Package ‘fusionchartsR’

December 20, 2021

**Type** Package

**Version** 0.0.3

**Title** Embedding 'FusionCharts Javascript' Library in R

**Description** FusionCharts provides awesome and minimalist functions to make beautiful interactive charts <<https://www.fusioncharts.com/>>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.1.2

**Imports** htmlwidgets, jsonlite, magrittr, shiny

**Suggests** rmarkdown, knitr

**NeedsCompilation** no

**Author** Alex Yahiaoui Martinez [aut, cre]

**Maintainer** Alex Yahiaoui Martinez <yahiaoui-martinez.alex@outlook.com>

**Repository** CRAN

**Date/Publication** 2021-12-20 20:40:05 UTC

## R topics documented:

available_charts . . . . .	2
fusionAnchors . . . . .	2
fusionAxis . . . . .	3
fusionBackground . . . . .	4
fusionCanvas . . . . .	6
fusionCaption . . . . .	7
fusionCustomAxis . . . . .	8
fusionCustomLegend . . . . .	11
fusionDiv . . . . .	13
fusionLegend . . . . .	15
fusionLogo . . . . .	16
fusionMultiPlot . . . . .	17
fusionMultiPlot-shiny . . . . .	18

fusionPalette . . . . .	18
fusionPlot . . . . .	20
fusionPlotOutput . . . . .	21
fusionSubcaption . . . . .	22
fusionTheme . . . . .	23
fusionTooltip . . . . .	23
fusionTrendline . . . . .	24
runDemo . . . . .	26
%>% . . . . .	27

<b>Index</b>	<b>28</b>
--------------	-----------

---

available_charts	<i>List of available charts in fusionchartsR</i>
------------------	--

---

### Description

List of available charts in fusionchartsR

### Usage

```
available_charts()
```

### Examples

```
library(fusionchartsR)
available_charts()
```

---

fusionAnchors	<i>Adding FusionCharts anchors</i>
---------------	------------------------------------

---

### Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/anchors-and-lines>

### Usage

```
fusionAnchors(
  fusionPlot,
  drawAnchors = TRUE,
  showvalues = FALSE,
  anchorSides = "0",
  anchorRadius = "3",
  anchorAlpha = "100",
  anchorBorderThickness = "1",
  anchorBorderColor = "#5a5a5a",
```

```

    anchorBgColor = "#ffffff",
    anchorBgAlpha = "100",
    anchorImageAlpha = "100",
    anchorImageScale = "150"
  )

```

### Arguments

fusionPlot	fusionPlot object got by fusionPlot()
drawAnchors	Show the anchors
showvalues	Show the values of the anchors
anchorSides	Specify the number of sides to define the shape of the anchor
anchorRadius	Set the radius of the anchor
anchorAlpha	Set the transparency of the anchor
anchorBorderThickness	Set the thickness of the anchor border
anchorBorderColor	Set the hex code for anchor border color
anchorBgColor	Set the hex code for anchor background color
anchorBgAlpha	Set the transparency of the anchor background
anchorImageAlpha	Set the transparency of the image
anchorImageScale	Set the scale of the image

### Examples

```

library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "line") %>%
  fusionAnchors(anchorRadius = "6", anchorBorderThickness = "2") %>%
  fusionTheme(theme = "fusion")

```

---

fusionAxis

*Adding FusionCharts axis*

---

### Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/axes>

**Usage**

```
fusionAxis(
  fusionPlot,
  xAxisName = "Change X axis",
  yAxisName = "Change Y axis",
  AxisNameFont = "Arial",
  AxisNameFontSize = "12",
  AxisNameFontColor = "#999999",
  AxisNameFontBold = TRUE,
  AxisNameFontItalic = FALSE
)
```

**Arguments**

fusionPlot	fusionPlot object got by fusionPlot()
xAxisName	Specify the title of the X-axis of the chart
yAxisName	Specify the title of the Y-axis of the chart
AxisNameFont	Set the font family of axis
AxisNameFontSize	Set the font size (between 0 and 72) of axis
AxisNameFontColor	Set the font color of axis in hex code
AxisNameFontBold	Set the font style to bold
AxisNameFontItalic	Set the font style to italic

**Examples**

```
library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "column3d") %>%
  fusionAxis(xAxisName = "Countries", yAxisName = "Numbers", AxisNameFontSize = "20") %>%
  fusionCustomAxis(xAxisPosition = "top", yAxisPosition = "right") %>%
  fusionTheme(theme = "gammel")
```

---

fusionBackground

*Adding FusionCharts borders & background*


---

**Description**

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/border-and-background>

**Usage**

```
fusionBackground(  
  fusionPlot,  
  showBorder = FALSE,  
  borderColor = "#666666",  
  borderThickness = "4",  
  borderAlpha = "80",  
  bgColorStart = "#ffffff",  
  bgColorEnd = NULL,  
  bgAlphaStart = "50",  
  bgAlphaEnd = NULL,  
  bgratioStart = "60",  
  bgratioEnd = "40",  
  bgAngle = "180"  
)
```

**Arguments**

fusionPlot	fusionPlot object got by fusionPlot()
showBorder	Show the chart border
borderColor	Specify the color of the border
borderThickness	Set the thickness of the border
borderAlpha	Set the transparency of the border
bgColorStart, bgColorEnd	Set the hex codes of the starting and ending gradient colors
bgAlphaStart, bgAlphaEnd	Set the transparency of the starting ending gradient colors
bgratioStart, bgratioEnd	Set the radius of gradient colors
bgAngle	Set the angle in degrees of gradient colors

**Examples**

```
library(fusionchartsR)  
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))  
df %>%  
  fusionPlot(x = "label", y = "value", type = "column3d") %>%  
  fusionBackground(showBorder = TRUE, bgColorStart = "#DDDDDD") %>%  
  fusionTheme(theme = "fusion")
```

---

fusionCanvas

*Adding FusionCharts canvas*

---

## Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/canvas>

## Usage

```
fusionCanvas(  
    fusionPlot,  
    showCanvasBg = FALSE,  
    canvasbgColorFirst = "#5a5a5a",  
    canvasbgColorSecond = NULL,  
    canvasBgDepth = "0",  
    canvasbgAlpha = "100",  
    canvasBgRatioStart = "40",  
    canvasBgRatioEnd = "60",  
    canvasBgAngle = "0",  
    showCanvasBorder = FALSE,  
    canvasBorderColor = "#666666",  
    canvasBorderAlpha = "80",  
    canvasBorderThickness = "1",  
    showCanvasBase = FALSE,  
    canvasBaseDepth = "5",  
    canvasBaseColor = "#aaaaaa"  
)
```

## Arguments

fusionPlot	fusionPlot object got by fusionPlot()
showCanvasBg	Show the canvas background
canvasbgColorFirst	Specify the hex code of the first canvas background color
canvasbgColorSecond	Specify the hex code of the second canvas background color
canvasBgDepth	Set the depth of the canvas background
canvasbgAlpha	Set the transparency of the background color
canvasBgRatioStart	Set the first value of the canvas background ratio (in percentage)
canvasBgRatioEnd	Set the second value of the canvas background ratio (in percentage)
canvasBgAngle	Specify canvas background angle (in degrees)
showCanvasBorder	Show the canvas border

`canvasBorderColor` Set the border color  
`canvasBorderAlpha` Set the transparency of the border  
`canvasBorderThickness` Set the thickness of the border  
`showCanvasBase` Show the canvas base  
`canvasBaseDepth` Set the height of the canvas base  
`canvasBaseColor` Specify the hex code of the base color

### Examples

```

library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "column2d") %>%
  fusionCanvas(showCanvasBorder = TRUE, canvasBorderThickness = "4", canvasBorderAlpha = "80") %>%
  fusionTheme(theme = "fusion")
  
```

---

fusionCaption	<i>Adding FusionCharts caption</i>
---------------	------------------------------------

---

### Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/caption-and-sub-caption>

### Usage

```

fusionCaption(
  fusionPlot,
  caption = "Add a caption here",
  captionFont = "Arial",
  captionFontSize = "18",
  captionFontColor = "#5A5A5A",
  captionFontBold = TRUE,
  captionOnTop = TRUE,
  captionAlignment = c("center", "left", "right")
)
  
```

### Arguments

`fusionPlot` fusionPlot object got by fusionPlot()  
`caption` Specify the caption of the chart  
`captionFont` Set the caption font family

captionFontSize      Set the caption font size (between 0 and 72)

captionFontColor    Set the caption font color

captionFontBold     Enable caption font to bold

captionOnTop        Display the caption at the top of the chart

captionAlignment    Specify the horizontal alignment of the caption

### Examples

```
library(fusionchartsR)

df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
fusionPlot(data = df, x = "label", y = "value", type = "column2d") %>%
  fusionCaption(caption = "Caption on the left", captionAlignment = "left") %>%
  fusionSubcaption(subcaption = "subcaption too") %>%
  fusionTheme(theme = "fusion")
```

---

fusionCustomAxis	<i>Customing FusionCharts axis</i>
------------------	------------------------------------

---

### Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/axes>

### Usage

```
fusionCustomAxis(
  fusionPlot,
  showlabels = TRUE,
  xAxisPosition = c("bottom", "top", "left", "right"),
  yAxisPosition = c("left", "right", "top", "bottom"),
  AxisNameBorderColor = NULL,
  AxisNameBorderAlpha = "0",
  AxisNameBorderPadding = "6",
  AxisNameBorderRadius = "3",
  AxisNameBorderThickness = "2",
  AxisNameBorderDashed = FALSE,
  AxisNameBorderDashLen = "4",
  AxisNameBorderDashGap = "2",
  AxisNameBgColor = NULL,
  AxisNameBgAlpha = "0",
  AxisNameFontAlpha = "100",
  AxisValueFont = "Arial",
```



```

AxisValueFontSize = "1px",
AxisValueFontColor = NULL,
AxisValueFontBold = FALSE,
AxisValueFontItalic = FALSE,
AxisValueAlpha = "100",
AxisValueBgColor = NULL,
AxisValueBgAlpha = "50",
AxisValueBorderColor = "#ffffff",
AxisValueBorderAlpha = "0",
AxisValueBorderPadding = "5",
AxisValueBorderRadius = "2",
AxisValueBorderThickness = "3",
AxisValueBorderDashed = FALSE,
AxisValueBorderDashLen = "2",
AxisValueBorderDashGap = "2"
)

```

### Arguments

fusionPlot	fusionPlot object got by fusionPlot()
showlabels	Display the data labels
xAxisPosition	change the position of the x-axis
yAxisPosition	change the position of the y-axis
AxisNameBorderColor	Set the border color of the name of the axis
AxisNameBorderAlpha	Set the transparency of the border around the name of axis
AxisNameBorderPadding	Set the padding of the border around the name of the axis
AxisNameBorderRadius	Set the radius of the border around the name of the axis
AxisNameBorderThickness	Set the thickness of the border around the name of the axis
AxisNameBorderDashed	Make the border around the name of the axis dashed
AxisNameBorderDashLen	Set the length of each dash in the dashed border around the name of the axis
AxisNameBorderDashGap	Set the gap between two consecutive dashes in the dashed border around the name of the axis
AxisNameBgColor	Set the background color of the name of the axis
AxisNameBgAlpha	Set the transparency of the background of the name of the axis
AxisNameFontAlpha	Set the transparency of the name of the axis

**AxisValueFont** Set the font of the axis values  
**AxisValueFontSize**  
 Set the font size (between 0 to 72) of the axis values  
**AxisValueFontColor**  
 Set the font color of the axis  
**AxisValueFontBold**  
 Set the font of the axis values to bold  
**AxisValueFontItalic**  
 Set the font for the axis values to italics  
**AxisValueAlpha** Set the degree of transparency of the axis values  
**AxisValueBgColor**  
 Set the background color of the axis values  
**AxisValueBgAlpha**  
 Set the background color transparency of the axis values  
**AxisValueBorderColor**  
 Set the border color of the axis values  
**AxisValueBorderAlpha**  
 Set the transparency of the border of the axis values  
**AxisValueBorderPadding**  
 Set the padding of the axis values border  
**AxisValueBorderRadius**  
 Set the border radius of the axis values  
**AxisValueBorderThickness**  
 Set the border thickness of the axis values  
**AxisValueBorderDashed**  
 Make the axis values border dashed  
**AxisValueBorderDashLen**  
 Set the length of each dash for the dashed borders around axis values  
**AxisValueBorderDashGap**  
 Set the gap between two consecutive dashes for the dashed borders around the axis values

## Examples

```

library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "column3d") %>%
  fusionAxis(xAxisName = "Countries", yAxisName = "Numbers", AxisNameFontSize = "20") %>%
  fusionCustomAxis(xAxisPosition = "top", yAxisPosition = "right") %>%
  fusionTheme(theme = "gammel")
  
```

---

fusionCustomLegend	<i>Customizing FusionCharts legend</i>
--------------------	--

---

### Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/legend>

### Usage

```
fusionCustomLegend(
    fusionPlot,
    plotHighlightEffect = FALSE,
    plotHighlightEffectColor = "#7f7f7f",
    plotHighlightEffectAlpha = "60",
    drawCustomLegendIcon = TRUE,
    legendIconBgColor = NULL,
    legendIconAlpha = "100",
    legendIconBgAlpha = "100",
    legendIconBorderColor = "#123456",
    legendIconBorderThickness = "0",
    legendIconSides = "1",
    legendIconStartAngle = "45",
    legendScrollBgColor = "#5A5A5A",
    legendBgColor = "#CCCCCC",
    legendBgAlpha = "0",
    legendBorderColor = "#666666",
    legendBorderThickness = "0",
    legendBorderAlpha = "40",
    legendCaptionAlignment = c("center", "left", "right"),
    legendShadow = FALSE,
    legendItemFontBold = FALSE,
    legendItemFont = "Arial",
    legendItemFontSize = "14",
    legendItemFontColor = "#5A5A5A",
    legendItemHover = FALSE,
    legendItemHoverFontColor = "#cccccc"
)
```

### Arguments

fusionPlot	fusionPlot object got by fusionPlot()
plotHighlightEffect	Enable highlighting of corresponding data series after hover over a legend text
plotHighlightEffectColor	Specify the color
plotHighlightEffectAlpha	Specify the opacity

`drawCustomLegendIcon`  
Enable drawing of a custom legend icon

`legendIconBgColor`  
Specify the hex color code for the background of the legend icon

`legendIconAlpha`  
Set the legend icon transparency (0 to 100)

`legendIconBgAlpha`  
Set the legend icon background transparency

`legendIconBorderColor`  
Specify the hex color code for the border of the legend icon

`legendIconBorderThickness`  
Set the thickness of the legend icon border

`legendIconSides`  
Set the number of sides for the legend icon

`legendIconStartAngle`  
Set the starting angle for drawing the legend icon

`legendScrollBgColor`  
Specify the background color of the scroll bar

`legendBgColor` Specify the background color for the legend

`legendBgAlpha` Specify the background transparency for the legend

`legendBorderColor`  
Specify the border color for the legend

`legendBorderThickness`  
Specify the border thickness for the legend

`legendBorderAlpha`  
Specify the border transparency for the legend

`legendCaptionAlignment`  
Specify the horizontal alignment of the legend caption

`legendShadow` Enable the legend shadow

`legendItemFontBold`  
Display legend keys in bold

`legendItemFont` Specify the legend item font

`legendItemFontSize`  
Specify the legend item font size (0 to 72)

`legendItemFontColor`  
Specify the legend item font color

`legendItemHover`  
Enable hover effect to legend item

`legendItemHoverFontColor`  
Specify the legend item font color on hover

## Examples

```
library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "doughnut2d") %>%
  fusionCustomLegend(plotHighlightEffect = TRUE) %>%
  fusionTheme(theme = "fusion")
```

---

fusionDiv

*Adding FusionCharts Div & Grid*

---

## Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/div-lines-and-grids>  
& <https://www.fusioncharts.com/dev/chart-guide/chart-configurations/vertical-div-lines>

## Usage

```
fusionDiv(
  fusionPlot,
  adjustDiv = FALSE,
  numDivLines = "5",
  divLineColor = "#5a5a5a",
  divLineAlpha = "10",
  divLineDashed = FALSE,
  divLineDashLen = "5",
  divLineDashGap = "6",
  numVDivLines = "5",
  vDivLineColor = "#F2F2F2",
  vDivLineThickness = "1",
  vDivLineAlpha = "100",
  vDivLineDashed = FALSE,
  vDivLineDashLen = "5",
  vDivLineDashGap = "3",
  showAlternateHGridColor = FALSE,
  alternateHGridColor = "#5a5a5a",
  alternateHGridAlpha = "1",
  showAlternateVGridColor = FALSE,
  alternateVGridColor = "#5a5a5a",
  alternateVGridAlpha = "3"
)
```

## Arguments

fusionPlot	fusionPlot object got by fusionPlot()
adjustDiv	Enable the automatic adjustment of horizontal lines

numDivLines      Set the number of hozitontal lines  
 divLineColor     Specify the hex code for the color of the hozitontal lines  
 divLineAlpha     Set the transparency of the hozitontal lines  
 divLineDashed    Display the hozitontal lines as dashed  
 divLineDashLen   Set the length of each dashed hozitontal lines  
 divLineDashGap   Set the gap between the dashed hozitontal lines  
 numVDivLines    Specify the number of vertical lines  
 vDivLineColor    Set the color of the vertical lines  
 vDivLineThickness  
                   Set the thickness of the vertical lines  
 vDivLineAlpha    Set the transparency of the vertical lines  
 vDivLineDashed   Display the vertical lines as dashed  
 vDivLineDashLen  
                   Set the length of each dashed vertical lines  
 vDivLineDashGap  
                   Set the gap between the dashed vertical lines  
 showAlternateHGridColor  
                   Display the horizontal grid bands  
 alternateHGridColor  
                   Specify the hex code for the color of the horizontal grid  
 alternateHGridAlpha  
                   Set the transparency of the horizontal grid  
 showAlternateVGridColor  
                   Display the vertical grid bands  
 alternateVGridColor  
                   Specify the hex code for the color of the vertical grid  
 alternateVGridAlpha  
                   Set the transparency of the vertical grid

### Examples

```

library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "column2d") %>%
  fusionDiv(divLineColor = "#6699cc", divLineAlpha = "60", divLineDashed = TRUE) %>%
  fusionTheme(theme = "fusion")

```

---

fusionLegend	<i>Adding FusionCharts legend</i>
--------------	-----------------------------------

---

**Description**

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/legend>

**Usage**

```
fusionLegend(  
  fusionPlot,  
  showLegend = TRUE,  
  interactiveLegend = TRUE,  
  legendPosition = c("bottom", "left", "right"),  
  legendAllowDrag = FALSE,  
  legendIconScale = "1",  
  reverseLegend = FALSE,  
  legendCaption = NULL,  
  legendCaptionBold = TRUE,  
  legendCaptionFont = "Arial",  
  legendCaptionFontSize = "14",  
  legendCaptionFontColor = "#333333"  
)
```

**Arguments**

fusionPlot	fusionPlot object got by fusionPlot()
showLegend	Show the legend
interactiveLegend	Enable interactive legend
legendPosition	Specify the position of the legend
legendAllowDrag	Make the legend draggable
legendIconScale	Specify the legend icon size (values from "1" to "5")
reverseLegend	Reverse the order of datasets
legendCaption	Specify the legend caption value
legendCaptionBold	Set the legend caption font style to bold
legendCaptionFont	Specify the legend caption font
legendCaptionFontSize	Specify the legend caption font size
legendCaptionFontColor	Specify the hex color code for the caption font legend

**Examples**

```
library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "doughnut2d") %>%
  fusionLegend(legendCaption = "LegendCaption", legendCaptionFontSize = "24") %>%
  fusionTheme(theme = "fusion")
```

fusionLogo

*Adding FusionCharts logo***Description**

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/loading-external-logo>

**Usage**

```
fusionLogo(
  fusionPlot,
  logoURL = "NULL",
  logoAlpha = "40",
  logoScale = "80",
  logoPosition = c("TL", "TR", "BL", "BR", "CC"),
  logoLink = NULL
)
```

**Arguments**

fusionPlot	fusionPlot object got by fusionPlot()
logoURL	Specify the URL of the external logo
logoAlpha	Set the transparency of the external logo
logoScale	Set the scale of the external logo (0 to 300)
logoPosition	Specify the position of the external logo
logoLink	Add an external link to the external logo

**Examples**

```
library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
logoURL <- "https://static.fusioncharts.com/sampledData/images/Logo-HM-72x72.png"
df %>%
  fusionPlot(x = "label", y = "value", type = "doughnut2d") %>%
  fusionLogo(logoURL = logoURL) %>%
  fusionTheme(theme = "fusion")
```



---

fusionMultiPlot      *Create new multiple charts*

---

### Description

Main function to make interactive charts. Check all charts at <https://www.fusioncharts.com/charts>

### Usage

```
fusionMultiPlot(  
  data,  
  x,  
  y,  
  col = NULL,  
  type = "msstepline",  
  numberSuffix = NULL  
)
```

### Arguments

data	Default dataset to use
x, y	character name of variable
col	define seriesname variable
type	See 'available_charts()'
numberSuffix	Specify the suffix for all the Y-axis values on the chart

### Examples

```
library(fusionchartsR)  
  
# Multiple charts  
new.data <- data.frame(  
  label = rep(x = c(2012:2016), times = 2),  
  seriesname = c(rep("iOS App Store", 5), rep("Google Play Store", 5)),  
  values = c(1:10)  
)  
  
new.data %>%  
  fusionMultiPlot(  
    x = "label",  
    y = "values",  
    col = "seriesname",  
    type = "mscolumn2d",  
  ) %>%  
  fusionTheme(theme = "fusion")
```

---

fusionMultiPlot-shiny *Shiny bindings for fusionMultiPlot*

---

### Description

Output and render functions for using fusionMultiPlot within Shiny applications and interactive Rmd documents.

### Usage

```
fusionMultiPlotOutput(outputId, width = "100%", height = "400px")
renderFusionMultiPlot(expr, env = parent.frame(), quoted = FALSE)
```

### Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a fusionMultiPlot
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

---

fusionPalette *Adding FusionCharts palette*

---

### Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/data-plot>

### Usage

```
fusionPalette(
  fusionPlot,
  palettecolors = NULL,
  usePlotGradientColor = FALSE,
  plotGradientColor = "#003366",
  plotFillAngle = "0",
  plotFillRatioStart = "90",
  plotFillRatioEnd = "100",
  plotFillAlpha = "100",
  showPlotBorder = FALSE,
  drawFullAreaBorder = FALSE,
```

```

inheritPlotBorderColor = FALSE,
plotBorderDashed = FALSE,
plotBorderDashLen = "4",
plotBorderDashGap = "4",
plotBorderThickness = "1",
plotBorderColor = "#666666",
useRoundEdges = FALSE,
plotHoverEffect = FALSE,
plotFillHoverColor = "#5D62B5",
plotFillHoverAlpha = "100",
plotBorderHoverColor = "#000000",
plotBorderHoverAlpha = "100",
plotBorderHoverThickness = "1",
plotBorderHoverDashed = TRUE,
plotBorderHoverDashLen = "6",
plotBorderHoverDashGap = "2"
)

```

### Arguments

**fusionPlot** fusionPlot object got by fusionPlot()

**palettecolors** Specify your custom palette for data plots

**usePlotGradientColor**  
Use the gradient effect

**plotGradientColor**  
Specify the hex code of the gradient color

**plotFillAngle** Set the fill angle for the gradient (0 to 360)

**plotFillRatioStart**  
Specify the start of the gradient effect

**plotFillRatioEnd**  
Specify the end of the gradient effect

**plotFillAlpha** Set the transparency of the gradient fill

**showPlotBorder** Show the plot border

**drawFullAreaBorder**  
To set the top border of the area chart (only works if showPlotBorder = TRUE)

**inheritPlotBorderColor**  
Enable the plot border to inherit the color of an area plot

**plotBorderDashed**  
Make the border dashed

**plotBorderDashLen**  
Set the length of each dash in plot-border (in pixels)

**plotBorderDashGap**  
Set the gap between two consecutive dashes in plot border (in pixels)

**plotBorderThickness**  
Set the thickness of the plot border

plotBorderColor	Set the color of the plot border
useRoundEdges	Enable rounded edges (2D Column or Bar charts only)
plotHoverEffect	Enable hover effects for the data plots
plotFillHoverColor	Set the hover color for data plots in hex code format
plotFillHoverAlpha	Set the transparency for hover color for data plots
plotBorderHoverColor	Set the hover border color
plotBorderHoverAlpha	Set the transparency of hover border for data plots
plotBorderHoverThickness	Set the hover border thickness (in pixels)
plotBorderHoverDashed	Make dashed borders on hover
plotBorderHoverDashLen	Set the length of each dash for all data plots on hover
plotBorderHoverDashGap	Set the gap between two consecutive dashes for all data plots on hover(in pixels)

## Examples

```
library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))

df %>%
  fusionPlot(x = "label", y = "value", type = "pie2d") %>%
  fusionTheme(theme = "gammel")

df %>%
  fusionPlot(x = "label", y = "value", type = "pie2d") %>%
  fusionPalette(palettecolors = c("5d62b5", "29c3be", "f2726f")) %>%
  fusionTheme(theme = "gammel")
```

---

fusionPlot

*Create new charts*

---

## Description

Main function to make interactive charts. Check all charts at <https://www.fusioncharts.com/charts>

## Usage

```
fusionPlot(data, x, y, type = "column2d", numberSuffix = NULL)
```

**Arguments**

data	Default dataset to use
x, y	character name of variable
type	See ‘available_charts()’
numberSuffix	Specify the suffix for all the Y-axis values on the chart

**Examples**

```
library(fusionchartsR)

# Single
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "pie2d") %>%
  fusionTheme(theme = "fusion")
```

---

fusionPlotOutput      *Shiny bindings for fusionPlot*

---

**Description**

Output and render functions for using fusionPlot within Shiny applications and interactive Rmd documents.

**Usage**

```
fusionPlotOutput(outputId, width = "100%", height = "400px")

renderfusionPlot(expr, env = parent.frame(), quoted = FALSE)
```

**Arguments**

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a fusionPlot
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

---

fusionSubcaption      *Adding FusionCharts subcaption*

---

## Description

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/caption-and-sub-caption>

## Usage

```
fusionSubcaption(
  fusionPlot,
  subcaption = "Add a subCaption here",
  subcaptionFont = "Arial",
  subcaptionFontSize = "14",
  subcaptionFontColor = "#999999",
  subcaptionFontBold = FALSE
)
```

## Arguments

fusionPlot	fusionPlot object got by fusionPlot()
subcaption	Specify the subcaption of the chart
subcaptionFont	Set the subcaption font family
subcaptionFontSize	Set the subcaption font size (between 0 and 72)
subcaptionFontColor	Set the subcaption font color in hex code
subcaptionFontBold	Enable subcaption font to bold

## Examples

```
library(fusionchartsR)

mtcars %>%
  fusionPlot(
    x = "cyl",
    y = "mpg",
    type = "boxandwhisker2d"
  ) %>%
  fusionCaption(caption = "Caption on the left", captionAlignment = "left") %>%
  fusionSubcaption(subcaption = "subcaption too") %>%
  fusionPalette(palettecolors = c("#5D62B5", "#979AD0")) %>%
  fusionTheme(theme = "fusion")
```

---

fusionTheme	<i>Adding FusionCharts theme</i>
-------------	----------------------------------

---

**Description**

<https://www.fusioncharts.com/dev/themes/introduction-to-themes>

**Usage**

```
fusionTheme(  
  fusionPlot,  
  theme = c("fusion", "gammel", "candy", "zune", "ocean", "carbon", "umber")  
)
```

**Arguments**

fusionPlot	fusionPlot object got by fusionPlot()
theme	Chart theme

**Examples**

```
library(fusionchartsR)  
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))  
df %>%  
  fusionPlot(x = "label", y = "value", type = "pie2d") %>%  
  fusionTheme(theme = "gammel")
```

---

fusionTooltip	<i>Adding FusionCharts tooltip</i>
---------------	------------------------------------

---

**Description**

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/tool-tips>

**Usage**

```
fusionTooltip(  
  fusionPlot,  
  showToolTip = TRUE,  
  tooltipBorderColor = "#666666",  
  tooltipBgColor = "#ffffff",  
  tooltipBgAlpha = "100",  
  showToolTipShadow = TRUE  
)
```

**Arguments**

**fusionPlot** fusionPlot object got by fusionPlot()  
**showToolTip** Display tooltip  
**toolTipBorderColor**  
                   Specify the color of the tooltip border  
**toolTipBgColor** Specify the hex code for the tooltip background color  
**toolTipBgAlpha** Set the tooltip background color transparency  
**showToolTipShadow**  
                   Enable tooltip shadow

**Examples**

```

library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "doughnut2d") %>%
  fusionTooltip(toolTipBgColor = "#3526ad", toolTipBgAlpha = "50", showToolTipShadow = FALSE) %>%
  fusionTheme(theme = "fusion")
  
```

---

 fusionTrendline

*Adding FusionCharts trend-line/trend-zone*


---

**Description**

<https://www.fusioncharts.com/dev/chart-guide/chart-configurations/trend-lines-and-zones>

**Usage**

```

fusionTrendline(
  fusionPlot,
  isTrendZone = FALSE,
  displayValue = NULL,
  startValue = NULL,
  endValue = NULL,
  color = "#000000",
  thickness = 2,
  alpha = "60",
  valueOnRight = TRUE,
  trendValueFont = "Arial",
  trendValueFontSize = "12",
  trendValueFontBold = TRUE,
  trendValueFontItalic = FALSE,
  trendValueAlpha = "80",
  trendValueBgColor = "#000000",
  trendValueBgAlpha = "10",
  
```



```

trendValueBorderColor = "#000000",
trendValueBorderAlpha = "80",
trendValueBorderPadding = "4",
trendValueBorderRadius = "5",
trendValueBorderThickness = "2",
trendValueBorderDashed = FALSE,
trendValueBorderDashLen = "#5A5A5A",
trendValueBorderDashGap = "1"
)

```

### Arguments

fusionPlot	fusionPlot object got by fusionPlot()
isTrendZone	Render a trend zone on a chart
displayValue	Add text next to the trend-line
startValue	Specify the data value of the starting point of the trend-line
endValue	Specify the data value of the ending point of the trend-line
color	Specify the hex code for the color of the trend-line
thickness	Specify the thickness of the trend-line(in pixels)
alpha	Specify the transparency of the trend-line
valueOnRight	Enable right position
trendValueFont	Set the font family for the trend-line display values
trendValueFontSize	Set the font size for the trend-line display values
trendValueFontBold	Make trend-line display values appear in bold
trendValueFontItalic	Make trend-line display values appear in italic
trendValueAlpha	Set the transparency for the trend-line display values
trendValueBgColor	Set the color for the background of the trend-line display values
trendValueBgAlpha	Set the transparency for the background of trend-line display values
trendValueBorderColor	Set the color for the border around the trend-line display values
trendValueBorderAlpha	Set the transparency for the border around the trend-line display values (0 to 100)
trendValueBorderPadding	Set the padding for the border around the trend-line display values
trendValueBorderRadius	Set the radius for the border around the trend-line display values

`trendValueBorderThickness`  
Set the thickness of the border around the trend-line display values

`trendValueBorderDashed`  
Specify whether the border around the trend-line display value will be drawn as a dashed line

`trendValueBorderDashLen`  
Set the length of each dash

`trendValueBorderDashGap`  
Set the gap between each dash

### Examples

```
library(fusionchartsR)
df <- data.frame(label = c("Venezuela", "Saudi", "Canada", "Russia"), value = c(290, 260, 180, 115))
df %>%
  fusionPlot(x = "label", y = "value", type = "column2d") %>%
  fusionTrendline(displayValue = "Help", startValue = "100") %>%
  fusionTheme(theme = "candy")
```

---

runDemo

*Fusioncharts Demo*

---

### Description

Running Shiny App

### Usage

```
runDemo()
```

### Examples

```
if(interactive()){
  library(shiny)
  library(fusionchartsR)
  runDemo()
}
```

---

%>%

*Pipe*

---

### **Description**

Like dplyr, fusionchartsR also uses the pipe function, %>% to turn function composition into a series of imperative statements.

### **Arguments**

lhs, rhs      A visualisation and a function to apply to it

# Index

[%>%, 27](#)

[available\\_charts, 2](#)

[fusionAnchors, 2](#)

[fusionAxis, 3](#)

[fusionBackground, 4](#)

[fusionCanvas, 6](#)

[fusionCaption, 7](#)

[fusionCustomAxis, 8](#)

[fusionCustomLegend, 11](#)

[fusionDiv, 13](#)

[fusionLegend, 15](#)

[fusionLogo, 16](#)

[fusionMultiPlot, 17](#)

[fusionMultiPlot-shiny, 18](#)

[fusionMultiPlotOutput](#)

[\(fusionMultiPlot-shiny\), 18](#)

[fusionPalette, 18](#)

[fusionPlot, 20](#)

[fusionPlotOutput, 21](#)

[fusionSubcaption, 22](#)

[fusionTheme, 23](#)

[fusionTooltip, 23](#)

[fusionTrendline, 24](#)

[renderFusionMultiPlot](#)

[\(fusionMultiPlot-shiny\), 18](#)

[renderfusionPlot \(fusionPlotOutput\), 21](#)

[runDemo, 26](#)