

Package ‘oro.nifti’

December 31, 2016

Version 0.7.2

Title Rigorous - NIfTI + ANALYZE + AFNI : Input / Output

Description Functions for the input/output and visualization of medical imaging data that follow either the ANALYZE, NIfTI or AFNI formats. This package is part of the Rigorous Analytics bundle.

Depends R (>= 2.14.0)

Suggests XML, testthat

Imports stats, bitops, splines, graphics, grDevices, methods, utils, abind, RNifti

Enhances dcemriS4, fmri, oro.dicom

License BSD_3_clause + file LICENSE

URL <http://rig.oro.us.com>, <http://rigorousanalytics.blogspot.com>

LazyData true

LazyDataCompression gzip

Collate 'auditTrail.R' 'niftiS4.R' 'analyzeS4.R' 'afniS4.R' 'is.R' 'nifti_assign.R' 'coerce.R' 'writeS4.R' 'convert_anlz.R' 'convert_nifti.R' 'cal_img.R' 'drop_img_dim.R' 'hotmetal.R' 'miscellaneous.R' 'plot.R' 'blend.R' 'readS4.R' 'remove.R' 'tim_colors.R' 'transform.R' 'wrappers.R' 'onefile.R' 'voxdim.R' 'anlz_Operators.R' 'Operators.R' 'zero_trans.R' 'aux_file.R' 'cal_max.R' 'cal_min.R' 'descrip.R' 'glmax.R' 'glmin.R' 'pixdim.R' 'qform_code.R' 'scl_inter.R' 'scl_slope.R' 'sform_code.R' 'vox_offset.R' 'bitpix.R' 'data_type.R' 'datatype.R' 'db_name.R' 'dim_.R' 'dim_info.R' 'extender.R' 'extents.R' 'img_data.R' 'intent_code.R' 'intent_name.R' 'intent_p1.R' 'intent_p2.R' 'intent_p3.R' 'magic.R' 'qoffset_x.R' 'qoffset_y.R' 'qoffset_z.R' 'quatern_b.R' 'quatern_c.R' 'quatern_d.R' 'quaternion.R' 'regular.R' 'session_error.R' 'sizeof_hdr.R' 'slice_code.R' 'slice_duration.R' 'slice_end.R' 'slice_start.R' 'srow_x.R' 'srow_y.R' 'srow_z.R' 'toffset.R' 'xyzt_units.R' 'cal_units.R' 'compressed.R' 'dim_un0.R' 'exp_date.R' 'exp_time.R'

'field_skip.R' 'funused1.R' 'funused2.R' 'funused3.R'
 'generated.R' 'hist_un0.R' 'hkey_un0.R' 'nii2oro.R' 'oro2nii.R'
 'omax.R' 'omin.R' 'orient.R' 'origin.R' 'patient_id.R'
 'scannum.R' 'smax.R' 'smin.R' 'start_field.R' 'unused1.R'
 'verified.R' 'views.R' 'vols_added.R' 'vox_units.R' 'voxres.R'
 'zzz.R'

RoxygenNote 5.0.1.9000

NeedsCompilation no

Author Brandon Whitcher [aut, cre],
 Volker Schmid [aut],
 Andrew Thornton [aut],
 Karsten Tabelow [ctb],
 Jon Clayden [ctb],
 John Muschelli [ctb]

Maintainer Brandon Whitcher <bwhitcher@gmail.com>

Repository CRAN

Date/Publication 2016-12-31 16:32:14

R topics documented:

afni-class	5
anzl	7
anzl-class	8
anzl-nifti-ops	11
as.anzl	12
as.nifti	12
Audit Trails	13
audit.trail-methods	16
aux_file-methods	17
bitpix-methods	18
blend	19
calibrateImage	20
cal_max-methods	21
cal_min-methods	23
cal_units-methods	24
coerce-methods	25
compressed-methods	26
Convert ANALYZE Codes	27
Convert NIFTI Codes	28
convert.scene	30
datatype-methods	31
data_type-methods	32
db_name-methods	33
descrip-methods	34
dim_-methods	36
dim_info-methods	37

dim_un0-methods	38
dropImageDimension	39
exp_date-methods	40
exp_time-methods	41
extender-methods	42
extents-methods	43
field_skip-methods	44
funused1-methods	45
funused2-methods	46
funused3-methods	47
generated-methods	48
glmax-methods	49
glmin-methods	50
hist_un0-methods	51
hkey_un0-methods	52
hotmetal	53
image-methods	54
img_data-methods	55
integerTranslation	56
intent_code-methods	57
intent_name-methods	58
intent_p1-methods	59
intent_p2-methods	60
intent_p3-methods	61
is.afni	62
is.anlz	63
is.nifti	63
magic-methods	64
nifti	65
nifti-class	66
nifti-operators	68
niftiAuditTrail-class	69
niftiExtension-class	70
niftiExtensionSection-class	71
nifti_assign-methods	71
nii2oro	72
nsli	72
omax-methods	73
omin-methods	74
onefile	75
orient-methods	76
orientation-methods	77
origin-methods	78
oro2nii	79
orthographic-methods	79
overlay-methods	81
patient_id-methods	83
performPermutation	84

pixdim-methods	85
qform_code-methods	86
qoffset_x-methods	87
qoffset_y-methods	88
qoffset_z-methods	89
quaternion2rotation	90
quatern_b-methods	91
quatern_c-methods	92
quatern_d-methods	93
readAFNI	94
readANALYZE	96
readNIfTI	97
regular-methods	99
reorient	100
resetSlopeIntercept	101
rmnii.gz	101
scannum-methods	102
scl_inter-methods	103
scl_slope-methods	104
session_error-methods	105
sform_code-methods	106
sizeof_hdr-methods	107
slice_code-methods	108
slice_duration-methods	109
slice_end-methods	110
slice_start-methods	112
smax-methods	113
smin-methods	114
srow_x-methods	115
srow_y-methods	116
srow_z-methods	117
start_field-methods	118
tim.colors	119
toffset-methods	120
translateCoordinate	121
unused1-methods	122
verified-methods	123
views-methods	124
vols_added-methods	125
voxdim	126
voxres	126
vox_offset-methods	127
vox_units-methods	128
writeAFNI-methods	129
writeANALYZE-methods	131
writeNIfTI-methods	132
xyzt2space	135
xyzt_units-methods	136

afni-class	<i>Class "afni"</i>
------------	---------------------

Description

The AFNI class for medical imaging data.

Usage

```
## S4 method for signature 'afni'
show(object)
```

Arguments

object An object of class afni.

Objects from the Class

Objects can be created by calls of the form `new("afni", data, dim, dimnames, ...)`.

Slots

```
.Data: Object of class "array" contains the imaging data
DATASET_RANK: Object of class "integer"
DATASET_DIMENSIONS: Object of class "integer"
TYPESTRING: Object of class "character"
SCENE_DATA: Object of class "integer"
ORIENT_SPECIFIC: Object of class "integer"
ORIGIN: Object of class "numeric"
DELTA: Object of class "numeric"
TAXIS_NUMS: Object of class "integer"
TAXIS_FLOATS: Object of class "numeric"
TAXIS_OFFSETS: Object of class "numeric"
IDCODE_STRING: Object of class "character"
IDCODE_DATE: Object of class "character"
BYTEORDER_STRING: Object of class "character"
BRICK_STATS: Object of class "numeric"
BRICK_TYPES: Object of class "integer"
BRICK_FLOAT_FACS: Object of class "numeric"
BRICK_LABS: Object of class "character"
BRICK_STATAUX: Object of class "numeric"
```

STAT_AUX: Object of class "numeric"
HISTORY_NOTE: Object of class "character"
NOTES_COUNT: Object of class "integer"
NOTE_NUMBER: Object of class "character"
TAGALIGN_MATVEC: Object of class "numeric"
VOLREG_MATVEC: Object of class "array"
VOLREG_ROTCOM: Object of class "character"
VOLREG_CENTER_OLD: Object of class "numeric"
VOLREG_CENTER_BASE: Object of class "numeric"
VOLREG_ROT_PARENT_IDCODE: Object of class "character"
VOLREG_ROT_PARENT_NAME: Object of class "character"
VOLREG_GRID_PARENT_IDCODE: Object of class "character"
VOLREG_GRID_PARENT_NAME: Object of class "character"
VOLREG_INPUT_IDCODE: Object of class "character"
VOLREG_INPUT_NAME: Object of class "character"
VOLREG_BASE_IDCODE: Object of class "character"
VOLREG_BASE_NAME: Object of class "character"
VOLREG_ROTCOM_NUM: Object of class "integer"
IDCODE_ANAT_PARENT: Object of class "character"
TO3D_ZPAD: Object of class "integer"
IDCODE_WARP_PARENT: Object of class "character"
WARP_TYPE: Object of class "integer"
WARP_DATA: Object of class "numeric"
MARKS_XYZ: Object of class "numeric"
MARKS_LAB: Object of class "character"
MARKS_HELP: Object of class "character"
MARKS_FLAGS: Object of class "integer"
TAGSET_NUM: Object of class "integer"
TAGSET_FLOATS: Object of class "numeric"
TAGSET_LABELS: Object of class "character"
LABEL_1: Object of class "character"
LABEL_2: Object of class "character"
DATASET_NAME: Object of class "character"
DATASET_KEYWORDS: Object of class "character"
BRICK_KEYWORDS: Object of class "character"

Extends

Class `"array"`, from data part.
 Class `"matrix"`, by class `"array"`, distance 2, with explicit test and coerce.
 Class `"structure"`, by class `"array"`, distance 2.
 Class `"vector"`, by class `"array"`, distance 3, with explicit coerce.
 Class `"vector"`, by class `"array"`, distance 5, with explicit test and coerce. `@export @rdname afni-class`

Author(s)

Karsten Tabelow <karsten.tabelow@wias-berlin.de>

References

AFNI
<http://afni.nimh.nih.gov/pub/dist/src/README.attributes>

See Also

`nifti`, `anlz`

Examples

```
showClass("afni")
```

anlz

Constructor for Analyze

Description

Constructor for Analyze class objects.

Usage

```
anlz(img = array(0, dim = rep(1, 4)), dim, datatype = 2, ...)
```

Arguments

<code>img</code>	is a multidimensional array of data.
<code>dim</code>	is the dimension of the data (default = missing).
<code>datatype</code>	is an integer that denotes the type of data contained in each voxel. See the function <code>convert.datatype.anlz</code> or the ANALYZE documentation for more details.
<code>...</code>	allows for additional ‘slots’ to be specified.

Value

An object of class anlz.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>

See Also

[anlz](#), [nifti](#), [nifti](#), [convert.datatype.anlz](#)

Examples

```
aim <- anlz() # default
```

anlz-class

Class "anlz"

Description

The ANALYZE class for medical imaging data.

Usage

```
## S4 method for signature 'anlz'  
show(object)
```

Arguments

object An object of class anlz.

Objects from the Class

Objects can be created by calls of the form `new("anlz", data, dim, dimnames, ...)` or by calling the `anlz` function.

Slots

.Data: Object of class "array" contains the imaging data
sizeof_hdr: Object of class "numeric" contains the size of the header (= 348)
data_type: Object of class "character"
db_name: Object of class "character"
extents: Object of class "numeric"
session_error: Object of class "numeric"
regular: Object of class "character"
hkey_un0: Object of class "character"
dim_: Object of class "vector" contains the dimensions of the imaging data
vox_units: Object of class "character"
cal_units: Object of class "character"
unused1: Object of class "numeric"
datatype: Object of class "numeric"
bitpix: Object of class "numeric" contains the number of bits per voxel (pixel)
dim_un0: Object of class "numeric"
pixdim: Object of class "vector" contains the real-world dimensions of the imaging data
vox_offset: Object of class "numeric"
funused1: Object of class "numeric"
funused2: Object of class "numeric"
funused3: Object of class "numeric"
cal_max: Object of class "numeric" contains the maximum display intensity
cal_min: Object of class "numeric" contains the minimum display intensity
compressed: Object of class "numeric"
verified: Object of class "numeric"
glmax: Object of class "numeric"
glmin: Object of class "numeric"
descrip: Object of class "character"
aux_file: Object of class "character"
orient: Object of class "character"
origin: Object of class "numeric"
generated: Object of class "character"
scannum: Object of class "character"
patient_id: Object of class "character"
exp_date: Object of class "character"
exp_time: Object of class "character"
hist_un0: Object of class "character"

views: Object of class "numeric"
vols_added: Object of class "numeric"
start_field: Object of class "numeric"
field_skip: Object of class "numeric"
omax: Object of class "numeric"
omin: Object of class "numeric"
smax: Object of class "numeric"
smin: Object of class "numeric"

Extends

Class "array", from data part.
Class "matrix", by class "array", distance 2, with explicit test and coerce.
Class "structure", by class "array", distance 2.
Class "vector", by class "array", distance 3, with explicit coerce.
Class "vector", by class "array", distance 5, with explicit test and coerce.

Methods

image signature(x = "anlz"): displays the image(s).
show signature(object = "anlz"): prints out a summary of the imaging data.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>

See Also

[nifti](#), [niftiExtension](#)

Examples

```
showClass("anlz")
```

Description

Overloaded operators for anlz and nifti objects

Usage

```
## S4 method for signature 'anlz,anlz'  
Ops(e1, e2)  
  
## S4 method for signature 'anlz,numeric'  
Ops(e1, e2)  
  
## S4 method for signature 'numeric,anlz'  
Ops(e1, e2)  
  
## S4 method for signature 'nifti,anlz'  
Ops(e1, e2)  
  
## S4 method for signature 'anlz,nifti'  
Ops(e1, e2)
```

Arguments

e1	object
e2	object

Author(s)

John Muschelli <muschellij2@gmail.com>

Examples

```
img01 <- anlz(array(1:64, c(4,4,4,1)), datatype=4)  
img02 <- anlz(array(64:1, c(4,4,4,1)), datatype=4)  
is.anlz(img01 + img02)  
is.anlz(sqrt(2) * img01)  
is.anlz(img02 / pi)
```

as.anlz	<i>as.anlz</i>
---------	----------------

Description

Internal function that converts multidimensional arrays to ANALYZE class objects.

Usage

```
as.anlz(from, value = NULL, verbose = FALSE)
```

Arguments

from	is the object to be converted.
value	is the nifti class object to use as a template for various ANALYZE header information.
verbose	is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.

Value

An object of class anlz.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>,
 Brandon Whitcher <bwhitcher@gmail.com>

as.nifti	<i>as.nifti</i>
----------	-----------------

Description

Internal function that converts multidimensional arrays to NIFTI class objects.

Usage

```
as.nifti(from, value = NULL, verbose = FALSE)
```

Arguments

from	is the object to be converted.
value	is the anlz class object to use as a template for various NIFTI header information.
verbose	is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.

Value

An object of class `nifti`.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>.
Brandon Whitcher <bwhitcher@gmail.com>

Audit Trails

Facilitate the Creation and Modification of Audit Trails

Description

Facilitate the creation and modification of audit trails for NIFTI class objects.

Usage

```
oro.nifti.info(type)

enableAuditTrail()

getLastCallWithName(functionName)

newAuditTrail()

niftiExtensionToAuditTrail(nim, workingDirectory = NULL, filename = NULL,
    call = NULL)

niftiAuditTrailSystemNode(type = "system-info", workingDirectory = NULL,
    filename = NULL, call = NULL)

niftiAuditTrailSystemNodeEvent(trail, type = NULL, call = NULL,
    workingDirectory = NULL, filename = NULL, comment = NULL)

niftiAuditTrailCreated(history = NULL, call = NULL,
    workingDirectory = NULL, filename = NULL)

niftiAuditTrailEvent(trail, type = NULL, call = NULL, comment = NULL)
```

Arguments

<code>type</code>	An identifier to add some meaning to the event.
<code>functionName</code>	The name of a function on the call stack.
<code>nim</code>	is an object of class <code>niftiAuditTrail</code> or can be converted to such.
<code>workingDirectory</code>	The working directory associated with the 'filename'.

filename	The filename associated with the nifti object.
call	A call, function name in the call-stack or a string.
trail	The XMLAbstractNode representing the audit trail or the niftiAuditTrail object with a trail that will be amended.
comment	Some textual comment
history	An XMLAbstractNode to store historical events for inclusion in the 'trail'.

Details

The function `oro.nifti.info` is used to find the ecode or the XML namespace relevant to the audit trail.

The function `enableAuditTrail` is turned "off" by default to minimize package dependencies. Should one wish to turn "on" the audit trail functionality, then one should set the option `NIFTI.audit.trail` to `TRUE` and call the function `enableAuditTrail`. Setting the option `NIFTI.audit.trail` to `FALSE` will disable the audit trail.

The function `newAuditTrail` returns an `XMLAbstractNode` representing the root node of an audit trail. This is mostly intended as an internal function.

The function `niftiExtensionToAuditTrail` takes an object representing a NIFTI object, casts it as a `niftiAuditTrail` and checks if there is an extension (a `niftiExtensionSection`) with ecode equal to `oro.nifti.info("ecode")`; i.e. has a extension with data representing a serialized audit trail. The function will then strip the object of this extension parsing the serialized edata into an audit trail and adding a 'read' event to the trail.

The function `niftiAuditTrailToExtension` takes a `niftiAuditTrail` and returns a `niftiExtensionSection` with edata containing the serialized form of the audit trail after adding a 'saved' event to the trail.

The function `niftiAuditTrailSystemNodeEvent` adds an element with name equal to `type` to the trail. It uses the `niftiAuditTrailSystemNode` function to create the node.

The function `niftiAuditTrailSystemNode` is an internal function creating an `XMLAbstractNode` element with name `type` and attributes giving information about the R system and library. The `filename` and `call` will also be added as attributes if available.

The function `niftiAuditTrailEvent` adds an element with name `event` to the trail. The arguments `type`, `filename`, `call` are added as attributes and the `comment` is the text value of the element.

The function `niftiAuditTrailCreated` will create a new audit trail containing a system node element created with the child `history` with the contents `history`. If the last element of the `history` given is an event with `type="processing"`, then this node will be removed from the `history` and its `call` attribute will be used as the value of the `call` attribute on the created node.

The function `getLastCallWithName` will search the call stack for a call of the function `functionName`, returning last call to that function if possible. It will default to the call of the function which called the function which called `getLastCallWithName` if there was no such call (and if there was no such call it will return the call of itself).

Note

These functions are mostly intended to be used internally in order to document the changes that occur to NIFTI objects due to functions that are audit-trail aware. However, as the precise manner

in which these functions are used is not documented anywhere else, we shall proceed to describe which functions are audit-trail aware and how they interact with the audit trail.

`as.nifti` and its S4 alias `as(nim, "nifti")` will always produce `niftiAuditTrail` objects if the functionality is turned on. The function `niftiAuditTrailCreated` will be used and if an exemplar object is provided (e.g., `as.nifti(array, niftiExemplar)`) then the trail of the exemplar will be used as the history.

`readNIFTI` and `writeNIFTI` also always produce `niftiAuditTrail` objects if the functionality is turned on. The functions `niftiExtensionToAuditTrail` and `niftiAuditTrailToExtension` are used internally by these functions to facilitate this behaviour.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net> and Brandon Whitcher <bwhitcher@gmail.com>

Examples

```
## A good example of the use of these functions is shown by this
## wrapper function which takes a function fun(nim, ...) returning
## lists of arrays which are nifti-ized using as(...)
options("niftiAuditTrail"=TRUE)
enableAuditTrail()

wrapper <- function(functionToWrap, nameOfCallingFunction, nim, ...) {
  if (!is(nim, "nifti"))
    nim <- as(nim, "nifti")

  if (is(nim, "niftiAuditTrail")) {
    ## This will force as(...) to set the call which created the
    ## results to the calling function's call rather than
    ## as(result, nifti) as it would otherwise do
    slot(nim, "trail") <- niftiAuditTrailEvent(slot(nim, "trail"), "processing",
                                              nameOfCallingFunction)
  }

  result <- functionToWrap(nim, ...)
  as(result, "nifti") <- nim
  return(result)
}

## An example of how wrapper is used follows:
functionToWrap <- function(ignored, x, y) {
  return (array(1, dim=c(x,y)))
}

## The nifti-ized form
niftiizedForm <- function(nim,...) {
  return(wrapper(functionToWrap, "niftiizedForm", nim, ...))
}

## Not run:
if (isTRUE(getOption("niftiAuditTrail"))) {
```

```
    print(slot(as.nifti(functionToWrap(nifti()), 4, 4), nifti()), "trail")
    print(slot(niftiizedForm(nifti()), 4, 4), "trail")
  }

## End(Not run)
```

audit.trail-methods *Extract or Replace NIFTI Audit Trail*

Description

Operators that act on the audit trail (XML) in the NIFTI header.

Usage

```
audit.trail(object)

## S4 method for signature 'nifti'
audit.trail(object)

audit.trail(object) <- value

## S4 replacement method for signature 'nifti'
audit.trail(object) <- value
```

Arguments

object	is of class nifti.
value	Value to assign to trail slot

Methods

object = "nifti" Extract or replace NIFTI audit trail.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>

aux_file-methods *Extract Image Attribute aux_file*

Description

Methods that act on the aux_file field in the NIFTI/ANALYZE header.

Usage

```
aux_file(object)

## S4 method for signature 'nifti'
aux_file(object)

## S4 method for signature 'anlz'
aux_file(object)

aux_file(object) <- value

## S4 replacement method for signature 'nifti'
aux_file(object) <- value

## S4 replacement method for signature 'anlz'
aux_file(object) <- value

aux.file(object)

## S4 method for signature 'nifti'
aux.file(object)

## S4 method for signature 'anlz'
aux.file(object)

aux.file(object) <- value

## S4 replacement method for signature 'nifti'
aux.file(object) <- value

## S4 replacement method for signature 'anlz'
aux.file(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the aux_file field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

Examples

```
## Not run:
url <- "http://nifti.nimh.nih.gov/nifti-1/data/avg152T1_RL_nifti.nii.gz"
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "mniRL.nii.gz")
download.file(url, urlfile, quiet=TRUE)

## End(Not run)
options("niftiAuditTrail"=FALSE)

urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "mniRL.nii.gz")
mniRL <- readNIfTI(urlfile)
aux.file(mniRL)
aux.file(mniRL) <- "avg152T1_RL_nifti"
aux.file(mniRL)
```

bitpix-methods

Extract Image Attribute bitpix

Description

Methods that act on the bitpix field in the NIfTI/ANALYZE header.

Usage

```
bitpix(object)

## S4 method for signature 'nifti'
bitpix(object)

## S4 method for signature 'anlz'
```

```
bitpix(object)

bitpix(object) <- value

## S4 replacement method for signature 'nifti'
bitpix(object) <- value

## S4 replacement method for signature 'anlz'
bitpix(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the bitpix field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

blend	<i>Merge Two Nifti or ANALYZE Volumes</i>
-------	---

Description

Two volumes of medical imaging data are merged together in the superior-inferior (or \$z\$) direction. One assumes that there is at least one slice that overlaps between the two volumes.

Usage

```
blendVolumes(x, y, seqX, seqY, method = "linear")

## S4 method for signature 'nifti,nifti'
blend(x, y, seqX, seqY, method = "linear")

## S4 method for signature 'anlz,anlz'
```

```
blend(x, y, seqX, seqY, method = "linear")

## S4 method for signature 'anzl,nifti'
blend(x, y, seqX, seqY, method = "linear")

## S4 method for signature 'nifti,anzl'
blend(x, y, seqX, seqY, method = "linear")
```

Arguments

`x`, `y` are objects of class `nifti` or `anzl`.
`seqX`, `seqY` are vectors that provide the z -coordinate values for the two imaging volumes.
`method` is the type of weighing to use when combining information where there is an overlap (default = "linear").

Value

A single volume that blends the voxel-wise information from `x` and `y`.

Methods

```
x = "nifti", y = "nifti" Merge x and y.  

x = "anzl", y = "anzl" Merge x on y.  

x = "nifti", y = "anzl" Merge x on y.  

x = "anzl", y = "nifti" Merge x and y.
```

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

See Also

[image-methods](#), [overlay-methods](#)

calibrateImage

Set Minimum/Maximum Values for NIFTI data

Description

Rescales image `cal_max` and `cal_min` slots to be the max and min, respectively, of an object of class `nifti`, with `na.rm = TRUE`. This is so that when images are rendered/written, the values correspond to those in the array (stored in `.Data` slot) are plotted on correct greyscale and no error is given by `writeNIFTI`.

Usage

```
calibrateImage(img, infok = TRUE)
```

```
cal_img(img, infok = TRUE)
```

Arguments

`img` is a nifti object.

`infok` is a logical value whether or not Inf and -Inf are acceptable (default = TRUE). If FALSE and max or min is infinity, then `cal_min` or `cal_max` is set to infinity (negative or positive), respectively.

Value

An object of class nifti.

Author(s)

John Muschelli <muschellij2@gmail.com>

cal_max-methods

Extract Image Attribute cal_max

Description

Methods that act on the `cal_max` field in the NIFTI/ANALYZE header.

Usage

```
cal_max(object)

## S4 method for signature 'nifti'
cal_max(object)

## S4 method for signature 'anlz'
cal_max(object)

cal_max(object) <- value

## S4 replacement method for signature 'nifti'
cal_max(object) <- value

## S4 replacement method for signature 'anlz'
cal_max(object) <- value

cal.max(object)
```

```
## S4 method for signature 'nifti'  
cal.max(object)  
  
## S4 method for signature 'anlz'  
cal.max(object)  
  
cal.max(object) <- value  
  
## S4 replacement method for signature 'nifti'  
cal.max(object) <- value  
  
## S4 replacement method for signature 'anlz'  
cal.max(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the cal_max field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

Examples

```
## Not run:  
url <- "http://nifti.nimh.nih.gov/nifti-1/data/avg152T1_LR_nifti.nii.gz"  
urlfile <- file.path(system.file("nifti", package="oro.nifti"),  
                      "mniLR.nii.gz")  
download.file(url, urlfile, quiet=TRUE)  
  
## End(Not run)  
urlfile <- file.path(system.file("nifti", package="oro.nifti"),  
                      "mniLR.nii.gz")  
mniLR <- readNIFTI(urlfile)  
cal.max(mniLR)
```

cal_min-methods *Extract Image Attribute cal_min*

Description

Methods that act on the `cal_min` field in the NIFTI/ANALYZE header.

Usage

```
cal_min(object)

## S4 method for signature 'nifti'
cal_min(object)

## S4 method for signature 'anlz'
cal_min(object)

cal_min(object) <- value

## S4 replacement method for signature 'nifti'
cal_min(object) <- value

## S4 replacement method for signature 'anlz'
cal_min(object) <- value

cal.min(object)

## S4 method for signature 'nifti'
cal.min(object)

## S4 method for signature 'anlz'
cal.min(object)

cal.min(object) <- value

## S4 replacement method for signature 'nifti'
cal.min(object) <- value

## S4 replacement method for signature 'anlz'
cal.min(object) <- value
```

Arguments

<code>object</code>	is an object of class <code>nifti</code> or <code>anlz</code> .
<code>value</code>	is the value to assign to the <code>cal_min</code> field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

Examples

```
## Not run:
url <- "http://nifti.nimh.nih.gov/nifti-1/data/avg152T1_LR_nifti.nii.gz"
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "mniLR.nii.gz")
download.file(url, urlfile, quiet=TRUE)

## End(Not run)
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "mniLR.nii.gz")
mniLR <- readNIFTI(urlfile)
cal.min(mniLR)
```

cal_units-methods

Extract Image Attribute cal_units

Description

Methods that act on the cal_units field in the NIFTI/ANALYZE header.

Usage

```
cal_units(object)

## S4 method for signature 'anlz'
cal_units(object)

cal_units(object) <- value

## S4 replacement method for signature 'anlz'
cal_units(object) <- value
```



```

cal.units(object)

## S4 method for signature 'anlz'
cal.units(object)

cal.units(object) <- value

## S4 replacement method for signature 'anlz'
cal.units(object) <- value

```

Arguments

object is an object of class `nifti` or `anlz`.
value is the value to assign to the `cal_units` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

coerce-methods

Force an Object to Belong to the ANALYZE or NIFTI Class

Description

Methods for function `coerce` in Package ‘methods’.

Arguments

object is an object of class `array` or inherits from `array`.
Class is the name of the class to which ‘object’ should be coerced; i.e., `nifti`.
value is the values used to modify ‘object’ (see the discussion below). You should supply an object with class `nifti` in order to pass NIFTI header information.
from is the object to be converted.
value is the `nifti` class object to use as a template for various ANALYZE/NIFTI header information.

`verbose` is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.

Value

An object of class `anlz` or `nifti`.

Methods

from = "anlz", to = "nifti" An object of class `anlz` is coerced into a NIfTI object.

from = "array", to = "anlz" An object of class `array` is coerced into an ANALYZE object.

from = "array", to = "nifti" An object of class `array` is coerced into a NIfTI object.

from = "list", to = "anlz" All objects of class `array` in the list are coerced into ANALYZE objects. All other objects are left alone. The original list structure is retained.

from = "list", to = "nifti" All objects of class `array` in the list are coerced into NIfTI objects. All other objects are left alone. The original list structure is retained.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>,
Brandon Whitcher <bwhitcher@gmail.com>

See Also

[as](#)

compressed-methods *Extract Image Attribute* compressed

Description

Methods that act on the compressed field in the NIfTI/ANALYZE header.

Usage

```
compressed(object)

## S4 method for signature 'anlz'
compressed(object)

compressed(object) <- value

## S4 replacement method for signature 'anlz'
compressed(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
value is the value to assign to the compressed field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

Convert ANALYZE Codes *Convert ANALYZE Codes*

Description

Codes that appear in the ANALYZE header are mapped to meaningful character strings.

Usage

```
convert.bitpix.anlz(bitpix = NULL)

convert.datatype.anlz(datatype.code = NULL)

convert.orient.anlz(orientation)
```

Arguments

bitpix is the bit-per-pixel code.
datatype.code defines data type.
orientation defines the orientation.

Details

switch statements are used to map a numeric code to the appropriate string.

Value

A character string.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>

See Also

[convert.datatype](#), [convert.bitpix](#), [convert.intent](#), [convert.form](#), [convert.units](#), [convert.slice](#)

Examples

```
## 4 = SIGNED_SHORT
convert.datatype.anlz(4)
## 16 = FLOAT
convert.datatype.anlz(16)
## 2 = "sagittal unflipped"
convert.orient.anlz(2)
## 4 = "coronal flipped"
convert.orient.anlz(4)
```

Convert NIFTI Codes *Convert Nifti Codes*

Description

Codes that appear in the ANALYZE header are mapped to meaningful character strings.

Usage

```
convert.bitpix(bitpix = NULL)

convert.datatype(datatype.code = NULL)

convert.intent(intent.code = NULL)

convert.form(form.code)

convert.units(units, inverse = FALSE)

convert.slice(slice.code)
```

Arguments

<code>bitpix</code>	is the bit-per-pixel code.
<code>datatype.code</code>	defines data type.
<code>intent.code</code>	is the NIfTI intent code.
<code>form.code</code>	is the (x, y, z) coordinate system.
<code>units</code>	is the units of <code>pixdim[1..4]</code> .
<code>inverse</code>	is a logical value that denotes the direction of unit conversion.
<code>slice.code</code>	is the slice timing order.

Details

`switch` statements are used to map a numeric code to the appropriate string.

Value

A character string.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

References

Neuroimaging Informatics Technology Initiative (NIfTI)
<http://nifti.nimh.nih.gov/>

Examples

```
## 4 = SIGNED_SHORT
convert.datatype.anlz(4)
## 16 = FLOAT
convert.datatype.anlz(16)
## 2 = "sagittal unflipped"
convert.orient.anlz(2)
## 4 = "coronal flipped"
convert.orient.anlz(4)
```

convert.scene	<i>Convert AFNI data codes</i>
---------------	--------------------------------

Description

Codes that appear in the AFNI header are mapped to meaningful character strings.

Usage

```
convert.scene(scene.data, typestring)
```

Arguments

scene.data	defines data type.
typestring	defines whether func or anat data.

Details

switch statements are used to map a numeric code to the appropriate string.

Value

A character string.

Author(s)

Karsten Tabelow <karsten.tabelow@wias-berlin.de>

References

AFNI
<http://afni.nimh.nih.gov/pub/dist/src/README.attributes>

See Also

[convert.datatype.anlz](#), [convert.orient.anlz](#)

Examples

```
## 4 = CT for anatomic data  
convert.scene(4, "3DIM_HEAD_ANAT")
```

datatype-methods *Extract Image Attribute* datatype

Description

Methods that act on the datatype field in the NIFTI/ANALYZE header.

Usage

```
datatype(object)

## S4 method for signature 'nifti'
datatype(object)

## S4 method for signature 'anlz'
datatype(object)

datatype(object) <- value

## S4 replacement method for signature 'nifti'
datatype(object) <- value

## S4 replacement method for signature 'anlz'
datatype(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the datatype field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

data_type-methods *Extract Image Attribute data_type*

Description

Methods that act on the data_type field in the NIFTI/ANALYZE header.

Usage

```
data_type(object)

## S4 method for signature 'nifti'
data_type(object)

## S4 method for signature 'anlz'
data_type(object)

data_type(object) <- value

## S4 replacement method for signature 'nifti'
data_type(object) <- value

## S4 replacement method for signature 'anlz'
data_type(object) <- value

data.type(object)

## S4 method for signature 'nifti'
data.type(object)

## S4 method for signature 'anlz'
data.type(object)

data.type(object) <- value

## S4 replacement method for signature 'nifti'
data.type(object) <- value

## S4 replacement method for signature 'anlz'
data.type(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the data_type field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

db_name-methods	<i>Extract Image Attribute db_name</i>
-----------------	--

Description

Methods that act on the db_name field in the NIFTI/ANALYZE header.

Usage

```
db_name(object)

## S4 method for signature 'nifti'
db_name(object)

## S4 method for signature 'anlz'
db_name(object)

db_name(object) <- value

## S4 replacement method for signature 'nifti'
db_name(object) <- value

## S4 replacement method for signature 'anlz'
db_name(object) <- value

db.name(object)

## S4 method for signature 'nifti'
db.name(object)

## S4 method for signature 'anlz'
db.name(object)
```

```
db.name(object) <- value

## S4 replacement method for signature 'nifti'
db.name(object) <- value

## S4 replacement method for signature 'anlz'
db.name(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the db_name field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

descrip-methods	<i>Extract Image Attribute descrip</i>
-----------------	--

Description

Methods that act on the descrip field in the NIFTI/ANALYZE header.

Usage

```
descrip(object)

## S4 method for signature 'nifti'
descrip(object)

## S4 method for signature 'anlz'
descrip(object)
```

```
descrip(object) <- value

## S4 replacement method for signature 'nifti'
descrip(object) <- value

## S4 replacement method for signature 'anlz'
descrip(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the descrip field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

Examples

```
## Not run:
url <- "http://nifti.nimh.nih.gov/nifti-1/data/avg152T1_LR_nifti.nii.gz"
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                     "mniLR.nii.gz")
download.file(url, urlfile, quiet=TRUE)

## End(Not run)
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                     "mniLR.nii.gz")
mniLR <- readNIFTI(urlfile)
descrip(mniLR)
## Not run:
descrip(mniLR) <- paste(descrip(mniLR), version$version.string, sep="; ")
descrip(mniLR)

## End(Not run)
```

dim_-methods

Extract Image Attribute dim_

Description

Methods that act on the dim_ field in the NIFTI/ANALYZE header.

Usage

```
dim_(object)

## S4 method for signature 'nifti'
dim_(object)

## S4 method for signature 'anlz'
dim_(object)

dim_(object) <- value

## S4 replacement method for signature 'nifti'
dim_(object) <- value

## S4 replacement method for signature 'anlz'
dim_(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the dim_ field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

dim_info-methods *Extract Image Attribute dim_info*

Description

Methods that act on the dim_info field in the NIFTI/ANALYZE header.

Usage

```
dim_info(object)

## S4 method for signature 'nifti'
dim_info(object)

dim_info(object) <- value

## S4 replacement method for signature 'nifti'
dim_info(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the dim_info field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

dim_un0-methods *Extract Image Attribute dim_un0*

Description

Methods that act on the dim_un0 field in the NIFTI/ANALYZE header.

Usage

```
dim_un0(object)

## S4 method for signature 'anzl'
dim_un0(object)

dim_un0(object) <- value

## S4 replacement method for signature 'anzl'
dim_un0(object) <- value
```

Arguments

object is an object of class nifti or anzl.
value is the value to assign to the dim_un0 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

dropImageDimension *Drop Image Dimension*

Description

Drops a dimension of an image that has one-dimension and sets respective values to 0 in pixdim or 1 in dim.

Usage

```
dropImageDimension(img, onlylast = TRUE, warn = TRUE)
```

```
drop_img_dim(img, onlylast = TRUE, warn = TRUE)
```

Arguments

img	nifti object
onlylast	is a logical variable (default = TRUE). Drop the dimension only if it is the last dimension. For example, if dim is 10x10x1x10 then no dimension is dropped, but if dim is 10x10x10x1 then it will be changed to 10x10x10.
warn	produces a text output if the number of dimensions is under three.

Value

Object of class nifti

Examples

```
nim <- nifti(array(rnorm(10^3), dim = rep(10, 3)))
nim2 <- nifti(array(rnorm(10^3), dim = c(10, 10, 1, 10)))
dropImageDimension(nim2)
dropImageDimension(nim2, onlylast = FALSE)
nim3 <- nifti(array(rnorm(10^3), dim = c(10, 10, 10, 1)))
dropImageDimension(nim3)
dropImageDimension(nim3, onlylast = FALSE) # the same as above
nim4 <- nifti(array(rnorm(10^3), dim = c(10, 10, 10, 1, 10)))
dim(nim4[, , 1, ])
dim(nim4[, , 1, , drop=TRUE])
dropImageDimension(nim4)

nim5 <- nifti(array(rnorm(10^4), dim = c(1, 10, 10, 10, 1, 10)))
dropImageDimension(nim5)
dropImageDimension(nim5, onlylast = FALSE)

nim6 <- nifti(array(rnorm(10^3), dim = c(1, 10, 10, 10, 1, 1)))
dropImageDimension(nim6)
## Not run:
```

```

## 27 scans of Colin Holmes (MNI) brain co-registered and averaged
## NIfTI two-file format
URL <- "http://imaging.mrc-cbu.cam.ac.uk/downloads/Colin/colin_1mm.tgz"
urlfile <- file.path(tempdir(), "colin_1mm.tgz")
download.file(URL, dest=urlfile, quiet=TRUE)
untar(urlfile, exdir=tempdir())
colin <- readNIfTI(file.path(tempdir(), "colin_1mm"))
dim(colin)
dim_(colin)
pixdim(colin)
# this will error
writeNIfTI(colin, filename = tempfile())
colin <- dropImageDimension(colin)
writeNIfTI(colin, filename = tempfile())

## End(Not run)

```

exp_date-methods *Extract Image Attribute exp_date*

Description

Methods that act on the exp_date field in the NIfTI/ANALYZE header.

Usage

```

exp_date(object)

## S4 method for signature 'anlz'
exp_date(object)

exp_date(object) <- value

## S4 replacement method for signature 'anlz'
exp_date(object) <- value

```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the exp_date field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

exp_time-methods	<i>Extract Image Attribute exp_time</i>
------------------	---

Description

Methods that act on the exp_time field in the NIfTI/ANALYZE header.

Usage

```
exp_time(object)

## S4 method for signature 'anzl'
exp_time(object)

exp_time(object) <- value

## S4 replacement method for signature 'anzl'
exp_time(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the exp_time field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

extender-methods *Extract Image Attribute* extender

Description

Methods that act on the extender field in the NIFTI/ANALYZE header.

Usage

```
extender(object)

## S4 method for signature 'nifti'
extender(object)

extender(object) <- value

## S4 replacement method for signature 'nifti'
extender(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the extender field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

extents-methods *Extract Image Attribute* extents

Description

Methods that act on the extents field in the NIfTI/ANALYZE header.

Usage

```
extents(object)

## S4 method for signature 'nifti'
extents(object)

## S4 method for signature 'anlz'
extents(object)

extents(object) <- value

## S4 replacement method for signature 'nifti'
extents(object) <- value

## S4 replacement method for signature 'anlz'
extents(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the extents field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

field_skip-methods *Extract Image Attribute field_skip*

Description

Methods that act on the field_skip field in the NIFTI/ANALYZE header.

Usage

```
field_skip(object)

## S4 method for signature 'anzl'
field_skip(object)

field_skip(object) <- value

## S4 replacement method for signature 'anzl'
field_skip(object) <- value

field.skip(object)

## S4 method for signature 'anzl'
field.skip(object)

field.skip(object) <- value

## S4 replacement method for signature 'anzl'
field.skip(object) <- value
```

Arguments

object is an object of class nifti or anzl.
value is the value to assign to the field_skip field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

funused1-methods	<i>Extract Image Attribute</i> funused1
------------------	---

Description

Methods that act on the funused1 field in the NIfTI/ANALYZE header.

Usage

```
funused1(object)

## S4 method for signature 'anzl'
funused1(object)

funused1(object) <- value

## S4 replacement method for signature 'anzl'
funused1(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the funused1 field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

funused2-methods *Extract Image Attribute funused2*

Description

Methods that act on the funused2 field in the NIFTI/ANALYZE header.

Usage

```
funused2(object)

## S4 method for signature 'anlz'
funused2(object)

funused2(object) <- value

## S4 replacement method for signature 'anlz'
funused2(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the funused2 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

funused3-methods *Extract Image Attribute funused3*

Description

Methods that act on the funused3 field in the NIFTI/ANALYZE header.

Usage

```
funused3(object)

## S4 method for signature 'anlz'
funused3(object)

funused3(object) <- value

## S4 replacement method for signature 'anlz'
funused3(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the funused3 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

generated-methods *Extract Image Attribute* generated

Description

Methods that act on the generated field in the NIFTI/ANALYZE header.

Usage

```
generated(object)

## S4 method for signature 'anzl'
generated(object)

generated(object) <- value

## S4 replacement method for signature 'anzl'
generated(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the generated field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

`glmax-methods`*Extract Image Attribute glmax*

Description

Methods that act on the `glmax` field in the NIFTI/ANALYZE header.

Usage

```
glmax(object)

## S4 method for signature 'nifti'
glmax(object)

## S4 method for signature 'anlz'
glmax(object)

glmax(object) <- value

## S4 replacement method for signature 'nifti'
glmax(object) <- value

## S4 replacement method for signature 'anlz'
glmax(object) <- value
```

Arguments

<code>object</code>	is an object of class <code>nifti</code> or <code>anlz</code> .
<code>value</code>	is the value to assign to the <code>glmax</code> field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

`glmin-methods`*Extract Image Attribute glmin*

Description

Methods that act on the `glmin` field in the NIFTI/ANALYZE header.

Usage

```
glmin(object)

## S4 method for signature 'nifti'
glmin(object)

## S4 method for signature 'anlz'
glmin(object)

glmin(object) <- value

## S4 replacement method for signature 'nifti'
glmin(object) <- value

## S4 replacement method for signature 'anlz'
glmin(object) <- value
```

Arguments

<code>object</code>	is an object of class <code>nifti</code> or <code>anlz</code> .
<code>value</code>	is the value to assign to the <code>glmin</code> field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

hist_un0-methods *Extract Image Attribute hist_un0*

Description

Methods that act on the hist_un0 field in the NIFTI/ANALYZE header.

Usage

```
hist_un0(object)

## S4 method for signature 'anzl'
hist_un0(object)

hist_un0(object) <- value

## S4 replacement method for signature 'anzl'
hist_un0(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the hist_un0 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

hkey_un0-methods *Extract Image Attribute* hkey_un0

Description

Methods that act on the hkey_un0 field in the NIFTI/ANALYZE header.

Usage

```
hkey_un0(object)

## S4 method for signature 'anzl'
hkey_un0(object)

hkey_un0(object) <- value

## S4 replacement method for signature 'anzl'
hkey_un0(object) <- value

hkey.un0(object)

## S4 method for signature 'anzl'
hkey.un0(object)

hkey.un0(object) <- value

## S4 replacement method for signature 'anzl'
hkey.un0(object) <- value
```

Arguments

object is an object of class nifti or anzl.
value is the value to assign to the hkey_un0 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

hotmetal

Hot Metal Color Table

Description

The hotmetal color table patterned after the one used in Matlab.

Usage

```
hotmetal(n = 64)
```

Arguments

`n` is the number of color levels (default = 64).

Details

Based on the `tim.colors` function in the **fields** package. The `hotmetal` function has been modified to break any dependence on code in the **fields** package. Spline interpolation (`interpSpline`) is used when the number of requested colors is not the default.

Value

A vector of character strings giving the colors in hexadecimal format.

See Also

[terrain.colors](#), [tim.colors](#), [topo.colors](#)

Examples

```
hotmetal(10)  
image(outer(1:20, 1:20, "+"), col=hotmetal(75), main="hotmetal")
```

Description

Produce “lightbox” layout of images for nifti, anlz and afni objects.

Usage

```
## S4 method for signature 'nifti'
image(x, z = 1, w = 1, col = gray(0:64/64),
      plane = c("axial", "coronal", "sagittal"), plot.type = c("multiple",
"single"), zlim = NULL, xlab = "", ylab = "", axes = FALSE,
      oma = rep(0, 4), mar = rep(0, 4), bg = "black", ...)

## S4 method for signature 'anlz'
image(x, z = 1, w = 1, col = gray(0:64/64),
      plane = c("axial", "coronal", "sagittal"), plot.type = c("multiple",
"single"), zlim = NULL, xlab = "", ylab = "", axes = FALSE,
      oma = rep(0, 4), mar = rep(0, 4), bg = "black", ...)

## S4 method for signature 'afni'
image(x, ...)
```

Arguments

x	is an object of class nifti or similar.
z	is the slice to be displayed (ignored when plot.type = "multiple").
w	is the time point to be displayed (4D arrays only).
col	is grayscale (by default).
plane	is the plane of acquisition to be displayed (choices are 'axial', 'coronal', 'sagittal').
plot.type	allows the choice between all slices being displayed, in a matrix (left-to-right, top-to-bottom), or a single slice.
zlim	is set to NULL by default and utilizes the internal image range.
xlab	is set to "" since all margins are set to zero.
ylab	is set to "" since all margins are set to zero.
axes	is set to FALSE since all margins are set to zero.
oma	is the size of the outer margins in the par function.
mar	is the number of lines of margin in the par function.
bg	is the background color in the par function.
...	other arguments to the image function may be provided here.

Details

Uses the S3 generic function `image`, with medical-image friendly settings, to display `nifti`, `anlz` and `afni` class objects in a “lightbox” layout.

Methods

`x = "ANY"` Generic function: see [image](#).

`x = "nifti"` Produce images for `x`.

`x = "anlz"` Produce images for `x`.

`x = "afni"` Produce images for `x`.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

See Also

[orthographic-methods](#), [overlay-methods](#)

img_data-methods *Extract Image Attribute .Data*

Description

Methods that act on the `.Data` field in the NIFTI/ANALYZE header.

Usage

```
img_data(object)

## S4 method for signature 'nifti'
img_data(object)

## S4 method for signature 'anlz'
img_data(object)

## S4 method for signature 'character'
img_data(object)

## S4 method for signature 'ANY'
img_data(object)

img_data(object) <- value

## S4 replacement method for signature 'nifti'
img_data(object) <- value
```

```
## S4 replacement method for signature 'anlz'  
img_data(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
value is the value to assign to the `.Data` field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<http://www.mayo.edu/bir/PDF/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

integerTranslation *integerTranslation*

Description

...

Usage

```
integerTranslation(nim, data, verbose = FALSE)
```

```
invertIntegerTranslation(nim, verbose = FALSE)
```

Arguments

nim is an object of class `nifti`.
data is ...
verbose is a logical variable (default = `FALSE`) that allows text-based feedback during execution of the function.

Details

...

Value

...

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>

intent_code-methods *Extract Image Attribute* intent_code

Description

Methods that act on the `intent_code` field in the NIFTI/ANALYZE header.

Usage

```
intent_code(object)

## S4 method for signature 'nifti'
intent_code(object)

intent_code(object) <- value

## S4 replacement method for signature 'nifti'
intent_code(object) <- value

intent.code(object)

## S4 method for signature 'nifti'
intent.code(object)

intent.code(object) <- value

## S4 replacement method for signature 'nifti'
intent.code(object) <- value
```

Arguments

`object` is an object of class `nifti` or `anlz`.
`value` is the value to assign to the `intent_code` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

intent_name-methods *Extract Image Attribute* intent_name

Description

Methods that act on the intent_name field in the NIfTI/ANALYZE header.

Usage

```
intent_name(object)

## S4 method for signature 'nifti'
intent_name(object)

intent_name(object) <- value

## S4 replacement method for signature 'nifti'
intent_name(object) <- value

intent.name(object)

## S4 method for signature 'nifti'
intent.name(object)

intent.name(object) <- value

## S4 replacement method for signature 'nifti'
intent.name(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the intent_name field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

intent_p1-methods	<i>Extract Image Attribute intent_p1</i>
-------------------	--

Description

Methods that act on the intent_p1 field in the NIFTI/ANALYZE header.

Usage

```
intent_p1(object)

## S4 method for signature 'nifti'
intent_p1(object)

intent_p1(object) <- value

## S4 replacement method for signature 'nifti'
intent_p1(object) <- value

intent.p1(object)

## S4 method for signature 'nifti'
intent.p1(object)

intent.p1(object) <- value

## S4 replacement method for signature 'nifti'
intent.p1(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the intent_p1 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

intent_p2-methods *Extract Image Attribute intent_p2*

Description

Methods that act on the intent_p2 field in the NIFTI/ANALYZE header.

Usage

```
intent_p2(object)

## S4 method for signature 'nifti'
intent_p2(object)

intent_p2(object) <- value

## S4 replacement method for signature 'nifti'
intent_p2(object) <- value

intent.p2(object)

## S4 method for signature 'nifti'
intent.p2(object)

intent.p2(object) <- value

## S4 replacement method for signature 'nifti'
intent.p2(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the intent_p2 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

intent_p3-methods	<i>Extract Image Attribute intent_p3</i>
-------------------	--

Description

Methods that act on the intent_p3 field in the NIFTI/ANALYZE header.

Usage

```
intent_p3(object)

## S4 method for signature 'nifti'
intent_p3(object)

intent_p3(object) <- value

## S4 replacement method for signature 'nifti'
intent_p3(object) <- value

intent.p3(object)

## S4 method for signature 'nifti'
intent.p3(object)

intent.p3(object) <- value

## S4 replacement method for signature 'nifti'
intent.p3(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the intent_p3 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

is.afni

check object

Description

Check whether object is of class `afni`.

Usage

```
is.afni(x)
```

Arguments

`x` is an object to be checked.

Value

Logical indicating whether object is of class `afni`.

Author(s)

Karsten Tabelow <karsten.tabelow@wias-berlin.de>

References

AFNI
<http://afni.nimh.nih.gov/pub/dist/src/README.attributes>

See Also

`afni`

is.anlz	<i>check object</i>
---------	---------------------

Description

Check whether object is of class [anzl](#).

Usage

```
is.anlz(x)
```

Arguments

x is an object to be checked.

Value

Logical indicating whether object is of class [anzl](#).

Author(s)

Karsten Tabelow <karsten.tabelow@wias-berlin.de>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>

See Also

[anzl](#)

is.nifti	<i>check object</i>
----------	---------------------

Description

Check whether object is of class [nifti](#).

Usage

```
is.nifti(x)
```

Arguments

x is an object to be checked.

Value

Logical indicating whether object is of class `nifti`.

Author(s)

Karsten Tabelow <karsten.tabelow@wias-berlin.de>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

See Also

`nifti`

magic-methods

Extract Image Attribute magic

Description

Methods that act on the magic field in the NIfTI/ANALYZE header.

Usage

```
magic(object)

## S4 method for signature 'nifti'
magic(object)

magic(object) <- value

## S4 replacement method for signature 'nifti'
magic(object) <- value
```

Arguments

`object` is an object of class `nifti` or `anlz`.
`value` is the value to assign to the magic field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

nifti *Constructor for NIfTI*

Description

Constructor for NIfTI class objects.

Usage

```
nifti(img = array(0, dim = rep(1, 4)), dim, datatype = 2, cal.min = NULL,  
      cal.max = NULL, pixdim = NULL, ...)
```

Arguments

img	is a multidimensional array of data.
dim	is the dimension of the data (default = missing).
datatype	is an integer that denotes the type of data contained in each voxel. See <code>convert.datatype</code> or the NIfTI documentation for more details.
cal.min	allows user-specified minimum value in the array (visualization purposes only).
cal.max	allows user-specified minimum value in the array (visualization purposes only).
pixdim	allows user-specified pixel dimension vector (length = 8).
...	allows for additional 'slots' to be specified.

Value

An object of class `nifti`.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

See Also

[nifti](#), [anlz](#), [convert.datatype](#)

Examples

```
options("niftiAuditTrail"=FALSE)

nim <- nifti() # default
nim
nim <- nifti(datatype=4) # 2-byte integers
nim
```

nifti-class

Class "nifti"

Description

The NIFTI class for medical imaging data.

Usage

```
## S4 method for signature 'nifti'
show(object)
```

Arguments

object An object of class nifti.

Objects from the Class

Objects can be created by calls of the form `new("nifti", data, dim, dimnames, ...)` or by calling the `nifti` function.

Slots

```
.Data: Object of class "array" contains the imaging data
sizeof_hdr: Object of class "numeric" contains the size of the header (= 348)
data_type: Object of class "character"
db_name: Object of class "character"
extents: Object of class "numeric"
session_error: Object of class "numeric"
regular: Object of class "character"
dim_info: Object of class "numeric" contains MRI slice ordering
dim_: Object of class "vector" contains the dimensions of the imaging data
intent_p1: Object of class "numeric"
intent_p2: Object of class "numeric"
intent_p3: Object of class "numeric"
```

intent_code: Object of class "numeric"
datatype: Object of class "numeric"
bitpix: Object of class "numeric" contains the number of bits per voxel (pixel)
slice_start: Object of class "numeric"
pixdim: Object of class "vector" contains the real-world dimensions of the imaging data
vox_offset: Object of class "numeric" contains the voxel offset (= 352 when no extensions exist)
scl_slope: Object of class "numeric"
scl_inter: Object of class "numeric"
slice_end: Object of class "numeric"
slice_code: Object of class "numeric"
xyzt_units: Object of class "numeric"
cal_max: Object of class "numeric" contains the maximum display intensity
cal_min: Object of class "numeric" contains the minimum display intensity
slice_duration: Object of class "numeric"
toffset: Object of class "numeric"
glmax: Object of class "numeric"
glmin: Object of class "numeric"
descrip: Object of class "character"
aux_file: Object of class "character"
qform_code: Object of class "numeric"
sform_code: Object of class "numeric"
quatern_b: Object of class "numeric"
quatern_c: Object of class "numeric"
quatern_d: Object of class "numeric"
qoffset_x: Object of class "numeric"
qoffset_y: Object of class "numeric"
qoffset_z: Object of class "numeric"
srow_x: Object of class "vector"
srow_y: Object of class "vector"
srow_z: Object of class "vector"
intent_name: Object of class "character"
magic: Object of class "character"
extender: Object of class "vector"
reoriented: Object of class "logical"

Extends

Class `"array"`, from data part.
Class `"matrix"`, by class `"array"`, distance 2, with explicit test and coerce.
Class `"structure"`, by class `"array"`, distance 2.
Class `"vector"`, by class `"array"`, distance 3, with explicit coerce.
Class `"vector"`, by class `"array"`, distance 5, with explicit test and coerce.

Methods

image signature(x = "nifti"): displays the image(s).
orthographic signature(x = "nifti"): displays the image(s).
overlay signature(x = "nifti", y = "nifti"): displays the image(s).
show signature(object = "nifti"): prints out a summary of the imaging data.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>,
Andrew Thornton <zeripath@users.sourceforge.net>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

See Also

[anlz](#), [niftiExtension](#), [niftiAuditTrail](#)

Examples

```
showClass("nifti")
```

Description

Overloaded operators for nifti objects

Usage

```
## S4 method for signature 'nifti,nifti'  
Ops(e1, e2)  
  
## S4 method for signature 'nifti,numeric'  
Ops(e1, e2)  
  
## S4 method for signature 'numeric,nifti'  
Ops(e1, e2)
```

Arguments

e1 is an object of class nifti.
e2 is an object of class nifti.

Author(s)

John Muschelli <muschellij2@gmail.com>

Examples

```
img01 <- nifti(array(1:64, c(4,4,4,1)), datatype=4)  
img02 <- nifti(array(64:1, c(4,4,4,1)), datatype=4)  
is.nifti(img01 + img02)  
is.nifti(sqrt(2) * img01)  
is.nifti(img02 / pi)
```

niftiAuditTrail-class *Class "niftiAuditTrail"*

Description

An extension of the NIFTI class that adds an audit trail in XML format.

Objects from the Class

Objects can be created by calls of the form `new("niftiAuditTrail", data, dim, dimnames, ...)`.

Methods

`show` signature(object = "niftiAuditTrail"): prints out a summary of the imaging data.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

See Also

[nifti](#), [niftiExtension](#)

Examples

```
showClass("niftiAuditTrail")
```

niftiExtension-class *Class "niftiExtension"*

Description

An extension of the NIfTI class that allows “extensions” that conform to the NIfTI data standard.

Objects from the Class

Objects can be created by calls of the form `new("niftiExtension", data, dim, dimnames, ...)`.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

See Also

[nifti](#), [niftiAuditTrail](#)

Examples

```
showClass("niftiExtension")
```

niftiExtensionSection-class
Class "niftiExtensionSection"

Description

A niftiExtensionSection contains the fields that conform to the NIFTI standard regarding header extensions. A niftiExtension is composed of one or more of these objects.

Objects from the Class

Objects can be created by calls of the form `new("niftiExtensionSection", data, dim, dimnames, ...)`.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>,
Andrew Thornton <zeripath@users.sourceforge.net>

References

NIFTI-1
<http://nifti.nimh.nih.gov/>

See Also

[niftiExtension](#), [nifti](#)

Examples

```
showClass("niftiExtensionSection")
```

nifti_assign-methods *Methods for Function [<- in Package 'base'*

Description

Methods for function [<- in Package 'base'

Methods

x = "nifti", i = "ANY", j = "ANY", value = "ANY" Replaces the data at the provided co-ordinates with the value provided and updates the header.

x = "nifti", i = "numeric", j = "numeric", value = "ANY" Replaces the data at the provided co-ordinates with the value provided and updates the header.

x = "nifti", i = "ANY", j = "missing", value = "ANY" Replaces the data row i of the provided nifti object with the value provided and updates the header.

x = "nifti", i = "numeric", j = "missing", value = "ANY" Replaces the data row i of the provided nifti object with the value provided and updates the header.

x = "nifti", i = "missing", j = "missing", value = "array" Replaces the data of the provided nifti object with the array provided and updates the header.

 nii2oro

Convert RNifti niftiImage to oro.nifti nifti object

Description

Converts a niftiImage from RNifti to a nifti object from the oro.nifti package

Usage

```
nii2oro(image)
```

Arguments

image niftiImage object

Value

Object of class `nifti`

 nsli

Dimension Accessor Functions

Description

Functions to extract the higher dimensions from ANALYZE/NIFTI data.

Usage

```
nsli(x)
```

```
NSLI(x)
```

```
ntim(x)
```

```
NTIM(x)
```


Arguments

`x` is a three- or four-dimensional array (e.g., read in from an ANALYZE/NIfTI file).

Details

Simple calls to `dim` to replicate the functionality of `nrow` and `ncol` for higher dimensions of an array that are commonly required when manipulating medical imaging data.

Value

Third (slice) or fourth (time) dimension of the array.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

See Also

[readNIfTI](#), [readANALYZE](#)

omax-methods

Extract Image Attribute omax

Description

Methods that act on the `omax` field in the NIfTI/ANALYZE header.

Usage

```
omax(object)

## S4 method for signature 'anlz'
omax(object)

omax(object) <- value

## S4 replacement method for signature 'anlz'
omax(object) <- value
```

Arguments

`object` is an object of class `nifti` or `anlz`.
`value` is the value to assign to the `omax` field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

omin-methods

Extract Image Attribute omin

Description

Methods that act on the omin field in the NIFTI/ANALYZE header.

Usage

```
omin(object)

## S4 method for signature 'anzl'
omin(object)

omin(object) <- value

## S4 replacement method for signature 'anzl'
omin(object) <- value
```

Arguments

object is an object of class nifti or anzl.
value is the value to assign to the omin field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

onefile

Creates the onefile Specification for NIfTI

Description

Changes the magic and vox_offset slots to be consistent with the onefile option in `writeNIfTI`.
As of version 0.4.0, `oro.nifti` did not support the "ni1" magic type for output.

Usage

```
onefile(img)
```

Arguments

`img` is a `nifti`-class object.

Value

Object of class `nifti`.

Author(s)

John Muschelli <muschellij2@gmail.com>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

orient-methods *Extract Image Attribute orient*

Description

Methods that act on the orient field in the NIfTI/ANALYZE header.

Usage

```
orient(object)

## S4 method for signature 'anzl'
orient(object)

orient(object) <- value

## S4 replacement method for signature 'anzl'
orient(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the orient field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

Description

Methods that act on the “qform” and “sform” information in the NIfTI header.

Usage

```
sform(object)

## S4 method for signature 'nifti'
sform(object)

qform(object)

## S4 method for signature 'nifti'
qform(object)
```

Arguments

`object` is an object of class `nifti`.

Methods

object = "nifti" Extract or replace NIfTI description.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

Examples

```
## Not run:
url <- "http://nifti.nimh.nih.gov/nifti-1/data/avg152T1_LR_nifti.nii.gz"
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "mniLR.nii.gz")
download.file(url, urlfile, quiet=TRUE)

## End(Not run)
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "mniLR.nii.gz")
mniLR <- readNIfTI(urlfile)
sform(mniLR)
```

origin-methods *Extract Image Attribute* origin

Description

Methods that act on the origin field in the NIfTI/ANALYZE header.

Usage

```
origin(object)

## S4 method for signature 'anzl'
origin(object)

origin(object) <- value

## S4 replacement method for signature 'anzl'
origin(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the origin field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

oro2nii	<i>Convert oro.nifti nifti to RNifti niftiImage object</i>
---------	--

Description

Converts a nifti from oro.nifti to a niftiImage object from the RNifti package

Usage

```
oro2nii(image, verbose = FALSE)
```

Arguments

image	nifti object
verbose	print messages, passed to <code>writeNIFTI</code>

Value

Object of class niftiImage

orthographic-methods	<i>Methods for Function 'orthographic' in Package 'dcmriS4'</i>
----------------------	---

Description

Produce orthographic display for nifti, anlz and afni objects.

Usage

```
orthographic.nifti(x, y = NULL, xyz = NULL, w = 1, col = gray(0:64/64),
  col.y = hotmetal(), zlim = NULL, zlim.y = NULL, crosshairs = TRUE,
  col.crosshairs = "red", xlab = "", ylab = "", axes = FALSE,
  oma = rep(0, 4), mar = rep(0, 4), bg = "black", text = NULL,
  text.color = "white", text.cex = 2, ...)
```

```
orthographic(x, ...)
```

```
## S4 method for signature 'nifti'
```

```
orthographic(x, y = NULL, xyz = NULL, w = 1,
  col = gray(0:64/64), col.y = hotmetal(), zlim = NULL, zlim.y = NULL,
  crosshairs = TRUE, col.crosshairs = "red", xlab = "", ylab = "",
  axes = FALSE, oma = rep(0, 4), mar = rep(0, 4), bg = "black",
  text = NULL, text.color = "white", text.cex = 2, ...)
```

```
## S4 method for signature 'anlz'
```

```

orthographic(x, y = NULL, xyz = NULL, w = 1,
  col = gray(0:64/64), col.y = hotmetal(), zlim = NULL, zlim.y = NULL,
  crosshairs = TRUE, col.crosshairs = "red", xlab = "", ylab = "",
  axes = FALSE, oma = rep(0, 4), mar = rep(0, 4), bg = "black",
  text = NULL, text.color = "white", text.cex = 2, ...)

## S4 method for signature 'array'
orthographic(x, ...)

## S4 method for signature 'afni'
orthographic(x, ...)

```

Arguments

<code>x</code>	is an object of class <code>nifti</code> or similar.
<code>y</code>	is an object of class <code>nifti</code> or similar for the overlay.
<code>xyz</code>	is the coordinate for the center of the crosshairs.
<code>w</code>	is the time point to be displayed (4D arrays only).
<code>col</code>	is grayscale (by default).
<code>col.y</code>	is hotmetal (by default).
<code>zlim</code>	is the minimum and maximum 'z' values passed into image.
<code>zlim.y</code>	is the minimum and maximum 'z' values passed into image for the overlay.
<code>crosshairs</code>	is a logical value for the presence of crosshairs in all three orthogonal planes (default = TRUE).
<code>col.crosshairs</code>	is the color of the crosshairs (default = red).
<code>xlab</code>	is set to "" since all margins are set to zero.
<code>ylab</code>	is set to "" since all margins are set to zero.
<code>axes</code>	is set to FALSE since all margins are set to zero.
<code>oma</code>	is the size of the outer margins in the <code>par</code> function.
<code>mar</code>	is the number of lines of margin in the <code>par</code> function.
<code>bg</code>	is the background color in the <code>par</code> function.
<code>text</code>	allows the user to specify text to appear in the fourth (unused) pane.
<code>text.color</code>	is the color of the user-specified text (default = "white").
<code>text.cex</code>	is the size of the user-specified text (default = 2).
<code>...</code>	other arguments to the <code>image</code> function may be provided here.

Methods

`x = "afni"` Produce orthographic display for `x`.
`x = "anzl"` Produce orthographic display for `x`.
`x = "array"` Produce orthographic display for `x`.
`x = "nifti"` Produce orthographic display for `x`.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

See Also

[image-methods](#), [overlay-methods](#)

overlay-methods

Methods for Function overlay

Description

Methods for function overlay

Usage

```
overlay.nifti(x, y, z = 1, w = 1, col.x = gray(0:64/64),
  col.y = hotmetal(), zlim.x = NULL, zlim.y = NULL, plane = c("axial",
  "coronal", "sagittal"), plot.type = c("multiple", "single"), xlab = "",
  ylab = "", axes = FALSE, oma = rep(0, 4), mar = rep(0, 4),
  bg = "black", ...)
```

```
overlay(x, y, ...)
```

```
## S4 method for signature 'nifti,nifti'
```

```
overlay(x, y, z = 1, w = 1, col.x = gray(0:64/64),
  col.y = hotmetal(), zlim.x = NULL, zlim.y = NULL, plane = c("axial",
  "coronal", "sagittal"), plot.type = c("multiple", "single"), xlab = "",
  ylab = "", axes = FALSE, oma = rep(0, 4), mar = rep(0, 4),
  bg = "black", ...)
```

```
## S4 method for signature 'anlz,anlz'
```

```
overlay(x, y, z = 1, w = 1, col.x = gray(0:64/64),
  col.y = hotmetal(), zlim.x = NULL, zlim.y = NULL, plane = c("axial",
  "coronal", "sagittal"), plot.type = c("multiple", "single"), xlab = "",
  ylab = "", axes = FALSE, oma = rep(0, 4), mar = rep(0, 4),
  bg = "black", ...)
```

```
## S4 method for signature 'anlz,nifti'
```

```
overlay(x, y, z = 1, w = 1, col.x = gray(0:64/64),
  col.y = hotmetal(), zlim.x = NULL, zlim.y = NULL, plane = c("axial",
  "coronal", "sagittal"), plot.type = c("multiple", "single"), xlab = "",
  ylab = "", axes = FALSE, oma = rep(0, 4), mar = rep(0, 4),
  bg = "black", ...)
```

```
## S4 method for signature 'nifti,anlz'
```

```
overlay(x, y, z = 1, w = 1, col.x = gray(0:64/64),
```

```

col.y = hotmetal(), zlim.x = NULL, zlim.y = NULL, plane = c("axial",
"coronal", "sagittal"), plot.type = c("multiple", "single"), xlab = "",
ylab = "", axes = FALSE, oma = rep(0, 4), mar = rep(0, 4),
bg = "black", ...)

## S4 method for signature 'array,array'
overlay(x, y, ...)

## S4 method for signature 'array,nifti'
overlay(x, y, ...)

## S4 method for signature 'nifti,array'
overlay(x, y, ...)

## S4 method for signature 'array,anlz'
overlay(x, y, ...)

## S4 method for signature 'anlz,array'
overlay(x, y, ...)

## S4 method for signature 'afni,afni'
overlay(x, y, ...)

## S4 method for signature 'afni,array'
overlay(x, y, ...)

```

Arguments

<code>x, y</code>	is an object of class <code>nifti</code> or similar.
<code>z</code>	is the slice to be displayed (ignored when <code>plot.type = "multiple"</code>).
<code>w</code>	is the time point to be displayed (4D arrays only).
<code>col.x</code>	is grayscale (by default).
<code>col.y</code>	is hotmetal (by default).
<code>zlim.x, zlim.y</code>	are set to <code>NULL</code> (by default) and taken from the header information.
<code>plane</code>	is the plane of acquisition to be displayed (choices are 'axial', 'coronal', 'sagittal').
<code>plot.type</code>	allows the choice between all slices being displayed, in a matrix (left-to-right, top-to-bottom), or a single slice.
<code>xlab</code>	is set to "" since all margins are set to zero.
<code>ylab</code>	is set to "" since all margins are set to zero.
<code>axes</code>	is set to <code>FALSE</code> since all margins are set to zero.
<code>oma</code>	is the size of the outer margins in the <code>par</code> function.
<code>mar</code>	is the number of lines of margin in the <code>par</code> function.
<code>bg</code>	is the background color in the <code>par</code> function.
<code>...</code>	other arguments to the <code>image</code> function may be provided here.

Details

The `image` command is used multiple times to simultaneously visualize one of the three orthogonal planes in two multidimensional arrays, one on top of the other, for medical imaging data.

Methods

`x = "nifti", y = "nifti"` Produce overlay of y on x.

`x = "anlz", y = "anlz"` Produce overlay of y on x.

`x = "afni", y = "afni"` Produce overlay of y on x.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

See Also

[image-methods](#), [overlay-methods](#)

patient_id-methods *Extract Image Attribute patient_id*

Description

Methods that act on the `patient_id` field in the NIFTI/ANALYZE header.

Usage

```
patient_id(object)

## S4 method for signature 'anlz'
patient_id(object)

patient_id(object) <- value

## S4 replacement method for signature 'anlz'
patient_id(object) <- value

patient.id(object)

## S4 method for signature 'anlz'
patient.id(object)

patient.id(object) <- value

## S4 replacement method for signature 'anlz'
patient.id(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
 value is the value to assign to the `patient_id` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIFTI-1
<http://nifti.nimh.nih.gov/>

performPermutation *Transform array with orthogonal permutation matrix*

Description

Given an orthogonal permutation matrix T , an array of dimensions and a one-dimensional representation of data. It will return a transformed array with the transformed dimensions.

Usage

```
performPermutation(T, real.dimensions, data, verbose = FALSE)
```

Arguments

`T` is an orthogonal matrix.
`real.dimensions` is a one-dimensional array, representing the length of dimensions in data.
`data` is a one-dimensional representation of the data to be transformed.
`verbose` is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.

Details

This function is mainly used by the `reorient` function to transform nifti data into neuroradiological convention.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>

See Also

[reorient](#), [inverseReorient](#)

pixdim-methods *Extract Image Attribute* pixdim

Description

Methods that act on the pixdim field in the NIFTI/ANALYZE header.

Usage

```
pixdim(object)

## S4 method for signature 'nifti'
pixdim(object)

## S4 method for signature 'anlz'
pixdim(object)

pixdim(object) <- value

## S4 replacement method for signature 'nifti'
pixdim(object) <- value

## S4 replacement method for signature 'anlz'
pixdim(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the pixdim field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
 NIfTI-1
<http://nifti.nimh.nih.gov/>

Examples

```
## Not run:
url <- "http://nifti.nimh.nih.gov/nifti-1/data/avg152T1_LR_nifti.nii.gz"
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
"mniLR.nii.gz")
download.file(url, urlfile, quiet=TRUE)

## End(Not run)
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
"mniLR.nii.gz")
mniLR <- readNIfTI(urlfile)
pixdim(mniLR)
```

qform_code-methods *Extract Image Attribute* qform_code

Description

Methods that act on the qform_code field in the NIFTI/ANALYZE header.

Usage

```
qform_code(object)

## S4 method for signature 'nifti'
qform_code(object)

qform_code(object) <- value

## S4 replacement method for signature 'nifti'
qform_code(object) <- value

qform.code(object)

## S4 method for signature 'nifti'
qform.code(object)

qform.code(object) <- value

## S4 replacement method for signature 'nifti'
qform.code(object) <- value
```

Arguments

object is an object of class nifti or anlz.
 value is the value to assign to the qform_code field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIFTI-1
<http://nifti.nimh.nih.gov/>

qoffset_x-methods *Extract Image Attribute* qoffset_x

Description

Methods that act on the qoffset_x field in the NIFTI/ANALYZE header.

Usage

```
qoffset_x(object)

## S4 method for signature 'nifti'
qoffset_x(object)

qoffset_x(object) <- value

## S4 replacement method for signature 'nifti'
qoffset_x(object) <- value

qoffset.x(object)

## S4 method for signature 'nifti'
qoffset.x(object)

qoffset.x(object) <- value

## S4 replacement method for signature 'nifti'
qoffset.x(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
 value is the value to assign to the `qoffset_x` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIFTI-1
<http://nifti.nimh.nih.gov/>

qoffset_y-methods *Extract Image Attribute* qoffset_y

Description

Methods that act on the `qoffset_y` field in the NIFTI/ANALYZE header.

Usage

```
qoffset_y(object)

## S4 method for signature 'nifti'
qoffset_y(object)

qoffset_y(object) <- value

## S4 replacement method for signature 'nifti'
qoffset_y(object) <- value

qoffset.y(object)

## S4 method for signature 'nifti'
qoffset.y(object)

qoffset.y(object) <- value

## S4 replacement method for signature 'nifti'
qoffset.y(object) <- value
```


Arguments

object is an object of class `nifti` or `anlz`.
 value is the value to assign to the `qoffset_y` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIFTI-1
<http://nifti.nimh.nih.gov/>

qoffset_z-methods *Extract Image Attribute* qoffset_z

Description

Methods that act on the `qoffset_z` field in the NIFTI/ANALYZE header.

Usage

```
qoffset_z(object)

## S4 method for signature 'nifti'
qoffset_z(object)

qoffset_z(object) <- value

## S4 replacement method for signature 'nifti'
qoffset_z(object) <- value

qoffset.z(object)

## S4 method for signature 'nifti'
qoffset.z(object)

qoffset.z(object) <- value

## S4 replacement method for signature 'nifti'
qoffset.z(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
 value is the value to assign to the `qoffset_z` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIFTI-1
<http://nifti.nimh.nih.gov/>

quaternion2rotation *Convert Quaternion into a Rotation Matrix*

Description

The affine/rotation matrix R is calculated from the quaternion parameters.

Usage

```
quaternion2rotation(b, c, d, tol = 1e-07)
```

```
quaternion2mat44(nim, tol = 1e-07)
```

Arguments

`b` is the quaternion b parameter.
`c` is the quaternion c parameter.
`d` is the quaternion d parameter.
`tol` is a very small value used to judge if a number is essentially zero.
`nim` is an object of class `nifti`.

Details

The quaternion representation is chosen for its compactness in representing rotations. The orientation of the (x, y, z) axes relative to the (i, j, k) axes in 3D space is specified using a unit quaternion $[a, b, c, d]$, where $a^2 + b^2 + c^2 + d^2 = 1$. The (b, c, d) values are all that is needed, since we require that $a = [1 - (b^2 + c^2 + d^2)]^{1/2}$ be non-negative. The (b, c, d) values are stored in the `(quatern_b, quatern_c, quatern_d)` fields.

Value

The (proper) 3×3 rotation matrix or 4×4 affine matrix.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

Examples

```
## This R matrix is represented by quaternion [a,b,c,d] = [0,1,0,0]
## (which encodes a 180 degree rotation about the x-axis).
(R <- quaternion2rotation(1, 0, 0))
```

quatern_b-methods *Extract Image Attribute* quatern_b

Description

Methods that act on the quatern_b field in the NIfTI/ANALYZE header.

Usage

```
quatern_b(object)

## S4 method for signature 'nifti'
quatern_b(object)

quatern_b(object) <- value

## S4 replacement method for signature 'nifti'
quatern_b(object) <- value

quatern.b(object)

## S4 method for signature 'nifti'
quatern.b(object)

quatern.b(object) <- value

## S4 replacement method for signature 'nifti'
quatern.b(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
 value is the value to assign to the `quatern_b` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIFTI-1
<http://nifti.nimh.nih.gov/>

quatern_c-methods *Extract Image Attribute quatern_c*

Description

Methods that act on the `quatern_c` field in the NIFTI/ANALYZE header.

Usage

```
quatern_c(object)

## S4 method for signature 'nifti'
quatern_c(object)

quatern_c(object) <- value

## S4 replacement method for signature 'nifti'
quatern_c(object) <- value

quatern.c(object)

## S4 method for signature 'nifti'
quatern.c(object)

quatern.c(object) <- value

## S4 replacement method for signature 'nifti'
quatern.c(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
value is the value to assign to the `quatern_c` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

quatern_d-methods *Extract Image Attribute quatern_d*

Description

Methods that act on the `quatern_d` field in the NIFTI/ANALYZE header.

Usage

```
quatern_d(object)

## S4 method for signature 'nifti'
quatern_d(object)

quatern_d(object) <- value

## S4 replacement method for signature 'nifti'
quatern_d(object) <- value

quatern.d(object)

## S4 method for signature 'nifti'
quatern.d(object)

quatern.d(object) <- value

## S4 replacement method for signature 'nifti'
quatern.d(object) <- value
```

Arguments

object is an object of class `nifti` or `anlz`.
 value is the value to assign to the `quatern_d` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIFTI-1
<http://nifti.nimh.nih.gov/>

 readAFNI

readAFNI

Description

These functions read in the header information and multidimensional array from a binary file in AFNI format into a `afni`-class object.

Usage

```
readAFNI(fname, vol = NULL, verbose = FALSE, warn = -1, call = NULL)
```

Arguments

`fname` is the file name of the AFNI file.
`vol` vector of brick numbers to be read from file.
`verbose` is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.
`warn` is a number to regulate the display of warnings (default = -1). See options for more details.
`call` keeps track of the current function call for use in the AFNI extension.

Details

The readAFNI function utilizes internal methods readBin and readLines to efficiently extract information from the header and binary file(s). Compression is allowed on the BRIK file using gzip.

Current acceptable data types include

`list("INT16")` DT SIGNED SHORT (16 bits per voxel)

`list("FLOAT32")` DT FLOAT (32 bits per voxel)

`list("COMPLEX128")` DT COMPLEX (128 bits per voxel)

Value

object of class `afni`

Author(s)

Karsten Tabelow <karsten.tabelow@wias-berlin.de>

References

AFNI

<http://afni.nimh.nih.gov/pub/dist/src/README.attributes>

See Also

`readANALYZE`, `readNIFTI`

Examples

```
## Not run:
## Taken from the AFNI Matlab Library
## http://afni.nimh.nih.gov/pub/dist/data/afni_matlab_data.tgz
afni.path <- system.file("afni", package="oro.nifti")
orig <- readAFNI(file.path(afni.path, "ARzs_CW_avvr.DEL+orig"))
image(orig, zlim=c(0.5,256), oma=rep(2,4))
orthographic(orig, zlim=c(0.5,256), oma=rep(2,4))
## Taken from the AFNI installation
TT <- readAFNI(file.path(afni.path, "TT_N27_EZ_LR+tlrc"))
image(TT, zlim=c(0.5,256), oma=rep(2,4))
orthographic(TT, zlim=c(0.5,256), oma=rep(2,4))

## End(Not run)
```

readANALYZE	<i>readANALYZE</i>
-------------	--------------------

Description

These functions read in the header information and multi-dimensional array from a binary file in Analyze 7.5 format.

Usage

```
readANALYZE(fname, SPM = FALSE, verbose = FALSE, warn = -1)
```

Arguments

fname	Pathname of the Analyze pair of files .img and .hdr without the suffix.
SPM	is a logical variable (default = FALSE) that forces the voxel data values to be rescaled using the funused1 ANALYZE header field. This is an undocumented convention of ANALYZE files processed using the Statistical Parametric Mapping (SPM) software.
verbose	is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.
warn	is a number to regulate the display of warnings (default = -1). See options for more details.

Details

The internal functions readBin and rawToChar are utilized in order to efficiently extract information from a binary file. The types of data are limited to 1- and 2-byte integers, 4-byte floats and 8-byte doubles.

Value

An object of class anlz is produced.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>,
Volker Schmid <volkerschmid@users.sourceforge.net>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>

See Also

[readNIfTI](#)

Examples

```
## avg152T1
anlz.path <- system.file("anlz", package="oro.nifti")
mni152 <- readANALYZE(file.path(anlz.path, "avg152T1"))
image(mni152, oma=rep(2,4))
orthographic(mni152, oma=rep(2,4))
```

readNifTI

readNifTI

Description

These functions read in the header information and multidimensional array from a binary file in NIFTI-1 format into a `nifti`-class object.

Usage

```
readNifTI(fname, verbose = FALSE, warn = -1, reorient = TRUE,
  call = NULL, force_extension = FALSE)
```

Arguments

<code>fname</code>	is the file name of the NIFTI file(s).
<code>verbose</code>	is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.
<code>warn</code>	is a number to regulate the display of warnings (default = -1). See options for more details.
<code>reorient</code>	is a logical variable (default = TRUE) that enforces Qform/Sform transformations.
<code>call</code>	keeps track of the current function call for use in the NifTI extension.
<code>force_extension</code>	this function will check to see if the <code>vox_offset</code> is correct. If this is forced to 348, which some (very) old NIFTI writers use, this may cause an error if the extension is read, and so it is skipped (with a warning). If <code>force_extension = TRUE</code> , then reading the extension is forced (when appropriate).

Details

The `readNifTI` function utilizes internal methods `readBin` and `readChar` to efficiently extract information from the binary file(s).

Current acceptable data types include

list("UINT8") BINARY (1 bit per voxel)

list("INT16") SIGNED SHORT (16 bits per voxel)

list("INT32") SIGNED INT (32 bits per voxel)

```
list("FLOAT32") FLOAT (32 bits per voxel)
list("DOUBLE64") DOUBLE (64 bits per voxel)
list("UINT16") UNSIGNED SHORT (16 bits per voxel)
list("UINT32") UNSIGNED INT (32 bits per voxel)
```

Value

An object of class `nifti`.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>,
Volker Schmid <volkerschmid@users.sourceforge.net>,
Andrew Thornton <zeripath@users.sourceforge.net>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

See Also

[readAFNI](#), [readANALYZE](#)

Examples

```
## Not run:
url <- "http://nifti.nimh.nih.gov/nifti-1/data/filtered_func_data.nii.gz"
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "filtered_func_data")
download.file(url, urlfile, quiet=TRUE)

## End(Not run)
## The NIfTI file provided here contains the first 18 volumes (10%)
## of the original data set
urlfile <- file.path(system.file("nifti", package="oro.nifti"),
                    "filtered_func_data")
(ffd <- readNIfTI(urlfile))
image(ffd, oma=rep(2,4))
orthographic(ffd, oma=rep(2,4))
## Not run:
## 27 scans of Colin Holmes (MNI) brain co-registered and averaged
## NIfTI two-file format
URL <- "http://imaging.mrc-cbu.cam.ac.uk/downloads/Colin/colin_1mm.tgz"
urlfile <- file.path(tempdir(), "colin_1mm.tgz")
download.file(URL, dest=urlfile, quiet=TRUE)
untar(urlfile, exdir=tempdir())
colin <- readNIfTI(file.path(tempdir(), "colin_1mm"))
image(colin, oma=rep(2,4))
orthographic(colin, oma=rep(2,4))
```

```
## End(Not run)
```

regular-methods	<i>Extract Image Attribute</i>	regular
-----------------	--------------------------------	---------

Description

Methods that act on the regular field in the NIFTI/ANALYZE header.

Usage

```
regular(object)

## S4 method for signature 'nifti'
regular(object)

## S4 method for signature 'anlz'
regular(object)

regular(object) <- value

## S4 replacement method for signature 'nifti'
regular(object) <- value

## S4 replacement method for signature 'anlz'
regular(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the regular field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

reorient	<i>Reorient Image using NIfTI header</i>
----------	--

Description

Transforms in the NIfTI header are parsed and normalized versions of these transforms are applied.

Usage

```
reorient(nim, data, verbose = FALSE, invert = FALSE, tol = 1e-07)
```

```
inverseReorient(nim, verbose = FALSE)
```

Arguments

nim	is an object of class <code>nifti</code> .
data	is an array associated with <code>nim</code> .
verbose	is a logical variable (default = <code>FALSE</code>) that allows text-based feedback during execution of the function.
invert	stores the inverse transform.
tol	is a very small value used to judge if a number is essentially zero.

Details

This function utilizes the `performPermutation` function internally.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>,
Brandon Whitcher <bwhitcher@gmail.com>

See Also

[performPermutation](#)

resetSlopeIntercept *Change Intercept to 0 and Slope to 1 in NIfTI Object*

Description

Forces image scl_slope to 1 and scl_inter to be 0 of slots of class nifti. This is so that when images are rendered/written, the values correspond to those in the array (stored in the .Data slot) and are not scaled.

Usage

```
resetSlopeIntercept(img)
```

```
zero_trans(img)
```

Arguments

img is a nifti object (or character of filename). If an anlz object is passed, the unaltered anlz object is returned.

Value

An object of the same type passed.

Author(s)

John Muschelli <muschellij2@gmail.com>

rmniigz *Remove File Extensions Around the NIfTI/ANALYZE Formats*

Description

Simple function(s) that remove file extensions commonly found when using NIfTI-1 or ANALYZE format files.

Usage

```
rmniigz(x)
```

```
rmnii(x)
```

```
rmgz(x)
```

```
rmhdrgz(x)
```

```
rmhdr(x)
rmimggz(x)
rmimg(x)
```

Arguments

x is the file name.

Value

The file name without offending suffix.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

scannum-methods *Extract Image Attribute* scannum

Description

Methods that act on the scannum field in the NIFTI/ANALYZE header.

Usage

```
scannum(object)

## S4 method for signature 'anzl'
scannum(object)

scannum(object) <- value

## S4 replacement method for signature 'anzl'
scannum(object) <- value
```

Arguments

object is an object of class nifti or anzl.
value is the value to assign to the scannum field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

scl_inter-methods *Extract Image Attribute scl_inter*

Description

Methods that act on the scl_inter field in the NIFTI/ANALYZE header.

Usage

```
scl_inter(object)

## S4 method for signature 'nifti'
scl_inter(object)

scl_inter(object) <- value

## S4 replacement method for signature 'nifti'
scl_inter(object) <- value

scl.inter(object)

## S4 method for signature 'nifti'
scl.inter(object)

scl.inter(object) <- value

## S4 replacement method for signature 'nifti'
scl.inter(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the scl_inter field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

scl_slope-methods *Extract Image Attribute scl_slope*

Description

Methods that act on the scl_slope field in the NIFTI/ANALYZE header.

Usage

```
scl_slope(object)

## S4 method for signature 'nifti'
scl_slope(object)

scl_slope(object) <- value

## S4 replacement method for signature 'nifti'
scl_slope(object) <- value

scl.slope(object)

## S4 method for signature 'nifti'
scl.slope(object)

scl.slope(object) <- value

## S4 replacement method for signature 'nifti'
scl.slope(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the scl_slope field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

session_error-methods *Extract Image Attribute* session_error

Description

Methods that act on the session_error field in the NIFTI/ANALYZE header.

Usage

```
session_error(object)

## S4 method for signature 'nifti'
session_error(object)

## S4 method for signature 'anlz'
session_error(object)

session_error(object) <- value

## S4 replacement method for signature 'nifti'
session_error(object) <- value

## S4 replacement method for signature 'anlz'
session_error(object) <- value

session.error(object)

## S4 method for signature 'nifti'
session.error(object)

## S4 method for signature 'anlz'
session.error(object)
```

```
session.error(object) <- value

## S4 replacement method for signature 'nifti'
session.error(object) <- value

## S4 replacement method for signature 'anlz'
session.error(object) <- value
```

Arguments

`object` is an object of class `nifti` or `anlz`.
`value` is the value to assign to the `session_error` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

sform_code-methods *Extract Image Attribute* sform_code

Description

Methods that act on the `sform_code` field in the NIFTI/ANALYZE header.

Usage

```
sform_code(object)

## S4 method for signature 'nifti'
sform_code(object)

sform_code(object) <- value

## S4 replacement method for signature 'nifti'
```

```
sform_code(object) <- value  
  
sform.code(object)  
  
## S4 method for signature 'nifti'  
sform.code(object)  
  
sform.code(object) <- value  
  
## S4 replacement method for signature 'nifti'  
sform.code(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the sform_code field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

sizeof_hdr-methods *Extract Image Attribute sizeof_hdr*

Description

Methods that act on the sizeof_hdr field in the NIFTI/ANALYZE header.

Usage

```
sizeof_hdr(object)  
  
## S4 method for signature 'nifti'  
sizeof_hdr(object)
```

```
## S4 method for signature 'anlz'
sizeof_hdr(object)

sizeof_hdr(object)

## S4 method for signature 'nifti'
sizeof_hdr(object)

## S4 method for signature 'anlz'
sizeof_hdr(object)
```

Arguments

object is an object of class nifti or anlz.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://portal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

slice_code-methods *Extract Image Attribute slice_code*

Description

Methods that act on the slice_code field in the NIFTI/ANALYZE header.

Usage

```
slice_code(object)

## S4 method for signature 'nifti'
slice_code(object)

slice_code(object) <- value

## S4 replacement method for signature 'nifti'
```

```
slice_code(object) <- value

slice.code(object)

## S4 method for signature 'nifti'
slice.code(object)

slice.code(object) <- value

## S4 replacement method for signature 'nifti'
slice.code(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the slice_code field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

slice_duration-methods

Extract Image Attribute slice_duration

Description

Methods that act on the slice_duration field in the NIFTI/ANALYZE header.

Usage

```
slice_duration(object)

## S4 method for signature 'nifti'
slice_duration(object)
```

```
slice_duration(object) <- value

## S4 replacement method for signature 'nifti'
slice_duration(object) <- value

slice.duration(object)

## S4 method for signature 'nifti'
slice.duration(object)

slice.duration(object) <- value

## S4 replacement method for signature 'nifti'
slice.duration(object) <- value
```

Arguments

`object` is an object of class `nifti` or `anlz`.
`value` is the value to assign to the `slice_duration` field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

slice_end-methods

Extract Image Attribute slice_end

Description

Methods that act on the `slice_end` field in the NIFTI/ANALYZE header.

Usage

```
slice_end(object)

## S4 method for signature 'nifti'
slice_end(object)

slice_end(object) <- value

## S4 replacement method for signature 'nifti'
slice_end(object) <- value

slice.end(object)

## S4 method for signature 'nifti'
slice.end(object)

slice.end(object) <- value

## S4 replacement method for signature 'nifti'
slice.end(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the slice_end field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

slice_start-methods *Extract Image Attribute slice_start*

Description

Methods that act on the slice_start field in the NIFTI/ANALYZE header.

Usage

```
slice_start(object)

## S4 method for signature 'nifti'
slice_start(object)

slice_start(object) <- value

## S4 replacement method for signature 'nifti'
slice_start(object) <- value

slice.start(object)

## S4 method for signature 'nifti'
slice.start(object)

slice.start(object) <- value

## S4 replacement method for signature 'nifti'
slice.start(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the slice_start field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

smax-methods	<i>Extract Image Attribute</i> smax
--------------	-------------------------------------

Description

Methods that act on the smax field in the NIFTI/ANALYZE header.

Usage

```
smax(object)

## S4 method for signature 'anzl'
smax(object)

smax(object) <- value

## S4 replacement method for signature 'anzl'
smax(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the smax field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

smin-methods

Extract Image Attribute smin

Description

Methods that act on the smin field in the NIFTI/ANALYZE header.

Usage

```
smin(object)

## S4 method for signature 'anzl'
smin(object)

smin(object) <- value

## S4 replacement method for signature 'anzl'
smin(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the smin field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

srow_x-methods	<i>Extract Image Attribute srow_x</i>
----------------	---------------------------------------

Description

Methods that act on the srow_x field in the NIFTI/ANALYZE header.

Usage

```
srow_x(object)

## S4 method for signature 'nifti'
srow_x(object)

srow_x(object) <- value

## S4 replacement method for signature 'nifti'
srow_x(object) <- value

srow.x(object)

## S4 method for signature 'nifti'
srow.x(object)

srow.x(object) <- value

## S4 replacement method for signature 'nifti'
srow.x(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the srow_x field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIfTI-1
<http://nifti.nimh.nih.gov/>

srow_y-methods	<i>Extract Image Attribute srow_y</i>
----------------	---------------------------------------

Description

Methods that act on the srow_y field in the NIfTI/ANALYZE header.

Usage

```
srow_y(object)

## S4 method for signature 'nifti'
srow_y(object)

srow_y(object) <- value

## S4 replacement method for signature 'nifti'
srow_y(object) <- value

srow.y(object)

## S4 method for signature 'nifti'
srow.y(object)

srow.y(object) <- value

## S4 replacement method for signature 'nifti'
srow.y(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the srow_y field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
 NIfTI-1
<http://nifti.nimh.nih.gov/>

srow_z-methods	<i>Extract Image Attribute srow_z</i>
----------------	---------------------------------------

Description

Methods that act on the srow_z field in the NIfTI/ANALYZE header.

Usage

```
srow_z(object)

## S4 method for signature 'nifti'
srow_z(object)

srow_z(object) <- value

## S4 replacement method for signature 'nifti'
srow_z(object) <- value

srow.z(object)

## S4 method for signature 'nifti'
srow.z(object)

srow.z(object) <- value

## S4 replacement method for signature 'nifti'
srow.z(object) <- value
```

Arguments

object is an object of class nifti or anlz.
 value is the value to assign to the srow_z field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
 Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

start_field-methods *Extract Image Attribute* start_field

Description

Methods that act on the start_field field in the NIfTI/ANALYZE header.

Usage

```
start_field(object)

## S4 method for signature 'anzl'
start_field(object)

start_field(object) <- value

## S4 replacement method for signature 'anzl'
start_field(object) <- value
```

Arguments

object is an object of class nifti or anzl.
value is the value to assign to the start_field field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

`tim.colors`*Tim's Useful Color Table*

Description

A pleasing rainbow style color table patterned after that used in Matlab.

Usage

```
tim.colors(n = 64)
```

Arguments

`n` is the number of color levels (default = 64).

Details

Based on the `tim.colors` function in the **fields** package. The `tim.colors` function here has been modified to break any dependence on code in the **fields** package. Spline interpolation (`interpSpline`) is used when the number of requested colors is not the default.

Value

A vector of character strings giving the colors in hexadecimal format.

Author(s)

Tim Hoar (GSP-NCAR); modified by Brandon Whitcher

See Also

[hotmetal](#), [topo.colors](#), [terrain.colors](#)

Examples

```
tim.colors(10)
image(outer(1:20, 1:20, "+"), col=tim.colors(75), main="tim.colors")
```

toffset-methods *Extract Image Attribute toffset*

Description

Methods that act on the toffset field in the NIfTI/ANALYZE header.

Usage

```
toffset(object)

## S4 method for signature 'nifti'
toffset(object)

toffset(object) <- value

## S4 replacement method for signature 'nifti'
toffset(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the toffset field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

translateCoordinate *Translate Voxel Coordinates*

Description

Translates a voxel index into the continuous coordinate space defined by the NIFTI qform and sform information.

Usage

```
translateCoordinate(i, nim, verbose = FALSE)
```

Arguments

i	An index vector in nim.
nim	An object of class <code>nifti</code> .
verbose	Provide detailed output to the user.

Details

This function takes as input a `nifti` object and an index vector in the voxel space of the object and translates that voxel index into the continuous coordinate space defined by the object's qform and sform.

Please note:

1. By default the index `i` varies most rapidly, etc.
2. The ANALYZE 7.5 coordinate system is

+x	=	Left
+y	=	Anterior
+z	=	Superior

(A left-handed co-ordinate system).

3. The three methods below give the locations of the voxel centres in the x,y,z system. In many cases programs will want to display the data on other grids. In which case the program will be required to convert the desired (x,y,z) values in to voxel values using the inverse transformation.
4. Method 2 uses a factor `qfac` which is either -1 or 1. `qfac` is stored in `pixdim[0]`. If `pixdim[0] != 1` or -1, which should not occur, we assume 1.
5. The units of the `xyzt` are set in `xyzt_units` field.

Value

A `nifti`-class object with translated coordinates.

Author(s)

Andrew Thornton <zeripath@users.sourceforge.net>

Examples

```
ffd <- readNIFTI(file.path(system.file("nifti", package="oro.nifti"),
                                   "filtered_func_data"))
xyz <- c(1,1,1)
translateCoordinate(xyz, ffd, verbose=TRUE)
xyz <- trunc(dim(ffd)[1:3]/2)
translateCoordinate(xyz, ffd, verbose=TRUE)
```

unused1-methods

Extract Image Attribute unused1

Description

Methods that act on the unused1 field in the NIFTI/ANALYZE header.

Usage

```
unused1(object)

## S4 method for signature 'anlz'
unused1(object)

unused1(object) <- value

## S4 replacement method for signature 'anlz'
unused1(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the unused1 field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

verified-methods	<i>Extract Image Attribute verified</i>
------------------	---

Description

Methods that act on the verified field in the NIfTI/ANALYZE header.

Usage

```
verified(object)

## S4 method for signature 'anzl'
verified(object)

verified(object) <- value

## S4 replacement method for signature 'anzl'
verified(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the verified field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

views-methods

Extract Image Attribute views

Description

Methods that act on the views field in the NIFTI/ANALYZE header.

Usage

```
views(object)

## S4 method for signature 'anzl'
views(object)

views(object) <- value

## S4 replacement method for signature 'anzl'
views(object) <- value
```

Arguments

object	is an object of class nifti or anzl.
value	is the value to assign to the views field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

vols_added-methods *Extract Image Attribute* vols_added

Description

Methods that act on the vols_added field in the NIFTI/ANALYZE header.

Usage

```
vols_added(object)

## S4 method for signature 'anlz'
vols_added(object)

vols_added(object) <- value

## S4 replacement method for signature 'anlz'
vols_added(object) <- value

vols.added(object)

## S4 method for signature 'anlz'
vols.added(object)

vols.added(object) <- value

## S4 replacement method for signature 'anlz'
vols.added(object) <- value
```

Arguments

object is an object of class nifti or anlz.
value is the value to assign to the vols_added field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

voxdim *Gets Voxel Dimensions*

Description

Grabs the pixdim and takes the correct elements

Usage

```
voxdim(img)
```

Arguments

img nifti object

Value

Vector of length 3

voxres *Gets Voxel Resolution*

Description

Grabs the 3 voxel dimensions and takes the product

Usage

```
voxres(img, units = c("mm", "cm"))
```

Arguments

img nifti object
units output unit, either cubic mm or cubic cm.

Value

Scalar numeric, one number, in cubic mm or cubic cm (cc/mL).

vox_offset-methods *Extract Image Attribute* vox_offset

Description

Methods that act on the vox_offset field in the NIFTI/ANALYZE header.

Usage

```
vox_offset(object)

## S4 method for signature 'nifti'
vox_offset(object)

## S4 method for signature 'anlz'
vox_offset(object)

vox_offset(object) <- value

## S4 replacement method for signature 'nifti'
vox_offset(object) <- value

## S4 replacement method for signature 'anlz'
vox_offset(object) <- value

vox.offset(object)

## S4 method for signature 'nifti'
vox.offset(object)

## S4 method for signature 'anlz'
vox.offset(object)

vox.offset(object) <- value

## S4 replacement method for signature 'nifti'
vox.offset(object) <- value

## S4 replacement method for signature 'anlz'
vox.offset(object) <- value
```

Arguments

object	is an object of class nifti or anlz.
value	is the value to assign to the vox_offset field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschelli2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

vox_units-methods *Extract Image Attribute vox_units*

Description

Methods that act on the vox_units field in the NIFTI/ANALYZE header.

Usage

```
vox_units(object)

## S4 method for signature 'anzl'
vox_units(object)

vox_units(object) <- value

## S4 replacement method for signature 'anzl'
vox_units(object) <- value

vox.units(object)

## S4 method for signature 'anzl'
vox.units(object)

vox.units(object) <- value

## S4 replacement method for signature 'anzl'
vox.units(object) <- value
```

Arguments

object is an object of class nifti or anzl.
value is the value to assign to the vox_units field.

Details

See documentation on the ANALYZE and/or NIfTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIfTI-1
<http://nifti.nimh.nih.gov/>

writeAFNI-methods *writeAFNI*

Description

This function saves a afni-class object to HEAD/BRICK pair in AFNI format.

Usage

```
writeAFNI(nim, ...)  
  
## S4 method for signature 'afni'  
writeAFNI(nim, fname, verbose = FALSE, warn = -1)
```

Arguments

nim	is an object of class afni.
...	Additional variables defined by the method.
fname	is the path and file name to save the AFNI file (.HEAD/BRICK) without the suffix.
verbose	is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.
warn	is a number to regulate the display of warnings (default = -1). See options for more details.

Details

The writeAFNI function utilizes the internal writeBin and writeLines command to write information to header/binary file pair.

Current acceptable data types include

INT16" DT SIGNED SHORT (16 bits per voxel)

FLOAT32" DT FLOAT (32 bits per voxel)

"COMPLEX128" DT COMPLEX (128 bits per voxel)

Value

Nothing.

Methods

nim = "afni" Write AFNI volume to disk.

nim = "ANY" Not implemented.

Author(s)

Karsten Tabelow <karsten.tabelow@wias-berlin.de>

References

AFNI

<http://afni.nimh.nih.gov/pub/dist/src/README.attributes>

See Also

[writeANALYZE](#), [writeNIFTI](#)

Examples

```
## Taken from the AFNI Matlab Library
## http://afni.nimh.nih.gov/pub/dist/data/afni_matlab_data.tgz
afni.path <- system.file("afni", package="oro.nifti")
orig <- readAFNI(file.path(afni.path, "ARzs_CW_avvr.DEL+orig"))
writeAFNI(orig, "test-afni-image", verbose=TRUE)

data <- readAFNI("test-afni-image", verbose=TRUE)
image(orig, zlim=c(0.5,256), oma=rep(2,4), bg="white")
image(data, zlim=c(0.5,256), oma=rep(2,4), bg="white")
abs.err <- abs(data - orig)
image(as(abs.err, "nifti"), zlim=range(0,1), oma=rep(2,4),
      bg="white")
```

writeANALYZE-methods *writeANALYZE*

Description

This function saves an Analyze-class object to a single binary file in Analyze format.

Usage

```
## S4 method for signature 'anlz'  
writeANALYZE(aim, filename, gzipped = TRUE,  
             verbose = FALSE, warn = -1, compression = 6)
```

Arguments

aim	is an object of class <code>anlz</code> .
filename	is the path and file name to save the Analyze file pair (<code>.hdr,img</code>) without the suffixes.
gzipped	is a character string that enables exportation of compressed (<code>.gz</code>) files (default = <code>TRUE</code>).
verbose	is a logical variable (default = <code>FALSE</code>) that allows text-based feedback during execution of the function.
warn	is a number to regulate the display of warnings (default = <code>-1</code>). See options for more details.
compression	The amount of compression to be applied when writing a file when <code>gzipped = TRUE</code>

Details

The `writeANALYZE` function utilizes the internal `writeBin` and `writeChar` command to write information to a binary file.

Value

Nothing.

Methods

object = "anlz" Write ANALYZE volume to disk.

Author(s)

Brandon Whitcher <bwhitcher@gmail.com>

References

Analyze 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>

See Also

[writeAFNI](#), [writeNIfTI](#)

Examples

```
norm <- dnorm(seq(-5, 5, length=32), sd=2)
norm <- (norm-min(norm)) / max(norm-min(norm))
img <- outer(outer(norm, norm), norm)
img <- round(255*img)
img[17:32,,] <- 255 - img[17:32,,]
img.anlz <- anlz(img) # create Analyze object

writeANALYZE(img.anlz, "test-anlz-image-uint8", verbose=TRUE)
## These files should be viewable in, for example, FSLview
## Make sure you adjust the min/max values for proper visualization
data <- readANALYZE("test-anlz-image-uint8", verbose=TRUE)
image(img.anlz, oma=rep(2,4), bg="white")
image(data, oma=rep(2,4), bg="white")
abs.err <- abs(data - img.anlz)
image(as(abs.err, "anlz"), zlim=range(img.anlz), oma=rep(2,4), bg="white")

## Not run:
## Loop through all possible data types
datatypes <- list(code=c(2, 4, 8, 16, 64),
                  name=c("uint8", "int16", "int32", "float", "double"))
equal <- vector("list")
for (i in 1:length(datatypes$code)) {
  fname <- paste("test-anlz-image-", datatypes$name[i], sep="")
  rm(img.anlz)
  img.anlz <- anlz(img, datatype=datatypes$code[i])
  writeANALYZE(img.anlz, fname)
  equal[[i]] <- all(readANALYZE(fname) == img)
}
names(equal) <- datatypes$name
unlist(equal)

## End(Not run)
```

writeNIfTI-methods

writeNIfTI

Description

This function saves a NIfTI-class object to a single binary file in NIfTI format.

Usage

```
## S4 method for signature 'nifti'
writeNIfTI(nim, filename, onefile = TRUE, gzipped = TRUE,
  verbose = FALSE, warn = -1, compression = 6)

## S4 method for signature 'anlz'
writeNIfTI(nim, filename, onefile = TRUE, gzipped = TRUE,
  verbose = FALSE, warn = -1, compression = 6)

## S4 method for signature 'array'
writeNIfTI(nim, filename, onefile = TRUE, gzipped = TRUE,
  verbose = FALSE, warn = -1, compression = 6)
```

Arguments

nim	is an object of class nifti or anlz.
filename	is the path and file name to save the NIfTI file (.nii) without the suffix.
onefile	is a logical value that allows the scanning of single-file (.nii) or dual-file format (.hdr and .img) NIfTI files (default = TRUE).
gzipped	is a character string that enables exportation of compressed (.gz) files (default = TRUE).
verbose	is a logical variable (default = FALSE) that allows text-based feedback during execution of the function.
warn	is a number to regulate the display of warnings (default = -1). See options for more details.
compression	The amount of compression to be applied when writing a file when gzipped = TRUE

Details

The writeNIfTI function utilizes the internal writeBin and writeChar command to write information to a binary file.

Current acceptable data types include

```
list("UINT8") DT BINARY (1 bit per voxel)
list("INT16") DT SIGNED SHORT (16 bits per voxel)
list("INT32") DT SIGNED INT (32 bits per voxel)
list("FLOAT32") DT FLOAT (32 bits per voxel)
list("DOUBLE64") DT DOUBLE (64 bits per voxel)
list("UINT16") DT UNSIGNED SHORT (16 bits per voxel)
```

Value

Nothing.

Methods

object = "anzl" Convert ANALYZE object to class nifti and write the NIfTI volume to disk.

object = "array" Convert array to class nifti and write the NIfTI volume to disk.

object = "nifti" Write NIfTI volume to disk.

Author(s)

Brandon Whitcer <bwhitcer@gmail.com>,
Volker Schmid <volkerschmid@users.sourceforge.net>

References

NIfTI-1
<http://nifti.nimh.nih.gov/>

See Also

[writeAFNI](#), [writeANALYZE](#)

Examples

```
norm <- dnorm(seq(-5, 5, length=32), sd=2)
norm <- (norm-min(norm)) / max(norm-min(norm))
img <- outer(outer(norm, norm), norm)
img <- round(255 * img)
img[17:32,,] <- 255 - img[17:32,,]
img.nifti <- nifti(img) # create NIfTI object

writeNIfTI(img.nifti, "test-nifti-image-uint8", verbose=TRUE)
## These files should be viewable in, for example, FSLview
## Make sure you adjust the min/max values for proper visualization
data <- readNIfTI("test-nifti-image-uint8", verbose=TRUE)
image(img.nifti, oma=rep(2,4), bg="white")
image(data, oma=rep(2,4), bg="white")
abs.err <- abs(data - img.nifti)
image(as(abs.err, "nifti"), zlim=range(img.nifti), oma=rep(2,4),
      bg="white")

## Not run:
## Loop through all possible data types
datatypes <- list(code=c(2, 4, 8, 16, 64),
                 name=c("uint8", "int16", "int32", "float", "double"))
equal <- vector("list")
for (i in 1:length(datatypes$code)) {
  fname <- paste("test-nifti-image-", datatypes$name[i], sep="")
  rm(img.nifti)
  img.nifti <- nifti(img, datatype=datatypes$code[i])
  writeNIfTI(img.nifti, fname, verbose=TRUE)
  equal[[i]] <- all(readNIfTI(fname) == img)
}
```

```

names(equal) <- datatypes$name
unlist(equal)

## End(Not run)

```

xyzt2space

Bitwise Conversion Subroutines

Description

Units of spatial and temporal dimensions, and MRI-specific spatial and temporal information.

Usage

```

xyzt2space(xyzt)

xyzt2time(xyzt)

space.time2xyzt(ss, tt)

dim2freq(di)

dim2phase(di)

dim2slice(di)

```

Arguments

xyzt	represents the units of pixdim[1..4] in the NIfTI header.
ss	is the character string of spatial units. Valid strings are: “Unknown”, “meter”, “mm” and “micron”.
tt	is the character string of temporal units. Valid strings are: “sec”, “msec”, “usec”, “Hz”, “ppm” and “rads”.
di	represents MRI slice ordering in the NIfTI header.

Details

The functions `xyzt2space` and `xyzt2time` can be used to mask off the undesired bits from the `xyzt_units` fields, leaving “pure” space and time codes.

http://nifti.nimh.nih.gov/nifti-1/documentation/nifti1fields/nifti1fields_pages/xyzt_units.html

The functions `dim2freq`, `dim2phase`, and `dim2slice` can be used to extract values from the `dim_info` byte.

http://nifti.nimh.nih.gov/nifti-1/documentation/nifti1fields/nifti1fields_pages/dim_info.html

Value

For `diminfo`: the frequency, phase and slice dimensions encode which spatial dimension (1,2, or 3) corresponds to which acquisition dimension for MRI data. For `xyz_t_units`: the codes are used to indicate the units of `pixdim`. Dimensions 1,2,3 are for x,y,z; dimension 4 is for time (t).

Author(s)

B. Whitcher <bwhitcher@gmail.com>

References

Neuroimaging Informatics Technology Initiative (NIFTI)
<http://nifti.nimh.nih.gov/>

See Also

[convert.units](#), [convert.slice](#)

xyz_t_units-methods *Extract Image Attribute xyz_t_units*

Description

Methods that act on the `xyz_t_units` field in the NIFTI/ANALYZE header.

Usage

```
xyz_t_units(object)

## S4 method for signature 'nifti'
xyz_t_units(object)

xyz_t_units(object) <- value

## S4 replacement method for signature 'nifti'
xyz_t_units(object) <- value

xyz_t_units(object)

## S4 method for signature 'nifti'
xyz_t_units(object)

xyz_t_units(object) <- value

## S4 replacement method for signature 'nifti'
xyz_t_units(object) <- value
```


Arguments

object	is an object of class <code>nifti</code> or <code>anz</code> .
value	is the value to assign to the <code>xyzt_units</code> field.

Details

See documentation on the ANALYZE and/or NIFTI data standards for more details.

Author(s)

John Muschelli <muschellij2@gmail.com>,
Brandon Whitcher <bwhitcher@gmail.com>

References

ANALYZE 7.5
<https://rportal.mayo.edu/bir/ANALYZE75.pdf>
NIFTI-1
<http://nifti.nimh.nih.gov/>

Index

- *Topic **Misc**
 - rmniigz, 101
- *Topic **aplot**
 - hotmetal, 53
 - tim.colors, 119
- *Topic **classes**
 - afni-class, 5
 - anlz-class, 8
 - nifti-class, 66
 - niftiAuditTrail-class, 69
 - niftiExtension-class, 70
 - niftiExtensionSection-class, 71
- *Topic **file**
 - readAFNI, 94
 - readANALYZE, 96
 - readNIFTI, 97
 - writeAFNI-methods, 129
 - writeANALYZE-methods, 131
 - writeNIFTI-methods, 132
- *Topic **methods**
 - audit.trail-methods, 16
 - blend, 19
 - coerce-methods, 25
 - image-methods, 54
 - nifti_assign-methods, 71
 - orientation-methods, 77
 - orthographic-methods, 79
 - overlay-methods, 81
 - readAFNI, 94
 - writeAFNI-methods, 129
 - writeANALYZE-methods, 131
 - writeNIFTI-methods, 132
- *Topic **misc**
 - convert.scene, 30
 - nsli, 72
 - xyzt2space, 135
- [<-, ANY, ANY, ANY, ANY-method
(nifti_assign-methods), 71
- [<-, nifti, ANY, ANY, ANY-method
(nifti_assign-methods), 71
- [<-, nifti, missing, missing, array-method
(nifti_assign-methods), 71
- [<-, nifti, numeric, missing, ANY-method
(nifti_assign-methods), 71
- [<-, nifti, numeric, numeric, ANY-method
(nifti_assign-methods), 71
- [<--methods (nifti_assign-methods), 71
- afni, 62, 94, 95
- afni-class, 5
- anlz, 7, 7, 8, 63, 65, 68
- anlz-class, 8
- anlz-nifti-ops, 11
- array, 7, 10, 68
- as, 26
- as, array, anlz-method (coerce-methods),
25
- as, array, nifti-method (coerce-methods),
25
- as.anlz, 12
- as.nifti, 12
- as<-, array, anlz-method
(coerce-methods), 25
- as<-, array, nifti-method
(coerce-methods), 25
- Audit Trails, 13
- audit.trail (audit.trail-methods), 16
- audit.trail, nifti-method
(audit.trail-methods), 16
- audit.trail-methods, 16
- audit.trail<- (audit.trail-methods), 16
- audit.trail<-, nifti-method
(audit.trail-methods), 16
- aux.file (aux_file-methods), 17
- aux.file, anlz-method
(aux_file-methods), 17

- aux.file, nifti-method
(aux_file-methods), 17
- aux.file<- (aux_file-methods), 17
- aux.file<-, anlz-method
(aux_file-methods), 17
- aux.file<-, nifti-method
(aux_file-methods), 17
- aux_file (aux_file-methods), 17
- aux_file, anlz-method
(aux_file-methods), 17
- aux_file, nifti-method
(aux_file-methods), 17
- aux_file-methods, 17
- aux_file-methods, (aux_file-methods), 17
- aux_file<- (aux_file-methods), 17
- aux_file<-, anlz-method
(aux_file-methods), 17
- aux_file<-, nifti-method
(aux_file-methods), 17

- bitpix (bitpix-methods), 18
- bitpix, anlz-method (bitpix-methods), 18
- bitpix, nifti-method (bitpix-methods), 18
- bitpix-methods, 18
- bitpix-methods, (bitpix-methods), 18
- bitpix<- (bitpix-methods), 18
- bitpix<-, anlz-method (bitpix-methods),
18
- bitpix<-, nifti-method (bitpix-methods),
18
- blend, 19
- blend, anlz, anlz-method (blend), 19
- blend, anlz, anlz-methods (blend), 19
- blend, anlz, nifti-method (blend), 19
- blend, anlz, nifti-methods (blend), 19
- blend, nifti, anlz-method (blend), 19
- blend, nifti, anlz-methods (blend), 19
- blend, nifti, nifti-method (blend), 19
- blend, nifti, nifti-methods (blend), 19
- blendVolumes (blend), 19

- cal.max (cal_max-methods), 21
- cal.max, anlz-method (cal_max-methods),
21
- cal.max, nifti-method (cal_max-methods),
21
- cal.max<- (cal_max-methods), 21
- cal.max<-, anlz-method
(cal_max-methods), 21

- cal.min (cal_min-methods), 23
- cal.min, anlz-method (cal_min-methods),
23
- cal.min, nifti-method (cal_min-methods),
23
- cal.min<- (cal_min-methods), 23
- cal.min<-, anlz-method
(cal_min-methods), 23
- cal.min<-, nifti-method
(cal_min-methods), 23
- cal.min<-, nifti-method (cal_min-methods),
23
- cal.min<-, nifti-method (cal_min-methods),
23
- cal.min-methods, 23
- cal.min-methods, (cal_min-methods), 23
- cal.min<- (cal_min-methods), 23
- cal.min<-, anlz-method
(cal_min-methods), 23
- cal.min<-, nifti-method
(cal_min-methods), 23
- cal_min (cal_min-methods), 23
- cal_min, anlz-method (cal_min-methods),
23
- cal_min, nifti-method (cal_min-methods),
23
- cal_min-methods, 23
- cal_min-methods, (cal_min-methods), 23
- cal_min<- (cal_min-methods), 23
- cal_min<-, anlz-method
(cal_min-methods), 23
- cal_min<-, nifti-method
(cal_min-methods), 23
- cal_units (cal_units-methods), 24
- cal_units, anlz-method
(cal_units-methods), 24
- cal_units, nifti-method
(cal_units-methods), 24
- cal_units<- (cal_units-methods), 24
- cal_units<-, anlz-method
(cal_units-methods), 24
- cal_img (calibrateImage), 20
- cal_max (cal_max-methods), 21
- cal_max, anlz-method (cal_max-methods),
21
- cal_max, nifti-method (cal_max-methods),
21
- cal_max-methods, 21
- cal_max-methods, (cal_max-methods), 21
- cal_max<- (cal_max-methods), 21
- cal_max<-, anlz-method
(cal_max-methods), 21
- cal_max<-, nifti-method
(cal_max-methods), 21
- cal_min (cal_min-methods), 23
- cal_min, anlz-method (cal_min-methods),
23
- cal_min, nifti-method (cal_min-methods),
23
- cal_min-methods, 23
- cal_min-methods, (cal_min-methods), 23
- cal_min<- (cal_min-methods), 23
- cal_min<-, anlz-method
(cal_min-methods), 23
- cal_min<-, nifti-method
(cal_min-methods), 23
- cal_units (cal_units-methods), 24
- cal_units, anlz-method
(cal_units-methods), 24

- cal_units-methods, [24](#)
- cal_units-methods, (cal_units-methods), [24](#)
- cal_units<- (cal_units-methods), [24](#)
- cal_units<- ,anzl-method (cal_units-methods), [24](#)
- calibrateImage, [20](#)
- coerce,anzl,nifti-method (coerce-methods), [25](#)
- coerce,array,anzl-method (coerce-methods), [25](#)
- coerce,array,nifti-method (coerce-methods), [25](#)
- coerce,list,anzl-method (coerce-methods), [25](#)
- coerce,list,nifti-method (coerce-methods), [25](#)
- coerce-methods, [25](#)
- coerce<- ,anzl,nifti-method (coerce-methods), [25](#)
- coerce<- ,array,anzl-method (coerce-methods), [25](#)
- coerce<- ,array,nifti-method (coerce-methods), [25](#)
- coerce<- ,list,anzl-method (coerce-methods), [25](#)
- coerce<- ,list,nifti-method (coerce-methods), [25](#)
- compressed (compressed-methods), [26](#)
- compressed,anzl-method (compressed-methods), [26](#)
- compressed-methods, [26](#)
- compressed-methods, (compressed-methods), [26](#)
- compressed<- (compressed-methods), [26](#)
- compressed<- ,anzl-method (compressed-methods), [26](#)
- Convert ANALYZE Codes, [27](#)
- Convert NIfTI Codes, [28](#)
- convert.bitpix, [28](#)
- convert.bitpix (Convert NIfTI Codes), [28](#)
- convert.bitpix.anzl (Convert ANALYZE Codes), [27](#)
- convert.datatype, [28](#), [65](#)
- convert.datatype (Convert NIfTI Codes), [28](#)
- convert.datatype.anzl, [8](#), [30](#)
- convert.datatype.anzl (Convert ANALYZE Codes), [27](#)
- convert.form, [28](#)
- convert.form (Convert NIfTI Codes), [28](#)
- convert.intent, [28](#)
- convert.intent (Convert NIfTI Codes), [28](#)
- convert.orient.anzl, [30](#)
- convert.orient.anzl (Convert ANALYZE Codes), [27](#)
- convert.scene, [30](#)
- convert.slice, [28](#), [136](#)
- convert.slice (Convert NIfTI Codes), [28](#)
- convert.units, [28](#), [136](#)
- convert.units (Convert NIfTI Codes), [28](#)
- data.type (data_type-methods), [32](#)
- data.type,anzl-method (data_type-methods), [32](#)
- data.type,nifti-method (data_type-methods), [32](#)
- data.type<- (data_type-methods), [32](#)
- data.type<- ,anzl-method (data_type-methods), [32](#)
- data.type<- ,nifti-method (data_type-methods), [32](#)
- data_type (data_type-methods), [32](#)
- data_type,anzl-method (data_type-methods), [32](#)
- data_type,nifti-method (data_type-methods), [32](#)
- data_type-methods, [32](#)
- data_type-methods, (data_type-methods), [32](#)
- data_type<- (data_type-methods), [32](#)
- data_type<- ,anzl-method (data_type-methods), [32](#)
- data_type<- ,nifti-method (data_type-methods), [32](#)
- datatype (datatype-methods), [31](#)
- datatype,anzl-method (datatype-methods), [31](#)
- datatype,nifti-method (datatype-methods), [31](#)
- datatype-methods, [31](#)
- datatype-methods, (datatype-methods), [31](#)
- datatype<- (datatype-methods), [31](#)
- datatype<- ,anzl-method (datatype-methods), [31](#)
- datatype<- ,nifti-method (datatype-methods), [31](#)

- db.name (db_name-methods), 33
- db.name, anlz-method (db_name-methods), 33
- db.name, nifti-method (db_name-methods), 33
- db.name<- (db_name-methods), 33
- db.name<-, anlz-method (db_name-methods), 33
- db.name<-, nifti-method (db_name-methods), 33
- db_name (db_name-methods), 33
- db_name, anlz-method (db_name-methods), 33
- db_name, nifti-method (db_name-methods), 33
- db_name-methods, 33
- db_name-methods, (db_name-methods), 33
- db_name<- (db_name-methods), 33
- db_name<-, anlz-method (db_name-methods), 33
- db_name<-, nifti-method (db_name-methods), 33
- descrip (descrip-methods), 34
- descrip, anlz-method (descrip-methods), 34
- descrip, nifti-method (descrip-methods), 34
- descrip-methods, 34
- descrip-methods, (descrip-methods), 34
- descrip<- (descrip-methods), 34
- descrip<-, anlz-method (descrip-methods), 34
- descrip<-, nifti-method (descrip-methods), 34
- dim2freq (xyzt2space), 135
- dim2phase (xyzt2space), 135
- dim2slice (xyzt2space), 135
- dim_ (dim_-methods), 36
- dim_, anlz-method (dim_-methods), 36
- dim_, nifti-method (dim_-methods), 36
- dim_-methods, 36
- dim_-methods, (dim_-methods), 36
- dim_<- (dim_-methods), 36
- dim_<-, anlz-method (dim_-methods), 36
- dim_<-, nifti-method (dim_-methods), 36
- dim_info (dim_info-methods), 37
- dim_info, nifti-method (dim_info-methods), 37
- dim_info-methods, 37
- dim_info-methods, (dim_info-methods), 37
- dim_info<- (dim_info-methods), 37
- dim_info<-, nifti-method (dim_info-methods), 37
- dim_un0 (dim_un0-methods), 38
- dim_un0, anlz-method (dim_un0-methods), 38
- dim_un0-methods, 38
- dim_un0-methods, (dim_un0-methods), 38
- dim_un0<- (dim_un0-methods), 38
- dim_un0<-, anlz-method (dim_un0-methods), 38
- drop_img_dim (dropImageDimension), 39
- dropImageDimension, 39
- enableAuditTrail (Audit Trails), 13
- exp_date (exp_date-methods), 40
- exp_date, anlz-method (exp_date-methods), 40
- exp_date-methods, 40
- exp_date-methods, (exp_date-methods), 40
- exp_date<- (exp_date-methods), 40
- exp_date<-, anlz-method (exp_date-methods), 40
- exp_time (exp_time-methods), 41
- exp_time, anlz-method (exp_time-methods), 41
- exp_time-methods, 41
- exp_time-methods, (exp_time-methods), 41
- exp_time<- (exp_time-methods), 41
- exp_time<-, anlz-method (exp_time-methods), 41
- extender (extender-methods), 42
- extender, nifti-method (extender-methods), 42
- extender-methods, 42
- extender-methods, (extender-methods), 42
- extender<- (extender-methods), 42
- extender<-, nifti-method (extender-methods), 42
- extents (extents-methods), 43
- extents, anlz-method (extents-methods), 43
- extents, nifti-method (extents-methods), 43
- extents-methods, 43
- extents-methods, (extents-methods), 43
- extents<- (extents-methods), 43

- extents<- ,anzl-method
(extents-methods), 43
- extents<- ,nifti-method
(extents-methods), 43
- field.skip (field_skip-methods), 44
- field.skip,anzl-method
(field_skip-methods), 44
- field.skip,nifti-method
(field_skip-methods), 44
- field.skip<- (field_skip-methods), 44
- field.skip<- ,anzl-method
(field_skip-methods), 44
- field_skip (field_skip-methods), 44
- field_skip,anzl-method
(field_skip-methods), 44
- field_skip-methods, 44
- field_skip-methods,
(field_skip-methods), 44
- field_skip<- (field_skip-methods), 44
- field_skip<- ,anzl-method
(field_skip-methods), 44
- funused1 (funused1-methods), 45
- funused1,anzl-method
(funused1-methods), 45
- funused1-methods, 45
- funused1-methods, (funused1-methods), 45
- funused1<- (funused1-methods), 45
- funused1<- ,anzl-method
(funused1-methods), 45
- funused2 (funused2-methods), 46
- funused2,anzl-method
(funused2-methods), 46
- funused2-methods, 46
- funused2-methods, (funused2-methods), 46
- funused2<- (funused2-methods), 46
- funused2<- ,anzl-method
(funused2-methods), 46
- funused3 (funused3-methods), 47
- funused3,anzl-method
(funused3-methods), 47
- funused3-methods, 47
- funused3-methods, (funused3-methods), 47
- funused3<- (funused3-methods), 47
- funused3<- ,anzl-method
(funused3-methods), 47
- generated (generated-methods), 48
- generated,anzl-method
(generated-methods), 48
- generated-methods, 48
- generated-methods, (generated-methods),
48
- generated<- (generated-methods), 48
- generated<- ,anzl-method
(generated-methods), 48
- getLastCallWithName (Audit Trails), 13
- glmax (glmax-methods), 49
- glmax,anzl-method (glmax-methods), 49
- glmax,nifti-method (glmax-methods), 49
- glmax-methods, 49
- glmax-methods, (glmax-methods), 49
- glmax<- (glmax-methods), 49
- glmax<- ,anzl-method (glmax-methods), 49
- glmax<- ,nifti-method (glmax-methods), 49
- glmin (glmin-methods), 50
- glmin,anzl-method (glmin-methods), 50
- glmin,nifti-method (glmin-methods), 50
- glmin-methods, 50
- glmin-methods, (glmin-methods), 50
- glmin<- (glmin-methods), 50
- glmin<- ,anzl-method (glmin-methods), 50
- glmin<- ,nifti-method (glmin-methods), 50
- hist_un0 (hist_un0-methods), 51
- hist_un0,anzl-method
(hist_un0-methods), 51
- hist_un0-methods, 51
- hist_un0-methods, (hist_un0-methods), 51
- hist_un0<- (hist_un0-methods), 51
- hist_un0<- ,anzl-method
(hist_un0-methods), 51
- hkey.un0 (hkey_un0-methods), 52
- hkey.un0,anzl-method
(hkey_un0-methods), 52
- hkey.un0,nifti-method
(hkey_un0-methods), 52
- hkey.un0<- (hkey_un0-methods), 52
- hkey.un0<- ,anzl-method
(hkey_un0-methods), 52
- hkey_un0 (hkey_un0-methods), 52
- hkey_un0,anzl-method
(hkey_un0-methods), 52
- hkey_un0-methods, 52
- hkey_un0-methods, (hkey_un0-methods), 52
- hkey_un0<- (hkey_un0-methods), 52

- hkey_un0<- ,anzl-method
(hkey_un0-methods), 52
- hotmetal, 53, 119
- image, 55
- image,afni-method (image-methods), 54
- image,anzl-method (image-methods), 54
- image,ANY-method (image-methods), 54
- image,nifti-method (image-methods), 54
- image-methods, 54
- image.nifti (image-methods), 54
- img_data (img_data-methods), 55
- img_data,anzl-method
(img_data-methods), 55
- img_data,ANY-method (img_data-methods),
55
- img_data,character-method
(img_data-methods), 55
- img_data,nifti-method
(img_data-methods), 55
- img_data-methods, 55
- img_data-methods, (img_data-methods), 55
- img_data<- (img_data-methods), 55
- img_data<- ,anzl-method
(img_data-methods), 55
- img_data<- ,nifti-method
(img_data-methods), 55
- integerTranslation, 56
- intent.code (intent_code-methods), 57
- intent.code,nifti-method
(intent_code-methods), 57
- intent.code<- (intent_code-methods), 57
- intent.code<- ,nifti-method
(intent_code-methods), 57
- intent.name (intent_name-methods), 58
- intent.name,nifti-method
(intent_name-methods), 58
- intent.name<- (intent_name-methods), 58
- intent.name<- ,nifti-method
(intent_name-methods), 58
- intent.p1 (intent_p1-methods), 59
- intent.p1,nifti-method
(intent_p1-methods), 59
- intent.p1<- (intent_p1-methods), 59
- intent.p1<- ,nifti-method
(intent_p1-methods), 59
- intent.p2 (intent_p2-methods), 60
- intent.p2,nifti-method
(intent_p2-methods), 60
- intent.p2-methods, 60
- intent.p2-methods, (intent_p2-methods),
60
- intent.p2<- (intent_p2-methods), 60
- intent.p2<- ,nifti-method
(intent_p2-methods), 60
- intent.p3 (intent_p3-methods), 61
- intent.p3,nifti-method
(intent_p3-methods), 61
- intent.p3<- (intent_p3-methods), 61
- intent.p3<- ,nifti-method
(intent_p3-methods), 61
- intent_code (intent_code-methods), 57
- intent_code,nifti-method
(intent_code-methods), 57
- intent_code-methods, 57
- intent_code-methods,
(intent_code-methods), 57
- intent_code<- (intent_code-methods), 57
- intent_code<- ,nifti-method
(intent_code-methods), 57
- intent_name (intent_name-methods), 58
- intent_name,nifti-method
(intent_name-methods), 58
- intent_name-methods, 58
- intent_name-methods,
(intent_name-methods), 58
- intent_name<- (intent_name-methods), 58
- intent_name<- ,nifti-method
(intent_name-methods), 58
- intent_p1 (intent_p1-methods), 59
- intent_p1,nifti-method
(intent_p1-methods), 59
- intent_p1-methods, 59
- intent_p1-methods, (intent_p1-methods),
59
- intent_p1<- (intent_p1-methods), 59
- intent_p1<- ,nifti-method
(intent_p1-methods), 59
- intent_p2 (intent_p2-methods), 60
- intent_p2,nifti-method
(intent_p2-methods), 60
- intent_p2-methods, 60
- intent_p2-methods, (intent_p2-methods),
60
- intent_p2<- (intent_p2-methods), 60
- intent_p2<- ,nifti-method
(intent_p2-methods), 60
- intent_p3 (intent_p3-methods), 61
- intent_p3,nifti-method
(intent_p3-methods), 61

- intent_p3-methods, [61](#)
- intent_p3-methods, (intent_p3-methods), [61](#)
- intent_p3<- (intent_p3-methods), [61](#)
- intent_p3<- ,nifti-method (intent_p3-methods), [61](#)
- inverseReorient, [85](#)
- inverseReorient (reorient), [100](#)
- invertIntegerTranslation (integerTranslation), [56](#)
- is.afni, [62](#)
- is.anlz, [63](#)
- is.nifti, [63](#)

- magic (magic-methods), [64](#)
- magic,nifti-method (magic-methods), [64](#)
- magic-methods, [64](#)
- magic-methods, (magic-methods), [64](#)
- magic<- (magic-methods), [64](#)
- magic<- ,nifti-method (magic-methods), [64](#)
- matrix, [7](#), [10](#), [68](#)

- newAuditTrail (Audit Trails), [13](#)
- nifti, [7](#), [8](#), [10](#), [63–65](#), [65](#), [70–72](#), [79](#), [97](#)
- nifti-class, [66](#)
- nifti-operators, [68](#)
- nifti_assign-methods, [71](#)
- niftiAuditTrail, [68](#), [70](#)
- niftiAuditTrail-class, [69](#)
- niftiAuditTrailCreated (Audit Trails), [13](#)
- niftiAuditTrailEvent (Audit Trails), [13](#)
- niftiAuditTrailSystemNode (Audit Trails), [13](#)
- niftiAuditTrailSystemNodeEvent (Audit Trails), [13](#)
- niftiAuditTrailToExtension (Audit Trails), [13](#)
- niftiExtension, [10](#), [68](#), [70](#), [71](#)
- niftiExtension-class, [70](#)
- niftiExtensionSection-class, [71](#)
- niftiExtensionToAuditTrail (Audit Trails), [13](#)
- nii2oro, [72](#)
- NSLI (nqli), [72](#)
- nqli, [72](#)
- NTIM (nqli), [72](#)
- ntim (nqli), [72](#)

- omax (omax-methods), [73](#)
- omax,anzl-method (omax-methods), [73](#)
- omax-methods, [73](#)
- omax-methods, (omax-methods), [73](#)
- omax<- (omax-methods), [73](#)
- omax<- ,anzl-method (omax-methods), [73](#)
- omin (omin-methods), [74](#)
- omin,anzl-method (omin-methods), [74](#)
- omin-methods, [74](#)
- omin-methods, (omin-methods), [74](#)
- omin<- (omin-methods), [74](#)
- omin<- ,anzl-method (omin-methods), [74](#)
- onfile, [75](#)
- Ops,anzl,anzl-method (anzl-nifti-ops), [11](#)
- Ops,anzl,nifti-method (anzl-nifti-ops), [11](#)
- Ops,anzl,numeric-method (anzl-nifti-ops), [11](#)
- Ops,nifti,anzl-method (anzl-nifti-ops), [11](#)
- Ops,nifti,nifti-method (nifti-operators), [68](#)
- Ops,nifti,numeric-method (nifti-operators), [68](#)
- Ops,numeric,anzl-method (anzl-nifti-ops), [11](#)
- Ops,numeric,nifti-method (nifti-operators), [68](#)
- options, [129](#), [131](#), [133](#)
- orient (orient-methods), [76](#)
- orient,anzl-method (orient-methods), [76](#)
- orient-methods, [76](#)
- orient-methods, (orient-methods), [76](#)
- orient<- (orient-methods), [76](#)
- orient<- ,anzl-method (orient-methods), [76](#)
- orientation-methods, [77](#)
- origin (origin-methods), [78](#)
- origin,anzl-method (origin-methods), [78](#)
- origin-methods, [78](#)
- origin-methods, (origin-methods), [78](#)
- origin<- (origin-methods), [78](#)
- origin<- ,anzl-method (origin-methods), [78](#)
- oro.nifti.info (Audit Trails), [13](#)
- oro2nii, [79](#)
- orthographic (orthographic-methods), [79](#)

- orthographic,afni-method
(orthographic-methods), 79
- orthographic,anlz-method
(orthographic-methods), 79
- orthographic,array-method
(orthographic-methods), 79
- orthographic,nifti-method
(orthographic-methods), 79
- orthographic-methods, 79
- orthographic.nifti
(orthographic-methods), 79
- overlay (overlay-methods), 81
- overlay,afni,afni-method
(overlay-methods), 81
- overlay,afni,array-method
(overlay-methods), 81
- overlay,anlz,anlz-method
(overlay-methods), 81
- overlay,anlz,array-method
(overlay-methods), 81
- overlay,anlz,nifti-method
(overlay-methods), 81
- overlay,array,anlz-method
(overlay-methods), 81
- overlay,array,array-method
(overlay-methods), 81
- overlay,array,nifti-method
(overlay-methods), 81
- overlay,nifti,anlz-method
(overlay-methods), 81
- overlay,nifti,array-method
(overlay-methods), 81
- overlay,nifti,nifti-method
(overlay-methods), 81
- overlay-methods, 81
- overlay.nifti (overlay-methods), 81
- patient.id (patient_id-methods), 83
- patient.id,anlz-method
(patient_id-methods), 83
- patient.id,nifti-method
(patient_id-methods), 83
- patient.id<- (patient_id-methods), 83
- patient.id<-,anlz-method
(patient_id-methods), 83
- patient_id (patient_id-methods), 83
- patient_id,anlz-method
(patient_id-methods), 83
- patient_id-methods, 83
- patient_id-methods,
(patient_id-methods), 83
- patient_id<- (patient_id-methods), 83
- patient_id<- ,anlz-method
(patient_id-methods), 83
- performPermutation, 84, 100
- pixdim (pixdim-methods), 85
- pixdim,anlz-method (pixdim-methods), 85
- pixdim,nifti-method (pixdim-methods), 85
- pixdim-methods, 85
- pixdim-methods, (pixdim-methods), 85
- pixdim<- (pixdim-methods), 85
- pixdim<- ,anlz-method (pixdim-methods),
85
- pixdim<- ,nifti-method (pixdim-methods),
85
- qform (orientation-methods), 77
- qform,nifti-method
(orientation-methods), 77
- qform-methods (orientation-methods), 77
- qform.code (qform_code-methods), 86
- qform.code,nifti-method
(qform_code-methods), 86
- qform.code<- (qform_code-methods), 86
- qform.code<- ,nifti-method
(qform_code-methods), 86
- qform_code (qform_code-methods), 86
- qform_code,nifti-method
(qform_code-methods), 86
- qform_code-methods, 86
- qform_code-methods,
(qform_code-methods), 86
- qform_code<- (qform_code-methods), 86
- qform_code<- ,nifti-method
(qform_code-methods), 86
- qoffset.x (qoffset_x-methods), 87
- qoffset.x,nifti-method
(qoffset_x-methods), 87
- qoffset.x<- (qoffset_x-methods), 87
- qoffset.x<- ,nifti-method
(qoffset_x-methods), 87
- qoffset.y (qoffset_y-methods), 88
- qoffset.y,nifti-method
(qoffset_y-methods), 88
- qoffset.y<- (qoffset_y-methods), 88
- qoffset.y<- ,nifti-method
(qoffset_y-methods), 88
- qoffset.z (qoffset_z-methods), 89

- qoffset.z,nifti-method
(qoffset_z-methods), 89
- qoffset.z<- (qoffset_z-methods), 89
- qoffset.z<-,nifti-method
(qoffset_z-methods), 89
- qoffset_x (qoffset_x-methods), 87
- qoffset_x,nifti-method
(qoffset_x-methods), 87
- qoffset_x-methods, 87
- qoffset_x-methods, (qoffset_x-methods), 87
- qoffset_x<- (qoffset_x-methods), 87
- qoffset_x<-,nifti-method
(qoffset_x-methods), 87
- qoffset_y (qoffset_y-methods), 88
- qoffset_y,nifti-method
(qoffset_y-methods), 88
- qoffset_y-methods, 88
- qoffset_y-methods, (qoffset_y-methods), 88
- qoffset_y<- (qoffset_y-methods), 88
- qoffset_y<-,nifti-method
(qoffset_y-methods), 88
- qoffset_z (qoffset_z-methods), 89
- qoffset_z,nifti-method
(qoffset_z-methods), 89
- qoffset_z-methods, 89
- qoffset_z-methods, (qoffset_z-methods), 89
- qoffset_z<- (qoffset_z-methods), 89
- qoffset_z<-,nifti-method
(qoffset_z-methods), 89
- quatern.b (quatern_b-methods), 91
- quatern.b,nifti-method
(quatern_b-methods), 91
- quatern.b<- (quatern_b-methods), 91
- quatern.b<-,nifti-method
(quatern_b-methods), 91
- quatern.c (quatern_c-methods), 92
- quatern.c,nifti-method
(quatern_c-methods), 92
- quatern.c<- (quatern_c-methods), 92
- quatern.c<-,nifti-method
(quatern_c-methods), 92
- quatern.d (quatern_d-methods), 93
- quatern.d,nifti-method
(quatern_d-methods), 93
- quatern.d<- (quatern_d-methods), 93
- quatern.d<-,nifti-method
(quatern_d-methods), 93
- quatern.d<- ,nifti-method
(quatern_d-methods), 93
- quatern_b (quatern_b-methods), 91
- quatern_b,nifti-method
(quatern_b-methods), 91
- quatern_b-methods, 91
- quatern_b-methods, (quatern_b-methods), 91
- quatern_b<- (quatern_b-methods), 91
- quatern_b<- ,nifti-method
(quatern_b-methods), 91
- quatern_c (quatern_c-methods), 92
- quatern_c,nifti-method
(quatern_c-methods), 92
- quatern_c-methods, 92
- quatern_c-methods, (quatern_c-methods), 92
- quatern_c<- (quatern_c-methods), 92
- quatern_c<- ,nifti-method
(quatern_c-methods), 92
- quatern_d (quatern_d-methods), 93
- quatern_d,nifti-method
(quatern_d-methods), 93
- quatern_d-methods, 93
- quatern_d-methods, (quatern_d-methods), 93
- quatern_d<- (quatern_d-methods), 93
- quatern_d<- ,nifti-method
(quatern_d-methods), 93
- quaternion2mat44 (quaternion2rotation), 90
- quaternion2rotation, 90
- readAFNI, 94, 98
- readANALYZE, 73, 95, 96, 98
- readNIfTI, 73, 95, 96, 97
- regular (regular-methods), 99
- regular, anlz-method (regular-methods), 99
- regular,nifti-method (regular-methods), 99
- regular-methods, 99
- regular-methods, (regular-methods), 99
- regular<- (regular-methods), 99
- regular<-, anlz-method
(regular-methods), 99
- regular<-,nifti-method
(regular-methods), 99
- reorient, 84, 85, 100

- resetSlopeIntercept, 101
- rmgz (rmniigz), 101
- rmhdr (rmniigz), 101
- rmhdrgz (rmniigz), 101
- rmimg (rmniigz), 101
- rmimggz (rmniigz), 101
- rmnii (rmniigz), 101
- rmniigz, 101

- scannum (scannum-methods), 102
- scannum, anlz-method (scannum-methods), 102
- scannum-methods, 102
- scannum-methods, (scannum-methods), 102
- scannum<- (scannum-methods), 102
- scannum<-, anlz-method (scannum-methods), 102
- scl.inter (scl_inter-methods), 103
- scl.inter, nifti-method (scl_inter-methods), 103
- scl.inter<- (scl_inter-methods), 103
- scl.inter<-, nifti-method (scl_inter-methods), 103
- scl.slope (scl_slope-methods), 104
- scl.slope, nifti-method (scl_slope-methods), 104
- scl.slope<- (scl_slope-methods), 104
- scl.slope<-, nifti-method (scl_slope-methods), 104
- scl_inter (scl_inter-methods), 103
- scl_inter, nifti-method (scl_inter-methods), 103
- scl_inter-methods, 103
- scl_inter-methods, (scl_inter-methods), 103
- scl_inter<- (scl_inter-methods), 103
- scl_inter<-, nifti-method (scl_inter-methods), 103
- scl_slope (scl_slope-methods), 104
- scl_slope, nifti-method (scl_slope-methods), 104
- scl_slope-methods, 104
- scl_slope-methods, (scl_slope-methods), 104
- scl_slope<- (scl_slope-methods), 104
- scl_slope<-, nifti-method (scl_slope-methods), 104
- session.error (session_error-methods), 105
- session.error, anlz-method (session_error-methods), 105
- session.error, nifti-method (session_error-methods), 105
- session.error<- (session_error-methods), 105
- session.error<-, anlz-method (session_error-methods), 105
- session.error<-, nifti-method (session_error-methods), 105
- session_error (session_error-methods), 105
- session_error, anlz-method (session_error-methods), 105
- session_error, nifti-method (session_error-methods), 105
- session_error-methods, 105
- session_error-methods, (session_error-methods), 105
- session_error<- (session_error-methods), 105
- session_error<-, anlz-method (session_error-methods), 105
- session_error<-, nifti-method (session_error-methods), 105
- sform (orientation-methods), 77
- sform, nifti-method (orientation-methods), 77
- sform-methods (orientation-methods), 77
- sform.code (sform_code-methods), 106
- sform.code, nifti-method (sform_code-methods), 106
- sform.code<- (sform_code-methods), 106
- sform.code<-, nifti-method (sform_code-methods), 106
- sform_code (sform_code-methods), 106
- sform_code, nifti-method (sform_code-methods), 106
- sform_code-methods, 106
- sform_code-methods, (sform_code-methods), 106
- sform_code<- (sform_code-methods), 106
- sform_code<-, nifti-method (sform_code-methods), 106
- show, afni-method (afni-class), 5
- show, anlz-method (anlz-class), 8
- show, nifti-method (nifti-class), 66
- sizeof.hdr (sizeof_hdr-methods), 107

- sizeof_hdr, anlz-method
(sizeof_hdr-methods), 107
- sizeof_hdr, nifti-method
(sizeof_hdr-methods), 107
- sizeof_hdr (sizeof_hdr-methods), 107
- sizeof_hdr, anlz-method
(sizeof_hdr-methods), 107
- sizeof_hdr, nifti-method
(sizeof_hdr-methods), 107
- sizeof_hdr-methods, 107
- sizeof_hdr-methods,
(sizeof_hdr-methods), 107
- slice.code (slice_code-methods), 108
- slice.code, nifti-method
(slice_code-methods), 108
- slice.code<- (slice_code-methods), 108
- slice.code<-, nifti-method
(slice_code-methods), 108
- slice.duration
(slice_duration-methods), 109
- slice.duration, nifti-method
(slice_duration-methods), 109
- slice.duration<-
(slice_duration-methods), 109
- slice.duration<-, nifti-method
(slice_duration-methods), 109
- slice.end (slice_end-methods), 110
- slice.end, nifti-method
(slice_end-methods), 110
- slice.end<- (slice_end-methods), 110
- slice.end<-, nifti-method
(slice_end-methods), 110
- slice.start (slice_start-methods), 112
- slice.start, nifti-method
(slice_start-methods), 112
- slice.start<- (slice_start-methods), 112
- slice.start<-, nifti-method
(slice_start-methods), 112
- slice_code (slice_code-methods), 108
- slice_code, nifti-method
(slice_code-methods), 108
- slice_code-methods, 108
- slice_code-methods,
(slice_code-methods), 108
- slice_code<- (slice_code-methods), 108
- slice_code<-, nifti-method
(slice_code-methods), 108
- slice_duration
(slice_duration-methods), 109
- slice_duration, nifti-method
(slice_duration-methods), 109
- slice_duration-methods, 109
- slice_duration-methods,
(slice_duration-methods), 109
- slice_duration<-
(slice_duration-methods), 109
- slice_duration<-, nifti-method
(slice_duration-methods), 109
- slice_end (slice_end-methods), 110
- slice_end, nifti-method
(slice_end-methods), 110
- slice_end-methods, 110
- slice_end-methods, (slice_end-methods),
110
- slice_end<- (slice_end-methods), 110
- slice_end<-, nifti-method
(slice_end-methods), 110
- slice_start (slice_start-methods), 112
- slice_start, nifti-method
(slice_start-methods), 112
- slice_start-methods, 112
- slice_start-methods,
(slice_start-methods), 112
- slice_start<- (slice_start-methods), 112
- slice_start<-, nifti-method
(slice_start-methods), 112
- smax (smax-methods), 113
- smax, anlz-method (smax-methods), 113
- smax-methods, 113
- smax-methods, (smax-methods), 113
- smax<- (smax-methods), 113
- smax<-, anlz-method (smax-methods), 113
- smin (smin-methods), 114
- smin, anlz-method (smin-methods), 114
- smin-methods, 114
- smin-methods, (smin-methods), 114
- smin<- (smin-methods), 114
- smin<-, anlz-method (smin-methods), 114
- space.time2xyzt (xyzt2space), 135
- srow.x (srow_x-methods), 115
- srow.x, nifti-method (srow_x-methods),
115
- srow.x<- (srow_x-methods), 115
- srow.x<-, nifti-method (srow_x-methods),
115
- srow.y (srow_y-methods), 116

- srow.y,nifti-method (srow_y-methods),
116
- srow.y<- (srow_y-methods), 116
- srow.y<- ,nifti-method (srow_y-methods),
116
- srow.z (srow_z-methods), 117
- srow.z,nifti-method (srow_z-methods),
117
- srow.z<- (srow_z-methods), 117
- srow.z<- ,nifti-method (srow_z-methods),
117
- srow_x (srow_x-methods), 115
- srow_x,nifti-method (srow_x-methods),
115
- srow_x-methods, 115
- srow_x-methods, (srow_x-methods), 115
- srow_x<- (srow_x-methods), 115
- srow_x<- ,nifti-method (srow_x-methods),
115
- srow_y (srow_y-methods), 116
- srow_y,nifti-method (srow_y-methods),
116
- srow_y-methods, 116
- srow_y-methods, (srow_y-methods), 116
- srow_y<- (srow_y-methods), 116
- srow_y<- ,nifti-method (srow_y-methods),
116
- srow_z (srow_z-methods), 117
- srow_z,nifti-method (srow_z-methods),
117
- srow_z-methods, 117
- srow_z-methods, (srow_z-methods), 117
- srow_z<- (srow_z-methods), 117
- srow_z<- ,nifti-method (srow_z-methods),
117
- start_field (start_field-methods), 118
- start_field,anlz-method
(start_field-methods), 118
- start_field-methods, 118
- start_field-methods,
(start_field-methods), 118
- start_field<- (start_field-methods), 118
- start_field<- ,anlz-method
(start_field-methods), 118
- structure, 7, 10, 68
- terrain.colors, 53, 119
- tim.colors, 53, 119
- toffset (toffset-methods), 120
- toffset,nifti-method (toffset-methods),
120
- toffset-methods, 120
- toffset-methods, (toffset-methods), 120
- toffset<- (toffset-methods), 120
- toffset<- ,nifti-method
(toffset-methods), 120
- topo.colors, 53, 119
- translateCoordinate, 121
- unused1 (unused1-methods), 122
- unused1,anlz-method (unused1-methods),
122
- unused1-methods, 122
- unused1-methods, (unused1-methods), 122
- unused1<- (unused1-methods), 122
- unused1<- ,anlz-method
(unused1-methods), 122
- vector, 7, 10, 68
- verified (verified-methods), 123
- verified,anlz-method
(verified-methods), 123
- verified-methods, 123
- verified-methods, (verified-methods),
123
- verified<- (verified-methods), 123
- verified<- ,anlz-method
(verified-methods), 123
- views (views-methods), 124
- views,anlz-method (views-methods), 124
- views-methods, 124
- views-methods, (views-methods), 124
- views<- (views-methods), 124
- views<- ,anlz-method (views-methods), 124
- vols.added (vols_added-methods), 125
- vols.added,anlz-method
(vols_added-methods), 125
- vols.added,nifti-method
(vols_added-methods), 125
- vols.added<- (vols_added-methods), 125
- vols.added<- ,anlz-method
(vols_added-methods), 125
- vols_added (vols_added-methods), 125
- vols_added,anlz-method
(vols_added-methods), 125
- vols_added-methods, 125
- vols_added-methods,
(vols_added-methods), 125

- vox.offset (vox_offset-methods), 127
 - vox.offset, anlz-method (vox_offset-methods), 127
 - vox.offset, nifti-method (vox_offset-methods), 127
 - vox.offset<- (vox_offset-methods), 127
 - vox.offset<-, anlz-method (vox_offset-methods), 127
 - vox.offset<-, nifti-method (vox_offset-methods), 127
 - vox.units (vox_units-methods), 128
 - vox.units, anlz-method (vox_units-methods), 128
 - vox.units, nifti-method (vox_units-methods), 128
 - vox.units<- (vox_units-methods), 128
 - vox.units<-, anlz-method (vox_units-methods), 128
 - vox_offset (vox_offset-methods), 127
 - vox_offset, anlz-method (vox_offset-methods), 127
 - vox_offset, nifti-method (vox_offset-methods), 127
 - vox_offset-methods, 127
 - vox_offset-methods, (vox_offset-methods), 127
 - vox_offset<- (vox_offset-methods), 127
 - vox_offset<-, anlz-method (vox_offset-methods), 127
 - vox_offset<-, nifti-method (vox_offset-methods), 127
 - vox_units (vox_units-methods), 128
 - vox_units, anlz-method (vox_units-methods), 128
 - vox_units-methods, 128
 - vox_units-methods, (vox_units-methods), 128
 - vox_units<- (vox_units-methods), 128
 - vox_units<-, anlz-method (vox_units-methods), 128
 - voxdim, 126
 - voxres, 126
- writeAFNI, 132, 134
- writeAFNI (writeAFNI-methods), 129
- writeAFNI, afni-method (writeAFNI-methods), 129
- writeAFNI, ANY-method (writeAFNI-methods), 129
- writeAFNI-methods, 129
- writeANALYZE, 130, 134
- writeANALYZE (writeANALYZE-methods), 131
- writeANALYZE, anlz-method (writeANALYZE-methods), 131
- writeANALYZE-methods, 131
- writeNIfTI, 75, 79, 130, 132
- writeNIfTI (writeNIfTI-methods), 132
- writeNIfTI, anlz-method (writeNIfTI-methods), 132
- writeNIfTI, array-method (writeNIfTI-methods), 132
- writeNIfTI, nifti-method (writeNIfTI-methods), 132
- writeNIfTI-methods, 132
- xyzt.units (xyzt_units-methods), 136
- xyzt.units, nifti-method (xyzt_units-methods), 136
- xyzt.units<- (xyzt_units-methods), 136
- xyzt.units<-, nifti-method (xyzt_units-methods), 136
- xyzt2space, 135
- xyzt2time (xyzt2space), 135
- xyzt_units (xyzt_units-methods), 136
- xyzt_units, nifti-method (xyzt_units-methods), 136
- xyzt_units-methods, 136
- xyzt_units-methods, (xyzt_units-methods), 136
- xyzt_units<- (xyzt_units-methods), 136
- xyzt_units<-, nifti-method (xyzt_units-methods), 136
- zero_trans (resetSlopeIntercept), 101