

Package ‘protr’

July 13, 2018

Version 1.5-1

Title Generating Various Numerical Representation Schemes for Protein Sequences

Description Comprehensive toolkit for generating various numerical features of protein sequences described in Xiao et al. (2015) <DOI:10.1093/bioinformatics/btv042>. For full functionality, the software 'ncbi-blast+' is needed, see <https://blast.ncbi.nlm.nih.gov/Blast.cgi?PAGE_TYPE=BlastDocs&DOC_TYPE=Download> for more information.

Maintainer Nan Xiao <me@nanx.me>

License BSD_3_clause + file LICENSE

URL <https://nanx.me/protr/>, <https://github.com/road2stat/protr>,
<http://protr.org>

BugReports <https://github.com/road2stat/protr/issues>

SystemRequirements ncbi-blast+ (see <https://blast.ncbi.nlm.nih.gov/Blast.cgi?PAGE_TYPE=BlastDocs&DOC_TYPE=Download>)

LazyData true

VignetteBuilder knitr

Depends R (>= 3.0.2)

Suggests knitr, rmarkdown, Biostrings, GOSemSim, foreach, doParallel, org.Hs.eg.db

Encoding UTF-8

RoxygenNote 6.0.1.9000

NeedsCompilation no

Author Nan Xiao [aut, cre] (<<https://orcid.org/0000-0002-0250-5673>>),
Qing-Song Xu [aut],
Dong-Sheng Cao [aut]

Repository CRAN

Date/Publication 2018-07-13 04:30:02 UTC

R topics documented:

protr-package	3
AA2DACOR	4
AA3DMoRSE	5
AAACF	5
AABLOSUM100	5
AABLOSUM45	6
AABLOSUM50	6
AABLOSUM62	6
AABLOSUM80	7
AABurden	7
AAConn	7
AAConst	8
AAACPSA	8
AADescAll	8
AAEdgeAdj	9
AAEigIdx	9
AAFGC	9
AAGeom	10
AAGETAWAY	10
AAindex	10
AAInfo	11
AAMetaInfo	11
AAMOE2D	11
AAMOE3D	12
AAMolProp	12
AAPAM120	12
AAPAM250	13
AAPAM30	13
AAPAM40	13
AAPAM70	14
AARandic	14
AARDF	14
AATopo	15
AATopoChg	15
AAWalk	15
AAWHIM	16
acc	16
extractAAC	17
extractAPAAC	18
extractBLOSUM	20
extractCTDC	21
extractCTDCClass	22
extractCTDD	23
extractCTDDClass	25
extractCTDT	26
extractCTDTClass	27

extractCTriad	29
extractCTriadClass	30
extractDC	31
extractDescScales	32
extractFAScales	33
extractGeary	34
extractMDSScales	36
extractMoran	37
extractMoreauBroto	39
extractPAAC	41
extractProtFP	43
extractProtFPGap	44
extractPSSM	45
extractPSSMAcc	48
extractPSSMFeature	49
extractQSO	50
extractScales	51
extractScalesGap	52
extractSOCN	54
extractTC	55
getUniProt	56
OptAA3d	56
parGOSim	57
parSeqSim	58
protcheck	59
protseg	60
readFASTA	61
readPDB	62
removeGaps	63
twoGOSim	64
twoSeqSim	65
Index	67

protr-package	<i>Generating Various Numerical Representation Schemes for Protein Sequences</i>
---------------	--

Description

The protr package is a comprehensive toolkit for generating various numerical representation schemes of protein sequence. The descriptors are extensively utilized in bioinformatics and chemogenomics research. The commonly used descriptors include amino acid composition, autocorrelation, CTD, conjoint triad, quasi-sequence order, pseudo amino acid composition, and profile-based descriptors derived by Position-Specific Scoring Matrix (PSSM). The descriptors for proteochemometric (PCM) modeling include the scales-based descriptors derived by principal components analysis, factor analysis, multidimensional scaling, amino acid properties (AAindex), 20+ classes of 2D and 3D molecular descriptors (Topological, WHIM, VHSE, etc.), and BLOSUM/PAM matrix-derived

descriptors. The `protr` package also integrates the function of parallelized similarity computation derived by pairwise protein sequence alignment and Gene Ontology (GO) semantic similarity measures.

Details

Package: `protr`
Type: `Package`
License: `BSD_3_clause`

Note

The package vignette can be opened with `vignette("protr")`.

The web server for this package, ProtrWeb can be accessed from: <http://protr.org>.

Bug reports and feature requests should be sent to <https://github.com/road2stat/protr/issues>.

References

Xiao, N., Cao, D.-S., Zhu, M.-F., and Xu, Q.-S. (2015). `protr`/ProtrWeb: R package and web server for generating various numerical representation schemes of protein sequences. *Bioinformatics* 31 (11), 1857–1859.

AA2DACOR

2D Autocorrelations Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the 2D autocorrelations descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AA2DACOR)
```

AA3DMoRSE

3D-MoRSE Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the 3D-MoRSE descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AA3DMoRSE)
```

AAACF

Atom-Centred Fragments Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the atom-centred fragments descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAACF)
```

AABLOSUM100

BLOSUM100 Matrix for 20 Amino Acids

Description

BLOSUM100 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AABLOSUM100)
```

AABLOSUM45

BLOSUM45 Matrix for 20 Amino Acids

Description

BLOSUM45 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AABLOSUM45)
```

AABLOSUM50

BLOSUM50 Matrix for 20 Amino Acids

Description

BLOSUM50 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AABLOSUM50)
```

AABLOSUM62

BLOSUM62 Matrix for 20 Amino Acids

Description

BLOSUM62 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AABLOSUM62)
```

AABLOSUM80

BLOSUM80 Matrix for 20 Amino Acids

Description

BLOSUM80 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AABLOSUM80)
```

AABurden

Burden Eigenvalues Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the Burden eigenvalues descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AABurden)
```

AAConn

Connectivity Indices Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the connectivity indices descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAConn)
```

AAConst	<i>Constitutional Descriptors for 20 Amino Acids calculated by Dragon</i>
---------	---

Description

This dataset includes the constitutional descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAConst)
```

AACPSA	<i>CPSA Descriptors for 20 Amino Acids calculated by Discovery Studio</i>
--------	---

Description

This dataset includes the CPSA descriptors of the 20 amino acids calculated by Discovery Studio (version 2.5) used for scales extraction in this package.

Details

All amino acid molecules had also been optimized with MOE 2011.10 (semiempirical AM1) before calculating these CPSA descriptors. The SDF file containing the information of the optimized amino acid molecules is included in this package. See [OptAA3d](#) for more information.

Examples

```
data(AACPSA)
```

AADescAll	<i>All 2D Descriptors for 20 Amino Acids calculated by Dragon</i>
-----------	---

Description

This dataset includes all the 2D descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AADescAll)
```

AAEdgeAdj	<i>Edge Adjacency Indices Descriptors for 20 Amino Acids calculated by Dragon</i>
-----------	---

Description

This dataset includes the edge adjacency indices descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAEdgeAdj)
```

AAEigIdx	<i>Eigenvalue-Based Indices Descriptors for 20 Amino Acids calculated by Dragon</i>
----------	---

Description

This dataset includes the eigenvalue-based indices descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAEigIdx)
```

AAFGC	<i>Functional Group Counts Descriptors for 20 Amino Acids calculated by Dragon</i>
-------	--

Description

This dataset includes the functional group counts descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAFGC)
```

AAGeom

Geometrical Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the geometrical descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAGeom)
```

AAGETAWAY

GETAWAY Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the GETAWAY descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAGETAWAY)
```

AAindex

AAindex Data of 544 Physicochemical and Biological Properties for 20 Amino Acids

Description

The data was extracted from the AAindex1 database ver 9.1 (<ftp://ftp.genome.jp/pub/db/community/aaindex/aaindex1>) as of November, 2012 (Data Last Modified 2006-08-14).

Details

With this dataset, users can investigate each property's accession number and other details. Visit <http://www.genome.jp/dbget/aaindex.html> for more information.

Examples

```
data(AAindex)
```

AAInfo	<i>Information Indices Descriptors for 20 Amino Acids calculated by Dragon</i>
--------	--

Description

This dataset includes the information indices descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAInfo)
```

AAMetaInfo	<i>Meta Information for the 20 Amino Acids</i>
------------	--

Description

This dataset includes the meta information of the 20 amino acids used for the 2D and 3D descriptor calculation in this package. Each column represents:

- AAName Amino Acid Name
- Short One-Letter Representation
- Abbreviation Three-Letter Representation
- mol SMILE Representation
- PUBCHEM_COMPOUND_CID PubChem CID for the Amino Acid
- PUBCHEM_LINK PubChem Link for the Amino Acid

Examples

```
data(AAMetaInfo)
```

AAMOE2D	<i>2D Descriptors for 20 Amino Acids calculated by MOE 2011.10</i>
---------	--

Description

This dataset includes the 2D descriptors of the 20 amino acids calculated by MOE 2011.10 used for scales extraction in this package.

Examples

```
data(AAMOE2D)
```

AAMOE3D

3D Descriptors for 20 Amino Acids calculated by MOE 2011.10

Description

This dataset includes the 3D descriptors of the 20 amino acids calculated by MOE 2011.10 used for scales extraction in this package. All amino acid molecules had also been optimized with MOE (semiempirical AM1) before calculating these 3D descriptors. The SDF file containing the information of the optimized amino acid molecules is included in this package. See [OptAA3d](#) for more information.

Examples

```
data(AAMOE3D)
```

AAMolProp

Molecular Properties Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the molecular properties descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAMolProp)
```

AAPAM120

PAM120 Matrix for 20 Amino Acids

Description

PAM120 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AAPAM120)
```

AAPAM250

PAM250 Matrix for 20 Amino Acids

Description

PAM250 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AAPAM250)
```

AAPAM30

PAM30 Matrix for 20 Amino Acids

Description

PAM30 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AAPAM30)
```

AAPAM40

PAM40 Matrix for 20 Amino Acids

Description

PAM40 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AAPAM40)
```

AAPAM70

PAM70 Matrix for 20 Amino Acids

Description

PAM70 Matrix for the 20 amino acids. The matrix was extracted from the Biostrings package of Bioconductor.

Examples

```
data(AAPAM70)
```

AARandic

Randic Molecular Profiles Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the Randic molecular profiles descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AARandic)
```

AARDF

RDF Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the RDF descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AARDF)
```

AATopo

Topological Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the topological descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AATopo)
```

AATopoChg

Topological Charge Indices Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the topological charge indices descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AATopoChg)
```

AAWalk

Walk and Path Counts Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the walk and path counts descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAWalk)
```

AAWHIM

WHIM Descriptors for 20 Amino Acids calculated by Dragon

Description

This dataset includes the WHIM descriptors of the 20 amino acids calculated by Dragon (version 5.4) used for scales extraction in this package.

Examples

```
data(AAWHIM)
```

acc

Auto Cross Covariance (ACC) for Generating Scales-Based Descriptors of the Same Length

Description

This function calculates the auto covariance and auto cross covariance for generating scale-based descriptors of the same length.

Usage

```
acc(mat, lag)
```

Arguments

mat A $p \times n$ matrix. Each row represents one scale (total p scales), each column represents one amino acid position (total n amino acids).

lag The lag parameter. Must be less than the amino acids.

Value

A length $lag \times p^2$ named vector, the element names are constructed by: the scales index (crossed scales index) and lag index.

Note

Please see the references for details about auto cross covariance.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Wold, S., Jonsson, J., Sjörström, M., Sandberg, M., & Rönner, S. (1993). DNA and peptide sequences and chemical processes multivariately modelled by principal component analysis and partial least-squares projections to latent structures. *Analytica chimica acta*, 277(2), 239–253.

Sjörström, M., Rönner, S., & Wieslander, A. (1995). Polypeptide sequence property relationships in *Escherichia coli* based on auto cross covariances. *Chemometrics and intelligent laboratory systems*, 29(2), 295–305.

See Also

See [extractScales](#) for scales-based descriptors. For more details, see [extractDescScales](#) and [extractProtFP](#).

Examples

```
p = 8 # p is the scales number
n = 200 # n is the amino acid number
lag = 7 # the lag parameter
mat = matrix(rnorm(p * n), nrow = p, ncol = n)
acc(mat, lag)
```

extractAAC

Amino Acid Composition Descriptor

Description

This function calculates the Amino Acid Composition descriptor (dim: 20).

Usage

```
extractAAC(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

A length 20 named vector

Author(s)

Nan Xiao <<https://nanx.me>>

References

M. Bhasin, G. P. S. Raghava. Classification of Nuclear Receptors Based on Amino Acid Composition and Dipeptide Composition. *Journal of Biological Chemistry*, 2004, 279, 23262.

See Also

See [extractDC](#) and [extractTC](#) for Dipeptide Composition and Tripeptide Composition descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractAAC(x)
```

extractAPAAC	<i>Amphiphilic Pseudo Amino Acid Composition (APseAAC) Descriptor</i>
--------------	---

Description

This function calculates the Amphiphilic Pseudo Amino Acid Composition (APseAAC, or APAAC) descriptor (dim: $20 + (n * \lambda)$, n is the number of properties selected, default is 80).

Usage

```
extractAPAAC(x, props = c("Hydrophobicity", "Hydrophilicity"), lambda = 30,
  w = 0.05, customprops = NULL)
```

Arguments

x	A character vector, as the input protein sequence.
props	A character vector, specifying the properties used. 2 properties are used by default, as listed below: 'Hydrophobicity' Hydrophobicity value of the 20 amino acids 'Hydrophilicity' Hydrophilicity value of the 20 amino acids
lambda	The lambda parameter for the APAAC descriptors, default is 30.
w	The weighting factor, default is 0.05.
customprops	A $n \times 21$ named data frame contains n customized property. Each row contains one property. The column order for different amino acid types is 'AccNo', 'A', 'R', 'N', 'D', 'C', 'E', 'Q', 'G', 'H', 'I', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y', 'V', and the columns should also be <i>exactly</i> named like this. The AccNo column contains the properties' names. Then users should explicitly specify these properties with these names in the argument props. See the examples below for a demonstration. The default value for customprops is NULL.

Value

A length $20 + n * \lambda$ named vector, n is the number of properties selected.

Note

Note the default 20 * 2 prop values have already been independently given in the function. Users can also specify other (up to 544) properties with the Accession Number in the [AAindex](#) data, with or without the default three properties, which means users should explicitly specify the properties to use. For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Kuo-Chen Chou. Prediction of Protein Cellular Attributes Using Pseudo-Amino Acid Composition. *PROTEINS: Structure, Function, and Genetics*, 2001, 43: 246-255.

Kuo-Chen Chou. Using Amphiphilic Pseudo Amino Acid Composition to Predict Enzyme Sub-family Classes. *Bioinformatics*, 2005, 21, 10-19.

JACS, 1962, 84: 4240-4246. (C. Tanford). (The hydrophobicity data)

PNAS, 1981, 78:3824-3828 (T.P.Hopp & K.R.Woods). (The hydrophilicity data)

See Also

See [extractPAAC](#) for the pseudo amino acid composition (PseAAC) descriptor.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractAPAAC(x)
```

```
myprops = data.frame(
  AccNo = c("MyProp1", "MyProp2", "MyProp3"),
  A = c(0.62, -0.5, 15), R = c(-2.53, 3, 101),
  N = c(-0.78, 0.2, 58), D = c(-0.9, 3, 59),
  C = c(0.29, -1, 47), E = c(-0.74, 3, 73),
  Q = c(-0.85, 0.2, 72), G = c(0.48, 0, 1),
  H = c(-0.4, -0.5, 82), I = c(1.38, -1.8, 57),
  L = c(1.06, -1.8, 57), K = c(-1.5, 3, 73),
  M = c(0.64, -1.3, 75), F = c(1.19, -2.5, 91),
  P = c(0.12, 0, 42), S = c(-0.18, 0.3, 31),
  T = c(-0.05, -0.4, 45), W = c(0.81, -3.4, 130),
  Y = c(0.26, -2.3, 107), V = c(1.08, -1.5, 43))
```

```
# use 2 default properties, 4 properties from the
# AAindex database, and 3 customized properties
extractAPAAC(
  x, customprops = myprops,
  props = c(
    "Hydrophobicity", "Hydrophilicity",
```

```

    "CIDH920105", "BHAR880101",
    "CHAM820101", "CHAM820102",
    "MyProp1", "MyProp2", "MyProp3")
)

```

 extractBLOSUM

BLOSUM and PAM Matrix-Derived Descriptors

Description

This function calculates BLOSUM matrix-derived descriptors. For users' convenience, `protr` provides the BLOSUM45, BLOSUM50, BLOSUM62, BLOSUM80, BLOSUM100, PAM30, PAM40, PAM70, PAM120, and PAM250 matrices for the 20 amino acids to select from.

Usage

```

extractBLOSUM(x, submat = "AABLOSUM62", k, lag, scale = TRUE,
              silent = TRUE)

```

Arguments

<code>x</code>	A character vector, as the input protein sequence.
<code>submat</code>	Substitution matrix for the 20 amino acids. Should be one of AABLOSUM45, AABLOSUM50, AABLOSUM62, AABLOSUM80, AABLOSUM100, AAPAM30, AAPAM40, AAPAM70, AAPAM120, or AAPAM250. Default is "AABLOSUM62".
<code>k</code>	Integer. The number of selected scales (i.e. the first <code>k</code> scales) derived by the substitution matrix. This can be selected according to the printed relative importance values.
<code>lag</code>	The lag parameter. Must be less than the amino acids.
<code>scale</code>	Logical. Should we auto-scale the substitution matrix (<code>submat</code>) before doing eigen decomposition? Default is TRUE.
<code>silent</code>	Logical. Whether we print the relative importance of each scales (diagonal value of the eigen decomposition result matrix <code>B</code>) or not. Default is TRUE.

Value

A length `lag * p^2` named vector, `p` is the number of scales selected.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Georgiev, A. G. (2009). Interpretable numerical descriptors of amino acid space. *Journal of Computational Biology*, 16(5), 703–723.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
blosum = extractBLOSUM(
  x, submat = "AABLOSUM62", k = 5, lag = 7, scale = TRUE, silent = FALSE)
```

extractCTDC

CTD Descriptors - Composition

Description

This function calculates the Composition descriptor of the CTD descriptors (dim: 21).

Usage

```
extractCTDC(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

A length 21 named vector

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Inna Dubchak, Ilya Muchink, Stephen R. Holbrook and Sung-Hou Kim. Prediction of protein folding class using global description of amino acid sequence. *Proceedings of the National Academy of Sciences*. USA, 1995, 92, 8700-8704.

Inna Dubchak, Ilya Muchink, Christopher Mayor, Igor Dralyuk and Sung-Hou Kim. Recognition of a Protein Fold in the Context of the SCOP classification. *Proteins: Structure, Function and Genetics*, 1999, 35, 401-407.

See Also

See [extractCTDT](#) and [extractCTDD](#) for Transition and Distribution of the CTD descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractCTDC(x)
```

extractCTDCClass	<i>CTD Descriptors - Composition (with customized amino acid classification support)</i>
------------------	--

Description

This function calculates the Composition descriptor of the CTD descriptors, with customized amino acid classification support.

Usage

```
extractCTDCClass(x, aagroup1, aagroup2, aagroup3)
```

Arguments

x	A character vector, as the input protein sequence.
aagroup1	A named list which contains the first group of customized amino acid classification. See example below.
aagroup2	A named list which contains the second group of customized amino acid classification. See example below.
aagroup3	A named list which contains the third group of customized amino acid classification. See example below.

Value

A length $k * 3$ named vector, k is the number of amino acid properties used.

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Inna Dubchak, Ilya Muchink, Stephen R. Holbrook and Sung-Hou Kim. Prediction of protein folding class using global description of amino acid sequence. *Proceedings of the National Academy of Sciences*. USA, 1995, 92, 8700-8704.

Inna Dubchak, Ilya Muchink, Christopher Mayor, Igor Dralyuk and Sung-Hou Kim. Recognition of a Protein Fold in the Context of the SCOP classification. *Proteins: Structure, Function and Genetics*, 1999, 35, 401-407.

See Also

See [extractCTDTClass](#) and [extractCTDDClass](#) for Transition and Distribution of the CTD descriptors with customized amino acid classification support.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]

# using five customized amino acid property classification
group1 = list(
  "hydrophobicity" = c("R", "K", "E", "D", "Q", "N"),
  "normwaalsvolume" = c("G", "A", "S", "T", "P", "D", "C"),
  "polarizability" = c("G", "A", "S", "D", "T"),
  "secondarystruct" = c("E", "A", "L", "M", "Q", "K", "R", "H"),
  "solventaccess" = c("A", "L", "F", "C", "G", "I", "V", "W"))

group2 = list(
  "hydrophobicity" = c("G", "A", "S", "T", "P", "H", "Y"),
  "normwaalsvolume" = c("N", "V", "E", "Q", "I", "L"),
  "polarizability" = c("C", "P", "N", "V", "E", "Q", "I", "L"),
  "secondarystruct" = c("V", "I", "Y", "C", "W", "F", "T"),
  "solventaccess" = c("R", "K", "Q", "E", "N", "D"))

group3 = list(
  "hydrophobicity" = c("C", "L", "V", "I", "M", "F", "W"),
  "normwaalsvolume" = c("M", "H", "K", "F", "R", "Y", "W"),
  "polarizability" = c("K", "M", "H", "F", "R", "Y", "W"),
  "secondarystruct" = c("G", "N", "P", "S", "D"),
  "solventaccess" = c("M", "S", "P", "T", "H", "Y"))

extractCTDDClass(x, aagroup1 = group1, aagroup2 = group2, aagroup3 = group3)
```

extractCTDD

CTD Descriptors - Distribution

Description

This function calculates the Distribution descriptor of the CTD descriptors (dim: 105).

Usage

```
extractCTDD(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

A length 105 named vector

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Inna Dubchak, Ilya Muchink, Stephen R. Holbrook and Sung-Hou Kim. Prediction of protein folding class using global description of amino acid sequence. *Proceedings of the National Academy of Sciences*. USA, 1995, 92, 8700-8704.

Inna Dubchak, Ilya Muchink, Christopher Mayor, Igor Dralyuk and Sung-Hou Kim. Recognition of a Protein Fold in the Context of the SCOP classification. *Proteins: Structure, Function and Genetics*, 1999, 35, 401-407.

See Also

See [extractCTDC](#) and [extractCTDT](#) for Composition and Transition of the CTD descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractCTDD(x)
```

extractCTDDClass	<i>CTD Descriptors - Distribution (with customized amino acid classification support)</i>
------------------	---

Description

This function calculates the Distribution descriptor of the CTD descriptors, with customized amino acid classification support.

Usage

```
extractCTDDClass(x, aagroup1, aagroup2, aagroup3)
```

Arguments

x	A character vector, as the input protein sequence.
aagroup1	A named list which contains the first group of customized amino acid classification. See example below.
aagroup2	A named list which contains the second group of customized amino acid classification. See example below.
aagroup3	A named list which contains the third group of customized amino acid classification. See example below.

Value

A length $k * 15$ named vector, k is the number of amino acid properties used.

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Inna Dubchak, Ilya Muchink, Stephen R. Holbrook and Sung-Hou Kim. Prediction of protein folding class using global description of amino acid sequence. *Proceedings of the National Academy of Sciences*. USA, 1995, 92, 8700-8704.

Inna Dubchak, Ilya Muchink, Christopher Mayor, Igor Dralyuk and Sung-Hou Kim. Recognition of a Protein Fold in the Context of the SCOP classification. *Proteins: Structure, Function and Genetics*, 1999, 35, 401-407.

See Also

See [extractCTDCClass](#) and [extractCTDTClass](#) for Composition and Transition of the CTD descriptors with customized amino acid classification support.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]

# using five customized amino acid property classification
group1 = list(
  "hydrophobicity" = c("R", "K", "E", "D", "Q", "N"),
  "normwaalsvolume" = c("G", "A", "S", "T", "P", "D", "C"),
  "polarizability" = c("G", "A", "S", "D", "T"),
  "secondarystruct" = c("E", "A", "L", "M", "Q", "K", "R", "H"),
  "solventaccess" = c("A", "L", "F", "C", "G", "I", "V", "W"))

group2 = list(
  "hydrophobicity" = c("G", "A", "S", "T", "P", "H", "Y"),
  "normwaalsvolume" = c("N", "V", "E", "Q", "I", "L"),
  "polarizability" = c("C", "P", "N", "V", "E", "Q", "I", "L"),
  "secondarystruct" = c("V", "I", "Y", "C", "W", "F", "T"),
  "solventaccess" = c("R", "K", "Q", "E", "N", "D"))

group3 = list(
  "hydrophobicity" = c("C", "L", "V", "I", "M", "F", "W"),
  "normwaalsvolume" = c("M", "H", "K", "F", "R", "Y", "W"),
  "polarizability" = c("K", "M", "H", "F", "R", "Y", "W"),
  "secondarystruct" = c("G", "N", "P", "S", "D"),
  "solventaccess" = c("M", "S", "P", "T", "H", "Y"))

extractCTDCClass(x, aagroup1 = group1, aagroup2 = group2, aagroup3 = group3)
```

 extractCTDT

CTD Descriptors - Transition

Description

This function calculates the Transition descriptor of the CTD descriptors (dim: 21).

Usage

```
extractCTDT(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

A length 21 named vector

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Inna Dubchak, Ilya Muchink, Stephen R. Holbrook and Sung-Hou Kim. Prediction of protein folding class using global description of amino acid sequence. *Proceedings of the National Academy of Sciences*. USA, 1995, 92, 8700-8704.

Inna Dubchak, Ilya Muchink, Christopher Mayor, Igor Dralyuk and Sung-Hou Kim. Recognition of a Protein Fold in the Context of the SCOP classification. *Proteins: Structure, Function and Genetics*, 1999, 35, 401-407.

See Also

See [extractCTDC](#) and [extractCTDD](#) for Composition and Distribution of the CTD descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractCTDT(x)
```

extractCTDTClass	<i>CTD Descriptors - Transition (with customized amino acid classification support)</i>
------------------	---

Description

This function calculates the Transition descriptor of the CTD descriptors, with customized amino acid classification support.

Usage

```
extractCTDTClass(x, aagroup1, aagroup2, aagroup3)
```

Arguments

x	A character vector, as the input protein sequence.
aagroup1	A named list which contains the first group of customized amino acid classification. See example below.
aagroup2	A named list which contains the second group of customized amino acid classification. See example below.

aagroup3 A named list which contains the third group of customized amino acid classification. See example below.

Value

A length $k \times 3$ named vector, k is the number of amino acid properties used.

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Inna Dubchak, Ilya Muchink, Stephen R. Holbrook and Sung-Hou Kim. Prediction of protein folding class using global description of amino acid sequence. *Proceedings of the National Academy of Sciences*. USA, 1995, 92, 8700-8704.

Inna Dubchak, Ilya Muchink, Christopher Mayor, Igor Dralyuk and Sung-Hou Kim. Recognition of a Protein Fold in the Context of the SCOP classification. *Proteins: Structure, Function and Genetics*, 1999, 35, 401-407.

See Also

See [extractCTDCClass](#) and [extractCTDDClass](#) for Composition and Distribution of the CTD descriptors with customized amino acid classification support.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]

# using five customized amino acid property classification
group1 = list(
  "hydrophobicity" = c("R", "K", "E", "D", "Q", "N"),
  "normwaalsvolume" = c("G", "A", "S", "T", "P", "D", "C"),
  "polarizability" = c("G", "A", "S", "D", "T"),
  "secondarystruct" = c("E", "A", "L", "M", "Q", "K", "R", "H"),
  "solventaccess" = c("A", "L", "F", "C", "G", "I", "V", "W"))

group2 = list(
  "hydrophobicity" = c("G", "A", "S", "T", "P", "H", "Y"),
  "normwaalsvolume" = c("N", "V", "E", "Q", "I", "L"),
  "polarizability" = c("C", "P", "N", "V", "E", "Q", "I", "L"),
  "secondarystruct" = c("V", "I", "Y", "C", "W", "F", "T"),
  "solventaccess" = c("R", "K", "Q", "E", "N", "D"))

group3 = list(
```

```

"hydrophobicity" = c("C", "L", "V", "I", "M", "F", "W"),
"normwaalsvolume" = c("M", "H", "K", "F", "R", "Y", "W"),
"polarizability" = c("K", "M", "H", "F", "R", "Y", "W"),
"secondarystruct" = c("G", "N", "P", "S", "D"),
"solventaccess" = c("M", "S", "P", "T", "H", "Y")

extractCTDTCClass(x, aagroup1 = group1, aagroup2 = group2, aagroup3 = group3)

```

extractCTriad	<i>Conjoint Triad Descriptor</i>
---------------	----------------------------------

Description

This function calculates the Conjoint Triad descriptor (dim: 343).

Usage

```
extractCTriad(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

A length 343 named vector

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

J.W. Shen, J. Zhang, X.M. Luo, W.L. Zhu, K.Q. Yu, K.X. Chen, Y.X. Li, H.L. Jiang. Predicting Protein-protein Interactions Based Only on Sequences Information. *Proceedings of the National Academy of Sciences*. 007, 104, 4337–4341.

Examples

```

x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractCTriad(x)

```

extractCTriadClass	<i>Conjoint Triad Descriptor (with customized amino acid classification support)</i>
--------------------	--

Description

This function calculates the Conjoint Triad descriptor, with customized amino acid classification support.

Usage

```
extractCTriadClass(x, aaclass)
```

Arguments

x A character vector, as the input protein sequence.
aaiclass A list containing the customized amino acid classification. See example below.

Value

A length k^3 named vector, where k is the number of customized classes of the amino acids.

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

J.W. Shen, J. Zhang, X.M. Luo, W.L. Zhu, K.Q. Yu, K.X. Chen, Y.X. Li, H.L. Jiang. Predicting Protein-protein Interactions Based Only on Sequences Information. *Proceedings of the National Academy of Sciences*. 007, 104, 4337–4341.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]

# use customized amino acid classification (normalized van der Waals volume)
newclass = list(
  c("G", "A", "S", "T", "P", "D", "C"),
  c("N", "V", "E", "Q", "I", "L"),
  c("M", "H", "K", "F", "R", "Y", "W"))

extractCTriadClass(x, aaclass = newclass)
```

extractDC	<i>Dipeptide Composition Descriptor</i>
-----------	---

Description

This function calculates the Dipeptide Composition descriptor (dim: 400).

Usage

```
extractDC(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

A length 400 named vector

Author(s)

Nan Xiao <<https://nanx.me>>

References

M. Bhasin, G. P. S. Raghava. Classification of Nuclear Receptors Based on Amino Acid Composition and Dipeptide Composition. *Journal of Biological Chemistry*, 2004, 279, 23262.

See Also

See [extractAAC](#) and [extractTC](#) for Amino Acid Composition and Tripeptide Composition descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractDC(x)
```

extractDescScales *Scales-Based Descriptors with 20+ classes of Molecular Descriptors*

Description

This function calculates the scales-based descriptors with molecular descriptors sets calculated by Dragon, Discovery Studio and MOE. Users can specify which molecular descriptors to select from one of these descriptor sets by specify the numerical or character index of the molecular descriptors in the descriptor set.

Usage

```
extractDescScales(x, propmat, index = NULL, pc, lag, scale = TRUE,  
                  silent = TRUE)
```

Arguments

x	A character vector, as the input protein sequence.
propmat	The matrix containing the descriptor set for the amino acids, which can be chosen from AAMOE2D, AAMOE3D, AACPSA, AADescAll, AA2DACOR, AA3DMORSE, AAACF, AABurden, AACConn, AACConst, AAEdgeAdj, AAeigIdx, AAFGC, AAGeom, AAGETAWAY, AAInfo, AAMolProp, AARandic, AARDF, AATopo, AATopoChg, AAWalk, and AAWHIM.
index	Integer vector or character vector. Specify which molecular descriptors to select from one of these descriptor sets by specify the numerical or character index of the molecular descriptors in the descriptor set. Default is NULL, which means selecting all the molecular descriptors in this descriptor set.
pc	Integer. The maximum dimension of the space which the data are to be represented in. Must be no greater than the number of amino acid properties provided.
lag	The lag parameter. Must be less than the amino acids.
scale	Logical. Should we auto-scale the property matrix (propmat) before doing MDS? Default is TRUE.
silent	Logical. Whether we print the standard deviation, proportion of variance and the cumulative proportion of the selected principal components or not. Default is TRUE.

Value

A length lag * p^2 named vector, p is the number of scales selected.

Author(s)

Nan Xiao <<https://nanx.me>>

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
descscales = extractDescScales(
  x, propmat = "AATopo", index = c(37:41, 43:47),
  pc = 5, lag = 7, silent = FALSE)
```

 extractFAScales

Scales-Based Descriptors derived by Factor Analysis

Description

This function calculates scales-based descriptors derived by Factor Analysis (FA). Users can provide customized amino acid property matrices.

Usage

```
extractFAScales(x, propmat, factors, scores = "regression", lag,
  scale = TRUE, silent = TRUE)
```

Arguments

x	A character vector, as the input protein sequence.
propmat	A matrix containing the properties for the amino acids. Each row represent one amino acid type, each column represents one property. Note that the one-letter row names must be provided for we need them to seek the properties for each AA type.
factors	Integer. The number of factors to be fitted. Must be no greater than the number of AA properties provided.
scores	Type of scores to produce. The default is "regression", which gives Thompson's scores, "Bartlett" given Bartlett's weighted least-squares scores.
lag	The lag parameter. Must be less than the amino acids number in the protein sequence.
scale	Logical. Should we auto-scale the property matrix (propmat) before doing Factor Analysis? Default is TRUE.
silent	Logical. Whether we print the SS loadings, proportion of variance and the cumulative proportion of the selected factors or not. Default is TRUE.

Value

A length $\text{lag} * p^2$ named vector, p is the number of scales (factors) selected.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Atchley, W. R., Zhao, J., Fernandes, A. D., & Druke, T. (2005). Solving the protein sequence metric problem. *Proceedings of the National Academy of Sciences of the United States of America*, 102(18), 6395-6400.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
data(AATopo)
tprops = AATopo[, c(37:41, 43:47)] # select a set of topological descriptors
fa = extractFAScales(
  x, propmat = tprops, factors = 5, lag = 7, silent = FALSE)
```

extractGeary

Geary Autocorrelation Descriptor

Description

This function calculates the Geary autocorrelation descriptor (dim: length(props) * nlag).

Usage

```
extractGeary(x, props = c("CIDH920105", "BHAR880101", "CHAM820101",
  "CHAM820102", "CHOC760101", "BIGC670101", "CHAM810101", "DAYM780201"),
  nlag = 30L, customprops = NULL)
```

Arguments

x	A character vector, as the input protein sequence.
props	A character vector, specifying the Accession Number of the target properties. 8 properties are used by default, as listed below: AccNo. CIDH920105 Normalized average hydrophobicity scales (Cid et al., 1992) AccNo. BHAR880101 Average flexibility indices (Bhaskaran-Ponnuswamy, 1988) AccNo. CHAM820101 Polarizability parameter (Charton-Charton, 1982) AccNo. CHAM820102 Free energy of solution in water, kcal/mole (Charton-Charton, 1982) AccNo. CHOC760101 Residue accessible surface area in tripeptide (Chothia, 1976) AccNo. BIGC670101 Residue volume (Bigelow, 1967) AccNo. CHAM810101 Steric parameter (Charton, 1981) AccNo. DAYM780201 Relative mutability (Dayhoff et al., 1978b)
nlag	Maximum value of the lag parameter. Default is 30.

`customprops` A $n \times 21$ named data frame contains n customized property. Each row contains one property. The column order for different amino acid types is 'AccNo', 'A', 'R', 'N', 'D', 'C', 'E', 'Q', 'G', 'H', 'I', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y', 'V', and the columns should also be *exactly* named like this. The AccNo column contains the properties' names. Then users should explicitly specify these properties with these names in the argument `props`. See the examples below for a demonstration. The default value for `customprops` is NULL.

Value

A length `length(props) * nlag` named vector.

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

- AAindex: Amino acid index database. <http://www.genome.ad.jp/dbget/aaindex.html>
- Feng, Z.P. and Zhang, C.T. (2000) Prediction of membrane protein types based on the hydrophobic index of amino acids. *Journal of Protein Chemistry*, 19, 269-275.
- Horne, D.S. (1988) Prediction of protein helix content from an autocorrelation analysis of sequence hydrophobicities. *Biopolymers*, 27, 451-477.
- Sokal, R.R. and Thomson, B.A. (2006) Population structure inferred by local spatial autocorrelation: an usage from an Amerindian tribal population. *American Journal of Physical Anthropology*, 129, 121-131.

See Also

See [extractMoreauBroto](#) and [extractMoran](#) for Moreau-Broto autocorrelation descriptors and Moran autocorrelation descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractGeary(x)
```

```
myprops = data.frame(
  AccNo = c("MyProp1", "MyProp2", "MyProp3"),
  A = c(0.62, -0.5, 15), R = c(-2.53, 3, 101),
  N = c(-0.78, 0.2, 58), D = c(-0.9, 3, 59),
  C = c(0.29, -1, 47), E = c(-0.74, 3, 73),
  Q = c(-0.85, 0.2, 72), G = c(0.48, 0, 1),
  H = c(-0.4, -0.5, 82), I = c(1.38, -1.8, 57),
```

```

L = c(1.06, -1.8, 57), K = c(-1.5, 3, 73),
M = c(0.64, -1.3, 75), F = c(1.19, -2.5, 91),
P = c(0.12, 0, 42), S = c(-0.18, 0.3, 31),
T = c(-0.05, -0.4, 45), W = c(0.81, -3.4, 130),
Y = c(0.26, -2.3, 107), V = c(1.08, -1.5, 43))

# Use 4 properties in the AAindex database, and 3 customized properties
extractGeary(
  x, customprops = myprops,
  props = c(
    "CIDH920105", "BHAR880101",
    "CHAM820101", "CHAM820102",
    "MyProp1", "MyProp2", "MyProp3")
)

```

extractMDSScales

Scales-Based Descriptors derived by Multidimensional Scaling

Description

This function calculates scales-based descriptors derived by Multidimensional Scaling (MDS). Users can provide customized amino acid property matrices.

Usage

```
extractMDSScales(x, propmat, k, lag, scale = TRUE, silent = TRUE)
```

Arguments

x	A character vector, as the input protein sequence.
propmat	A matrix containing the properties for the amino acids. Each row represent one amino acid type, each column represents one property. Note that the one-letter row names must be provided for we need them to seek the properties for each AA type.
k	Integer. The maximum dimension of the space which the data are to be represented in. Must be no greater than the number of AA properties provided.
lag	The lag parameter. Must be less than the amino acids.
scale	Logical. Should we auto-scale the property matrix (propmat) before doing MDS? Default is TRUE.
silent	Logical. Whether to print the k eigenvalues computed during the scaling process or not. Default is TRUE.

Value

A length lag * p^2 named vector, p is the number of scales (dimensionality) selected.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Venkataraman, M. S., & Braun, W. (2001). New quantitative descriptors of amino acids based on multidimensional scaling of a large number of physical-chemical properties. *Molecular modeling annual*, 7(12), 445–453.

See Also

See [extractScales](#) for scales-based descriptors derived by Principal Components Analysis.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
data(AATopo)
tprops = AATopo[, c(37:41, 43:47)] # select a set of topological descriptors
mds = extractMDSscales(x, propmat = tprops, k = 5, lag = 7, silent = FALSE)
```

extractMoran

Moran Autocorrelation Descriptor

Description

This function calculates the Moran autocorrelation descriptor (dim: length(props) * nlag).

Usage

```
extractMoran(x, props = c("CIDH920105", "BHAR880101", "CHAM820101",
  "CHAM820102", "CHOC760101", "BIGC670101", "CHAM810101", "DAYM780201"),
  nlag = 30L, customprops = NULL)
```

Arguments

x	A character vector, as the input protein sequence.
props	A character vector, specifying the Accession Number of the target properties. 8 properties are used by default, as listed below: AccNo. CIDH920105 Normalized average hydrophobicity scales (Cid et al., 1992) AccNo. BHAR880101 Average flexibility indices (Bhaskaran-Ponnuswamy, 1988) AccNo. CHAM820101 Polarizability parameter (Charton-Charton, 1982) AccNo. CHAM820102 Free energy of solution in water, kcal/mole (Charton-Charton, 1982) AccNo. CHOC760101 Residue accessible surface area in tripeptide (Chothia, 1976)

	AccNo. BIGC670101 Residue volume (Bigelow, 1967)
	AccNo. CHAM810101 Steric parameter (Charton, 1981)
	AccNo. DAYM780201 Relative mutability (Dayhoff et al., 1978b)
nlag	Maximum value of the lag parameter. Default is 30.
customprops	A $n \times 21$ named data frame contains n customized property. Each row contains one property. The column order for different amino acid types is 'AccNo', 'A', 'R', 'N', 'D', 'C', 'E', 'Q', 'G', 'H', 'I', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y', 'V', and the columns should also be <i>exactly</i> named like this. The AccNo column contains the properties' names. Then users should explicitly specify these properties with these names in the argument props. See the examples below for a demonstration. The default value for customprops is NULL.

Value

A length `length(props) * nlag` named vector.

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

- AAindex: Amino acid index database. <http://www.genome.ad.jp/dbget/aaindex.html>
- Feng, Z.P. and Zhang, C.T. (2000) Prediction of membrane protein types based on the hydrophobic index of amino acids. *Journal of Protein Chemistry*, 19, 269-275.
- Horne, D.S. (1988) Prediction of protein helix content from an autocorrelation analysis of sequence hydrophobicities. *Biopolymers*, 27, 451-477.
- Sokal, R.R. and Thomson, B.A. (2006) Population structure inferred by local spatial autocorrelation: an usage from an Amerindian tribal population. *American Journal of Physical Anthropology*, 129, 121-131.

See Also

See [extractMoreauBroto](#) and [extractGeary](#) for Moreau-Broto autocorrelation descriptors and Geary autocorrelation descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractMoran(x)

myprops = data.frame(
```

```

AccNo = c("MyProp1", "MyProp2", "MyProp3"),
A = c(0.62, -0.5, 15), R = c(-2.53, 3, 101),
N = c(-0.78, 0.2, 58), D = c(-0.9, 3, 59),
C = c(0.29, -1, 47), E = c(-0.74, 3, 73),
Q = c(-0.85, 0.2, 72), G = c(0.48, 0, 1),
H = c(-0.4, -0.5, 82), I = c(1.38, -1.8, 57),
L = c(1.06, -1.8, 57), K = c(-1.5, 3, 73),
M = c(0.64, -1.3, 75), F = c(1.19, -2.5, 91),
P = c(0.12, 0, 42), S = c(-0.18, 0.3, 31),
T = c(-0.05, -0.4, 45), W = c(0.81, -3.4, 130),
Y = c(0.26, -2.3, 107), V = c(1.08, -1.5, 43))

# Use 4 properties in the AAindex database, and 3 customized properties
extractMoran(
  x, customprops = myprops,
  props = c(
    "CIDH920105", "BHAR880101",
    "CHAM820101", "CHAM820102",
    "MyProp1", "MyProp2", "MyProp3")
)

```

extractMoreauBroto *Normalized Moreau-Broto Autocorrelation Descriptor*

Description

This function calculates the normalized Moreau-Broto autocorrelation descriptor (dim: length(props) * nlag).

Usage

```

extractMoreauBroto(x, props = c("CIDH920105", "BHAR880101", "CHAM820101",
  "CHAM820102", "CHOC760101", "BIGC670101", "CHAM810101", "DAYM780201"),
  nlag = 30L, customprops = NULL)

```

Arguments

x	A character vector, as the input protein sequence.
props	A character vector, specifying the Accession Number of the target properties. 8 properties are used by default, as listed below: AccNo. CIDH920105 Normalized average hydrophobicity scales (Cid et al., 1992) AccNo. BHAR880101 Average flexibility indices (Bhaskaran-Ponnuswamy, 1988) AccNo. CHAM820101 Polarizability parameter (Charton-Charton, 1982) AccNo. CHAM820102 Free energy of solution in water, kcal/mole (Charton-Charton, 1982) AccNo. CHOC760101 Residue accessible surface area in tripeptide (Chothia, 1976)

	AccNo. BIGC670101 Residue volume (Bigelow, 1967)
	AccNo. CHAM810101 Steric parameter (Charton, 1981)
	AccNo. DAYM780201 Relative mutability (Dayhoff et al., 1978b)
nlag	Maximum value of the lag parameter. Default is 30.
customprops	A $n \times 21$ named data frame contains n customized property. Each row contains one property. The column order for different amino acid types is 'AccNo', 'A', 'R', 'N', 'D', 'C', 'E', 'Q', 'G', 'H', 'I', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y', 'V', and the columns should also be <i>exactly</i> named like this. The AccNo column contains the properties' names. Then users should explicitly specify these properties with these names in the argument props. See the examples below for a demonstration. The default value for customprops is NULL.

Value

A length $\text{length}(\text{props}) * \text{nlag}$ named vector.

Note

For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

- AAindex: Amino acid index database. <http://www.genome.ad.jp/dbget/aaindex.html>
- Feng, Z.P. and Zhang, C.T. (2000) Prediction of membrane protein types based on the hydrophobic index of amino acids. *Journal of Protein Chemistry*, 19, 269-275.
- Horne, D.S. (1988) Prediction of protein helix content from an autocorrelation analysis of sequence hydrophobicities. *Biopolymers*, 27, 451-477.
- Sokal, R.R. and Thomson, B.A. (2006) Population structure inferred by local spatial autocorrelation: an usage from an Amerindian tribal population. *American Journal of Physical Anthropology*, 129, 121-131.

See Also

See [extractMoran](#) and [extractGeary](#) for Moran autocorrelation descriptors and Geary autocorrelation descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractMoreauBroto(x)

myprops = data.frame(
```

```

AccNo = c("MyProp1", "MyProp2", "MyProp3"),
A = c(0.62, -0.5, 15), R = c(-2.53, 3, 101),
N = c(-0.78, 0.2, 58), D = c(-0.9, 3, 59),
C = c(0.29, -1, 47), E = c(-0.74, 3, 73),
Q = c(-0.85, 0.2, 72), G = c(0.48, 0, 1),
H = c(-0.4, -0.5, 82), I = c(1.38, -1.8, 57),
L = c(1.06, -1.8, 57), K = c(-1.5, 3, 73),
M = c(0.64, -1.3, 75), F = c(1.19, -2.5, 91),
P = c(0.12, 0, 42), S = c(-0.18, 0.3, 31),
T = c(-0.05, -0.4, 45), W = c(0.81, -3.4, 130),
Y = c(0.26, -2.3, 107), V = c(1.08, -1.5, 43))

# Use 4 properties in the AAindex database, and 3 customized properties
extractMoreauBroto(
  x, customprops = myprops,
  props = c(
    "CIDH920105", "BHAR880101",
    "CHAM820101", "CHAM820102",
    "MyProp1", "MyProp2", "MyProp3")
)

```

extractPAAC

Pseudo Amino Acid Composition (PseAAC) Descriptor

Description

This function calculates the Pseudo Amino Acid Composition (PseAAC) descriptor (dim: $20 + \lambda$, default is 50).

Usage

```

extractPAAC(x, props = c("Hydrophobicity", "Hydrophilicity", "SideChainMass"),
  lambda = 30, w = 0.05, customprops = NULL)

```

Arguments

x	A character vector, as the input protein sequence.
props	A character vector, specifying the properties used. 3 properties are used by default, as listed below: 'Hydrophobicity' Hydrophobicity value of the 20 amino acids 'Hydrophilicity' Hydrophilicity value of the 20 amino acids 'SideChainMass' Side-chain mass of the 20 amino acids
lambda	The lambda parameter for the PseAAC descriptors, default is 30.
w	The weighting factor, default is 0.05.

customprops A $n \times 21$ named data frame contains n customized property. Each row contains one property. The column order for different amino acid types is 'AccNo', 'A', 'R', 'N', 'D', 'C', 'E', 'Q', 'G', 'H', 'I', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y', 'V', and the columns should also be *exactly* named like this. The AccNo column contains the properties' names. Then users should explicitly specify these properties with these names in the argument props. See the examples below for a demonstration. The default value for customprops is NULL.

Value

A length $2\theta + 1$ named vector

Note

Note the default $2\theta * 3$ prop values have already been independently given in the function. Users can also specify other (up to 544) properties with the Accession Number in the [AAindex](#) data, with or without the default three properties, which means users should explicitly specify the properties to use. For this descriptor type, users need to intelligently evaluate the underlying details of the descriptors provided, instead of using this function with their data blindly. It would be wise to use some negative and positive control comparisons where relevant to help guide interpretation of the results.

Author(s)

Nan Xiao <<https://nanx.me>>

References

- Kuo-Chen Chou. Prediction of Protein Cellular Attributes Using Pseudo-Amino Acid Composition. *PROTEINS: Structure, Function, and Genetics*, 2001, 43: 246-255.
- Kuo-Chen Chou. Using Amphiphilic Pseudo Amino Acid Composition to Predict Enzyme Subfamily Classes. *Bioinformatics*, 2005, 21, 10-19.
- JACS, 1962, 84: 4240-4246. (C. Tanford). (The hydrophobicity data)
- PNAS, 1981, 78:3824-3828 (T.P.Hopp & K.R.Woods). (The hydrophilicity data)
- CRC Handbook of Chemistry and Physics, 66th ed., CRC Press, Boca Raton, Florida (1985). (The side-chain mass data)
- R.M.C. Dawson, D.C. Elliott, W.H. Elliott, K.M. Jones, Data for Biochemical Research 3rd ed., Clarendon Press Oxford (1986). (The side-chain mass data)

See Also

See [extractAPAAC](#) for amphiphilic pseudo amino acid composition descriptor.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractPAAC(x)
```

```

myprops = data.frame(
  AccNo = c("MyProp1", "MyProp2", "MyProp3"),
  A = c(0.62, -0.5, 15), R = c(-2.53, 3, 101),
  N = c(-0.78, 0.2, 58), D = c(-0.9, 3, 59),
  C = c(0.29, -1, 47), E = c(-0.74, 3, 73),
  Q = c(-0.85, 0.2, 72), G = c(0.48, 0, 1),
  H = c(-0.4, -0.5, 82), I = c(1.38, -1.8, 57),
  L = c(1.06, -1.8, 57), K = c(-1.5, 3, 73),
  M = c(0.64, -1.3, 75), F = c(1.19, -2.5, 91),
  P = c(0.12, 0, 42), S = c(-0.18, 0.3, 31),
  T = c(-0.05, -0.4, 45), W = c(0.81, -3.4, 130),
  Y = c(0.26, -2.3, 107), V = c(1.08, -1.5, 43))

# use 3 default properties, 4 properties from the
# AAindex database, and 3 customized properties
extractPAAC(
  x, customprops = myprops,
  props = c(
    "Hydrophobicity", "Hydrophilicity", "SideChainMass",
    "CIDH920105", "BHAR880101",
    "CHAM820101", "CHAM820102",
    "MyProp1", "MyProp2", "MyProp3")
)

```

extractProtFP

Amino Acid Properties Based Scales Descriptors (Protein Fingerprint)

Description

This function calculates amino acid properties based scales descriptors (protein fingerprint). Users can specify which AAindex properties to select from the AAindex database by specify the numerical or character index of the properties in the AAindex database.

Usage

```
extractProtFP(x, index = NULL, pc, lag, scale = TRUE, silent = TRUE)
```

Arguments

x	A character vector, as the input protein sequence.
index	Integer vector or character vector. Specify which AAindex properties to select from the AAindex database by specify the numerical or character index of the properties in the AAindex database. Default is NULL, means selecting all the AA properties in the AAindex database.
pc	Integer. Use the first pc principal components as the scales. Must be no greater than the number of AA properties provided.
lag	The lag parameter. Must be less than the amino acids.
scale	Logical. Should we auto-scale the property matrix before PCA? Default is TRUE.

silent Logical. Whether we print the standard deviation, proportion of variance and the cumulative proportion of the selected principal components or not. Default is TRUE.

Value

A length $\text{lag} * p^2$ named vector, p is the number of scales (principal components) selected.

Author(s)

Nan Xiao <<https://nanx.me>>

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
fp = extractProtFP(
  x, index = c(160:165, 258:296), pc = 5, lag = 7, silent = FALSE)
```

extractProtFPGap	<i>Amino Acid Properties Based Scales Descriptors (Protein Fingerprint) with Gap Support</i>
------------------	--

Description

This function calculates amino acid properties based scales descriptors (protein fingerprint) with gap support. Users can specify which AAindex properties to select from the AAindex database by specify the numerical or character index of the properties in the AAindex database.

Usage

```
extractProtFPGap(x, index = NULL, pc, lag, scale = TRUE, silent = TRUE)
```

Arguments

x	A character vector, as the input protein sequence. Use '-' to represent gaps in the sequence.
index	Integer vector or character vector. Specify which AAindex properties to select from the AAindex database by specify the numerical or character index of the properties in the AAindex database. Default is NULL, means selecting all the AA properties in the AAindex database.
pc	Integer. Use the first pc principal components as the scales. Must be no greater than the number of AA properties provided.
lag	The lag parameter. Must be less than the amino acids.
scale	Logical. Should we auto-scale the property matrix before PCA? Default is TRUE.
silent	Logical. Whether we print the standard deviation, proportion of variance and the cumulative proportion of the selected principal components or not. Default is TRUE.

Value

A length $\text{lag} * p^2$ named vector, p is the number of scales (principal components) selected.

Author(s)

Nan Xiao <<https://nanx.me>>

Examples

```
# amino acid sequence with gaps
x = readFASTA(system.file("protseq/align.fasta", package = "protr"))$`IXI_235`
fp = extractProtFPGap(
  x, index = c(160:165, 258:296), pc = 5, lag = 7, silent = FALSE)
```

extractPSSM	<i>Compute PSSM (Position-Specific Scoring Matrix) for given protein sequence</i>
-------------	---

Description

This function calculates the PSSM (Position-Specific Scoring Matrix) derived by PSI-Blast for given protein sequence or peptides.

Usage

```
extractPSSM(seq, start.pos = 1L, end.pos = nchar(seq),
  psiblast.path = NULL, makeblastdb.path = NULL, database.path = NULL,
  iter = 5, silent = TRUE, evalue = 10L, word.size = NULL,
  gapopen = NULL, gapextend = NULL, matrix = "BLOSUM62",
  threshold = NULL, seg = "no", soft.masking = FALSE,
  culling.limit = NULL, best.hit.overhang = NULL,
  best.hit.score.edge = NULL, xdrop.ungap = NULL, xdrop.gap = NULL,
  xdrop.gap.final = NULL, window.size = NULL, gap.trigger = 22L,
  num.threads = 1L, pseudocount = 0L, inclusion.ethresh = 0.002)
```

Arguments

<code>seq</code>	Character vector, as the input protein sequence.
<code>start.pos</code>	Optional integer denoting the start position of the fragment window. Default is 1, i.e. the first amino acid of the given sequence.
<code>end.pos</code>	Optional integer denoting the end position of the fragment window. Default is <code>nchar(seq)</code> , i.e. the last amino acid of the given sequence.
<code>psiblast.path</code>	Character string indicating the path of the <code>psiblast</code> program. If NCBI Blast+ was previously installed in the operation system, the path will be automatically detected.

makeblastdb.path	Character string indicating the path of the makeblastdb program. If NCBI Blast+ was previously installed in the system, the path will be automatically detected.
database.path	Character string indicating the path of a reference database (a FASTA file).
iter	Number of iterations to perform for PSI-Blast.
silent	Logical. Whether the PSI-Blast running output should be shown or not (May not work on some Windows versions and PSI-Blast versions), default is TRUE.
eval	Expectation value (E) threshold for saving hits. Default is 10.
word.size	Word size for wordfinder algorithm. An integer ≥ 2 .
gapopen	Integer. Cost to open a gap.
gapextend	Integer. Cost to extend a gap.
matrix	Character string. The scoring matrix name (default is "BLOSUM62").
threshold	Minimum word score such that the word is added to the BLAST lookup table. A real value ≥ 0 .
seg	Character string. Filter query sequence with SEG ("yes", "window locut hicut", or "no" to disable). Default is "no".
soft.masking	Logical. Apply filtering locations as soft masks? Default is FALSE.
culling.limit	An integer ≥ 0 . If the query range of a hit is enveloped by that of at least this many higher-scoring hits, delete the hit. Incompatible with best.hit.overhang and best.hit.score.edge.
best.hit.overhang	Best Hit algorithm overhang value (A real value ≥ 0 and ≤ 0.5 , recommended value: 0.1). Incompatible with culling.limit.
best.hit.score.edge	Best Hit algorithm score edge value (A real value ≥ 0 and ≤ 0.5 , recommended value: 0.1). Incompatible with culling.limit.
xdrop.ungap	X-dropoff value (in bits) for ungapped extensions.
xdrop.gap	X-dropoff value (in bits) for preliminary gapped extensions.
xdrop.gap.final	X-dropoff value (in bits) for final gapped alignment.
window.size	An integer ≥ 0 . Multiple hits window size, To specify 1-hit algorithm, use 0.
gap.trigger	Number of bits to trigger gapping. Default is 22.
num.threads	Integer. Number of threads (CPUs) to use in the BLAST search. Default is 1.
pseudocount	Integer. Pseudo-count value used when constructing PSSM. Default is 0.
inclusion.ethresh	E-value inclusion threshold for pairwise alignments. Default is 0.002.

Details

For given protein sequences or peptides, PSSM represents the log-likelihood of the substitution of the 20 types of amino acids at that position in the sequence. Note that the output value is not normalized.

Value

The original PSSM, a numeric matrix which has `end.pos - start.pos + 1` columns and 20 named rows.

Note

The function requires the `makeblastdb` and `psiblast` programs to be properly installed in the operation system or their paths provided.

The two command-line programs are included in the NCBI-BLAST+ software package. To install NCBI Blast+ for your operating system, see https://blast.ncbi.nlm.nih.gov/Blast.cgi?PAGE_TYPE=BlastDocs&DOC_TYPE=Download for detailed instructions.

Ubuntu/Debian users can directly use the command `sudo apt-get install ncbi-blast+` to install NCBI Blast+. For OS X users, download `ncbi-blast-... .dmg` then install. For Windows users, download `ncbi-blast-... .exe` then install.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Altschul, Stephen F., et al. "Gapped BLAST and PSI-BLAST: a new generation of protein database search programs." *Nucleic acids research* 25.17 (1997): 3389–3402.

Ye, Xugang, Guoli Wang, and Stephen F. Altschul. "An assessment of substitution scores for protein profile-profile comparison." *Bioinformatics* 27.24 (2011): 3356–3363.

Rangwala, Huzefa, and George Karypis. "Profile-based direct kernels for remote homology detection and fold recognition." *Bioinformatics* 21.23 (2005): 4239–4247.

See Also

[extractPSSMFeature](#) [extractPSSMAcc](#)

Examples

```
if (Sys.which("makeblastdb") == "" | Sys.which("psiblast") == "") {
  cat("Cannot find makeblastdb or psiblast. Please install NCBI Blast+ first")
} else {
  x = readFASTA(system.file(
    "protseq/P00750.fasta", package = "protr"))[[1]]
  dbpath = tempfile("tempdb", fileext = ".fasta")
  invisible(file.copy(from = system.file(
    "protseq/Plasminogen.fasta", package = "protr"), to = dbpath))
  pssmmat = extractPSSM(seq = x, database.path = dbpath)
  dim(pssmmat) # 20 x 562 (P00750: length 562, 20 Amino Acids)
```

}

extractPSSMAcc	<i>Profile-based protein representation derived by PSSM (Position-Specific Scoring Matrix) and auto cross covariance</i>
----------------	--

Description

This function calculates the feature vector based on the PSSM by running PSI-Blast and auto cross covariance transformation.

Usage

```
extractPSSMAcc(pssmmat, lag)
```

Arguments

pssmmat	The PSSM computed by extractPSSM .
lag	The lag parameter. Must be less than the number of amino acids in the sequence (i.e. the number of columns in the PSSM matrix).

Value

A length $lag * 20^2$ named numeric vector, the element names are derived by the amino acid name abbreviation (crossed amino acid name abbreviation) and lag index.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Wold, S., Jonsson, J., Sjörström, M., Sandberg, M., & Rannar, S. (1993). DNA and peptide sequences and chemical processes multivariately modelled by principal component analysis and partial least-squares projections to latent structures. *Analytica chimica acta*, 277(2), 239–253.

See Also

[extractPSSM](#) [extractPSSMFeature](#)

Examples

```
if (Sys.which("makeblastdb") == "" | Sys.which("psiblast") == "") {  
  cat("Cannot find makeblastdb or psiblast. Please install NCBI Blast+")  
} else {  
  x = readFASTA(system.file(  
    "protseq/P00750.fasta", package = "protr"))[[1]]  
  dbpath = tempfile("tempdb", fileext = ".fasta")  
  invisible(file.copy(from = system.file(  
    "protseq/Plasminogen.fasta", package = "protr"), to = dbpath))  
  
  pssmmat = extractPSSM(seq = x, database.path = dbpath)  
  pssmacc = extractPSSMAcc(pssmmat, lag = 3)  
  tail(pssmacc)  
}
```

extractPSSMFeature	<i>Profile-based protein representation derived by PSSM (Position-Specific Scoring Matrix)</i>
--------------------	--

Description

This function calculates the profile-based protein representation derived by PSSM. The feature vector is based on the PSSM computed by [extractPSSM](#).

Usage

```
extractPSSMFeature(pssmmat)
```

Arguments

pssmmat The PSSM computed by [extractPSSM](#).

Details

For a given sequence, the PSSM feature represents the log-likelihood of the substitution of the 20 types of amino acids at that position in the sequence.

Each PSSM feature value in the vector represents the degree of conservation of a given amino acid type. The value is normalized to interval (0, 1) by the transformation $1/(1+e^{-x})$.

Value

A numeric vector which has $20 \times N$ named elements, where N is the size of the window (number of rows of the PSSM).

Author(s)

Nan Xiao <<https://nanx.me>>

References

Ye, Xugang, Guoli Wang, and Stephen F. Altschul. "An assessment of substitution scores for protein profile-profile comparison." *Bioinformatics* 27.24 (2011): 3356–3363.

Rangwala, Huzefa, and George Karypis. "Profile-based direct kernels for remote homology detection and fold recognition." *Bioinformatics* 21.23 (2005): 4239–4247.

See Also

[extractPSSM](#) [extractPSSMAcc](#)

Examples

```
if (Sys.which("makeblastdb") == "" | Sys.which("psiblast") == "") {  
  cat("Cannot find makeblastdb or psiblast. Please install NCBI Blast+")  
} else {  
  
  x = readFASTA(system.file(  
    "protseq/P00750.fasta", package = "protr"))[[1]]  
  dbpath = tempfile("tempdb", fileext = ".fasta")  
  invisible(file.copy(from = system.file(  
    "protseq/Plasminogen.fasta", package = "protr"), to = dbpath))  
  
  pssmmat = extractPSSM(seq = x, database.path = dbpath)  
  pssmfeature = extractPSSMFeature(pssmmat)  
  head(pssmfeature)  
  
}
```

extractQSO

Quasi-Sequence-Order (QSO) Descriptor

Description

This function calculates the Quasi-Sequence-Order (QSO) descriptor (dim: $20 + 20 + (2 * nlag)$, default is 100).

Usage

```
extractQSO(x, nlag = 30, w = 0.1)
```

Arguments

x A character vector, as the input protein sequence.
nlag The maximum lag, default is 30.
w The weighting factor, default is 0.1.

Value

A length $20 + 20 + (2 * nlag)$ named vector

Author(s)

Nan Xiao <<https://nanx.me>>

References

Kuo-Chen Chou. Prediction of Protein Subcellar Locations by Incorporating Quasi-Sequence-Order Effect. *Biochemical and Biophysical Research Communications*, 2000, 278, 477-483.
Kuo-Chen Chou and Yu-Dong Cai. Prediction of Protein Sucellular Locations by GO-FunD-PseAA Predictor. *Biochemical and Biophysical Research Communications*, 2004, 320, 1236-1239.
Gisbert Schneider and Paul Wrede. The Rational Design of Amino Acid Sequences by Artificial Neural Networks and Simulated Molecular Evolution: Do Novo Design of an Idealized Leader Cleavage Site. *Biophys Journal*, 1994, 66, 335-344.

See Also

See [extractSOCN](#) for sequence-order-coupling numbers.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]  
extractQS0(x)
```

extractScales

Scales-Based Descriptors derived by Principal Components Analysis

Description

This function calculates scales-based descriptors derived by Principal Components Analysis (PCA). Users can provide customized amino acid property matrices. This function implements the core computation procedure needed for the scales-based descriptors derived by AA-Properties (AAindex) and scales-based descriptors derived by 20+ classes of 2D and 3D molecular descriptors (Topological, WHIM, VHSE, etc.) in the protr package.

Usage

```
extractScales(x, propmat, pc, lag, scale = TRUE, silent = TRUE)
```

Arguments

x	A character vector, as the input protein sequence.
propmat	A matrix containing the properties for the amino acids. Each row represent one amino acid type, each column represents one property. Note that the one-letter row names must be provided for we need them to seek the properties for each AA type.
pc	Integer. Use the first pc principal components as the scales. Must be no greater than the number of AA properties provided.
lag	The lag parameter. Must be less than the amino acids.
scale	Logical. Should we auto-scale the property matrix (propmat) before PCA? Default is TRUE.
silent	Logical. Whether we print the standard deviation, proportion of variance and the cumulative proportion of the selected principal components or not. Default is TRUE.

Value

A length $\text{lag} * p^2$ named vector, p is the number of scales (principal components) selected.

Author(s)

Nan Xiao <<https://nanx.me>>

See Also

See [extractDescScales](#) scales descriptors based on 20+ classes of molecular descriptors, and [extractProtFP](#) for amino acid property based scales descriptors (protein fingerprint).

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
data(AAindex)
AAidxmat = t(na.omit(as.matrix(AAindex[, 7:26])))
scales = extractScales(x, propmat = AAidxmat, pc = 5, lag = 7, silent = FALSE)
```

extractScalesGap	<i>Scales-Based Descriptors derived by Principal Components Analysis (with Gap Support)</i>
------------------	---

Description

This function calculates scales-based descriptors derived by Principal Components Analysis (PCA), with gap support. Users can provide customized amino acid property matrices. This function implements the core computation procedure needed for the scales-based descriptors derived by AA-Properties (AAindex) and scales-based descriptors derived by 20+ classes of 2D and 3D molecular descriptors (Topological, WHIM, VHSE, etc.) in the protr package.

Usage

```
extractScalesGap(x, propmat, pc, lag, scale = TRUE, silent = TRUE)
```

Arguments

x	A character vector, as the input protein sequence. Use '-' to represent gaps in the sequence.
propmat	A matrix containing the properties for the amino acids. Each row represent one amino acid type, each column represents one property. Note that the one-letter row names must be provided for we need them to seek the properties for each AA type.
pc	Integer. Use the first pc principal components as the scales. Must be no greater than the number of AA properties provided.
lag	The lag parameter. Must be less than the amino acids.
scale	Logical. Should we auto-scale the property matrix (propmat) before PCA? Default is TRUE.
silent	Logical. Whether to print the standard deviation, proportion of variance and the cumulative proportion of the selected principal components or not. Default is TRUE.

Value

A length $\text{lag} * p^2$ named vector, p is the number of scales (principal components) selected.

Author(s)

Nan Xiao <<https://nanx.me>>

See Also

See [extractProtFPGap](#) for amino acid property based scales descriptors (protein fingerprint) with gap support.

Examples

```
# amino acid sequence with gaps
x = readFASTA(system.file("protseq/align.fasta", package = "protr"))$`IXI_235`
data(AAindex)
AAidxmat = t(na.omit(as.matrix(AAindex[, 7:26])))
scales = extractScalesGap(x, propmat = AAidxmat, pc = 5, lag = 7, silent = FALSE)
```

`extractSOCN`*Sequence-Order-Coupling Numbers*

Description

This function calculates the Sequence-Order-Coupling Numbers (dim: `nlag * 2`, default is 60).

Usage

```
extractSOCN(x, nlag = 30)
```

Arguments

<code>x</code>	A character vector, as the input protein sequence.
<code>nlag</code>	The maximum lag, default is 30.

Value

A length `nlag * 2` named vector

Author(s)

Nan Xiao <<https://nanx.me>>

References

Kuo-Chen Chou. Prediction of Protein Subcellar Locations by Incorporating Quasi-Sequence-Order Effect. *Biochemical and Biophysical Research Communications*, 2000, 278, 477-483.

Kuo-Chen Chou and Yu-Dong Cai. Prediction of Protein Sucellular Locations by GO-FunD-PseAA Predictor. *Biochemical and Biophysical Research Communications*, 2004, 320, 1236-1239.

Gisbert Schneider and Paul Wrede. The Rational Design of Amino Acid Sequences by Artifical Neural Networks and Simulated Molecular Evolution: Do Novo Design of an Idealized Leader Cleavage Site. *Biophys Journal*, 1994, 66, 335-344.

See Also

See [extractQSO](#) for quasi-sequence-order descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractSOCN(x)
```

extractTC	<i>Tripeptide Composition Descriptor</i>
-----------	--

Description

This function calculates the Tripeptide Composition descriptor (dim: 8,000).

Usage

```
extractTC(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

A length 8,000 named vector

Author(s)

Nan Xiao <<https://nanx.me>>

References

M. Bhasin, G. P. S. Raghava. Classification of Nuclear Receptors Based on Amino Acid Composition and Dipeptide Composition. *Journal of Biological Chemistry*, 2004, 279, 23262.

See Also

See [extractAAC](#) and [extractDC](#) for Amino Acid Composition and Dipeptide Composition descriptors.

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
extractTC(x)
```

`getUniProt`*Retrieve Protein Sequences from UniProt by Protein ID*

Description

This function retrieves protein sequences from uniprot.org by protein ID(s).

Usage

```
getUniProt(id)
```

Arguments

`id` A character vector, as the protein ID(s).

Value

A list, each component contains one protein sequence.

Author(s)

Nan Xiao <<https://nanx.me>>

See Also

See [readFASTA](#) for reading FASTA format files.

Examples

```
## Not run:  
# Network latency may slow down this example  
# Only test this when your connection is fast enough  
ids = c("P00750", "P00751", "P00752")  
getUniProt(ids)  
## End(Not run)
```

`OptAA3d`*OptAA3d.sdf - 20 Amino Acids Optimized with MOE 2011.10
(Semiempirical AM1)*

Description

OptAA3d.sdf - 20 Amino Acids Optimized with MOE 2011.10 (Semiempirical AM1)

Examples

```
# This operation requires the rcdk package
# require(rcdk)
# optaa3d = load.molecules(system.file("sysdata/OptAA3d.sdf", package = "protr"))
# view.molecule.2d(optaa3d[[1]]) # view the first AA
```

parGOSim	<i>Protein Sequence Similarity Calculation based on Gene Ontology (GO) Similarity</i>
----------	---

Description

This function calculates protein sequence similarity based on Gene Ontology (GO) similarity.

Usage

```
parGOSim(golist, type = c("go", "gene"), ont = "MF", organism = "human",
  measure = "Resnik", combine = "BMA")
```

Arguments

golist	A character vector, each component contains a character vector of GO terms or one Entrez Gene ID.
type	Input type of golist, 'go' for GO Terms, 'gene' for gene ID.
ont	Default is 'MF', can be one of 'MF', 'BP', or 'CC' subontologies.
organism	Default is 'human', can be one of 'anopheles', 'arabidopsis', 'bovine', 'canine', 'chicken', 'chimp', 'coelicolor', 'ecolik12', 'ecsakai', 'fly', 'human', 'malaria', 'mouse', 'pig', 'rat', 'rhesus', 'worm', 'xenopus', 'yeast' or 'zebrafish'.
measure	Default is 'Resnik', can be one of 'Resnik', 'Lin', 'Rel', 'Jiang' or 'Wang'.
combine	Default is 'BMA', can be one of 'max', 'average', 'rcmax' or 'BMA' for combining semantic similarity scores of multiple GO terms associated with protein.

Value

A n x n similarity matrix.

Author(s)

Nan Xiao <<https://nanx.me>>

See Also

See [twoGOSim](#) for calculating the GO semantic similarity between two groups of GO terms or two Entrez gene IDs. See [parSeqSim](#) for paralleled protein similarity calculation based on Smith-Waterman local alignment.

Examples

```
## Not run:
# Be careful when testing this since it involves GO similarity computation
# and might produce unpredictable results in some environments

library("GOSemSim")
library("org.Hs.eg.db")

# by GO Terms
go1 = c("GO:0005215", "GO:0005488", "GO:0005515",
        "GO:0005625", "GO:0005802", "GO:0005905") # AP4B1
go2 = c("GO:0005515", "GO:0005634", "GO:0005681",
        "GO:0008380", "GO:0031202") # BCAS2
go3 = c("GO:0003735", "GO:0005622", "GO:0005840",
        "GO:0006412") # PDE4DIP
glist = list(go1, go2, go3)
gsimmat1 = parGOSim(glist, type = "go", ont = "CC")
print(gsimmat1)

# by Entrez gene id
genelist = list(c("150", "151", "152", "1814", "1815", "1816"))
gsimmat2 = parGOSim(genelist, type = "gene")
print(gsimmat2)
## End(Not run)
```

parSeqSim

Parallellized Protein Sequence Similarity Calculation based on Sequence Alignment

Description

This function implemented the parallellized version for calculating protein sequence similarity based on sequence alignment.

Usage

```
parSeqSim(protlist, cores = 2, type = "local", submat = "BLOSUM62")
```

Arguments

protlist	A length n list containing n protein sequences, each component of the list is a character string, storing one protein sequence. Unknown sequences should be represented as "".
cores	Integer. The number of CPU cores to use for parallel execution, default is 2. Users can use the detectCores() function in the parallel package to see how many cores they could use.
type	Type of alignment, default is 'local', could be 'global' or 'local', where 'global' represents Needleman-Wunsch global alignment; 'local' represents Smith-Waterman local alignment.

submat Substitution matrix, default is 'BLOSUM62', can be one of 'BLOSUM45', 'BLOSUM50', 'BLOSUM62', 'BLOSUM80', 'BLOSUM100', 'PAM30', 'PAM40', 'PAM70', 'PAM120', or 'PAM250'.

Value

A n x n similarity matrix.

Author(s)

Nan Xiao <<https://nanx.me>>

See Also

See `twoSeqSim` for protein sequence alignment for two protein sequences. See `parGOSim` for protein similarity calculation based on Gene Ontology (GO) semantic similarity.

Examples

```
## Not run:
# Be careful when testing this since it involves parallelisation
# and might produce unpredictable results in some environments

library("Biostrings")
library("foreach")
library("doParallel")

s1 = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
s2 = readFASTA(system.file("protseq/P08218.fasta", package = "protr"))[[1]]
s3 = readFASTA(system.file("protseq/P10323.fasta", package = "protr"))[[1]]
s4 = readFASTA(system.file("protseq/P20160.fasta", package = "protr"))[[1]]
s5 = readFASTA(system.file("protseq/Q9NZP8.fasta", package = "protr"))[[1]]
plist = list(s1, s2, s3, s4, s5)
psimmat = parSeqSim(plist, cores = 2, type = "local", submat = "BLOSUM62")
print(psimmat)
## End(Not run)
```

protcheck

Protein sequence amino acid type sanity check

Description

This function checks if the protein sequence's amino acid types are in the 20 default types.

Usage

```
protcheck(x)
```

Arguments

x A character vector, as the input protein sequence.

Value

Logical. TRUE if all of the amino acid types of the sequence are within the 20 default types.

Author(s)

Nan Xiao <<https://nanx.me>>

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
protcheck(x) # TRUE
protcheck(paste(x, "Z", sep = "")) # FALSE
```

protseg

Protein Sequence Segmentation/Partition

Description

This function extracts the segmentations from the protein sequence.

Usage

```
protseg(x, aa = c("A", "R", "N", "D", "C", "E", "Q", "G", "H", "I", "L", "K",
  "M", "F", "P", "S", "T", "W", "Y", "V"), k = 7)
```

Arguments

x A character vector, as the input protein sequence.
 aa A character, the amino acid type. One of 'A', 'R', 'N', 'D', 'C', 'E', 'Q', 'G', 'H', 'I', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y', 'V'.
 k A positive integer, specifies the window size (half of the window), default is 7.

Value

A named list, each component contains one of the segmentations (a character string), names of the list components are the positions of the specified amino acid in the sequence.

Author(s)

Nan Xiao <<https://nanx.me>>

Examples

```
x = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]
protseg(x, aa = "R", k = 5)
```

readFASTA	<i>Read Protein Sequences in FASTA Format</i>
-----------	---

Description

This function reads protein sequences in FASTA format.

Usage

```
readFASTA(file = system.file("protseq/P00750.fasta", package = "protr"),
           legacy.mode = TRUE, seqonly = FALSE)
```

Arguments

file	Path to the file containing the protein sequences in FASTA format. If it does not contain an absolute or relative path, the file name is relative to the current working directory, <code>getwd</code> . The default here is to read the <code>P00750.fasta</code> file which is present in the <code>protseq</code> directory of the <code>protr</code> package.
legacy.mode	If set to TRUE, lines starting with a semicolon (;) are ignored. Default value is TRUE.
seqonly	If set to TRUE, only sequences are returned without attempt to modify them or to get their names and annotations (execution time is divided approximately by a factor 3). Default value is FALSE.

Value

Character vector of the protein sequences.

The three returned arguments are just different forms of the same output. If one is interested in a Mahalanobis metric over the original data space, the first argument is all she/he needs. If a transformation into another space (where one can use the Euclidean metric) is preferred, the second returned argument is sufficient. Using A and B is equivalent in the following sense.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Pearson, W.R. and Lipman, D.J. (1988) Improved tools for biological sequence comparison. *Proceedings of the National Academy of Sciences of the United States of America*, **85**: 2444–2448.

See Also

See `getUniProt` for retrieving protein sequences from uniprot.org.

Examples

```
P00750 = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))
```

`readPDB`*Read Protein Sequences in PDB Format*

Description

This function reads protein sequences in PDB (Protein Data Bank) format, and return the amino acid sequences represented by single-letter code.

Usage

```
readPDB(file = system.file("protseq/4HHB.pdb", package = "protr"))
```

Arguments

<code>file</code>	Path to the file containing the protein sequences in PDB format. If it does not contain an absolute or relative path, the file name is relative to the current working directory, <code>getwd</code> . The default here is to read the 4HHB.PDB file which is present in the <code>protseq</code> directory of the <code>protr</code> package.
-------------------	--

Value

Character vector of the protein sequence.

Author(s)

Nan Xiao <<https://nanx.me>>

References

Protein Data Bank Contents Guide: Atomic Coordinate Entry Format Description, Version 3.30. Accessed 2013-06-26. ftp://ftp.wwpdb.org/pub/pdb/doc/format_descriptions/Format_v33_Letter.pdf

See Also

See [readFASTA](#) for reading protein sequences in FASTA format.

Examples

```
Seq4HHB = readPDB(system.file("protseq/4HHB.pdb", package = "protr"))
```

removeGaps	<i>Remove or replace gaps from protein sequences.</i>
------------	---

Description

Remove/replace gaps or any irregular characters from protein sequences, to make them suitable for feature extraction or sequence alignment based similarity computation.

Usage

```
removeGaps(x, pattern = "-", replacement = "", ...)
```

Arguments

x	character vector, containing the input protein sequence(s).
pattern	character string contains the gap (or other irregular) character to be removed or replaced. Default is "-". For advanced usage, see gsub .
replacement	a replacement for matched characters. Default is "" (remove the matched character).
...	additional parameters for gsub .

Value

a vector of protein sequence(s) with gaps or irregular characters removed/replaced.

Author(s)

Nan Xiao <<https://nanx.me>>

Examples

```
# amino acid sequences that contain gaps ("-")
aaseq <- list(
  "MHGDTPTLHEYMLDLQPETTDLYCYEQLSDSSE-EEDEIDGPAGQAEPDRAHYNIIVTFCKCDSTLRLCVQS",
  "MHGDTPTLHEYMLDLQPETTDLYCYEQLNDSSE-EEDEIDGPAGQAEPDRAHYNIIVTFCKCDSTLRLCVQS"
)

## Not run:
#' # gaps create issues for alignment
parSeqSim(aaseq)

# remove the gaps
nogapseq <- removeGaps(aaseq)
parSeqSim(nogapseq)
## End(Not run)
```

twoGOSim	<i>Protein Similarity Calculation based on Gene Ontology (GO) Similarity</i>
----------	--

Description

This function calculates the Gene Ontology (GO) similarity between two groups of GO terms or two Entrez gene IDs.

Usage

```
twoGOSim(id1, id2, type = c("go", "gene"), ont = "MF", organism = "human",
         measure = "Resnik", combine = "BMA")
```

Arguments

id1	A character vector. length > 1: each element is a GO term; length = 1: the Entrez Gene ID.
id2	A character vector. length > 1: each element is a GO term; length = 1: the Entrez Gene ID.
type	Input type of id1 and id2, 'go' for GO Terms, 'gene' for gene ID.
ont	Default is 'MF', can be one of 'MF', 'BP', or 'CC' subontologies.
organism	Default is 'human', can be one of 'anopheles', 'arabidopsis', 'bovine', 'canine', 'chicken', 'chimp', 'coelicolor', 'ecolik12', 'ecsakai', 'fly', 'human', 'malaria', 'mouse', 'pig', 'rat', 'rhesus', 'worm', 'xenopus', 'yeast' or 'zebrafish'.
measure	Default is 'Resnik', can be one of 'Resnik', 'Lin', 'Rel', 'Jiang' or 'Wang'.
combine	Default is 'BMA', can be one of 'max', 'average', 'rcmax' or 'BMA' for combining semantic similarity scores of multiple GO terms associated with protein.

Value

A $n \times n$ matrix.

Author(s)

Nan Xiao <<https://nanx.me>>

See Also

See [parGOSim](#) for protein similarity calculation based on Gene Ontology (GO) semantic similarity. See [parSeqSim](#) for paralleled protein similarity calculation based on Smith-Waterman local alignment.

Examples

```
## Not run:
# Be careful when testing this since it involves GO similarity computation
# and might produce unpredictable results in some environments

library("GOSemSim")
library("org.Hs.eg.db")

# by GO terms
go1 = c("GO:0004022", "GO:0004024", "GO:0004023")
go2 = c("GO:0009055", "GO:0020037")
gsim1 = twoGOSim(go1, go2, type = "go", ont = "MF", measure = "Wang")
print(gsim1)

# by Entrez gene id
gene1 = "241"
gene2 = "251"
gsim2 = twoGOSim(gene1, gene2, type = "gene", ont = "BP", measure = "Lin")
print(gsim2)
## End(Not run)
```

twoSeqSim

*Protein Sequence Alignment for Two Protein Sequences***Description**

This function implements the sequence alignment between two protein sequences.

Usage

```
twoSeqSim(seq1, seq2, type = "local", submat = "BLOSUM62")
```

Arguments

seq1	A character string, containing one protein sequence.
seq2	A character string, containing another protein sequence.
type	Type of alignment, default is 'local', could be 'global' or 'local', where 'global' represents Needleman-Wunsch global alignment; 'local' represents Smith-Waterman local alignment.
submat	Substitution matrix, default is 'BLOSUM62', can be one of 'BLOSUM45', 'BLOSUM50', 'BLOSUM62', 'BLOSUM80', 'BLOSUM100', 'PAM30', 'PAM40', 'PAM70', 'PAM120', or 'PAM250'.

Value

An Biostrings object containing the scores and other alignment information.

Author(s)

Nan Xiao <<https://nanx.me>>

See Also

See [parSeqSim](#) for paralleled pairwise protein similarity calculation based on sequence alignment.
See [twoGOSim](#) for calculating the GO semantic similarity between two groups of GO terms or two Entrez gene IDs.

Examples

```
## Not run:  
# Be careful when testing this since it involves sequence alignment  
# and might produce unpredictable results in some environments  
library("Biostrings")  
s1 = readFASTA(system.file("protseq/P00750.fasta", package = "protr"))[[1]]  
s2 = readFASTA(system.file("protseq/P10323.fasta", package = "protr"))[[1]]  
seqalign = twoSeqSim(s1, s2)  
summary(seqalign)  
print(seqalign@score)  
## End(Not run)
```

Index

- *Topic **AAindex**
 - AAindex, 10
 - extractProtFP, 43
 - extractProtFPGap, 44
- *Topic **APAAC**
 - extractAPAAC, 18
- *Topic **APseAAC**
 - extractAPAAC, 18
- *Topic **Alignment**
 - extractPSSM, 45
 - extractPSSMAcc, 48
 - extractPSSMFeature, 49
- *Topic **Amphiphilic**
 - extractAPAAC, 18
- *Topic **BLOSUM**
 - extractBLOSUM, 20
- *Topic **Blast**
 - extractPSSM, 45
 - extractPSSMAcc, 48
 - extractPSSMFeature, 49
- *Topic **CTD**
 - extractCTDC, 21
 - extractCTDCClass, 22
 - extractCTDD, 23
 - extractCTDDClass, 25
 - extractCTDT, 26
 - extractCTDTClass, 27
- *Topic **Composition**
 - extractAAC, 17
 - extractAPAAC, 18
 - extractCTDC, 21
 - extractCTDCClass, 22
 - extractCTDD, 23
 - extractCTDDClass, 25
 - extractDC, 31
 - extractPAAC, 41
 - extractTC, 55
- *Topic **Conjoint**
 - extractCTriad, 29
 - extractCTriadClass, 30
- *Topic **Coupling**
 - extractSOCN, 54
- *Topic **Dipeptide**
 - extractDC, 31
- *Topic **FASTA**
 - readFASTA, 61
- *Topic **Factor**
 - extractFAScales, 33
- *Topic **GO**
 - parGOSim, 57
 - twoGOSim, 64
- *Topic **Geary**
 - extractGeary, 34
- *Topic **MDS**
 - extractMDSScales, 36
- *Topic **Moran**
 - extractMoran, 37
- *Topic **Moreau-Broto**
 - extractMoreauBroto, 39
- *Topic **Ontology**
 - parGOSim, 57
 - twoGOSim, 64
- *Topic **Order**
 - extractSOCN, 54
- *Topic **PAAC**
 - extractPAAC, 41
- *Topic **PAM**
 - extractBLOSUM, 20
- *Topic **PCA**
 - extractScales, 51
 - extractScalesGap, 52
- *Topic **PCM**
 - extractBLOSUM, 20
 - extractDescScales, 32
 - extractFAScales, 33
 - extractMDSScales, 36
 - extractScales, 51
 - extractScalesGap, 52

- *Topic **PDB**
 - readPDB, 62
- *Topic **PSSM**
 - extractPSSM, 45
 - extractPSSMAcc, 48
 - extractPSSMFeature, 49
- *Topic **PseAAC**
 - extractPAAC, 41
- *Topic **Pseudo**
 - extractPAAC, 41
- *Topic **QSO**
 - extractQSO, 50
- *Topic **SOCN**
 - extractSOCN, 54
- *Topic **Transition**
 - extractCTDT, 26
 - extractCTDTClass, 27
- *Topic **Triad**
 - extractCTriad, 29
 - extractCTriadClass, 30
- *Topic **Tripeptide**
 - extractTC, 55
- *Topic **UniProt**
 - getUniProt, 56
- *Topic **acc**
 - acc, 16
- *Topic **alignment**
 - parSeqSim, 58
 - twoSeqSim, 65
- *Topic **autocorrelation**
 - extractGeary, 34
 - extractMoran, 37
 - extractMoreauBroto, 39
- *Topic **check**
 - protcheck, 59
- *Topic **covariance**
 - acc, 16
- *Topic **datasets**
 - AA2DACOR, 4
 - AA3DMorSE, 5
 - AAACF, 5
 - AABLOSUM100, 5
 - AABLOSUM45, 6
 - AABLOSUM50, 6
 - AABLOSUM62, 6
 - AABLOSUM80, 7
 - AABurden, 7
 - AAConn, 7
 - AAConst, 8
 - AACPSA, 8
 - AADescAll, 8
 - AAEdgeAdj, 9
 - AAEigIdx, 9
 - AAFGC, 9
 - AAGeom, 10
 - AAGETAWAY, 10
 - AAindex, 10
 - AAInfo, 11
 - AAMetaInfo, 11
 - AAMOE2D, 11
 - AAMOE3D, 12
 - AAMolProp, 12
 - AAPAM120, 12
 - AAPAM250, 13
 - AAPAM30, 13
 - AAPAM40, 13
 - AAPAM70, 14
 - AARandic, 14
 - AARDF, 14
 - AATopo, 15
 - AATopoChg, 15
 - AAWalk, 15
 - AAWHIM, 16
 - OptAA3d, 56
- *Topic **extract**
 - extractAAC, 17
 - extractAPAAC, 18
 - extractBLOSUM, 20
 - extractCTDC, 21
 - extractCTDCClass, 22
 - extractCTDD, 23
 - extractCTDDClass, 25
 - extractCTDT, 26
 - extractCTDTClass, 27
 - extractCTriad, 29
 - extractCTriadClass, 30
 - extractDC, 31
 - extractDescScales, 32
 - extractFAScales, 33
 - extractGeary, 34
 - extractMDSScales, 36
 - extractMoran, 37
 - extractMoreauBroto, 39
 - extractPAAC, 41
 - extractProtFP, 43
 - extractProtFPGap, 44

- extractPSSM, 45
- extractPSSMAcc, 48
- extractPSSMFeature, 49
- extractQSO, 50
- extractScales, 51
- extractScalesGap, 52
- extractSOCN, 54
- extractTC, 55
- *Topic **gap**
 - extractProtFPGap, 44
 - extractScalesGap, 52
- *Topic **normalized**
 - extractMoreauBroto, 39
- *Topic **parallel**
 - parSeqSim, 58
 - twoSeqSim, 65
- *Topic **read**
 - readPDB, 62
- *Topic **scales**
 - extractDescScales, 32
 - extractProtFP, 43
 - extractProtFPGap, 44
 - extractScales, 51
 - extractScalesGap, 52
- *Topic **segmentation**
 - protseg, 60
- *Topic **similarity**
 - parGOSim, 57
 - parSeqSim, 58
 - twoGOSim, 64
 - twoSeqSim, 65
- AA2DACOR, 4
- AA3DMoRSE, 5
- AAACF, 5
- AABLOSUM100, 5
- AABLOSUM45, 6
- AABLOSUM50, 6
- AABLOSUM62, 6
- AABLOSUM80, 7
- AABurden, 7
- AAConn, 7
- AAConst, 8
- AACPSA, 8
- AADescAll, 8
- AAEdgeAdj, 9
- AAEigIdx, 9
- AAFGC, 9
- AAGeom, 10
- AAGETAWAY, 10
- AAindex, 10, 19, 42
- AAInfo, 11
- AAMetaInfo, 11
- AAMOE2D, 11
- AAMOE3D, 12
- AAMolProp, 12
- AAPAM120, 12
- AAPAM250, 13
- AAPAM30, 13
- AAPAM40, 13
- AAPAM70, 14
- AARandic, 14
- AARDF, 14
- AATopo, 15
- AATopoChg, 15
- AAWalk, 15
- AAWHIM, 16
- acc, 16
- extractAAC, 17, 31, 55
- extractAPAAC, 18, 42
- extractBLOSUM, 20
- extractCTDC, 21, 24, 27
- extractCTDCClass, 22, 26, 28
- extractCTDD, 21, 23, 27
- extractCTDDClass, 23, 25, 28
- extractCTDT, 21, 24, 26
- extractCTDTClass, 23, 26, 27
- extractCTriad, 29
- extractCTriadClass, 30
- extractDC, 18, 31, 55
- extractDescScales, 17, 32, 52
- extractFAScales, 33
- extractGeary, 34, 38, 40
- extractMDSScales, 36
- extractMoran, 35, 37, 40
- extractMoreauBroto, 35, 38, 39
- extractPAAC, 19, 41
- extractProtFP, 17, 43, 52
- extractProtFPGap, 44, 53
- extractPSSM, 45, 48–50
- extractPSSMAcc, 47, 48, 50
- extractPSSMFeature, 47, 48, 49
- extractQSO, 50, 54
- extractScales, 17, 37, 51
- extractScalesGap, 52
- extractSOCN, 51, 54
- extractTC, 18, 31, 55

getUniProt, [56](#), [61](#)

getwd, [61](#), [62](#)

gsub, [63](#)

OptAA3d, [8](#), [12](#), [56](#)

parGOSim, [57](#), [59](#), [64](#)

parSeqSim, [57](#), [58](#), [64](#), [66](#)

protcheck, [59](#)

protr (protr-package), [3](#)

protr-package, [3](#)

protseg, [60](#)

readFASTA, [56](#), [61](#), [62](#)

readPDB, [62](#)

removeGaps, [63](#)

twoGOSim, [57](#), [64](#), [66](#)

twoSeqSim, [65](#)