

# Package ‘rbounds’

January 2, 2012

**Type** Package

**Title** Perform Rosenbaum bounds sensitivity tests for matched and unmatched data.

**Version** 0.9

**Date** 2011-10-04

**Author** Luke J. Keele

**Maintainer** Luke J. Keele <ljk20@psu.edu>

**Depends** R (>= 2.8.1), Matching (>= 4.6-2)

**Description** Takes matched and unmatched data and calculates Rosenbaum bounds for the treatment effect. Calculates bounds for binary data, Hodges-Lehmann point estimates, Wilcoxon signed-rank test for matched data and matched IV estimators, and for data with multiple matched controls. Is designed to work with the Matching package and operate on Match() objects.

**License** GPL (>= 2)

**Repository** CRAN

**Date/Publication** 2011-10-11 15:24:22

## R topics documented:

AngristLavy . . . . .	2
binarysens . . . . .	2
data.prep . . . . .	4
hlsens . . . . .	5
iv_sens . . . . .	7
mcontrol . . . . .	8
print.rbounds . . . . .	10
psens . . . . .	11

<b>Index</b>	<b>13</b>
--------------	-----------

AngristLavy

*Angrist and Lavy (1999) Maimonides' Rule Data Set*

---

**Description**

Angrist and Lavy (1999) data set used by Rosenbaum (2010) to demonstrate his instrumental variable sensitivity analysis.

**Usage**

AngristLavy

**Format**

A data.frame with 318 observations on the following 5 variables).

enrollment: Enrolled number of students in each cohort

pct\_disadv: Percentage of students that are economically disadvantaged.

classsize: Size of class or classes for each cohort.

avgmth: Average math test score for each class.

z: A recode of enrollment with 1 indicating a cohort with 41 or more students, i.e. two classes. This serves as the instrument which encourages smaller classes.

**Source**

Angrist, Joshua and Lavy, Victor (1999). "Using Maimonides' Rule to Estimate the Effect of Class Size on Scholastic Achievement." *Quarterly Journal of Economics* 114, 533–575.

Rosenbaum, Paul R. (2010). *Design of Observational Studies*. Springer-Verlag.

**References**

Rosenbaum, Paul R. (2010). *Design of Observational Studies*. Springer-Verlag.

---

binarysens

*Binary Sensitivity Test*

---

**Description**

Function to calculate Rosenbaum bounds for binary data.

**Usage**

```
binarysens(x,y, Gamma=6, GammaInc=1)
```

**Arguments**

x	Count of the first set of discrepant pairs in a table of treated and control outcomes.
y	Count of the second set of discrepant pairs in a table of treated and control outcomes.
Gamma	Upper-bound on gamma parameter.
GammaInc	To set user specified increments for gamma parameter.

**Author(s)**

Luke Keele, Penn State University, <ljk20@psu.edu>

**References**

Rosenbaum, Paul R. (2002) *Observational Studies*. Springer-Verlag.

**See Also**

See also [data.prep](#), [psens](#), [hlsens](#), [Match](#), [mcontrol](#)

**Examples**

```
# Example From Rosenbaum Observational Studies Pg 112
# Success: Died From Lung Cancer
# 110 Discrepant Pairs
# 12 Discrepant Pairs

# Sensitivity Test
binarysens(12,110)

# Example Using Match()

#Load Matching Software and Data

library(Matching)
data(GerberGreenImai)

# Estimate Propensity Score
pscore.glm <- glm(PHN.C1 ~ PERSONS + VOTE96.1 + NEW +
  MAJORPTY + AGE + WARD + PERSONS:VOTE96.1 + PERSONS:NEW +
  AGE2, family = binomial(logit), data = GerberGreenImai)

#save data objects
D <- GerberGreenImai$PHN.C1
Y <- GerberGreenImai$VOTED98
X <- fitted(pscore.glm)

# Match - without replacement
m.obj <- Match(Y = Y, Tr = D, X = X, M = 1, replace=FALSE)
```

```
summary(m.obj)

# One should check balance, but let's skip that step for now.

# Sensitivity Test
binarysens(m.obj, Gamma=2, GammaInc=.1)
```

---

data.prep

---

*Format Match() object for sensitivity test.*


---

## Description

This function reshapes the output from Match() to create the necessary objects for mcontrol().

## Usage

```
# Default Method
data.prep(obj, Y = NULL, group.size = 3)
```

## Arguments

obj	An object from the Match() function.
Y	Internal argument to the Match object.
group.size	The size of the matched groups. Three for one treated unit and two control units.

## Details

This functions takes a Match() object and formats it for use with the mcontrol() function. The output is a list with the three objects needed for the arguments of the mcontrol() function.

## Value

Y	The matched outcomes
id	A vector which identifies the matched groups: 1, 1, 1 for matched group one; 2, 2, 2 for match group 2, etc.
treat	A vector with 1's for treated units and 0's for control units

## Author(s)

Luke Keele, Penn State University, <ljk20@psu.edu>

## References

Rosenbaum, Paul R. (2002) *Observational Studies*. Springer-Verlag.

**See Also**

See also [binarysens](#), [psens](#), [hlsens](#), [Match](#), [mcontrol](#)

**Examples**

```
# Load Matching Software and Data
library(Matching)
data(lalonde)

# Estimate Propensity Score
DWglm <- glm(treat~age + I(age^2) + educ + I(educ^2) + black + hisp +
             married + nodegr + re74 + I(re74^2) + re75 + I(re75^2) +
             u74 + u75, family=binomial, data=lalonde)

# Save data objects
Y <- lalonde$re78 # the outcome of interest
Tr <- lalonde$treat # the treatment of interest

# Match
mDW <- Match(Y = Y, Tr = Tr, X = DWglm$fitted, M = 2)

# One should check balance, but let's skip that step for now.

# Create Data Object
tmp <- data.prep(mDW, group.size=3)

# Sensitivity Test
mcontrol(tmp$Y, tmp$id, tmp$treat, group.size = 3)
```

---

hlsens

*Rosenbaum Bounds for Hodges-Lehmann Point Estimate*


---

**Description**

Function to calculate Rosenbaum bounds for continuous or ordinal outcomes based on Hodges-Lehmann point estimate.

**Usage**

```
# Default Method
hlsens(x, y = NULL, pr = 0.1, Gamma = 6, GammaInc = 1)
```

**Arguments**

x Treatment group outcomes in same order as treatment group outcomes or an objects from `Match()`.

y	Control group outcomes in same order as treatment group outcomes unnecessary when using Match() object.
pr	Search precision parameter.
Gamma	Upper-bound on gamma parameter.
GammaInc	To set user specified increments for gamma parameter.

### Details

For large data sets this function can be quite slow if pr is set to low. If the data set is larger, it is best to set pr to .5 before trying values such as .01. Generally, the results from the function are insensitive to the value for pr.

### Author(s)

Luke Keele, Penn State University, <ljk20@psu.edu>

### References

Rosenbaum, Paul R. (2002) *Observational Studies*. Springer-Verlag.

### See Also

See also [data.prep](#), [binarysens](#), [psens](#), [Match](#), [mcontrol](#)

### Examples

```
# Replication of Rosenbaum Sensitivity Tests From Chapter 4 of
# Observational Studies

# Data: Matched Data of Lead Blood Levels in Children
trt <- c(38, 23, 41, 18, 37, 36, 23, 62, 31, 34, 24, 14, 21, 17, 16, 20,
15, 10, 45, 39, 22, 35, 49, 48, 44, 35, 43, 39, 34, 13, 73, 25, 27)

ctrl <- c(16, 18, 18, 24, 19, 11, 10, 15, 16, 18, 18, 13, 19, 10, 16,
16, 24, 13, 9, 14, 21, 19, 7, 18, 19, 12, 11, 22, 25, 16, 13, 11, 13)

hlsens(trt, ctrl)

# Load Matching Software and Data
library(Matching)
data(lalonde)

# Estimate Propensity Score
DWglm <- glm(treat~age + I(age^2) + educ + I(educ^2) + black + hisp +
  married + nodegr + re74 + I(re74^2) + re75 + I(re75^2) +
  u74 + u75, family=binomial, data=lalonde)

# Save data objects
Y <- lalonde$re78 # the outcome of interest
Tr <- lalonde$treat # the treatment of interest
```

```
# Match - without replacement
mDW <- Match(Y=Y, Tr=Tr, X=DWglm$fitted, replace=FALSE)

# One should check balance, but let's skip that step for now.

# Sensitivity Test:
hlsens(mDW, pr=.1, Gamma=2, GammaInc=.1)
```

---

iv_sens	<i>Function to calculate Rosenbaum bounds for IV Estimator based on Wilcoxon sign rank test.</i>
---------	--

---

## Description

iv\_sens performs a non-parametric, instrumental variable sensitivity analysis on matched pairs following the logic of the Neyman-Rubin framework for causal inference. The function supports a variable-valued instrument.

## Usage

```
iv_sens(Rt, Rc, Dt, Dc, Gamma = 6, GammaInc = 1)
```

## Arguments

Rt,Rc	Vectors of observed response outcomes for matched treatment and control observations, respectively.
Dt,Dc	Vectors of observed doses for matched observations, respectively. This is level of dose encouraged by the instrument.
Gamma	Upper-bound on gamma parameter.
GammaInc	To set user specified increments for gamma parameter.

## Details

Given matched pairs of observations on an instrument Z, which encourages dose D, this function performs a Rosenbaum's bounds sensitivity analysis. Note that matching is done on levels of the instrument. See example below.

## Value

Returns an object of class rbounds.

## Author(s)

Luke Keele, Penn State University, <ljk20@psu.edu>

Jason W. Morgan, Ohio State University, <morgan.746@osu.edu>

## References

- Angrist, Joshua D., Imbens, Guido W., and Rubin, Donald B. (1996). "Identification of Causal Effects Using Instrumental Variables." *Journal of the American Statistical Association* 91/434, pp. 444–455.
- Rosenbaum, Paul R. (1996). "Comment." *Journal of the American Statistical Association* 91/434, pp. 465–468.
- Rosenbaum, Paul R. (2002). *Observational Studies*. Springer-Verlag.
- Rosenbaum, Paul R. (2010). *Design of Observational Studies*. Springer-Verlag.

## See Also

See also [data.prep](#), [binarysens](#), [hlsens](#), [Match](#), [mcontrol](#)

## Examples

```
## Example from Rosenbaum (2010, ch. 5).

data(AngristLavy)

#Match on Economic Status Across Levels of the Instrument
rr <- Match(Y=AngristLavy$avgmth, Tr=AngristLavy$z, X=AngristLavy$pct_disadv,
  estimand ="ATC", M=2, replace=FALSE)

#ITT Estimate
summary(rr)

#Extract Matched Outcome Data
ctrl <- AngristLavy$avgmth[rr$index.control]
trt <- AngristLavy$avgmth[rr$index.treated]

#Extract Matched Doses
#Doses Encouraged By Instrument - Here Class Size
csize.trt <- AngristLavy$classize[rr$index.treated]
csize.ctrl <- AngristLavy$classize[rr$index.control]

#Run Sensitivity Analysis
iv_sens(trt, ctrl, csize.trt, csize.ctrl, Gamma=2, GammaInc=.1)
```

---

mcontrol

*Sensitivity Analysis For Multiple Matched Controls*

---

## Description

Function to calculate Rosenbaum bounds for continuous or ordinal outcomes based on Wilcoxon sign rank test  $p$ -value when there are multiple matched control units.

**Usage**

```
# Default Method
mcontrol(y, grp.id, treat.id, group.size = 3, Gamma = 4, GammaInc = 1)
```

**Arguments**

y	Vector of grouped matched outcomes.
treat.id	A vector indicating the treated unit in each matched group.
grp.id	A vector indicating matched groups.
group.size	The size of the matched groups. Three for one treated unit and two control units.
Gamma	Upper-bound on gamma parameter.
GammaInc	To set increments for gamma parameter.

**Details**

The matched data needs to be in a very particular form for this function to work. The data must be sorted by matched groups with indicators for each matched group and for treated and control units. The simplest way to prepare the data is to use the `Match()` function and use the `data.prep()` function to format the data.

Currently this function only takes matched data with 2 or 3 controls units matched to each treated unit.

This function does not handle data where the number of control units is not the same for every treated unit.

**Author(s)**

Luke Keele, Penn State University, <ljk20@psu.edu>

**References**

Rosenbaum, Paul R. (2002) *Observational Studies*. Springer-Verlag.

**See Also**

See also [data.prep](#), [binarysens](#), [psens](#), [Match](#), [hlsens](#)

**Examples**

```
# Load Matching Software and Data
library(Matching)
data(lalonde)

# Estimate Propensity Score
DWglm <- glm(treat~age + I(age^2) + educ + I(educ^2) + black + hisp +
  married + nodegr + re74 + I(re74^2) + re75 + I(re75^2) +
  u74 + u75, family=binomial, data=lalonde)
```

```
# Save data objects
Y <- lalonde$re78 # the outcome of interest
Tr <- lalonde$treat # the treatment of interest

# Match - without replacement
mDW <- Match(Y=Y, Tr=Tr, X=DWglm$fitted, M=2, replace=FALSE)

# One should check balance, but let's skip that step for now.

# Create Data Object:
tmp <- data.prep(mDW, group.size=3)

# Sensitivity Test
mcontrol(tmp$Y, tmp$id, tmp$treat, group.size=3)
```

---

print.rbounds

*Summarize output from rbounds object*

---

## Description

Summary method for rbounds object.

## Usage

```
## S3 method for class 'rbounds'
print(x, ...)
```

## Arguments

x                   An object of class rbounds as produced by [binarysens](#), [hlsens](#), or [psens](#).  
...                  Any additional arguments.

## Author(s)

Jason W. Morgan, Ohio State University, <morgan.746@osu.edu>

## See Also

Also see [binarysens](#), [psens](#), and [hlsens](#).

---

psens                      *Rosenbaum Bounds for Sign Rank*

---

### Description

Function to calculate Rosenbaum bounds for continuous or ordinal outcomes based on Wilcoxon sign rank test.

### Usage

```
# Default Method
psens(x, y = NULL, Gamma = 6, GammaInc = 1)
```

### Arguments

x	Treatment group outcomes in same order as treatment group outcomes or an objects from a <a href="#">Match</a> .
y	Control group outcomes in same order as treatment group outcomes unnecessary when using a <a href="#">Match</a> object.
Gamma	Upper-bound on gamma parameter.
GammaInc	To set user-specified increments for gamma parameter.

### Author(s)

Luke Keele, Penn State University, <ljk20@psu.edu>

### References

Rosenbaum, Paul R. (2002) *Observational Studies*. Springer-Verlag.

### See Also

See also [data.prep](#), [binarysens](#), [hlsens](#), [Match](#), [mcontrol](#)

### Examples

```
# Replication of Rosenbaum Sensitivity Tests From Chapter 4 of
# Observational Studies

# Data: Matched Data of Lead Blood Levels in Children
trt <- c(38, 23, 41, 18, 37, 36, 23, 62, 31, 34, 24, 14, 21, 17, 16, 20,
        15, 10, 45, 39, 22, 35, 49, 48, 44, 35, 43, 39, 34, 13, 73, 25,
        27)
ctrl <- c(16, 18, 18, 24, 19, 11, 10, 15, 16, 18, 18, 13, 19, 10, 16,
         16, 24, 13, 9, 14, 21, 19, 7, 18, 19, 12, 11, 22, 25, 16, 13,
         11, 13)
```

```
psens(trt, ctrl)

# Example With Match()

# Load Matching Software and Data
library(Matching)
data(lalonde)

# Estimate Propensity Score
DWglm <- glm(treat ~ age + I(age^2) + educ + I(educ^2) + black + hisp +
             married + nodegr + re74 + I(re74^2) + re75 + I(re75^2) +
             u74 + u75, family=binomial, data=lalonde)

# Save data objects
Y <- lalonde$re78 #the outcome of interest
Tr <- lalonde$treat #the treatment of interest

# Match - without replacement
mDW <- Match(Y=Y, Tr=Tr, X=DWglm$fitted, replace=FALSE)

# One should check balance, but let's skip that step for now.

# Sensitivity Test
psens(mDW, Gamma = 2, GammaInc = 0.1)
```

# Index

## \*Topic **datasets**

AngristLavy, [2](#)

AngristLavy, [2](#)

binarysens, [2](#), [5](#), [6](#), [8–11](#)

data.prep, [3](#), [4](#), [6](#), [8](#), [9](#), [11](#)

hlsens, [3](#), [5](#), [5](#), [8–11](#)

iv\_sens, [7](#)

Match, [3](#), [5](#), [6](#), [8](#), [9](#), [11](#)

mcontrol, [3](#), [5](#), [6](#), [8](#), [8](#), [11](#)

print.rbounds, [10](#)

psens, [3](#), [5](#), [6](#), [9](#), [10](#), [11](#)

summary.rbounds (print.rbounds), [10](#)