

Package ‘rgrass7’

August 6, 2019

Version 0.2-1

Date 2019-07-23

Title Interface Between GRASS 7 Geographical Information System and R

Description Interpreted interface between 'GRASS' 7 geographical information system and R, based on starting R from within the 'GRASS' 'GIS' environment, or running free-standing R in a temporary 'GRASS' location; the package provides facilities for using all 'GRASS' commands from the R command line. This package may not be used for 'GRASS' 6, for which 'spgrass6' should be used.

Depends R (>= 3.3.0), XML

Imports stats, utils, methods

Suggests rgdal (>= 1.0-6), RSQLite, sp (>= 0.9), sf (>= 0.7.6), stars

SystemRequirements GRASS (>= 7)

License GPL (>= 2)

URL <http://grass.osgeo.org/>,
<https://r-forge.r-project.org/projects/spgrass/>

Collate AAA.R options.R rgrass.R bin_link.R vect_link.R initGRASS.R
xml1.R

NeedsCompilation no

Author Roger Bivand [cre, aut],
Rainer Krug [ctb],
Markus Neteler [ctb],
Sebastian Jeworutzki [ctb]

Maintainer Roger Bivand <Roger.Bivand@nhh.no>

Repository CRAN

Date/Publication 2019-08-06 09:10:02 UTC

R topics documented:

rgrass7-package	2
execGRASS	3
gmeta	6
initGRASS	8
readRAST	10
readVECT	13
Index	18

rgrass7-package	<i>Interface between GRASS geographical information system and R</i>
-----------------	--

Description

Interpreted interface between GRASS geographical information system, version 7, and R, based on starting R from within the GRASS environment, or on running R stand-alone and creating a throw-away GRASS environment from within R. The interface uses classes defined in the sp package to hold spatial data.

Details

Index:

readRAST	read GRASS raster files
writeRAST	write GRASS raster files
readVECT	read GRASS vector object files
writeVECT	write GRASS vector object files
gmeta	read GRASS metadata from the current LOCATION
getLocationProj	return a PROJ.4 string of projection information
gmeta2grd	create a GridTopology object from the GRASS region
vInfo	return vector geometry information
vColumns	return vector database columns information
vDataCount	return count of vector database rows
vect2neigh	return area neighbours with shared boundary length

Note that the examples now use the smaller subset North Carolina location: http://grass.osgeo.org/sampleddata/north_carolina/nc_basic_spm_grass7.tar.gz

Author(s)

Roger Bivand

Maintainer: Roger Bivand <Roger.Bivand@nhh.no>

Examples

```

use_sp()
run <- FALSE
if (nchar(Sys.getenv("GISRC")) > 0 &&
    read.dcf(Sys.getenv("GISRC"))[1,"LOCATION_NAME"] == "nc_basic_spm_grass7") run <- TRUE
if (run) {
  # require(rgdal)
  elevation <- readRAST("elevation", ignore.stderr=TRUE, plugin=FALSE)
  summary(elevation)
}
if (run) {
  grd <- gmeta2grd(ignore.stderr=TRUE)
  grd
}
if (run) {
  set.seed(1)
  pts <- sp::spsample(elevation, 200, "random")
  smple <- sp::SpatialPointsDataFrame(pts, data=sp::over(pts, elevation))
  summary(smple)
}
if (run) {
  writeVECT(smple, "sp_dem", v.in.ogr_flags=c("overwrite", "o"), ignore.stderr=TRUE)
  bugsDF <- readVECT("schools", ignore.stderr=TRUE, mapset="PERMANENT")
  summary(bugsDF)
}
if (run) {
  vInfo("streams", ignore.stderr=TRUE)
}
if (run) {
  vColumns("streams", ignore.stderr=TRUE)
}
if (run) {
  vDataCount("streams", ignore.stderr=TRUE)
}
if (run) {
  streams <- readVECT("streams", type="line",
    remove.duplicates=FALSE, ignore.stderr=TRUE, plugin=FALSE)
  summary(streams)
}

```

execGRASS

Run GRASS commands

Description

The functions provide an interface to GRASS commands run through system, based on the values returned by the `--interface` description flag using XML parsing. If required parameters are omitted, and have declared defaults, the defaults will be used.

Usage

```

execGRASS(cmd, flags = NULL, ..., parameters = NULL, intern = NULL,
  ignore.stderr = NULL, Sys_ignore.stdout=FALSE, Sys_wait=TRUE,
  Sys_input=NULL, Sys_show.output.on.console=TRUE, Sys_minimized=FALSE,
  Sys_invisible=TRUE, echoCmd=NULL, redirect=FALSE, legacyExec=NULL)
doGRASS(cmd, flags = NULL, ..., parameters = NULL, echoCmd=NULL,
  legacyExec=NULL)
parseGRASS(cmd, legacyExec=NULL)
## S3 method for class 'GRASS_interface_desc'
print(x, ...)
getXMLencoding()
setXMLencoding(enc)

```

Arguments

cmd	GRASS command name
flags	character vector of GRASS command flags
...	for execGRASS and doGRASS, GRASS module parameters given as R named arguments directly. For the print method, other arguments to print method. The storage modes of values passed must match those required in GRASS, so a single GRASS string must be a character vector of length 1, a single GRASS integer must be an integer vector of length 1 (may be an integer constant such as 10L), and a single GRASS float must be a numeric vector of length 1. For multiple values, use vectors of suitable length
parameters	list of GRASS command parameters, used if GRASS parameters are not given as R arguments directly; the two methods for passing GRASS parameters may not be mixed. The storage modes of values passed must match those required in GRASS, so a single GRASS string must be a character vector of length 1, a single GRASS integer must be an integer vector of length 1 (may be an integer constant such as 10L), and a single GRASS float must be a numeric vector of length 1. For multiple values, use vectors of suitable length
intern	default NULL, in which case set internally from get.useInternOption; a logical (not 'NA') which indicates whether to make the output of the command an R object. Not available unless 'popen' is supported on the platform
ignore.stderr	default NULL, taking the value set by set.ignore.stderrOption, a logical indicating whether error messages written to 'stderr' should be ignored
Sys_ignore.stdout, Sys_wait, Sys_input	pass extra arguments to system
Sys_show.output.on.console, Sys_minimized, Sys_invisible	pass extra arguments to system on Windows systems only
echoCmd	default NULL, taking the logical value set by set.echoCmdOption, print GRASS command to be executed to console
redirect	default FALSE, if TRUE, add "2>&1" to the command string and set intern to TRUE; only used in legacy mode

legacyExec	default NULL, taking the logical value set by <code>set.legacyExecOption</code> which is initialised to FALSE on “unix” platforms and TRUE otherwise. If TRUE, use <code>system</code> , if FALSE use <code>system2</code> and divert <code>stderr</code> to temporary file to record error messages and warnings from GRASS modules
x	object to be printed
enc	character string to replace UTF-8 in header of XML data generated by GRASS module <code>-interface-description</code> output when the internationalised messages are not in UTF-8 (known to apply to French, which is in latin1)

Details

`parseGRASS` checks to see whether the GRASS command has been parsed already and cached in this session; if not, it reads the interface description, parses it and caches it for future use. `doGRASS` assembles a proposed GRASS command with flags and parameters as a string, wrapping `parseGRASS`, and `execGRASS` is a wrapper for `doGRASS`, running the command through `system` (from 0.7-4, the `...` argument is not used for passing extra arguments for `system`). The command string is termed `proposed`, because not all of the particular needs of commands are provided by the interface description, and no check is made for the existence of input objects. Support for multiple parameter values added with help from Patrick Caldon. Support for defaults and for direct use of GRASS parameters instead of a parameter list suggested by Rainer Krug.

Value

`parseGRASS` returns a `GRASS_interface_desc` object, `doGRASS` returns a character string with a proposed GRASS command - the expanded command name is returned as an attribute, and `execGRASS` returns what `system` or `system2` return, particularly depending on the `intern` argument when the character strings output by GRASS modules are returned. If `intern` is FALSE, `system` returns the module exit code, while `system2` returns the module exit code with “`resOut`” and “`resErr`” attributes.

Note

If any package command fails with a UTF-8 error from the XML package, try using `setXMLencoding` to work around the problem that GRASS modules declare `-interface-description` output as UTF-8 without ensuring that it is (French is of 6.4.0 RC5 latin1).

Author(s)

Roger S. Bivand, e-mail: <Roger.Bivand@nhh.no>

See Also

[system](#)

Examples

```
run <- FALSE
if (nchar(Sys.getenv("GISRC")) > 0 &&
    read.dcf(Sys.getenv("GISRC"))[1,"LOCATION_NAME"] == "nc_basic_spm_grass7") run <- TRUE
oechoCmd <- get.echoCmdOption()
```

```

    set.echoCmdOption(TRUE)
  if (run) {
    print(parseGRASS("r.slope.aspect"))
  }
  if (run) {
    doGRASS("r.slope.aspect", flags=c("overwrite"),
            elevation="elevation.dem", slope="slope", aspect="aspect")
  }
  if (run) {
    pars <- list(elevation="elevation", slope="slope", aspect="aspect")
    doGRASS("r.slope.aspect", flags=c("overwrite"), parameters=pars)
  }
  if (run) {
    print(parseGRASS("r.buffer"))
  }
  if (run) {
    doGRASS("r.buffer", flags=c("overwrite"), input="schools", output="bmap",
            distances=seq(1000,15000,1000))
  }
  if (run) {
    pars <- list(input="schools", output="bmap", distances=seq(1000,15000,1000))
    doGRASS("r.buffer", flags=c("overwrite"), parameters=pars)
  }
  if (run) {
    set.echoCmdOption(oechoCmd)
    try(res <- execGRASS("r.stats", input = "fire_blocksgg", # no such file
                        flags = c("C", "n")), silent=FALSE)
  }
  if (run) {
    res <- execGRASS("r.stats", input = "fire_blocksgg", flags = c("C", "n"),
                    legacyExec=TRUE)
    print(res)
  }
  if (run) {
    if (res != 0) {
      resERR <- execGRASS("r.stats", input = "fire_blocksgg",
                          flags = c("C", "n"), redirect=TRUE, legacyExec=TRUE)
      print(resERR)
    }
  }
}

```

gmeta

Reads GRASS metadata from the current LOCATION

Description

GRASS LOCATION metadata are read into a list in R; helper function getLocationProj returns an sproj-compliant PROJ.4 string of projection information. The helper function gmeta2grd creates a GridTopology object from the current GRASS mapset region definitions. The new use_sf() and use_sp() functions permit the user to use "sf" and "stars" classes for raster and vector objects in R; use will be extended over time.

Usage

```

use_sf()
use_sp()
gmeta(ignore.stderr = FALSE)
getLocationProj(ignore.stderr = FALSE)
gmeta2grd(ignore.stderr = FALSE)
## S3 method for class 'gmeta'
print(x, ...)
get.ignore.stderrOption()
get.stop_on_no_flags_parasOption()
get.useGDALOption()
get.pluginOption()
get.echoCmdOption()
get.useInternOption()
get.legacyExecOption()
get.defaultFlagsOption()
get.suppressEchoCmdInFuncOption()
set.ignore.stderrOption(value)
set.stop_on_no_flags_parasOption(value)
set.useGDALOption(value)
set.pluginOption(value)
set.echoCmdOption(value)
set.useInternOption(value)
set.legacyExecOption(value)
set.defaultFlagsOption(value)
set.suppressEchoCmdInFuncOption(value)

```

Arguments

<code>ignore.stderr</code>	default FALSE, can be set to TRUE to silence <code>system()</code> output to standard error; does not apply on Windows platforms
<code>x</code>	S3 object returned by <code>gmeta</code>
<code>...</code>	arguments passed through <code>print</code> method
<code>value</code>	logical value for setting options on <code>ignore.stderr</code> set by default on package load to FALSE, <code>stop_on_no_flags_paras</code> set by default on package load to TRUE, <code>useGDAL</code> set by default on package load to TRUE, <code>plugin</code> set by default on package load to NULL, <code>echoCmd</code> set by default on package load to FALSE. <code>useIntern</code> sets the <code>intern</code> argument globally; <code>legacyExec</code> sets the <code>legacyExec</code> option globally, but is initialized to FALSE on unix systems (all but Windows) and TRUE on Windows; <code>defaultFlags</code> is initialized to NULL, but may be a character vector with values from <code>c("quiet", "verbose")</code> <code>suppressEchoCmdInFunc</code> default TRUE suppresses the effect of <code>echoCmd</code> within package functions, may be set FALSE for debugging.

Value

Returns list of `g.gisenv`, `g.region -g3`, and `g.proj` values

Author(s)

Roger S. Bivand, e-mail: <Roger.Bivand@nhh.no.>

Examples

```

use_sp()
run <- FALSE
if (nchar(Sys.getenv("GISRC")) > 0 &&
    read.dcf(Sys.getenv("GISRC"))[1,"LOCATION_NAME"] == "nc_basic_spm_grass7") run <- TRUE
if (run) {
  G <- gmeta()
  print(G)
}
if (run) {
  sp::CRS(getLocationProj())
}
if (run) {
  grd <- gmeta2grd()
  print(grd)
}
if (run) {
  ncells <- prod(slot(grd, "cells.dim"))
  df <- data.frame(k=rep(1, ncells))
  mask_SG <- sp::SpatialGridDataFrame(grd, data=df)
  print(summary(mask_SG))
}

```

initGRASS

Initiate GRASS session

Description

Run GRASS interface in an R session not started within GRASS. In general, most users will use `initGRASS` in throwaway locations, to use GRASS modules on R objects without the need to define and populate a location. The function initializes environment variables used by GRASS, the `.gisrc` used by GRASS for further environment variables, and a temporary location.

The locking functions are used internally, but are exposed for experienced R/GRASS scripters needing to use the GRASS module “`g.mapset`” through `initGRASS` in an existing GRASS location. In particular, “`g.mapset`” may leave a `.gislock` file in the current MAPSET, so it may be important to call `unlink(.gislock)` to clean up before quitting the R session. `remove_GISRC` may be used to try to remove the file given in the “`GISRC`” environment variable if created by `initGRASS` with argument `remove_GISRC= TRUE`.

Usage

```

initGRASS(gisBase, home, SG, gisDbase, addon_base, location, mapset,
  override = FALSE, use_g.dirseps.exe = TRUE, pid, remove_GISRC=FALSE)
get.GIS_LOCK()

```

```

set.GIS_LOCK(pid)
unset.GIS_LOCK()
unlink_.gislock()
remove_GISRC()

```

Arguments

gisBase	The directory path to GRASS binaries and libraries, containing bin and lib sub-directories among others
home	The directory in which to create the .gisrc file; defaults to \$HOME on Unix systems and to USERPROFILE on Windows systems; can usually be set to tempdir()
SG	An optional SpatialGrid object to define the DEFAULT_WIND of the temporary location
gisDbase	if missing, tempdir() will be used; GRASS GISDBASE directory for the working session
addon_base	if missing, assumed to be "\$HOME/.grass7/addons" on Unix-like platforms, on MS Windows "%APPDATA%\GRASS7\addons", and checked for existence
location	if missing, basename(tempfile()) will be used; GRASS location directory for the working session
mapset	if missing, basename(tempfile()) will be used; GRASS mapset directory for the working session
override	default FALSE, set to TRUE if accidental trashing of GRASS .gisrc files and locations is not a problem
use_g.dirseps.exe	default TRUE; when TRUE appears to work for WinGRASS Native binaries, when FALSE for QGIS GRASS binaries; ignored on other platforms.
pid	default as.integer(round(runif(1, 1, 1000))), integer used to identify GIS_LOCK; the value here is arbitrary, but probably should be set correctly
remove_GISRC	default FALSE; if TRUE, attempt to unlink the temporary file named in the "GISRC" environment variable when the R session terminates or when this package is unloaded

Details

The function establishes an out-of-GRASS working environment providing GRASS commands with the environment variable support required, and may also provide a temporary location for use until the end of the running R session if the home argument is set to tempdir(), and the gisDbase argument is not given. Running gmeta6 shows where the location is, should it be desired to archive it before leaving R.

Value

The function runs gmeta6 before returning the current values of the running GRASS session that it provides.

Note

If any package command fails with a UTF-8 error from the XML package, try using `setXMLencoding` to work around the problem that GRASS modules declare `-interface-description` output as UTF-8 without ensuring that it is (French is of 6.4.0 RC5 latin1).

Author(s)

Roger S. Bivand, e-mail: <Roger.Bivand@nhh.no>

See Also

[gmeta](#)

Examples

```
## Not run:
initGRASS("/usr/bin/grass-7.0.0", home=tempdir())
initGRASS("C:/GRASS", home=tempdir())

## End(Not run)
```

readRAST

Read and write GRASS 7 raster files

Description

Read GRASS 7 raster files from GRASS 7 into R `SpatialGridDataFrame` objects, and write single columns of R `SpatialGridDataFrame` objects to GRASS 7. `readRAST` and `writeRAST` use temporary binary files and `r.out.bin` and `r.in.bin` for speed reasons.

Usage

```
readRAST(vname, cat=NULL, ignore.stderr = get.ignore.stderrOption(),
         NODATA=NULL, plugin=get.pluginOption(), mapset=NULL,
         useGDAL=get.useGDALOption(), close_OK=TRUE, drivename="GTiff",
         driverFileExt=NULL, return_SGDF=TRUE)
writeRAST(x, vname, zcol = 1, NODATA=NULL,
         ignore.stderr = get.ignore.stderrOption(), useGDAL=get.useGDALOption(),
         overwrite=FALSE, flags=NULL, drivename="GTiff")
```

Arguments

<code>vname</code>	A vector of GRASS 7 raster file names
<code>cat</code>	default NULL; if not NULL, must be a logical vector matching <code>vname</code> , stating which (CELL) rasters to return as factor
<code>ignore.stderr</code>	default taking the value set by <code>set.ignore.stderrOption</code> ; can be set to TRUE to silence <code>system()</code> output to standard error; does not apply on Windows platforms

plugin	default taking the value set by <code>set.pluginOption</code> ; NULL does auto-detection, changes to FALSE if <code>vname</code> is longer than 1, and a sanity check will be run on raster and current region, and the function will revert to FALSE if mismatch is found; if TRUE, the plugin is available and the raster should be read in its original region and resolution; if the plugin is used, no further arguments other than <code>mapset</code> are respected
mapset	default NULL, if plugin is TRUE, the mapset of the file to be imported will be autodetected; if not NULL and if plugin is TRUE, a character string overriding the autodetected mapset, otherwise ignored
useGDAL	(effectively defunct, only applies to use of plugin) default taking the value set by <code>set.useGDALOption</code> ; use plugin and <code>readGDAL</code> if autodetected or <code>plugin=TRUE</code> ; or for writing <code>writeGDAL</code> , <code>GTiff</code> , and <code>r.in.gdal</code> , if FALSE using <code>r.out.bin</code> or <code>r.in.bin</code>
close_OK	default TRUE - clean up possible open connections used for reading metadata; may be set to FALSE to avoid the side-effect of other user-opened connections being broken
drivername	default "GTiff"; a valid GDAL writable driver name to define the file format for intermediate files
driverFileExt	default NULL; otherwise string value of required driver file name extension
return_SGDF	default TRUE returning a <code>SpatialGridDataFrame</code> object, if FALSE, return a list with a <code>GridTopology</code> object, a list of bands, and a <code>proj4string</code> ; see example below
x	A <code>SpatialGridDataFrame</code> object for export to GRASS as a raster layer
zcol	Attribute column number or name
NODATA	by default NULL, in which case it is set to one less than <code>floor()</code> of the data values, otherwise an integer NODATA value (required to be integer by GRASS <code>r.out.bin</code>)
overwrite	default FALSE, if TRUE inserts "overwrite" into the value of the <code>flags</code> argument if not already there to allow existing GRASS rasters to be overwritten
flags	default NULL, character vector, for example "overwrite"

Value

`readRAST` returns a `SpatialGridDataFrame` objects with an `data.frame` in the data slots, and with the projection argument set. Note that the projection argument set is the the GRASS rendering of `proj4`, and will differ from the WKT/ESRI rendering returned by `readVECT` in form but not meaning. They are exchangeable but not textually identical, usually with the `+ellps=` term replaced by ellipsoid parameters verbatim. If `return_SGDF` is FALSE, a list with a `GridTopology` object, a list of bands, and a `proj4string` is returned, with an S3 class attribute of "gridList".

Author(s)

Roger S. Bivand, e-mail: <Roger.Bivand@nhh.no>

Examples

```

use_sp()
run <- FALSE
if (nchar(Sys.getenv("GISRC")) > 0 &&
    read.dcf(Sys.getenv("GISRC"))[1,"LOCATION_NAME"] == "nc_basic_spm_grass7") run <- TRUE
GV <- Sys.getenv("GRASS_VERBOSE")
Sys.setenv("GRASS_VERBOSE"=0)
# require(rgdal)
ois <- get.ignore.stderrOption()
set.ignore.stderrOption(TRUE)
get.useGDALOption()
if (run) {
  nc_basic <- readRAST(c("geology", "elevation"), cat=c(TRUE, FALSE),
    useGDAL=FALSE)
  nc_basic <- readRAST(c("geology", "elevation"), cat=c(TRUE, FALSE),
    useGDAL=TRUE)
  print(table(nc_basic$geology))
}
if (run) {
  execGRASS("r.stats", flags=c("c", "l", "quiet"), input="geology")
}
if (run) {
  boxplot(nc_basic$elevation ~ nc_basic$geology)
}
if (run) {
  nc_basic$sqdem <- sqrt(nc_basic$elevation)
}
if (run) {
  if ("GRASS" %in% rgdal::gdalDrivers()$name) {
    execGRASS("g.region", raster="elevation")
    dem1 <- readRAST("elevation", plugin=TRUE, mapset="PERMANENT")
    print(summary(dem1))
    execGRASS("g.region", raster="elevation")
  }
}
if (run) {
  writeRAST(nc_basic, "sqdemSP", zcol="sqdem", flags=c("quiet", "overwrite"))
  execGRASS("r.info", map="sqdemSP")
}
if (run) {
  execGRASS("g.remove", flags="f", name="sqdemSP", type="raster")
}
if (run) {
  writeRAST(nc_basic, "sqdemSP", zcol="sqdem", useGDAL=TRUE, flags=c("quiet", "overwrite"))
  execGRASS("r.info", map="sqdemSP")
}
if (run) {
  print(system.time(sqdemSP <- readRAST(c("sqdemSP", "elevation"),
    useGDAL=TRUE, return_SGDF=FALSE)))
}
if (run) {
  print(system.time(sqdemSP <- readRAST(c("sqdemSP", "elevation"),

```

```

        useGDAL=TRUE, return_SGDF=TRUE)))
    }
    if (run) {
      print(system.time(sqdemSP <- readRAST(c("sqdemSP", "elevation"),
        useGDAL=FALSE, return_SGDF=TRUE)))
    }
    if (run) {
      print(system.time(sqdemSP <- readRAST(c("sqdemSP", "elevation"),
        useGDAL=FALSE, return_SGDF=FALSE)))
    }
    if (run) {
      str(sqdemSP)
      mat <- do.call("cbind", sqdemSP$dataList)
      str(mat)
    }
    if (run) {
      print(system.time(SGDF <- sp::SpatialGridDataFrame(grid=sqdemSP$grid,
        proj4string=sqdemSP$proj4string, data=as.data.frame(sqdemSP$dataList))))
    }
    if (run) {
      summary(SGDF)
    }
    if (run) {
      execGRASS("g.remove", flags="f", name="sqdemSP", type="raster")
      execGRASS("r.mapcalc", expression="basins0 = basins - 1")
      execGRASS("r.stats", flags="c", input="basins0")
    }
    if (run) {
      basins0 <- readRAST("basins0")
      print(table(basins0$basins0))
    }
    if (run) {
      basins0 <- readRAST("basins0", plugin=FALSE)
      print(table(basins0$basins0))
    }
    if (run) {
      execGRASS("g.remove", flags="f", name="basins0", type="raster")
    }
    Sys.setenv("GRASS_VERBOSE"=GV)
    set.ignore.stderrOption(ois)

```

readVECT

Read and write GRASS 7 vector object files

Description

readVECT moves one GRASS 7 vector object file with attribute data through a temporary shapefile to a Spatial*DataFrame object of type determined by the GRASS 7 vector object; writeVECT moves a Spatial*DataFrame object through a temporary shapefile to a GRASS vector object file. vect2neigh returns neighbour pairs with shared boundary length as described by Markus Neteler,

in <https://stat.ethz.ch/pipermail/r-sig-geo/2005-October/000616.html>. `cygwin_clean_temp` can be called to try to clean the GRASS mapset-specific temporary directory under `cygwin`.

Usage

```
readVECT(vname, layer, type=NULL, plugin=NULL,
  remove.duplicates = TRUE, ignore.stderr=NULL,
  with_prj=TRUE, with_c=FALSE, mapset=NULL,
  pointDropZ=FALSE, driver=NULL)
writeVECT(SDF, vname, v.in.ogr.flags=NULL,
  ignore.stderr = NULL, driver=NULL,
  min_area=0.0001, snap=-1)
vInfo(vname, layer, ignore.stderr = NULL)
vColumns(vname, layer, ignore.stderr = NULL)
vDataCount(vname, layer, ignore.stderr = NULL)
vect2neigh(vname, ID=NULL, ignore.stderr = NULL, remove=TRUE, vname2=NULL,
  units="k")
```

Arguments

<code>vname</code>	A GRASS 7 vector file name
<code>layer</code>	a layer name (string); if missing set to default of "1"
<code>type</code>	override type detection when multiple types are non-zero, passed to <code>v.out.ogr</code>
<code>plugin</code>	default NULL if which case it will be set to the value set by <code>set.pluginOption</code> ; NULL for auto-detection, may be set to FALSE to avoid or TRUE if the plugin is known to be available; if the plugin is used, no further arguments other than mapset are respected
<code>remove.duplicates</code>	In line and area vector objects, multiple geometrical features may be associated with a single cat number, leading to duplication of data rows; this argument attempts to combine the geometrical features so that they match a single data row
<code>ignore.stderr</code>	default the value set by <code>set.ignore.stderrOption</code> ; NULL, taking the value set by <code>set.ignore.stderrOption</code> , can be set to TRUE to silence <code>system()</code> output to standard error; does not apply on Windows platforms
<code>with_prj</code>	default TRUE, write ESRI-style PRJ file for transferred data
<code>with_c</code>	default FALSE in GRASS 7; if FALSE, export features with category (labeled) only; if not default, all features are exported, including GRASS "islands" which are probably spurious exterior rings filling holes.
<code>mapset</code>	if plugin is TRUE, the mapset of the file to be imported may be changed from the current mapset by passing a character string
<code>pointDropZ</code>	default FALSE, if TRUE, discard third coordinates for point geometries; third coordinates are always discarded for line and polygon geometries
<code>driver</code>	default NULL, which will lead to the choice of the first driver found in a ordered preferred vector, currently <code>c("SQLite", "ESRI Shapefile")</code> ; a valid OGR writable driver name to define the file format for intermediate files, one of <code>c("GML", "SQLite")</code> , <code>c("ESRI_Shapefile")</code> is preferred as these construct the names of the intermediate files adequately

min_area	default 0.0001); Minimum size of area to be imported (square meters) Smaller areas and islands are ignored. Should be greater than snap^2
snap	default -1); Snapping threshold for boundaries (map units). '-1' for no snap
SDF	A Spatial*DataFrame to be moved to GRASS 7 as a vector object, for SpatialPointsDataFrame, SpatialLinesDataFrame, and SpatialPolygonsDataFrame objects, or an equivalent "sf" object
v.in.ogr.flags	Character vector containing additional optional flags and/or options for v.in.ogr, particularly "o" and "overwrite"
ID	A valid DB column name for unique identifiers (optional)
remove	default TRUE, remove copied vectors created in vect2neigh
vname2	If on a previous run, remove was FALSE, the name of the temporary vector may be given to circumvent its generation
units	default "k"; see GRASS v. to .db manual page for alternatives

Value

readVECT imports a GRASS 7 vector object into an Spatial*DataFrame or equivalent "sf" object with the type determined by the type of the GRASS 7 vector object. readVECT and writeVECT attempt to preserve longer column/field names despite using the "ESRI Shapefile" format for transfer.

vect2neigh returns a data frame object with left and right neighbours and boundary lengths, also given class GRASSneigh and spatial.neighbour (as used in spdep). The incantation to retrieve the neighbours list is sn2listw(vect2neigh())\$neighbours, and to retrieve the boundary lengths: sn2listw(vect2neigh())\$weights. The GRASSneigh object has two other useful attributes: external is a vector giving the length of shared boundary between each polygon and the external area, and total giving each polygon's total boundary length.

Note

Please note that the OGR drivers used may not handle missing data gracefully. From rgdal release 0.5-27, missing values are taken as unset OGR field values. If the OGR driver encodes them in this way, NAs will be moved across the interface correctly from R to GRASS, and from GRASS to R using the OGR GRASS vector plugin. Work is continuing to correct v.out.ogr so that it emits unset fields, which affects users with no OGR GRASS plugin for the present. Thanks to Dylan Beaudette for helping with missing data handling.

Author(s)

Roger S. Bivand, e-mail: <Roger.Bivand@nhh.no.>

Examples

```
use_sp()
run <- FALSE
if (nchar(Sys.getenv("GISRC")) > 0 &&
    read.dcf(Sys.getenv("GISRC"))[1,"LOCATION_NAME"] == "nc_basic_spm_grass7") run <- TRUE
GV <- Sys.getenv("GRASS_VERBOSE")
Sys.setenv("GRASS_VERBOSE"=0)
```

```

# require(rgdal)
ois <- get.ignore.stderrOption()
set.ignore.stderrOption(TRUE)
if (run) {
  execGRASS("v.info", map="schools", layer="1")
}
if (run) {
  print(vInfo("schools"))
  schs <- readVECT("schools", plugin=NULL)
  print(summary(schs))
}
if (run) {
  schs1 <- readVECT("schools", plugin=FALSE)
  print(summary(schs1))
}
if (run) {
  writeVECT(schs, "newsch", v.in.ogr_flags=c("o", "overwrite"))
  execGRASS("v.info", map="newsch", layer="1")
}
if (run) {
  nschs <- readVECT("newsch")
  print(summary(nschs))
}
if (run) {
  print(all.equal(names(nschs), as.character(vColumns("newsch"))[,2])))
}
if (run) {
  names(nschs) <- paste("ABCDEFGHIJKLMNO", names(nschs), sep="")
  writeVECT(nschs, "newsch1", v.in.ogr_flags=c("o", "overwrite"))
}
if (run) {
  print(all.equal(names(nschs), as.character(vColumns("newsch1"))[-1,2])))
}
if (run) {
  nschs1 <- readVECT("newsch1")
  print(all.equal(names(nschs), names(nschs1)[-1]))
}
if (run) {
  print(summary(nschs1))
}
if (run) {
  schs <- readVECT("schools", driver="ESRI Shapefile")
  names(schs) <- paste("ABCDEFGHIJKLMNO", names(schs), sep="")
  writeVECT(schs, "newsch", v.in.ogr_flags=c("o", "overwrite"),
    driver="ESRI Shapefile")
  print(all.equal(names(schs), as.character(vColumns("newsch"))[-1,2])))
}
if (run) {
  nschs <- readVECT("newsch", driver="ESRI Shapefile")
  all.equal(names(schs), names(nschs)[-1])
}
if (run) {
  print(vInfo("roadsmajor"))
}

```

```
}
if (run) {
  roads <- readVECT("roadsmajor")
  print(summary(roads))
}
if (run) {
  cen_neig <- vect2neigh("census")
  str(cen_neig)
}
use_sf()
if (run) {
  print(vInfo("schools"))
  schs <- readVECT("schools", plugin=NULL)
  print(summary(schs))
}
if (run) {
  schs1 <- readVECT("schools", plugin=FALSE)
  print(summary(schs1))
}
if (run) {
  writeVECT(schs, "newsch", v.in.ogr_flags=c("o", "overwrite"))
  execGRASS("v.info", map="newsch", layer="1")
}
if (run) {
  nschs <- readVECT("newsch")
  print(summary(nschs))
}
Sys.setenv("GRASS_VERBOSE"=GV)
set.ignore.stderrOption(ois)
use_sp()
```

Index

*Topic **package**

rgrass7-package, 2

*Topic **spatial**

execGRASS, 3

gmeta, 6

initGRASS, 8

readRAST, 10

readVECT, 13

rgrass7-package, 2

doGRASS (execGRASS), 3

execGRASS, 3

get.defaultFlagsOption (gmeta), 6

get.echoCmdOption (gmeta), 6

get.GIS_LOCK (initGRASS), 8

get.ignore.stderrOption (gmeta), 6

get.legacyExecOption (gmeta), 6

get.pluginOption (gmeta), 6

get.stop_on_no_flags_parasOption
(gmeta), 6

get.suppressEchoCmdInFuncOption
(gmeta), 6

get.useGDALOption (gmeta), 6

get.useInternOption (gmeta), 6

getLocationProj (gmeta), 6

getXMLencoding (execGRASS), 3

gmeta, 6, 10

gmeta2grd (gmeta), 6

initGRASS, 8

parseGRASS (execGRASS), 3

print.gmeta (gmeta), 6

print.GRASS_interface_desc (execGRASS),
3

readRAST, 10

readVECT, 13

remove_GISRC (initGRASS), 8

rgrass7 (rgrass7-package), 2

rgrass7-package, 2

set.defaultFlagsOption (gmeta), 6

set.echoCmdOption (gmeta), 6

set.GIS_LOCK (initGRASS), 8

set.ignore.stderrOption (gmeta), 6

set.legacyExecOption (gmeta), 6

set.pluginOption (gmeta), 6

set.stop_on_no_flags_parasOption
(gmeta), 6

set.suppressEchoCmdInFuncOption
(gmeta), 6

set.useGDALOption (gmeta), 6

set.useInternOption (gmeta), 6

setXMLencoding (execGRASS), 3

system, 5

unlink_.gislock (initGRASS), 8

unset.GIS_LOCK (initGRASS), 8

use_sf (gmeta), 6

use_sp (gmeta), 6

vColumns (readVECT), 13

vDataCount (readVECT), 13

vect2neigh (readVECT), 13

vInfo (readVECT), 13

writeRAST (readRAST), 10

writeVECT (readVECT), 13