

Package ‘rpsychi’

February 15, 2012

Title Statistics for psychiatric research

Version 0.8

Date 2012-01-03

Author Yasuyuki Okumura <yokumura@blue.zero.jp>

Maintainer Yasuyuki Okumura <yokumura@blue.zero.jp>

Depends gtools

Description The rpsychi offers a number of functions for psychiatry, psychiatric nursing, clinical psychology. Functions are primarily for statistical significance testing using published work. For example, you can conduct a factorial analysis of variance (ANOVA), which requires only the mean, standard deviation, and sample size for each cell, rather than the individual data. This package covers fundamental statistical tests such as t-test, chi-square test, analysis of variance, and multiple regression analysis. With some exceptions, you can obtain effect size and its confidence interval. These functions help you to obtain effect size from published work, and then to conduct a priori power analysis or meta-analysis, even if a researcher do not report effect size in a published work.

License GPL (>= 2)

URL <http://blue.zero.jp/yokumura/>

LazyLoad yes

Encoding UTF-8

Repository CRAN

Date/Publication 2012-01-03 08:12:22

R topics documented:

rpsychi-package	2
dep.oneway	4
dep.oneway.second	5
dep.t.test	7
dep.t.test.second	9
formatted	10
groupSummary	11
ind.oneway	12
ind.oneway.second	14
ind.prop	16
ind.prop.second	18
ind.t.test	19
ind.t.test.second	21
ind.twoway	23
ind.twoway.second	24
lower2R	26
md.pattern2	27
multreg	29
multreg.second	31
r2cov	33
samplesize.d	34
samplesize.etasq	35
samplesize.h	36
samplesize.r	37
samplesize.rsq	38
ssd	39
ssd2sd	40
svar	41
zero.r.test	42
zero.r.test.second	43
Index	45

rpsychi-package

*Statistics for psychiatric research***Description**

The rpsychi offers a number of functions for psychiatry, psychiatric nursing, clinical psychology. Functions are primarily for statistical significance testing using published work. For example, you can conduct a factorial analysis of variance (ANOVA), which requires only the mean, standard deviation, and sample size for each cell, rather than the individual data. This package covers fundamental statistical tests such as t-test, chi-square test, analysis of variance, and multiple regression analysis. With some exceptions, you can obtain effect size and its confidence interval. These functions help you to obtain effect size from published work, and then to conduct a priori power analysis or meta-analysis, even if a researcher do not report effect size in a published work.

Details

Package: rpsychi
Type: Package
Version: 0.7
Date: 2011-11-12
License: GPL (version 2 or later)
LazyLoad: yes

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

- Cohen B (2000) Calculating a factorial ANOVA from means and standard deviations. *Understanding Statistics*, 1, 191-203.
- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
- Cohen J (1988). *Statistical power analysis for the behavioral sciences* (2nd ed). Hillsdale, NJ: Erlbaum.
- Cohen J, Cohen P, Aiken LS (2003) *Applied multiple regression/correlation analysis for the behavioral sciences* (3rd ed). Mahwah, NJ: Erlbaum.
- Iwasaki M (2002) *Foundations of incomplete data analysis* (in Japanese) Tokyo: EconomistSha Publishing.
- Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.
- Smithson M (2001) Correct confidence intervals for various regression effect sizes and parameters: The importance of noncentral distributions in computing intervals, 61, 605-632.
- Tabachnick BG, Fidell LS (2007) *Experimental designs using ANOVA*. Belmont, CA: Thomson.
- Toyoda H (1998) *Introduction to structural equation modeling* (in Japanese) Tokyo: Asakura Publishing.

Examples

```
##Kline (2004) Table 6.15
my.cont <- matrix(c(-5,-3,-1,1,3,5,
                  5,-1,-4,-4,-1,5), ncol=6, nrow=2, byrow=TRUE)
dep.oneway.second(m = c(11.77,21.39,27.5,31.02,32.58,34.2),
                 sd = c(7.6,8.44,8.95,9.21,9.49,9.62),
                 n = 137,
```

```
corr=lower2R(c(.77, .59, .50, .48, .46, .81, .72, .69, .68, .89,
               .84, .8, .91, .88, .93)),
contr=my.contr)
```

dep.oneway	<i>A one-way design with dependent samples using individual data: Reporting effect size</i>
------------	---

Description

dep.oneway conducts a one-way design with dependent samples, namely one-way repeated-measures analysis of variance, using individual data.

Usage

```
dep.oneway(formula, data, block,
            contr = NULL, sig.level = 0.05, digits = 3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of one independent variable containing a factor with two or more levels
data	a data frame contains the variables in the formula and block
block	a character string specify the blocking variable
contr	a matrix or vector contains the contrast weights
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a one-way design with dependent samples, namely one-way repeated-measures analysis of variance, using individual data. If you do not specify contr, all possible pairwise contrasts will be calculated.

Value

The returned object of dep.oneway contains the following components:

anova.table	returns a ANOVA table containing sums of squares, degrees of freedom, mean squares, F values, and a p value
omnibus.es	returns a omnibus effect size which is a partial η^2
raw.contrasts	returns raw mean differences, their confidence intervals, and standard errors
standardized.contrasts	returns standardized mean differences for the contrasts (Hedges's g) and their approximate confidence intervals for population standardized mean differences

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Kline RB (2004) Beyond significance testing: Reforming data analysis methods in behavioral research. Washington: American Psychological Association.

See Also

[dep.oneway.second](#)

Examples

```
##Kline (2004) Table 6.3
dat <- data.frame(y = c(9,12,13,15,16,
                      8,12,11,10,14,
                      10,11,13,11,15),
                 x = rep(factor(c("a","b","c")), each=5),
                 subj = rep(paste("s", 1:5, sep=""), times=3)
                 )
dep.oneway(formula = y~x, data=dat, block="subj")

##contrast 1: a - c, contrast 2 : 1/2(a + c) - b
my.cont <- matrix(c(1,0,-1,1/2,-1,1/2), ncol=3, nrow=2, byrow=TRUE)
dep.oneway(formula = y~x, data=dat, block="subj", contr=my.cont)
```

dep.oneway.second	<i>A one-way design with dependent samples using published work: Reporting effect size</i>
-------------------	--

Description

dep.oneway.second conducts a one-way design with dependent samples, namely one-way repeated-measures analysis of variance, using published work.

Usage

```
dep.oneway.second(m, sd, n, corr,
                 unbiased = TRUE, contr = NULL, sig.level = 0.05, digits = 3)
```

Arguments

<code>m</code>	a numeric vector contains the means (<code>length(m) >= 2</code>)
<code>sd</code>	a numeric vector contains the sample/unbiased standard deviations (<code>length(sd) >= 2</code>)
<code>n</code>	a numeric contains the sample size (<code>length(n) >= 2</code>)
<code>corr</code>	a matrix or data frame contains the correlation matrix
<code>unbiased</code>	<code>sd</code> contains unbiased standard deviations (<code>unbiased = TRUE</code> , default) or sample standard deviations (<code>unbiased = FALSE</code>)
<code>contr</code>	a matrix or vector contains the contrast weights
<code>sig.level</code>	a numeric contains the significance level (default 0.05)
<code>digits</code>	the specified number of decimal places (default 3)

Details

This function conducts a one-way design with dependent samples, namely one-way repeated-measures analysis of variance, using published work. If you do not specify `contr`, all possible pairwise contrasts will be calculated.

Value

The returned object of `dep.oneway.second` contains the following components:

<code>anova.table</code>	returns a ANOVA table containing sums of squares, degrees of freedom, mean squares, F values, and a p value
<code>omnibus.es</code>	returns a omnibus effect size which is a partial η^2
<code>raw.contrasts</code>	returns raw mean differences, their confidence intervals, and standard errors
<code>standardized.contrasts</code>	returns standardized mean differences for the contrasts (Hedges's g) and their approximate confidence intervals for population standardized mean differences

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Kline RB (2004) Beyond significance testing: Reforming data analysis methods in behavioral research. Washington: American Psychological Association.

See Also

[dep.oneway, lower2R](#)

Examples

```
##Kline (2004) Table 6.3
dat <- data.frame(y = c(9,12,13,15,16,
                      8,12,11,10,14,
                      10,11,13,11,15),
                 x = rep(factor(c("a","b","c")), each=5),
                 subj = rep(paste("s", 1:5, sep=""), times=3)
                 )
dep.oneway(formula = y~x, data=dat, block="subj")

datwide <- reshape(dat, direction="wide", idvar="subj", timevar="x")
tmp <- datwide[,-1]
dep.oneway.second(m = apply(tmp, 2, mean), apply(tmp, 2, sd), n = nrow(tmp), corr=cor(tmp))
```

```
##Kline (2004) Table 6.15
my.contr <- matrix(c(-5,-3,-1,1,3,5,
                    5,-1,-4,-4,-1,5), ncol=6, nrow=2, byrow=TRUE)
dep.oneway.second(m = c(11.77,21.39,27.5,31.02,32.58,34.2),
                 sd = c(7.6,8.44,8.95,9.21,9.49,9.62),
                 n = 137,
                 corr=lower2R(c(.77,.59,.50,.48,.46,.81,.72,.69,.68,.89,
                                .84,.8,.91,.88,.93)),
                 contr=my.contr)
```

dep.t.test	<i>A t-test with dependent samples using individual data: Reporting effect size</i>
------------	---

Description

dep.t.test conducts a t-test with dependent samples using individual data.

Usage

```
dep.t.test(formula, data, block,
           sig.level=.05, digits=3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of one independent variable containing a factor with two levels
data	a data frame contains the variables in the fomrmula
block	a character string specify the blocking variable
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a t-test with dependent samples using individual data.

Value

The returned object of `dep.t.test.second` contains the following components:

`samp.stat` returns the means, standard deviations, sample size, and correlation
`raw.difference` returns a raw mean difference, its' confidence interval, and standard error
`standardized.difference`
returns a standardized mean difference (Hedges's g) and its' approximate confidence interval for a population standardized mean difference

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Kline RB (2004) Beyond significance testing: Reforming data analysis methods in behavioral research. Washington: American Psychological Association.

See Also

[dep.t.test.second](#)

Examples

```
##Kline (2004) Table 4.4
dat <- data.frame(y = c(9,12,13,15,16,8,12,11,10,14),
                 x = rep(factor(c("a","b")), each=5),
                 subj = rep(paste("s", 1:5, sep=""), times=2)
                 )
dep.t.test(y~x, block="subj", data=dat)
```

dep.t.test.second *A t-test with dependent samples using published work: Reporting effect size*

Description

dep.t.test.second conducts a t-test with dependent samples using published work.

Usage

```
dep.t.test.second(m, sd, n, corr,
                 unbiased = TRUE, sig.level = 0.05, digits = 3)
```

Arguments

m	a numeric vector contains the means (length(m) = 2)
sd	a numeric vector contains the sample/unbiased standard deviations (length(sd) = 2)
n	a numeric contains the sample size (length(n) = 2)
corr	a numeric contains the correlation
unbiased	sd contains unbiased standard deviations (unbiased = TRUE, default) or sample standard deviations (unbiased = FALSE)
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a t-test with dependent samples using published work.

Value

The returned object of dep.t.test.second contains the following components:

samp.stat	returns the means, standard deviations, sample size, and correlation
raw.difference	returns a raw mean difference, its' confidence interval, and standard error
standardized.difference	returns a standardized mean difference (Hedges's <i>g</i>) and its' approximate confidence interval for a population standardized mean difference

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Kline RB (2004) Beyond significance testing: Reforming data analysis methods in behavioral research. Washington: American Psychological Association.

See Also

[dep.t.test](#)

Examples

```
##Kline (2004) Table 4.4
dat <- data.frame(y = c(9,12,13,15,16,8,12,11,10,14),
  x = rep(factor(c("a","b")), each=5),
  subj = rep(paste("s", 1:5, sep=""), times=2)
)
datwide <- reshape(dat, direction="wide", idvar="subj", timevar="x")

dep.t.test.second(m = tapply(dat$y, dat$x, mean),
  sd = tapply(dat$y, dat$x, sd),
  n = nlevels(dat$subj),
  corr = cor(datwide[,2:3])[1,2]
)

dep.t.test.second(m = tapply(dat$y, dat$x, mean),
  sd = tapply(dat$y, dat$x, sd),
  n = 30,
  corr = cor(datwide[,2:3])[1,2]
)
```

formatted

Convert a numeric vector into a character vector with the specified number of decimal place

Description

formatted convert a numeric vector into a character vector with the specified number of decimal place.

Usage

```
formatted(x, digits = 2)
```

Arguments

x a numeric vector
 digits the specified number of decimal places (default 2)

Value

Return a character vector.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

Examples

```
data(infert)
x <- svar(infert$age)   #sample variance
formatted(x)
formatted(x, digits=4)
```

groupSummary	<i>Compute summary statistics by group</i>
--------------	--

Description

groupSummary summarize continuous variables by providing means and sample standard deviations and categorical variables by giving numbers and percentages for each group.

Usage

```
groupSummary(data, group = NULL, digits = 3)
```

Arguments

data	a data frame contains the variables
group	a character string specify the grouping variable (default NULL)
digits	the specified number of decimal places (default 3)

Details

This function summarize continuous variables by providing means and sample standard deviations and categorical variables by giving numbers and percentages for each group. Missing values (NA) will be stripped before the computation proceeds. If you do not specify group, this function will summarize the variables for total group only.

Value

Return a data frame containing (1) means and/or numbers, (2) sample standard deviations and/or percentages, (3) numbers of available data for total and each group.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

See Also

[ssd](#)

Examples

```
data(infert)
infert$case <- factor(infert$case, labels=c("control", "case"))
infert$induced <- factor(infert$induced, labels=c("0", "1", "2 or more"))
infert$spontaneous <- factor(infert$spontaneous, labels=c("0", "1", "2 or more"))

#continuous and categorical variables
groupSummary(infert, group="case")

#continuous variables only
groupSummary(infert[, c(2,3,7,8, 5)], group="case")

#categorical variables only
groupSummary(infert[, c(1,4, 6, 5)], group="case")

#total sample
groupSummary(infert[, c(1,4, 6, 5)])
```

ind.oneway

*A one-way design with independent samples using individual data:
Reporting effect size*

Description

ind.oneway conducts a one-way design with independent samples, namely one-way randomized-group analysis of variance, using individual data.

Usage

```
ind.oneway(formula, data,
            contr = NULL, sig.level = 0.05, digits = 3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of one independent variable containing a factor with two or more levels
data	a data frame contains the variables in the formula
contr	a matrix or vector contains the contrast weights
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a one-way design with independent samples, namely one-way randomized-group analysis of variance, using individual data. If you do not specify `contr`, all possible pairwise contrasts will be calculated. Statistical power is calculated using the following specifications:

- (a) small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by `formula` and `data`
- (c) significance level specified by `sig.level`

Value

The returned object of `ind.oneway` contains the following components:

<code>anova.table</code>	returns a ANOVA table containing sums of squares, degrees of freedom, mean squares, F values
<code>omnibus.es</code>	returns a omnibus effect size which is a η^2 , and its' confidence interval
<code>raw.contrasts</code>	returns raw mean differences, their confidence intervals, and standard errors
<code>standardized.contrasts</code>	returns standardized mean differences for the contrasts (Hedges's g), their approximate confidence intervals for population standardized mean differences, and standard errors
<code>power</code>	returns statistical power for detecting small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
- Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.

See Also

[ind.oneway.second, samplesize.etasq](#)

Examples

```
##Kline (2004) Table 6.3
dat <- data.frame(y = c(9,12,13,15,16,
                      8,12,11,10,14,
                      10,11,13,11,15),
                 x = rep(factor(c("a", "b", "c")), each=5)
                 )
ind.oneway(formula = y~x, data=dat, sig.level=.05, digits=3)

##contrast 1: a - c, contrast 2: 1/2(a + c) - b
my.cont <- matrix(c(1,0,-1,1/2,-1,1/2), ncol=3, nrow=2, byrow=TRUE)
ind.oneway(formula = y~x, data=dat, contr=my.cont, sig.level=.05, digits=3)
```

ind.oneway.second	<i>A one-way design with independent samples using published work: Reporting effect size</i>
-------------------	--

Description

ind.oneway.second conducts a one-way design with independent samples, namely one-way randomized-group analysis of variance, using published work.

Usage

```
ind.oneway.second(m, sd, n,
                 unbiased = TRUE, contr = NULL, sig.level = 0.05, digits = 3)
```

Arguments

m	a numeric vector contains the means (length(m) >= 2)
sd	a numeric vector contains the sample/unbiased standard deviations (length(sd) >= 2)
n	a numeric contains the sample size (length(n) >= 2)
unbiased	sd contains unbiased standard deviations (unbiased = TRUE, default) or sample standard deviations (unbiased = FALSE)
contr	a matrix or vector contains the contrast weights
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a one-way design with independent samples, namely one-way randomized-group analysis of variance, using published work. If you do not specify `contr`, all possible pairwise contrasts will be calculated. Statistical power is calculated using the following specifications:

- (a) small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by `n`
- (c) significance level specified by `sig.level`

Value

The returned object of `ind.oneway.second` contains the following components:

<code>anova.table</code>	returns a ANOVA table containing sums of squares, degrees of freedom, mean squares, F values
<code>omnibus.es</code>	returns a omnibus effect size which is a η^2 , and its' confidence interval
<code>raw.contrasts</code>	returns raw mean differences, their confidence intervals, and standard errors
<code>standardized.contrasts</code>	returns standardized mean differences for the contrasts (Hedges's g), their approximate confidence intervals for population standardized mean differences, and standard errors
<code>power</code>	returns statistical power for detecting small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

- Cohen B (2000) Calculating a factorial ANOVA from means and standard deviations. *Understanding Statistics*, 1, 191-203.
- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
- Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.

See Also

[ind.oneway](#), [samplesize.etasq](#)

Examples

```
##Kline (2004) Table 6.3
dat <- data.frame(y = c(9,12,13,15,16,
                      8,12,11,10,14,
                      10,11,13,11,15),
                 x = rep(factor(c("a","b","c")), each=5)
                 )

##contrast 1: a - c, contrast 2: 1/2(a + c) - b
my.cont <- matrix(c(1,0,-1,1/2,-1,1/2), ncol=3, nrow=2, byrow=TRUE)

ind.oneway.second(m = tapply(dat$y, dat$x, mean),
                 sd = tapply(dat$y, dat$x, sd),
                 n = tapply(dat$y, dat$x, length))

ind.oneway.second(m = tapply(dat$y, dat$x, mean),
                 sd = tapply(dat$y, dat$x, sd),
                 n = tapply(dat$y, dat$x, length),
                 contr = my.cont)
```

ind.prop	<i>A Z test for the equality of two proportions using individual data: Reporting effect size</i>
----------	--

Description

ind.prop conducts a Z test for the equality of two proportions using individual data.

Usage

```
ind.prop(formula, data, sig.level=.05, digits=3, lev.count=2, ref.ind=1)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a factor with two levels, and the right-hand-side of one independent variable containing a factor with two levels
data	a data frame contains the variables in the fomrmula
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)
lev.count	a numeric contains the level to be counted (default 2)
ref.ind	the reference for the independent variable (default 1)

Details

This function conducts a Z test for the equality of two proportions using individual data. Statistical power is calculated using the following specifications:

- (a) small ($h = 0.20$), medium ($h = 0.50$), and large ($h = 0.80$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by `n`
- (c) significance level specified by `sig.level`

Value

The returned object of `ind.prop` contains the following components:

<code>samp.stat</code>	returns the proportions, sample sizes, and a effect size index (Cohen's h)
<code>risk.difference</code>	returns a risk difference, its' confidence interval, and standard error
<code>risk.ratio</code>	returns a risk ratio, its' confidence interval, and a standard error of a log-transformed risk ratio
<code>odds.ratio</code>	returns a odds ratio, its' confidence interval, and a standard error of a log-transformed odds ratio
<code>power</code>	returns statistical power for detecting small ($h = 0.20$), medium ($h = 0.50$), and large ($h = 0.80$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
- Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.

See Also

[ind.prop.second](#), [samplesize.h](#)

Examples

```
##Kline (2004) Chapter 5
x1 <- c("relapsed", "not relapsed")
y1 <- c("control", "treatment")

dat <- data.frame(y =
```

```

factor(c(rep(x1, c(60, 40)), rep(x1, c(40, 60))), levels=x1),
x = factor(rep(y1, each=100), levels=y1)
)
tab <- xtabs(~x+y, data=dat)
tab
ind.prop(y~x, data=dat, lev.count=2, ref.ind=1) #Odds for not relapse is higher in treatment than control condition.
ind.prop(y~x, data=dat, lev.count=1, ref.ind=1) #Odds for relapse is lower in treatment than control condition.
ind.prop(y~x, data=dat, lev.count=2, ref.ind=2) #Odds for not relapse is lower in control than treatment condition.
ind.prop(y~x, data=dat, lev.count=1, ref.ind=2) #Odds for relapse is higher in control than treatment condition.

```

ind.prop.second *A Z test for the equality of two proportions using published work*

Description

ind.prop.second conducts a Z test for the equality of two proportions using published work.

Usage

```
ind.prop.second(x, n, sig.level = 0.05, digits = 3, ref.ind=1)
```

Arguments

x	a numeric vector (length(x) = 2) contains the counts of successes
n	a numeric vector (length(n) = 2) contains the sample sizes
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)
ref.ind	the reference for the independent variable (default 1)

Details

This function conducts a Z test for the equality of two proportions using published work. Statistical power is calculated using the following specifications:

- (a) small ($h = 0.20$), medium ($h = 0.50$), and large ($h = 0.80$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by n
- (c) significance level specified by sig.level

Value

The returned object of ind.prop.second contains the following components:

samp.stat	returns the proportions, sample sizes, and a effect size index (Cohen's h)
risk.difference	returns a risk difference, its' confidence interval, and standard error

risk.ratio	returns a risk ratio, its' confidence interval, and a standard error of a log-transformed risk ratio
odds.ratio	returns a odds ratio, its' confidence interval, and a standard error of a log-transformed odds ratio
power	returns statistical power for detecting small ($h = 0.20$), medium ($h = 0.50$), and large ($h = 0.80$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
 Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.

See Also

[ind.prop](#), [samplesize.h](#)

Examples

```
##Kline (2004) Chapter 5
x1 <- c("relapsed", "not relapsed")
y1 <- c("control", "treatment")

dat <- data.frame(y =
  factor(c(rep(x1, c(60, 40)), rep(x1, c(40, 60))), levels=x1),
  x = factor(rep(y1, each=100), levels=y1)
)
tab <- xtabs(~x+y, data=dat)
tab
ind.prop.second(x=tab[,1], n = rowSums(tab))          #Risk for relapse is lower in treatment than control condition
ind.prop.second(x=tab[,1], n = rowSums(tab), ref.ind=2) #Risk for relapse is higher in control than treatment condition
```

ind.t.test	<i>A t-test with independent samples using individual data: Reporting effect size</i>
------------	---

Description

ind.t.test conducts a t-test with independent samples using individual data.

Usage

```
ind.t.test(formula, data, correct=TRUE,
           sig.level = 0.05, digits = 3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of one independent variable containing a factor with two levels
data	a data frame contains the variables in the formula
correct	a logical indicating whether to compute an unbiased standardized mean difference (<i>delta</i>) or not (<code>correct = TRUE</code>)
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a t-test with independent samples using individual data. Statistical power is calculated using the following specifications:

- (a) small ($d = 0.20$), medium ($d = 0.50$), and large ($d = 0.80$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by `formula` and `data`
- (c) significance level specified by `sig.level`

Value

The returned object of `ind.t.test` contains the following components:

<code>samp.stat</code>	returns the means, standard deviations, and sample sizes
<code>raw.difference</code>	returns a raw mean difference, its' confidence interval, and standard error
<code>standardized.difference</code>	returns a standardized mean difference (Hedges's g), its' approximate confidence interval for population standardized mean difference, and standard error
<code>power</code>	returns statistical power for detecting small ($d = 0.20$), medium ($d = 0.50$), and large ($d = 0.80$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.

Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.

See Also

[ind.t.test.second, samplesize.d](#)

Examples

```
##Kline (2004) Table 4.4
dat <- data.frame(y = c(9,12,13,15,16,8,12,11,10,14),
                 x = rep(factor(c("a","b")), each=5)
                 )
ind.t.test(y~x, data=dat, correct=FALSE)
```

ind.t.test.second	<i>A t-test with independent samples using published work: Reporting effect size</i>
-------------------	--

Description

ind.t.test.second conducts a t-test with independent samples using published work.

Usage

```
ind.t.test.second(m, sd, n,
                 unbiased = TRUE, correct=TRUE, sig.level = 0.05, digits = 3)
```

Arguments

m	a numeric vector contains the means (length(m) = 2)
sd	a numeric vector contains the sample/unbiased standard deviations (length(sd) = 2)
n	a numeric contains the sample size (length(n) = 2)
unbiased	sd contains unbiased standard deviations (unbiased = TRUE, default) or sample standard deviations (unbiased = FALSE)
correct	a logical indicating whether to compute an unbiased standardized mean difference (<i>delta</i>) or not (correct = TRUE)
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a t-test with independent samples using published work. Statistical power is calculated using the following specifications:

- (a) small ($d = 0.20$), medium ($d = 0.50$), and large ($d = 0.80$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by `n`
- (c) significance level specified by `sig.level`

Value

The returned object of `ind.t.test.second` contains the following components:

<code>samp.stat</code>	returns the means, standard deviations, and sample sizes
<code>raw.difference</code>	returns a raw mean difference, its' confidence interval, and standard error
<code>standardized.difference</code>	returns a standardized mean difference (Hedges's g), its' approximate confidence interval for population standardized mean difference, and standard error
<code>power</code>	returns statistical power for detecting small ($d = 0.20$), medium ($d = 0.50$), and large ($d = 0.80$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
- Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.

See Also

[ind.t.test](#), [samplesize.d](#)

Examples

```
##Kline (2004) Table 4.4
dat <- data.frame(y = c(9,12,13,15,16,8,12,11,10,14),
                 x = rep(factor(c("a","b")), each=5)
                 )
ind.t.test.second(m = tapply(dat$y, dat$x, mean),
                 sd = tapply(dat$y, dat$x, sd),
                 n = tapply(dat$y, dat$x, length), correct=FALSE
                 )
```

```
ind.t.test.second(m = tapply(dat$y, dat$x, mean),
                 sd = tapply(dat$y, dat$x, sd),
                 n = tapply(dat$y, dat$x, length), correct=TRUE
                 ) #approximate unbiased estimator of delta
```

ind.twoway	<i>A two-way design with independent samples using individual data</i>
------------	--

Description

ind.twoway conducts a two-way design with independent samples, namely two-way randomized-group analysis of variance, using individual data.

Usage

```
ind.twoway(formula, data, sig.level=.05, digits=3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of two independent variables containing a factor with two or more levels
data	a data frame contains the variables in the formula
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a two-way design with independent samples, namely two-way randomized-group analysis of variance, using individual data. The main effect of the first independent variable will be shown in "(row)" section, and the main effect of the second one will be shown in "(col)" section. Always the interaction effect of the two independent variables will be calculated. Statistical power is calculated using the following specifications:

- (a) small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by formula and data
- (c) significance level specified by sig.level

Value

The returned object of ind.oneway contains the following components:

anova.table	returns a ANOVA table containing sums of squares, degrees of freedom, mean squares, F values
omnibus.es	returns a omnibus effect sizes which is a partial η^2 , and its' confidence interval for each main and interaction effect
power	returns statistical power for detecting small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Cohen B (2000) Calculating a factorial ANOVA from means and standard deviations. *Understanding Statistics*, 1, 191-203.

Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.

Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.

See Also

[ind.twoway.second](#)

Examples

```
##Kline (2004) Table 7.5
dat <- data.frame(
  y = c(2,3,4,1,3,1,3,4,5,5,6,6,6,7),
  A = factor(c(rep("A1",5), rep("A2", 9))),
  B = factor(c(rep("B1",3), rep("B2",2), rep("B1",2), rep("B2",7)))
)

ind.twoway(y~A*B, data=dat)
```

ind.twoway.second

A two-way design with independent samples using published work

Description

ind.twoway.second conducts a two-way design with independent samples, namely two-way randomized-group analysis of variance, using published work.

Usage

```
ind.twoway.second(m, sd, n,
  unbiased = TRUE, sig.level = 0.05, digits = 3)
```

Arguments

<code>m</code>	a matrix contains the means
<code>sd</code>	a matrix contains the sample/unbiased standard deviations
<code>n</code>	a matrix contains the sample size
<code>unbiased</code>	<code>sd</code> contains unbiased standard deviations (<code>unbiased = TRUE</code> , default) or sample standard deviations (<code>unbiased = FALSE</code>)
<code>sig.level</code>	a numeric contains the significance level (default 0.05)
<code>digits</code>	the specified number of decimal places (default 3)

Details

This function conducts a two-way design with independent samples, namely two-way randomized-group analysis of variance, using published work. Statistical power is calculated using the following specifications:

- (a) small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by `n`
- (c) significance level specified by `sig.level`

Value

The returned object of `ind.oneway.second` contains the following components:

<code>anova.table</code>	returns a ANOVA table containing sums of squares, degrees of freedom, mean squares, F values
<code>omnibus.es</code>	returns a omnibus effect sizes which is a partial η^2 , and its' confidence interval for each main and interaction effect
<code>power</code>	returns statistical power for detecting small ($\eta^2 = 0.01$), medium ($\eta^2 = 0.06$), and large ($\eta^2 = 0.14$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

- Cohen B (2000) Calculating a factorial ANOVA from means and standard deviations. *Understanding Statistics*, 1, 191-203.
- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
- Kline RB (2004) *Beyond significance testing: Reforming data analysis methods in behavioral research*. Washington: American Psychological Association.
- Tabachnick BG, Fidell LS (2007) *Experimental designs using ANOVA*. Belmont, CA: Thomson.

See Also[ind.twoway](#)**Examples**

```
##Cohen (2000) Table 1
m.mat <- matrix(c(37.13, 39.31, 39.22, 32.71), ncol=2) #2 * 2
sd.mat <- matrix(c(13.82, 9.42, 9.43, 9.62), ncol=2)
n.mat <- matrix(c(9, 13, 8, 14), ncol=2)

ind.twoway.second(m = m.mat, sd = sd.mat, n = n.mat)

##Tabachnick and Fidell (2007)
#5.7 Complete example of two-way randomized-groups ANOVA (p.221-236)
m.mat <- matrix(c(837.9, 573.6, 354.9, 699.0, 112.0,
  852.2, 781.6, 683.3, 1193.9, 130.0), ncol=2) #5 * 2
sd.mat <- matrix(c(189.87449, 61.31195, 147.93351, 128.51891, 43.36922,
  227.17042, 104.81221, 116.25934, 198.36692, 37.64158), ncol=2) #5 * 2
n.mat <- matrix(rep(10, 10), ncol=2)

ind.twoway.second(m = m.mat, sd = sd.mat, n = n.mat)

##Kline (2004) Table 7.5
dat <- data.frame(
  y = c(2,3,4,1,3,1,3,4,5,5,6,6,6,7),
  A = factor(c(rep("A1",5), rep("A2", 9))),
  B = factor(c(rep("B1",3), rep("B2",2), rep("B1",2), rep("B2",7)))
)
ind.twoway.second(m = tapply(dat$y, list(dat$A,dat$B), mean),
  sd = tapply(dat$y, list(dat$A,dat$B), sd),
  n = tapply(dat$y, list(dat$A,dat$B), length)
)
```

lower2R

*Convert a vector containing correlations into a correlation matrix***Description**

lower2R converts a vector containing correlations into a correlation matrix.

Usage

```
lower2R(x, varname=NULL)
```

Arguments

x a numeric vector contains the correlations
varname a character vector contains the row and column names

Details

This function converts a vector containing correlations into a correlation matrix. `x` contains the elements that consist of the lower triangle of the correlation matrix. The length of `varname` should be equal to the number of rows and columns in the correlation matrix.

Value

Return a matrix containing the correlation matrix.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Kline RB (2004) Beyond significance testing: Reforming data analysis methods in behavioral research. Washington: American Psychological Association.

See Also

[svar](#), [ssd](#), [svar](#), [ssd2sd](#), [r2cov](#)

Examples

```
lower2R(c(1:15))

##Kline (2004) Table 6.15
lower2R(c(.77, .59, .50, .48, .46, .81, .72, .69, .68, .89,
          .84, .8, .91, .88, .93))

lower2R(c(.77, .59, .50, .48, .46, .81, .72, .69, .68, .89,
          .84, .8, .91, .88, .93),
        varname=paste("trial", 1:6, sep=""))
```

md.pattern2

Display missing-data patterns

Description

md.pattern2 displays missing-data patterns

Usage

```
md.pattern2(x)
```

Arguments

x a data frame

Details

This function displays missing-data patterns. `md.pattern` in `library(mice)` is extended to sort variables.

Value

Return a matrix with `ncol(x) + 1` columns, in which each row corresponds to a missing data pattern (1 = observed, 0 = missing). Rows and columns are sorted in increasing amounts of the sample sizes. The last column and row contain row and column counts, respectively. The row name contains the sample sizes in the specific missing data patterns.

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Iwasaki M (2002) Foundations of incomplete data analysis (in Japanese) Tokyo: EconomistSha Publishing.

Examples

```
##Iwasaki (2002)
dat <- data.frame(matrix(c(
  71 , 68, 72, 72, 90, 72, 77, 76, 84, 77,
  1850,2000,2100,1700, NA,2200,2150, NA, NA, NA,
  136 , 139, 147, 142, NA, 150, 156, NA, 152, NA,
  34 , 45 , 50, 38, NA, 41, 43, 52, 57, 48
), ncol=4))
md.pattern2(dat)

#sample sizes in the specific pattern
#^
#^          numbers of missing data in each pattern
#|          ^
#|          |
#  X2 X3 X4 X1 NA
#6   1  1  1  1  0
#2   0  0  1  1  2
#1   0  0  0  1  3
#1   0  1  1  1  1
#Sum  4  3  1  0  8 --> numbers of missing data in each variable
```

 multreg

A multiple regression analysis using individual data

Description

multreg conducts a multiple regression analysis using individual data.

Usage

```
multreg(formula, data, sig.level = 0.05, digits = 3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of several independent variables containing a numeric variable
data	a data frame contains the variables in the fomrmula
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a multiple regression analysis using individual data. The dependent variable and independent variables should be a numeric vector. In this function, you cannot specify any interaction nor any curvilinear effect. Statistical power is calculated using the following specifications:

- (a) small ($R^2 = 0.02$), medium ($R^2 = 0.13$), and large ($R^2 = 0.26$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by data
- (c) significance level specified by sig.level
- (d) numbers of independent variable specified by formula

Value

samp.stat	returns the means and unbiased standard deviations
corr.partial.corr	returns a product-moment correlation matrix (lower triangle) and a partial correlation matrix given all remaining variables (upper triangle)
corr.confidence	returns lower and upper confidence limits (lower and upper triangles, respectively)
omnibus.es	returns a coefficient of determination and its' confidence interval

`raw.estimates` returns partial regression coefficients, their confidence intervals, and standard errors

`standardized.estimates` returns standardized partial regression coefficients, their confidence intervals, and standard errors

`power` returns statistical power for detecting small ($R^2 = 0.02$), medium ($R^2 = 0.13$), and large ($R^2 = 0.26$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.

Cohen J, Cohen P, Aiken LS (2003) *Applied multiple regression/correlation analysis for the behavioral sciences* (3rd ed). Mahwah, NJ: Erlbaum.

Smithson M (2001) Correct confidence intervals for various regression effect sizes and parameters: The importance of noncentral distributions in computing intervals, 61, 605-632.

See Also

[multreg.second](#), [samplesize.rsq](#)

Examples

```
##Cohen (2003) Table 3.5.1
dat <- data.frame(
  salary = c(51876, 54511, 53425, 61863, 52926, 47034, 66432, 61100, 41934,
    47454, 49832, 47047, 39115, 59677, 61458, 54528, 60327, 56600,
    52542, 50455, 51647, 62895, 53740, 75822, 56596, 55682, 62091,
    42162, 52646, 74199, 50729, 70011, 37939, 39652, 68987, 55579,
    54671, 57704, 44045, 51122, 47082, 60009, 58632, 38340, 71219,
    53712, 54782, 83503, 47212, 52840, 53650, 50931, 66784, 49751,
    74343, 57710, 52676, 41195, 45662, 47606, 44301, 58582),
  pubs = c(18, 3, 2, 17, 11, 6, 38, 48, 9, 22, 30, 21,
    10, 27, 37, 8, 13, 6, 12, 29, 29, 7, 6, 69, 11, 9,
    20, 41, 3, 27, 14, 23, 1, 7, 19, 11, 31, 9, 12, 32,
    26, 12, 9, 6, 39, 16, 12, 50, 18, 16, 5, 20, 50,
    6, 19, 11, 13, 3, 8, 11, 25, 4),
  cites = c(50, 26, 50, 34, 41, 37, 48, 56, 19, 29,
    28, 31, 25, 40, 61, 32, 36, 69, 47, 29, 35,
    35, 18, 90, 60, 30, 27, 35, 14, 56, 50, 25,
    35, 1, 69, 69, 27, 50, 32, 33, 45, 54, 47, 29,
    69, 47, 43, 55, 33, 28, 42, 24, 31, 27,
    83, 49, 14, 36, 34, 70, 27, 28)
```

```
)
multreg(salary~ pubs + cits, data=dat)
```

multreg.second

A multiple regression analysis using published work

Description

multreg.second conducts a multiple regression analysis using published work.

Usage

```
multreg.second(formula, corr, n,
               m = NULL, sd = NULL, sig.level = 0.05, digits = 3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of several independent variables containing a numeric variable
corr	a matrix or data frame contains the correlation matrix
n	a numeric contains the sample size
m	a numeric vector contains the means (default NULL)
sd	a numeric vector contains the sample/unbiased standard deviations (default NULL)
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a multiple regression analysis using published work. The dependent variable and independent variables should be a numeric vector. In this function, you cannot specify any interaction nor any curvilinear effect. If you do not specify `m` and `sd`, `raw.estimates` will not be obtained. Statistical power is calculated using the following specifications:

- (a) small ($R^2 = 0.02$), medium ($R^2 = 0.13$), and large ($R^2 = 0.26$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by data
- (c) significance level specified by `sig.level`
- (d) numbers of independent variable specified by `formula`

Value

corr.partial.corr	returns a product-moment correlation matrix (lower triangle) and a partial correlation matrix given all remaining variables (upper triangle)
corr.confidence	returns lower and upper confidence limits (lower and upper triangles, respectively)
omnibus.es	returns a coefficient of determination and its' confidence interval
raw.estimated	returns partial regression coefficients, their confidence intervals, and standard errors
standardized.estimated	returns standardized partial regression coefficients, their confidence intervals, and standard errors
power	returns statistical power for detecting small ($R^2 = 0.02$), medium ($R^2 = 0.13$), and large ($R^2 = 0.26$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

- Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.
- Cohen J, Cohen P, Aiken LS (2003) *Applied multiple regression/correlation analysis for the behavioral sciences* (3rd ed). Mahwah, NJ: Erlbaum.
- Smithson M (2001) Correct confidence intervals for various regression effect sizes and parameters: The importance of noncentral distributions in computing intervals, 61, 605-632.

See Also

[multreg](#), [samplesize.rsq](#)

Examples

```
##Cohen (2003) Table 3.5.1
dat <- data.frame(
  salary = c(51876, 54511, 53425, 61863, 52926, 47034, 66432, 61100, 41934,
    47454, 49832, 47047, 39115, 59677, 61458, 54528, 60327, 56600,
    52542, 50455, 51647, 62895, 53740, 75822, 56596, 55682, 62091,
    42162, 52646, 74199, 50729, 70011, 37939, 39652, 68987, 55579,
    54671, 57704, 44045, 51122, 47082, 60009, 58632, 38340, 71219,
    53712, 54782, 83503, 47212, 52840, 53650, 50931, 66784, 49751,
    74343, 57710, 52676, 41195, 45662, 47606, 44301, 58582),
  pubs = c(18, 3, 2, 17, 11, 6, 38, 48, 9, 22, 30, 21,
```

```

10, 27, 37, 8, 13, 6, 12, 29, 29, 7, 6, 69, 11, 9,
20, 41, 3, 27, 14, 23, 1, 7, 19, 11, 31, 9, 12, 32,
26, 12, 9, 6, 39, 16, 12, 50, 18, 16, 5, 20, 50,
6, 19, 11, 13, 3, 8, 11, 25, 4),
cits = c(50, 26, 50, 34, 41, 37, 48, 56, 19, 29,
28, 31, 25, 40, 61, 32, 36, 69, 47, 29, 35,
35, 18, 90, 60, 30, 27, 35, 14, 56, 50, 25,
35, 1, 69, 69, 27, 50, 32, 33, 45, 54, 47, 29,
69, 47, 43, 55, 33, 28, 42, 24, 31, 27,
83, 49, 14, 36, 34, 70, 27, 28) )

multreg.second(salary~ pubs + cits, corr=cor(dat), n= nrow(dat))
multreg.second(salary~ pubs + cits, corr=cor(dat), n= nrow(dat),
m = apply(dat, 2, mean), sd=apply(dat, 2, sd))

```

r2cov

Convert correlation matrix into covariance matrix

Description

r2cov converts correlation matrix and sample/unbiased standard deviation into sample/unbiased covariance matrix.

Usage

```
r2cov(sd, R)
```

Arguments

sd	a numeric vector contains the sample/unbiased standard deviations
R	a matrix or data frame contains the correlation matrix

Details

This function converts correlation matrix and sample/unbiased standard deviation into sample/unbiased covariance matrix using the following equation: $S = D^{1/2}RD^{1/2}$, where S is a sample/unbiased covariance matrix, R is a correlation matrix, and $D^{1/2}$ is a square matrix with sd on the main diagonal and 0's elsewhere. The length of sd should be equal to the number of rows and columns in R.

Value

Return a matrix containing the sample/unbiased covariance matrix.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Toyoda H (1998) Introduction to structural equation modeling (in Japanese) Tokyo: Asakura Publishing.

See Also

[svar](#), [ssd](#), [svar](#), [ssd2sd](#), [lower2R](#)

Examples

```
##data(iris)
x <- iris[,1:4]
cov(x)
r2cov(apply(x, 2, sd), cor(x))

##Toyoda (1998) p.34
r2cov(sd = sqrt(c(.862, 1.089, 0.606)),
      R = lower2R(c(.505, -0.077, -.233)))
```

samplesize.d

Sample size estimation in the t test for means

Description

samplesize.d determines the sample size, when specified the effect size to be detected, desired statistical power, and significance level. samplesize.d always specifies two-sided test.

Usage

```
samplesize.d(delta, power = 0.8, sig.level = 0.05)
```

Arguments

delta	a numeric contains the effect size (Cohen's <i>d</i>) to be detected
power	a numeric contains the desired statistical power (default 0.80)
sig.level	a numeric contains the significance level (default 0.05)

Value

Return a numeric containing the appropriate sample size in each group.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Cohen J (1988). Statistical power analysis for the behavioral sciences (2nd ed). Hillsdale, NJ: Erlbaum.

See Also

[ind.t.test](#), [ind.t.test.second](#)

Examples

```
##Cohen (1988) ex.2.9  
samplesize.d(delta=.20, power=.95, sig.level=.05)
```

samplesize.etasq

Sample size estimation in the analysis of variance

Description

samplesize.etasq determines the sample size, when specified the number of group, effect size to be detected, desired statistical power, and significance level.

Usage

```
samplesize.etasq(k, delta, power=.80, sig.level=.05)
```

Arguments

k	a numeric contains the number of group
delta	a numeric contains the effect size (η^2) to be detected
power	a numeric contains the desired statistical power (default 0.80)
sig.level	a numeric contains the significance level (default 0.05)

Value

Return a numeric containing the appropriate sample size in each group.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Cohen J (1988). Statistical power analysis for the behavioral sciences (2nd ed). Hillsdale, NJ: Erlbaum.

See Also

[ind.oneway](#), [ind.oneway.second](#)

Examples

```
##Cohen (1988) ex.8.10
f <- .25
samplesize.etasq(k=4, delta= f^2/(1+f^2), power=.80, sig.level=.05)
```

samplesize.h

Sample size estimation in the differences between proportions

Description

samplesize.h determines the sample size, when specified the effect size to be detected, desired statistical power, and significance level. samplesize.h always specifies two-sided test.

Usage

```
samplesize.h(delta, power = 0.8, sig.level = 0.05)
```

Arguments

delta	a numeric contains the effect size (Cohen's <i>h</i>) to be detected
power	a numeric contains the desired statistical power (default 0.80)
sig.level	a numeric contains the significance level (default 0.05)

Value

Return a numeric containing the appropriate sample size in each group.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Cohen J (1988). Statistical power analysis for the behavioral sciences (2nd ed). Hillsdale, NJ: Erlbaum.

See Also

[ind.prop](#), [ind.prop.second](#)

Examples

```
##Cohen (1988) ex.6.7
samplesize.h(delta=.20, power=.90, sig.level=.01)

##Cohen (1988) ex.6.8
samplesize.h(delta=.2828, power=.95, sig.level=.05)
```

samplesize.r	<i>Sample size estimation in the significance testing of a product moment correlation</i>
--------------	---

Description

samplesize.r determines the sample size, when specified the effect size to be detected, desired statistical power, and significance level. samplesize.r always specifies two-sided test.

Usage

```
samplesize.r(delta, power = 0.8, sig.level = 0.05)
```

Arguments

delta	a numeric contains the effect size (product moment correlation) to be detected
power	a numeric contains the desired statistical power (default 0.80)
sig.level	a numeric contains the significance level (default 0.05)

Value

Return a numeric containing the appropriate sample size.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Cohen J (1988). Statistical power analysis for the behavioral sciences (2nd ed). Hillsdale, NJ: Erlbaum.

See Also

[zero.r.test](#), [zero.r.test.second](#)

Examples

```
##Cohen (1988) ex.3.4  
samplesize.r(delta=.3, power=.8, sig.level=.05)
```

samplesize.rsq	<i>Sample size estimation in the F tests of variance proportions</i>
----------------	--

Description

samplesize.rsq determines the sample size, when specified the effect size to be detected, desired statistical power, and significance level.

Usage

```
samplesize.rsq(delta, n.ind, power = 0.8, sig.level = 0.05)
```

Arguments

delta	a numeric contains the effect size (Cohen's R^2) to be detected
n.ind	a numeric contains the number of independent variables
power	a numeric contains the desired statistical power (default 0.80)
sig.level	a numeric contains the significance level (default 0.05)

Value

Return a numeric containing the appropriate sample size.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Cohen J (1988). Statistical power analysis for the behavioral sciences (2nd ed). Hillsdale, NJ: Erlbaum.

See Also

[multreg](#), [multreg.second](#)

Examples

```
##Cohen (1988) ex.9.18
samplesize.rsq(delta=.16, n.ind=20, power = .90, sig.level=.05)
```

ssd

Compute sample standard deviation

Description

ssd computes a sample standard deviation.

Usage

```
ssd(x, na.rm = TRUE)
```

Arguments

x	a numeric vector
na.rm	missing values (NA) will be stripped before the computation proceeds (na.rm = TRUE, default)

Value

Return a numeric containing a sample standard deviation.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

See Also

[r2cov](#), [svar](#), [svar](#), [ssd2sd](#), [lower2R](#)

Examples

```
data(infert)
ssd(infert$age)      #sample standard deviation
sd(infert$age)      #unbiased standard deviation
```

ssd2sd

Convert sample standard deviation into unbiased one

Description

ssd2sd converts a sample standard deviation into unbiased one.

Usage

```
ssd2sd(n, ssd)
```

Arguments

n a numeric contains the sample size
ssd a numeric contains the sample standard deviation

Value

Return a numeric containing the unbiased standard deviation.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

See Also

[r2cov](#), [svar](#), [ssd](#), [svar](#), [lower2R](#)

Examples

```
data(infert)
ssd2sd(nrow(infert), ssd(infert$age))
sd(infert$age)
```

svar *Compute sample variance*

Description

svar computes a sample variance.

Usage

```
svar(x, na.rm = TRUE)
```

Arguments

x	a numeric vector
na.rm	missing values (NA) will be stripped before the computation proceeds (na.rm = TRUE, default)

Value

Return a numeric containing a sample variance.

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

See Also

[r2cov](#), [svar](#), [ssd](#), [ssd2sd](#), [lower2R](#)

Examples

```
data(infert)
svar(infert$age) #sample variance
var(infert$age) #unbiased variance
```

zero.r.test	<i>A significance testing of a product moment correlation using individual data</i>
-------------	---

Description

zero.r.test conducts a significance testing of a product moment correlation using individual data

Usage

```
zero.r.test(formula, data, sig.level = 0.05, digits = 3)
```

Arguments

formula	two-sided formula; the left-hand-side of which gives one dependent variable containing a numeric variable, and the right-hand-side of one independent variable containing a numeric variable
data	a data frame contains the variables in the formula
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a significance testing of a product moment correlation using individual data. Statistical power is calculated using the following specifications:

- (a) small ($r = 0.10$), medium ($r = 0.30$), and large ($r = 0.50$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)
- (b) sample size specified by data
- (c) significance level specified by sig.level

Value

The returned object of zero.r.test contains the following components:

samp.stat	returns the means and unbiased standard deviations
correlation	returns a product moment correlation, its' approximate confidence interval for population correlation, and standard error
power	returns statistical power for detecting small ($r = 0.10$), medium ($r = 0.30$), and large ($r = 0.50$) population effect sizes

Author(s)

Yasuyuki Okumura
 Department of Social Psychiatry,
 National Institute of Mental Health,
 National Center of Neurology and Psychiatry
 <yokumura@blue.zero.jp>

References

Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.

See Also

[zero.r.test.second](#), [samplesize.r](#)

Examples

```
dat <- data.frame(x = c(44.4, 45.9, 41.9, 53.3, 44.7, 44.1, 50.7, 45.2, 60.1),
                 y = c( 2.6,  3.1,  2.5,  5.0,  3.6,  4.0,  5.2,  2.8,  3.8))
zero.r.test(y~x, data=dat)
```

zero.r.test.second	<i>A significance testing of a product moment correlation using published work</i>
--------------------	--

Description

zero.r.test.second conducts a significance testing of a product moment correlation using published work.

Usage

```
zero.r.test.second(r, n, sig.level = 0.05, digits = 3)
```

Arguments

r	a numeric contains the product moment correlation
n	a numeric contains the sample size
sig.level	a numeric contains the significance level (default 0.05)
digits	the specified number of decimal places (default 3)

Details

This function conducts a significance testing of a product moment correlation using published work. Statistical power is calculated using the following specifications:

(a) small ($r = 0.10$), medium ($r = 0.30$), and large ($r = 0.50$) population effect sizes, according to the interpretive guideline for effect sizes by Cohen (1992)

(b) sample size specified by n

(c) significance level specified by sig.level

Value

The returned object of `zero.r.test` contains the following components:

<code>correlation</code>	returns a product moment correlation, its' approximate confidence interval for population correlation, and standard error
<code>power</code>	returns statistical power for detecting small ($r = 0.10$), medium ($r = 0.30$), and large ($r = 0.50$) population effect sizes

Author(s)

Yasuyuki Okumura
Department of Social Psychiatry,
National Institute of Mental Health,
National Center of Neurology and Psychiatry
<yokumura@blue.zero.jp>

References

Cohen J (1992) A power primer. *Psychological Bulletin*, 112, 155-159.

See Also

[zero.r.test](#), [samplesize.r](#)

Examples

```
zero.r.test.second(r = 0.571, n = 9)
```

Index

*Topic **array**

lower2R, 26
md.pattern2, 27
r2cov, 33

*Topic **design**

dep.oneway, 4
dep.oneway.second, 5
dep.t.test, 7
dep.t.test.second, 9
ind.oneway, 12
ind.oneway.second, 14
ind.prop, 16
ind.prop.second, 18
ind.t.test, 19
ind.t.test.second, 21
ind.twoway, 23
ind.twoway.second, 24
multreg, 29
multreg.second, 31
samplesize.d, 34
samplesize.etasq, 35
samplesize.h, 36
samplesize.r, 37
samplesize.rsq, 38
zero.r.test, 42
zero.r.test.second, 43

*Topic **htest**

dep.oneway, 4
dep.oneway.second, 5
dep.t.test, 7
dep.t.test.second, 9
ind.oneway, 12
ind.oneway.second, 14
ind.prop, 16
ind.prop.second, 18
ind.t.test, 19
ind.t.test.second, 21
ind.twoway, 23
ind.twoway.second, 24

multreg, 29

multreg.second, 31
samplesize.d, 34
samplesize.etasq, 35
samplesize.h, 36
samplesize.r, 37
samplesize.rsq, 38
zero.r.test, 42
zero.r.test.second, 43

*Topic **package**

rpsychi-package, 2

*Topic **univar**

formatted, 10
groupSummary, 11
ssd, 39
ssd2sd, 40
svar, 41

dep.oneway, 4, 6
dep.oneway.second, 5, 5
dep.t.test, 7, 10
dep.t.test.second, 8, 9

formatted, 10

groupSummary, 11

ind.oneway, 12, 15, 36
ind.oneway.second, 14, 14, 36
ind.prop, 16, 19, 37
ind.prop.second, 17, 18, 37
ind.t.test, 19, 22, 35
ind.t.test.second, 21, 21, 35
ind.twoway, 23, 26
ind.twoway.second, 24, 24

lower2R, 6, 26, 34, 40, 41

md.pattern2, 27

multreg, 29, 32, 39
multreg.second, 30, 31, 39

r2cov, 27, 33, 40, 41
rpsychi (rpsychi-package), 2
rpsychi-package, 2

samplesize.d, 21, 22, 34
samplesize.etasq, 14, 15, 35
samplesize.h, 17, 19, 36
samplesize.r, 37, 43, 44
samplesize.rsq, 30, 32, 38
ssd, 12, 27, 34, 39, 40, 41
ssd2sd, 27, 34, 40, 40, 41
svar, 27, 34, 40, 41, 41

zero.r.test, 38, 42, 44
zero.r.test.second, 38, 43, 43