

# Package ‘scape’

May 1, 2018

**Version** 2.3-2

**Date** 2018-05-01

**Title** Statistical Catch-at-Age Plotting Environment

**Imports** stats, utils, coda, Hmisc, lattice

**Suggests** gdata

**LazyData** yes

**Description** Import, plot, and diagnose results from statistical catch-at-age models, used in fisheries stock assessment.

**License** GPL (>= 2)

**NeedsCompilation** no

**Author** Arni Magnusson [aut, cre]

**Maintainer** Arni Magnusson <arni.magnusson@ices.dk>

**Depends** R (>= 2.10)

**Repository** CRAN

**Date/Publication** 2018-05-01 17:37:04 UTC

## R topics documented:

|                         |    |
|-------------------------|----|
| scape-package . . . . . | 2  |
| estN . . . . .          | 3  |
| estSigmaI . . . . .     | 6  |
| estSigmaR . . . . .     | 8  |
| getN . . . . .          | 10 |
| getSigmaI . . . . .     | 11 |
| getSigmaR . . . . .     | 12 |
| importADCAM . . . . .   | 13 |
| importCol . . . . .     | 14 |
| importMCMC . . . . .    | 16 |
| importProj . . . . .    | 17 |
| iterate . . . . .       | 18 |
| plotB . . . . .         | 19 |

|                     |    |
|---------------------|----|
| plotCA . . . . .    | 21 |
| plotCL . . . . .    | 23 |
| plotIndex . . . . . | 26 |
| plotLA . . . . .    | 28 |
| plotN . . . . .     | 30 |
| plotSel . . . . .   | 32 |
| x.cod . . . . .     | 33 |
| x.ling . . . . .    | 35 |
| x.oreo . . . . .    | 37 |
| x.saithe . . . . .  | 38 |
| x.sbw . . . . .     | 40 |
| xmcmc . . . . .     | 41 |
| xproj . . . . .     | 42 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>44</b> |
|--------------|-----------|

---

|               |  |
|---------------|--|
| scape-package | <i>Statistical Catch-at-Age Plotting Environment</i> |
|---------------|--|

---

## Description

Import and plot results from statistical catch-at-age models, used in fisheries stock assessments.

## Details

*Import model results:*

|                          |                         |
|--------------------------|-------------------------|
| <code>importADCAM</code> | ADCAM model results     |
| <code>importCol</code>   | Coleraine model results |

*Plot model fit to data:*

|                        |                 |
|------------------------|-----------------|
| <code>plotCA</code>    | catch at age    |
| <code>plotCL</code>    | catch at length |
| <code>plotIndex</code> | abundance index |
| <code>plotLA</code>    | length at age   |

*Plot derived quantities:*

|                      |                                    |
|----------------------|------------------------------------|
| <code>plotB</code>   | biomass, recruitment, and landings |
| <code>plotN</code>   | numbers at age                     |
| <code>plotSel</code> | selectivity and maturity           |

*Sigmas and sample sizes:*

|   |          |
|---|----------|
| <code>getN, getSigmaI, getSigmaR</code> | extract  |
| <code>estN, estSigmaI, estSigmaR</code> | estimate |

`iterate`

combine all `get*` and `est*`

*Import MCMC results:*

`importMCMC` traces of likelihoods, parameters, biomass and recruitment  
`importProj` medium-term projections of biomass and catch

*Examples:*

`x.cod`, `x.ling`, `x.oreo`, `x.saithe`, `x.sbw` cod, ling, oreo, and whiting assessments  
`xmcmc`, `xproj` MCMC results

### Note

`browseVignettes()` shows the vignettes, found in the ‘`scape/doc`’ directory.

### Author(s)

Arni Magnusson.

### References

- Magnusson, A. (2005) *R goes fishing: Analyzing fisheries data using AD Model Builder and R*. Proceedings of the 4th International Workshop on Distributed Statistical Computing.
- Magnusson, A. and Hilborn, R. (2007) What makes fisheries data informative? *Fish and Fisheries* **8**, 337–358.
- Magnusson, A., Punt, A. E., and Hilborn, R. (2013) Measuring uncertainty in fisheries stock assessment: the delta method, bootstrap, and MCMC. *Fish and Fisheries* **14**, 325–342.

### See Also

Most **scape** graphics are `trellis` plots, rendered with the **lattice** package.

The functions `Args` and `ll` (package **gdata**) can be useful for browsing unwieldy functions and objects.

The **plotMCMC** package can be used to diagnose the results of MCMC analysis.

---

estN

*Estimate Effective Sample Size*

---

### Description

Estimate the effective sample size for catch-at-age or catch-at-length data, based on the multinomial distribution.

**Usage**

```
estN(model, what="CAc", series=NULL, init=NULL, FUN=mean, ceiling=Inf,
      digits=0)
```

```
estN.int(P, Phat) # internal function
```

**Arguments**

|         |   |
|---------|---|
| model   | fitted scape model containing catch-at-age and/or catch-at-length data.                           |
| what    | name of model element: "CAc", "CAS", "CLc", or "CLs".   |
| series  | vector of strings indicating which gears or surveys to analyze (all by default).                  |
| init    | initial sample size, determining the relative pattern of the effective sample size between years. |
| FUN     | function to standardize the effective sample size.  |
| ceiling | largest possible sample size in one year.   |
| digits  | number of decimal places to use when rounding, or NULL to suppress rounding.                      |
| P       | observed catch-at-age or catch-at-length matrix.  |
| Phat    | fitted catch-at-age or catch-at-length matrix.  |

**Details**

The `init` sample sizes set a fixed pattern for the relative sample sizes between years. For example, if there are two years of catch-at-age data and the initial sample sizes are 100 in year 1 and 200 in year 2, the effective sample size will be two times greater in year 2 than in year 1, although both will be scaled up or down depending on how closely the model fits the catch-at-age data. The value of `init` can be one of the following:

NULL means read the initial sample sizes from the existing SS column (default).

**model** means read the initial sample sizes from the SS column in that model (object of class `scape`).

**numeric vector** means those are the initial sample sizes (same length as the number of years).

FALSE means ignore the initial sample sizes and use the empirical multinomial sample size ( $\hat{n}$ ) in each year.

1 means calculate one effective sample size to use across all years, e.g. the mean or median of  $\hat{n}$ .

The idea behind `FUN=mean` is to guarantee that regardless of the value of `init`, the mean effective sample size will always be the same. Other functions can be used to a similar effect, such as `FUN=median`.

The `estN` function is implemented for basic single-sex datasets. If the data are sex-specific, `estN` pools (averages) the sexes before estimating effective sample sizes. The general function `estN.int`, on the other hand, is suitable for analyzing any datasets in matrix format. The 'int' in `estN.int` stands for internal (not integer), analogous to `rep.int`, `seq.int`, `sort.int`, and similar functions.

**Value**

Numeric vector of effective sample sizes (one value if `init=1`), or a list of such vectors when analyzing multiple series.

**Note**

This function uses the empirical multinomial sample size to estimate an effective sample size, which may be appropriate as likelihood weights for catch-at-age and catch-at-length data. The better the model fits the data, the larger the effective sample size. See McAllister and Ianelli (1997), Gavaris and Ianelli (2002), and Magnusson et al. (2013).

estN can be used iteratively, along with [estSigmaI](#) and [estSigmaR](#) to assign likelihood weights that are indicated by the model fit to the data. Sigmas and sample sizes are then adjusted between model runs, until they converge. The [iterate](#) function facilitates this procedure.

If  $P_{t,a}$  is the observed proportion of fish at age (or length bin)  $a$  in year  $t$ , and  $\hat{P}_{t,a}$  is the fitted proportion, then the estimated sample size in that year is:

$$\hat{n}_t = \sum_a \hat{P}_{t,a}(1 - \hat{P}_{t,a}) \bigg/ \sum_a (P_{t,a} - \hat{P}_{t,a})^2$$

Due to the non-random and non-independent nature of sampling fish, the effective sample size, for statistical purposes, is much less than the number of fish sampled. Common starting points include using the number of tows as the sample size in each year, or using the empirical multinomial sample sizes. Those “initial” sample sizes can then be scaled up or down. Sample sizes between 20 and 200 are common in the stock assessment literature.

**References**

Gavaris, S. and Ianelli, J. N. (2002) Statistical issues in fisheries’ stock assessments. *Scandinavian Journal of Statistics* **29**, 245–271.

Magnusson, A., Punt, A. E., and Hilborn, R. (2013) Measuring uncertainty in fisheries stock assessment: the delta method, bootstrap, and MCMC. *Fish and Fisheries* **14**, 325–342.

McAllister, M. K. and Ianelli, J. N. (1997) Bayesian stock assessment using catch-age data and the sampling-importance resampling algorithm. *Canadian Journal of Fisheries and Aquatic Sciences* **54**, 284–300.

**See Also**

[getN](#), [getSigmaI](#), [getSigmaR](#), [estN](#), [estSigmaI](#), and [estSigmaR](#) extract and estimate sample sizes and sigmas.

[iterate](#) combines all the [get\\*](#) and [est\\*](#) functions in one call.

[plotCA](#) and [plotCL](#) show what is behind the sample-size estimation.

[scape-package](#) gives an overview of the package.

**Examples**

```
## Exploring candidate sample sizes:

getN(x.sbw)      # sample sizes used in assessment: number of tows
estN(x.sbw)      # effective sample size, given data (tows) and model fit
estN(x.sbw, ceiling=200) # could use this
estN(x.sbw, init=FALSE) # from model fit, disregarding tows
```

```

plotCA(x.sbw)          # years with good fit => large sample size
estN(x.sbw, init=1)    # one sample size across all years
estN(x.sbw, init=c(rep(1,14),rep(2,9))) # two sampling periods

## Same mean, regardless of init:

mean(estN(x.sbw, digits=NULL))
mean(estN(x.sbw, digits=NULL, init=FALSE))
mean(estN(x.sbw, digits=NULL, init=1))
mean(estN(x.sbw, digits=NULL, init=c(rep(1,14),rep(2,9))))

## Same median, regardless of init:

median(estN(x.sbw, FUN=median, digits=NULL))
median(estN(x.sbw, FUN=median, digits=NULL, init=FALSE))
median(estN(x.sbw, FUN=median, digits=NULL, init=1))
median(estN(x.sbw, FUN=median, digits=NULL, init=c(rep(1,14),rep(2,9))))

## Multiple series:

getN(x.ling, "CLc")    # sample size used in assessment
getN(x.ling, "CLc", digits=0) # rounded
estN(x.ling, "CLc")    # model fit implies larger sample sizes

getN(x.ling, "CLc", series="1", digits=0) # get one series
estN(x.ling, "CLc", series="1")          # estimate one series

```

---

estSigmaI

*Estimate Abundance Index Sigma*


---

### Description

Estimate the effective sigma (magnitude of observation noise) for a survey or commercial abundance index, based on the empirical standard deviation.

### Usage

```
estSigmaI(model, what="s", series=NULL, init=NULL, FUN=mean, p=1,
          digits=2)
```

### Arguments

|        |  |
|--------|--|
| model  | fitted scape model containing element CPUE and/or Survey.                              |
| what   | which effective sigma to estimate: "c"[ommercial] or "s"[urvey] abundance index.       |
| series | vector of strings indicating which gears or surveys to analyze (all by default).       |
| init   | initial sigma, determining the relative pattern of the effective sigmas between years. |

|                     |  |
|---------------------|--|
| <code>FUN</code>    | function to use when scaling a vector of sigmas.                             |
| <code>p</code>      | effective number of parameters estimated in the model.                       |
| <code>digits</code> | number of decimal places to use when rounding, or NULL to suppress rounding. |

### Details

The `init` sigmas set a fixed pattern for the relative sigmas between years. For example, if there are two years of abundance index data and the initial sigmas are 0.1 in year 1 and 0.2 in year 2, the effective sigma will be two times greater in year 2 than in year 1, although both will be scaled up or down depending on how closely the model fits the abundance index. The value of `init` can be one of the following:

NULL means read the initial sigmas from the existing CV column (default).

**model** means read the initial sigmas from the CV column in that model (object of class `scape`).

**numeric vector** means those are the initial sigmas (same length as the number of years).

FALSE or 1 means use one effective sigma ( $\hat{\sigma}$ ) across all years.

The idea behind `FUN=mean` is to guarantee that regardless of the value of `init`, the mean effective sigma will always be the same. Other functions can be used to a similar effect, such as `FUN=median`.

### Value

Numeric vector of effective sigmas (one value if `init=1`), or a list of such vectors when analyzing multiple series.

### Note

This function uses the empirical standard deviation to estimate an effective sigma, which may be appropriate as likelihood weights for abundance index data. The better the model fits the data, the smaller the effective sigma.

`estSigmaI` can be used iteratively, along with `estN` and `estSigmaR` to assign likelihood weights that are indicated by the model fit to the data. Sigmas and sample sizes are then adjusted between model runs, until they converge. The `iterate` function facilitates this procedure.

If  $r_{ss}$  is the residual sum of squares in log space,  $n$  is the number of abundance index data points, and  $p$  is the effective number of parameters estimated in the model, then the estimated effective sigma is:

$$\hat{\sigma} = \sqrt{\frac{r_{ss}}{n - p}}$$

There is no simple way to calculate  $p$  for statistical catch-at-age models. The default value of 1 is likely to underestimate the true magnitude of observation noise.

**See Also**

[getN](#), [getSigmaI](#), [getSigmaR](#), [estN](#), [estSigmaI](#), and [estSigmaR](#) extract and estimate sample sizes and sigmas.

[iterate](#) combines all the `get*` and `est*` functions in one call.

[plotIndex](#) shows what is behind the sigma estimation.

[scape-package](#) gives an overview of the package.

**Examples**

```
## Exploring candidate sigmas:

getSigmaI(x.cod)      # sigma used in assessment 0.20
estSigmaI(x.cod)     # model fit implies 0.17
plotIndex(x.cod)     # model fit
estSigmaI(x.cod, p=8) # eight estimated parameters implies 0.22

getSigmaI(x.sbw)      # sigma used in assessment
estSigmaI(x.sbw)     # model fit implies smaller sigma
estSigmaI(x.sbw, init=1) # could use 0.17 in all years

## Same mean, regardless of init:

mean(estSigmaI(x.sbw, digits=NULL))
mean(estSigmaI(x.sbw, digits=NULL, init=1))

## Same median, regardless of init:

median(estSigmaI(x.sbw, FUN=median, digits=NULL))
median(estSigmaI(x.sbw, FUN=median, digits=NULL, init=1))

## Multiple series:

getSigmaI(x.oreo, "c")          # sigma used in assessment
getSigmaI(x.oreo, "c", digits=2) # rounded
estSigmaI(x.oreo, "c")          # model fit implies smaller sigma
estSigmaI(x.oreo, "c", init=1)  # could use 0.19 in all years
estSigmaI(x.oreo, "c", init=1, digits=3) # series 2 slightly worse fit
# estSigmaI(x.oreo, "c", init=1, p=11) # more parameters than datapoints

getSigmaI(x.oreo, "c", series="Series 2-1") # get one series
estSigmaI(x.oreo, "c", series="Series 2-1") # estimate one series
```

---

 estSigmaR

*Estimate Recruitment Sigma*


---

**Description**

Estimate sigma R (recruitment variability), based on the empirical standard deviation of recruitment deviates in log space.



**Usage**

```
estSigmaR(model, digits=2)
```

**Arguments**

`model` fitted scape model containing element `Dev`.  
`digits` number of decimal places to use when rounding, or `NULL` to suppress rounding.

**Value**

Vector of two numbers, estimating recruitment variability based on (1) the estimated age composition in the first year, and (2) subsequent annual recruitment.

**Note**

This function uses the empirical standard deviation to estimate sigma R, which may be appropriate as likelihood penalty (or Bayesian prior distribution) for recruitment deviates from the stock-recruitment curve. The smaller the estimated recruitment deviates, the smaller the estimated sigma R.

`estSigmaR` can be used iteratively, along with `estN` and `estSigmaI` to assign likelihood weights that are indicated by the model fit to the data. Sigmas and sample sizes are then adjusted between model runs, until they converge. The `iterate` function facilitates this procedure.

If  $ss$  is the sum of squared recruitment deviates in log space and  $n$  is the number of estimated recruitment deviates, then the estimated sigma R is:

$$\sigma_R = \sqrt{\frac{ss}{n}}$$

The denominator is neither  $n-1$  nor  $n-p$ , since  $ss$  is based on deviates from zero and not the mean, and the deviates do not converge to zero as the number of model parameters increases.

**See Also**

`getN`, `getSigmaI`, `getSigmaR`, `estN`, `estSigmaI`, and `estSigmaR` extract and estimate sample sizes and sigmas.

`iterate` combines all the `get*` and `est*` functions in one call.

`plotN` and `plotB(..., what="s")` show what is behind the sigma R estimation.

`scape-package` gives an overview of the package.

**Examples**

```
getSigmaR(x.cod) # sigmaR used in assessment 0.5 and 1.0
estSigmaR(x.cod) # model estimates imply 0.20 and 0.52

getSigmaR(x.ling) # 0.6, deterministic age distribution in first year
estSigmaR(x.ling) # model estimates imply 0.36

getSigmaR(x.sbw)
```

```

estSigmaR(x.sbw) # large deviates in first year
plotN(x.sbw)     # enormous plus group and 1991 cohort

# x.oreo assessment had deterministic recruitment, so no deviates

```

---

getN

*Extract Sample Size*


---

### Description

Extract the sample size that was used in a model, from catch-at-age or catch-at-length data.

### Usage

```
getN(model, what="CAC", series=NULL, digits=NULL)
```

### Arguments

|        |  |
|--------|--|
| model  | fitted scape model containing catch-at-age and/or catch-at-length data.          |
| what   | name of model element: "CAC", "CAS", "CLC", or "CLS".                            |
| series | vector of strings indicating which gears or surveys to analyze (all by default). |
| digits | number of decimal places to use when rounding, or NULL to suppress rounding.     |

### Value

Numeric vector of year-specific sample sizes, or a list of such vectors when analyzing multiple series.

### Note

Thin wrapper to access `model$element$SS`, providing a uniform interface with other `get*` and `est*` functions.

See discussion in the [estN](#) documentation.

### See Also

[getN](#), [getSigmaI](#), [getSigmaR](#), [estN](#), [estSigmaI](#), and [estSigmaR](#) extract and estimate sample sizes and sigmas.

[scape-package](#) gives an overview of the package.

**Examples**

```
## Exploring candidate sample sizes:

getN(x.sbw) # sample sizes used in assessment: number of tows
estN(x.sbw) # effective sample size, given data (tows) and model fit

## Multiple series:

getN(x.ling, "CLc")           # sample size used in assessment
getN(x.ling, "CLc", digits=0) # rounded
estN(x.ling, "CLc")          # model fit implies larger sample sizes

getN(x.ling, "CLc", series="1", digits=0) # get one series
estN(x.ling, "CLc", series="1")          # estimate one series
```

---

|                        |                                      |
|------------------------|--------------------------------------|
| <code>getSigmaI</code> | <i>Extract Abundance Index Sigma</i> |
|------------------------|--------------------------------------|

---

**Description**

Extract the sigma (magnitude of observation noise) that was used in a model, from survey or commercial abundance index data.

**Usage**

```
getSigmaI(model, what="s", series=NULL, digits=NULL)
```

**Arguments**

|                     |  |
|---------------------|--|
| <code>model</code>  | fitted scape model containing element CPUE and/or Survey.                        |
| <code>what</code>   | which sigma to extract: "c"[ommercial] or "s"[urvey] abundance index.            |
| <code>series</code> | vector of strings indicating which gears or surveys to analyze (all by default). |
| <code>digits</code> | number of decimal places to use when rounding, or NULL to suppress rounding.     |

**Value**

Numeric vector of year-specific sigmas, or a list of such vectors when analyzing multiple series.

**Note**

Thin wrapper to access `model$element$CV`, providing a uniform interface with other `get*` and `est*` functions.

See discussion in the [estSigmaI](#) documentation.

**See Also**

getN, [getSigmaI](#), [getSigmaR](#), [estN](#), [estSigmaI](#), and [estSigmaR](#) extract and estimate sample sizes and sigmas.

[scape-package](#) gives an overview of the package.

**Examples**

```
## Exploring candidate sigmas:

getSigmaI(x.cod) # sigma used in assessment 0.20
estSigmaI(x.cod) # model fit implies 0.17

## Multiple series:

getSigmaI(x.oreo, "c")           # sigma used in assessment
getSigmaI(x.oreo, "c", digits=2) # rounded
estSigmaI(x.oreo, "c")           # model fit implies smaller sigma

getSigmaI(x.oreo, "c", series="Series 2-1") # get one series
estSigmaI(x.oreo, "c", series="Series 2-1") # estimate one series
```

---

|           |                                  |
|-----------|----------------------------------|
| getSigmaR | <i>Extract Recruitment sigma</i> |
|-----------|----------------------------------|

---

**Description**

Extract sigma R (recruitment variability) that was used in a model, as indicated in the Dev\$sigmaR model component.

**Usage**

```
getSigmaR(model, digits=NULL)
```

**Arguments**

|        |  |
|--------|--|
| model  | fitted scape model containing element Dev.   |
| digits | digitsnumber of decimal places to use when rounding, or NULL to suppress rounding. |

**Value**

Vector of two numbers, representing recruitment variability in (1) the estimated age composition in the first year, and (2) subsequent annual recruitment.

**Note**

Thin wrapper to access model\$Dev\$sigmaR, providing a uniform interface with other get\* and est\* functions.

See discussion in the [estSigmaR](#) documentation.

**See Also**

[getN](#), [getSigmaI](#), [getSigmaR](#), [estN](#), [estSigmaI](#), and [estSigmaR](#) extract and estimate sample sizes and sigmas.

**Examples**

```
getSigmaR(x.cod) # sigmaR used in assessment 0.5 and 1.0
estSigmaR(x.cod) # model estimates imply 0.20 and 0.52

getSigmaR(x.ling) # 0.6, deterministic age distribution in first year
estSigmaR(x.ling) # model estimates imply 0.36

getSigmaR(x.sbw)
estSigmaR(x.sbw) # large deviates in first year
plotN(x.sbw)     # enormous plus group and 1991 cohort

# x.oreo assessment had deterministic recruitment, so no deviates
```

---

importADCAM

---

*Import ADCAM Model Results*


---

**Description**

Import ADCAM model results into a standard format suitable for plotting.

**Usage**

```
importADCAM(dir)
```

**Arguments**

`dir` directory containing the results files ('resultsbyyearandage', 'resultsbyyear', 'resultsbyage'), as well as the input file 'catchparameters' specifying selectivity periods.

**Value**

A list of class scape containing the following elements:

|        |   |
|--------|---|
| N      | predicted numbers at age  |
| B      | predicted biomass, recruitment, and observed landings (year things) |
| Se1    | predicted selectivity and observed maturity (age things)            |
| Dev    | predicted recruitment deviates from the stock-recruitment curve     |
| Survey | survey abundance index and fit                                      |
| CAC    | commercial C@A (catch at age) and fit                               |
| CAs    | survey C@A (catch at age) and fit                                   |

**Note**

B\$VB is reference biomass.

Survey\$CV is 0 to give plotIndex sensible y-axis limits.

Cac\$SS and Cas\$SS are the  $\log(\text{obs}+\text{const}) - \log(\text{fit}+\text{const})$  residuals used in the ADCAM likelihood.

**References**

Bjornsson, H. and A. Magnusson. (2009) *ADCAM user manual (draft version)*. ICES CM 2009/ACOM:56 Annex 6.

**See Also**

[read.table](#), [readLines](#), and [scan](#) import any data.

[x.saithe](#) was created using importADCAM.

[importCol](#) imports Coleraine model results.

[scape-package](#) gives an overview of the package.

**Examples**

```
path <- system.file("example/saithe", package="scape")
saithe <- importADCAM(path)
```

---

importCol

---

*Import Coleraine Model Results*


---

**Description**

Import Coleraine model results from '.res' file, and rearrange into a standard format suitable for plotting.

**Usage**

```
importCol(res.file, Dev=FALSE, CPUE=FALSE, Survey=FALSE, Cac=FALSE,
          Cas=FALSE, CLc=FALSE, CLs=FALSE, LA=FALSE, quiet=TRUE)
```

**Arguments**

|          |   |
|----------|---|
| res.file | name of Coleraine model results file to import.           |
| Dev      | whether recruitment deviates were estimated in model.     |
| CPUE     | whether model was fitted to catch-per-unit-effort data.   |
| Survey   | whether model was fitted to survey abundance index data.  |
| Cac      | whether model was fitted to commercial catch-at-age data. |
| Cas      | whether model was fitted to survey catch-at-age data.     |

|       |  |
|-------|--|
| CLc   | whether model was fitted to commercial catch-at-length data. |
| CLs   | whether model was fitted to survey catch-at-length data.     |
| LA    | whether model was fitted to length-at-age data.              |
| quiet | whether to report progress while parsing file.               |

### Value

A list of class `scape` containing at least `N`, `B`, and `Se1`. The other elements may or may not be included in the list, depending on how `importCol` was called:

|   |   |
|---|---|
| <code>N</code>                          | predicted numbers at age  |
| <code>B</code>                          | predicted biomass, recruitment, and observed landings (year things) |
| <code>Se1</code>                        | predicted selectivity and observed maturity (age things)            |
| <code>Dev</code>                        | predicted recruitment deviates from the stock-recruitment curve     |
| <code>CPUE</code> , <code>Survey</code> | commercial and survey abundance index and fit                       |
| <code>CAC</code> , <code>CAs</code>     | commercial and survey C@A (catch at age) and fit                    |
| <code>CLc</code> , <code>CLs</code>     | commercial and survey C@L (catch at length) and fit                 |
| <code>LA</code>                         | observed L@A and fit  |

### Note

This import function is implemented for the Coleraine statistical catch-at-age software, and can serve as a template for **scape** users who would like to implement import functions for specific stock assessment software.

The functions `l1` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `l1(x.cod)`, `l1(x.cod$N)`, and `head(x.cod$N)`.

### References

Hilborn, R., Maunder, M., Parma, A., Ernst, B., Payne, J., and Starr, P. (2003) *Coleraine: A generalized age-structured stock assessment model*. User's manual version 2.0. University of Washington Report SAFS-UW-0116.

### See Also

[read.table](#), [readLines](#), and [scan](#) import any data.

[x.cod](#), [x.ling](#), [x.oreo](#), and [x.sbw](#) were created using `importCol`.

[importADCAM](#) imports ADCAM model results.

[scape-package](#) gives an overview of the package.

### Examples

```
path <- system.file("example/cod.res", package="scape")
cod <- importCol(path, Dev=TRUE, Survey=TRUE, CAC=TRUE, CAs=TRUE)
```

importMCMC

*Import Coleraine MCMC Results***Description**

Import Coleraine MCMC traces for likelihoods, parameters, spawning biomass, and recruitment.

**Usage**

```
importMCMC(dir, coda=FALSE, quiet=TRUE, pretty.labels=FALSE,
           l.choose=NULL, p.choose=NULL)
```

**Arguments**

|                            |   |
|----------------------------|---|
| <code>dir</code>           | directory containing the files ‘mcmclike.out’, ‘params.pst’, ‘spawbiom.pst’ and ‘recruits.pst’. |
| <code>coda</code>          | whether data frames should be coerced to class <code>mcmc</code> using the <b>coda</b> package. |
| <code>quiet</code>         | whether to report progress while parsing files in directory.                                    |
| <code>pretty.labels</code> | whether likelihood and parameter columns should be renamed                                      |
| <code>l.choose</code>      | vector of strings, indicating which likelihood components to import, or NULL to import all.     |
| <code>p.choose</code>      | vector of strings, indicating which parameters to import, or NULL to import all.                |

**Value**

A list containing:

|   |                     |
|---|---------------------|
| L | likelihoods         |
| P | parameters          |
| B | biomass by year     |
| R | recruitment by year |

as data frames, or `mcmc` objects if `coda=TRUE`.

**Note**

The functions `l1` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `l1(xmcmc)`, `l1(xmcmc$P)`, and `head(xmcmc$P)`.

The **plotMCMC** package is recommended for plotting MCMC diagnostics and posteriors.

**References**

Hilborn, R., Maunder, M., Parma, A., Ernst, B., Payne, J., and Starr, P. (2003) *Coleraine: A generalized age-structured stock assessment model*. User’s manual version 2.0. University of Washington Report SAFS-UW-0116.



**See Also**

[read.table](#), [readLines](#), and [scan](#) import any data.

[importMCMC](#) and [importProj](#) import Coleraine MCMC results.

[xmcnc](#) was created using [importMCMC](#).

[scape-package](#) gives an overview of the package.

**Examples**

```
path <- system.file("example/mcmc", package="scape")
mcmc <- importMCMC(path) # or rename and select particular elements:
mcmc <- importMCMC(path, pretty.labels=TRUE,
  l.choose=c("CAc", "CAs", "Survey", "Prior", "Total"),
  p.choose=c("R0", "Rinit", "uinit", "cSleft", "cSfull",
    "sSleft", "sSfull", "logq"))
```

---

importProj

---

*Import Coleraine MCMC Projections*


---

**Description**

Import Coleraine MCMC traces for spawning biomass and catch, projected into the near future.

**Usage**

```
importProj(dir, coda=FALSE, quiet=TRUE)
```

**Arguments**

|                    |   |
|--------------------|---|
| <code>dir</code>   | directory containing the files ‘strategy.out’, ‘projspb.m.pst’ and ‘procatch.pst’.              |
| <code>coda</code>  | whether data frames should be coerced to class <code>mcmc</code> using the <b>coda</b> package. |
| <code>quiet</code> | whether to report progress while parsing files in directory.                                    |

**Value**

A list containing:

`B` biomass by catch policy and year

`Y` catch by catch policy and year

as lists of data frames, or `mcmc` objects if `coda=TRUE`.

**Note**

MCMC projections can be used to evaluate the short-term outcome of harvest policies (constant catch or constant harvest rate), given the uncertainty about parameter values and random future recruitment.

The functions `ll` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `ll(xproj)`, `ll(xproj$B)`, `ll(xproj$B$"0.2")`, and `head(xproj$B$"0.2")`.

The **plotMCMC** package is recommended for plotting MCMC diagnostics and posteriors.

**References**

Hilborn, R., Maunder, M., Parma, A., Ernst, B., Payne, J., and Starr, P. (2003) *Coleraine: A generalized age-structured stock assessment model*. User's manual version 2.0. University of Washington Report SAFS-UW-0116.

**See Also**

[read.table](#), [readLines](#), and [scan](#) import any data.

[importMCMC](#) and [importProj](#) import Coleraine MCMC results.

[xproj](#) was created using [importProj](#).

[scape-package](#) gives an overview of the package.

**Examples**

```
path <- system.file("example/mcmc", package="scape")
proj <- importProj(path)
```

---

iterate

*Get Candidate Sigmas and Sample Sizes*

---

**Description**

Compare current sigmas and sample sizes with candidate values, by running variations of `estSigmaR`, `estN`, and `estSigmaI` on all model components.

**Usage**

```
iterate(model, ceiling=Inf, p=1, digits.n=0, digits.sigma=2)
```

**Arguments**

|                           |  |
|---------------------------|--|
| <code>model</code>        | fitted <code>scape</code> model.   |
| <code>ceiling</code>      | largest possible sample size in one year, passed to <code>estN</code> .                                |
| <code>p</code>            | effective number of parameters estimated in the model, passed to <code>estSigmaI</code> .              |
| <code>digits.n</code>     | number of decimal places to use when rounding sample sizes, or <code>NULL</code> to suppress rounding. |
| <code>digits.sigma</code> | number of decimal places to use when rounding sigmas, or <code>NULL</code> to suppress rounding.       |

**Value**

List containing data frames summarizing current sigmas and sample sizes, as well as candidate values. The following abbreviations are used in column names:

**sigmahat** candidate sigma, the empirical standard deviation.

**nhat** candidate sample sizes, the empirical multinomial sample sizes.

**candbar** vector of candidate values, whose mean equals sigmahat or nhat.

**candmed** vector of candidate values, whose median equals sigmahat or nhat.

**candbar1** vector of identical candidate values, the mean of nhat.

**candmed1** vector of identical candidate values, the median of nhat.

**See Also**

[getN](#), [getSigmaI](#), [getSigmaR](#), [estN](#), [estSigmaI](#), and [estSigmaR](#) extract and estimate sample sizes and sigmas.

`iterate` combines all the `get*` and `est*` functions in one call.

[scape-package](#) gives an overview of the package.

**Examples**

```
iterate(x.cod)
iterate(x.ling)
iterate(x.oreo)
iterate(x.sbw)
```

---

plotB

*Plot Biomass, Recruitment, and Landings*

---

**Description**

Plot scape model predicted biomass, stock recruitment, and landings.

**Usage**

```
plotB(model, what="d", series=NULL, years=NULL, axes=TRUE, div=1,
       legend="bottom", main="", xlab="", ylab="", cex.main=1.2,
       cex.legend=1, cex.lab=1, cex.axis=0.8, las=1,
       tck=c(1,what=="d")/2, tick.number=5, lty.grid=3, col.grid="white",
       pch=16, cex.points=0.8, col.points="black", lty.lines=1:3,
       lwd.lines=2, col.lines="black", ratio.bars=3, col.bars="gray",
       plot=TRUE, ...)
```

**Arguments**

|             |   |
|-------------|---|
| model       | fitted scape model.   |
| what        | what to plot: "d"[efault], "s"[tock recruitment], or "l"[andings].                                    |
| series      | vector of strings indicating which column names in model\$B data frame to plot (all by default).      |
| years       | vector of numbers indicating which years to include (all by default).                                 |
| axes        | whether to plot axis values.  |
| div         | denominator to shorten values on the y axis, or a vector with two elements referring to x and y axis. |
| legend      | legend location: "bottom", "left", "top", "right", or "" to suppress legend.                          |
| main        | main title.   |
| xlab        | x-axis label.   |
| ylab        | y-axis label.   |
| cex.main    | size of main title.   |
| cex.legend  | size of legend text.  |
| cex.lab     | size of axis labels.  |
| cex.axis    | size of tick labels.  |
| las         | orientation of tick labels: 0=parallel, 1=horizontal, 2=perpendicular, 3=vertical.                    |
| tck         | tick mark length.   |
| tick.number | number of tick marks.   |
| lty.grid    | line type of gridlines.   |
| col.grid    | color of gridlines.   |
| pch         | symbol for points.  |
| cex.points  | size of points.   |
| col.points  | color of points.  |
| lty.lines   | line type of main lines.  |
| lwd.lines   | line width of main lines.   |
| col.lines   | color of main lines.  |
| ratio.bars  | width of bars.  |
| col.bars    | color of bars.  |
| plot        | whether to draw plot.   |
| ...         | passed to xyplo <sup>t</sup> and panel.superpose.   |

**Details**

The "d"[efault] plot shows spawning biomass and vulnerable biomass as lines, and landings as bars, on the same scale.

**Value**

When `plot=TRUE`, a trellis plot is drawn and a data frame is returned, containing the data used for plotting. When `plot=FALSE`, a trellis object is returned.

**Note**

The `Args` function from the **gdata** package is recommended for reviewing the arguments, instead of `args`.

**See Also**

[xyplot](#), [panel.barchart](#), and [panel.superpose](#) are the underlying drawing functions.

[plotCA](#), [plotCL](#), [plotIndex](#), and [plotLA](#) plot model fit and data.

[plotB](#), [plotN](#), and [plotSel](#) plot derived quantities.

[scape-package](#) gives an overview of the package.

**Examples**

```
plotB(x.ling, series=c("VB.1", "VB.2", "Y"), div=1000, xlab="Year\n",
      ylab="Biomass and landings (kt)")
```

```
plotB(x.ling, "s", div=1000, xlab="Biomass age 4+ (kt)",
      ylab="Recruitment (million one-year-olds)")
```

---

 plotCA

*Plot Catch at Age*


---

**Description**

Plot scape model fit to catch-at-age data.

**Usage**

```
plotCA(model, what="c", fit=TRUE, swap=FALSE, series=NULL, sex=NULL,
       years=NULL, ages=NULL, axes=TRUE, same.limits=TRUE, log=FALSE,
       base=10, eps.log=1e-5, main="", xlab="", ylab="", cex.main=1.2,
       cex.lab=1, cex.axis=0.8, cex.strip=0.8, col.strip="gray95",
       strip=strip.custom(bg=col.strip), las=!fit, tck=c(1,fit)/2,
       tick.number=5, lty.grid=3, col.grid="gray", pch=16,
       cex.points=0.5, col.points="black", lty.lines=1, lwd.lines=2,
       col.lines=c("red", "blue"), plot=TRUE, ...)
```

**Arguments**

|             |  |
|-------------|--|
| model       | fitted scape model containing element CAc and/or CAs.                              |
| what        | what to plot: "c"[ommercial] or "s"[urvey] catch at age.                           |
| fit         | whether to overlay fitted values on observed data.                                 |
| swap        | whether to swap ages and years between axes or panels.                             |
| series      | string indicating which gear or survey to plot (first by default).                 |
| sex         | string indicating which sex to plot (both by default).                             |
| years       | vector of numbers indicating which years to plot (all by default).                 |
| ages        | vector of numbers indicating which ages to plot (all by default).                  |
| axes        | whether to plot axis values.   |
| same.limits | whether panels should have same y-axis limits.                                     |
| log         | whether to log-transform values.   |
| base        | logarithm base.  |
| eps.log     | small number to add before log-transforming to avoid log 0.                        |
| main        | main title.  |
| xlab        | x-axis label.  |
| ylab        | y-axis label.  |
| cex.main    | size of main title.  |
| cex.lab     | size of axis labels.   |
| cex.axis    | size of tick labels.   |
| cex.strip   | size of strip labels.  |
| col.strip   | color of strip labels.   |
| strip       | logical flag (whether to plot strip labels), or a function passed to xyplot.       |
| las         | orientation of tick labels: 0=parallel, 1=horizontal, 2=perpendicular, 3=vertical. |
| tck         | tick mark length.  |
| tick.number | number of tick marks.  |
| lty.grid    | line type of gridlines.  |
| col.grid    | color of gridlines.  |
| pch         | symbol for points.   |
| cex.points  | size of points.  |
| col.points  | color of points.   |
| lty.lines   | line type of main lines, possibly a vector where element 2 refers to males.        |
| lwd.lines   | line width of main lines, possibly a vector where element 2 refers to males.       |
| col.lines   | color of main lines, possibly a vector where element 2 refers to males.            |
| plot        | whether to draw plot.  |
| ...         | passed to xyplot, panel.xyplot, panel.superpose, and panel.superpose.2.            |

**Value**

When `plot=TRUE`, a trellis plot is drawn and a data frame is returned, containing the data used for plotting. When `plot=FALSE`, a trellis object is returned.

**Note**

The `Args` function from the **gdata** package is recommended for reviewing the arguments, instead of `args`.

**See Also**

[xyplot](#), [panel.xyplot](#), and [panel.superpose](#) are the underlying drawing functions.

[plotCA](#), [plotCL](#), [plotIndex](#), and [plotLA](#) plot model fit and data.

[plotB](#), [plotN](#), and [plotSel](#) plot derived quantities.

[scape-package](#) gives an overview of the package.

**Examples**

```
plotCA(x.sbw, fit=FALSE, strip=FALSE, xlab="Age", ylab="Year",
       tick.number=10)
```

```
plotCA(x.cod, xlab="Age", ylab="Proportion in catch", cex.strip=0.7,
       cex.axis=0.7, col.lines="brown", layout=c(8,4))
```

```
plotCA(x.cod, xlab="Age", ylab="Proportion in catch", cex.strip=0.7,
       cex.axis=0.7, col.lines="brown", layout=c(2,4), swap=TRUE,
       ages=3:10, same.limits=FALSE)
```

```
plotCA(x.ling, "s", col.points=c("red","blue"), lty.lines=0, xlab="Age",
       ylab="Observed proportion in survey", tck=0.5, cex.strip=0.7,
       cex.axis=0.7)
```

```
plotCA(x.ling, "s", xlab="Age", ylab="Observed proportion in survey",
       fit=FALSE, cex.strip=0.7, cex.axis=0.7, tck=0.5, layout=c(5,2))
```

```
plotCA(x.ling, "s", xlab="Age", ylab="Observed proportion in survey",
       fit=FALSE, cex.strip=0.7, cex.axis=0.7, tck=0.5, layout=c(5,6),
       swap=TRUE)
```

---

 plotCL

---

*Plot Catch at Length*


---

**Description**

Plot scape model fit to catch-at-length data.

**Usage**

```
plotCL(model, what="c", fit=TRUE, swap=FALSE, series=NULL, sex=NULL,
       years=NULL, lengths=NULL, axes=TRUE, same.limits=TRUE, log=FALSE,
       base=10, eps.log=1e-5, main="", xlab="", ylab="", cex.main=1.2,
       cex.lab=1, cex.axis=0.8, cex.strip=0.8, col.strip="gray95",
       strip=strip.custom(bg=col.strip), las=!fit, tck=c(1,fit)/2,
       tick.number=5, lty.grid=3, col.grid="gray", pch=16,
       cex.points=0.5, col.points="black", lty.lines=1, lwd.lines=2,
       col.lines=c("red","blue"), plot=TRUE, ...)
```

**Arguments**

|             |  |
|-------------|--|
| model       | fitted scape model containing element CLc and/or CLs.                              |
| what        | what to plot: "c"[ommercial] or "s"[urvey] catch at length.                        |
| fit         | whether to overlay fitted values on observed data.                                 |
| swap        | whether to swap lengths and years between axes or panels.                          |
| series      | string indicating which gear or survey to plot (first by default).                 |
| sex         | string indicating which sex to plot (both by default).                             |
| years       | vector of numbers indicating which years to plot (all by default).                 |
| lengths     | vector of numbers indicating which lengths to plot (all by default).               |
| axes        | whether to plot axis values.   |
| same.limits | whether panels should have same y-axis limits.                                     |
| log         | whether to log-transform values.   |
| base        | logarithm base.  |
| eps.log     | small number to add before log-transforming to avoid log 0.                        |
| main        | main title.  |
| xlab        | x-axis label.  |
| ylab        | y-axis label.  |
| cex.main    | size of main title.  |
| cex.lab     | size of axis labels.   |
| cex.axis    | size of tick labels.   |
| cex.strip   | size of strip labels.  |
| col.strip   | color of strip labels.   |
| strip       | logical flag (whether to plot strip labels), or a function passed to xyplot.       |
| las         | orientation of tick labels: 0=parallel, 1=horizontal, 2=perpendicular, 3=vertical. |
| tck         | tick mark length.  |
| tick.number | number of tick marks.  |
| lty.grid    | line type of gridlines.  |
| col.grid    | color of gridlines.  |
| pch         | symbol for points.   |



|                         |   |
|-------------------------|---|
| <code>cex.points</code> | size of points.   |
| <code>col.points</code> | color of points.  |
| <code>lty.lines</code>  | line type of main lines, possibly a vector where element 2 refers to males.   |
| <code>lwd.lines</code>  | line width of main lines, possibly a vector where element 2 refers to males.  |
| <code>col.lines</code>  | color of main lines, possibly a vector where element 2 refers to males.   |
| <code>plot</code>       | whether to draw plot.   |
| <code>...</code>        | passed to <code>xyplot</code> , <code>panel.xyplot</code> , <code>panel.superpose</code> , and <code>panel.superpose.2</code> . |

**Value**

When `plot=TRUE`, a trellis plot is drawn and a data frame is returned, containing the data used for plotting. When `plot=FALSE`, a trellis object is returned.

**Note**

The `Args` function from the **gdata** package is recommended for reviewing the arguments, instead of `args`.

**See Also**

[xyplot](#), [panel.xyplot](#), and [panel.superpose](#) are the underlying drawing functions.  
[plotCA](#), [plotCL](#), [plotIndex](#), and [plotLA](#) plot model fit and data.  
[plotB](#), [plotN](#), and [plotSel](#) plot derived quantities.  
[scape-package](#) gives an overview of the package.

**Examples**

```
plotCL(x.ling, fit=FALSE, strip=FALSE, series="1", sex="Female",
       xlab="Length (cm)", ylab="Year")

plotCL(x.oreo, xlab="Length (cm)", ylab="Proportion in catch")

plotCL(x.oreo, "s", layout=c(2,1), xlab="Length (cm)",
       ylab="Observed proportion in survey", cex.points=0.8,
       col.points=c("red","blue"), lty.lines=0)

plotCL(x.ling, fit=FALSE, series="2", xlab="Length (cm)",
       ylab="Observed proportion in trawl catch", tck=0.5)

plotCL(x.ling, series="2", swap=TRUE, lengths=70:150, lty.grid=0)
```

plotIndex

*Plot Abundance Index***Description**

Plot scape model fit to abundance index data.

**Usage**

```
plotIndex(model, what="s", series=NULL, axes=TRUE, same.limits=FALSE,
          between=list(x=axes,y=axes), ylim=NULL, q=1, bar=1, log=FALSE,
          base=10, main="", xlab="", ylab="", cex.main=1.2, cex.lab=1,
          cex.axis=0.8, cex.strip=0.8, col.strip="gray95",
          strip=strip.custom(bg=col.strip), las=1, tck=c(1,0)/2,
          tick.number=5, lty.grid=3, col.grid="white", pch=16,
          cex.points=1.2, col.points="black", lty.lines=1, lwd.lines=4,
          col.lines="dimgray", lty.bar=1, plot=TRUE, ...)
```

**Arguments**

|             |  |
|-------------|--|
| model       | fitted scape model containing element CPUE and/or Survey.  |
| what        | what to plot: "c"[ommercial] or "s"[urvey] abundance index.  |
| series      | vector of strings indicating which gears or surveys to plot (all by default).                                |
| axes        | whether to plot axis values.   |
| same.limits | whether panels should have same y-axis limits.   |
| between     | list with x and y indicating panel spacing.  |
| ylim        | vector with lower and upper y-axis limits.   |
| q           | denominator to scale the y axis, e.g. to vulnerable biomass. Similar to the div argument in plotN and plotB. |
| bar         | extent of error bars relative to standard error.   |
| log         | whether to log-transform values.   |
| base        | logarithm base.  |
| main        | main title.  |
| xlab        | x-axis label.  |
| ylab        | y-axis label.  |
| cex.main    | size of main title.  |
| cex.lab     | size of axis labels.   |
| cex.axis    | size of tick labels.   |
| cex.strip   | size of strip labels.  |
| col.strip   | color of strip labels.   |
| strip       | logical flag (whether to plot strip labels), or a function passed to xypLOT.                                 |

|             |   |
|-------------|---|
| las         | orientation of tick labels: 0=parallel, 1=horizontal, 2=perpendicular, 3=vertical.          |
| tck         | tick mark length.   |
| tick.number | number of tick marks.   |
| lty.grid    | line type of gridlines.   |
| col.grid    | color of gridlines.   |
| pch         | symbol for points.  |
| cex.points  | size of points.   |
| col.points  | color of points and error bars.   |
| lty.lines   | line type of main lines.  |
| lwd.lines   | line width of main lines.   |
| col.lines   | color of main lines.  |
| lty.bar     | line type of error bars.  |
| plot        | whether to draw plot.   |
| ...         | passed to <code>xyplot</code> , <code>panel.xyplot</code> , and <code>panel.xYplot</code> . |

**Value**

When `plot=TRUE`, a trellis plot is drawn and a data frame is returned, containing the data used for plotting. When `plot=FALSE`, a trellis object is returned.

**Note**

The `Args` function from the **gdata** package is recommended for reviewing the arguments, instead of `args`.

**See Also**

[xyplot](#), [panel.xyplot](#), and [panel.xYplot](#) are the underlying drawing functions.  
[plotCA](#), [plotCL](#), [plotIndex](#), and [plotLA](#) plot model fit and data.  
[plotB](#), [plotN](#), and [plotSel](#) plot derived quantities.  
[scape-package](#) gives an overview of the package.

**Examples**

```
plotIndex(x.cod, xlab="Year", ylab="Survey abundance index",
          strip=FALSE)

plotIndex(x.oreo, "c", series="Series 1-1", xlim=c(1981,1990))

plotIndex(x.oreo, "c", xlim=list(c(1981,1990),c(1992,2002)),
          xlab="Year", ylab="Observed CPUE",
          col.points=c("salmon","seagreen"), lty.lines=0)
```

plotLA

*Plot Length at Age***Description**

Plot scape model fit to length-at-age data.

**Usage**

```
plotLA(model, together=FALSE, sex=NULL, axes=TRUE, same.limits=TRUE,
        between=list(x=axes,y=axes), ylim=NULL, bands=1, main="",
        xlab="", ylab="", cex.main=1.2, cex.lab=1, cex.axis=0.8,
        cex.strip=0.8, col.strip="gray95",
        strip=strip.custom(bg=col.strip), las=1, tck=0, tick.number=5,
        lty.grid=3, col.grid="gray", pch=16, cex.points=0.5,
        col.points="black", lty.lines=1, lwd.lines=4,
        col.lines=c("red","blue"), lty.bands=2*(!together), lwd.bands=1,
        col.bands="black", plot=TRUE, ...)
```

**Arguments**

|             |  |
|-------------|--|
| model       | fitted scape model containing element LA.  |
| together    | whether to plot both sexes in one panel.   |
| sex         | string indicating which sex to plot (both by default).                             |
| axes        | whether to plot axis values.   |
| same.limits | whether panels should have same y-axis limits.                                     |
| between     | list with x and y indicating panel spacing.  |
| ylim        | vector with lower and upper y-axis limits.   |
| bands       | extent of error bands relative to standard error.                                  |
| main        | main title.  |
| xlab        | x-axis label.  |
| ylab        | y-axis label.  |
| cex.main    | size of main title.  |
| cex.lab     | size of axis labels.   |
| cex.axis    | size of tick labels.   |
| cex.strip   | size of strip labels.  |
| col.strip   | color of strip labels.   |
| strip       | logical flag (whether to plot strip labels), or a function passed to xypLOT.       |
| las         | orientation of tick labels: 0=parallel, 1=horizontal, 2=perpendicular, 3=vertical. |
| tck         | tick mark length.  |
| tick.number | number of tick marks.  |

|                         |  |
|-------------------------|--|
| <code>lty.grid</code>   | line type of gridlines.  |
| <code>col.grid</code>   | color of gridlines.  |
| <code>pch</code>        | symbol for points, possibly a vector where element 2 refers to males.        |
| <code>cex.points</code> | size of points, possibly a vector where element 2 refers to males.           |
| <code>col.points</code> | color of points, possibly a vector where element 2 refers to males.          |
| <code>lty.lines</code>  | line type of main lines, possibly a vector where element 2 refers to males.  |
| <code>lwd.lines</code>  | line width of main lines, possibly a vector where element 2 refers to males. |
| <code>col.lines</code>  | color of main lines, possibly a vector where element 2 refers to males.      |
| <code>lty.bands</code>  | line type of error bands.  |
| <code>lwd.bands</code>  | line width of error bands.   |
| <code>col.bands</code>  | color of error bands, possibly a vector where element 2 refers to males.     |
| <code>plot</code>       | whether to draw plot.  |
| <code>...</code>        | passed to <code>xyplot</code> and <code>panel.superpose.2</code> .           |

**Value**

When `plot=TRUE`, a trellis plot is drawn and a data frame is returned, containing the data used for plotting. When `plot=FALSE`, a trellis object is returned.

**Note**

The `Args` function from the **gdata** package is recommended for reviewing the arguments, instead of `args`.

**See Also**

[xyplot](#), [panel.xyplot](#), and [panel.superpose](#) are the underlying drawing functions.

[plotCA](#), [plotCL](#), [plotIndex](#), and [plotLA](#) plot model fit and data.

[plotB](#), [plotN](#), and [plotSel](#) plot derived quantities.

[scape-package](#) gives an overview of the package.

**Examples**

```
plotLA(x.oreo, xlab="Age", ylab="Length (cm)")

mykey <- list(text=list(lab=c("Female","Male")), space="right",
              lines=list(lwd=4,col=c("red","blue")))
plotLA(x.oreo, together=TRUE, xlab="Age", ylab="Length (cm)", pch=NA,
       key=mykey)

mykey <- list(text=list(lab=c("Female","Male")), space="right",
              points=list(pch=16,cex=0.5,col=c("red","blue")))
plotLA(x.oreo, together=TRUE, xlab="Age", ylab="Length (cm)",
       col.points=c("red","blue"), lty.lines=0, key=mykey)
```

---

plotN *Plot Numbers at Age*

---

### Description

Plot scape model predicted numbers at age.

### Usage

```
plotN(model, what="d", swap=FALSE, years=NULL, ages=NULL, axes=TRUE,
      same.limits=TRUE, div=1, log=FALSE, base=10, main="", xlab="",
      ylab="", cex.main=1.2, cex.lab=1, cex.axis=0.8, cex.strip=0.8,
      col.strip="gray95", strip=strip.custom(bg=col.strip),
      las=(what=="b"), tck=c(1,what=="b")/2, tick.number=10, lty.grid=3,
      col.grid="white", pch=16, cex.points=1, col.points="black",
      ratio.bars=3, col.bars="gray", plot=TRUE, ...)
```

### Arguments

|             |  |
|-------------|--|
| model       | fitted scape model.  |
| what        | what to plot: "d"[efault], "i"[initial year], "l"[last year], "r"[recruitment], "p"[panels], "b"[bubble plot]. |
| swap        | whether to swap ages and years between axes or panels.   |
| years       | vector of numbers indicating which years to plot (all by default).   |
| ages        | vector of numbers indicating which ages to plot (all by default).  |
| axes        | whether to plot axis values.   |
| same.limits | whether panels should have same y-axis limits.   |
| div         | denominator to shorten values on the y axis.   |
| log         | whether to log-transform values.   |
| base        | logarithm base.  |
| main        | main title.  |
| xlab        | x-axis label.  |
| ylab        | y-axis label.  |
| cex.main    | size of main title.  |
| cex.lab     | size of axis labels.   |
| cex.axis    | size of tick labels.   |
| cex.strip   | size of strip labels.  |
| col.strip   | color of strip labels.   |
| strip       | logical flag (whether to plot strip labels), or a function passed to xyplot.                                   |
| las         | orientation of tick labels: 0=parallel, 1=horizontal, 2=perpendicular, 3=vertical.                             |
| tck         | tick mark length.  |

|             |   |
|-------------|---|
| tick.number | number of tick marks.   |
| lty.grid    | line type of gridlines.   |
| col.grid    | color of gridlines.   |
| pch         | symbol for points.  |
| cex.points  | size of points.   |
| col.points  | color of points.  |
| ratio.bars  | width of bars.  |
| col.bars    | color of bars.  |
| plot        | whether to draw plot.   |
| ...         | passed to <code>xyplot</code> , <code>panel.barchart</code> , and <code>panel.xyplot</code> . |

### Details

The "d"[efault] plot is a combination of "i"[nitial year] and "r"[ecruitment].

### Value

When `plot=TRUE`, a trellis plot is drawn and a data frame is returned, containing the data used for plotting. When `plot=FALSE`, a trellis object is returned.

### Note

The `Args` function from the **gdata** package is recommended for reviewing the arguments, instead of `args`.

### See Also

[xyplot](#), [panel.xyplot](#), and [panel.barchart](#) are the underlying drawing functions.

[plotCA](#), [plotCL](#), [plotIndex](#), and [plotLA](#) plot model fit and data.

[plotB](#), [plotN](#), and [plotSel](#) plot derived quantities.

[scape-package](#) gives an overview of the package.

### Examples

```
plotN(x.cod, div=1000, xlab=c("Age (years)", "Year"),
      ylab="Individuals (million)")
```

```
plotN(x.cod, "l", div=1000, xlab="Age", ylab="Individuals (million)")
```

```
plotN(x.cod, "r", age=3, div=1000, xlim=c(1967,2002))
```

```
plotN(x.cod, "p", div=1000, ages=3:10, xlim=c(2,11), xlab="Age",
      ylab="Individuals (million)", cex.strip=0.7, cex.axis=0.7,
      tck=0.5)
```

```
plotN(x.cod, "b", xlab="Age (years)", ylab="Year", cex.points=0.7)
```

---

plotSel

*Plot Selectivity and Maturity*


---

### Description

Plot scape model predicted selectivity and observed maturity.

### Usage

```
plotSel(model, together=FALSE, series=NULL, sex=NULL, axes=TRUE,
        legend="bottom", main="", xlab="", ylab="", cex.main=1.2,
        cex.legend=1, cex.lab=1, cex.axis=0.8, cex.strip=0.8,
        col.strip="gray95", strip=strip.custom(bg=col.strip), las=1,
        tck=0, tick.number=5, lty.grid=3, col.grid="gray", pch="m",
        cex.points=1, col.points="black", lty.lines=1, lwd.lines=4,
        col.lines=c("red", "blue"), plot=TRUE, ...)
```

### Arguments

|             |  |
|-------------|--|
| model       | fitted scape model.  |
| together    | whether to plot gears in one panel.  |
| series      | vector of strings indicating which gears or surveys to plot (all by default).      |
| sex         | string indicating which sex to plot (both by default).                             |
| axes        | whether to plot axis values.   |
| legend      | legend location: "bottom", "left", "top", "right", or "" to suppress legend.       |
| main        | main title.  |
| xlab        | x-axis label.  |
| ylab        | y-axis label.  |
| cex.main    | size of main title.  |
| cex.legend  | size of legend text.   |
| cex.lab     | size of axis labels.   |
| cex.axis    | size of tick labels.   |
| cex.strip   | size of strip labels.  |
| strip       | logical flag (whether to plot strip labels), or a function passed to xypplot.      |
| col.strip   | color of strip labels.   |
| las         | orientation of tick labels: 0=parallel, 1=horizontal, 2=perpendicular, 3=vertical. |
| tck         | tick mark length.  |
| tick.number | number of tick marks.  |
| lty.grid    | line type of gridlines.  |
| col.grid    | color of gridlines.  |



|            |   |
|------------|---|
| pch        | symbol for points.  |
| cex.points | size of points.   |
| col.points | color of points.  |
| lty.lines  | line type of main lines.  |
| lwd.lines  | line width of main lines.   |
| col.lines  | color of main lines.  |
| plot       | whether to draw plot.   |
| ...        | passed to <code>xyplot</code> , <code>panel.points</code> , <code>panel.lines</code> , and <code>panel.superpose</code> . |

**Value**

When `plot=TRUE`, a trellis plot is drawn and a data frame is returned, containing the data used for plotting. When `plot=FALSE`, a trellis object is returned.

**Note**

The `Args` function from the **gdata** package is recommended for reviewing the arguments, instead of `args`.

**See Also**

[xyplot](#), [panel.points](#), [panel.lines](#), and [panel.superpose](#) are the underlying drawing functions.

[plotCA](#), [plotCL](#), [plotIndex](#), and [plotLA](#) plot model fit and data.

[plotB](#), [plotN](#), and [plotSel](#) plot derived quantities.

[scape-package](#) gives an overview of the package.

**Examples**

```
plotSel(x.ling, xlab="Age", ylab="Selectivity and maturity")

plotSel(x.cod, together=TRUE, xlab="Age\n", ylab="Selectivity",
        pch=NA, col.lines=c("coral", "navyblue"), strip=FALSE)
```

---

x.cod

*Cod Assessment*


---

**Description**

Stock assessment data and model fit for cod (*Gadus morhua*) in Icelandic waters, using a Coleraine statistical catch-at-age model.

This is a single-sex model with 10 age classes, the catch data starting in 1971 and ending in 2003. The model was fitted to three data components: survey abundance index, commercial catch at age, and survey catch at age.

**Usage**

x.cod

**Format**

List of class scape containing:

|        |   |
|--------|---|
| N      | predicted numbers at age  |
| B      | predicted biomass, recruitment, and observed landings (year things) |
| Se1    | predicted selectivity and observed maturity (age things)            |
| Dev    | predicted recruitment deviates from the stock-recruitment curve     |
| Survey | survey abundance index and fit                                      |
| CAC    | commercial C@A (catch at age) and fit                               |
| CAs    | survey C@A and fit  |

**Details**

Hilborn et al. (2003) give a general description of the Coleraine generalized model. Magnusson and Hilborn (2007) describe the model used in this assessment.

A maturity vector of zeros and ones was used to predict the biomass of age 4 and older, the quantity of main interest for the management of this stock.

Estimated parameters: R0, Rinit, uinit, Sleft[commercial], Sfull[c], Sleft[survey], Sfull[s], q, and 41 recruitment deviates.

**Note**

The list was imported from the file 'scape/example/cod.res' using importCol.

The functions `l1` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `l1(x.cod)`, `l1(x.cod$N)`, and `head(x.cod$N)`.

**Source**

Magnusson, A. (2003) *Coleraine assessment of the Icelandic cod stock*. ICES North Western Working Group (NWWG) WD 31.

Marine Research Institute (2003) *State of marine stocks in Icelandic waters 2002/2003*. Marine Research in Iceland 97.

**References**

Hilborn, R., Maunder, M., Parma, A., Ernst, B., Payne, J., and Starr, P. (2003) *Coleraine: A generalized age-structured stock assessment model*. User's manual version 2.0. University of Washington Report SAFS-UW-0116.

Magnusson, A. and Hilborn, R. (2007) What makes fisheries data informative? *Fish and Fisheries* **8**, 337–358.

**See Also**

[importCol](#) was used to import the fitted model.

[x.cod](#), [x.ling](#), [x.oreo](#), [x.saithe](#), and [x.sbw](#) are fitted scape models to explore.

[xmcnc](#) and [xproj](#) are MCMC results and projections for the [x.cod](#) model run.

[scape-package](#) gives an overview of the package.

**Examples**

```
plotB(x.cod)
plotCA(x.cod, "c")
plotCA(x.cod, "s")
plotIndex(x.cod, "s")
plotN(x.cod)
plotSel(x.cod)
```

---

x.ling

*Ling Assessment*


---

**Description**

Stock assessment data and model fit for ling (*Genypterus blacodes*) in New Zealand waters, using a Coleraine statistical catch-at-age model.

This is a two-sex model with 30 age classes and 29 length classes, the catch data starting in 1973 and ending in 2000. The model was fitted to five data components: longline abundance index, survey abundance index, survey catch at age, longline catch at length, and trawl catch at length.

**Usage**

```
x.ling
```

**Format**

List of class scape containing:

|        |   |
|--------|---|
| N      | predicted numbers at age  |
| B      | predicted biomass, recruitment, and observed landings (year things) |
| Sel    | predicted selectivity and observed maturity (age things)            |
| Dev    | predicted recruitment deviates from the stock-recruitment curve     |
| CPUE   | commercial abundance index and fit                                  |
| Survey | survey abundance index and fit                                      |
| CAs    | survey C@A (catch at age) and fit                                   |
| CLc    | commercial C@L (catch at length) and fit                            |

## Details

Hilborn et al. (2003) give a general description of the Coleraine generalized model.

Estimated parameters: R0, Rinit, Sleft[trawl], Sfemal[e][t], Smale[t], Sright[t], Sleft[longline], Sfemal[e][l], Smale[l], Sright[l], Sleft[survey], Sfemal[e][s], Smale[s], Sright[s], q[l], q[s], and 29 recruitment deviates.

## Note

The list was imported from the file 'scape/example/ling.res' using `importCol`.

The functions `ll` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `ll(x.ling)`, `ll(x.ling$N)`, and `head(x.ling$N)`.

## Source

Annala, J. H., Sullivan, K. J., O'Brien, C. J., and Smith, N. W. M., eds. (2001) *Report from the Fishery Assessment Plenary: Stock assessments and yield estimates*. Wellington: NIWA.

Magnusson, A. (2001) *SeaFIC assessment of Chatham Rise ling (LIN 3 and 4)*. Middle Depths Working Group Doc. 11. Report for the New Zealand Ministry of Fisheries.

## References

Hilborn, R., Maunder, M., Parma, A., Ernst, B., Payne, J., and Starr, P. (2003) *Coleraine: A generalized age-structured stock assessment model*. User's manual version 2.0. University of Washington Report SAFS-UW-0116.

## See Also

[importCol](#) was used to import the fitted model.

[x.cod](#), [x.ling](#), [x.oreo](#), [x.sai](#)[the](#), and [x.sbw](#) are fitted scape models to explore.

[scape-package](#) gives an overview of the package.

## Examples

```
plotB(x.ling)
plotCA(x.ling, "s")
plotCL(x.ling, "c", series="1")
plotCL(x.ling, "c", series="2")
plotIndex(x.ling, "c")
plotIndex(x.ling, "s")
plotN(x.ling)
plotSel(x.ling)
```

---

x.oreo

*Oreo Assessment*


---

**Description**

Stock assessment data and model fit for smooth oreo (*Pseudocyttus maculatus*) in New Zealand waters, using a Coleraine statistical catch-at-age model.

This is a two-sex model with 80 age classes and 44 length classes, the catch data starting in 1979 and ending in 2001. The model was fitted to seven data components: pre-GPS commercial abundance index, post-GPS commercial abundance index, survey abundance index, commercial catch at length, survey catch at length, female length at age, and male length at age.

**Usage**

```
x.oreo
```

**Format**

List of class scape containing:

|        |   |
|--------|---|
| N      | predicted numbers at age  |
| B      | predicted biomass, recruitment, and observed landings (year things) |
| Se1    | predicted selectivity and observed maturity (age things)            |
| CPUE   | commercial abundance index and fit                                  |
| Survey | survey abundance index and fit                                      |
| CLc    | commercial C@L (catch at length) and fit                            |
| CLs    | survey C@L and fit  |
| LA     | observed L@A (length at age)  |

**Details**

Hilborn et al. (2003) give a general description of the Coleraine generalized model.

Since relatively few smooth oreo individuals have been aged, this assessment admits uncertainty about the von Bertalanffy growth curve, which is estimated for each sex. The acoustic survey abundance estimate is considered absolute, so `q[survey]` is fixed at 1.

Estimated parameters: `R0`, `Sfull[commercial]`, `Sfull[survey]`, `q[pre-GPS]`, `q[post-GPS]`, `L80female`, `L80male`, `Kfemale`, `Kmale`, `CVfemale`, and `CVmale`.

**Note**

The list was imported from the files ‘scape/example/oreo.res’, ‘oreo.txt’, and ‘1\\_at\\_age.dat’ using `importCol`.

The functions `l1` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `l1(x.oreo)`, `l1(x.oreo$N)`, and `head(x.oreo$N)`.

## Source

Annala, J. H., Sullivan, K. J., O'Brien, C. J., Smith, N. W. M., and Grayling S. M., eds. (2003) *Report from the Fishery Assessment Plenary: Stock assessments and yield estimates*. Wellington: Ministry of Fisheries.

## References

Hilborn, R., Maunder, M., Parma, A., Ernst, B., Payne, J., and Starr, P. (2003) *Coleraine: A generalized age-structured stock assessment model*. User's manual version 2.0. University of Washington Report SAFS-UW-0116.

Magnusson, A. (2003) *Stock assessment of Chatham Rise smooth oreo (SSO4)*. Deepwater Working Group Doc. 16. Report for the New Zealand Ministry of Fisheries.

## See Also

[importCol](#) was used to import the fitted model.

[x.cod](#), [x.ling](#), [x.oreo](#), [x.saithe](#), and [x.sbw](#) are fitted scape models to explore.

[scape-package](#) gives an overview of the package.

## Examples

```
plotB(x.oreo)
plotCL(x.oreo, "c")
plotCL(x.oreo, "s")
plotIndex(x.oreo, "c")
plotIndex(x.oreo, "s")
plotLA(x.oreo)
plotN(x.oreo)
plotSel(x.oreo)
```

---

x.saithe

*Saithe Assessment*

---

## Description

Stock assessment data and model fit for saithe (*Pollachius virens*) in Icelandic waters, using an ADCAM-type (separable) catch-at-age model.

This is a single-sex model with 14 age classes, the catch data starting in 1980 and ending in 2014. The model was fitted to two data components: survey abundance index and commercial catch at age.

## Usage

```
x.saithe
```

## Format

List of class scape containing:

|        |   |
|--------|---|
| N      | predicted numbers at age  |
| B      | predicted biomass, recruitment, and observed landings (year things) |
| Sel    | predicted selectivity and observed maturity (age things)            |
| Dev    | predicted recruitment deviates from the stock-recruitment curve     |
| Survey | survey abundance index and fit                                      |
| C@C    | commercial C@A (catch at age) and fit                               |
| C@S    | survey C@A and fit  |

## Details

Bjornsson and Magnusson (2009) give a general description of the ADCAM modelling platform. The specific model used in this assessment is described in the ICES (2015) assessment report.

Fleet selectivity is modelled with three periods: 1980-1996, 1997-2003, and 2004 onwards.

## Note

The list was imported from results files in the directory 'scape/example/saithe' using `importADCAM`.

The functions `ll` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `ll(x.saithe)`, `ll(x.saithe$N)`, and `head(x.saithe$N)`.

## Source

ICES (2015) *Report of the North-Western Working Group (NWWG)*. ICES CM 2015/ACOM:07.

## References

Bjornsson, H. and A. Magnusson. (2009) *ADCAM user manual (draft version)*. ICES CM 2009/ACOM:56 Annex 6.

## See Also

[importADCAM](#) was used to import the fitted model.

[x.cod](#), [x.ling](#), [x.oreo](#), [x.saithe](#), and [x.sbw](#) are fitted scape models to explore.

[scape-package](#) gives an overview of the package.

## Examples

```
plotB(x.saithe)
plotCA(x.saithe, "c")
plotCA(x.saithe, "s")
plotIndex(x.saithe, "s")
plotN(x.saithe)
plotSel(x.saithe)
```

---

 x.sbw

*Whiting Assessment*


---

**Description**

Stock assessment data and model fit for southern blue whiting (*Micromesistius australis*) in New Zealand waters, using a Coleraine statistical catch-at-age model.

This is a single-sex model with 11 age classes, the catch data starting in 1979 and ending in 2002. The model was fitted to two data components: survey abundance index and commercial catch at age.

**Usage**

x.sbw

**Format**

List of class scape containing:

|        |   |
|--------|---|
| N      | predicted numbers at age  |
| B      | predicted biomass, recruitment, and observed landings (year things) |
| Sel    | predicted selectivity and observed maturity (age things)            |
| Dev    | predicted recruitment deviates from the stock-recruitment curve     |
| Survey | survey abundance index and fit                                      |
| CAC    | commercial C@A (catch at age) and fit                               |

**Details**

Hilborn et al. (2003) give a general description of the Coleraine generalized model.

The survey abundance index was preprocessed so that it contains only age 4 and older.

Estimated parameters: R0, Rinit, Rplus, Sleft[commercial], Sfull[c], q, and 33 recruitment deviates.

**Note**

The list was imported from the file 'scape/example/sbw.res' using importCol.

The functions `ll` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `ll(x.sbw)`, `ll(x.sbw$N)`, and `head(x.sbw$N)`.

**Source**

Annala, J. H., Sullivan, K. J., O'Brien, C. J., Smith, N. W. M., and Grayling S. M., eds. (2003) *Report from the Fishery Assessment Plenary: Stock assessments and yield estimates*. Wellington: Ministry of Fisheries.



## References

Branch, T. A., Magnusson, A., Hilborn, R., and Starr, P. J. (2002) *Stock assessment of the Campbell Island Rise population of southern blue whiting (*Micromesistius australis*) for the 2000–01 fishing season*. University of Washington Report SAFS-UW-0107.

Hilborn, R., Maunder, M., Parma, A., Ernst, B., Payne, J., and Starr, P. (2003) *Coleraine: A generalized age-structured stock assessment model*. User's manual version 2.0. University of Washington Report SAFS-UW-0116.

Magnusson, A. and Hilborn, R. 2004. *What is it in fisheries data that tells us about population abundance?* Poster presented at the 4th World Fisheries Congress, Vancouver, BC.

## See Also

[importCol](#) was used to import the fitted model.

[x.cod](#), [x.ling](#), [x.oreo](#), [x.saithe](#), and [x.sbw](#) are fitted scape models to explore.

[scape-package](#) gives an overview of the package.

## Examples

```
plotB(x.sbw)
plotCA(x.sbw, "c")
plotIndex(x.sbw, "s")
plotN(x.sbw)
plotSel(x.sbw)
```

---

xmcmc

MCMC Results from Cod Assessment

---

## Description

Markov chain Monte Carlo results from stock assessment of cod (*Gadus morhua*) in Icelandic waters.

## Usage

```
xmcmc
```

## Format

List containing four data frames:

- L likelihood components: CAc (commercial catch at age), CAs (survey catch at age), Survey (survey abundance index), Prior
- P estimated parameters: R0 (average virgin recruitment), Rinit (initial recruitment scaler), uinit (initial harvest rate), cSle
- B predicted biomass (age 4+) by year.
- R predicted recruitment by year.

**Details**

See the [x.cod](#) help page for details about the data and model.

**Note**

The list was imported from the files 'mcmclike.out', 'params.pst', 'spawbiom.pst' and 'recruits.pst', using the `importMCMC()` function. These files can be found in the 'scape/example/mcmc' directory.

The functions `l1` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `l1(xmcmc)`, `l1(xmcmc$P)`, and `head(xmcmc$P)`.

The **plotMCMC** package is recommended for plotting MCMC diagnostics and posteriors.

**References**

Magnusson, A., Punt, A. E., and Hilborn, R. (2013) Measuring uncertainty in fisheries stock assessment: the delta method, bootstrap, and MCMC. *Fish and Fisheries* **14**, 325–342.

**See Also**

[importMCMC](#) was used to import the MCMC results.

`xmcmc` and [xproj](#) are MCMC results and projections for the [x.cod](#) model run.

[scape-package](#) gives an overview of the package.

**Examples**

```
# See examples in package 'plotMCMC'
```

---

xproj

*MCMC Projections from Cod Assessment*

---

**Description**

Markov chain Monte Carlo projections from stock assessment of cod (*Gadus morhua*) in Icelandic waters.

**Usage**

```
xproj
```

**Format**

List containing two lists:

- B projected biomass by year, given a constant harvest rate policy: "0", "0.05", ..., "0.50".
- Y projected catch by year, given a constant harvest rate policy: "0", "0.05", ..., "0.50".

## Details

MCMC projections can be used to evaluate the medium-term outcome of harvest policies (in this case, a certain fixed harvest rate), given the uncertainty about parameter values and random future recruitment.

See the [x.cod](#) help page for details about the data and model.

## Note

The list was imported from the files 'strategy.out', 'projspbm.out' and 'procatch.out', using the `importProj()` function. These files can be found in the 'scape/example/mcmc' directory.

The functions `l1` (package **gdata**) and `head` are recommended for browsing nested objects, e.g. `l1(xproj)`, `l1(xproj$B)`, `l1(xproj$B$"0.25")`, and `head(xproj$B$"0.25")`.

The **plotMCMC** package is recommended for plotting MCMC diagnostics and posteriors.

## References

Magnusson, A., Punt, A. E., and Hilborn, R. (2013) Measuring uncertainty in fisheries stock assessment: the delta method, bootstrap, and MCMC. *Fish and Fisheries* **14**, 325–342.

## See Also

[importProj](#) was used to import the MCMC projections.

[xmcmc](#) and `xproj` are MCMC results and projections for the [x.cod](#) model run.

[scape-package](#) gives an overview of the package.

## Examples

```
# See examples in package 'plotMCMC'
```

# Index

estN, [2](#), [3](#), [7–10](#), [12](#), [13](#), [19](#)  
estSigmaI, [2](#), [5](#), [6](#), [9–13](#), [19](#)  
estSigmaR, [2](#), [5](#), [7](#), [8](#), [8](#), [10](#), [12](#), [13](#), [19](#)

getN, [2](#), [5](#), [8](#), [9](#), [10](#), [13](#), [19](#)  
getSigmaI, [2](#), [5](#), [8–10](#), [11](#), [12](#), [13](#), [19](#)  
getSigmaR, [2](#), [5](#), [8–10](#), [12](#), [12](#), [19](#)

importADCAM, [2](#), [13](#), [15](#), [39](#)  
importCol, [2](#), [14](#), [14](#), [35](#), [36](#), [38](#), [41](#)  
importMCMC, [3](#), [16](#), [18](#), [42](#)  
importProj, [3](#), [17](#), [17](#), [43](#)  
iterate, [3](#), [5](#), [8](#), [9](#), [18](#)

panel.barchart, [21](#), [31](#)  
panel.lines, [33](#)  
panel.points, [33](#)  
panel.superpose, [21](#), [23](#), [25](#), [29](#), [33](#)  
panel.xyplot, [27](#)  
panel.xyplot, [23](#), [25](#), [27](#), [29](#), [31](#)  
plotB, [2](#), [9](#), [19](#), [23](#), [25](#), [27](#), [29](#), [31](#), [33](#)  
plotCA, [2](#), [5](#), [21](#), [21](#), [25](#), [27](#), [29](#), [31](#), [33](#)  
plotCL, [2](#), [5](#), [21](#), [23](#), [23](#), [27](#), [29](#), [31](#), [33](#)  
plotIndex, [2](#), [8](#), [21](#), [23](#), [25](#), [26](#), [29](#), [31](#), [33](#)  
plotLA, [2](#), [21](#), [23](#), [25](#), [27](#), [28](#), [31](#), [33](#)  
plotN, [2](#), [9](#), [21](#), [23](#), [25](#), [27](#), [29](#), [30](#), [33](#)  
plotSel, [2](#), [21](#), [23](#), [25](#), [27](#), [29](#), [31](#), [32](#)

read.table, [14](#), [15](#), [17](#), [18](#)  
readLines, [14](#), [15](#), [17](#), [18](#)

scan, [14](#), [15](#), [17](#), [18](#)  
scape (scape-package), [2](#)  
scape-package, [2](#)

x.cod, [3](#), [15](#), [33](#), [36](#), [38](#), [39](#), [41–43](#)  
x.ling, [3](#), [15](#), [35](#), [35](#), [38](#), [39](#), [41](#)  
x.oreo, [3](#), [15](#), [35](#), [36](#), [37](#), [39](#), [41](#)  
x.saithe, [3](#), [14](#), [35](#), [36](#), [38](#), [38](#), [41](#)  
x.sbw, [3](#), [15](#), [35](#), [36](#), [38](#), [39](#), [40](#)  
xmcmc, [3](#), [17](#), [35](#), [41](#), [43](#)

xproj, [3](#), [18](#), [35](#), [42](#), [42](#)  
xyplot, [21](#), [23](#), [25](#), [27](#), [29](#), [31](#), [33](#)