

Package ‘shape’

January 2, 2012

Version 1.3.4

Date 2009-07-01

Title Functions for plotting graphical shapes, colors

Author Karline Soetaert <k.soetaert@nioo.knaw.nl>

Maintainer Karline Soetaert <k.soetaert@nioo.knaw.nl>

Depends R (>= 2.01), stats

Description Functions for plotting graphical shapes such as ellipses,circles, cylinders, arrows, ... Support for the book “A practical guide to ecological modelling - using R as a simulation platform” by Karline Soetaert and Peter M.J. Herman (2009). Springer. Includes demo(colorshapes)

License GPL (>= 3)

LazyData yes

Repository CRAN

Repository/R-Forge/Project diagram

Repository/R-Forge/Revision 42

Date/Publication 2011-08-11 10:07:45

R topics documented:

shape-package	2
A4	3
Arrowhead	4
Arrows	5
colorlegend	8
cylindersegment	9
drapecol	10
emptyplot	11

femmecol	12
filledcircle	13
filledcylinder	14
filledellipse	16
filledmultigonal	17
filledrectangle	19
filledshape	21
getellipse	23
greycol	24
intpalette	25
plotcircle	26
plotellipse	27
rotatexy	29
roundrect	30
shadepalette	31
textflag	32
writelabel	33

Index 34

shape-package	<i>Functions for plotting graphical shapes, colors</i>
---------------	--

Description

Functions for plotting graphical shapes such as ellipses, circles, cylinders, arrows, ...

Support for the book "A practical guide to ecological modelling - using R as a simulation platform" by Karline Soetaert and Peter M.J. Herman (2009). Springer.

Details

Package: shape
 Type: Package
 Version: 1.3.4
 Date: 2011-07-30
 License: GNU Public License 3 or above

This package is used in R-package ecolMod, which includes many more examples.

See also R-package diagram.

Changes in version 1.3.4: more consistent drawing of ellipse and circle segments, (functions getellipse, getcircle), added textflag. (both suggested by Tom Wilson)

Author(s)

Karline Soetaert (Maintainer)

See Also

[A4](#), [writelabel](#), [emptyplot](#), [drapecol](#), [femmecol](#), [intpalette](#), [shadepalette](#), [colorlegend](#), [greycol](#), [rotatexy](#), [Arrowhead](#), [Arrows](#), [cylindersegment](#), [filledcylinder](#), [filledcircle](#), [filledellipse](#), [filledmultigonal](#), [filledrectangle](#), [filledshape](#), [getellipse](#), [plotcircle](#), [plotellipse](#), [roundrect](#), [textflag](#).

Examples

```
## Not run:
## show examples (see respective help pages for details)
example(rotatexy)
example(filledshape)

## run demos
demo("colorshapes") # creating colored shapes

## open the directory with source code of demos
browseURL(paste(system.file(package="shape"), "/demo", sep=""))

## show package vignette
vignette("shape")
edit(vignette("shape"))
browseURL(paste(system.file(package="shape"), "/doc", sep=""))

## End(Not run)
```

A4

opens A4-sized window

Description

opens a graphics window, 8.5 inches wide, 11 inches high

Usage

A4 (...)

Arguments

... arguments passed to R-function X11.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

Arrowhead *adds arrowheads to a plot*

Description

adds one or more arrowheads to a plot; shape is either curved, a triangle, a circle or ellipse.

Usage

```
Arrowhead(x0, y0, angle = 0, arr.length = 0.4,
          arr.width = arr.length/2, arr.adj = 0.5,
          arr.type = "curved", lcol = "black", lty = 1,
          arr.col = lcol, arr.lwd = 2, npoint = 5)
```

Arguments

<code>x0</code>	x-coordinates of points at which to draw arrowhead; either one value or a vector.
<code>y0</code>	y-coordinates of points at which to draw arrowhead; either one value or a vector.
<code>angle</code>	angle of arrowhead (anti-clockwise, relative to x-axis), in degrees [0,360]; either one value or a vector.
<code>arr.length</code>	approximate length of arrowhead, in cm; either one value or a vector.
<code>arr.width</code>	approximate width of arrowhead, in cm; either one value or a vector.
<code>arr.adj</code>	0,0.5,1 specifying the adjustment of the arrowhead.
<code>arr.type</code>	type of arrowhead to draw, one of "curved", "triangle", "circle", "ellipse".
<code>lcol</code>	line color specifications; either one value or a vector.
<code>lty</code>	line type specifications; either one value or a vector.
<code>arr.col</code>	color of arrowhead; either one value or a vector.
<code>arr.lwd</code>	line width of arrowhead.
<code>npoint</code>	only if <code>arr.type = "curved"</code> : number of points to draw the curve; increase for smoother arrowheads

Details

`x0`, `y0`, `angle`, `arr.length`, `arr.width`, `lcol`, `lty` and `arr.col` can be a vector, of the same length.

- if `arr.adj = 0.5`, then the centre of the arrowhead is at the point at which it is drawn.
- `arr.adj = 1` causes the tip of the arrowhead to touch the point.
- `arr.adj = 0` causes the base of the arrowhead to touch the point.

The type of the arrowhead is set with `arr.type` which can take the values:

- "triangle": uses filled triangle
- "curved" : draws arrowhead with curved edges
- "circle" : draws circular head (where `arr.width=arr.length`)
- "ellipse" : draws ellipsoid head

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[Arrows](#)

Examples

```
emptyplot(main = "Arrowhead")
Arrowhead(x0 = runif(10), y0 = runif(10), angle = runif(10)*360,
          arr.length = 0.3, arr.type = "circle", arr.col = "green")
Arrowhead(x0 = runif(10), y0 = runif(10), angle = runif(10)*360,
          arr.length = 0.4, arr.type = "curved", arr.col = "red")
Arrowhead(x0 = runif(10), y0 = runif(10), angle = runif(10)*360,
          arr.length = runif(10), arr.type = "triangle",
          arr.col = rainbow(10))
```

Arrows

adds arrows with improved arrowhead to a plot

Description

adds one or more arrows to a plot; arrowhead shape is either curved, a triangle, a circle or simple

Usage

```
Arrows(x0, y0, x1, y1, code = 2, arr.length = 0.4,
       arr.width = arr.length/2, arr.adj = 0.5, arr.type = "curved",
       segment = TRUE, col = "black", lcol = col, lty = 1, arr.col = lcol,
       lwd = 2, arr.lwd = lwd, ...)
```

Arguments

x0	x-coordinates of points <i>*from*</i> which to draw arrows; either one value or a vector.
y0	y-coordinates of points <i>*from*</i> which to draw arrows; either one value or a vector.
x1	x-coordinates of points <i>*to*</i> which to draw arrows; either one value or a vector.
y1	y-coordinates of points <i>*to*</i> which to draw arrows; either one value or a vector.
code	integer code determining kind of arrows to draw.
arr.length	approximate length of arrowhead, in cm; either one value or a vector.
arr.width	approximate width of arrowhead, in cm; either one value or a vector.
arr.adj	0,0.5,1 specifying the adjustment of the arrowhead.

<code>arr.type</code>	type of arrowhead to draw, one of "simple", "curved", "triangle", "circle", "ellipse" or "T".
<code>segment</code>	logical specifying whether or not to draw line segments.
<code>col</code>	general line color specification; one value or a vector.
<code>lcol</code>	line color specifications; either one value or a vector. ignored when <code>arr.type = "simple" or "T"</code> - use "col"
<code>lty</code>	line type specifications; either one value or a vector.
<code>arr.col</code>	color of arrowhead; either one value or a vector.
<code>lwd</code>	general line width specification, used when <code>arr.type = "simple" or "T"</code>
<code>arr.lwd</code>	line width of arrowhead.
<code>...</code>	arguments passed to <code>lines</code> or <code>segments</code> function.

Details

`x0`, `y0`, `x1`, `y1`, `arr.length`, `arr.width`, `arr.adj`, `lcol`, `lty` and `arr.col` can be a vector, of the same length.

For each 'i', an arrow is drawn between the point '(x0[i], y0[i])' and the point '(x1[i], y1[i])'.

- If `code=1` an arrowhead is drawn at '(x0[i], y0[i])'
- if `code=2` an arrowhead is drawn at '(x1[i], y1[i])'
- If `code=3` an arrowhead is drawn at both ends of the arrow
- unless `arr.length = 0`, when no head is drawn.
- If `arr.adj = 0.5` then the centre of the arrowhead is at the point at which it is drawn.
- `arr.adj = 1` causes the tip of the arrowhead to touch the point.
- `arr.adj = 2` causes the base of the arrowhead to touch the point.

The type of the arrowhead is set with `arr.type` which can take the values:

- "simple" : uses comparable R function [arrows](#)
- "triangle": uses filled triangle
- "curved" : draws arrowhead with curved edges
- "circle" : draws circular head
- "ellipse" : draws ellipse head
- "T" : draws T-shaped (blunt) head

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[arrows](#) the comparable R function

[Arrowhead](#)

Examples

```

xlim <- c(-5 , 5)
ylim <- c(-10, 10)
plot(0, type = "n", xlim = xlim, ylim = ylim,
     main = "Arrows, type = 'curved'")
x0 <- runif(100, xlim[1], xlim[2])
y0 <- runif(100, ylim[1], ylim[2])
x1 <- x0+runif(100, -1, 1)
y1 <- y0+runif(100, -1, 1)
Arrows(x0, y0, x1, y1, arr.length = runif(100), code = 2,
       arr.type = "curved", arr.col = 1:100, lcol = 1:100)

plot(0, type = "n", xlim = xlim, ylim = ylim,
     main = "Arrows, type = 'circle'")
x0 <- runif(100, xlim[1], xlim[2])
y0 <- runif(100, ylim[1], ylim[2])
x1 <- x0 + runif(100, -1, 1)
y1 <- y0 + runif(100, -1, 1)
Arrows(x0, y0, x1, y1, arr.length = 0.2, code = 3,
       arr.type = "circle", arr.col = "grey")

plot(0, type = "n", xlim = xlim, ylim = ylim,
     main = "Arrows, type = 'ellipse'")
Arrows(x0, y0, x1, y1, arr.length = 0.2, arr.width = 0.5,
       code = 3, arr.type = "ellipse", arr.col = "grey")

curve(expr = sin(x), 0, 2*pi+0.25, main = "Arrows")
x <- seq(0, 2*pi, length.out = 10)
xd <- x + 0.025
Arrows(x, sin(x), xd, sin(xd), type = "triangle",
       arr.length = 0.5, segment = FALSE)

xx <- seq(0, 10*pi, length.out = 1000)
plot(sin(xx)*xx, cos(xx)*xx, type = "l", axes = FALSE,
     xlab = "", ylab = "", main = "Arrows, type = 'curved'")
x <- seq(0, 10*pi, length.out = 20)
x1 <- sin(x)*x
y1 <- cos(x)*x
xd <- x+0.01
x2 <- sin(xd)*xd
y2 <- cos(xd)*xd
Arrows(x1, y1, x2, y2, arr.type = "curved", arr.length = 0.4,
       segment = FALSE, code = 1, arr.adj = 0.5 )

plot(sin(xx)*xx, cos(xx)*xx, type = "l", axes = FALSE,
     xlab = "", ylab = "", main = "Arrows, type = 'T'")
Arrows(x1, y1, x2, y2, arr.type = "T", arr.length = 0.4,
       code = 1, arr.lwd = 2)

```

colorlegend *adds a color legend to a plot.*

Description

Adds a color legend to a plot.

Usage

```
colorlegend(col = femmecol(100), zlim, zlevels = 5, dz = NULL,
            zval = NULL, log = FALSE, posx = c(0.9, 0.93),
            posy = c(0.05, 0.9), main = NULL, main.cex = 1.0,
            main.col = "black", lab.col = "black",
            digit = 0, left = FALSE, ...)
```

Arguments

col	color palette to be used; also allowed are two extremes or one value.
zlim	two-valued vector, the minimum and maximum z values.
zlevels	number of z-levels, one value, ignored if dz or zval not equal to NULL.
dz	increment in legend values, one value; ignored if zval not equal to NULL.
zval	a vector of z-values to label legend.
log	logical indicating whether to log transform or not.
posx	relative position of left and right edge of color bar on first axis, [0,1].
posy	relative position on lower and upper edge of color bar on second axis, [0,1].
main	main title, written above the color bar.
main.cex	relative size of main title.
main.col	color of main title.
lab.col	color of labels.
digit	number of significant digits in labels.
left	logical indicating whether to put the labels on the right (TRUE) or on the left (FALSE).
...	arguments passed to R-function text when writing labels.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

Examples

```

emptyplot(main = "colorlegend")
colorlegend(zlim = c(0, 10))
colorlegend(posx = c(0.8, 0.83), col = greycol(100),
            zlim = c(0, 1), digit = 1)
colorlegend(posx = c(0.7, 0.73), left = TRUE, col = rainbow(100),
            zlim = c(0, 10), digit = 1, dz = 2.5)
colorlegend(posx = c(0.5, 0.53),
            col = intpalette(c("red", "yellow", "black"), 100),
            zlim = c(0, 20), zval = c(1, 3, 7, 15))
colorlegend(posy = c(0.0, 0.15), posx = c(0.2, 0.3),
            col = rainbow(100), zlim = c(0, 1),
            zlevels = NULL, main = "rainbow")
colorlegend(posy = c(0.25, 0.4), posx = c(0.2, 0.3),
            zlim = c(0, 1), zlevels = NULL, main = "femmecol")
colorlegend(posy = c(0.5, 0.65), posx = c(0.2, 0.3),
            col = terrain.colors(100), zlim = c(0, 1),
            zlevels = NULL, main = "terrain.colors")
colorlegend(posy = c(0.75, 0.9), posx = c(0.2, 0.3),
            col = heat.colors(100), zlim = c(0, 1),
            zlevels = NULL, main = "heat.colors")

```

cylindersegment	<i>adds part of a cylinder to a plot</i>
-----------------	--

Description

adds a segment of a cylinder to a plot

Usage

```

cylindersegment(rx = 1, ry = rx, from = pi, to = 3*pi/2, len = 1,
               mid = c(0,0), angle = 0, dr = 0.01, col = "black",
               delt = 1.0, ...)

```

Arguments

rx	horizontal radius of full cylinder.
ry	vertical radius of full cylinder.
from	start radius of segment, radians.
to	end radius of segment, radians.
len	cylinder length.
mid	midpoint of cylinder.
angle	rotation angle, degrees.
dr	size of segments, in radians, to draw top/bottom ellipse (decrease for smoother).
col	color of slice.
delt	increase factor, from left to right.
...	arguments passed to polygon function.

Details

When `angle = 0` (the default), the `cylindersegment` is parallel to the x-axis.

`rx` and `ry` are the horizontal and vertical radiusses of the bordering ellipses. Here "horizontal" and "vertical" denote the position BEFORE rotation

if `delt > 1`, the width of the cylinder will increase from left to right.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[filledcylinder](#)

Examples

```
emptyplot(main = "cylindersegment")
cylindersegment(mid = c(0.1, 0.5), rx = 0.1, ry = 0.1,
  from = pi, to = 3*pi/2, col = "blue",
  len = 0.5, delt = 1.1, lwd = 2, angle = 90)
cylindersegment(mid = c(0.8, 0.5), rx = 0.1, ry = 0.1,
  from = 0, to = pi/2, col = "red", len = 0.5,
  delt = 1.0, lwd = 2, angle = 45)
cylindersegment(mid = c(0.5, 0.5), rx = 0.1, ry = 0.1,
  from = pi/2, to = pi, col = "lightblue",
  len = 0.2, delt = 1.5, lwd = 2)
for (i in seq(0.1, 0.9, 0.1))
  cylindersegment(mid = c(i, 0.9), rx = 0.035, ry = 0.05,
    from = pi/2, to = 3*pi/2, col = "darkblue",
    len = 0.1, angle = 90)
```

drapecol

draping colors over a persp plot

Description

generates color(s) that will appear on the surface facets of a "persp" plot.

Usage

```
drapecol(A, col = femmecol(100), NAcol = "white")
```

Arguments

<code>A</code>	matrix with input grid.
<code>col</code>	color palette.
<code>NAcol</code>	color of NA elements.

Value

a vector of character strings giving the colors in hexadecimal format, one for each surface facet.

Note

This function is inspired by a similar function in package `fields`, unfortunately made unavailable in most recent version of `fields`

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>.

See Also

[persp](#)

Examples

```
persp(volcano, theta = 135, phi = 30, col = drapecol(volcano),
      main = "drapecol")
persp(volcano, theta = 135, phi = 30, col = drapecol(volcano),
      border = NA, main = "drapecol")
```

emptyplot	<i>open a plot without axes, labels,...</i>
-----------	---

Description

Creates a plotting region, bounded by `xlim` and `ylim`; without axes, labels, titles, useful for plotting shapes.

Usage

```
emptyplot(xlim = c(0, 1), ylim = xlim, asp = 1, frame.plot = FALSE,
          col = NULL, ...)
```

Arguments

<code>xlim</code>	the x limits (min,max) of the plot.
<code>ylim</code>	the y limits (min,max) of the plot.
<code>asp</code>	the y/x aspect ratio.
<code>frame.plot</code>	to toggle off drawing of a bounding box.
<code>col</code>	the background color.
<code>...</code>	arguments passed to R-function plot .

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[plot](#), [plot.default](#)

femmecol

red-green-blue color palette

Description

Creates a vector of (n) contiguous colors (darkblue-blue-cyan-yellow-red-darkred).

Usage

```
femmecol(n = 100)
```

Arguments

n number of colors.

Value

a vector of character strings giving the colors in hexadecimal format

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>.

See Also

[rainbow](#), [heat.colors](#), [topo.colors](#), the comparable R-functions.
[intpalette](#), [shadepalette](#)

Examples

```
filled.contour(volcano, color = femmecol, asp = 1, main = "femmecol")
femmecol(10)
image(matrix(nrow = 1, ncol = 100, data = 1:100),
       col = femmecol(100), main = "femmecol")
```

filledcircle	<i>adds colored circle to a plot</i>
--------------	--------------------------------------

Description

plots (part of) outer and inner circle and colors inbetween; color can be a palette.

Usage

```
filledcircle(r1 = 1, r2 = 0, mid = c(0,0), dr = 0.01, from = -pi, to = pi,  
            col = femmecol(100), values = NULL, zlim = NULL, lwd = 2, lcol = NA, ...)
```

Arguments

r1	radius of outer circle.
r2	radius of inner circle.
mid	midpoint of circle.
dr	size of segments, in radians, to draw circle (decrease for smoother).
from	starting angle for circle segment, radians.
to	final angle for circle segment, radians. The segment is drawn counterclockwise. The default is to draw a full circle.
col	color palette to be used; also allowed are two extremes or one value.
values	if not NULL, a matrix providing (radius,z-values) couples, used for coloring. .
zlim	Only if values is not NULL: the minimum and maximum z values for which colors should be plotted, defaulting to the range of the finite values of the second column of values.
lwd	width of external line.
lcol	line color.
...	arguments passed to R-function polygon .

Details

see [filledellipse](#) for details

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[filledshape](#), [filledcylinder](#), [filledellipse](#)

Examples

```

color <-graycol(n = 50)
dr    <- 0.05
emptyplot(xlim = c(-2, 2), col = color[length(color)],
          main = "filledcircle")
filledcircle(r1 = 1, mid = c(1, 1), dr = dr,
             col = shadepalette(endcol = "darkblue"))
filledcircle(r1 = 1, mid = c(-1, -1), dr = dr,
             col = shadepalette(endcol = "darkred"))
filledcircle(r1 = 1, r2 = 0.5, mid = c(0, 0), dr = dr,
             col = c(rev(color), color))
filledcircle(r1 = 1, mid = c(1, -1), dr = dr,
             col = intpalette(c("red", "blue", "orange"), 100))
filledcircle(mid = c(-1, 1))

emptyplot(main = "filledcircle")

for (i in seq(0, 0.45, 0.05))
  filledcircle(r1 = i+0.05, r2 = i,
              mid = c(0.5, 0.5), col = i*20)

```

filledcylinder	<i>adds a colored and rotated cylinder to a plot</i>
----------------	--

Description

adds a rotated and colored cylinder to a plot; color can be a palette

Usage

```

filledcylinder(rx = 1, ry = rx, len = 1, col = femmecol(100),
              lcol = NA, lwd = 2, lcolint = NULL, ltyint = 1,
              lwdint = lwd, mid = c(0,0), angle = 0, delt = 1,
              dr = 0.01, topcol = NULL, botcol = NULL, ...)

```

Arguments

rx	horizontal radius.
ry	vertical radius.
len	length.
col	color palette to be used; also allowed are two extremes or one value.
lcol	line color on external surface.
lwd	only if lcol!=NA, width of external line.
lcolint	only if lcol!=NA, line color on internal (hidden) surface.
ltyint	only if lcol!=NA, line type on internal (hidden) surface.
lwdint	only if dlcol!=NA, line width on internal (hidden) surface.

mid	midpoint of cylinder.
angle	rotation angle, degrees.
delt	increase factor, from left to right.
dr	size of segments, in radians, to draw top/bottom ellipse (decrease for smoother).
topcol	color (palette) of top (right) surface.
botcol	color (palette) of bottom (left) surface.
...	arguments passed to function filledellipse .

Details

When angle = 0 (the default), the cylinder is parallel to the x-axis

rx and ry are the horizontal and vertical radiusses of the bordering ellipses. Here "horizontal" and "vertical" denote the position BEFORE rotation

if delt > 1, the width of the cylinder will increase from left to right.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[filledellipse](#), [filledshape](#)

Examples

```
emptyplot(c(-1.2, 1.2), c(-1, 1), main = "filledcylinder")
col <- c(rev(greycol(n = 50)), greycol(n = 50))
col2 <- shadepalette("red", "blue", n = 50)
col3 <- shadepalette("yellow", "black", n = 50)
filledcylinder(rx = 0., ry = 0.2, len = 0.25, angle = 0, col = col,
              mid = c(-1, 0), topcol = col[25])
filledcylinder(rx = 0., ry = 0.2, angle = 90, col = col,
              mid = c(-0.5, 0), topcol = col[25])
filledcylinder(rx = 0.1, ry = 0.2, angle = 90, col = c(col2, rev(col2)),
              mid = c(0.45, 0), topcol = col2[25])
filledcylinder(rx = 0.05, ry = 0.2, angle = 90, col = c(col3, rev(col3)),
              mid = c(0.9, 0), topcol = col3[25])
filledcylinder(rx = 0.1, ry = 0.2, angle = 90, col = "white",
              lcol = "black", lcolint = "grey")

emptyplot(c(-1, 1), c(-1, 1), main = "filledcylinder")
col <- shadepalette("blue", "black", n = 50)
col2 <- shadepalette("red", "black", n = 50)
col3 <- shadepalette("yellow", "black", n = 50)
filledcylinder(rx = 0.025, ry = 0.2, angle = 90, col = c(col2, rev(col2)),
              mid = c(-0.8, 0), topcol = col2[25], delt = -1, lcol = "black")
filledcylinder(rx = 0.1, ry = 0.2, angle = 00, col = c(col, rev(col)),
              mid = c(0.0, 0.0), topcol = col, delt = -1.2, lcol = "black")
filledcylinder(rx = 0.075, ry = 0.2, angle = 90, col = c(col3, rev(col3)),
              mid = c(0.8, 0), topcol = col3[25], delt = 0.0, lcol = "black")
```

filledellipse *adds a colored and rotated ellipse to a plot*

Description

plots (part of) outer and inner ellipses and colors inbetween; color can be a palette

Usage

```
filledellipse(rx1 = 1, rx2 = 0, ry1 = rx1, ry2 = NULL, mid = c(0,0),
             dr = 0.01, angle = 0, from = -pi, to = pi, col = femmecol(100),
             values = NULL, zlim = NULL, lwd = 2, lcol = NA, ...)
```

Arguments

rx1	horizontal radius of outer ellipse.
rx2	horizontal radius of inner ellipse.
ry1	vertical radius of outer ellipse.
ry2	vertical radius of inner ellipse.
mid	midpoint of ellipse.
dr	size of segments, in radians, to draw ellipse (decrease for smoother).
angle	rotation angle, degrees.
from	starting angle for ellipse segment, radians.
to	final angle for ellipse segment, radians. The segment is drawn counterclockwise. The default is draw a full ellipse.
col	color palette to be used; also allowed are two extremes or one value.
values	if not NULL, a matrix providing (radius,z-values) couples, used for coloring. .
zlim	Only if values is not NULL: the minimum and maximum z values for which colors should be plotted, defaulting to the range of the finite values of the second column of values.
lwd	width of external line.
lcol	line color.
...	arguments passed to R-function polygon .

Details

draws (part of) an outer and inner ellipse, as specified by inner and outer radiusses:

rx1,ry1: horizontal and vertical radiusses of outer ellipse; rx2,ry2: same for inner ellipse. Here "horizontal" and "vertical" denote the position BEFORE rotation

Fills with a palette of colors inbetween

values: if not NULL, a matrix providing (radius,z-values) couples, used for coloring. Here radius are positive values denoting the relative distance between the shapes centre and edge. The radiusses

are rescaled to be in [0,1] if needed. z-values (2nd column of values) together with xlim and ylim denote the coloration level.

Colors in col will be interpolated to the z-values and used to color an interval as given by the input radiusses.

If rx2, the radius of the inner ellipse is 0, the ellipse is full.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[filledshape](#), [filledcylinder](#)

Examples

```
color <- greycol(50)
dr <- 0.05
emptyplot(xlim = c(-2, 2), ylim = c(-2, 2), col = color[length(color)],
          main = "filledellipse")
filledellipse(rx1 = 1, mid = c(1, 1) , dr = dr,
             col = shadepalette(endcol = "darkblue"))
filledellipse(rx1 = 1, ry1 = 0.5, mid = c(-1, -1), dr = dr, angle = 90,
             col = shadepalette(endcol = "darkred"))
filledellipse(rx1 = 1, ry1 = 0.5, rx2 = 0.5, dr = dr, mid = c(0, 0),
             col = c(rev(color), color))
filledellipse(rx1 = 0.5, mid = c(1, -1), dr = dr, from = pi, to = 1.5*pi,
             col = rev(shadepalette(endcol = "black")))
filledellipse(mid = c(-1, 1))

emptyplot(xlim = c(-2, 2), ylim = c(-2, 2), main = "filledellipse")
filledellipse(rx1 = 0.75, mid = c(-1, 1), col = greycol(100) , dr = dr,
             values = cbind (1:100, (1:100)^0.5))
filledellipse(rx1 = 0.75, mid = c(1, 1), col = greycol(100) , dr = dr,
             values = cbind (1:100, (1:100)))
filledellipse(rx1 = 0.75, mid = c(-1, -1), col = greycol(100), dr = dr,
             values = cbind (1:100, (1:100)^2))
filledellipse(rx1 = 0.75, mid = c(1, -1), col = greycol(100) , dr = dr,
             values = cbind (1:100, (1:100)^5))
```

filledmultigonal

adds a colored and rotated multigonal shape to a plot

Description

draws and colors a rotated shape with equal-sized vertices ; color can be a palette.

Usage

```
filledmultigonal(mid = c(0, 0), rx = 1, ry = rx, nr = 4,
                 col = femmecol(100), values = NULL,
                 zlim = NULL, lwd = 2, lcol = NA, angle = 0, ...)
```

Arguments

mid	midpoint of multigonal.
rx	horizontal radius.
ry	vertical radius.
nr	number of sides.
col	color palette to be used; also allowed are two extremes or one value.
values	if not NULL, a matrix providing (radius,z-values) couples, used for coloring.
zlim	Only if values is not NULL: the minimum and maximum z values for which colors should be plotted, defaulting to the range of the finite values of the second column of values.
lwd	width of external line.
lcol	line color.
angle	angle of rotation, in degrees.
...	arguments passed to R-function polygon .

Details

Coloration proceeds from midpoint to external edge

rx,ry: horizontal and vertical radiusses of the shape. Here "horizontal" and "vertical" denote the position BEFORE rotation

values: if not NULL, a matrix providing (radius,z-values) couples, used for coloring. Here radius are positive values denoting the relative distance between the shapes centre and edge. The radiusses are rescaled to be in [0,1] if needed. z-values (2nd column of values) together with zlim and col denote the coloration level.

Colors in col will be interpolated to the z-values and used to color an interval as given by the input radiusses.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[filledrectangle](#), [filledshape](#), [filledcylinder](#), [filledellipse](#)

Examples

```

emptyplot(c(-1, 1), main = "filledmultigonal")

filledmultigonal(rx = 0.25, ry = 0.125, nr = 3, mid = c(-0.75, 0.75),
  angle = 45, col = shadepalette("red", "blue", n = 50))
filledmultigonal(rx = 0.125, ry = 0.25, nr = 3, mid = c(-0.25, 0.75),
  col = shadepalette("red", "yellow", n = 50))
filledmultigonal(rx = 0.25, ry = 0.25, nr = 3, mid = c(0.25, 0.75),
  col = c("red", "orange"))
filledmultigonal(rx = 0.25, ry = 0.25, nr = 3, mid = c(0.75, 0.75),
  angle = 90, col = "red")

filledmultigonal(rx = 0.25, ry = 0.25, nr = 4, mid = c(-0.75, 0.25),
  angle = 0, col = shadepalette("red", "blue", n = 50))
filledmultigonal(rx = 0.25, ry = 0.25, nr = 4, mid = c(-0.25, 0.25),
  angle = 45, col = shadepalette("red", "blue", n = 50))
filledmultigonal(rx = 0.25, ry = 0.125, nr = 4, mid = c(0.25, 0.25),
  angle = 0, col = shadepalette("red", "blue", n = 50))
filledmultigonal(rx = 0.25, ry = 0.125, nr = 4, mid = c(0.75, 0.25),
  angle = 45, col = shadepalette("red", "blue", n = 50))

filledmultigonal(rx = 0.25, ry = 0.25, nr = 5, mid = c(-0.75, -0.25),
  angle = 0, col = shadepalette("darkgreen", "lightgreen", n = 50))
filledmultigonal(rx = 0.25, angle = 0, nr = 5, mid = c(-0.25, -0.25),
  col = rainbow(50))
filledmultigonal(rx = 0.25, angle = 30, nr = 6, mid = c(0.25, -0.25),
  col = femmecol(50))
filledmultigonal(rx = 0.25, ry = 0.125, angle = 30, nr = 6, mid = c(0.75, -0.25),
  col = "black")

filledmultigonal(rx = 0.25, col = "darkblue", nr = 7, mid = c(-0.75, -0.75))
filledmultigonal(rx = 0.25, col = "darkblue", nr = 9, mid = c(-0.25, -0.75))
filledmultigonal(rx = 0.25, col = "darkblue", nr = 3.7, mid = c(0.25, -0.75))
filledmultigonal(rx = 0.25, col = "darkblue", nr = 4.5, mid = c(0.75, -0.75))

```

filledrectangle	<i>adds a colored and rotated rectangle to a plot</i>
-----------------	---

Description

plots and colors a rotated rectangle; color can be a palette

Usage

```

filledrectangle(mid = c(0, 0), wx = 1, wy = wx, col = femmecol(100),
  values = NULL, zlim = NULL, lwd = 2, lcol = NA,
  angle = 0, ...)

```

Arguments

mid	midpoint of rectangle.
wx	horizontal width.
wy	vertical width.
col	color palette to be used; also allowed are two extremes or one value.
values	if not NULL, a matrix providing (radius,z-values) couples, used for coloring.
zlim	Only if values is not NULL: the minimum and maximum z values for which colors should be plotted, defaulting to the range of the finite values of the second column of values.
lwd	width of external line.
lcol	line color.
angle	angle of rotation, in degrees.
...	arguments passed to R-function polygon .

Details

If angle=0, coloration starts from top to bottom. This is different from [filledmultigonal](#), where coloration proceeds from middle to external

wx,wy: horizontal and vertical width of the shape Here "horizontal" and "vertical" denote the position BEFORE rotation

values: if not NULL, a matrix providing (radius,z-values) couples, used for coloring. Here radius are positive values denoting the relative distance between the shapes centre and edge. The radiusses are rescaled to be in [0,1] if needed. z-values (2nd column of values) together with zlim and col denote the coloration level.

Colors in col will be interpolated to the z-values and used to color an interval as given by the input radiusses.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>.

See Also

[filledmultigonal](#), [filledshape](#), [filledcylinder](#), [filledellipse](#)
[polygon](#), [rect](#) for corresponding R-functions.

Examples

```
color <- shadepalette(grey(0.3), "lightblue", n = 50)
emptyplot(main = "filledrectangle")
filledrectangle(wx = 0.5, wy = 0.5, col = color,
               mid = c(0.5, 0.5), angle = 0)
filledrectangle(wx = 0.25, wy = 0.25, col = "darkblue",
               mid = c(0.5, 0.5), angle = 45)
filledrectangle(wx = 0.125, wy = 0.125, col = c("lightblue", "blue"),
```

```

mid = c(0.5, 0.5), angle = 90)

color <- shadepalette(grey(0.3), "blue", n = 50)
emptyplot(c(-1, 1), main = "filledrectangle")
filledrectangle(wx = 0.5, wy = 0.5, col = color,
  mid = c(0, 0), angle = 0)
filledrectangle(wx = 0.5, wy = 0.5, col = color,
  mid = c(0.5, 0.5), angle = 90)
filledrectangle(wx = 0.5, wy = 0.5, col = color,
  mid = c(-0.5, -0.5), angle = -90)
filledrectangle(wx = 0.5, wy = 0.5, col = color,
  mid = c(0.5, -0.5), angle = 180)
filledrectangle(wx = 0.5, wy = 0.5, col = color,
  mid = c(-0.5, 0.5), angle = 270)

```

filledshape	<i>adds a colored shape to a plot</i>
-------------	---------------------------------------

Description

plots outer and inner shape and colors inbetween; color can be a palette

Usage

```

filledshape(xyouter, xyinner = colMeans(xyouter),
  col = femmecol(100), values = NULL,
  zlim = NULL, lcol = NA, lwd = 2, ...)

```

Arguments

xyouter	2-column matrix with x,y values of outer shape.
xyinner	2-column matrix of 2-valued vector with x,y values of inner shape; default is centroid of xyouter.
col	color palette to be used; also allowed are two extremes.
values	if not NULL, a matrix providing (radius,z-values) couples, used for coloring.
zlim	Only if values is not NULL: the minimum and maximum z values for which colors should be plotted, defaulting to the range of the finite values of the second column of *values*.
lcol	line color.
lwd	width of external line, only if lcol != NA.
...	arguments passed to R-function polygon

Details

draws and outer and inner shape, as specified in `xyouter`, and `xyinner` and fills with a palette of colors inbetween;

values: if not null, a matrix providing (radius,z-values) couples, used for coloring. Here radius are positive values denoting the relative distance between the shapes centre and edge. The radiusses are rescaled to be in [0,1] if needed. z-values (2nd column of values) together with `zlim` and `col` denote the coloration level.

Colors in `col` will be interpolated to the z-values and used to color an interval as given by the input radiusses.

If `xyinner` is a point, the shape is full.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[filledellipse](#), [filledcylinder](#)

Examples

```
#an egg
color <-greycol(100)
emptyplot(c(-3.2, 3.2), col = color[length(color)], main = "filledshape")
b <- 4
a <- 9
x <- seq(-sqrt(a), sqrt(a), by = 0.01)
g <- b-b/a*x^2 - 0.2*b*x + 0.2*b/a*x^3
g[g<0] <- 0
x1 <- c(x, rev(x))
g1 <- c(sqrt(g), rev(-sqrt(g)))
xouter <- cbind(x1, g1)
xouter <- rbind(xouter, xouter[1,])
filledshape(xouter, xyinner = c(-1, 0), col = color)

# a mill
color <- shadepalette(grey(0.3), "yellow", n = 50)
emptyplot(c(-3.3, 3.3), col = color[length(color)], main = "filledshape")
x <- seq(0, 0.8*pi, pi/100)
y <- sin(x)
xouter <- cbind(x, y)

for (i in seq(0, 360, 60))
  xouter <- rbind(xouter, rotatexy(cbind(x, y), mid = c(0, 0), angle = i))
filledshape(xouter, c(0, 0), col = color)

# abstract art
emptyplot(col = "darkgrey", main = "filledshape")
filledshape(matrix(ncol = 2, runif(100)), col = "darkblue")
```

getellipse	<i>x-y coordinates of ellipse</i>
------------	-----------------------------------

Description

calculates x-y values for (part of) an ellipse; the ellipse can be rotated

Usage

```
getellipse(rx = 1, ry = rx, mid = c(0, 0), dr = 0.01,  
           angle = 0, from = -pi, to = pi)
```

Arguments

rx	long radius of ellipse.
ry	short radius of ellipse.
mid	midpoint of ellipse.
dr	size of segments, in radians, to specify ellipse (decrease for smoother).
angle	rotation angle, degrees.
from	starting angle for ellipse segment, radians.
to	final angle for ellipse segment, radians. The segment is generated counterclockwise. The default is draw a full ellipse.

Details

rx and ry are the horizontal and vertical radiusses of the ellipses.

points from and to are joined counterclockwise. (this has changed since version 1.3.4).

Value

a 2-column matrix with x-y values of the ellipse

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[plotellipse](#), [filledellipse](#)

Examples

```

plot(getellipse(1, from = 0, to = pi/2), type = "l", col = "red",
     lwd = 2, main = "getellipse")
lines(getellipse(0.5, 0.25, mid = c(0.5, 0.5)), type = "l",
      col = "blue", lwd = 2)
lines(getellipse(0.5, 0.25, mid = c(0.5, 0.5), angle = 45),
      type = "l", col = "green", lwd = 2)

lines(getellipse(0.2, 0.2, mid = c(0.5, 0.5), from = 0, to = pi/2),
      type = "l", col = "orange", lwd = 2)
lines(getellipse(0.2, 0.2, mid = c(0.5, 0.5), from = pi/2, to = 0),
      type = "l", col = "black", lwd = 2)
lines(getellipse(0.1, 0.1, mid = c(0.75, 0.5), from = -pi/2, to = pi/2),
      type = "l", col = "black", lwd = 2)

emptyplot(main = "getellipse")
col <- femmecol(90)
for (i in seq(0, 180, by = 2))
  lines(getellipse(0.5, 0.25, mid = c(0.5, 0.5), angle = i),
        type = "l", col = col[(i/2)+1], lwd = 2)

```

greycol

white-black color palette

Description

Creates a vector of (n) contiguous colors from white/grey to black

Usage

```
greycol(n = 100, interval = c(0.0, 0.7))
```

Arguments

n number of colors.
interval interval *to* where to interpolate.

Details

greycol is an alias of graycol

Value

a vector of character strings giving the colors in hexadecimal format.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[rainbow](#), [heat.colors](#), [topo.colors](#), [femmecol](#)

Examples

```
filled.contour(volcano, color = graycol, asp = 1, main = "greycol,graycol")
graycol(10)
image(matrix(nrow = 1, ncol = 100, data = 1:100),
       col = graycol(100), main = "greycol,graycol")
```

intpalette

color palettes

Description

Returns color(s) that are a linear interpolation of a given set of colors.

Usage

```
intpalette(inputcol, numcol = length(x.to), x.from = NULL, x.to = NULL)
```

Arguments

inputcol	initial colors, <i>*from*</i> where to interpolate.
numcol	number of colors to interpolate <i>*to*</i> .
x.from	x-values <i>*from*</i> where to interpolate.
x.to	x-values where to interpolate <i>*to*</i> .

Details

Return value is a vector of **colors** in hexadecimal format.

This is different from [colorRamp](#)(R function), that returns a **function**

Value

a vector of character strings giving the interpolated colors in hexadecimal format

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[greycol](#), [femmecol](#), [shadepalette](#), [colorRamp](#) for comparable R function

Examples

```
intpalette(c("white", "black"), n = 10)
grey(seq(1, 0, length.out = 10))
image(matrix(nrow = 1, ncol = 100, data = 1:100),
       col = intpalette(c("red", "blue"), numcol = 100),
       main = "intpalette")
image(matrix(nrow = 1, ncol = 100, data = 1:100),
       col = intpalette(c("red", "blue", "yellow"), numcol = 100),
       main = "intpalette")
```

plotcircle

adds part of a colored circle to a plot

Description

adds (part of) a colored circle to a plot; an arrow can be drawn at a specified position

Usage

```
plotcircle(r = 1, ...)
```

Arguments

`r` radius of circle.
`...` arguments passed to function [plotellipse](#).

Details

`plotcircle` calls `plotellipse`, making sure that the figure drawn effectively looks like a circle. For graphs that have both axes of equal size, the circle will be equal to the ellipse with equal `rx` and `ry`. See second example

see [plotellipse](#) for details

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[plotellipse](#) to draw ellipses

Examples

```
# symmetrical axes
emptyplot(c(0, 1))
plotcircle(mid = c(0.5, 0.5), r = 0.25, from = 0, to = 3*pi/2,
           arrow = TRUE, arr.pos = 0.5, col = "red")
# symmetrical
plotellipse(mid = c(0.5, 0.5), rx = 0.2, ry = 0.2,
           arrow = TRUE, arr.pos = 0.5, col = "blue")

#non-symmetrical axes
emptyplot(c(0, 1), c(0, 2), main = "plotcircle", asp = FALSE)
plotcircle(mid = c(0.5, 0.5), r = 0.25, from = 0, to = 3*pi/2,
           arrow = TRUE, arr.pos = 0.5, col = "red")
plotellipse(mid = c(0.5, 0.5), rx = 0.25, ry = 0.25,
           arrow = TRUE, arr.pos = 0.5, col = "blue")
```

plotellipse

adds part of a colored and rotated ellipse to a plot

Description

adds (part of) a colored, and rotated ellipse to a plot; an arrow can be drawn at a specified position.

Usage

```
plotellipse(rx = 1, ry = 0.2, mid = c(0,0), dr = 0.01,
           angle = 0, from = -pi, to = pi, type = "l", lwd = 2,
           lcol = "black", col = NULL, arrow = FALSE,
           arr.length = 0.4, arr.width = arr.length*0.5,
           arr.type = "curved", arr.pos = 1, arr.code = 2,
           arr.adj = 0.5, arr.col = "black", ...)
```

Arguments

rx	long radius of ellipse.
ry	short radius of ellipse.
mid	midpoint of ellipse.
dr	size of segments, in radians, to draw ellipse (decrease for smoother).
angle	rotation angle, degrees.
from	starting angle for ellipse segment, radians.
to	final angle for ellipse segment, radians.
type	external line or points; "n" if no line.
lwd	width of external line.
lcol	line color.

col	fill color.
arrow	drawing arrowhead yes/no.
arr.length	length of arrowhead.
arr.width	width of arrowhead.
arr.type	type of arrow.
arr.pos	position of arrow, 0=start,1=end.
arr.code	integer code determining kind of arrows to draw.
arr.adj	adjustment of arrow.
arr.col	color of arrow head.
...	arguments passed to R-function lines .

Details

rx and ry are the horizontal and vertical radiusses of the ellipses.

The ellipse is drawn from the point defined by from to the point defined as to which are joined anti-clockwise.

if arrow is TRUE, an arrow is drawn along the path of the ellipse.

arr.length and arr.width set the size of the arrow.

The type of the arrowhead is set with arr.type which can take the values:

- "simple" : uses comparable R function [arrows](#).
- "triangle": uses filled triangle.
- "curved" : draws arrowhead with curved edges.
- "circle" : draws circular head.

arr.pos, a real value between 0 and 1 gives the position (0=start,1=end).

arr.col specifies the color, arr.code specifies where the angle points to.

arr.adj specifies the position adjustment - see [Arrows](#) for details.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>.

See Also

[getellipse](#), [filledellipse](#), [plotcircle](#).

Examples

```
emptyplot(c(-1, 1), main = "plotellipse")
plotellipse(rx = 0.8, ry = 0.3, angle = 60, col = "blue")
plotellipse(rx = 1.0, ry = 0.6, angle = 0, from = pi, to = 2*pi,
            arrow = TRUE, arr.pos = seq(0.1, 0.5, by = 0.1),
            arr.col = rainbow(5))
plotellipse(rx = 1.0, ry = 0.6, angle = 30, from = pi, to = 1.2*pi,
```

```

        col = "red")
plotellipse(rx = 0.1, ry = 0.6, from = 1.5*pi, to = pi,
            lcol = "orange", mid = c(0.2,0.2))
plotellipse(rx = 0.1, ry = 0.6, angle = 30, from = 1.5*pi, to = pi,
            lcol = "orange", mid = c(0.2,0.2))

```

rotatexy	<i>rotates 2-column matrix around a midpoint</i>
----------	--

Description

rotates xy values around a midpoint; xy is either a 2-columned matrix or a 2-valued vector

Usage

```
rotatexy(xy, angle, mid = colMeans(xy), asp = FALSE)
```

Arguments

xy	matrix with 2 columns, or a 2-valued vector to be rotated.
angle	angle of rotation, in degrees.
mid	rotation point, default=centroid.
asp	if true: aspect ratio is kept.

Value

a 2-column matrix with rotated values

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

Examples

```

x <- seq(0, 2*pi, pi/100)
y <- sin(x)
cols <- intpalette(c("blue", "green", "yellow", "red"), n = 500)
cols <- c(cols, rev(cols))
plot(x, y, type = "l", ylim = c(-3, 3), main = "rotatexy",
     col = cols[1], lwd = 2)
for (i in 2:1000)
  lines(rotatexy( cbind(x, y), angle = 0.18*i),
        col = cols[i], lwd = 2)

cols <- femmecol(1000)
plot(x, y, xlim = c(-1, 1), ylim = c(-1, 1), main = "rotatexy",
     col = cols[1], type = "n")
for (i in 2:1000) {

```

```

xy <- rotatexy(c(0, 1), angle = 0.36*i, mid = c(0,0))
points(xy[1], xy[2], col = cols[i], pch = ".", cex = 2)
}

```

roundrect	<i>adds a rounded rectangular box to a plot</i>
-----------	---

Description

adds a rectangular box with rounded left and right edges to a plot

Usage

```

roundrect(mid, radx, rady, rx = rady, dr = 0.01,
          col = "white", lcol = "black", lwd = 2, angle = 0, ...)

```

Arguments

mid	midpoint (x,y) of the box.
radx	horizontal radius of the box.
rady	vertical radius of the box.
rx	radius of rounded part.
dr	size of segments, in radians, to draw the rounded line (decrease for smoother).
col	fill color of the box.
lcol	line color surrounding box.
lwd	line width of line surrounding the box.
angle	rotation angle, degrees.
...	arguments passed to function filledshape .

Details

radx and rady are the horizontal and vertical radiusses of the box; rx is the horizontal radius of the rounded part.

Here horizontal and vertical denote the position BEFORE rotation.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

Examples

```

emptyplot(c(-0.1, 1.1), main = "roundrect")
for (i in 1:10)
  roundrect(mid = runif(2), col = i, radx = 0.1, rady = 0.05)
for (i in 1:5)
  roundrect(mid = runif(2), col = greycol(20), radx = 0.05,
            rady = 0.05, angle = runif(1)*360)

```

shadepalette *color palette inbetween two extremes*

Description

Returns color(s) that are a linear interpolation between two colors
these colors are suitable for shading shapes

Usage

```
shadepalette(n = 100, endcol = "red", incol = "white",  
            interval = c(0.0, 1.0))
```

Arguments

n	number of colors.
endcol	final color.
incol	initial color.
interval	interval *to* where to interpolate.

Value

a vector of character strings giving the interpolated colors in hexadecimal format

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

See Also

[intpalette](#), [grey](#), [femmecol](#) [colorRamp](#) for comparable R functions.

Examples

```
shadepalette(n = 10, "white", "black")  
image(matrix(nrow = 1, ncol = 100, data = 1:100),  
      col = shadepalette(100, "red", "blue"), main = "shadepalette")
```

textflag *adds a filled rounded rectangular box with a text to a plot*

Description

adds a rectangular box with rounded left and right edges to a plot

Usage

```
textflag(mid, radx, rady, rx = rady, dr = 0.01,
         col = femmecol(100), lcol = "white",
         bcol = lcol, lwd = 2, angle = 0, lab = NULL,
         leftright = TRUE,...)
```

Arguments

mid	midpoint (x,y) of the box.
radx	horizontal radius of the box.
rady	vertical radius of the box.
rx	radius of rounded part.
dr	size of segments, in radians, to draw the rounded line (decrease for smoother).
col	fill color of the box; the box will be filled from left to right.
lcol	line color surrounding box.
bcol	line color to remove the ellipse from the rectangular box.
lwd	line width of line surrounding the box.
angle	rotation angle, degrees.
lab	one label or a vector string of labels to be added in box.
leftright	if TRUE then coloring is from left to right else the coloring is from bottom to top box (for angle = 0).
...	arguments passed to function text .

Details

radx and rady are the horizontal and vertical radiusses of the box; rx is the horizontal radius of the rounded part.

Here horizontal and vertical denote the position BEFORE rotation.

This function is similar to function [roundrect](#), except that coloring is from left to right.

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

Examples

```
emptyplot()
textflag(mid = c(0.5, 0.5), radx = 0.5, rady = 0.1,
         lcol = "white", lab = "hello", cex = 5, font = 2:3)

textflag(mid = c(0.5, 0.15), radx = 0.5, rady = 0.1,
         rx = 0.3, lcol = "black", lab = "hello 2", cex = 4,
         font = 2, angle = 20)

textflag(mid = c(0.5, 0.85), radx = 0.5, rady = 0.1, rx = 0.03,
         lcol = "white", lab = "hello 3", cex = 4, font = 2,
         leftright = FALSE)
```

writelabel	<i>adds a label next to a plot</i>
------------	------------------------------------

Description

adds one-character label on left-upper margin, next to a plot

Usage

```
writelabel(text = NULL, nr = 1, at = -0.1, line = 1, cex = 1.5, ...)
```

Arguments

text	text to write.
nr	integer; if text = NULL: nr is converted to uppercase letter.
at	relative distance of label position, from left margin of plot region.
line	line above the plot region of label position.
cex	relative size of label.
...	arguments passed to R-function mtext .

Author(s)

Karline Soetaert <k.soetaert@nioo.knaw.nl>

Examples

```
plot(runif(2), main = "writelabel")
writelabel("A")
writelabel("B", at = 0)
writelabel("C", at = 1)
```

Index

*Topic **aplot**

Arrowhead, [4](#)
Arrows, [5](#)
colorlegend, [8](#)
cylindersegment, [9](#)
drapecol, [10](#)
filledcircle, [13](#)
filledcylinder, [14](#)
filledellipse, [16](#)
filledmultigonal, [17](#)
filledrectangle, [19](#)
filledshape, [21](#)
plotcircle, [26](#)
plotellipse, [27](#)
roundrect, [30](#)
textflag, [32](#)
writelabel, [33](#)

*Topic **color**

femmecol, [12](#)
greycol, [24](#)
intpalette, [25](#)
shadepalette, [31](#)

*Topic **device**

A4, [3](#)

*Topic **dplot**

getellipse, [23](#)

*Topic **hplot**

emptyplot, [11](#)

*Topic **manip**

rotatexy, [29](#)

*Topic **package**

shape-package, [2](#)

A4, [3](#), [3](#)

Arrowhead, [3](#), [4](#), [6](#)

Arrows, [3](#), [5](#), [5](#), [28](#)

arrows, [6](#), [28](#)

colorlegend, [3](#), [8](#)

colorRamp, [25](#), [31](#)

cylindersegment, [3](#), [9](#)

drapecol, [3](#), [10](#)

emptyplot, [3](#), [11](#)

femmecol, [3](#), [12](#), [25](#), [31](#)

filledcircle, [3](#), [13](#)

filledcylinder, [3](#), [10](#), [13](#), [14](#), [17](#), [18](#), [20](#), [22](#)

filledellipse, [3](#), [13](#), [15](#), [16](#), [18](#), [20](#), [22](#), [23](#),
[28](#)

filledmultigonal, [3](#), [17](#), [20](#)

filledrectangle, [3](#), [18](#), [19](#)

filledshape, [3](#), [13](#), [15](#), [17](#), [18](#), [20](#), [21](#), [30](#)

getellipse, [3](#), [23](#), [28](#)

graycol (greycol), [24](#)

grey, [31](#)

greycol, [3](#), [24](#), [25](#)

heat.colors, [12](#), [25](#)

intpalette, [3](#), [12](#), [25](#), [31](#)

lines, [28](#)

mtext, [33](#)

persp, [11](#)

plot, [11](#), [12](#)

plot.default, [12](#)

plotcircle, [3](#), [26](#), [28](#)

plotellipse, [3](#), [23](#), [26](#), [27](#)

polygon, [9](#), [13](#), [16](#), [18](#), [20](#), [21](#)

rainbow, [12](#), [25](#)

rect, [20](#)

rotatexy, [3](#), [29](#)

roundrect, [3](#), [30](#), [32](#)

shadepalette, [3](#), [12](#), [25](#), [31](#)

shape (shape-package), [2](#)

shape-package, [2](#)

text, [8](#), [32](#)

textflag, [3](#), [32](#)

topo.colors, [12](#), [25](#)

writelabel, [3](#), [33](#)