

# Package ‘snotelr’

October 14, 2022

**Title** Calculate and Visualize 'SNOTEL' Snow Data and Seasonality

**Version** 1.1

**Description** Programmatic interface to the 'SNOTEL' snow data (<https://www.nrcs.usda.gov/wps/portal/wcc/home>). Provides easy downloads of snow data into your R work space or a local directory. Additional post-processing routines to extract snow season indexes are provided.

**URL** <https://github.com/bluegreen-labs/snotelr>

**BugReports** <https://github.com/bluegreen-labs/snotelr/issues>

**Depends** R (>= 3.6)

**Imports** shiny, httr, utils, stats, rvest, magrittr, memoise

**Suggests** knitr, rmarkdown, covr, testthat, shinydashboard, leaflet, plotly, DT

**VignetteBuilder** knitr

**License** AGPL-3

**ByteCompile** true

**RoxygenNote** 7.2.1

**Encoding** UTF-8

**NeedsCompilation** no

**Author** Koen Hufkens [aut, cre] (<https://orcid.org/0000-0002-5070-8109>), BlueGreen Labs [cph, fnd]

**Maintainer** Koen Hufkens <[koen.hufkens@gmail.com](mailto:koen.hufkens@gmail.com)>

**Repository** CRAN

**Date/Publication** 2022-08-20 21:50:02 UTC

## R topics documented:

snotel_download	2
snotel_explorer	2
snotel_info	3
snotel_metric	3
snotel_phenology	4

**Index****5**


---

snotel_download	<i>Downloads snotel data based upon a subset of the sno-tel info as provided by snotel_info()</i>
-----------------	---------------------------------------------------------------------------------------------------

---

**Description**

Downloads snotel data based upon a subset of the sno-tel info as provided by snotel\_info()

**Usage**

```
snotel_download(site_id, path = tempdir(), internal = FALSE)
```

**Arguments**

site_id	subset of the sites listed by snotel_info()
path	where to save downloaded files (default = tempdir())
internal	return data to workspace, TRUE or FALSE (default = FALSE)

**Examples**

```
## Not run:
# download data for SNOTEL site 429 and 1287, returning data to
# the R workspace
df <- snotel_download(site_id = c(429,1287), internal = TRUE)

# list a few first rows
head(df)

## End(Not run)
```

---

snotel_explorer	<i>Start the SNOTEL shiny interface</i>
-----------------	-----------------------------------------

---

**Description**

Start the SNOTEL shiny interface

**Usage**

```
snotel_explorer()
```

**Examples**

```
# snotel_explorer()
```

---

snotel_info	<i>Downloads a SNOTEL site listing for further processing</i>
-------------	---------------------------------------------------------------

---

**Description**

Downloads a SNOTEL site listing for further processing

**Usage**

```
snotel_info(network = "sntl", path)
```

**Arguments**

network	network list to query (default = sntl, for SNOTEL)
path	path where to save the snotel information (site list)

**Examples**

```
## Not run:  
# download the meta-data from the SNOTEL server  
meta_data <- snotel_info()  
  
# show a couple of lines  
head(meta_data)  
  
## End(Not run)
```

---

snotel_metric	<i>Convert snotel data to metric from imperial units</i>
---------------	----------------------------------------------------------

---

**Description**

Data is read from either a snotel data frame and returned as such.

**Usage**

```
snotel_metric(df)
```

**Arguments**

df	snotel data frame
----	-------------------

**Details**

By default the conversion is done upon download. This function might serve some a purpose in processing of data grabbed straight from the server rather than through the package.

This is an internal function only. Hence, no examples are given.

**Value**

a data frame with imperial values converted to metric ones

---

snotel_phenology	<i>Calculates snow phenology from the snow water equivalent data</i>
------------------	----------------------------------------------------------------------

---

**Description**

First snow melt, first continuous snow melt, first snow accumulation and continuous snow accumulation are reported.

**Usage**

```
snotel_phenology(df)
```

**Arguments**

df                    a snotel data file or data frame

**Details**

Be sure to execute this code on individual sites when loading a combined tidy data frame containing data for multiple sites.

**Examples**

```
## Not run:  
# download one of the longer time series  
df <- snotel_download(site_id = 670, internal = TRUE)  
  
# calculate the snow phenology  
phenology <- snotel_phenology(df)  
  
# show a couple of lines  
head(phenology)  
  
## End(Not run)
```

# Index

snotel\_download, 2  
snotel\_explorer, 2  
snotel\_info, 3  
snotel\_metric, 3  
snotel\_phenology, 4