

Package ‘stacomir’

January 4, 2018

Version 0.5.3.1

Date 2018-01-04

Title Fish Migration Monitoring

Description Graphical outputs and treatment for a database of fish pass monitoring. It is a part of the 'STACOMI' open source project developed in France by the French Agency for Biodiversity (AFB) institute to centralize data obtained by fish pass monitoring. Version 0.5.3.1 is available in French and English. See <<http://stacomir.r-forge.r-project.org/>> for more information on 'STACOMI'.

License GPL (>= 2)

URL <http://stacomir.r-forge.r-project.org/>

Collate 'create_generic.R' 'data.R' 'fun_table_per_dis.R'
'fun_write_monthly.R' 'fungraph.R' 'fungraph_glasseel.R'
'funstat.R' 'funstat_daily.R' 'funtable.R'
'interface_report_annual.R' 'interface_report_dc.R'
'interface_report_df.R' 'interface_report_env.R'
'interface_report_ge_weight.R' 'interface_report_mig.R'
'interface_report_mig_char.R' 'interface_report_mig_env.R'
'interface_report_mig_interannual.R'
'interface_report_mig_mult.R' 'interface_report_sample_char.R'
'interface_report_sea_age.R' 'interface_report_silver_eel.R'
'interface_report_species.R' 'ref_checkbox.R' 'ref_choice.R'
'ref_coe.R' 'ref_dc.R' 'ref_df.R' 'ref_env.R' 'ref_horodate.R'
'ref_list.R' 'ref_par.R' 'ref_parqual.R' 'ref_parquan.R'
'ref_period.R' 'ref_stage.R' 'ref_taxa.R' 'ref_textbox.R'
'ref_timestep.R' 'ref_timestep_daily.R' 'ref_year.R'
'report_annual.R' 'report_dc.R' 'report_df.R' 'utilities.R'
'report_env.R' 'report_ge_weight.R' 'report_ope.R'
'report_mig.R' 'report_sample_char.R' 'report_mig_char.R'
'report_mig_mult.R' 'report_mig_env.R'
'report_mig_interannual.R' 'report_sea_age.R'
'report_silver_eel.R' 'report_species.R' 'setAs.R' 'stacomir.R'

LazyLoad yes

LazyData true

Depends R (>= 3.0.0), methods, stacomirtools, RODBC

Imports magrittr, intervals, RColorBrewer, stringr, gWidgets,
gWidgetsRGtk2, RPostgreSQL, ggplot2, reshape2, sqldf, graphics,
utils, stats, lattice, grDevices, Hmisc, RGtk2, lubridate,
dplyr, xtable, mgcv

Suggests testthat, viridis

Author Cedric Briand [aut, cre],
Marion Legrand [aut],
Timothee Besse [aut]

Maintainer Cedric Briand <cedric.briand00@gmail.com>

RoxygenNote 5.0.1

NeedsCompilation no

Repository CRAN

Repository/R-Forge/Project stacomir

Repository/R-Forge/Revision 470

Repository/R-Forge/DateTimeStamp 2018-01-04 13:31:37

Date/Publication 2018-01-04 20:35:21 UTC

R topics documented:

stacomir-package	7
barplot,report_annual-method	7
calcmig	8
calcule	9
calcule,report_ge_weight-method	9
calcule,report_mig-method	10
calcule,report_mig_char-method	11
calcule,report_mig_env-method	11
calcule,report_mig_interannual-method	12
calcule,report_mig_mult-method	13
calcule,report_sample_char-method	14
calcule,report_sea_age-method	14
calcule,report_silver_eel-method	15
calcule,report_species-method	16
charge	16
charge,ref_checkbox-method	17
charge,ref_choice-method	18
charge,ref_coe-method	19
charge,ref_dc-method	19
charge,ref_df-method	20
charge,ref_env-method	21
charge,ref_list-method	21
charge,ref_par-method	22
charge,ref_parqual-method	23

charge,ref_parquan-method	24
charge,ref_stage-method	24
charge,ref_taxa-method	25
charge,ref_textbox-method	26
charge,ref_year-method	26
charge,report_ge_weight-method	27
charge,report_mig-method	28
charge,report_mig_env-method	28
charge,report_mig_mult-method	29
chargecomplement-methods	30
charge_complement	30
charge_complement,ref_parqual-method	31
charge_with_filter,ref_par-method	32
charge_with_filter,ref_parqual-method	33
charge_with_filter,ref_parquan-method	34
charge_with_filter,ref_stage-method	35
charge_with_filter,ref_taxa-method	36
choicemult,ref_dc-method	36
choicemult,ref_taxa-method	37
choice_c,ref_choice-method	38
choice_c,ref_dc-method	39
choice_c,ref_df-method	40
choice_c,ref_env-method	40
choice_c,ref_horodate-method	41
choice_c,ref_list-method	42
choice_c,ref_par-method	42
choice_c,ref_stage-method	43
choice_c,ref_taxa-method	44
choice_c,ref_textbox-method	45
choice_c,ref_timestep_daily-method	45
choice_c,ref_year-method	46
choice_c,report_annual-method	47
choice_c,report_dc-method	48
choice_c,report_df-method	48
choice_c,report_env-method	49
choice_c,report_ge_weight-method	50
choice_c,report_mig-method	51
choice_c,report_mig_char-method	52
choice_c,report_mig_env-method	53
choice_c,report_mig_interannual-method	54
choice_c,report_mig_mult-method	55
choice_c,report_sample_char-method	56
choice_c,report_sea_age-method	57
choice_c,report_silver_eel-method	58
choice_c,report_species-method	59
coef_durif	59
colortable	60
connect,report_annual-method	61

connect,report_dc-method	61
connect,report_df-method	62
connect,report_env-method	63
connect,report_ge_weight-method	63
connect,report_mig-method	64
connect,report_mig_char-method	65
connect,report_mig_env-method	65
connect,report_mig_interannual-method	66
connect,report_mig_mult-method	67
connect,report_ope-method	67
connect,report_sample_char-method	68
connect,report_sea_age-method	68
connect,report_silver_eel-method	69
connect,report_species-method	70
createmessage	70
current_end_date,ref_timestep-method	71
envir_stacomi	71
funbarchart1DC	72
fungraph	72
fungraph_glasseel	73
funstat	74
funstat_daily	75
funtable	75
fun_aggreg_for_plot	76
fun_char_spe	77
fun_date_extraction	77
fun_report_mig_interannual	78
fun_report_mig_mult	79
fun_report_mig_mult_overlaps	79
fun_stage_durif	80
fun_table_per_dis	81
fun_weight_conversion	81
fun_write_monthly	82
getdbname	83
getnocurrent_step	83
getvalue	84
getvalue,ref_period-method	84
graphdate	85
graphe-methods	85
model	86
model,report_ge_weight-method	86
plot,report_annual,missing-method	87
plot,report_dc,ANY-method	88
plot,report_df,ANY-method	89
plot,report_env,missing-method	90
plot,report_ge_weight,missing-method	90
plot,report_mig,ANY-method	91
plot,report_mig_char,missing-method	92

plot,report_mig_env,missing-method	92
plot,report_mig_interannual,missing-method	93
plot,report_mig_mult,missing-method	94
plot,report_sample_char,missing-method	95
plot,report_sea_age,missing-method	95
plot,report_silver_eel,missing-method	96
plot,report_species,missing-method	97
print,report_dc-method	97
print,report_df-method	98
print,report_mig-method	98
print,report_mig_mult-method	99
print,report_sample_char-method	99
print,report_sea_age-method	100
print,report_silver_eel-method	100
progress_bar	101
quitte	102
ref_checkbox-class	102
ref_choice-class	103
ref_coe-class	104
ref_dc-class	104
ref_df-class	105
ref_env-class	106
ref_horodate-class	106
ref_par-class	107
ref_parqual-class	107
ref_parquan-class	108
ref_period-class	108
ref_stage-class	109
ref_taxa-class	109
ref_textbox-class	110
ref_timestep-class	110
ref_timestepChar-class	111
ref_timestep_daily-class	111
ref_year-class	112
report_annual-class	113
report_dc-class	115
report_df-class	116
report_env-class	118
report_ge_weight-class	119
report_mig-class	121
report_mig_char-class	123
report_mig_env-class	125
report_mig_interannual-class	127
report_mig_mult-class	131
report_ope-class	133
report_sample_char-class	133
report_sea_age-class	136
report_silver_eel-class	138

report_species-class	140
r_ann	141
r_ann_adour	142
r_dc	142
r_df	143
r_env	144
r_gew	144
r_mig	145
r_mig_char	146
r_mig_dc	146
r_mig_df	147
r_mig_env	147
r_mig_interannual	148
r_mig_interannual_vichy	148
r_mig_mult	149
r_mig_mult_dc	150
r_mig_mult_df	151
r_mig_mult_ope	151
r_mig_ope	152
r_sample_char	152
r_seaa	153
r_silver	154
setasqualitative	154
setasqualitative,report_mig_char-method	155
split_per_day	155
stacomi	156
summary,report_dc-method	157
summary,report_df-method	158
summary,report_mig-method	159
summary,report_mig_char-method	159
summary,report_mig_interannual-method	160
summary,report_mig_mult-method	161
summary,report_sample_char-method	161
summary,report_sea_age-method	162
summary,report_silver_eel-method	162
summary,report_species-method	163
supprime	163
supprime,ref_coe-method	164
supprime,report_mig_interannual-method	164
supprime,report_sea_age-method	165
vector_to_listsql	165
write_database	166
write_database,report_ge_weight-method	166
write_database,report_mig-method	167
write_database,report_sea_age-method	168
xtable,report_annual-method	168
xtable,report_mig_char-method	169

stacomir-package	<i>package Fish Migration Monitoring (stacomir)- Stations de Controle des Migrations</i>
------------------	--

Description

'Stacomir' enables to read informations in a database about fish migrations to build overviews of fish migrations and creating charts, plots, and summaries. The 'stacomir' project comprises an open source 'Postgres' database, and a 'java' interface to fill in data. Please contact the author if you want to try it out.

Details

Package:	stacomir
Type:	Package
Version:	0.5.3
Date:	2017-06-24
License:	GPL (>= 2)
LazyLoad:	yes
Depends:	methods

To use the stacomir package, simply load the library using `library(stacomir)`. Once done, type `stacomir()` in R terminal. The use of `stacomir(gr_interface=FALSE)` allows to launch stacomir without graphical interface from the command line. The program is currently translated to French, to switch to English or French type `Sys.setenv(LANG = "en")` `Sys.setenv(LANG = "fr")`

Author(s)

Author and Maintainer : <cedric.briand"at"eptb-vilaine.fr>

See Also

stacomirtools

Examples

```
#stacomir()
```

barplot,report_annual-method

barplot method for object [report_annual-class](#)

Description

barplot method for object [report_annual-class](#)

Usage

```
## S4 method for signature 'report_annual'
barplot(height, legend.text = NULL, ...)
```

Arguments

height	An object of class report_annual
legend.text	See barplot help
...	additional arguments passed to barplot

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

[report_annual-class](#) for examples

calcmig	<i>A data frame containing the default connection arguments. The program will use a file installed in c:/program files/stacomis but if not found will switch to this default value</i>
---------	--

Description

A data frame containing the default connection arguments. The program will use a file installed in c:/program files/stacomis but if not found will switch to this default value

Usage

```
calcmig
```

Format

An object of class data.frame with 1 rows and 11 columns.

calculer	<i>Generic method for calculations</i>
----------	--

Description

Generic method for calculations

Usage

```
calculer(object, ...)
```

Arguments

object	Object
...	Additional params

Author(s)

cedric.briand

calculer,report_ge_weight-method	<i>Calculer method for report_ge_weight</i>
----------------------------------	---

Description

Calculer method for report_ge_weight

Usage

```
## S4 method for signature 'report_ge_weight'  
calculer(object, silent = FALSE)
```

Arguments

object	An object of class report_ge_weight-class
silent	Boolean, if TRUE, information messages are not displayed, only warnings and errors

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

calculer,report_mig-method

Transforms migration per period to daily migrations, and performs the conversion from weights to number is data are stored as weights (glass eel).

Description

The calculation must be launched once data are filled by the connect method. Currently the negative argument has no effect.

Usage

```
## S4 method for signature 'report_mig'
calculer(object, negative = FALSE, silent = FALSE)
```

Arguments

object	An object of class report_mig-class
negative	a boolean indicating if a separate sum must be done for positive and negative values, if true, positive and negative counts return different rows
silent	Boolean, if TRUE, information messages are not displayed, only warnings and errors

Value

report_mig with calcdatas slot filled. It is a list with one element per counting device containing

method In the case of instantaneous periods (video counting) the sum of daily values is done by the [fun_report_mig_mult](#) method and the value indicated in method is "sum". If any migration monitoring period is longer than a day, then the migration is split using the [fun_report_mig_mult_overlaps](#) function and the value indicated in the method is "overlaps" as the latter method uses the overlap package to split migration period.

data the calculated data.

contient_poids A boolean which indicates, in the case of glass eel, that the function [fun_weight_conversion](#) has been run to convert the weights to numbers using the weight to number coefficients in the database (see [linkreport_ge_weight](#)).

negative A parameter indicating if negative migration (downstream in the case of upstream migration devices) have been converted to positive numbers, not developed yet

Note

The class report_mig does not handle escapement rates nor 'devenir' i.e. the destination of the fishes.

calcule,report_mig_char-method

Computes data to a standard format for the summary and plot methods.

Description

Merges the content of the list elements "parqual" and "parquan" in the data slot, and creates a single dataframe with one line per qualitative and quantitative pair. This methods allow to cross one quantity (e.g. length) with a qualitative parameter (e.g. sex).

Usage

```
## S4 method for signature 'report_mig_char'
calcule(object, silent = FALSE)
```

Arguments

object	An object of class report_mig_char-class
silent	Boolean default FALSE, if TRUE information messages not displayed

calcule,report_mig_env-method

Calculations for migration in the class [report_mig_env-class](#)

Description

Runs the calcule method in [report_mig_mult-class](#)

Usage

```
## S4 method for signature 'report_mig_env'
calcule(object, silent = FALSE)
```

Arguments

object	An object of class report_mig_env-class
silent	Boolean default FALSE, if TRUE information messages not displayed

Value

[report_mig_env-class](#) with data in slot `r_mig_env@report_mig_mult@calcddata`

calculer,report_mig_interannual-method
calculer method for report_mig_interannual

Description

Performs the calculation of seasonal coefficients for the `plot(plot.type="seasonal")` method. The numbers are split according to the period chosen, one of "day","week","month","2 weeks", French labels are also accepted as arguments. Once this is done, the seasonality of the migration is displayed using the day when the first fish was seen, then the days (or period) corresponding to 5, 50, 95, and 100 percent of the migration. The duration of 90

Usage

```
## S4 method for signature 'report_mig_interannual'  
calculer(object, silent = FALSE,  
         timesplit = "mois")
```

Arguments

<code>object</code>	An object of class <code>report_mig_interannual-class</code>
<code>silent</code>	Boolean, if TRUE, information messages are not displayed, only warnings and errors
<code>timesplit</code>	One of "day","week","month","2 weeks", "jour","semaine","quinzaine","mois"

Value

`report_mig` with `calcddata` slot filled.

Note

The class `report_mig` does not handle escapement rates nor 'devenir' i.e. the destination of the fishes.

Author(s)

Marion Legrand

```

calculer,report_mig_mult-method
    #' Transforms migration per period to daily migrations, and performs
    the conversion from weights to number is data are stored as weights
    (glass eel). This calculation is performed in a loop for all dc.

```

Description

The calculation must be launched once data are filled by the connect method. Currently the negative argument has no effect.

Usage

```

## S4 method for signature 'report_mig_mult'
calculer(object, negative = FALSE,
         silent = FALSE)

```

Arguments

object	An object of class report_mig_mult-class
negative	a boolean indicating if a separate sum must be done for positive and negative values, if true, positive and negative counts return different rows
silent	Default FALSE, should messages be stopped

Value

`report_mig_mult` with a list in slot `calculatedata`. For each dc one will find a list with the following elements

method In the case of instantaneous periods (video counting) the sum of daily values is done by the [fun_report_mig_mult](#) method and the value indicated in method is "sum". If any migration monitoring period is longer than a day, then the migration is split using the [fun_report_mig_mult_overlaps](#) function and the value indicated in the method is "overlaps" as the latter method uses the `overlap` package to split migration period.

data the calculated data. If weight are present, the columns display weight or numbers, the total number is "Effectif_total" and corresponds to the addition of numbers and numbers converted from weight, the total weight is "Poids_total"+"poids_depuis_effectifs" and corresponds to weighed glass eel plus glass eel number converted in weights. `CALCULE` corresponds to calculated number, `MESURE` to measured numbers, `EXPERT` to punctual expertise of migration (for instance measured in other path, or known migration of fishes passing the dam but not actually counted, `PONCTUEL` to fishes counted by visual identification but not by the counting apparatus (in case of technical problem for instance)

contient_poids A boolean which indicates, in the case of glass eel, that the function [fun_weight_conversion](#) has been run to convert the weights to numbers using the weight to number coefficients in the database (see `linkreport_ge_weight`).

negative A parameter indicating if negative migration (downstream in the case of upstream migration devices) have been converted to positive numbers, not developed yet

Note

The class does not handle escapement rates, though structurally those are present in the database. If you want to use those you will have to do the calculation manually from the data in `report_mig_mult@data`. Note also that running the `calculer` method requires to have a database called `test` in `postgres`, and empty database in which all `sqldf` group by queries are run. The user and password for the test database are taken from the `calcmig.csv` configuration file.

calculer,report_sample_char-method

Calculation for report_sample_char

Description

In that class, most treatments are done in the query, this method checks that data are available and fills information for year, month, two weeks, week, day

Usage

```
## S4 method for signature 'report_sample_char'
calculer(object, silent = FALSE)
```

Arguments

<code>object</code>	An object of class <code>report_sample_char-class</code>
<code>silent</code>	Boolean, if TRUE, information messages are not displayed, only warnings and errors

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

calculer,report_sea_age-method

Split data according to the limits set in the `limit1hm`, and `limit2hm` arguments of the `report_sea_age-class`.

Description

If no value are provided in the `limit1hm` slot, an error is returned, if no value is provided in the `limit2hm` slot a default upper value for salmon size is taken to ensure all salmon are either of age 1 or 2, but no age 3 are returned

Usage

```
## S4 method for signature 'report_sea_age'
calculer(object, silent)
```

Arguments

object An object of class [report_sea_age-class](#)
 silent Default FALSE, if TRUE the program should no display messages

Value

An object of class [report_sea_age-class](#) with calculated data in slot calcdata

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

calculer,report_silver_eel-method
Calculate individual silver eel parameters.

Description

This calculate method for report_silver_eel, will transform data from long (one line per size characteristic, size, weight, eye diameter, pectoral fin measurement, lateral line and constrast) to wide format (one line per silver eel). It will also calculate Durif silvering index and Pankhurst and Fulton's K.

Usage

```
## S4 method for signature 'report_silver_eel'
calculer(object, silent)
```

Arguments

object An object of class [report_silver_eel-class](#)
 silent Boolean, if TRUE, information messages are not displayed, only warnings and errors

Value

An object of class [report_silver_eel-class](#) with slot calcdata filled, as a list for each counting device

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

calcule,report_species-method
calculate method for report_species

Description

' the number will be split according to the split argument passed to the class, e.g. per year or month or week. Data from different DC will be grouped. Counts are given per taxa, unless there are several stages, in which case the counts correspond to taxa + stage.

Usage

```
## S4 method for signature 'report_species'
calcule(object, silent = FALSE)
```

Arguments

object	An object of class report_species-class
silent	Boolean, if TRUE, information messages are not displayed, only warnings and errors

Value

with calcddata slot filled.

charge *Generic method to load referentials*

Description

Generic method to load referentials

Usage

```
charge(object, ...)
```

Arguments

object	Object
...	Additional parms

Author(s)

cedric.briand

charge,ref_checkbox-method

Loading method for ref_checkbox referential objects

Description

Loading method for ref_checkbox referential objects

Usage

```
## S4 method for signature 'ref_checkbox'  
charge(object, title, labels, checked)
```

Arguments

object	An object of class ref_checkbox-class
title	Title of the frame
labels	Labels for checked
checked	Vector of boolean indicating if ref_checkbox are checked

Value

An object of class [ref_checkbox-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  object=new("ref_checkbox")  
  charge(object,title="essai",labels=c("par1","par2","par3"),checked=c(TRUE,TRUE,TRUE))  
  
## End(Not run)
```

charge,ref_choice-method

Loading method for Rechoice referential objects

Description

Loading method for Rechoice referential objects

Usage

```
## S4 method for signature 'ref_choice'  
charge(object, vecteur, label, selected)
```

Arguments

object	An object of class ref_choice
vecteur	A vector of name, see example code.
label	Labels for the choices
selected	An integer indicating which object is selected at launch

Value

An S4 object of class ref_choice

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other referential.objects: [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

Examples

```
## Not run:  
object=new("ref_choice")  
charge(object,vecteur=c("oui","non"),label="essai",selected=as.integer(1))  
  
## End(Not run)
```

charge,ref_coe-method *loads the coefficients for the period defined in class*

Description

The slots datedebut and datefin have to be filled before using charge

Usage

```
## S4 method for signature 'ref_coe'  
charge(object)
```

Arguments

object An object of class [ref_coe-class](#)

Value

Object of class ref_coe

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
object<- new("ref_coe")  
object@datedebut<-strptime("01/01/1996",format="%d/%m/%Y")  
object@datefin<-strptime("01/01/1997",format="%d/%m/%Y")  
charge(object)  
  
## End(Not run)
```

charge,ref_dc-method *Method to load the counting devices of the control station*

Description

Method to load the counting devices of the control station

Usage

```
## S4 method for signature 'ref_dc'  
charge(object)
```

Arguments

object An object of class [ref_dc-class](#)

Value

Object of class ref_dc

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

charge,ref_df-method *Loading method for DF referential objects*

Description

Loading method for DF referential objects

Usage

```
## S4 method for signature 'ref_df'  
charge(object)
```

Arguments

object An object of class [ref_df-class](#)

Value

An object of class ref_df

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  object=new("ref_df")  
  charge(object)  
  
## End(Not run)
```

charge,ref_env-method *Loading method for ref_env referential object*

Description

Loading method for ref_env referential object

Usage

```
## S4 method for signature 'ref_env'  
charge(object)
```

Arguments

object An object of class [ref_env-class](#)

Value

An S4 object of class ref_env

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
object=new("ref_env")  
charge(object)  
  
## End(Not run)
```

charge,ref_list-method
Loading method for refliste referential objects

Description

Loading method for refliste referential objects

Usage

```
## S4 method for signature 'ref_list'  
charge(object, listechoice, label)
```

Arguments

object	An object of class ref_list-class
listchoice	A character vector setting the possible values in which the user can select
label	A label for refliste

Value

An object of class ref_list

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  object=new("ref_list")  
  charge(object)  
  
## End(Not run)
```

charge,ref_par-method *Loading method for Repar referential objects*

Description

Loading method for Repar referential objects

Usage

```
## S4 method for signature 'ref_par'  
charge(object)
```

Arguments

object	An object of class ref_par-class
--------	--

Value

An S4 object of class ref_par

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  object=new("ref_par")  
  charge(object)  
  
## End(Not run)
```

charge,ref_parqual-method

Loading method for Reparqual referential objects

Description

Loading method for Reparqual referential objects

Usage

```
## S4 method for signature 'ref_parqual'  
charge(object)
```

Arguments

object An object of class [ref_parqual-class](#)

Value

An S4 object of class ref_parqual

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  object=new("ref_parqual")  
  charge(object)  
  
## End(Not run)
```

charge,ref_parquan-method

Loading method for Reparquan referential objects

Description

Loading method for Reparquan referential objects

Usage

```
## S4 method for signature 'ref_parquan'  
charge(object)
```

Arguments

object An object of class [ref_parquan-class](#)

Value

An S4 object of class ref_parquan

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
object=new("ref_parquan")  
charge(object)  
  
## End(Not run)
```

charge,ref_stage-method

Loading method for ref_stage referential objects

Description

Loading method for ref_stage referential objects

Usage

```
## S4 method for signature 'ref_stage'  
charge(object)
```


Arguments

object An object of class [ref_stage-class](#)

Value

An S4 object of class ref_stage

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
object=new("ref_stage")  
charge(object)  
  
## End(Not run)
```

charge,ref_taxa-method

Loading method for ref_taxa referential objects

Description

Loading method for ref_taxa referential objects

Usage

```
## S4 method for signature 'ref_taxa'  
charge(object)
```

Arguments

object An object of class [ref_taxa-class](#)

Value

An S4 object of class ref_taxa

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
object=new("ref_taxa")  
charge(object)  
## End(Not run)
```

charge,ref_textbox-method

Loading method for ReTextBox referential objects

Description

Loading method for ReTextBox referential objects

Usage

```
## S4 method for signature 'ref_textbox'  
charge(object, title, label)
```

Arguments

object	An object of class ref_textbox-class
title	A title for the frame
label	A label for the TextBox

Value

An S4 object of class ref_textbox

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  object=new("ref_textbox")  
  charge(object,title="un titre",label="20")  
  
## End(Not run)
```

charge,ref_year-method

Loading method for ref_year referential objects

Description

Selects year available either in the bjo table (if report_object==report_migInterannelle) or in the t_operation_ope table

Usage

```
## S4 method for signature 'ref_year'
charge(object, objectreport = "report_ge_weight")
```

Arguments

object An object of class ref_year
objectreport The object report, default "report_ge_weight" other possible value report_mig_interannual

Value

object An object of class ref_year with slot data filled with the selected value

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
object=new("ref_year")
charge(object)
validObject(annee)
showMethods("charge")

## End(Not run)
```

charge,report_ge_weight-method
charge method for report_ge_weight class

Description

charge method for report_ge_weight class

Usage

```
## S4 method for signature 'report_ge_weight'
charge(object)
```

Arguments

object An object of class [report_ge_weight-class](#)

Value

report_ge_weight with slots filled with user choice

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

charge,report_mig-method

Loads additional data on migration control operations, df (fishway) dc (counting device).

Description

this method creates additional classes in `envir_stacomi` for later use in plot (operations, DF operation, DC operation). So unlike in most report classes where the charge method is only used by the graphical interface, it is necessary to run charge for report_mig.

Usage

```
## S4 method for signature 'report_mig'
charge(object, silent = FALSE)
```

Arguments

object	An object of class report_mig-class
silent	Should the program be returning messages

Value

An object of class [report_mig-class](#) with slots filled by user choice

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

charge,report_mig_env-method

charge method for report_mig_env class

Description

Unique the other report classes where the charge method is only used by the graphical interface to collect and test objects in the environment `envir_stacomi`, and see if the right choices have been made in the graphical interface, this methods runs the [charge,report_mig_mult-method](#) and needs to be called from the command line (see examples)

Usage

```
## S4 method for signature 'report_mig_env'  
charge(object, silent = FALSE)
```

Arguments

object	An object of class report_mig_env-class
silent	Should the function remain silent (boolean)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

charge,report_mig_mult-method

charge method for report_mig_mult

Description

Unique the other report classes where the charge method is only used by the graphical interface to collect and test objects in the environment `envir_stacomi`, and see if the right choices have been made in the graphical interface, this method is used to load data on migration control operations fishway operations, and counting devices operations as data from those are displayed in the main plots.

Usage

```
## S4 method for signature 'report_mig_mult'  
charge(object, silent = FALSE)
```

Arguments

object	An object of class report_mig_mult-class
silent	Default FALSE, if TRUE the program should no display messages

Value

`report_mig_mult` with slots filled by user choice

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

chargecomplement-methods

Methods for Function chargecomplement

Description

Methods for function chargecomplement method chargecomplement this method is called after selecting the object (data only counts one line) and allows a request to obtain a complement, for instance possible values for a qualitative parameter

Methods

signature(object = "ref_parqual") collects possible values for a qualitative parameter, for instance for parameter sex would be values male & female

Examples

```
## Not run:  
dc_selectionne=6  
taxa_selectionne=2038  
stage_selectionne="AGJ"  
object=new("ref_parqual")  
object<-charge(object)  
chargecomplement(object)  
  
## End(Not run)
```

charge_complement

Generic method to load additional data

Description

Generic method to load additional data

Usage

```
charge_complement(object, ...)
```

Arguments

object	Object
...	Additional parms

Author(s)

cedric.briand

charge_complement,ref_parqual-method

Loads an additional dataset this method is loaded to obtain the possible values of a qualitative parameter. Here data only contains one line

Description

Loads an additional dataset this method is loaded to obtain the possible values of a qualitative parameter. Here data only contains one line

Usage

```
## S4 method for signature 'ref_parqual'  
charge_complement(object)
```

Arguments

object An object of class [ref_parqual-class](#)

Value

An S4 object of class `ref_parqual` with the `valqual` slot filled

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
dc_selectionne=6  
taxa_selectionne=2038  
stage_selectionne="AGJ"  
object=new("ref_parqual")  
object<-charge(object)  
charge_complement(object)  
  
## End(Not run)
```

charge_with_filter,ref_par-method

Loading method for Repar referential objects searching only those parameters existing for a DC, a Taxa, and a stage

Description

Loading method for Repar referential objects searching only those parameters existing for a DC, a Taxa, and a stage

Usage

```
## S4 method for signature 'ref_par'  
charge_with_filter(object, dc_selectionne, taxa_selectionne,  
  stage_selectionne)
```

Arguments

object An object of class [ref_par-class](#)
dc_selectionne A counting device selected for the report
taxa_selectionne The taxa selected for the report
stage_selectionne The stage selected for the report

Value

An S4 object of class `ref_par`

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  object=new("ref_par")  
  charge_with_filter(object,dc_selectionne=6,taxa_selectionne=2038,stage_selectionne=c("AGJ","CIV"))  
  
## End(Not run)
```

charge_with_filter,ref_parqual-method

Loading method for Reparqual referential objects searching only those parameters existing for a DC, a Taxon, and a stage

Description

Loading method for Reparqual referential objects searching only those parameters existing for a DC, a Taxon, and a stage

Usage

```
## S4 method for signature 'ref_parqual'  
charge_with_filter(object, dc_selectionne,  
  taxa_selectionne, stage_selectionne)
```

Arguments

object An object of class [ref_parqual-class](#)
dc_selectionne The dc set in the report object
taxa_selectionne The taxa set in the report object
stage_selectionne The stage set in the report object

Value

An S4 object of class [ref_parqual-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
dc_selectionne=6  
taxa_selectionne=2038  
stage_selectionne="AGJ"  
object=new("ref_parqual")  
charge_with_filter(object,dc_selectionne,taxa_selectionne,stage_selectionne)  
  
## End(Not run)
```

charge_with_filter,ref_parquan-method

Loading method for Reparquan referential objects searching only those parameters existing for a DC, a Taxon, and a stage

Description

Loading method for Reparquan referential objects searching only those parameters existing for a DC, a Taxon, and a stage

Usage

```
## S4 method for signature 'ref_parquan'  
charge_with_filter(object, dc_selectionne,  
  taxa_selectionne, stage_selectionne)
```

Arguments

object An object of class [ref_parquan-class](#)
dc_selectionne The dc set in the report object
taxa_selectionne The taxa set in the report object
stage_selectionne The stage set in the report object

Value

An S4 object of class `ref_parquan`

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
dc_selectionne=6  
taxa_selectionne=2038  
stage_selectionne="AGJ"  
object=new("ref_parquan")  
charge_with_filter(object,dc_selectionne,taxa_selectionne,stage_selectionne)  
  
## End(Not run)
```

charge_with_filter,ref_stage-method

Loading method for ref_stage referential objects searching only those stages existing for a DC and a Taxon

Description

Loading method for ref_stage referential objects searching only those stages existing for a DC and a Taxon

Usage

```
## S4 method for signature 'ref_stage'  
charge_with_filter(object, dc_selectionne,  
  taxa_selectionne)
```

Arguments

object An object of class [ref_stage-class](#)
dc_selectionne The selected counting device
taxa_selectionne The selected species

Value

An S4 object of class [ref_stage-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
dc_selectionne=6  
taxa_selectionne=2038  
object=new("ref_stage")  
charge_with_filter(object,dc_selectionne,taxa_selectionne)  
  
## End(Not run)
```

charge_with_filter,ref_taxa-method

Loading method for ref_taxa referential objects searching only taxa existing for a DC

Description

Loading method for ref_taxa referential objects searching only taxa existing for a DC

Usage

```
## S4 method for signature 'ref_taxa'  
charge_with_filter(object, dc_selectionne)
```

Arguments

object An object of class [ref_taxa-class](#)
dc_selectionne A counting device selected, only taxa attached to this dc are selected

Value

An S4 object of class ref_taxa

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
dc_selectionne=6  
object=new("ref_taxa")  
charge_with_filter(object,dc_selectionne=dc_selectionne)  
## End(Not run)
```

choicemult,ref_dc-method

choicemult, selection method for ref_dc allowing to select several DC

Description

choicemult, selection method for ref_dc allowing to select several DC

Usage

```
## S4 method for signature 'ref_dc'
choicemult(object, objectreport = NULL,
           is.enabled = TRUE)
```

Arguments

object	An object of class ref_dc
objectreport	A report object
is.enabled	A boolean indicating if the widget can be selected at launch

Note

The choice method has for arguments a report (report) object (e.g) is called from a report report(e.g report_sample_char). By default, the value of the objectreport is null. When it is not the method calls daughter widgets (e.g. the dc widget will call species) and fills it with the method [charge_with_filter,ref_taxa-method](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
win=gwindow()
group=gggroup(container=win,horizontal=FALSE)
object=new("ref_dc")
object<-charge(object)
objectreport=new("report_mig_mult")
choicemult(object=object,objectreport=objectreport)

## End(Not run)
```

choicemult,ref_taxa-method

Multiple Choice method for reftaxa referential objects, the graphical interface is built to allow for multiple choices. See load for method in the command line.

Description

Multiple Choice method for reftaxa referential objects, the graphical interface is built to allow for multiple choices. See load for method in the command line.

Usage

```
## S4 method for signature 'ref_taxa'  
choicemult(object, objectreport = NULL,  
           is.enabled = TRUE)
```

Arguments

object	An object of class ref_taxa-class
objectreport	An object report which includes the ref_taxa-class , default NULL
is.enabled	Sets if the frame is enabled at launch, default TRUE

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
object=new("ref_taxa")  
win=gwindow()  
group=gggroup(container=win,horizontal=FALSE)  
object<-charge(object)  
report_mig=new(report_mig)  
choicemult(object,objectreport=report_mig)  
  
## End(Not run)
```

choice_c,ref_choice-method

Choice_c method for refchoix referential objects

Description

Choice_c method for refchoix referential objects

Usage

```
## S4 method for signature 'ref_choice'  
choice_c(object, selectedvalue)
```

Arguments

object	An object of class ref_list-class
selectedvalue	the value selected in the combo

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
object=new("ref_list")
object<-charge(object,vecteur=c("1","2"),label="please choose")
object<-choice_c(object)

## End(Not run)
```

choice_c,ref_dc-method

Command line interface to select a counting device

Description

the choice_c method is intended to have the same behaviour as choice (which creates a widget in the graphical interface) but from the command line. The parameters for dc are transformed to integer as the ref_dc only takes integer in the dc slots. The method also loads the stations and ouvrages (dams) associated with the counting device (dc). The values passed to the choice_c method are then checked with the setValidity method. Finally, if an objectreport is passed as a parameter, the method will do a charge_with_filter to select only the taxa present in the counting devices

Usage

```
## S4 method for signature 'ref_dc'
choice_c(object, dc)
```

Arguments

object	an object of class ref_dc
dc	a character vector of dc chosen

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

Examples

```
## Not run:
win=gwindow()
group=gggroup(container=win,horizontal=FALSE)
object=new("ref_dc")
object<-charge(object)
objectreport=new("report_mig_mult")
choice_c(object=object,objectreport=objectreport,dc=1)

## End(Not run)
```

choice_c,ref_df-method

Command line interface to choose a fishway

Description

the choice_c method is intended to have the same behaviour as choice (which creates a widget in the graphical interface) but from the command line. The parameters for dF are transformed to integer as the ref_df only takes integer in the df slots. DF are third in hierarchy in the stacomi database Station>ouvrage>DF>DC>operation. This class is only used in the report_df class.

Usage

```
## S4 method for signature 'ref_df'  
choice_c(object, df)
```

Arguments

object	an object of class ref_df-class
df	a character vector of df chosen

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
win=gwindow()  
group=ggroup(container=win, horizontal=FALSE)  
object=new("ref_df")  
object<-charge(object)  
objectreport=new("report_mig_mult")  
choice_c(object=object, objectreport=objectreport, dc=1)  
  
## End(Not run)
```

choice_c,ref_env-method*Command line interface to select a monitoring station*

Description

the choice_c method is intended to have the same behaviour as choice (which creates a widget in the graphical interface) but from the command line.

Usage

```
## S4 method for signature 'ref_env'
choice_c(object, stationMesure)
```

Arguments

`object` an object of class `ref_env`

`stationMesure` a character vector of the monitoring station code (corresponds to `stm_libelle` in the `tj_stationmesure_stm` table)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,ref_horodate-method

Command line

Description

Command line

Usage

```
## S4 method for signature 'ref_horodate'
choice_c(object, nomassign = "horodate",
  funoutlabel = "nous avons le choix dans la date\n", horodate,
  silent = FALSE)
```

Arguments

`object` An object of class [ref_horodate-class](#)

`nomassign` The name assigned in environment `envir_stacom`i

`funoutlabel`, text displayed by the interface

`horodate` The horodate to set, formats "`%d/%m/%Y %H:%M:%s`", "`%d/%m/%y %H:%M:%s`", "`%Y-%m-%d %H:%M:%s`" formats can also be passed with the date set to the minute `%d/%m/%Y %H:%M` or the day `%d/%m/%Y ...` are accepted. The `choice_c` method assigns and

`silent` Default FALSE, should messages be displayed

Value

An object of class [ref_horodate-class](#) with slot `horodate` set, and assigns an object of class POSIXt with name `nomassign` in `envir_stacom`i

choice_c,ref_list-method

Choice_c method for ref_list referential objects

Description

Choice_c method for ref_list referential objects

Usage

```
## S4 method for signature 'ref_list'  
choice_c(object, selectedvalue)
```

Arguments

object An object of class [ref_list-class](#)
selectedvalue the value selected in the combo

Note

the choice method assigns an object of class refList named ref_list in the environment envir_stacom

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
object=new("ref_list")  
object<-charge(object,vecteur=c("1","2"),label="please choose")  
object<-choice_c(object)  
  
## End(Not run)
```

choice_c,ref_par-method

Command line interface to select a parameter

Description

the choice_c method is intended to have the same behaviour as choice (which creates a widget in the graphical interface) but from the command line. If an objectreport is passed as a parameter, the method will do a charge_with_filter to select only the taxa present in the counting devices

Usage

```
## S4 method for signature 'ref_par'  
choice_c(object, par, silent = FALSE)
```

Arguments

object	an object of class ref_par-class
par	A character vector of par
silent	Default FALSE but not used there

Value

An object of class [ref_par-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,ref_stage-method

choice_c method for ref_stage

Description

the choice_c method is intended to have the same behaviour as choice (which creates a widget in the graphical interface) but from the command line. The values passed to the choice_c method for stage is the code. Any numeric value will be discarded

Usage

```
## S4 method for signature 'ref_stage'  
choice_c(object, stage, silent = FALSE)
```

Arguments

object	An object of class ref_stage-class
stage	the vector of stages chosen
silent	Boolean, if TRUE, information messages are not displayed

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
object=new("ref_taxa")
object<-charge(object)
objectreport=new("report_mig_mult")
choice_c(object=object,objectreport=objectreport,"Anguilla anguilla")

## End(Not run)
```

choice_c,ref_taxa-method

choice_c method for ref_taxa

Description

the choice_cc method is intended to have the same behaviour as choice (which creates a widget in the graphical interface) but from the command line. The values passed to the choice_c method for taxa can be either numeric (2038 = Anguilla anguilla) or character.

Usage

```
## S4 method for signature 'ref_taxa'
choice_c(object, taxa)
```

Arguments

object	An object from the class ref_taxa
taxa	The vector of taxa, can be either code (numeric) or latin name

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
object=new("ref_taxa")
object<-charge(object)
objectreport=new("report_mig_mult")
choice_c(object=object,objectreport=objectreport,"Anguilla anguilla")

## End(Not run)
```

 choice_c,ref_textbox-method

Choice_c method for ReTextBox referential objects

Description

Choice_c method for ReTextBox referential objects

Usage

```
## S4 method for signature 'ref_textbox'
choice_c(object, value, nomassign = "ref_textbox")
```

Arguments

object	An object of class ref_textbox-class
value	The value to set
nomassign	The name with which the object will be assigned in envir_stacomi

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

 choice_c,ref_timestep_daily-method

choice_c method for class ref_timestep_daily

Description

the choice_c method is intended to have the same behaviour as choice (which creates a widget in the graphical interface) but from the command line.

Usage

```
## S4 method for signature 'ref_timestep_daily'
choice_c(object, datedebut, datefin)
```

Arguments

object	An object of class ref_timestep_daily-class
datedebut	A character (format "15/01/1996" or "1996-01-15" or "15-01-1996"), or POSIXct object
datefin	A character

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
object=new("ref_dc")
object<-charge(object)
choice_c(object=object,datedebut="2012-01-01",datefin="2013-01-01")

## End(Not run)
```

choice_c,ref_year-method

choice_c method for ref_year referential from the command line

Description

The choice_c method will issue a warning if the year is not present in the database Allows the selection of year and the assignment in environment envir_stacomis

Usage

```
## S4 method for signature 'ref_year'
choice_c(object, annee, nomassign = "ref_year",
  funoutlabel = gettext("Year selected\n", domain = "R-stacomisR"),
  silent = FALSE)
```

Arguments

object	An object of class ref_year-class
annee	The year to select, either as a character or as a numeric
nomassign	The name to be assigned in envir_stacomis
funoutlabel	The label that appears in funout
silent	Stops messages from being displayed if silent=TRUE, default FALSE

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
object=new("ref_year")
object<-charge(object)
win=gwindow(title="test ref_year")
group=gggroup(container=win,horizontal=FALSE)
choice(object,nomassign="ref_year",funoutlabel="essai",titleFrame="essai ref_year",preselect=1)
dispose(win)

## End(Not run)
```

choice_c,report_annual-method

command line interface for [report_annual-class](#)

Description

command line interface for [report_annual-class](#)

Usage

```
## S4 method for signature 'report_annual'
choice_c(object, dc, taxa, stage, annee debut,
         annee fin, silent = FALSE)
```

Arguments

object	An object of class report_annual-class
dc	A numeric or integer, the code of the dc, coerced to integer, see choice_c,ref_dc-method
taxa	Either a species name in latin or the SANDRE code for species (ie 2038=Anguilla anguilla), it should match the ref.tr_taxon_tax referential table in the stacom database, see choice_c,ref_taxa-method
stage	A stage code matching the ref.tr_stadedeveloppement_std table in the stacom database, see choice_c,ref_stage-method
annee debut	The starting the first year, passed as character or integer
annee fin	the finishing year
silent	Boolean, if TRUE, information messages are not displayed

Value

An object of class [report_annual-class](#) The choice_c method fills in the data slot for classes [ref_dc-class](#), [ref_taxa-class](#), [ref_stage-class](#) and two slots of [ref_year-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_dc-method

command line interface for report_dc class

Description

The choice_c method fills in the data slot for ref_dc, and then uses the choice_c methods of these object to "select" the data.

Usage

```
## S4 method for signature 'report_dc'
choice_c(object, dc, horodatedebut, horodatefin,
         silent = FALSE)
```

Arguments

object	An object of class ref_dc-class
dc	The dc to set
horodatedebut	A POSIXt or Date or character to fix the date of beginning of the report
horodatefin	A POSIXt or Date or character to fix the last date of the report
silent	Should program be silent or display messages

Value

An object of class [ref_dc-class](#) with slots filled

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_df-method

command line interface for report_df class

Description

The choice_c method fills in the data slot for ref_df, and then uses the choice_c methods of these object to "select" the data.

Usage

```
## S4 method for signature 'report_df'
choice_c(object, df, horodatedebut, horodatefin,
         silent = FALSE)
```


Arguments

object	An object of class ref_df-class
df	The df to set
horodatedebut	A POSIXt or Date or character to fix the date of beginning of the report
horodatefin	A POSIXt or Date or character to fix the last date of the report
silent	Should program be silent or display messages

Value

An object of class [ref_df-class](#) with slots filled

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_env-method

command line interface for report_env class

Description

command line interface for report_env class

Usage

```
## S4 method for signature 'report_env'
choice_c(object, stationMesure, datedebut, datefin,
        silent = FALSE)
```

Arguments

object	An object of class report_env-class
stationMesure	A character, the code of the monitoring station, which records environmental parameters choice_c,ref_env-method
datedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
datefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.
silent	Boolean default FALSE, if TRUE information messages not displayed.

Value

An object of class [report_env-class](#) The choice_c method fills in the data slot for ref_env and then uses the choice_c methods of these object to select the data.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr> @aliases choice_c.report_env

choice_c,report_ge_weight-method

command line interface for [report_ge_weight-class](#)

Description

command line interface for [report_ge_weight-class](#)

Usage

```
## S4 method for signature 'report_ge_weight'
choice_c(object, dc, aneedebut, aneefin,
         selectedvalue, silent = FALSE)
```

Arguments

object	An object of class report_ge_weight-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
anneedebut	The starting the first year, passed as character or integer
aneefin	the finishing year, must be > aneedebut (minimum one year in august to the next in august)
selectedvalue	A character to select and object in the ref_list-class
silent	Boolean, if TRUE, information messages are not displayed

Value

An object of class [report_ge_weight-class](#) The choice_c method fills in the data slot for classes [ref_dc-class](#) [ref_year-class](#) [ref_coe-class](#) [ref_list-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_mig-method

command line interface for report_mig class

Description

command line interface for report_mig class

Usage

```
## S4 method for signature 'report_mig'  
choice_c(object, dc, taxa, stage, datedebut, datefin)
```

Arguments

object	An object of class report_mig-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
taxa	Either a species name in latin or the SANDRE code for species (ie 2038=Anguilla anguilla), these should match the ref.tr_taxon_tax referential table in the stacom database, see choice_c,ref_taxa-method
stage	A stage code matching the ref.tr_stadedeveloppement_std table in the stacom database see choice_c,ref_stage-method
datedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
datefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.

Value

An object of class [report_mig-class](#) The choice_c method fills in the data slot for ref_dc, ref_taxa, ref_stage, and refref_timestep_daily and then uses the choice_c methods of these object to select the data.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_mig_char-method
command line interface for report_mig_char class

Description

command line interface for report_mig_char class

Usage

```
## S4 method for signature 'report_mig_char'
choice_c(object, dc, taxa, stage, parquan = NULL,
         parqual = NULL, horodatedebut, horodatefin, echantillon = gettext("with",
         domain = "R-stacomir"), silent = FALSE)
```

Arguments

object	An object of class report_mig_char-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
taxa	'2220=Salmo salar', can be a vector with several values these should match the ref.tr_taxon_tax referential table in the stacomir database, see choice_c,ref_taxa-method
stage	The stages selected, can be a vector with several values
parquan	Quantitative parameter
parqual	Qualitative parameter
horodatedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
horodatefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.
echantillon	Default "with" can be "without" (values "avec" and "sans") are accepted, checking without modifies the query in the connect method so that subsamples are not allowed,
silent	Default FALSE, if TRUE the program should no display messages

Value

An object of class [report_sea_age-class](#) The choice_c method fills in the data slot for classes [ref_dc-class](#), [ref_taxa-class](#), [ref_stage-class](#), [ref_par-class](#) and two slots of [ref_horodate-class](#) and then uses the choice_c methods of these object to select the data.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_mig_env-method
command line interface for report_env class

Description

command line interface for report_env class

Usage

```
## S4 method for signature 'report_mig_env'
choice_c(object, dc, taxa, stage, stationMesure,
         datedebut, datefin, silent = FALSE)
```

Arguments

object	An object of class report_env-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
taxa	'2038=Anguilla anguilla', these should match the ref.tr_taxon_tax referential table in the stacomi database, see choice_c,ref_taxa-method
stage	'AGJ=Yellow eel', 'AGG=Silver eel', 'CIV=glass eel'
stationMesure	A character, the code of the monitoring station, which records environmental parameters choice_c,ref_env-method
datedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
datefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.
silent	Boolean default FALSE, if TRUE information messages not displayed.

Value

An object of class [report_env-class](#) The choice_c method fills in the data slot for ref_env and then uses the choice_c methods of these object to select the data.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_mig_interannual-method
command line interface for report_mig_interannual class

Description

command line interface for report_mig_interannual class

Usage

```
## S4 method for signature 'report_mig_interannual'
choice_c(object, dc, taxa, stage, aneedebut,
         anneefin, silent = FALSE)
```

Arguments

object	An object of class report_mig_interannual-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
taxa	Either a species name in latin or the SANDRE code for species (ie 2038=Anguilla anguilla), it should match the ref.tr_taxon_tax referential table in the stacom database, see choice_c,ref_taxa-method
stage	A stage code matching the ref.tr_stadedeveloppement_std table in the stacom database, see choice_c,ref_stage-method
anneedebut	The starting the first year, passed as charcter or integer
anneefin	the finishing year
silent	Boolean, if TRUE, information messages are not displayed

Value

An object of class [report_mig_interannual-class](#) The choice_c method fills in the data slot for classes [ref_dc-class](#), [ref_taxa-class](#), [ref_stage-class](#) and two slots of [ref_year-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_mig_mult-method

command line interface for report_mig_mult class

Description

The choice_c method fills in the data slot for ref_dc, ref_taxa, ref_stage and then uses the choice_c methods of these object to "select" the data.

Usage

```
## S4 method for signature 'report_mig_mult'  
choice_c(object, dc, taxa, stage, datedebut,  
         datefin, silent = FALSE)
```

Arguments

object	An object of class report_mig-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
taxa	Either a species name in latin or the SANDRE code for species (ie 2038=Anguilla anguilla), these should match the ref.tr_taxon_tax referential table in the stacomi database, see choice_c,ref_taxa-method
stage	A stage code matching the ref.tr_stadedeveloppement_std table in the stacomi database see choice_c,ref_stage-method
datedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
datefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.
silent	Should messages be hided default FALSE

Value

An object of class [report_mig_mult-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_sample_char-method

command line interface for report_sample_char class

Description

command line interface for report_sample_char class

Usage

```
## S4 method for signature 'report_sample_char'
choice_c(object, dc, taxa, stage, par,
         horodatedebut, horodatefin, silent = FALSE)
```

Arguments

object	An object of class report_sample_char-class
dc	A numeric or integer, the code of the dc, coerced to integer, see choice_c,ref_dc-method
taxa	Either a species name in latin or the SANDRE code for species (ie 2038=Anguilla anguilla), these should match the ref.tr_taxon_tax referential table in the stacomi database, see choice_c,ref_taxa-method
stage	A stage code matching the ref.tr_stadedeveloppement_std table in the stacomi database, see choice_c,ref_stage-method
par	A parameter matching th ref.tg_parametre_par table in the stacomi database, see choice_c,ref_par-method
horodatedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
horodatefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.
silent	Boolean, if TRUE, information messages are not displayed

Value

An object of class [report_mig-class](#) The choice_c method fills in the data slot for classes [ref_dc-class](#), [ref_taxa-class](#), [ref_stage-class](#), [ref_par-class](#) and two slots of [ref_horodate-class](#) and then uses the choice_c methods of these object to select the data.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_sea_age-method
command line interface for report_sea_age class

Description

command line interface for report_sea_age class

Usage

```
## S4 method for signature 'report_sea_age'
choice_c(object, dc, taxa = 2220, stage = c("5",
      "11", "BEC", "BER", "IND"), par = c("1786", "1785", "C001", "A124"),
      horodatedebut, horodatefin, limit1hm, limit2hm, silent = FALSE)
```

Arguments

object	An object of class report_sea_age-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
taxa	'2220=Salmo salar', these should match the ref.tr_taxon_tax referential table in the stacomi database, see choice_c,ref_taxa-method
stage	'5','11','BEC','BER','IND'
par	Parameters chosen for the report are measured body size (1786), measured fork length (1785),video size (C001) and number of year at sea (A124)
horodatedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
horodatefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.
limit1hm	Size limit of a salmon for an one sea winter fish
limit2hm	Size limit of a salmon for a two sea winter fish
silent	Default FALSE, if TRUE the program should no display messages

Value

An object of class [report_sea_age-class](#) The choice_c method fills in the data slot for classes [ref_dc-class](#), [ref_taxa-class](#), [ref_stage-class](#), [ref_par-class](#) and two slots of [ref_horodate-class](#) and then uses the choice_c methods of these object to select the data.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

 choice_c,report_silver_eel-method

command line interface for report_silver_eel class

Description

command line interface for report_silver_eel class

Usage

```
## S4 method for signature 'report_silver_eel'
choice_c(object, dc, taxa = 2038,
  stage = "AGG", par = c("1786", "CCCC", "BBBB", "CONT", "LINP", "A111",
    "PECT"), horodatedebut, horodatefin, silent = FALSE)
```

Arguments

object	An object of class report_silver_eel-class
dc	A numeric or integer, the code of the dc, coerced to integer, see choice_c,ref_dc-method
taxa	'2038=Anguilla anguilla', these should match the ref.tr_taxon_tax referential table in the stacomi database, see choice_c,ref_taxa-method
stage	'AGG'
par	Parameters chosen for the report are body size (1786), vertical eye diameter (BBBB), horizontal eye diameter (CCCC), body contrast (CONT), presence of punctuation on the lateral line (LINP), length of the pectoral fin (PECT)
horodatedebut	The starting date as a character, formats like %Y-%m-%d or %d-%m-%Y can be used as input
horodatefin	The finishing date of the report, for this class this will be used to calculate the number of daily steps.
silent	Boolean, if TRUE, information messages are not displayed

Value

An object of class [report_mig-class](#) The choice_c method fills in the data slot for classes [ref_dc-class](#), [ref_taxa-class](#), [ref_stage-class](#), [ref_par-class](#) and two slots of [ref_horodate-class](#) and then uses the choice_c methods of these object to select the data.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

choice_c,report_species-method
command line interface for [report_species-class](#)

Description

command line interface for [report_species-class](#)

Usage

```
## S4 method for signature 'report_species'
choice_c(object, dc, split = "none", aneedebut,
         anneefin, silent = FALSE)
```

Arguments

object	An object of class report_species-class
dc	A numeric or integer, the code of the dc, coerced to integer,see choice_c,ref_dc-method
split	one of c("none","week","month","year")
anneedebut	The starting the first year, passed as character or integer
anneefin	the finishing year
silent	Boolean, if TRUE, information messages are not displayed

Value

An object of class [report_species-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

coef_durif *Silvering index coefficients from Caroline Durif (2009) to predict sil-
 vering stage from morphological parameters*

Description

Classification scores are calculated by multiplying the metrics BL = body length, W = weight, MD = mean eye diameter (Dv+Dh)/2, and FL length of the pectoral fin, with each parameter p as $S=Constant+BL*p(bl)+W*p(W)...$ The stage chosen is the one achieving the highest score

Usage

```
coef_durif
```

Format

An object of class `matrix` with 5 rows and 6 columns.

References

Durif, C.M., Guibert, A., and Elie, P. 2009. Morphological discrimination of the silvering stages of the European eel. In American Fisheries Society Symposium. pp. 103-111. <http://fishlarvae.org/common/SiteMedia/durif%20et%20al%202009b.pdf>

colortable	<i>Builds a table with colors to merge with a dataframe for later use in ggplot. An initial check will be done on the name of the color vector. A data frame is built. It contains a column color which is a factor. The factor order match the order of the vector (not the alphabetical order of the colors).</i>
------------	---

Description

Builds a table with colors to merge with a dataframe for later use in ggplot. An initial check will be done on the name of the color vector. A data frame is built. It contains a column color which is a factor. The factor order match the order of the vector (not the alphabetical order of the colors).

Usage

```
colortable(color = NULL, vec, palette = "Set2",
           color_function = "brewer.pal")
```

Arguments

color	Either null (default) or a named vector of colors, the names should correspond to the values of vec
vec	The vector to match the color with, if a named vector or color is supplied the names should match
palette,	the name of the RColorBrewer palette, defaults to "Set2", ignored for other color gradient functions and if a named vector of colors is provided
color_function,	the name of the function used to brew the colors, one for "brewer.pal", "gray.colors", default to "brewer.pal, this argument is ignored if a named vector of color is passed.

Value

A dataframe with two columns, the vector (name) and the color (color) as a reordered factor

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_annual-method

connect method for report_annual class this method performs the sum over the year attention this function does not count subsamples.

Description

connect method for report_annual class this method performs the sum over the year attention this function does not count subsamples.

Usage

```
## S4 method for signature 'report_annual'
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_annual-class
silent	Stops messages from being displayed if silent=TRUE, default FALSE

Value

An instantiated object with values filled with user choice
 A dataframe with column effectif, comprising the sum of report_mig counts

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_dc-method

connect method for report_dc

Description

loads the working periods and type of arrest or disfunction of the DC

Usage

```
## S4 method for signature 'report_dc'
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_dc-class
silent	boolean, default FALSE, if TRUE messages are not displayed

Value

An object of class [report_dc-class](#)

Author(s)

cedric.briand

connect,report_df-method

connect method for report_df

Description

connect method for report_df

Usage

```
## S4 method for signature 'report_df'  
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_df-class loads the working periods and type of arrest or disfunction of the DF
silent	Boolean, TRUE removes messages.

Value

An object of class report_df

Author(s)

cedric.briand

connect,report_env-method
connect method for report_env class

Description

connect method for report_env class

Usage

```
## S4 method for signature 'report_env'  
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_env-class
silent	Default FALSE, if TRUE the program should no display messages

Value

an object of report_env class

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_ge_weight-method
connect method for report_Poids_moyen

Description

connect method for report_Poids_moyen

Usage

```
## S4 method for signature 'report_ge_weight'  
connect(object)
```

Arguments

object	An object of class report_ge_weight-class
--------	---

Value

report_Poids_Moyen request corresponding to user choices, mean weight w is calculated as $\text{car_valeur_quantitatif}/\text{lot_effectif}$. These coefficients are stored in the database, and the connect method loads them from the table using the [ref_coe-class](#)

Note

dates for the request are from august to august (a glass eel season)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_mig-method
connect method for report_mig

Description

uses the report_mig_mult method

Usage

```
## S4 method for signature 'report_mig'  
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_mig-class
silent	Boolean default FALSE, if TRUE information messages not displayed

Value

report_mig with slot @data filled from the database

connect,report_mig_char-method
connect method for report_mig_char

Description

uses the report_mig_mult method

Usage

```
## S4 method for signature 'report_mig_char'  
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_mig_char-class
silent	Boolean default FALSE, if TRUE information messages not displayed

Value

report_mig_char with slot @data filled from the database

connect,report_mig_env-method
connect method for report_mig_env class

Description

connect method for report_mig_env class

Usage

```
## S4 method for signature 'report_mig_env'  
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_mig_env-class
silent	Default FALSE, if TRUE the program should no display messages

Value

an object of report_mig_env class

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

```
connect,report_mig_interannual-method  
    connect method for report_mig_interannual
```

Description

This method will check if the data in the `t_reportjournalier_bjo` table has no missing data, if missing the program will load missing data. As a second step, the program will check if the numbers in the table `t_reportjournalier_bjo` differ from those in the database, and propose to re-run the `report_mig` (which has a `write_database` method to write daily reports) for those years.

Usage

```
## S4 method for signature 'report_mig_interannual'  
connect(object, silent = FALSE,  
        check = TRUE)
```

Arguments

<code>object</code>	An object of class <code>report_mig_interannual-class</code>
<code>silent</code>	Stops messages from being displayed if <code>silent=TRUE</code> , default <code>FALSE</code>
<code>check</code>	Checks that data are corresponding between <code>report_annual</code> and <code>report_mig</code>

Value

`report_mig_interannual` an instantiated object with values filled with user choice

Note

We expect different results between daily reports from the `t_reportjournalier_bjo` table and the annual sums from `report_annual` for glass eels as those may have been weighted and not only counted. The `t_reportjournalier_bjo` table used by `report_mig_interannual` contains the sum of glass eel numbers converted from weights and those directly counted. The `report_annual` does not.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_mig_mult-method
connect method for report_mig_mult

Description

this method loads data from the database for report_mig but also fills the table of conversion coefficient, if the taxa is eel. It also calls connect method for [report_df-class](#), [report_dc-class](#) and [report_ope-class](#) associated with the report and used by the [fungraph](#) and [fungraph_glasseel](#) functions.

Usage

```
## S4 method for signature 'report_mig_mult'
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_mig_mult-class
silent	Boolean, if TRUE messages are not displayed

Value

An object of class [report_mig_mult-class](#) with slot @data filled from the database

connect,report_ope-method
connect method for report_ope

Description

connect method for report_ope

Usage

```
## S4 method for signature 'report_ope'
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_ope-class load data from the operation table, one dataset per DC
silent	Boolean, TRUE removes messages.

Value

An object of class [report_ope-class](#)

Author(s)

cedric.briand

connect,report_sample_char-method

connect method for report_sample_char

Description

connect method for report_sample_char

Usage

```
## S4 method for signature 'report_sample_char'  
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_sample_char-class
silent	Boolean if TRUE messages are not displayed

Value

An object of class [report_sample_char-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_sea_age-method

connect method for report_sea_age

Description

connect method for report_sea_age

Usage

```
## S4 method for signature 'report_sea_age'  
connect(object, silent = FALSE)
```

Arguments

object An object of class [report_sea_age-class](#)
silent Default FALSE, if TRUE the program should no display messages

Value

An object of class [report_sea_age-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_silver_eel-method
connect method for report_silver_eel

Description

connect method for report_silver_eel

Usage

```
## S4 method for signature 'report_silver_eel'  
connect(object, silent = FALSE)
```

Arguments

object An object of class [report_silver_eel-class](#)
silent Boolean if TRUE messages are not displayed

Value

An object of class [report_silver_eel-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

connect,report_species-method
connect method for report_species

Description

connect method for report_species

Usage

```
## S4 method for signature 'report_species'  
connect(object, silent = FALSE)
```

Arguments

object	An object of class report_species
silent	Boolean, if TRUE, information messages are not displayed

Value

An object of class report_species with data slot filled

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

createmessage *Generic method to forward outputs*

Description

Generic method to forward outputs

Usage

```
createmessage(object, ...)
```

Arguments

object	Object
...	Additional parms

Author(s)

cedric.briand

current_end_date,ref_timestep-method

Gets the ending date of a time step for an object of class [ref_timestep-class](#)

Description

Gets the ending date of a time step for an object of class [ref_timestep-class](#)

Usage

```
## S4 method for signature 'ref_timestep'
current_end_date(object)
```

Arguments

object An object of class [ref_timestep-class](#)

Value

Currentend_date, The ending date for the current timestep

envir_stacomi *Environment where most objects from the package are stored and then loaded by the charge method*

Description

envir_stacomi envir_stacomi <- new.env(parent = baseenv()) is the environment where most object created by the interface are stored

This is where the graphical interface stores its objects try ls(envir=envir_stacomi)

This is where the graphical interface stores its objects try ls(envir=envir_stacomi)

Usage

```
envir_stacomi
```

```
envir_stacomi
```

```
envir_stacomi
```

Format

An object of class environment of length 0.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

funbarchart1DC *Handler for barchart for report_df class from the graphical interface*

Description

Handler for barchart for report_df class from the graphical interface

Usage

```
funbarchart1DC(h, ...)
```

Arguments

h	handler
...	additional parameters

Note

The program cuts periods which overlap between two month

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fungraph *Function for report_mig graphs including numbers DF DC operations*

Description

This graph is for species other than glass eel

Usage

```
fungraph(report_mig, tableau, time.sequence, taxa, stage, dc = NULL, silent,  
          color = NULL, color_ope = NULL, ...)
```


Arguments

report_mig	An object of class <code>report_mig</code>
tableau	A data frame with the with the following columns : No.pas,debut_pas,fin_pas,ope_dic_identifiant,lot_tax_code,lot_std_code,type_de_quantite,MESURE,CALCULE,EXPERT,PONCTUEL,Effectif_total,taux_d_echappement,coe_valeur_coefficient
time.sequence	A vector POSIXt
taxa	The species
stage	The stage
dc	The DC
silent	Message displayed or not
color	Default NULL, a vector of color in the following order, working, stopped, 1...5 types of operation for the fishway or DC, measured, calculated, expert, direct observation. If null will be set to <code>brewer.pal(12,"Paired")[c(8,10,4,6,1,2,3,5,7)]</code>
color_ope	Default NULL, a vector of color for the operations. Default to <code>brewer.pal(4,"Paired")</code>
...	additional parameters passed to <code>matplot</code> , <code>main</code> , <code>ylab</code> , <code>ylim</code> , <code>lty</code> , <code>pch</code> , <code>bty</code> , <code>cex.main</code> , it is currently not a good idea to change <code>xlim</code> (numbers are wrong, the month plot covers all month, and legend placement is wrong)

Note

this function is intended to be called from the plot method in `report_mig_mult` and `report_mig`

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fungraph_glasseel	<i>Graph function for glass eel migration. Differs from fungraph as it does not draw the ggplot graph for month</i>
-------------------	---

Description

This graph will also plot numbers and bars according to whether the glass eel have been counted through weight or numbers

Usage

```
fungraph_glasseel(report_mig, table, time.sequence, taxa, stage, dc = null,
  silent, color = NULL, color_ope = NULL, ...)
```

Arguments

report_mig	an object of class report_mig-class or an object of class report_mig_mult-class
table	a data frame with the results
time.sequence	a vector POSIXt
taxa	the species
stage	the stage
dc	the counting device, default to null, only necessary for report_mig_mult-class
silent	Message displayed or not
color	Default NULL, a vector of length 11 of color in the following order, numbers, weight, working, stopped, 1...5 types of operation, the 2 latest colors are not used but kept for consistency with fungraph for the fishway, if null will be set to <code>brewer.pal(12,"Paired")[c(4,6,1,2,3,5,7,8,10,11,12)]</code>
color_ope	Default NULL, a vector of color for the operations. Default to <code>brewer.pal(4,"Paired")</code>
...	additional parameters passed to plot, main, ylab, cex.main, font.main, type, xlim, ylim, lty, bty, pch it is not possible to change xlim

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

funstat

Function to calculate statistics per month

Description

Function to calculate statistics per month

Usage

```
funstat(tableau, time.sequence, taxa, stage, DC, silent)
```

Arguments

tableau	A table with the following columns : No.pas,debut_pas,fin_pas, ope_dic_identifiant,lot_tax_code,lot_std_EXPERT,PONCTUEL,Effectif_total,taux_d_echappement,coe_valeur_coefficient
time.sequence	Passed from report_mig or report_mig_mult
taxa	Taxa
stage	The Stage
DC	The counting device
silent	Message displayed or not

Note

this function is intended to be called from within the summary method

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

funstat_daily *function to create daily statistics*

Description

function to create daily statistics

Usage

```
funstat_daily(tableau, time.sequence, taxa, stage, DC)
```

Arguments

tableau	A table
time.sequence	Time sequence from report_mig and report_mig_mult
taxa	A taxa
stage	A stage
DC	A counting device

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

funtable *function to print and save statistics in .csv and .html formats for re-
port_mig and report_mig_mult class*

Description

function to print and save statistics in .csv and .html formats for report_mig and report_mig_mult class

Usage

```
funtable(tableau, time.sequence, taxa, stage, DC, resum, silent)
```

Arguments

tableau	A table with the following columns : No.pas,debut_pas,fin_pas, ope_dic_identifiant,lot_tax_code,lot_std_EXPERT,PONCTUEL,Effectif_total,taux_d_echappement,coe_valeur_coefficient
time.sequence	Passed from report_mig or report_mig_mult
taxa	Taxa
stage	The Stage
DC	The counting device
resum	A summary table generated by funstat
silent	If TRUE, all messages turned off (except warnings and errors)

Note

this function is intended to be called from within the summary method

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fun_aggreg_for_plot *returns a table where all components within the list calcddata are aggregated and formatted for plot*

Description

returns a table where all components within the list calcddata are aggregated and formatted for plot

Usage

```
fun_aggreg_for_plot(object)
```

Arguments

object An object of class `report_mig_mult-class`

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fun_char_spe	<i>function used to remove special non utf8 character which cause the gtk interface to crash</i>
--------------	--

Description

function used to remove special non utf8 character which cause the gtk interface to crash

Usage

```
fun_char_spe(text)
```

Arguments

text	a text string which might contain no utf8 characters
------	--

Value

text

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fun_date_extraction	<i>This function extracts temporal characteristics from a dataframe</i>
---------------------	---

Description

This function extracts temporal characteristics from a dataframe

Usage

```
fun_date_extraction(data, nom_coldt, annee = TRUE, mois = TRUE,  
  quinzaine = FALSE, semaine = TRUE, semaine_std = FALSE,  
  jour_an = FALSE, jour_mois = TRUE, heure = FALSE)
```

Arguments

data	a data frame containing a Date or POSIXt column
nom_coldt	the name of the column containing date or POSIXt entry to be processed
annee	logical do you want a column describing year to be added to the dataframe
mois	logical, add column with month
quinzaine	logical, add column with 15 days

semaine	logical, add column with weeks
semaine_std	logical, add column with standard weeks (using isoweek from lubridate)
jour_an	logical, add column with day of year
jour_mois	logical, add column with day of month
heure	logical, add column with hour

Value

data The dataframe with date column filled

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fun_report_mig_interannual
statistics per time period

Description

function called for bilamMigrationInterannuelle objects renames columns replaces nulls, and calculates reports with time period larger than day

Usage

```
fun_report_mig_interannual(dat, annee = NULL, timesplit = NULL)
```

Arguments

dat	a data frame with columns ("bjo_annee", "bjo_jour", "bjo_labelquantite", "bjo_valeur")
annee	The year to exclude from the historical series (it will be plotted against the historical series)
timesplit	"week" "2 week" "month" as provided to seq.POSIXt, default NULL

Value

a data frame with mean, max, and min calculated for each timesplit

fun_report_mig_mult *Calculate daily migration by simple repartition*

Description

Function to calculate daily migration from migration monitoring whose length is less than one day, typically video recording whose period are instant events.

Usage

```
fun_report_mig_mult(time.sequence, datasub, negative = FALSE)
```

Arguments

time.sequence	the time sequence to be filled in with new data
datasub	the initial dataset
negative	"boolean", default FALSE, TRUE indicates a separate sum for negative and positive migrations

Value

A data.frame with number summed over over the time.sequence. The function returns the same output than [fun_report_mig_mult_overlaps](#) but is intended to work faster. In the data.frame, the total number is "Effectif_total" and corresponds to the addition of numbers and numbers converted from weight, the total weight is "Poids_total"+"poids_depuis_effectifs" and corresponds to weighed glass eel plus glass eel number converted in weights.

Note

The method uses sqldf, configured to access a postgres database, and runs caclulations on a database called test (the username and password for test are set in the calcmig.csv configuration file).

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fun_report_mig_mult_overlaps
Function to calculate daily migration using overlaps functions

Description

Function to calculate daily migration from migration monitoring whose length is more than one day, this calculation relies on the (false) assumption that migration is evenly spread over time.

Usage

```
fun_report_mig_mult_overlaps(time.sequence, datasub, negative = FALSE)
```

Arguments

`time.sequence` the time sequence to be filled in with new data

`datasub` the initial dataset

`negative` "boolean", default FALSE, TRUE indicates a separate sum for negative and positive migrations to `time.sequence` period and summed over the new sequence. A migration operation spanning several days will be converted to "daily" values assuming that the migration was regular over time. The function returns one row per taxa, stages, counting device. It does not account for the destination of taxa. It returns separate rows for quantities and numbers. Several columns are according to the type of measure (MESURE, CALCULE, PONCTUEL or EXPERT).

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

calculer,report_mig_mult-method

fun_stage_durif

Function to calculate the stages from Durif

Description

Function to calculate the stages from Durif

Usage

```
fun_stage_durif(data)
```

Arguments

`data` A dataset with columns BL, W, Dv, Dh, FL corresponding to body length (mm), Weight (g), vertical eye diameter (mm), vertical eye diameter (mm), and pectoral fin length (mm)

Author(s)

Laurent Beaulaton <laurent.beaulaton"at"onema.fr>

fun_table_per_dis *functions called in DF and DC*

Description

functions called in DF and DC

Usage

```
fun_table_per_dis(typeperiode, tempsdebut, tempsfin, libelle, date = TRUE)
```

Arguments

typeperiode	ref.tr_typearretdisp_tar(per_tar_code) the code of the period (see table ref.tr_typearretdisp_tar)
tempsdebut	ref.tr_typearretdisp_tar(per_date_debut) starting timestamp of the period
tempsfin	The posgres column ref.tr_typearretdisp_tar(per_date_fin) ending timestamp of the period
libelle	The posgres column ref.tr_typearretdisp_tar(libelle)description of the period type
date	Boolean, should the function return a POSIXt or date value

Value

A list

Note

returns either POSIXt or date if date=TRUE

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fun_weight_conversion *returns a table where weights and number are calculated from number and weights respectively performs a query to collect the conversion coefficients*

Description

returns a table where weights and number are calculated from number and weights respectively performs a query to collect the conversion coefficients

Usage

```
fun_weight_conversion(tableau, time.sequence, silent)
```

Arguments

tableau	Table issued from report_mig
time.sequence	Time sequence from report_mig
silent	If silent=TRUE do not display messages

Value

tableau, the data frame

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

fun_write_monthly *This writes monthly data in t_reportmensuel_mens table*

Description

This writes monthly data in t_reportmensuel_mens table

Usage

```
fun_write_monthly(report_mig, resum, silent)
```

Arguments

report_mig	an object of class report_mig
resum	data frame with summary per month
silent	Suppresses messages

Note

This function is launched by fun_Ecritreport_daily, the resum dataset is created by the [funstat](#) function

getdbname	<i>Retrieves the dbname from a connection using "baseODBC"</i>
-----------	--

Description

When running a connection using ODBC, the connection string does not contain the name of the database. Pointing to the database is done while setting the ODBC connection, but the program has no "way" to know what the name of the database is. Since we are using sqldf to connect to the base, we need to know the database name, fortunately it is stored in the ODBC connection string. This method gets this name, from a "trial" connection to one of the table of the database.

Usage

```
getdbname()
```

Value

A string with the name of the database

getnocurrent_step	<i>Generic method to get current time step</i>
-------------------	--

Description

Generic method to get current time step

Usage

```
getnocurrent_step(object, ...)
```

Arguments

object	An object
...	Additional parameters passed to the method

getvalue *Generic method getvalue*

Description

Generic method getvalue

Usage

```
getvalue(object, ...)
```

Arguments

object	Object
...	Additional parms

Author(s)

cedric.briand

getvalue,ref_period-method
Returns the POSIXt value of a given name

Description

Returns the POSIXt value of a given name

Usage

```
## S4 method for signature 'ref_period'  
getvalue(object, id)
```

Arguments

object	An object of class ref_period-class
id	one of "jour", "semaine", "quinzaine", "mois"

Value

"a character to be used in seq.POSIXt

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:  
  getvalue(new("ref_period"), "quinzaine")  
  
## End(Not run)
```

graphdate *function used for some lattice graphs with dates*

Description

function used for some lattice graphs with dates

Usage

```
graphdate(vectordate)
```

Arguments

vectordate date or POSIXt

Value

vectordate (without class)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

graphe-methods *Methods for Function graphe*

Description

method with a parameter choice to join several graphs called by several handlers (buttons)

Methods

signature(object = "report_migPar") method with a parameter choice to join several graphs called by several handlers (buttons)

model	<i>Generic for prediction</i>
-------	-------------------------------

Description

Generic for prediction

Usage

```
model(object, ...)
```

Arguments

object	Object
...	Additional parms

Author(s)

cedric.briand

model,report_ge_weight-method

model method for report_ge_weight' this method uses samples collected over the season to model the variation in weight of glass eel or yellow eels.

Description

model method for report_ge_weight' this method uses samples collected over the season to model the variation in weight of glass eel or yellow eels.

Usage

```
## S4 method for signature 'report_ge_weight'
model(object, model.type = "seasonal",
      silent = FALSE)
```

Arguments

object	An object of class report_ge_weight-class
model.type	default "seasonal", "seasonal1", "seasonal2", "manual".
silent	Default FALSE, if TRUE the program should no display messages

Details

Depending on model.type several models are produced

- model.type="seasonal". The simplest model uses a seasonal variation, it is fitted with a sine wave curve allowing a cyclic variation $w \sim a \cdot \cos(2 \cdot \pi \cdot (d' - T) / 365) + b$ with a period T. The modified day d' used in this model is set at 1 the 1st of august $doy = d' + d0$; $d0 = 212$, $doy = \text{julian days}$
- model.type="seasonal1". A time component is introduced in the model, which allows for a long term variation along with the seasonal variation. This long term variation is fitted with a gam, the time variable is set at zero at the beginning of the first day of observed values. The seasonal variation is modeled on the same modified julian time as model.type="seasonal" but here we use a cyclic cubic spline cc, which allows to return at the value of $d0=0$ at $d=365$. This model was considered as the best to model size variations by Diaz & Briand in prep. but using a large set of values over years.
- model.type="seasonal2". The seasonal trend in the previous model is now modelled with a sine curve similar to the sine curve used in seasonal. The formula for this is $\sin(\omega vt) + \cos(\omega vt)$, where vt is the time index variable ω is a constant that describes how the index variable relates to the full period (here, $2\pi/365 = 0.0172$). The model is written as following $w \cos(0.0172 * doy) + \sin(0.0172 * doy) + s(time)$.
- model.type="manual". The dataset don (the raw data), coe (the coefficients already present in the database, and newcoe the dataset to make the predictions from, are written to the environment envir_stacomi. please see example for further description on how to fit your own model, build the table of coefficients, and write it to the database.

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

plot,report_annual,missing-method
Plot method for report_annual

Description

Plot method for report_annual

Usage

```
## S4 method for signature 'report_annual,missing'
plot(x, plot.type = "point",
     silent = FALSE)
```

Arguments

x	An object of class report_annual-class
plot.type	Default point
silent	Stops displaying the messages. <ul style="list-style-type: none"> plot.type="point": ggplot+geom_point'

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

[report_mig_interannual-class](#) for examples

plot,report_dc,ANY-method

Different plots for report_dc

Description

- plot.type=1 A barplot of the operation time per month
- plot.type=2 Barchat giving the time per type of operation
- plot.type=2 Rectangle plots drawn along a line
- plot.type=4 Plots per day drawn over the period to show the operation of a df, days in x, hours in y

Usage

```
## S4 method for signature 'report_dc,ANY'
plot(x, y, plot.type = 1, silent = FALSE,
     main = NULL)
```

Arguments

x	An object of class report_dc-class
y	From the formals but missing
plot.type	One of barchart,box. Defaut to barchart showing a summary of the df operation per month, can also be box, a plot with adjacent rectangles.
silent	Stops displaying the messages.
main	The title of the graph, if NULL a default title will be plotted with the number of the DF

Value

Nothing but prints the different plots

Note

The program cuts periods which overlap between two month. The splitting of different periods into month is assigned to the `envir_stacom` environment

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_df,ANY-method

Different plots for report_df

Description

- `plot.type=1` A barplot of the operation time per month
- `plot.type=2` Barchat giving the time per type of operation
- `plot.type=2` Rectangle plots drawn along a line
- `plot.type=4` Plots per day drawn over the period to show the operation of a df, days in x, hours in y

Usage

```
## S4 method for signature 'report_df,ANY'
plot(x, y, plot.type = 1, silent = FALSE,
     main = NULL)
```

Arguments

<code>x</code>	An object of class <code>report_df-class</code>
<code>y</code>	From the formals but missing
<code>plot.type</code>	One of <code>barchart,box</code> . Defaut to <code>barchart</code> showing a summary of the df operation per month, can also be <code>box</code> , a plot with adjacent rectangles.
<code>silent</code>	Stops displaying the messages.
<code>main</code>	The title of the graph, if <code>NULL</code> a default title will be plotted with the number of the DF

Value

Nothing but prints the different plots

Note

The program cuts periods which overlap between two month. The splitting of different periods into month is assigned to the `envir_stacom` environment

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_env,missing-method
Plot method for report_env

Description

Plot method for report_env

Usage

```
## S4 method for signature 'report_env,missing'
plot(x, silent = FALSE)
```

Arguments

x	An object of class report_env-class
silent	Stops displaying the messages

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_ge_weight,missing-method
Plot method for report_ge_weight'

Description

Plot method for report_ge_weight'

Usage

```
## S4 method for signature 'report_ge_weight,missing'
plot(x, plot.type = "point",
     silent = FALSE)
```

Arguments

x	An object of class report_ge_weight-class
plot.type	Default "1". "1" plot of mean weight of glass eel against the mean date of operation (halfway between start, and end of operation). The ggplot "p" can be accessed from <code>envir_stacomi</code> using <code>get("p",envir_stacomi)</code> . "2" standard plot of current coefficient. "3" same as "1" but with size according to number.
silent	Stops displaying the messages.

Note

the model method provides plots for the fitted models

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_mig,ANY-method

Plots of various type for report_mig.

Description

- plot.type="standard" calls [fungraph](#) and [fungraph_glasseel](#) functions to plot as many "report_mig" as needed, the function will test for the existence of data for one dc, one taxa, and one stage
- plot.type="step" creates Cumulated graphs for report_mig_mult. Data are summed per day for different dc taxa and stages
- plot.type="multiple" Method to overlay graphs for report_mig_mult (multiple dc/taxa/stage in the same plot)

Usage

```
## S4 method for signature 'report_mig,ANY'
plot(x, y, plot.type = "standard", color = NULL,
     color_ope = NULL, silent = FALSE, ...)
```

Arguments

x	An object of class report_mig
y	From the formals but missing
plot.type	One of "standard","step". Default to standard the standard report_mig with dc and operation displayed, can also be step or multiple
color	Default NULL, argument passed for the plot.type="standard" method. A vector of color in the following order : (1) working, (2) stopped, (3:7) 1...5 types of operation, (8:11) numbers, weight, NULL, NULL (if glass eel), (8:11) measured, calculated, expert, direct observation for other taxa. If null will be set to <code>brewer.pal(12,"Paired")[c(8,10,4,6,1,2,3,5,7)]</code>
color_ope	Default NULL, argument passed for the plot.type="standard" method. A vector of color for the operations. Default to <code>brewer.pal(4,"Paired")</code>
silent	Stops displaying the messages.
...	Additional arguments passed to <code>matplot</code> or <code>plot</code> if plot.type="standard", see ... in fungraph_glasseel and fungraph

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

`plot,report_mig_char,missing-method`
plot method for report_mig_char

Description

plot method for report_mig_char

Usage

```
## S4 method for signature 'report_mig_char,missing'
plot(x, color_parm = NULL,
     plot.type = "qual", silent = FALSE, ...)
```

Arguments

<code>x</code>	An object of class <code>report_mig_char</code>
<code>color_parm</code>	A named vector for the colors of either parameters (if <code>plot.type=quant</code>) or levels for parameters (if <code>plot.type=qual</code>).
<code>plot.type</code>	One of "qual", "quant" "crossed" default to qual
<code>silent</code>	Boolean default FALSE, if TRUE information messages not displayed
<code>...</code>	Additional parameters

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

`plot,report_mig_env,missing-method`
Plot method for report_mig_env

Description

Plot method for report_mig_env

Usage

```
## S4 method for signature 'report_mig_env,missing'
plot(x, color_station = NULL,
     color_dc = NULL, silent = FALSE)
```

Arguments

x	An object of class <code>report_mig_env</code>
color_station	A named vector of station color (e.g. <code>c("temp_gabion"="red","coef_maree"="blue","phases_lune"="green")</code>) default null
color_dc	A named vector giving the color for each dc default null (e.g. <code>c("5"="#4D4D4D","6"="#E6E6E6","12"="")</code>)
silent	Stops displaying the messages.

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

plot,report_mig_interannual,missing-method
Plot method for report_mig_interannual

Description

Several of these plots are scaled against the same year, ie the comparison is based on year 2000, meaning that day 1 would correspond to the first date of 2000, which is also a saturday, the last day of the week.

Usage

```
## S4 method for signature 'report_mig_interannual,missing'
plot(x, plot.type = "standard",
     timesplit = "mois", silent = FALSE)
```

Arguments

x	An object of class <code>report_mig_interannual</code>
plot.type	Default standard
timesplit	Used for plot.type barchart or dotplot, Default mois (month) other possible values are semaine (week), quinzaine (2 weeks), English values within parenthesis are also accepted.
silent	Stops displaying the messages. <ul style="list-style-type: none"> • plot.type="line": one line per daily report_mig • plot.type="standard": the current year is displayed against a ribbon of historical values" • plot.type="density": creates density plot to compare seasonality, data computed by 15 days period • plot.type="step" : creates step plots to compare seasonality, the year chosen in the interface is the latest if silent=TRUE, or it can be selected in the droplist. It is highlighted against the other with a dotted line

- plot.type="barchart": comparison of daily migration of one year against periodic migration for the other years available in the chronicle, different periods can be chosen with argument timesplit
- plot.type="pointrange": Pointrange graphs, different periods can be chosen with argument timesplit
- plot.type="seasonal": plot to display summary statistics about the migration period

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_mig_mult,missing-method

Plots of various type for report_mig_mult

Description

- plot.type="standard" calls [fungraph](#) and [fungraph_glasseel](#) functions to plot as many "report_mig" as needed, the function will test for the existence of data for one dc, one taxa, and one stage
- plot.type="step" creates Cumulated graphs for report_mig_mult. Data are summed per day for different dc taxa and stages
- plot.type="multiple" Method to overlay graphs for report_mig_mult (multiple dc/taxa/stage in the same plot)

Usage

```
## S4 method for signature 'report_mig_mult,missing'
plot(x, plot.type = "standard",
     color = NULL, color_ope = NULL, silent = FALSE, ...)
```

Arguments

x	An object of class report_mig_mult
plot.type	One of "standard", "step", "multiple". Default to standard the standard report_mig with dc and operation displayed, can also be step or multiple
color	Default NULL, argument passed for the plot.type="standard" method. A vector of color in the following order : (1) working, (2) stopped, (3:7) 1...5 types of operation, (8:11) numbers, weight, NULL, NULL (if glass eel), (8:11) measured, calculated, expert, direct observation for other taxa. If null will be set to brewer.pal(12,"Paired")[c(8,10,4,6,1,2,3,5,7)]
color_ope	Default NULL, argument passed for the plot.type="standard" method. A vector of color for the operations. Default to brewer.pal(4,"Paired")
silent	Stops most messages from being displayed
...	Additional arguments passed to matplot or plot if plot.type="standard", see ... in fungraph_glasseel and fungraph

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_sample_char,missing-method
Plots of various type for reportcarlot

Description

Plots of various type for reportcarlot

Usage

```
## S4 method for signature 'report_sample_char,missing'  
plot(x, plot.type = "1",  
      silent = FALSE)
```

Arguments

x	An object of class report_sample_char
plot.type	One of "1","violin plot". Defaut to 1 , can also be 2 boxplot or 3 points.
silent	Stops displaying the messages.
...	Additional arguments, see plot, plot.default and par

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_sea_age,missing-method
Plots of various type for report_sea_age

Description

Plots of various type for report_sea_age

Usage

```
## S4 method for signature 'report_sea_age,missing'  
plot(x, plot.type = "1", silent = FALSE)
```

Arguments

<code>x</code>	An object of class report_sea_age-class
<code>plot.type</code>	Default "1" <ul style="list-style-type: none"> • <code>plot.type="1"</code> density plot by sea age • <code>plot.type="2"</code> Density plot by sea age and dc
<code>silent</code>	Default FALSE, if TRUE the program should no display messages.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

`plot,report_silver_eel,missing-method`
Plots of various type for report_silver_eel

Description

Plots of various type for `report_silver_eel`

Usage

```
## S4 method for signature 'report_silver_eel,missing'
plot(x, plot.type = "1",
     silent = FALSE)
```

Arguments

<code>x</code>	An object of class report_silver_eel-class
<code>plot.type</code>	Default "1" <ul style="list-style-type: none"> • <code>plot.type="1"</code> Lattice plot of Durif's stages according to Body Length and Eye Index (average of vertical and horizontal diameters). If several DC are provided then a comparison of data per dc is provided • <code>plot.type="2"</code> Lattice plot giving a comparison of Durif's stage proportion over time, if several DC are provided an annual comparison is proposed, if only one DC is provided then the migration is split into month. • <code>plot.type="3"</code> Series of graphs showing mean Fulton's coefficient, Pankhurst eye index, along with a size weight analysis and regression using robust regression (rlm more robust to the presence of outliers) • <code>plot.type="4"</code> Lattice cloud plot of Pankurst~ Body Length ~ weight)
<code>silent</code>	Stops displaying the messages.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

plot,report_species,missing-method
Plot method for report_species

Description

Plot method for report_species

Usage

```
## S4 method for signature 'report_species,missing'  
plot(x, plot.type = "pie", color = NULL,  
     silent = FALSE)
```

Arguments

x	An object of class report_species-class
plot.type	Default pie #' <ul style="list-style-type: none">• plot.type="pie": A pie'• plot.type="barchart" : A barchart
color	Default NULL, a vector of colors of length corresponding to the number of taxa-stage different values, use <code>unique(bilesp@calcddata\$taxa_stage)</code> to get that number. The color applies to both pie and barchart plots
silent	Stops displaying the messages.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

print,report_dc-method
Method to print the command line of the object

Description

Method to print the command line of the object

Usage

```
## S4 method for signature 'report_dc'  
print(x, ...)
```

Arguments

x An object of class report_dc
... Additional parameters passed to print

Author(s)

cedric.briand

print,report_df-method

Method to print the command line of the object

Description

Method to print the command line of the object

Usage

```
## S4 method for signature 'report_df'  
print(x, ...)
```

Arguments

x An object of class report_df
... Additional parameters passed to print

Author(s)

cedric.briand

print,report_mig-method

Method to print the command line of the object

Description

Method to print the command line of the object

Usage

```
## S4 method for signature 'report_mig'  
print(x, ...)
```

Arguments

x An object of class report_mig
... Additional parameters passed to print

Author(s)

cedric.briand

print,report_mig_mult-method

Method to print the command line of the object

Description

Method to print the command line of the object

Usage

```
## S4 method for signature 'report_mig_mult'  
print(x, ...)
```

Arguments

x An object of class report_mig_mult
... Additional parameters passed to print

Author(s)

cedric.briand

print,report_sample_char-method

Method to print the command line of the object

Description

Method to print the command line of the object

Usage

```
## S4 method for signature 'report_sample_char'  
print(x, ...)
```

Arguments

x An object of class report_sample_char
... Additional parameters passed to print

Author(s)

cedric.briand

print,report_sea_age-method

Method to print the command line of the object

Description

Method to print the command line of the object

Usage

```
## S4 method for signature 'report_sea_age'  
print(x, ...)
```

Arguments

x An object of class report_sea_age
... Additional parameters passed to print

Author(s)

cedric.briand

print,report_silver_eel-method

Method to print the command line of the object

Description

Method to print the command line of the object

Usage

```
## S4 method for signature 'report_silver_eel'  
print(x, ...)
```

Arguments

x An object of class report_silver_eel
 . . . Additional parameters passed to print

Author(s)

cedric.briand

progress_bar *Progress bar using a gtkdialog, the progress bar is assigned in env-
 vir_stacom* This progress bar has a button to close.

Description

Progress bar using a gtkdialog, the progress bar is assigned in env-
 vir_stacom This progress bar has a button to close.

Usage

```
progress_bar(title, progress_text, width = 400, height = 50, pulse = TRUE)
```

Arguments

title The title of the bar
 progress_text The text to display for progression
 width Width of the progress bar
 height Height of the progress bar
 pulse Do you want the widget to pulse

Value

nothing

Note

The name of the progress bar is progres, it will be assigned in env-
 vir_stacom, it contains a progress bar widget named progress bar, also assigned in env-
 vir_stacom See example for use.

Author(s)

cedric.briand

Examples

```
## Not run:
progress_bar(title="Trial",progress_text="progress text")
fraction_progressed=seq(0,1,length.out=50)
progress_bar<-get("progress_bar",envir_stacomi)
for(i in fraction_progressed){
  Sys.sleep(0.1)
  progress_bar$setText(sprintf("%d%% progression",round(100*i)))
  progress_bar$setFraction(i)
}
dispose(progres)

## End(Not run)
```

quitte	<i>function used to clean the objects within the group and the graphs and also elements remaining in the envir_stacomi environment</i>
--------	--

Description

function used to clean the objects within the group and the graphs and also elements remaining in the envir_stacomi environment

Usage

```
quitte(...)
```

Arguments

... additional arguments passed to the function

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

ref_checkbox-class	<i>ref_checkbox referencial class</i>
--------------------	---------------------------------------

Description

referential class allows to choose for several parms with checkbox

Slots

title A "character", the title of the box giving the possible choices

labels The logical parameters choice

checked A boolean vector

Objects from the Class

Objects can be created by calls of the form `new("ref_checkbox", ...)`.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_choice-class	<i>Class "ref_choice"</i>
------------------	---------------------------

Description

ref_choice referential class allows to choose within several values with radiobuttons

Slots

listechoice A character vector giving possible choices

label A character, title of the box giving the possible choices

selected An Integer the initial selected value (as an index), first=1 used in gradio

Objects from the Class

Objects can be created by calls of the form `new("ref_choice", listechoice=character() ,label=character() ,selected=integer())`.

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_coe-class *Class "ref_coe"*

Description

Enables to load conversion coefficients quantity-number. This class only exists to load the data with its method charge. It is not used directly as component of the graphical interface, as the year is already loaded in the different report objects

Slots

data A data.frame
datedebut A "POSIXlt"
datefin A "POSIXlt"

Objects from the Class

Objects can be created by calls of the form `new("ref_coe")`.

Note

Class loading coefficient of conversion between quantity (weights or volumes of glass eel) and numbers between a starting and finishing date

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_dc-class *Class "ref_dc"*

Description

Description of a control device.

Slots

dc_selectionne Object of class "integer", The selected device
 ouvrage Object of class "integer", the attached dam
 station Object of class "character", the attached migration monitoring station, this is necessary to join the table of escapements calculated at the station level.
 data Object of class "data.frame" data pertaining to the control device

Objects from the Class

Objects can be created by calls of the form `new("ref_dc", dc_selectionne=integer(), ouvrage=integer(), data=dat`

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

 ref_df-class

 Class "ref_df"

Description

Representation of a fishway, contains description data of all fishways from the database along with the selected fishways (df) (integer) Objects from the Class: Objects can be created by calls of the form `new("ref_df", df_selectionne=integer(), ouvrage=integer(), data=data.frame())`.

Arguments

df_selectionne Object of class "integer" The identifier of the fishway
 ouvrage Object of class "integer" The attached dam
 data Object of class "data.frame" Data concerning the fishway

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_env-class *Class "ref_env"*

Description

Enables to load measure stations and to select one of them

Slots

dataframe Data concerning the measure station

Objects from the Class

Objects can be created by calls of the form `new("ref_env", ...)`.

Author(s)

cedric.briand"at"eptb-vilaine.fr

ref_horodate-class *Class ref_horodate*

Description

choice of date with method to show current and previous year

Slots

horodate a "POSIXt"

Objects from the Class

Objects can be created by calls of the form `new("ref_horodate", ...{ })`.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_par-class	<i>Class "ref_par"</i>
---------------	------------------------

Description

Class enabling to load the list of parameters and select one of them

Slots

data A data.frame
 par_selected A character vector corresponding to par_code
 data="data.frame" the list of parameters

Objects from the Class

Objects can be created by calls of the form

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_parqual-class	<i>Class "ref_parqual"</i>
-------------------	----------------------------

Description

Class enabling to load the list of qualitative parameters and to select one of them. It inherits from 'ref_par', uses its 'choice' method

Slots

valqual="data.frame" the list of qualitative parameters

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_parquan-class *Class "ref_parquan"*

Description

Class enabling to load the list of quantitative parameters and to select one of them. It inherits from 'ref_par', uses its 'choice' method

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_period-class *Class "ref_period" referential class*

Description

ref_period referential class to choose a period

Slots

data="data.frame" providing correspondance between period and their English names

Objects from the Class

Objects can be created by calls of the form `new("ref_period", ...)`.

Note

pgval are used by seq.POSIXt

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_stage-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_stage-class	Class "ref_stage"
-----------------	-------------------

Description

Representation of a fish phase

Objects from the Class

Objects can be created by calls of the form `new("ref_stage", data="data.frame")`.

list("data") Object of class "data.frame" ~ The phases available in the database

: Object of class "data.frame" ~ The phases available in the database

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_taxa-class](#), [ref_year-class](#)

ref_taxa-class	Class "ref_taxa"
----------------	------------------

Description

Loading and selection of fish species. This class is a referential class, and it is integrated into refreport objects.

Slots

data A "data.frame" of species available in the database

Objects from the Class

Objects can be created by calls of the form `new("ref_taxa", ...)`.

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_year-class](#)

ref_textbox-class *ref_textbox referencial class*

Description

allows to a put a value within a glabel

Slots

title="character" the title of the box giving the possible choices
labels the logical parameters choice
checked a vector

Author(s)

cedric.briand"at"eptb-vilaine.fr

ref_timestep-class *Class "ref_timestep"*

Description

Describes a time step

Objects from the Class

Objects can be created by calls of the form `new("ref_timestep", dateDebut="POSIXt", step_duration=numeric(), nb_s`

list("dateDebut") Object of class "POSIXt" Starting date

: Object of class "POSIXt" Starting date

list("step_duration") Object of class "numeric" Step length

: Object of class "numeric" Step length

list("nb_step") Object of class "numeric" Number of steps

: Object of class "numeric" Number of steps

list("nocurrent_step") Object of class "integer" Number of the current step

: Object of class "integer" Number of the current step

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

[ref_timestep_daily](#)

ref_timestepChar-class

Class "ref_timestepChar"

Description

Character to represent a ref_timestep

Objects from the Class

Objects can be created by calls of the form `new("ref_timestepChar", ...{})`

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

[ref_timestep](#)

Examples

```
showClass("ref_timestepChar")
```

ref_timestep_daily-class

Class "ref_timestep_daily"

Description

Representation of a ref_timestep object with a step length equal to one day. It receives an inheritance from ref_timestep

Details

validity_ref_timestep_daily

Objects from the Class

Objects can be created by calls of the form `new("ref_timestep_daily", dateDebut="POSIXt", step_duration=numeric())`

list("dateDebut") Object of class "POSIXt" Starting date

: Object of class "POSIXt" Starting date

list("step_duration") Object of class "numeric" Step length

: Object of class "numeric" Step length

list("nb_step") Object of class "numeric" Number of steps

: Object of class "numeric" Number of steps

list("nocurrent_step") Object of class "integer" Number of the current step

: Object of class "integer" Number of the current step

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

[ref_timestep](#)

ref_year-class

Year reference class

Description

Class used to select one or several years

Slots

`data` A `data.frame` with the list of possible years selected as numerics

`annee_selectionnee` A numeric vector

Objects from the Class

Objects can be created by calls of the form `new("ref_year", data=data.frame(), annee_selectionnee=numeric())`.

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other referential.objects: [charge](#), [ref_choice-method](#), [ref_checkbox-class](#), [ref_choice-class](#), [ref_coe-class](#), [ref_dc-class](#), [ref_df-class](#), [ref_horodate-class](#), [ref_list-class](#), [ref_par-class](#), [ref_parqual-class](#), [ref_parquan-class](#), [ref_period-class](#), [ref_stage-class](#), [ref_taxa-class](#)

report_annual-class *Class "report_annual"*

Description

This class displays annual migration counts, for several counting device, taxa or stages.

Slots

dc Object of class [ref_dc-class](#), the counting device, multiple values allowed

data Object of class "data.frame" data for report lot

taxa An object of class [ref_taxa-class](#), multiple values allowed

stage An object of class [ref_stage-class](#), multiple values allowed

anneedebut Object of class [ref_year-class](#). ref_year allows to choose year of beginning

anneefin Object of class [ref_year-class](#) ref_year allows to choose last year of the report

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomir)
# launching stacomir without selecting the scheme or interface
stacomir(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
# the following script will load the Arzal dataset if connected to iav schema
## Not run:
baseODBC<-get("baseODBC",envir=envir_stacomir)
baseODBC[c(2,3)]<-rep("iav",2)
assign("baseODBC",baseODBC,envir_stacomir)
sch<-get("sch",envir=envir_stacomir)
assign("sch","iav.",envir_stacomir)
r_ann<-new("report_annual")
r_ann<-choice_c(r_ann,
dc=c(5,6,12),
taxa=c("Anguilla anguilla"),
stage=c("AGJ","AGG"),
anneedebut="1996",
```

```

anneefin="2015",
silent=FALSE)
r_ann<-connect(r_ann)

## End(Not run)
# the following dataset has been generated by the previous code
data(r_ann)
xtr_ann<-stacomIR::xtable(r_ann,
dc_name=c("Passe bassins", "Piege anguille RG", "Piege anguille RD"),
tax_name="Anguille",
std_name=c("Arg.", "Jaun. "))
# below not run but one can create a file as following
## Not run:
path=file.path(path.expand(get("datawd", envir=envir_stacomir)),
paste(paste(r_ann@dc@dc_selectionne, collapse="+"), "_",
paste(r_ann@taxa@data$tax_code, collapse="+"), "_",
paste(r_ann@stage@data$std_code, collapse="+"), "_",
r_ann@anneedebut@annee_selectionnee, ":"),
r_ann@anneefin@annee_selectionnee, ".html", sep=""), fsep = "/" )
# here you can add an argument file=path
print(xtr_ann, type="html")

# the following uses the "addtorow" argument which creates nice column headings,
# format.args creates a thousand separator
# again this will need to be saved in a file using the file argument
print(xtr_ann,
add.to.row=get("addtorow", envir_stacomir),
include.rownames = TRUE,
include.colnames = FALSE,
format.args = list(big.mark = " ", decimal.mark = ","))
)
# barplot transforms the data, further arguments can be passed as to barplot
barplot(r_ann)
barplot(r_ann,
args.legend=list(x="topleft", bty = "n"),
col=c("#CA003E", "#1A9266", "#E10168", "#005327", "#FF9194"))

# An example with custom arguments for legend.text (overriding plot defaults)
data(r_ann_adour)
if (requireNamespace("RColorBrewer", quietly = TRUE)){
lesdc<-r_ann_adour@dc@data$dc_code[r_ann_adour@dc@data$dc%in%r_ann_adour@dc@dc_selectionne]
barplot(r_ann_adour,
legend.text=lesdc,
args.legend=list(x="topleft", bty = "n"),
col=RColorBrewer::brewer.pal(9, "Spectral"),
beside=TRUE)
}
plot(r_ann_adour)

## End(Not run)

```

report_dc-class	<i>Class "report_dc" report du fonctionnement du dispositif de comptage</i>
-----------------	---

Description

The counting device is not always working. It may be stopped either following a monitoring protocol, or due to malfunction of the device, this class allows to draw graphics allowing an overview of the device operation

Slots

data A data frame
 dc An object of class ref_dc-class
 horodatedebut An object of class ref_horodate-class
 horodatefin An object of class ref_horodate-class

Objects from the Class

Objects can be created by calls of the form `new("report_dc", ...)`.

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomIR)
stacomI(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
#####
## An example that will work only if the database is present
## and the program installed and comprises the schema iav
#####
## Not run:
  r_dc=new("report_dc")
  r_dc<-choice_c(r_dc,
  5,
  horodatedebut="2000-01-01",
  horodatefin="2015-12-31",
  silent=TRUE)
```

```

Sys.setenv(TZ='GMT')
# This dataset formating is GMT. If this option is not set
# the dataset is tranformed from timestamp to date
r_dc<-connect(r_dc)
# this dataset has been loaded by the previous lines
#####
# Without connexion to the database (use dataset r_dc)
#####
data("r_dc")
plot(r_dc,plot.type="1")
plot(r_dc,plot.type="2")
plot(r_dc,plot.type="3",main="trial title")
plot(r_dc,plot.type="4",main="trial title")
# the following will write in the datawd folder
summary(r_dc)

## End(Not run)
##

```

report_df-class

Report on fishway operation

Description

Fishways (DF) are of various nature, from very simple eel ladders fed by water discharged from the river, to more complex fishways with levels adjusted by the opening of various gates and regulators. The objective of this class is to provide an assessment of the working status of a fishway throughout the year. A number of fishes ascending a fishway has meaning only if we know that the fishway is operational, and that the counting operated on the fishway has remained operational. In the database the operation of the fishway (DF) and counting device (DC) is agregated in one table (`t_periodefonctdispositif_per`). The column `per_etat_fonctionnement` indicates whether the fishway is operational (with a boolean) and the column `per_tar_code` indicates the status of either the fishway or DC. In the database four types of operation are set, "1"=normal operation, "2"=Device stopped in normal operation (ie lift ascending, high tide...), "3"="Stopped for maintenance or other problem", "4"="Works but not fully operational, ie flow problem, flood, clogged with debris...", "5"="Not known")

Slots

`data` A data frame

`df` An object of class `ref_df-class`

`horodatedebut` An object of class `ref_horodate-class`

`horodatefin` An object of class `ref_horodate-class`

Objects from the Class

Objects can be created by calls of the form `new("report_df")`.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomiR)
stacomi(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
## An example that will work with the database installed only
## Not run:
  r_df=new("report_df")
  r_df<-choice_c(r_df,
  1,
  horodatedebut="2015-01-01",
  horodatefin="2015-12-31",
  silent=TRUE)
  Sys.setenv(TZ='GMT')
  # the times at Arzal are recorded continuously
  # they are converted to date when a time appears while the hour is changing
  # hence the following
  r_df<-connect(r_df)

## End(Not run)

data("r_df")
plot(r_df,plot.type="4")
# the following examples work but take a while to compute
## Not run:
  plot(r_df,plot.type="1")
  plot(r_df,plot.type="2",main="A nice title")
  plot(r_df,plot.type="3",main="A nice title")

## End(Not run)
```

report_env-class	<i>class report_env simple output of one or several environmental conditions...</i>
------------------	---

Description

Annual overview of environmental conditions. This class enables to draw some plot, but will mostly used to build joined graphs crossing the information from [report_mig_mult-class](#) and [report_mig_env-class](#)

Slots

horodatedebut [ref_horodate-class](#)
 horodatefin [ref_horodate-class](#)
 stationMesure [ref_env-class](#)
 data data.frame

Author(s)

cedric.briand"at"eptb-vilaine.fr

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomIR)
stacomI(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
## Not run:
  r_env<-new("report_env")
  r_env<-choice_c(r_env,
  stationMesure=c("temp_gabion", "coef_maree"),
  datedebut="2008-01-01",
  datefin="2008-12-31",
  silent=FALSE)
  r_env<-connect(r_env)

## End(Not run)

data("r_env")
plot(r_env, silent=TRUE)
```

 report_ge_weight-class

Trend of wet weight in glass eel

Description

In trapping ladders, glass eel are seldom counted, as they are too tiny to handle and too numerous to count. The usual operation is to weight them, or to use a bucket to measure their volume. These weights or volumes will later need to be converted to numbers. The glass eel weight may follow a seasonal pattern. It's the case for *Anguilla anguilla* glass eel in the Bay of Biscay. Weights can be modelled using sine wave curves, or more complex gam models. This class has a model test method to try those models, which can also be used to extract coefficients manually to manually test more complex models. Some plots are provided to display the coefficients stored in the database, and the model results. A parameter provided in the graphical interface or in the command line (slot `liste`) takes values "1", ">1", "tous" which mean respectively use only individual sample of glass eels, or use "group weights" which can be more close to the real weight of glass eel during counts as glass eel are not completely drained from their water during handling to preserve their mucus. The list choice "tous" means that both individual and group weights are selected.

Slots

`data` A "data.frame" data for report lot

`calcdata` A list containing two processed data frames, `data` and `coe`

`dc` Object of class [ref_dc-class](#), the counting device

`annee debut` Object of class [ref_year-class](#). `ref_year` allows to choose the year of beginning

`annee fin` Object of class [ref_year-class](#) `ref_year` allows to choose last year of the report

`coe` Object of class [ref_coe-class](#) class loading coefficient of conversion between quantity (weights or volumes of glass eel) and numbers

`liste` Object of class [ref_list-class](#) `ref_list` referential class choose within a list, here the choice is whether subsamples or not. Subsamples in the `stacomi` database are samples with a non null value for parent sample. Migration counts are never made on subsamples but those can be integrated to calculate mean weights.

Note

In this class some tools are available to import glass eel measurement from experimental fishing in the estuary. For the `charge` method dates for the request are from august to august (a glass eel season)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomir)
# launching stacomir without selecting the scheme or interface
stacomir(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
## Not run:
#create an instance of the class
r_gew<-new("report_ge_weight")
baseODBC<-get("baseODBC",envir=envir_stacomir)
baseODBC[c(2,3)]<-rep("iav",2)
assign("baseODBC",baseODBC,envir_stacomir)
sch<-get("sch",envir=envir_stacomir)
assign("sch","iav.",envir_stacomir)
r_gew@liste<-charge(object=r_gew@liste,listechoice=c("=1", ">1", "tous"),label="")
# here I'm using weights when number are larger than 1 ie wet weight
# always choose a date from one year to the next eg 2010 to 2011
# as the dates are from august to august
r_gew<-choice_c(r_gew,
dc=c(6),
annee debut="2009",
annee fin="2015",
selectedvalue=">1",
silent=FALSE)
r_gew<-connect(r_gew)
r_gew<-calculer(r_gew)

## End(Not run)
# load the dataset generated by previous lines
data("r_gew")
# the calculation will fill the slot calcdat

# A ggplot showing the trend in weight
plot(r_gew, plot.type=1)
# A plot showing both the data and the trend as recorded in the database
plot(r_gew, plot.type=2)
# Same as plot.type=1 but with size according to size of the sample,
# usefull for wet weights where weight are recorded on a number of glass eel
plot(r_gew, plot.type=3)
## Not run:
# First model with nls, see Guerault and Desaunay (1993)
model(r_gew,model.type="seasonal")
model(r_gew,model.type="seasonal1")

## End(Not run)
```

report_mig-class	<i>Migration report for one DC, one species and one stage</i>
------------------	---

Description

This class performs a migration summary. A migration monitoring operation can correspond to a single horodate (in the case of some video monitoring operation) or comprise a period which does not necessarily span a full day. The daily migration is calculated by splitting the operation between days, and the migration is either grouped or split according to the length of the different time spans.

Slots

dc Object of class [ref_dc-class](#): the control device
 taxa Object of class [ref_taxa-class](#): the species
 stage Object of class [ref_stage-class](#) : the stage of the fish
 timestep Object of class [ref_timestep_daily-class](#) : the time step constrained to daily value and 365 days
 data Object of class `data.frame` with data filled in from the connect method
 calcdata A "list" of calculated daily data, one per dc, filled in by the calcule method
 coef_conversion A `data.frame` of daily weight to number conversion coefficients, filled in by the connect method if any weight are found in the data slot.
 time.sequence Object of class `POSIXct` : a time sequence of days generated by the calcule method

Note

In practise, the `report_mig` class uses methods (`calcule`, `connect`...) from the more elaborate [report_mig_mult-class](#)

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
library(stacomir)

stacomir(gr_interface=FALSE,login_window=FALSE,database_expected=FALSE)
## launches the application in the command line
## here an example of loading
```

```

## not run as the program is possibly not installed
## this example generates the r_mig dataset
## Not run:
  stacomi(gr_interface=FALSE,
  login_window=FALSE,
  database_expected=TRUE)
  r_mig=new("report_mig")
  r_mig=choice_c(r_mig,
  dc=5,
  taxa=c("Liza ramada"),
  stage=c("IND"),
  datedebut="2015-01-01",
  datefin="2015-12-31")
  r_mig<-charge(r_mig)
  # launching charge will also load classes associated with the report
  # e.g. report_ope, report_df, report_dc
  r_mig<-connect(r_mig)
  #####
# calculations
# note this requires to have a database test configured in postgres for use with sqldf
#####
  r_mig<-calculer(r_mig,silent=TRUE)

## End(Not run)
#####
# loading data
## use the following to get the raw data loaded by the connect method
# not shown there as the database and program might not be installed
# All three classes report... were created by the charge and connect method
# of report_mig_mult
# in the previous example
#####
data("r_mig")
data("r_mig_ope")
assign("report_ope",r_mig_ope,envir=envir_stacomi)
data("r_mig_df")
assign("report_df",r_mig_df,envir=envir_stacomi)
data("r_mig_dc")
assign("report_dc",r_mig_dc,envir=envir_stacomi)

#Individual plot for all DC (standard), taxa and stage where data present
#silent argument to stop all messages
plot(r_mig,plot.type="standard",silent=TRUE)
#cumulated migration at the station (all stages and DC grouped)
plot(r_mig,plot.type="step")

# data will be written in the data directory specified in the stacomi/calcmig.csv
#file

## Not run:
  summary(r_mig,silent=TRUE)

```

```
## End(Not run)
# this will write the daily report for later in in the reportnMigrationInterannuelle-class
## Not run:
  write_database(r_mig,silent=TRUE,dbname="bd_contmig_nat",host="localhost",port=5432)

## End(Not run)
```

report_mig_char-class *Migration report along with quantitative and qualitative characteristics*

Description

Migration along with qualitative or quantitative characteristics or both (e.g.) weight of eels according to the size class per period of time, weight of fish according to gender, number of fish per age class. This class does not split migration evenly over time period. So, unlike calculations made in class `report_mig` and `report_mig_mult` the whole time span of the migration operation is not considered, only the date of beginning of the operation is used to perform calculations.

Slots

`calldata` A "list" of calculated data, filled in by the `calcule` method
`data` A `data.frame` inherited from `report_sample_char-class`
`dc` An object of class `ref_dc-class` inherited from `report_sample_char-class`
`taxa` An object of class `ref_taxa-class` inherited from `report_sample_char-class`
`stage` An object of class `ref_stage-class` inherited from `report_sample_char-class`
`horodatedebut` An object of class `ref_horodate-class` inherited from `report_sample_char-class`
`horodatefin` An object of class `ref_horodate-class` inherited from `report_sample_char-class`
`par` An object of class `ref_par-class` inherited from `report_sample_char-class`
`echantillon` An object of class `ref_choice-class`, vector of choice
`parquan` An object of class `ref_parquan-class`, quantitative parameter
`parqual` An object of class `ref_parqual-class`, qualitative parameter

Objects from the Class

Objects can be created by calls of the form `new("report_mig_char", ...)`. they are loaded by the interface using `interface_report_mig_char` function.

Note

The main difference between this class and `report_sample_char-class` is that this class allows to select (or not) the samples, and that it handles quantitative and qualitative parameters separately.

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomir)

stacomir(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)

## Not run:
r_mig_char<-new("report_mig_char")
baseODBC<-get("baseODBC",envir=envir_stacomir)
baseODBC[c(2,3)]<-rep("logrami",2)
assign("baseODBC",baseODBC,envir_stacomir)
sch<-get("sch",envir=envir_stacomir)
assign("sch","logrami.",envir_stacomir)
# here parqual is not in the list
# so this is equivalent to parqual=NULL
# default for echantillon is "with"
r_mig_char<-choice_c(r_mig_char,
dc=c(107,108,101),
taxa=c("Salmo salar"),
stage=c('5','11','BEC','BER','IND'),
parquan=c('A124','C001','1786','1785'),
horodatedebut="2012-01-01",
horodatefin="2012-12-31",
silent=FALSE)
# r_mig_char<-charge(r_mig_char) not necessary there
r_mig_char<-connect(r_mig_char)

## End(Not run)
# load the dataset generated by previous lines
data("r_mig_char")
# age will be plotted as a qualitative variable
r_mig_char<-setasqualitative(r_mig_char,par='A124',
breaks=c(0,1.5,2.5,10),
label=c("age 1","age 2","age 3"))
r_mig_char<-calcule(r_mig_char,silent=TRUE)
plot(r_mig_char,plot.type="quant",silent=TRUE)
# one quantitative parameter found, manual choice of color
plot(r_mig_char,plot.type="quant",color_parm=c("C001"="red"),silent=TRUE)
plot(r_mig_char,plot.type="qual",silent=TRUE)
plot(r_mig_char,plot.type="crossed")
plot(r_mig_char,plot.type="crossed",
color_parm=c("age 1"="#379ec6","age 2"="#173957","age 3"="#b09953"))
xt<-xtable(r_mig_char)
```

```

# use method print.xtable to get the output
## Not run:
# An example with several years
r_mig_char<-new("report_mig_char")
baseODBC<-get("baseODBC",envir=envir_stacomi)
baseODBC[c(2,3)]<-rep("logrami",2)
assign("baseODBC",baseODBC,envir_stacomi)
sch<-get("sch",envir=envir_stacomi)
assign("sch","logrami.",envir_stacomi)
# here parqual is not in the list
# so this is equivalent to parqual=NULL
r_mig_char<-choice_c(r_mig_char,
  dc=c(107,108,101),
  taxa=c("Salmo salar"),
  stage=c('5','11','BEC','BER','IND'),
  parquan=c('A124','C001','1786','1785'),
  horodatedebut="2009-01-01",
  horodatefin="2012-12-31",
  #echantillon="with", # alternative "without"
  silent=FALSE)
# r_mig_char<-charge(r_mig_char) not necessary there
r_mig_char<-connect(r_mig_char)
# load the dataset generated by previous lines
r_mig_char<-setasqualitative(r_mig_char,par='A124',
  breaks=c(0,1.5,2.5,10),
  label=c("age 1","age 2","age 3"))
r_mig_char<-calcule(r_mig_char,silent=TRUE)

## End(Not run)

```

```
report_mig_env-class  Class "report_mig_env"
```

Description

Enables to compute an annual overview of fish migration and environmental conditions in the same chart. Environmental conditions may trigger migration events, variation in flow or temperatures can be plotted along migration to check graphically for a possible relation. To enable this, environmental conditions are loaded from an "environmental monitoring station", which records environmental parameters and is attached to a migratory station in the database. This class enables both continuous output (temperature -flow) as well as discrete parameters (qualitative = moon phase, type of operation of a gate, opening of a gate...) which will be displayed on the graph. Values are scaled so that single plot can display migration numbers and environmental parameters. Environmental parameters when stored at a time scale lower than a day are averaged per day, unless they are qualitative parameters, in which case only the first event of the day is displayed on the annual plot.

Slots

report_mig_mult [report_mig_mult-class](#)
 report_env [report_env-class](#)

Author(s)

cedric.briand"at"eptb-vilaine.fr marion.legrand"at"logrami.fr
 Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#),
[report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_interannual-class](#),
[report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#),
[report_species-class](#)

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#),
[report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_interannual-class](#),
[report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#),
[report_species-class](#)

Examples

```
require(stacomIR)
stacomI(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
# the following will load the data provided the user has access to the database
# with data in the iav example scheme.
## Not run:
  r_mig_env<-new("report_mig_env")
  r_mig_env<-choice_c(r_mig_env,
  dc=c(5,6,12),
  taxa=c("Anguilla anguilla"),
  stage=c("AGJ", "AGG", "CIV"),
  stationMesure=c("temp_gabion", "coef_maree", "phases_lune"),
  datedebut="2008-01-01",
  datefin="2008-12-31",
  silent=FALSE)
  r_mig_env<-charge(r_mig_env) # this is necessary to load operations, DF and DC
  r_mig_env<-connect(r_mig_env)
  r_mig_env<-calculer(r_mig_env,silent=TRUE)

## End(Not run)

data("r_mig_env")
# An example of plot with custom colors.
plot(r_mig_env,
color_station=c("temp_gabion"="red", "coef_maree"="blue", "phases_lune"="pink"),
color_dc=c("5"="yellow", "6"="orange", "12"="purple")
)
```

```
report_mig_interannual-class
      Class "report_mig_interannual"
```

Description

When daily report are written in the `t_reportjournalier_bjo` table by the [report_mig-class](#) they can be used by this class to display interannual comparisons of migration. When running its `connect` method, this class will run the [report_mig-class](#) for each year where data are missing, or where the annual sum in the `t_reportjournalier_bjo` table differs from the counts generated by the [report_annual-class](#) : rows have been changed in the database. Different charts are produced with different period grouping. See [write_database.report_mig-method](#) for details about how this method inserts data in the `t_reportjournalier_bjo` table.

Slots

`dc` An object of class [ref_dc-class](#), the counting device
`data` A data.frame data loaded from the daily migration table `t_bilanmigrationjournalier_bjo`
`taxa` An object of class [ref_taxa-class](#)
`stage` An object of class [ref_stage-class](#)
`start_year` An object of class [ref_year-class](#). `ref_year` allows to choose year of beginning
`end_year` An object of class [ref_year-class](#) `ref_year` allows to choose last year of the report
`calcdata` A list of calculated data, filled in by the `calcule` method

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomIR)
# launching stacomI without selecting the scheme or interface
stacomI(gr_interface=FALSE,
        login_window=FALSE,
        database_expected=FALSE)
##### If you have connection to the database with the pmp scheme #####
## Not run:

# overriding user schema to point to Parc Marais Poitevin
```

```

# (longest historical dataset available
# in France for eel ...) this suppose you have access to the pmp schema...
# a glimpse of the dataset is still available in the r_mig_interannual dataset
# loaded in the package...
baseODBC<-get("baseODBC",envir=envir_stacomi)
baseODBC[c(2,3)]<-rep("pmp",2)
assign("baseODBC",baseODBC,envir_stacomi)
sch<-get("sch",envir=envir_stacomi)
assign("sch","pmp.",envir_stacomi)
r_mig_interannual<-new("report_mig_interannual")
r_mig_interannual<-choice_c(r_mig_interannual,
dc=c(16),
taxa=c("Anguilla anguilla"),
stage=c("AGJ"),
anneedebut="1990",
anneefin="2015",
silent=TRUE)
r_mig_interannual<-connect(r_mig_interannual,silent=TRUE)

## End(Not run)
#####otherwise use this #####
# load the dataset generated by previous lines
data("r_mig_interannual")
#####
# the first plot is of little interest, it allows to see what data
# are available... simple lines
# For irregular operations like those reported at the enfrenaux eel ladder...
plot(r_mig_interannual,plot.type="line",silent=TRUE)

# a plot to show the seasonality, this graph may be misleading if the
# migration is not monitored all year round. Note the y unit is not very informative
# you need to have the viridis package loaded to run this example
plot(r_mig_interannual,plot.type="density",silent=TRUE)
## Not run:
  if (requireNamespace("ggplot2", quietly = TRUE)&
      requireNamespace("viridis", quietly = TRUE)){
g<-get("g",envir=envir_stacomi)
g+
ggplot2::scale_fill_manual(values=viridis::viridis(22))+
ggplot2::ggtitle("Saisonnalite de la migration aux Enfrenaux")
  }
#####
# the standard plot is showing daily values
#####
plot(r_mig_interannual,plot.type="standard",silent=TRUE)
# Manual edition of the graph produced
  if (requireNamespace("ggplot2", quietly = TRUE)){
    g1<-get("g1",envir=envir_stacomi)
    g1<-g1+ggplot2::ggtitle("Les Enfrenaux")+
ggplot2::scale_fill_manual(name="Source",
values=c("purple", "#0A0C01"),
labels = c("historical set", "2015 values"))+
ggplot2::scale_colour_manual(name="Source", values="#B8EA00",

```



```

labels = c("historical mean")) +
ggplot2::ylab("Nombre d'anguilles")
  print(g1)
}
#####
# Another graph to show a "manual" processing of the data
# and their extraction from the data slot
#####
if (requireNamespace("ggplot2", quietly = TRUE)&
    requireNamespace("viridis", quietly = TRUE)){
  dat<-fun_date_extraction(r_mig_interannual@data, # data to import
"bjo_jour", # name of the column where dates are found
annee=FALSE,
mois=TRUE,
semaine =TRUE,
jour_mois=FALSE)
# sum per month
  res<-dplyr::select(dat,bjo_valeur,bjo_annee,semaine)
  res<-dplyr::group_by(res,bjo_annee,semaine)
  res<-dplyr::summarize(res,effectif=sum(bjo_valeur))
  ggplot2::ggplot(res, ggplot2::aes(x = semaine, y = bjo_annee,fill=effectif)) +
    ggplot2::geom_tile(colour="black") + ggplot2::coord_fixed() +
    viridis::scale_fill_viridis(begin=0,option="D") + ggplot2::theme_bw()+
    ggplot2::theme(panel.background= ggplot2::element_rect(fill = "#9360A9"),
panel.grid.major=ggplot2::element_line(colour="#C1DB39"),
panel.grid.minor=ggplot2::element_line(colour="#7DD632"))+
    ggplot2::ylab("year")+ggplot2::xlab("week")+
    ggplot2::ggtitle("Historical trend at Les Enfrenaux Eel trap")

}
#####
# barchart with different splitting periods
# the migration is displayed against seasonal data
# extacted from all other years loaded in the report
#####
# available arguments for timesplit are "quinzaine" and "mois" and "semaine"
# with the silent=TRUE argument, it's always the latest year that is selected,
# otherwise the user is prompted with a choice, to select the year he wants
# to compare will all others...
  plot(r_mig_interannual,plot.type="barchart",timesplit="quinzaine",silent=TRUE)
# Comparison with historical values. Each year and 2 weeks values
# is a point on the graph...
  plot(r_mig_interannual,plot.type="pointrange",timesplit="mois",silent=TRUE)
#####
# Step plot
# different years shown in the graph
# the current year (or the selected year if silent=FALSE)
# is displayed with a dotted line
#####
  plot(r_mig_interannual,plot.type="step",silent=TRUE)
  if (requireNamespace("ggplot2", quietly = TRUE)&
      requireNamespace("viridis", quietly = TRUE)){
g<-get("g",envir=envir_stacomi) + ggplot2::theme_minimal()

```

```

g+viridis::scale_color_viridis(discrete=TRUE)+
ggplot2::ggtitle("Cumulated migration step plot
at les Enfrenaux eel trap")

}
#####
# Plots for seasonality of the salmon migration
# using a Loire river dataset (Vichy fishway)
#####
data("r_mig_interannual_vichy")
# the following show how data are processed to get
# statistics for seasonal migration, daily values
r_mig_interannual_vichy<-calculer(r_mig_interannual_vichy,timesplit="jour",silent=TRUE)
#r_mig_interannual_vichy@calldata #check this to see the results
# statistics for seasonal migration, weekly values
r_mig_interannual_vichy<-calculer(r_mig_interannual_vichy,timesplit="semaine",silent=TRUE)
#r_mig_interannual_vichy@calldata

# the plot method also runs the calculer method
plot(r_mig_interannual_vichy,plot.type="seasonal",timesplit="semaine",silent=TRUE)
plot(r_mig_interannual_vichy,plot.type="seasonal",timesplit="mois",silent=TRUE)
plot(r_mig_interannual_vichy,plot.type="seasonal",timesplit="jour",silent=TRUE)

#####
# Plots for seasonality using another Loire river dataset
# with the migration of Lampreys (Petromyzon marinus)
# recorded at the the Descarte DF (Vienne)
#####
# run this only if you are connected to the logrami dataset
baseODBC<-get("baseODBC",envir=envir_stacomi)
baseODBC[c(2,3)]<-rep("logrami",2)
assign("baseODBC",baseODBC,envir_stacomi)
sch<-get("sch",envir=envir_stacomi)
assign("sch","logrami.",envir_stacomi)
bmi_des<-new("report_mig_interannual")
bmi_des<-choice_c(bmi_des,
dc=c(23),
taxa=c("Petromyzon marinus"),
stage=c("5"),
annee debut="2007",
annee fin="2014",
silent=TRUE)
bmi_des<-connect(bmi_des)
bmi_des<-calculer(bmi_des,timesplit="semaine")
plot(bmi_des,plot.type="seasonal",timesplit="semaine")
plot(bmi_des,plot.type="seasonal",timesplit="jour")
plot(bmi_des,plot.type="seasonal",timesplit="mois")

## End(Not run)

```

report_mig_mult-class *Migration reports for multiple DC / species / stages*

Description

Migration counts for several Fish counting devices (DC), several taxa and several stages. This migration count can be built either by the graphical interface or from the command line (see examples).

Slots

dc An object of class `ref_dc-class`

taxa An object of class `ref_taxa-class`

stage An object of class `ref_stage-class`

timestep An object of class `ref_timestep_daily-class`

data A data.frame containing raw data filled by the connect method

calcddata A "list" of calculated daily data, one per dc, filled in by the calcule method

coef_conversion A data frame of daily weight to number conversion coefficients, filled in by the connect method if any weight are found in the data slot.

time.sequence A POSIXt time sequence

Note

A Migration report comes from a migration monitoring : the fishes are monitored in a section of river, this section is called a control station (station). Most often, there is a dam, one or several fishways (DF) which comprise one or several counting devices (DC). On each counting device, the migration is recorded. It can be either an instant recording (video control) or the use of traps, Operations are monitoring operations during a period. For each operation, several species of fishes can be recorded (samples). In the case of migratory fishes the stage of development is important as it may indicate generic migrations, to and fro, between the river and the sea.

Hence a Multiple Migration report is built from several one or several counting devices (DC), one or several Taxa (Taxon), one or several stages (stage). The migration can be also recorded not as numbers, but in the case of glass eels, as weight, which will be later transformed to number, from daily conversion coefficients. The methods in this class test whether the counts are numbers or another type of quantity. This class makes different calculations than `report_mig`, it does not handle escapement coefficients, it uses quantities other than numbers if necessary (only used for glass eel in the connect method).

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: `report_annual-class`, `report_dc-class`, `report_df-class`, `report_env-class`, `report_ge_weight-class`, `report_mig-class`, `report_mig_char-class`, `report_mig_env-class`, `report_mig_interannual-class`, `report_sample_char-class`, `report_sea_age-class`, `report_silver_eel-class`, `report_species-class`

Examples

```

library(stacomiR)

stacomi(gr_interface=FALSE,login_window=FALSE,database_expected=FALSE)
## launches the application in the command line
## here an example of loading
## the following lines will only run if you have the program installed
## and the iav scheme available in the database
## this example generates the r_mig_mult dataset
## Not run:
  stacomi(gr_interface=FALSE,
    login_window=FALSE,
    database_expected=TRUE)
  r_mig_mult=new("report_mig_mult")
  r_mig_mult=choice_c(r_mig_mult,
    dc=c(5,6,12),
    taxa=c("Anguilla anguilla"),
    stage=c("AGG","AGJ","CIV"),datedebut="2011-01-01",datefin="2011-12-31")
  r_mig_mult<-charge(r_mig_mult)
  # launching charge will also load classes associated with the report
  # e.g. report_ope, report_df, report_dc
  r_mig_mult<-connect(r_mig_mult)
  # calculations
  r_mig_mult<-calcule(r_mig_mult,silent=TRUE)

## End(Not run)

# Use this as example if you don't have a connexion to the database
data("r_mig_mult")
# The following re-create the object at the time of loading
# All three classes were created by the charge and connect
# method of report_mig_mult in the previous example
data("r_mig_mult_ope")
assign("report_ope",r_mig_mult_ope,envir=envir_stacomi)
data("r_mig_mult_df")
assign("report_df",r_mig_mult_df,envir=envir_stacomi)
data("r_mig_mult_dc")
assign("report_dc",r_mig_mult_dc,envir=envir_stacomi)
# use the following to get the raw data loaded by the connect method
# not shown there as the database and program might not be installed

#Individual plot for all DC, taxa and stage where data present
#Silent=TRUE to turn off messages
# not run because of multiple graphical devices

plot(r_mig_mult,plot.type="standard",silent=TRUE)
## Not run:
# colors in the following order (glass eel)
# working, stopped, 1..5 types of operation,numbers, weight, 2 unused colors
# for yellow eel and other taxa

```

```

# stopped, 1...5 types of operation, ponctuel, expert, calcule, mesure, working,
plot(r_mig_mult, plot.type="standard",
color=c("#DEF76B", "#B950B5", "#9ABDDA", "#781A74", "#BF9D6E", "#FFC26E",
"#A66F24", "#012746", "#6C3E00", "#DC7ED8", "#8AA123"),
color_ope=c("#5589B5", "#FFDB6E", "#FF996E", "#1C4D76"),
silent=TRUE)
#For the following plot, beware, all stages and DC are grouped. This can make sense
# for instance if you want to display the cumulated migration for one species
# in several counting devices located on the same dam...
plot(r_mig_mult, plot.type="step", silent=TRUE)

# Combined plot for ggplot2
plot(r_mig_mult, plot.type="multiple", silent=TRUE)
# Data will be written in the data directory specified in
# the stacomi/calcmig.csv file
summary(r_mig_mult, silent=TRUE)

## End(Not run)

```

report_ope-class	<i>Report on operations</i>
------------------	-----------------------------

Description

Operations are monitoring operations generated between two dates. In the case of video monitoring or similar, they can be instantaneous

Objects from the Class

Objects can be created by calls of the form `new("report_ope")`.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

report_sample_char-class	<i>Class "report_sample_char"</i>
--------------------------	-----------------------------------

Description

The `report_sample_char` class is used to load and display sample characteristics, which can be either continuous or discrete variable, for instance, it can be used to analyze size or sex structure during a given period.

Slots

data A data frame
 dc An object of class [ref_dc-class](#): the control devices
 taxa An object of class [ref_taxa-class](#): the species
 stage An object of class [ref_stage-class](#) : the stages of the fish
 par An object of class [ref_par-class](#): the parameters used
 horodatedebut An object of class [ref_horodate-class](#)
 horodatefin An object of class [ref_horodate-class](#)

Objects from the Class

Objects can be created by calls of the form `new("report_sample_char", ...)`

Note

This class is displayed by `interface_report_sample_char`, in the database, the class calls the content of the view `vue_lot_ope_car`

Author(s)

Cedric Briand <cedric.briand@eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sea_age-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```

require(stacomIR)
# launching stacomI without selecting the scheme or interface
stacomI(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
# the following script will load the Arzal dataset
#if connected to iav schema
## Not run:
#create an instance of the class
r_sample_char<-new("report_sample_char")
# the following will load data for size,
# parameters 1786 (total size) C001 (size at video control)
# dc 5 and 6 are fishways located on the Arzal dam
# two stages are selected
r_sample_char<-choice_c(r_sample_char,
dc=c(5,6),
taxa=c("Anguilla anguilla"),
stage=c("AGJ", "CIV"),

```

```

par=c(1785,1786,1787,"C001"),
horodatedebut="2013-01-01",
horodatefin="2013-12-31",
silent=FALSE)
# two warning produced, ignored if silent=TRUE
r_sample_char<-connect(r_sample_char)
r_sample_char<-calculer(r_sample_char,silent=TRUE)

## End(Not run)
# load the dataset generated by previous lines
data("r_sample_char")

# A "violin" plot
plot(r_sample_char,plot.type="1",silent=TRUE)
# get the plot from envir_stacomi to change labels for name
# if you use require(ggplot2) the :: argument is not needed
# e.g. write require(ggplot2);g<-get("g",envir=envir_stacomi)
# g+xlab("size")+ylab("year")
if (requireNamespace("ggplot2", quietly = TRUE)){
  g<-get("g",envir=envir_stacomi)
  g+ggplot2::xlab("size")+ggplot2::ylab("year")
}
# A boxplot per month
plot(r_sample_char,plot.type="2",silent=TRUE)
# A xyplot
plot(r_sample_char,plot.type="3",silent=TRUE)

## Not run:

#####
# an example graph created manually from data
#####
# two variables one on DC, one on stage
# passing dc information to the stage variable
r_sample_char@data$std_libelle[r_sample_char@data$sope_dic_identifiant==5]<-
  "Yellow eel (vert. slot fishway)"
r_sample_char@data$std_libelle[r_sample_char@data$std_libelle=="Anguille jaune"]<-
  "Yellow eel (ramp)"
r_sample_char@data$std_libelle[r_sample_char@data$std_libelle=="civelle"]<-
  "Glass eel (ramp)"
# creating a boxplot with custom output : an example
# again if you use require(ggplot2) the :: argument is not needed

if (requireNamespace("ggplot2", quietly = TRUE)){
g<-ggplot2::ggplot(r_sample_char@data)+
ggplot2::geom_boxplot(ggplot2::aes(x=annee,
y =car_valeur_quantitatif,
fill = std_libelle))+
ggplot2::xlab("size")+ggplot2::ylab("year")+
ggplot2::scale_fill_manual("stage & fishway",
values=c("Yellow eel (vert. slot fishway)"="blue",
"Yellow eel (ramp)"="turquoise3",

```

```

"Glass eel (ramp)"="Cyan")+
ggplot2::theme_bw()
print(g)
}

# get a simple summary using Hmisc::describe

summary(r_sample_char)
# get the command line to create the object using choice_c
# when the graphical interface has been used
print(r_sample_char)

## End(Not run)

```

```
report_sea_age-class  Class "report_sea_age"
```

Description

the `report_sea_age` class is used to dispatch adult salmon to age class according to their size and to basin dependent limits set by the user. Once checked with graphs and summary statistics, the results are to be written to the database.

Slots

`data` A data frame with data generated from the database

`calcddata` A list of dc with processed data. This lists consists of two elements

- (1) `data` A dataset with age set to be used by the plot and summary methods
- (2) `tj_caracteristiquelot_car` A dataset to import into the database

`dc` Object of class [ref_dc-class](#): the control devices

`taxa` Object of class [ref_taxa-class](#): the species

`stage` Object of class [ref_stage-class](#) : the stages of the fish

`par` Object of class [ref_par-class](#): the parameters used

`horodatedebut` An object of class [ref_horodate-class](#)

`horodatefin` An object of class [ref_horodate-class](#)

`limit1hm` The size limit, in mm between 1 sea winter fishes and 2 sea winter fishes

`limit2hm` The size limit, in mm between 2 sea winter fishes and 3 sea winter fishes

Objects from the Class

Objects can be created by calls of the form `new("report_sea_age", ...)`

Note

This class is displayed by `interface_report_sea_age`

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_silver_eel-class](#), [report_species-class](#)

Examples

```
require(stacomiR)
stacomi(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
## Not run:
  #create an instance of the class
  r_seaa<-new("report_sea_age")
  baseODBC<-get("baseODBC",envir=envir_stacomi)
  baseODBC[c(2,3)]<-rep("logrami",2)
  assign("baseODBC",baseODBC,envir_stacomi)
  sch<-get("sch",envir=envir_stacomi)
  assign("sch","logrami.",envir_stacomi)
  r_seaa<-choice_c(r_seaa,
  dc=c(107,108,101),
  horodatedebut="2012-01-01",
  horodatefin="2012-12-31",
  limit1hm=675,
  limit2hm=875,
  silent=FALSE
  )
  r_seaa<-connect(r_seaa)
  r_seaa<-calculer(r_seaa)

## End(Not run)
# load the dataset generated by previous lines
# Salmons from the loire on two dams
data("r_seaa")
# the calculation will fill the slot calcddata

# stages are in r_seaa@calcddata[["6"]][,"stage"]
#look at data structure using str(r_seaa@calcddata[["6"]])

# plot data to confirm the split by limits is correct
plot(r_seaa, plot.type=1)

# if there are several dc, data it split by dc
plot(r_seaa, plot.type=2)
## Not run:
# print a summary statistic, and save the output in a list for later use
```

```

stats<-summary(r_seaa)

write_database(r_seaa)

## End(Not run)

```

```

report_silver_eel-class
      Class "report_silver_eel"

```

Description

the `report_silver_eel` class is used to calculate various statistics about the silver eel run. It comprises calculation of various maturation index such as Durif's stages and Pankhurst eye index. The objective is to provide standardized output to the stations monitoring the silver eel run.

Slots

`data` A data frame with data generated from the database

`calcdata` A list of dc with processed data. Each dc contains a data frame with

- (1) qualitative data on body contrast (CONT), presence of punctuation on the lateral line (LNP)
- (2) quantitative data "BL" Body length, "W" weight, "Dv" vertical eye diameter, "Dh" horizontal eye diameter, "FL" pectoral fin length
- (3) calculated durif stages, Pankhurst's index, Fulton's body weight coefficient `K_ful`
- (4) other columns containing data pertaining to the sample and the control operation: `lot_identifiant`, `ope_identifiant`, `ope_dic_identifiant`, `ope_date_debut`, `ope_date_fin`, `dev_code` (destination code of fish), `dev_libelle` (text for destination of fish)

`dc` Object of class [ref_dc-class](#): the control devices

`taxa` An object of class [ref_taxa-class](#): the species

`stage` An object of class [ref_stage-class](#) : the stages of the fish

`par` An object of class [ref_par-class](#): the parameters used

`horodatedebut` An object of class [ref_horodate-class](#)

`horodatefin` An object of class [ref_horodate-class](#)

Objects from the Class

Objects can be created by calls of the form `new("report_silver_eel", ...)`

Note

This class is displayed by `interface_report_silver_eel`

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_species-class](#)

Examples

```
require(stacomiR)
# launching stacomi without selecting the scheme or interface
stacomi(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
# the following script will load data from the two Anguillere monitored in the Somme

## Not run:
#create an instance of the class
r_silver<-new("report_silver_eel")
baseODBC<-get("baseODBC",envir=envir_stacomi)
baseODBC[c(2,3)]<-rep("fd80",2)
assign("baseODBC",baseODBC,envir_stacomi)
sch<-get("sch",envir=envir_stacomi)
assign("sch","fd80.",envir_stacomi)
r_silver<-choice_c(r_silver,
dc=c(2,6),
horodatedebut="2010-09-01",
horodatefin="2016-10-04",
silent=FALSE)
r_silver<-connect(r_silver)

## End(Not run)
# load the dataset generated by previous lines
data("r_silver")
# the calculation will fill the slot calcddata
r_silver<-calcule(r_silver)
# stages are in r_silver@calcddata[["6"]][,"stage"]
#look at data structure using str(r_silver@calcddata[["6"]])

# standard plot as drawn by Laurent Beaulaton (Analyse des donnees d'argentine acquises en France)
# showing Durif's stage according to size and eye diameter
plot(r_silver, plot.type=1)

# number per month or year and Durif's stage (year if number of dc >1)
plot(r_silver, plot.type=2)

# plot showing fulton's coefficient, and size weight graphs
# inspired from Acou et al., 2009
# Differential Production and Condition Indices of Premigrant
```

```

# Eels in Two Small Atlantic Coastal Catchments
# of France
plot(r_silver, plot.type=3)
# get a list of summary data and print output to screen

plot(r_silver, plot.type=4)
# print a summary statistic, and save the output in a list for later use
stats<-summary(r_silver)

```

report_species-class *Counts of number per taxa/stages*

Description

This class is used to make the assessment of all species, and their number. It is intended as a simple way to check what fishes are present (taxa + development stage). Unlike the report_annual, it is not restricted to chosen taxa or stages but gives counts for all species present. The taxa is reported unless a taxa has several case, in which case the different stages for the taxa will be reported Using the split arguments the calc method of the class will count numbers, subsamples are not accounted for in the Overview. The split argument currently takes values year or month. The class is intended to be used over long periods e.g years. The plot method writes either an histogram or a pie chart of number per year/week/month.

Slots

dc an object of class [ref_dc-class](#)
anneedebut Object of class [ref_year-class](#)
anneefin Object of class [ref_year-class](#)
data data.frame
calcdata data.frame with data processed by the calc method
split Object of class [ref_list-class](#) ref_list referential class choose within a list

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

See Also

Other report.Objects: [report_annual-class](#), [report_dc-class](#), [report_df-class](#), [report_env-class](#), [report_ge_weight-class](#), [report_mig-class](#), [report_mig_char-class](#), [report_mig_env-class](#), [report_mig_interannual-class](#), [report_mig_mult-class](#), [report_sample_char-class](#), [report_sea_age-class](#), [report_silver_eel-class](#)

Examples

```

require(stacomR)
stacomr(gr_interface=FALSE,
login_window=FALSE,
database_expected=FALSE)
## Not run:
  bilespl<-new("report_species")
  # split is one of "none", "year", "week", "month
  bilespl<-choice_c(bilespl,
dc=c(5,6,12),
split="year",
anneeebut="2008",
anneefin="2012",
silent=FALSE)
#bilespl<-charge(bilespl) this is used by the graphical interface
bilespl<-connect(bilespl)
bilespl<-calcule(bilespl)
plot(bilespl,plot.type="pie",silent=FALSE)
plot(bilespl,plot.type="barplot",silent=FALSE)
bilespl<-choice_c(bilespl,
dc=c(5,6,12),
split="month",
anneeebut="2015",
anneefin="2016",
silent=FALSE)
bilespl<-charge(bilespl)
bilespl<-connect(bilespl)
plot(bilespl,plot.type="pie",silent=FALSE)
plot(bilespl,plot.type="barplot",silent=FALSE)
#length(unique(bilespl@calcddata$taxa_stage)) # 15
# here creating a vector of length 15 with nice blending colours
color<-c(mycolorrampblue(5),
mycolorrampyellow(5),
mycolorrampred(5))
plot(bilespl,plot.type="barplot",color=color,silent=TRUE)
summary(bilespl)

## End(Not run)

```

r_ann

Annual migration of yellow and silver eel for three fishways / counting devices at the Arzal dam (data from 1995 to 2016)

Description

The dataset corresponds to the three fishways located on the Arzal dam, filled with annual data

Usage

r_ann

Format

An object of class [report_annual-class](#) with data slot loaded.

r_ann_adour	<i>Annual migration of salmon in the Adour and tributaries</i>
-------------	--

Description

The dataset corresponds to the fishways DC=33:40 of the Adour for adult migrant salmons from 1996 to 2005 (annual counts). It has been kindly provided as an example set by the Migradour association.

Usage

r_ann_adour

Format

An object of class [report_annual-class](#) with data slot loaded.

r_dc	<i>Counting Device (DC) operation from 2000 to 2015 at the Arzal dam (Vilaine, France)</i>
------	--

Description

This data corresponds to the data collected at the vertical slot fishway camera from 2000 to 2015. It represents an object of class [report_dc-class](#) with data loaded

Usage

r_dc

Format

An object of class `report_dc` with 4 slots:

data A dataframe with 544 obs. of 7 variables

per_dis_identifiant The number of the DC

per_date_debut Starting time a POSIXct

per_date_fin Ending time a POSIXct

ope_dic_identifiant DC id

per_commentaires A comment

per_etat_fonctionnement Integer 1= working, 0 not working

per_tar_code The type of operation ("1"=normal operation, "2"=Device stopped in normal operation (e.g. the trap is disactivated for the duration of the fish sorting and counting by operators), "3"="Stopped for maintenance or other problem", "4"="Works but not fully operational, i.e. the camera is not working properly because of high turbidity...", "5"="Not known")

libelle label corresponding to per_tar_code

df the ref_dc object with 3 slots filled with data corresponding to the iav postgres schema

horodatedebut the ref_horodate with horodate set for starting date

horodatefin the ref_horodate with horodate set for ending date

 r_df

Overview of the fishway operation at Arzal in (Vilaine France).

Description

This dataset corresponds to the data collected at the vertical slot fishway in 2015, the fishway is working daily with a cycle depending on tide. This dataset is used to show an example of detailed output for an object of class [report_df-class](#) with data loaded

Usage

r_df

Format

An object of class report_df with 4 slots:

data A dataframe with 4261 obs. of 7 variables

per_dis_identifiant The number of the DF

per_date_debut Starting time a POSIXct

per_date_fin Ending time a POSIXct

ope_dic_identifiant DF id

per_commentaires A comment

per_etat_fonctionnement Integer 1= working, 0 not working

per_tar_code The type of operation ("1"=normal operation, "2"=Device stopped in normal operation (ie lift ascending, high tide...), "3"="Stopped for maintenance or other problem", "4"="Works but not fully operational, ie flow problem, flood, clogged with debris...", "5"="Not known")

libelle label corresponding to per_tar_code

df the ref_df object with 3 slots filled with data corresponding to the iav postgres schema

horodatedebut the ref_horodate with horodate set for starting date

horodatefin the ref_horodate with horodate set for ending date'

r_env

*An object of class report_env with data loaded***Description**

The dataset corresponds to the daily temperatures and moon phases in Arzal (Vilaine estuary, France). This environmental station is used to analyze conditions in which fish migrated at Arzal dam

Usage

r_env

Format

An object of class [report_env-class](#) with data slot loaded:

stationMesure the ref_env object with 5 slots filled with data corresponding to the iav postgres schema

horodatedebut object of class ref_horodate-class : the start date selected

horodatefin object of class ref_horodate-class : the end date selected

data A dataframe with 723 rows and 6 variables

env_date_debut start date

env_date_fin end date

env_methode_obtention method of data collection, measured, calculated...

env_val_identifiant the value of the parameter if qualitative

env_valeur_quantitatif the value of the parameter if quantitative

env_stm_identifiant station id

r_gew

*Wet weight of glass eel from the trapping ladder (Arzal, Vilaine France)***Description**

Data correspond to glass eel collected in the Vilaine at the trapping ladder (Arzal, France). The years selected are 2009 to 2012, the query used in the [report_ge_weight-class](#) loads from 2008-08-01 to 2012-08-01 Glass eel are too numerous to be counted. They are weighted and in the stacom database, a table with daily coefficients (in N glass eel/g) to transform weight into number. The weight is called a "wet weight" as we don't want to drain any of the mucus in glass eel when weighting them. Samples of 50 to 200 glass eel are weighted and then counted to provide an idea of the seasonal evolution of wet weight.

Usage

r_gew

Format

An object of class report_ge_weight of length 1.

r_mig	<i>Video counting of thin lipped mullet (Liza ramada) in 2015 in the Vilaine (France)</i>
-------	---

Description

This dataset corresponds to the data collected at the vertical slot fishway in 2015, video recording of the thin lipped mullet *Liza ramada* migration

Usage

r_mig

Format

An object of class report_mig with 8 slots:

dc the ref_dc object with 4 slots filled with data corresponding to the iav postgres schema

taxa the ref_taxa the taxa selected

stage the ref_stage the stage selected

timestep the ref_timestep_daily calculated for all 2015

data A dataframe with 10304 rows and 11 variables

ope_identifiant operation id

lot_identifiant sample id

lot_identifiant sample id

ope_dic_identifiant dc id

lot_tax_code species id

lot_std_code stage id

value the value

type_de_quantite either effectif (number) or poids (weights)

lot_dev_code destination of the fishes

lot_methode_obtention method of data collection, measured, calculated...

coef_conversion A data frame with 0 observations : no quantity are reported for video recording of mullets, only numbers

time.sequence A time sequence generated for the report, used internally

r_mig_char	<i>Qualitative and quantitative parameters describing Salmon migration at Decize (Loire)</i>
------------	--

Description

The dataset corresponds to the characteristics (qualitative and quantitative) of salmo salar migrating at Decize (Loire river) and Vichy (Allier river) counting device in 2012. It has been loaded as an example for the report_mig_char-class and kindly provided by Loire Grands Migrateurs (LOGRAMI).

Usage

r_mig_char

Format

An object of class [report_mig_char-class](#) with data slot loaded:

calcddata slot to be filled with the calcule method

data A list of 2 elements

parqual values of all the qualitative parameters

parquan values of all the quantitative parameters

dc the ref_dc : the control devices selected

taxa the ref_taxa : Salmo salar selected

stage the ref_stage : the stages selected

par an object of class [ref_par-class](#): the parameters used

horodatedebut an object of class ref_horodate-class : the start date selected

horodatefin an object of class ref_horodate-class : the end date selected

r_mig_dc	<i>Counting device operation for the video recording (Arzal dam, Vilaine, France).</i>
----------	--

Description

This dataset corresponds to the data collected in the vertical slot fishway for the video recording operation. It is loaded along with r_mig to demonstrate the use of the [report_mig-class](#) when the database is not loaded

Usage

r_mig_dc

Format

An object of class [report_dc-class](#)

r_mig_df	<i>Fishway operation for the vertical slot fishway (Arzal dam, Vilaine, France).</i>
----------	--

Description

This dataset corresponds to the data collected at in the vertical slot fishway it is loaded along with [r_mig](#) and used to demonstrate the [report_mig-class](#) when the database is not installed.

Usage

r_mig_df

Format

An object of class [report_df-class](#)

r_mig_env	<i>An object of class report_mig_env with data loaded</i>
-----------	---

Description

The dataset correspond to data loaded for the Arzal dam (Vilaine) in 2008, two quantitative parameters (temperature and tide coefficient) and a qualitative parameter (moon phase) are loaded.

Usage

r_mig_env

Format

An object of class [report_env-class](#) with data slot loaded:

report_mig_mult An object of class [report_mig_mult-class](#)

report_env An object of class [report_env-class](#)#'

r_mig_interannual	<i>Daily glass eel and elver migration from 1984 to 2016 in the Sevre Niortaise</i>
-------------------	---

Description

The first eel trapping ladder in France was built by Antoine Legault and the team from Rennes in the Sevre Niortaise, Marais Poitevin. Also refurbished several times since 1984 it has been operational at the same location and provides one of the longest series of eel migration. For this reason, the dataset has been loaded as an example for the `report_mig_interannual-class`. It has been kindly provided by the parc du Marais Poitevin.

Usage

```
r_mig_interannual
```

Format

An object of class `report_mig_interannual-class` with data loaded.

r_mig_interannual_vichy	<i>Seasonality of salmon migration at the Vichy counting station (Loire)</i>
-------------------------	--

Description

This data corresponds to the data collected at the Vichy fishway between 1997 and 2012, video recording of the *Salmo salar* upstream migration. This dataset has been kindly provided by Loire Grands Migrateurs.

Usage

```
r_mig_interannual_vichy
```

Format

An object of class `report_mig_interannual-class` with 7 slots:

dc the `ref_dc` object with 4 slots filled with data corresponding to the `iav` postgres schema

taxa the `ref_taxa` the taxa selected

stage the `ref_stage` the stage selected

start_year the `ref_timestep_daily` calculated for all 2015

end_year the `ref_timestep_daily` calculated for all 2015

data A dataframe with 7138 rows and 10 variables

bj_o_identifiant sample id
bj_o_dis_identifiant dc id
bj_o_tax_code species id
bj_o_std_code stage id
bj_o_annee year
bj_o_jour date
bj_o_labelquantite method of data collection, measured, calculated...
bj_o_horodateexport date with special format for export
bj_o_org_code organisme provided the data

r_mig_mult

Anguilla migration at the Arzal station (report_mig_mult-class)

Description

This data corresponds to data collected from three fishways and correspond to the migration station at Arzal (Vilaine estuary, France) in 2011 for three continental stages of eel (*Anguilla anguilla*) : glass eel, yellow eel and silver eel.

Usage

r_mig_mult

Format

An object of class `report_mig_mult` with slots:

dc the `ref_dc` object filled with data
taxa the `ref_taxa` object filled in with data corresponding to `dc`
stage the `ref_stage` object filled in with data corresponding to `dc`, and `taxa`
timestep the `ref_timestep_daily` calculated for all 2011
data A dataframe with 400 rows and 11 variables

- ope_identifiant** operation id
- lot_identifiant** sample id
- lot_identifiant** sample id
- ope_dic_identifiant** dc id
- lot_tax_code** species id
- lot_std_code** stage id
- value** the value
- type_de_quantite** either effectif (number) or poids (weights)
- lot_dev_code** destination of the fishes
- lot_methode_obtention** method of data collection, measured, calculated...

calcddata slot to be filled with the `calcule` method
coef_conversion A data frame with 364 observations with daily coefficients to convert from weight to numbers
time.sequence A time sequence generated for the report, used internally by the object

r_mig_mult_dc	<i>Counting device operation for three different counting device in Arzal (Vilaine, France)</i>
---------------	---

Description

This dataset corresponds to data collected at three different control devices. This object is of class `report_dc-class` with data loaded it is loaded along with `r_mig_mult` and used in demonstration for the `report_mig_mult-class`

Usage

```
r_mig_mult_dc
```

Format

An object of class `report_dc` with 4 slots

data A dataframe with 25 rows and 7 variables

per_dis_identifiant the df or dc unique id

per_date_debut the starting date of the counting device operation POSIXct

per_date_fin the ending date of the counting device operation POSIXct

per_commentaires comments on the counting device operation

per_etat_fonctionnement Boolean, is the counting device working ?

lot_std_code stage id

per_tar_code The type of operation for the DC, 1 normal operation, 2 device stopped in normal operation (the stop is considered as normal, e.g. you don't monitor video if a cage has been placed to trap fishes), 3 stopped for maintenance or other problem, 4 the DC is working but not well (escapement in a tank, high turbidity preventing video counting...), 5 unknown operation.

libelle The label for the type or operation

dc the ref_dc the DC with 4 slots

dc_selectionne the selected device

ouvrage the dam

station the monitoring station, a section of river

data A dataset of all dc present in the database with 10 observations

horodatedebut the beginning date, a `ref_horodate-class`

horodatefin the ending date, a `ref_horodate-class`

r_mig_mult_df	<i>Fishway operation at the Arzal Dam (Vilaine France) (3 Fishways in 2011)</i>
---------------	---

Description

This dataset corresponds to the data collected at three different fishways it is loaded along with [r_mig_mult](#) and used in demonstration for the [report_mig_mult-class](#)

Usage

```
r_mig_mult_df
```

Format

An object of class `report_df` [report_df-class](#)

r_mig_mult_ope	<i>Counting operations for three different counting device in Arzal (Vilaine, France)</i>
----------------	---

Description

This dataset corresponds to the data collected at three different control devices It is an object of class [report_ope-class](#) with data loaded. it is loaded along with [r_mig_mult](#)

Usage

```
r_mig_mult_ope
```

Format

An object of class `report_ope`

r_mig_ope	<i>An object of class report_ope-class with data loaded</i>
-----------	---

Description

This dataset corresponds to the data collected at the vertical slot fishway in Arzal (Vilaine river estuary, France). The operation of the fishway is dependent on tide and is recorded every 10 minutes. This dataset has to be loaded along with [r_mig](#) to demonstrate the use of the [report_mig-class](#)

Usage

r_mig_ope

Format

An object of class report_ope

r_sample_char	<i>Size of yellow and glass eel at the Arzal dam (Vilaine, France) in the fishway and main eel trapping ladder.</i>
---------------	---

Description

This dataset corresponds to the data collected at two different control devices at the Arzal control station (see example in [report_sample_char-class](#)), all body size parameters (total size, size converted from pixel in video control) are used in example

Usage

r_sample_char

Format

An object of class [report_sample_char-class](#)

r_seaa *An object of class report_sea_age with data loaded*

Description

This dataset corresponds to the data collected at Vichy (left and right bank fishways) and Decize-Saint Leger des Vignes fishways (respectively on the Allier and Loire river, France) in 2012 on the size structure of *Salmo salar*. It has been kindly provided by the Loire Grands Migrateurs (LOGRAMI) association.

Usage

r_seaa

Format

An object of class [report_sea_age-class](#) with 8 slots:

dc the ref_dc : the control devices selected
taxa the ref_taxa : *Salmo salar* selected
stage the ref_stage : the stages selected
par Object of class [ref_par-class](#): the parameters used
horodatedebut object of class ref_horodate-class : the start date selected
horodatefin object of class ref_horodate-class : the end date selected
limit1hm The size limit, in mm between 1 sea winter fishes and 2 sea winter fishes
limit2hm The size limit, in mm between 2 sea winter fishes and 3 sea winter fishes
data A dataframe with 898 rows and 20 variables

- ope_identifiant** operation id
- lot_identifiant** sample id
- ope_dic_identifiant** dc id
- ope_date_debut** start date
- ope_date_fin** end date
- lot_effectif** number of fishes
- lot_tax_code** species id
- lot_std_code** stages id
- tax_nom_latin** species latin names
- std_libelle** stages names
- dev_code** destination of the fishes id
- dev_libelle** destination of the fishes names
- par_nom** parameter name
- car_par_code** parameter id
- car_methode_obtention** method of data collection, measured, calculated...
- car_valeur_quantitatif** the value of the parameter

r_silver	<i>Silver eel migration in the Somme</i>
----------	--

Description

The dataset corresponds to the silver eel traps ("anguilleres) for 2015-2016. This dataset has been kindly provided by the Federation de Peche de la Somme, given the upstream location of the trap, most individuals are female

Usage

```
r_silver
```

Format

An object of class [report_silver_eel-class](#) with data slot loaded.

setasqualitative	<i>Generic method to transform quantitative par into a qualitative one</i>
------------------	--

Description

Generic method to transform quantitative par into a qualitative one

Usage

```
setasqualitative(object, ...)
```

Arguments

object	Object
...	Additional parms

Author(s)

cedric.briand

```
setasqualitative,report_mig_char-method
```

Turns a quantitative parameter into qualitative

Description

Turns a quantitative parameter into qualitative

Usage

```
## S4 method for signature 'report_mig_char'
setasqualitative(object, par, silent = FALSE, ...)
```

Arguments

object	An object of class ref_parquan-class
par	The code of a quantitative parameter
silent	Default FALSE, if TRUE the program should not display messages
...	Additional parms to the cut method cut

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

```
split_per_day
```

Create a dataframe suitable for charts per 24h and day

Description

This functions takes a data frame with a column with starting time and another with ending time If the period extends over midnight, it will be split into new lines, starting and ending at midnight

Usage

```
split_per_day(data, horodatedebut, horodatefin)
```

Arguments

data	The dataframe
horodatedebut	The beginning time
horodatefin	The ending time

Value

A data frame with four new columns, Hmin (hour min), Hmax (hmax), xmin (day) and xmax (next day), and new rows

Author(s)

cedric.briand

Examples

```
datatemp<-structure(list(per_dis_identifiant = c(1L, 1L, 1L),
per_date_debut = structure(c(1420056600,
1420071000, 1420081200), class = c("POSIXct", "POSIXt"), tzzone = ""),
per_date_fin = structure(c(1420071000, 1420081200, 1421000000
), class = c("POSIXct", "POSIXt"), tzzone = ""), per_commentaires = c("fonct calcul",
"fonct calcul", "fonct calcul"), per_etat_fonctionnement = c(1L,
0L, 0L), per_tar_code = 1:3, libelle = c("Fonc normal", "Arr ponctuel",
"Arr maint")), .Names = c("per_dis_identifiant", "per_date_debut",
"per_date_fin", "per_commentaires", "per_etat_fonctionnement",
"per_tar_code", "libelle"), row.names = c(NA, 3L), class = "data.frame")
newdf<-split_per_day(data=datatemp,horodatedebut="per_date_debut",
horodatefin="per_date_fin")
```

stacom

Function that loads the loginwindow, tests connection, and then destroys the window

Description

Function that loads the loginwindow, tests connection, and then destroys the window

Usage

```
stacom(gr_interface=TRUE,login_window=TRUE,database_expected=TRUE)
```

Arguments

gr_interface Boolean, if TRUE the program will launch the graphical interface

login_window Boolean, if TRUE a login window will be displayed asking the user to specify user name.

database_expected Boolean, if TRUE pre launch tests will be run to test the connection validity

Note

The default behaviour of the program is to run through the following elements

- login window The program opens a login window to prompt the user to give his usernames and passwords. default values will proposed from "C:/program files/stacomir/calcmig.csv" and if this file does not exists, from `file.path(.libPaths(), "stacomir", "config", "calcmig.csv")` as a default. If `login_window=FALSE` the program will skip the login window and use `calcmig` values for user (`uid`) and password(`pwd`) as a default.
- tests for connection Test for the existence of a `calcmig.csv` file, and then the existence of the file `usr.tr_taxon_tax` where `usr` is the username extracted from `calcmig`. These tests are only done if `database_expected=TRUE`. If the test don't pass, then the user is prompted for a "login window" even if argument `login_window` was set to `FALSE` at launch.
- graphical interface When either, previous tests have been run successfully, or the value for `database_expected=FALSE` the program will launch. If `graphical_interface` is `TRUE`, the program will use a graphical interface `interface_graphique` to build the graphical interface, otherwise the program is expected to run through the command line.

When `database_expected=FALSE` a connection to the database is not expected. Therefore test are run by calling examples object stored in `Rdata`. To change the language use `Sys.setenv(LANG = "fr")` or `Sys.setenv(LANG = "en")`

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
require(stacomir)
#launch stacomir with the graphical interface
## Not run:
stacomir()

## End(Not run)
# launch stacomir but do not prompt for password
## Not run:
stacomir(login_window=FALSE)

## End(Not run)
#launch stacomir without connection to the database
stacomir(gr_interface=FALSE,login_window=FALSE,database_expected=FALSE)
```

summary,report_dc-method

summary for report_dc, write csv and html output, and prints summary statistics

Description

summary for report_dc, write csv and html output, and prints summary statistics

Usage

```
## S4 method for signature 'report_dc'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_dc-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters (not used there)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_df-method

summary for report_df, write csv and html output, and prints summary statistics

Description

summary for report_df, write csv and html output, and prints summary statistics

Usage

```
## S4 method for signature 'report_df'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_df-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters (not used there)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_mig-method

summary for report_mig calls functions funstat and funtable to create migration overviews and generate csv and html output in the user data directory

Description

summary for report_mig calls functions funstat and funtable to create migration overviews and generate csv and html output in the user data directory

Usage

```
## S4 method for signature 'report_mig'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_mig-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters (not used there)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_mig_char-method

summary for report_mig_char

Description

summary for report_mig_char

Usage

```
## S4 method for signature 'report_mig_char'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_mig_char-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_mig_interannual-method

summary for report_mig_interannual provides summary statistics for the latest year (if silent=TRUE), or the year selected in the interface, if silent=FALSE. Mean, min and max are historical statistics with the selected year excluded from the historical dataset.

Description

summary for report_mig_interannual provides summary statistics for the latest year (if silent=TRUE), or the year selected in the interface, if silent=FALSE. Mean, min and max are historical statistics with the selected year excluded from the historical dataset.

Usage

```
## S4 method for signature 'report_mig_interannual'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_mig_interannual-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters (not used there)

Value

A list, one element per DC

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_mig_mult-method

summary for report_mig_mult calls functions funstat and funtable to create migration overviews and generate csv and html output in the user data directory

Description

summary for report_mig_mult calls functions funstat and funtable to create migration overviews and generate csv and html output in the user data directory

Usage

```
## S4 method for signature 'report_mig_mult'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_mig_mult-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters (not used there)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_sample_char-method

summary for report_sample_char

Description

summary for report_sample_char

Usage

```
## S4 method for signature 'report_sample_char'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_sample_char-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_sea_age-method

summary for report_sea_age

Description

summary for report_sea_age

Usage

```
## S4 method for signature 'report_sea_age'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_sea_age-class
silent	Default FALSE, if TRUE the program should no display messages.
...	Additional parameters

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_silver_eel-method

summary for report_silver_eel

Description

summary for report_silver_eel

Usage

```
## S4 method for signature 'report_silver_eel'  
summary(object, silent = FALSE, ...)
```

Arguments

object	An object of class report_silver_eel-class
silent	Should the program stay silent or display messages, default FALSE
...	Additional parameters

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

summary,report_species-method

summary for report_species generate csv and html output in the user data directory

Description

summary for report_species generate csv and html output in the user data directory

Usage

```
## S4 method for signature 'report_species'
summary(object, silent = FALSE)
```

Arguments

object	An object of class report_species-class
silent	Should the program stay silent or display messages, default FALSE

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

supprime

Generic method to delete entires from the database

Description

Generic method to delete entires from the database

Usage

```
supprime(object, ...)
```

Arguments

object	Object
...	Additional parms

Author(s)

cedric.briand

supprime,ref_coe-method

supprime method for "ref_coe" class

Description

supprime method for "ref_coe" class

Usage

```
## S4 method for signature 'ref_coe'  
supprime(object, tax, std, silent = FALSE)
```

Arguments

object	An object of class ref_coe-class
tax	'2038=Anguilla anguilla'
std	'CIV=civelle'
silent	Default FALSE, if TRUE the program should no display messages

Value

nothing

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

supprime,report_mig_interannual-method

supprime method for report_mig_interannual class

Description

supprime method for report_mig_interannual class

Usage

```
## S4 method for signature 'report_mig_interannual'  
supprime(object)
```

Arguments

object	An object of class report_mig_interannual-class
--------	---

Value

nothing

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

supprime,report_sea_age-method

supprime method for report_mig_interannual class

Description

supprime method for report_mig_interannual class

Usage

```
## S4 method for signature 'report_sea_age'
supprime(object, silent = FALSE)
```

Arguments

object	An object of class report_sea_age-class
silent	Default FALSE, if TRUE the program should no display messages

Value

nothing

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

vector_to_listsql

Transforms a vector into a string called within an sql command e.g. c('A','B','C') => in ('A','B','C')

Description

Transforms a vector into a string called within an sql command e.g. c(A,B,C) => in ('A','B','C')

Usage

```
vector_to_listsql(vect)
```

Arguments

vect a character vector

Value

listsql a list of value

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

write_database *Generic method write_database*

Description

Generic method write_database

Usage

```
write_database(object, ...)
```

Arguments

object Object
 ... Additional parms

Author(s)

cedric.briand

write_database,report_ge_weight-method
Function to write data to the stacomi database for [report_ge_weight-class](#)

Description

Data will be written in tj_coefficientconversion_coe table, if the class retrieves some data from the database, those will be deleted first.

Usage

```
## S4 method for signature 'report_ge_weight'  
write_database(object, silent = FALSE)
```

Arguments

object An object of class [report_ge_weight-class](#)
 silent Boolean, if TRUE, information messages are not displayed

Value

An object of class [report_ge_weight-class](#)

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

write_database,report_mig-method

*Command line method to write the daily and monthly counts to the
 t_bilanmigrationjournalier_bjo table*

Description

Daily values are needed to compare migrations from year to year, by the class [report_mig_interannual-class](#). They are added by by this function.

Usage

```
## S4 method for signature 'report_mig'
write_database(object, silent = TRUE,
  check_for_bjo = TRUE)
```

Arguments

object an object of class [report_mig](#)
 silent : TRUE to avoid messages
 check_for_bjo : do you want to check if data are already present in the bjo table, and delete them, this param was added otherwise connect method when called from report_mig_interannual runs in loops

Note

the user is asked whether or not he wants to overwrite data, if no data are present in the database, the import is done anyway. The name of the database is retrieved from the odbc link

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

Examples

```
## Not run:
stacomis(gr_interface=FALSE,login_window=FALSE,database_expected=FALSE)
data("r_mig")
r_mig<-calculer(r_mig)
write_database(report_mig=r_mig,silent=FALSE)

## End(Not run)
```

```
write_database,report_sea_age-method
```

Command line method to write the characteristic "sea age" (car_par_code='A124') into the tj_caracteristiquelot_car table in the user's scheme

Description

The sea age characteristic is calculated from the measured or calculated size of salmon and with a size/age rule defined by the user . the name of the database is retrieved from the odbc link defined in calcmig.csv

Usage

```
## S4 method for signature 'report_sea_age'
write_database(object, silent = TRUE)
```

Arguments

object an object of class [report_sea_age-class](#)
silent : Default FALSE, if TRUE the program should no display messages.

Author(s)

Cedric Briand <cedric.briand"at"eptb-vilaine.fr>

```
xtable,report_annual-method
```

xtable function for [report_annual-class](#) create an xtable objet but also assigns an add.to.column argument in envir_stacomis, for later use by the print.xtable method.

Description

xtable function for [report_annual-class](#) create an xtable objet but also assigns an add.to.column argument in envir_stacomis, for later use by the print.xtable method.

Usage

```
## S4 method for signature 'report_annual'
xtable(x, caption = NULL, label = NULL,
       align = NULL, digits = 0, display = NULL, auto = FALSE,
       dc_name = NULL, tax_name = NULL, std_name = NULL)
```

Arguments

x,	an object of class "report_annual"
caption,	see xtable
label,	see xtable
align,	see xtable, overridden if NULL
digits	default 0
display	see xtable
auto	see xtable
dc_name	A string indicating the names of the DC, in the order of x@dc@dc_selectionne if not provided DC codes are used.
tax_name	A string indicating the names of the taxa, if not provided latin names are used
std_name	A string indicating the stages names, if not provided then std_libelle are used

xtable,report_mig_char-method

xtable function for [report_mig_char-class](#) create an xtable objet to be later used by the print.xtable method.

Description

xtable function for [report_mig_char-class](#) create an xtable objet to be later used by the print.xtable method.

Usage

```
## S4 method for signature 'report_mig_char'
xtable(x, caption = NULL, label = NULL,
       align = NULL, digits = NULL, display = NULL, auto = FALSE, ...)
```

Arguments

x,	an object of class "report_mig_char"
caption,	see xtable
label,	see xtable
align,	see xtable, overridden if NULL
digits,	see xtable

display	see xtable
auto	see xtable
...	Additional parameters

Index

*Topic **classes**

- ref_coe-class, 104
- ref_dc-class, 104
- ref_env-class, 106
- ref_par-class, 107
- ref_parquan-class, 108
- ref_period-class, 108
- ref_stage-class, 109
- ref_timestep_daily-class, 111
- ref_timestepChar-class, 111
- ref_year-class, 112
- report_annual-class, 113
- report_dc-class, 115
- report_df-class, 116
- report_env-class, 118
- report_ge_weight-class, 119
- report_mig-class, 121
- report_mig_char-class, 123
- report_mig_env-class, 125
- report_mig_interannual-class, 127
- report_mig_mult-class, 131
- report_ope-class, 133
- report_sample_char-class, 133
- report_sea_age-class, 136
- report_silver_eel-class, 138
- report_species-class, 140

*Topic **database**

- chargecomplement-methods, 30
- stacomIR-package, 7

*Topic **datasets**

- calcmig, 8
- coef_durif, 59
- envir_stacom, 71
- r_gew, 144

*Topic **data**

- r_ann, 141
- r_ann_adour, 142
- r_dc, 142
- r_df, 143

- r_env, 144
- r_mig, 145
- r_mig_char, 146
- r_mig_dc, 146
- r_mig_df, 147
- r_mig_env, 147
- r_mig_interannual, 148
- r_mig_interannual_vichy, 148
- r_mig_mult, 149
- r_mig_mult_dc, 150
- r_mig_mult_df, 151
- r_mig_mult_ope, 151
- r_mig_ope, 152
- r_sample_char, 152
- r_seaa, 153
- r_silver, 154

*Topic **dynamic**

- stacomIR-package, 7

*Topic **environment**

- envir_stacom, 71

*Topic **methods**

- chargecomplement-methods, 30
- graphe-methods, 85

*Topic **package**

- stacomIR-package, 7

- barplot, report_annual-method, 7
- barplot.report_annual
(barplot, report_annual-method),
7

- calcmig, 8
- calcule, 9
- calcule, report_ge_weight-method, 9
- calcule, report_mig-method, 10
- calcule, report_mig_char-method, 11
- calcule, report_mig_env-method, 11
- calcule, report_mig_interannual-method,
12
- calcule, report_mig_mult-method, 13

- calculer, report_sample_char-method, 14
- calculer, report_sea_age-method, 14
- calculer, report_silver_eel-method, 15
- calculer, report_species-method, 16
- calculer.report_ge_weight
 - (calculer, report_ge_weight-method), 9
- calculer.report_mig
 - (calculer, report_mig-method), 10
- calculer.report_mig_char
 - (calculer, report_mig_char-method), 11
- calculer.report_mig_env
 - (calculer, report_mig_env-method), 11
- calculer.report_mig_interannual
 - (calculer, report_mig_interannual-method), 12
- calculer.report_mig_mult
 - (calculer, report_mig_mult-method), 13
- calculer.report_sample_char
 - (calculer, report_sample_char-method), 14
- calculer.report_sea_age
 - (calculer, report_sea_age-method), 14
- calculer.report_silver_eel
 - (calculer, report_silver_eel-method), 15
- calculer.report_species
 - (calculer, report_species-method), 16
- charge, 16
- charge, ref_checkbox-method, 17
- charge, ref_choice-method, 18
- charge, ref_coe-method, 19
- charge, ref_dc-method, 19
- charge, ref_df-method, 20
- charge, ref_env-method, 21
- charge, ref_list-method, 21
- charge, ref_par-method, 22
- charge, ref_parqual-method, 23
- charge, ref_parquan-method, 24
- charge, ref_stage-method, 24
- charge, ref_taxa-method, 25
- charge, ref_textbox-method, 26
- charge, ref_year-method, 26
- charge, report_ge_weight-method, 27
- charge, report_mig-method, 28
- charge, report_mig_env-method, 28
- charge, report_mig_mult-method, 28, 29
- charge.report_ge_weight
 - (charge, report_ge_weight-method), 27
- charge.report_mig
 - (charge, report_mig-method), 28
- charge.report_mig_env
 - (charge, report_mig_env-method), 28
- charge.report_mig_mult
 - (charge, report_mig_mult-method), 29
- charge_complement, 30
- charge_complement, ref_parqual-method, 31
- charge_with_filter, ref_par-method, 32
- charge_with_filter, ref_parqual-method, 33
- charge_with_filter, ref_parquan-method, 34
- charge_with_filter, ref_stage-method, 35
- charge_with_filter, ref_taxa-method, 36, 37
- chargecomplement
 - (chargecomplement-methods), 30
- chargecomplement, ref_parqual-method
 - (chargecomplement-methods), 30
- chargecomplement-methods, 30
- choice_c, ref_choice-method, 38
- choice_c, ref_dc-method, 39, 47, 50–59
- choice_c, ref_df-method, 40
- choice_c, ref_env-method, 40, 49, 53
- choice_c, ref_horodate-method, 41
- choice_c, ref_list-method, 42
- choice_c, ref_par-method, 42, 56
- choice_c, ref_stage-method, 43, 47, 51, 54–56
- choice_c, ref_taxa-method, 44, 47, 51–58
- choice_c, ref_textbox-method, 45
- choice_c, ref_timestep_daily-method, 45
- choice_c, ref_year-method, 46
- choice_c, report_annual-method, 47
- choice_c, report_dc-method, 48
- choice_c, report_df-method, 48

- choice_c,report_env-method, 49
- choice_c,report_ge_weight-method, 50
- choice_c,report_mig-method, 51
- choice_c,report_mig_char-method, 52
- choice_c,report_mig_env-method, 53
- choice_c,report_mig_interannual-method, 54
- choice_c,report_mig_mult-method, 55
- choice_c,report_sample_char-method, 56
- choice_c,report_sea_age-method, 57
- choice_c,report_silver_eel-method, 58
- choice_c,report_species-method, 59
- choice_c.report_annual
 - (choice_c,report_annual-method), 47
- choice_c.report_dc
 - (choice_c,report_dc-method), 48
- choice_c.report_df
 - (choice_c,report_df-method), 48
- choice_c.report_ge_weight
 - (choice_c,report_ge_weight-method), 50
- choice_c.report_mig
 - (choice_c,report_mig-method), 51
- choice_c.report_mig_char
 - (choice_c,report_mig_char-method), 52
- choice_c.report_mig_env
 - (choice_c,report_mig_env-method), 53
- choice_c.report_mig_interannual
 - (choice_c,report_mig_interannual-method), 54
- choice_c.report_mig_mult
 - (choice_c,report_mig_mult-method), 55
- choice_c.report_sample_char
 - (choice_c,report_sample_char-method), 56
- choice_c.report_sea_age
 - (choice_c,report_sea_age-method), 57
- choice_c.report_silver_eel
 - (choice_c,report_silver_eel-method), 58
- choice_c.report_species
 - (choice_c,report_species-method), 59
- choicemult,ref_dc-method, 36
- choicemult,ref_taxa-method, 37
- coef_durif, 59
- colortable, 60
- connect,report_annual-method, 61
- connect,report_dc-method, 61
- connect,report_df-method, 62
- connect,report_env-method, 63
- connect,report_ge_weight-method, 63
- connect,report_mig-method, 64
- connect,report_mig_char-method, 65
- connect,report_mig_env-method, 65
- connect,report_mig_interannual-method, 66
- connect,report_mig_mult-method, 67
- connect,report_ope-method, 67
- connect,report_sample_char-method, 68
- connect,report_sea_age-method, 68
- connect,report_silver_eel-method, 69
- connect,report_species-method, 70
- connect.report_annual
 - (connect,report_annual-method), 61
- connect.report_dc
 - (connect,report_dc-method), 61
- connect.report_df
 - (connect,report_df-method), 62
- connect.report_env
 - (connect,report_env-method), 63
- connect.report_ge_weight
 - (connect,report_ge_weight-method), 63
- connect.report_mig
 - (connect,report_mig-method), 64
- connect.report_mig_char
 - (connect,report_mig_char-method), 65
- connect.report_mig_interannual
 - (connect,report_mig_interannual-method), 66
- connect.report_mig_mult
 - (connect,report_mig_mult-method), 67
- connect.report_ope
 - (connect,report_ope-method), 67
- connect.report_sample_char
 - (connect,report_sample_char-method), 68

- 68
- connect.report_sea_age
(connect,report_sea_age-method),
68
- connect.report_silver_eel
(connect,report_silver_eel-method),
69
- connect.report_species
(connect,report_species-method),
70
- createmessage, 70
- current_end_date,ref_timestep-method,
71
- cut, 155
- envir_stacomi, 71
- fun_aggreg_for_plot, 76
- fun_char_spe, 77
- fun_date_extraction, 77
- fun_report_mig_interannual, 78
- fun_report_mig_mult, 10, 13, 79
- fun_report_mig_mult_overlaps, 10, 13, 79,
79
- fun_stage_durif, 80
- fun_table_per_dis, 81
- fun_weight_conversion, 10, 13, 81
- fun_write_monthly, 82
- funbarchart1DC, 72
- fungraph, 67, 72, 91, 94
- fungraph_glasseel, 67, 73, 91, 94
- funstat, 74, 82
- funstat_daily, 75
- funtable, 75
- getdbname, 83
- getnocurrent_step, 83
- getvalue, 84
- getvalue,ref_period-method, 84
- graphdate, 85
- graphe (graphe-methods), 85
- graphe,report_migPar-method
(graphe-methods), 85
- graphe-methods, 85
- interface_graphique, 157
- model, 86
- model,report_ge_weight-method, 86
- model.report_ge_weight
(model,report_ge_weight-method),
86
- plot,report_annual,missing-method, 87
- plot,report_dc,ANY-method, 88
- plot,report_df,ANY-method, 89
- plot,report_env,missing-method, 90
- plot,report_ge_weight,missing-method,
90
- plot,report_mig,ANY-method, 91
- plot,report_mig_char,missing-method,
92
- plot,report_mig_env,missing-method, 92
- plot,report_mig_interannual,missing-method,
93
- plot,report_mig_mult,missing-method,
94
- plot,report_sample_char,missing-method,
95
- plot,report_sea_age,missing-method, 95
- plot,report_silver_eel,missing-method,
96
- plot,report_species,missing-method, 97
- plot.report_annual
(plot,report_annual,missing-method),
87
- plot.report_dc
(plot,report_dc,ANY-method), 88
- plot.report_df
(plot,report_df,ANY-method), 89
- plot.report_env
(plot,report_env,missing-method),
90
- plot.report_ge_weight
(plot,report_ge_weight,missing-method),
90
- plot.report_mig
(plot,report_mig,ANY-method),
91
- plot.report_mig_char
(plot,report_mig_char,missing-method),
92
- plot.report_mig_env
(plot,report_mig_env,missing-method),
92
- plot.report_mig_interannual
(plot,report_mig_interannual,missing-method),
93

- plot.report_mig_mult
 - (plot,report_mig_mult,missing-method), 94
- plot.report_sample_char
 - (plot,report_sample_char,missing-method), 95
- plot.report_sea_age
 - (plot,report_sea_age,missing-method), 95
- plot.report_silver_eel
 - (plot,report_silver_eel,missing-method), 96
- plot.reportreport_species
 - (plot,report_species,missing-method), 97
- print,report_dc-method, 97
- print,report_df-method, 98
- print,report_mig-method, 98
- print,report_mig_mult-method, 99
- print,report_sample_char-method, 99
- print,report_sea_age-method, 100
- print,report_silver_eel-method, 100
- print.report_dc
 - (print,report_dc-method), 97
- print.report_df
 - (print,report_df-method), 98
- print.report_mig
 - (print,report_mig-method), 98
- print.report_mig_mult
 - (print,report_mig_mult-method), 99
- print.report_sample_char
 - (print,report_sample_char-method), 99
- print.report_sea_age
 - (print,report_sea_age-method), 100
- print.report_silver_eel
 - (print,report_silver_eel-method), 100
- progress_bar, 101
- quitte, 102
- r_ann, 141
- r_ann_adour, 142
- r_dc, 142
- r_df, 143
- r_env, 144
- r_gew, 144
- r_mig, 145, 146, 147, 152
- r_mig_char, 146
- r_mig_dc, 146
- r_mig_df, 147
- r_mig_env, 147
- r_mig_interannual, 148
- r_mig_interannual_vichy, 148
- r_mig_mult, 149, 150, 151
- r_mig_mult_dc, 150
- r_mig_mult_df, 151
- r_mig_mult_ope, 151
- r_mig_ope, 152
- r_sample_char, 152
- r_seaa, 153
- r_silver, 154
- ref_checkbox-class, 17, 102
- ref_choice-class, 103, 123
- ref_coe-class, 19, 50, 64, 104, 164
- ref_dc-class, 20, 47, 48, 50, 52, 54, 56–58, 104, 121, 123, 127, 134, 136, 138, 140
- ref_df-class, 20, 40, 49, 105
- ref_env-class, 21, 106, 118
- ref_horodate-class, 41, 52, 56–58, 106, 118, 123, 134, 138, 150
- ref_list-class, 22, 38, 42, 50
- ref_par-class, 22, 32, 43, 52, 56–58, 107, 123, 134, 136, 138, 146, 153
- ref_parqual-class, 23, 31, 33, 107, 123
- ref_parquan-class, 24, 34, 108, 123, 155
- ref_period-class, 84, 108
- ref_stage-class, 25, 35, 43, 47, 52, 54, 56–58, 109, 121, 123, 127, 134, 136, 138
- ref_taxa-class, 25, 36, 38, 47, 52, 54, 56–58, 109, 121, 123, 127, 134, 136, 138
- ref_textbox-class, 26, 45, 110
- ref_timestep, 111, 112
- ref_timestep-class, 71, 110
- ref_timestep_daily, 111
- ref_timestep_daily-class, 45, 111, 121
- ref_timestepChar-class, 111
- ref_year-class, 46, 47, 50, 54, 112, 127
- report_annual (report_annual-class), 113
- report_annual-class, 7, 8, 47, 61, 88, 113, 127, 142, 168

- report_dc (report_dc-class), 115
- report_dc-class, 61, 62, 67, 88, 115, 142, 147, 150
- report_df (report_df-class), 116
- report_df-class, 62, 67, 89, 116, 143, 147, 151
- report_env (report_env-class), 118
- report_env-class, 49, 53, 63, 90, 118, 126, 144, 147
- report_ge_weight
 - (report_ge_weight-class), 119
- report_ge_weight-class, 27, 50, 63, 86, 90, 119, 144, 166, 167
- report_mig, 73, 82, 167
- report_mig (report_mig-class), 121
- report_mig-class, 28, 51, 55, 56, 58, 64, 74, 121, 127, 146, 147, 152
- report_mig_char
 - (report_mig_char-class), 123
- report_mig_char-class, 52, 65, 123, 146, 169
- report_mig_env, 93
- report_mig_env (report_mig_env-class), 125
- report_mig_env-class, 11, 29, 65, 118, 125
- report_mig_interannual
 - (report_mig_interannual-class), 127
- report_mig_interannual-class, 54, 66, 88, 127, 148, 164, 167
- report_mig_mult
 - (report_mig_mult-class), 131
- report_mig_mult-class, 11, 13, 29, 55, 67, 74, 76, 118, 121, 126, 131, 147, 150, 151
- report_ope (report_ope-class), 133
- report_ope-class, 67, 68, 133, 151, 152
- report_sample_char
 - (report_sample_char-class), 133
- report_sample_char-class, 56, 68, 123, 133, 152
- report_sea_age (report_sea_age-class), 136
- report_sea_age-class, 14, 15, 52, 57, 69, 96, 136, 153, 162, 165, 168
- report_silver_eel
 - (report_silver_eel-class), 138
- report_silver_eel-class, 15, 58, 69, 96, 138, 154
- report_species (report_species-class), 140
- report_species-class, 59, 97, 140
- setasqualitative, 154
- setasqualitative, report_mig_char-method, 155
- split_per_day, 155
- stacomi, 156
- stacomiR-package, 7
- summary, report_dc-method, 157
- summary, report_df-method, 158
- summary, report_mig-method, 159
- summary, report_mig_char-method, 159
- summary, report_mig_interannual-method, 160
- summary, report_mig_mult-method, 161
- summary, report_sample_char-method, 161
- summary, report_sea_age-method, 162
- summary, report_silver_eel-method, 162
- summary, report_species-method, 163
- summary.report_dc
 - (summary, report_dc-method), 157
- summary.report_df
 - (summary, report_df-method), 158
- summary.report_mig
 - (summary, report_mig-method), 159
- summary.report_mig_char
 - (summary, report_mig_char-method), 159
- summary.report_mig_env
 - (connect, report_mig_env-method), 65
- summary.report_mig_interannual
 - (summary, report_mig_interannual-method), 160
- summary.report_mig_mult
 - (summary, report_mig_mult-method), 161
- summary.report_sample_char
 - (summary, report_sample_char-method), 161
- summary.report_sea_age
 - (summary, report_sea_age-method), 162
- summary.report_silver_eel
 - (summary, report_silver_eel-method),

162
summary.report_species
 (summary,report_species-method),
 163
supprime, 163
supprime,ref_coe-method, 164
supprime,report_mig_interannual-method,
 164
supprime,report_sea_age-method, 165
supprime.report_mig_interannual
 (supprime,report_mig_interannual-method),
 164
supprime.report_sea_age
 (supprime,report_sea_age-method),
 165

vector_to_listsql, 165

write_database, 166
write_database,report_ge_weight-method,
 166
write_database,report_mig-method, 127,
 167
write_database,report_sea_age-method,
 168
write_database.report_ge_weight
 (write_database,report_ge_weight-method),
 166
write_database.report_mig
 (write_database,report_mig-method),
 167
write_database.report_sea_age
 (write_database,report_sea_age-method),
 168

xtable,report_annual-method, 168
xtable,report_mig_char-method, 169
xtable.report_annual
 (xtable,report_annual-method),
 168
xtable.report_mig_char
 (xtable,report_mig_char-method),
 169