

# Package ‘yhat’

February 20, 2015

**Type** Package

**Title** Interpreting Regression Effects

**Version** 2.0-0

**Date** 2013-09-10

**Author** Kim Nimon <kim.nimon@gmail.com>, Fred Oswald, and J. Kyle Roberts.

**Maintainer** Kim Nimon <kim.nimon@gmail.com>

**Depends** R (>= 2.7.0)

**Imports** yacca, miscTools, plotrix, boot

**Suggests** MBESS

**Description** The purpose of this package is to provide methods to interpret multiple linear regression and canonical correlation results including beta weights, structure coefficients, validity coefficients, product measures, relative weights, all-possible-subsets regression, dominance analysis, commonality analysis, and adjusted effect sizes.

**License** GPL (>= 2)

**URL** <http://www.r-project.org>

**LazyLoad** yes

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2013-09-16 00:43:36

## R topics documented:

yhat-package . . . . .	2
aps . . . . .	3
boot.yhat . . . . .	4
booteval.yhat . . . . .	5
calc.yhat . . . . .	7
canonCommonality . . . . .	9
canonVariate . . . . .	10
ci.yhat . . . . .	11

combCI . . . . .	12
commonality . . . . .	13
commonalityCoefficients . . . . .	14
dombin . . . . .	15
dominance . . . . .	17
effect.size . . . . .	18
genList . . . . .	19
odd . . . . .	20
plotCI.yhat . . . . .	20
regr . . . . .	22
rlw . . . . .	23
setBits . . . . .	24

<b>Index</b>	<b>25</b>
--------------	-----------

---

yhat-package	<i>Interpreting Regression Effects</i>
--------------	--

---

## Description

The purpose of this package is to provide methods to interpret multiple linear regression and canonical correlation results including beta weights, structure coefficients, validity coefficients, product measures, relative weights, all-possible-subsets regression, dominance analysis, commonality analysis, and adjusted effect sizes.

## Details

Package:	yhat
Type:	Package
Version:	2.0-0
Date:	2013-09-10
License:	GPL (>= 2)
LazyLoad:	yes

## Author(s)

Kim Nimon <kim.nimon@gmail.com>, Fred L. Oswald, J. Kyle Roberts

## References

- Beaton, A. E. (1973) *Commonality*. (ERIC Document Reproduction Service No. ED111829)
- Butts, C. T. (2009). *yacca: Yet Another Canonical Correlation Analysis Package*. R package version 1.1.

Mood, A. M. (1969) Macro-analysis of the American educational system. *Operations Research*, **17**, 770-784.

Nimon, K., Lewis, M., Kane, R. & Haynes, R. M. (2008) An R package to compute commonality coefficients in the multiple regression case: An introduction to the package and a practical example. *Behavior Research Methods*, **40**(2), 457-466.

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods*, *16*, 650-674.

### See Also

[regrCommonalityCoefficients](#) [canonCommonality](#) [calc.yhat](#) [boot.yhat](#) [booteval.yhat](#) [plotCI.yhat](#)  
[apsCommonality](#) [dominance](#) [dombin](#) [rlw](#)

---

 aps

*All Possible Subsets Regression*


---

### Description

The function runs all possible subsets regression and returns data needed to run commonality and dominance analysis.

### Usage

```
aps(dataMatrix, dv, ivlist)
```

### Arguments

<code>dataMatrix</code>	Dataset containing the dependent and independent variables
<code>dv</code>	The dependent variable named in the dataset
<code>ivlist</code>	List of independent variables named in the dataset

### Details

Function returns all possible subset information that is used by [commonality](#) and [dominance](#). If data are missing, non-missing data are eliminated based on listwise deletion for full model.

### Value

<code>ivID</code>	Matrix containing independent variable IDs.
<code>PredBitMap</code>	All possible subsets predictor bit map.
<code>apsBitMap</code>	Index into all possible subsets predictor bit map.
<code>APSMatrix</code>	Table containing the number of predictors and Multiple R <sup>2</sup> for each possible set of predictors.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods*, 16, 650-674.

**See Also**

[calc.yhat](#) [commonality](#) [dominance](#) [rlw](#)

**Examples**

```
## APS regression predicting miles per gallon based
## on vehicle weight, type of
## carbtorator, & number of engine cylinders
apsOut<-aps(mtcars,"mpg",list("wt","carb","cyl"))

## APS regression predicting paragraph comprehension based
## on thre verbal tests: general info, sentence comprehension,
## & word classification

## Use HS dataset in MBESS
require("MBESS")
data(HS.data)
## APS
apsOut<-aps(HS.data,"paragrap",list("general","sentence",
                                   "wordc"))
```

---

boot.yhat

*Bootstrap metrics produced from /codecalc.yhat*

---

**Description**

This function is input to boot to bootstrap metrics computed from calc.yhat.

**Usage**

```
boot.yhat(data, indices, lmOut,regrou0)
```

**Arguments**

data	Original dataset
indices	Vector of indices which define the bootstrap sample
lmOut	Ouput of /codelm
regrou0	Output of /codecalc.yhat

**Details**

This function is input to `boot` to bootstrap metrics computed from `calc.yhat`.

**Value**

The output of `boot.yhat` when used in conjunction with `boot` is of class `boot` and is not further described here. The output is designed to be useful as input for `booteval.yhat`

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

**See Also**

[lm](#) [calc.yhat](#) [boot](#) [booteval.yhat](#)

**Examples**

```
## Bootstrap regression results predicting paragraph
## comprehension based on three verbal tests: general info,
## sentence comprehension, & word classification

## Use HS dataset in MBESS
require ("MBESS")
data(HS.data)

## Regression
lm.out<-lm(paragrap~general+sentence+wordc,data=HS.data)

## Calculate regression metrics
regrOut<-calc.yhat(lm.out)

## Bootstrap results
require ("boot")
boot.out<-boot(HS.data,boot.yhat,100,lmOut=lm.out,regrout0=regrOut)
```

---

booteval.yhat

*Evaluate bootstrap metrics produced from /codecalc.yhat*

---

**Description**

This function evaluates the bootstrap metrics produced from `/codeboot.yhat`.

**Usage**

```
booteval.yhat(regrOut, boot.out, bty, level, prec)
```

**Arguments**

regrOut	Output from calc.yhat
boot.out	Output from boot in conjunction with boot.yhat
bty	Type of confidence interval. Only types "perc", "norm", "basic", and "bca" supported.
level	Confidence level (e.g., .95)
prec	Integer indicating number of decimal places to be used.

**Details**

This function evaluates the bootstrap metrics produced from boot.yhat.

**Value**

Confidence intervals are reported for predictor and all possible subset metrics as well as differences between appropriate predictors and all possible subset metrics. The function also output the means, standard errors, probabilities, and reproducibility metrics for the dominance comparisons. Means and standard deviations are reported for Kendall's tau correlation between sample predictor metrics and the bootstrap statistics of like metrics.

combCIpm	Upper and lower CIs for predictor metrics
lowerCIpm	Lower CIs for predictor metrics
upperCIpm	Upper CIs for predictor metrics
combCIaps	Upper and lower CIs for APS metrics
lowerCIaps	Lower CIs for APS metrics
upperCIaps	Upper CIs for APS metrics
domBoot	Dominance analysis bootstrap results
tauDS	Descriptive statistics for Kendall's tau
combCIpmDiff	Upper and lower CIs for differences between predictor metrics
lowerCIpmDiff	Lower CIs for differences between predictor metrics
upperCIpmDiff	Upper CIs for differences between predictor metrics
combCIapsDiff	Upper and lower CIs for differences between APS metrics
lowerCIapsDiff	Lower CIs for differences between APS metrics
upperCIapsDiff	Upper CIs for differences between APS metrics
combCIincDiff	Upper and lower CIs for differences between incremental validity metrics
lowerCIincDiff	Lower CIs for differences between incremental validity metrics
upperCIincDiff	Upper CIs for differences between incremental validity metrics

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

**See Also**

[lm](#) [calc.yhat](#) [boot](#) [plotCI.yhat](#)

**Examples**

```
## Bootstrap regression results predicting paragraph
## comprehension based on four verbal tests: general info,
## sentence comprehension, & word classification

## Use HS dataset in MBESS
require ("MBESS")
data(HS.data)

## Regression
lm.out<-lm(paragrap~general+sentence+wordc,data=HS.data)

## Calculate regression metrics
regrOut<-calc.yhat(lm.out)

## Bootstrap results
require ("boot")
boot.out<-boot(HS.data,boot.yhat,100,lmOut=lm.out,regrout=regrOut)

## Evaluate bootstrap results
result<-booteval.yhat(regrOut,boot.out,bty="perc")
```

---

calc.yhat

*More regression indices for lm class objects*

---

**Description**

Reports beta weights, validity coefficients, structure coefficients, product measures, commonality analysis coefficients, and dominance analysis weights for `lm` class objects.

**Usage**

```
calc.yhat(lm.out,prec=3)
```

**Arguments**

lm.out            lm class object  
prec             level of precision for rounding, defaults to 3

**Details**

Takes the lm class object and reports beta weights, validity coefficients, structure coefficients, product measures, commonality analysis coefficients, and dominance analysis weights.

**Value**

PredictorMetrics  
                  Predictor metrics associated with lm class object  
OrderedPredictorMetrics  
                  Rank order of predictor metrics  
PairedDominanceMetrics  
                  Dominance analysis for predictor pairs  
APSRRelatedMetrics  
                  APS metrics associated with lm class object

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

**Examples**

```
## Predict paragraph comprehension based on three verbal
## tests: general info, sentence comprehension, & word
## classification

## Use HS dataset in MBESS
require("MBESS")
data(HS.data)

## Regression
lm.out<-lm(paragrap~general+sentence+wordc,data=HS.data)

## Regression Indices
regr.out<-calc.yhat(lm.out)
```



canonCommonality

*Commonality Coefficients for Canonical Correlation*

### Description

The `canonCommonality` function produces commonality data for both canonical variables sets. Variables in a given canonical set are used to partition the variance of the canonical variates produced from the *other* canonical set and vica versa. Commonality data is supplied for the number of canonical functions requested.

### Usage

```
canonCommonality(A, B, nofns = 1)
```

### Arguments

A	Matrix containing variable set A
B	Matrix containing variable set B
nofns	Number of canonical functions to analyze

### Details

The function `canonCommonality` has two required arguments and one optional argument. The first two arguments contain the two variable sets. The third argument is optional and defines the number of canonical functions to analyze. Unless specified, the number of canonical functions defaults to 1.

The function `canonCommonality` calls a function `canonVariate` to decompose canonical variates twice: the first time for the variable set identified in the first argument, the second time for the variable set identified in the second argument.

### Value

The function `canonCommonality` returns commonality data for both canonical variable sets. For the number of functions requested, both canonical variates are analyzed. For each canonical variate analyzed, two tables are returned. The first table lists the commonality coefficients and their contribution to the total effect, while the second table lists the unique and common effects for each regressor. The function returns the resulting output ordering the output according to the function's parameters.

### Author(s)

Kim Nimon <kim.nimon@gmail.com>

### References

Nimon, K., Henson, R., & Gates, M. (2010). Revisiting interpretation of canonical correlation analysis: A tutorial and demonstration of canonical commonality analysis. *Multivariate Behavioral Research*, 45,702-724.

**See Also**

[canonVariate](#)

**Examples**

```
## Example parallels the R builtin cancel and the
## yacca cca example
data(LifeCycleSavings)
pop <- LifeCycleSavings[, 2:3]
oec <- LifeCycleSavings[, -(2:3)]
## Perform Commonality Coefficient Analysis
canonCommonData<-canonCommonality(pop,oec,1)

## Use HS dataset in MBESS
require("MBESS")
data(HS.data)
attach(HS.data)
## Create canonical variable sets
MATH_REASON<-HS.data[,c("deduct","problemr")]
MATH_FUND<-HS.data[,c("numeric","arithmet","addition")]
## Perform Commonality Coefficient Analysis
canonCommonData<-canonCommonality(MATH_FUND,MATH_REASON,1)
detach(HS.data)
```

---

canonVariate

*Canonical Commonality Analysis*

---

**Description**

The `canonCommonality` function produces commonality data for a given canonical variable set. Using the variables in a given canonical set to partition the variance of the canonical variates produced from the *other* canonical set, commonality data is supplied for the number of canonical functions requested.

**Usage**

```
canonVariate(A, B, nofns)
```

**Arguments**

A	Matrix containing variable set A
B	Matrix containing variable set B
nofns	Number of canonical functions to analyze

## Details

For each canonical function, `canonVariate`: (a) creates a dataset that combines the matrix of variables for a given canonical set and the canonicate variate for the *other* canonical set; (b) calls `commonalityCoefficients`, passing the dataset, the name of the canonical variate, and the names of the variates in a given canonical set; (c) saves resultant output.

## Value

The function `canonVariate` returns commonality data for the canonical variable set input. For the number of functions requested, two tables are returned. The first table lists the commonality coefficients for each canonical function together with its contribution to the total effect, while the second table lists the unique and common effects for each regressor.

## Note

This function is internal to `canonCommonality`, called during runtime and passed the appropriate parameters. This is not an end-user function.

## Author(s)

Kim Nimon <kim.nimon@gmail.com>

## References

Nimon, K., Henson, R., & Gates, M. (2010). Revisiting interpretation of canonical correlation analysis: A tutorial and demonstration of canonical commonality analysis. *Multivariate Behavioral Research*, 45,702-724.

## See Also

[canonCommonality](#)

---

ci.yhat

*Compute CI*

---

## Description

This function retrieves the proper elements from `boot.ci`.

## Usage

```
ci.yhat(bty, CI)
```

## Arguments

bty	Type of CI
CI	CI

**Details**

This function retrieves the proper elements from boot.ci.

**Value**

This function returns the proper elements from boot.ci.

**Note**

This function is internal to the yhat package and not intended to be an end-user function.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

---

combCI

*Combine upper and lower confidence intervals*

---

**Description**

This function combines upper and lower confidence intervals along with sample statistics and optionally stars intervals that do not contain 0.

**Usage**

```
combCI(lowerCI, upperCI, est, star=FALSE )
```

**Arguments**

lowerCI	Lower CI
upperCI	Upper CI
est	Estimate
star	Boolean to indicate whether CIs that do not contain zero should be starred.

**Details**

This function evaluates the bootstrap metrics produced from /codeboot.yhat.

**Value**

Returns estimate with confidence interval in ( ). Optionally, confidence interval not containing 0 is starred.

**Note**

This function is internal to the yhat package and not intended to be an end-user function.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

---

commonality

*Commonality Analysis*

---

**Description**

This function conducts commonality analyses based on an all-possible-subsets regression.

**Usage**

```
commonality(apsOut)
```

**Arguments**

apsOut            Output from /codeaps

**Details**

This function conducts commonality analyses based on an all-possible-subsets regression.

**Value**

The function returns a matrix containing commonality coefficients and percentage of regression effect for each each possible set of predictors.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., Lewis, M., Kane, R. & Haynes, R. M. (2008) An R package to compute commonality coefficients in the multiple regression case: An introduction to the package and a practical example. *Behavior Research Methods, 40*, 457-466.

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

**See Also**

[aps calc.yhat dominance rlw](#)

**Examples**

```
## Predict paragraph comprehension based on three verbal
## tests: general info, sentence comprehension, & word
## classification

## Use HS dataset in MBESS
require("MBESS")
data(HS.data)

## All-possible-subsets regression
apsOut=aps(HS.data,"paragrap",list("general", "sentence", "wordc"))

## Commonality analysis
commonality(apsOut)
```

---

commonalityCoefficients

*Commonality Coefficients*

---

**Description**

Commonality Coefficients returns a list of two tables. The first table CC contains the list of commonality coefficients and the percent variance for each effect. The second CCTotByVar totals the unique and common effects for each independent variable.

**Usage**

```
commonalityCoefficients(dataMatrix, dv, ivlist, imat=FALSE)
```

**Arguments**

dataMatrix	Dataset containing the dependent and independent variables
dv	The dependent variable named in the dataset
ivlist	List of independent variables named in the dataset
imat	Echo flag, default to FALSE

**Details**

When echo flag is true, transitional matrices during commonality coefficient calculation are sent to output window. Default for this option is false. When set to true, the intermediate matrices for each commonality coefficient and regression combinations are printed in the output window.

**Value**

CC	Matrix containing commonality coefficients and percentage of variance for each effect.
CCTotalByVar	Table of unique and common effects for each independent variable.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., Lewis, M., Kane, R. & Haynes, R. M. (2008) An R package to compute commonality coefficients in the multiple regression case: An introduction to the package and a practical example. *Behavior Research Methods*, 40, 457-466.

**See Also**

[canonCommonality](#) [genList](#) [odd](#) [setBits](#)

**Examples**

```
## Predict miles per gallon based on vehicle weight, type of
## carbtorator, & number of engine cylinders
commonalityCoefficients(mtcars,"mpg",list("wt","carb","cyl"))

## Predict paragraph comprehension based on four verbal
## tests: general info, sentence comprehension, word
## classification, & word type
## Use HS dataset in MBESS
require("MBESS")
data(HS.data)
## Commonality Coefficient Analysis
commonalityCoefficients(HS.data,"paragrap",list("general",
"sentence","wordc","wordm"))
```

---

dombin

*Dominance Analysis*


---

**Description**

For each level of dominance and pairs of predictors in the full model, this function indicates whether a predictor "x1" dominates "x2", predictor "x2" dominates "x1", or that dominance cannot be established between predictors.

**Usage**

```
dombin(domOut)
```

## Arguments

domOut            Output from /codedominance

## Details

For each level of dominance and pairs of predictors in the full model, this function indicates whether a predictor "x1" dominates "x2", predictor "x2" dominates "x1", or that dominance cannot be established between predictors.

## Value

The function return a matrix that contains dominance level decisions (complete, conditional, and general) for each pair of predictors in the full model.

## Author(s)

Kim Nimon <kim.nimon@gmail.com>

## References

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

## See Also

[aps calc.yhat commonality dominance rlw](#)

## Examples

```
## Predict paragraph comprehension based on three verbal
## tests: general info, sentence comprehension, & word
## classification

## Use HS dataset in MBESS
require("MBESS")
data(HS.data)

## All-possible-subsets regression
apsOut=aps(HS.data,"paragra",list("general", "sentence", "wordc"))

## Dominance analysis
domOut=dominance(apsOut)

## Dominance analysis
dombin(domOut)
```



---

dominance	<i>Dominance Weights</i>
-----------	--------------------------

---

**Description**

Computes dominance weights including conditional and general.

**Usage**

```
dominance(apsOut)
```

**Arguments**

apsOut	Output from /codeaps
--------	----------------------

**Details**

Provides full dominance weights table that are used to compute conditional and general dominance weights as well as reports conditional and general dominance weights.

**Value**

DA	Dominance analysis table
CD	Conditional dominance weights
GD	General dominance weights

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

**See Also**

[aps calc.yhat dombin rlw](#)

**Examples**

```
## Predict paragraph comprehension based on three verbal
## tests: general info, sentence comprehension, & word
## classification

## Use HS dataset in MBESS
require("MBESS")
data(HS.data)
```

```
## All-possible-subsets regression
apsOut=aps(HS.data,"paragrap",list("general", "sentence", "wordc"))

## Dominance weights
dominance(apsOut)
```

---

effect.size

*Effect Size Computation for lm*

---

### Description

Creates adjusted effect sizes for linear regression.

### Usage

```
effect.size(lm.out)
```

### Arguments

lm.out            Output from lm class object

### Details

The function `effect.size` produces a family of effect size corrections for the R-squared metric produced from an `lm` class object. Suggestions for recommended correction are supplied, based on Yin and Fan (2001).

### Value

Returns adjusted R-squared metric.

### Author(s)

J. Kyle Roberts <kylar@smu.edu>

### References

Yin, P., & Fan. X. (2001) Estimated  $R^2$  shrinkage in multiple regression: A comparison of different analytical methods. *The Journal of Experimental Education*, 69, 203-224.

### See Also

[regr.yhat](#)

**Examples**

```
require ("MBESS")
data(HS.data)
attach(HS.data)
lm.out<-lm(deduct~addition*arithmet)
effect.size(lm.out)
detach(HS.data)
```

---

**genList***Generate List R<sup>2</sup> Values*

---

**Description**

Use the bitmap matrix to generate the list of  $R^2$  values needed.

**Usage**

```
genList(ivlist, value)
```

**Arguments**

ivlist	List of independent variables in dataset
value	Number of variables

**Details**

Returns the number of  $R^2$  values that will be calculated in output tables.

**Value**

Returns newlist from generate list function call.

**Note**

This function is internal to [commonalityCoefficients](#), called during runtime and passed the appropriate parameters. This is not an end-user function.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

odd

*isOdd Function*

---

**Description**

Function receives value and returns true if value is odd.

**Usage**

```
odd(val)
```

**Arguments**

val                    Value to check

**Details**

Determines value of parameter in argument.

**Value**

Returns true when value checked is odd. Otherwise, function returns a value false.

**Note**

This function is internal to [commonalityCoefficients](#), called during runtime and passed the appropriate parameters. This is not an end-user function.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

---

plotCI.yhat

*Plot CIs from yhat*

---

**Description**

This function plots CIs that have been produced from /codebooteval.yhat.

**Usage**

```
plotCI.yhat(sampStat, upperCI, lowerCI, pid=1:ncol(sampStat), nr=2, nc=2)
```

**Arguments**

sampStat	Set of sample statistics
upperCI	Set of upper CIs
lowerCI	Set of lower CIs
pid	Which set of Metrics to plot (default to all)
nr	Number of rows (default = 2)
nc	Number of columns(default = 2)

**Details**

This function plots CIs that have been produced from /codebooteval.yhat.

**Value**

This returns a plot of CIs that have been produced from /codebooteval.yhat.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

**See Also**

[lm](#) [calc.yhat](#) [boot](#) [booteval.yhat](#)

**Examples**

```
## Bootstrap regression results predicting paragraph
## comprehension based on three verbal tests: general info,
## sentence comprehension, & word classification

## Use HS dataset in MBESS
require ("MBESS")
data(HS.data)

## Regression
lm.out<-lm(paragrap~general+sentence+wordc,data=HS.data)

## Calculate regression metrics
regrOut<-calc.yhat(lm.out)

## Bootstrap results
require ("boot")
boot.out<-boot(HS.data,boot.yhat,100,lmOut=lm.out,regrout=regrOut)
```

```

## Evaluate bootstrap results
result<-booteval.yhat(regrOut,boot.out,bty="perc")

## Plot results
## plotCI.yhat(regrOut$PredictorMetrics[-nrow(regrOut$PredictorMetrics),],
## result$upperCIpm,result$lowerCIpm, pid=which(colnames(regrOut$PredictorMetrics)
## %in% c("Beta","rs","CD:0","CD:1","CD:2","GenDom","Pratt","RLW") == TRUE),nr=3,nc=3)

```

regr

*Regression effect reporting for lm class objects***Description**

The regr reports beta weights, standardized beta weights, structure coefficients, adjusted effect sizes, and commonality coefficients for lm class objects.

**Usage**

```
regr(lm.out)
```

**Arguments**

lm.out            lm class object

**Details**

The function regr takes the lm class object and reports beta weights, standardized beta weights, structure coefficients, adjusted effect sizes, and commonality coefficients for lm class objects.

**Value**

LM_Output	The summary of the output from the lm class object
Beta_Weights	Beta weights for the regression effects
Structure_Coefficients	Structure coefficients for the regression effects
Commonality_Data	Commonality coefficients for the regression effects. The output only produces a parsed version of CCdata
Effect_Size	Adjusted effect size computations based on R <sup>2</sup> adjustments

**Author(s)**

J. Kyle Roberts <kylerr@smu.edu>, Kim Nimon <kim.nimon@gmail.com>

**References**

Kraha, A., Turner, H., Nimon, K., Zientek, L., Henson, R. (2012). Tools to support multiple regression in the face of multicollinearity. *Frontiers in Psychology*, 3(102), 1-13.

**See Also**

[commonalityCoefficients](#), [effect.size](#)

**Examples**

```
require("MBESS")
data(HS.data)
attach(HS.data)
lm.out<-lm(deduct~addition*arithmet)
regr(lm.out)
detach(HS.data)
```

---

rlw

*Relative Weights*

---

**Description**

The function computes relative weights.

**Usage**

```
rlw(dataMatrix, dv, ivlist)
```

**Arguments**

dataMatrix	Dataset containing the dependent and independent variables
dv	The dependent variable named in the dataset
ivlist	List of independent variables named in the dataset

**Details**

The function computes relative weights.

**Value**

The function returns relative weights for each predictor.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>

**References**

Nimon, K., & Oswald, F. L. (2013). Understanding the results of multiple linear regression: Beyond standardized regression coefficients. *Organizational Research Methods, 16*, 650-674.

**See Also**

[aps.calc.yhat.commonality.dominance](#)

**Examples**

```
## Relative weights from regression model predicting paragraph
## comprehension based on three verbal tests: general info,
## sentence comprehension, & word classification

## Use HS dataset in MBESS
require("MBESS")
data(HS.data)

## Relative Weights
rwlOut<-rlw(HS.data,"paragrap",c("general","sentence","wordc"))
```

---

setBits

*Decimal to Binary*

---

**Description**

Creates the binary representation of n and stores it in the nth column of the matrix.

**Usage**

```
setBits(col, effectBitMap)
```

**Arguments**

col                    Column of matrix to represent in binary image  
effectBitMap        Matrix of mean combinations in binary form

**Details**

Creates the binary representation of col and stores it in its associated column.

**Value**

Returns matrix effectBitMap of mean combinations in binary form.

**Note**

This function is internal to [commonalityCoefficients](#), called during runtime and passed the appropriate parameters. This is not an end-user function.

**Author(s)**

Kim Nimon <kim.nimon@gmail.com>



# Index

## \*Topic **models**

aps, 3  
boot.yhat, 4  
booteval.yhat, 5  
commonality, 13  
commonalityCoefficients, 14  
dombin, 15  
dominance, 17  
plotCI.yhat, 20  
rlw, 23

## \*Topic **multivariate**

canonCommonality, 9  
canonVariate, 10

## \*Topic **package**

yhat-package, 2

## \*Topic **regression**

aps, 3  
boot.yhat, 4  
booteval.yhat, 5  
commonality, 13  
commonalityCoefficients, 14  
dombin, 15  
dominance, 17  
plotCI.yhat, 20  
rlw, 23

dombin, 3, 15, 17  
dominance, 3, 4, 14, 16, 17, 24

effect.size, 18, 23

genList, 15, 19

lm, 5, 7, 21

odd, 15, 20

plotCI.yhat, 3, 7, 20

regr, 3, 18, 22

rlw, 3, 4, 14, 16, 17, 23

setBits, 15, 24

yhat, 18

yhat (yhat-package), 2

yhat-package, 2

aps, 3, 3, 14, 16, 17, 24

boot, 5, 7, 21

boot.yhat, 3, 4

booteval.yhat, 3, 5, 5, 21

calc.yhat, 3–5, 7, 7, 14, 16, 17, 21, 24

canonCommonality, 3, 9, 11, 15

canonVariate, 10, 10

ci.yhat, 11

combCI, 12

commonality, 3, 4, 13, 16, 24

commonalityCoefficients, 3, 14, 19, 20, 23,

24