

# Package ‘ENMTools’

August 28, 2020

**Type** Package

**Title** Analysis of Niche Evolution using Niche and Distribution Models

**Version** 1.0.1

**Date** 2020-08-25

**Encoding** UTF-8

**Maintainer** Dan Warren <dan.l.warren@gmail.com>

**Description** Description: Tools for constructing niche models and analyzing patterns of niche evolution. Acts as an interface for many popular modeling algorithms, and allows users to conduct Monte Carlo tests to address basic questions in evolutionary ecology and biogeography. Warren, D.L., R.E. Glor, and M. Turelli (2008) <doi:10.1111/j.1558-5646.2008.00482.x> Glor, R.E., and D.L. Warren (2011) <doi:10.1111/j.1558-5646.2010.01177.x> Warren, D.L., R.E. Glor, and M. Turelli (2010) <doi:10.1111/j.1600-0587.2009.06142.x> Cardillo, M., and D.L. Warren (2016) <doi:10.1111/geb.12455> D.L. Warren, L.J. Beaumont, R. Dinnage, and J.B. Baumgartner (2019) <doi:10.1111/ecog.03900>.

**License** GPL-2

**LazyData** TRUE

**RoxygenNote** 7.1.0

**Imports** rgeos, knitr, ggplot2, gridExtra, lhs, magrittr, ENMeval, sp, spatstat, ggpubr, rgdal, forcats

**Depends** raster, dismo

**Suggests** testthat, hypervolume, leaflet, mgcv, ecospat, randomForest, ranger, caret, CalibratR, ape, ResourceSelection, ppmlasso, fields, reshape2, vip, pdp, fastshap, viridis, progress

**NeedsCompilation** no

**Author** Dan Warren [aut, cre] (<<https://orcid.org/0000-0002-8747-2451>>),  
Nick Matzke [ctb],  
Marcel Cardillo [ctb],  
John Baumgartner [ctb],  
Linda Beaumont [ctb],  
Nicholas Huron [ctb],  
Marianna Simoes [ctb],  
Teresa Iglesias [ctb],  
Russell Dinnage [aut] (<<https://orcid.org/0000-0003-0846-2819>>)

**Repository** CRAN

**Date/Publication** 2020-08-28 07:50:19 UTC

## R topics documented:

add.env . . . . .	3
background.points.buffer . . . . .	4
background.raster.buffer . . . . .	4
background.shape.buffer . . . . .	5
background.test . . . . .	6
calc.B1 . . . . .	7
calc.B2 . . . . .	8
check.bg . . . . .	9
check.clade . . . . .	9
check.species . . . . .	10
clamp.env . . . . .	11
combine.species . . . . .	11
drop.species . . . . .	12
enmtools.aoc . . . . .	13
enmtools.bc . . . . .	14
enmtools.calibrate . . . . .	15
enmtools.clade . . . . .	16
enmtools.dm . . . . .	17
enmtools.ecospat.bg . . . . .	18
enmtools.ecospat.id . . . . .	20
enmtools.gam . . . . .	21
enmtools.glm . . . . .	23
enmtools.hypervolume . . . . .	24
enmtools.maxent . . . . .	26
enmtools.ppmlasso . . . . .	27
enmtools.rf . . . . .	29
enmtools.rf.ranger . . . . .	30
enmtools.species . . . . .	32
enmtools.vip . . . . .	33
env.breadth . . . . .	34
env.evaluate . . . . .	35
env.overlap . . . . .	36
euro.worldclim . . . . .	37
geog.range.overlap . . . . .	38
hypervolume.overlap . . . . .	38
iberolacerta.clade . . . . .	39
identity.test . . . . .	40
install.extras . . . . .	41
interactive.plot . . . . .	42
interactive.plot.enmtools.model . . . . .	43
interactive.plot.enmtools.species . . . . .	44
marginal.plots . . . . .	44

moses.list . . . . .	45
multistack.pca . . . . .	46
node.overlap . . . . .	47
point.overlap . . . . .	47
rangebreak.blob . . . . .	48
rangebreak.linear . . . . .	50
rangebreak.ribbon . . . . .	51
raster.breadth . . . . .	53
raster.cor . . . . .	54
raster.cor.matrix . . . . .	54
raster.cor.plot . . . . .	55
raster.overlap . . . . .	56
raster.pca . . . . .	56
raster.resid . . . . .	57
raster.standardize . . . . .	58
sim.points . . . . .	58
species.from.file . . . . .	59
threespace.plot . . . . .	60
trimdups.by.raster . . . . .	60
visualize.enm . . . . .	61
visualize.overlap . . . . .	62
<b>Index</b>	<b>64</b>

---

add.env	<i>Takes an enmtools.species object and a set of environment layers, and adds the environmental predictor values to the occurrence data. Typically not called by the user directly. Code modified from Elith and Hijmans SDM with R tutorial</i>
---------	--

---

## Description

Takes an enmtools.species object and a set of environment layers, and adds the environmental predictor values to the occurrence data. Typically not called by the user directly. Code modified from Elith and Hijmans SDM with R tutorial

## Usage

```
add.env(species, env, verbose = TRUE)
```

## Arguments

species	An enmtools.species or enmtools.clade object
env	A raster stack of environmental variables
verbose	Controls printing of progress messages

**Value**

An `enmtools.species` object with environmental data attached to it.

---

`background.points.buffer`

*Takes a set of points, a buffer radius, a sample size, and a mask and returns randomly sampled points from within that buffer radius. Code modified from Elith and Hijmans SDM with R tutorial*

---

**Description**

Takes a set of points, a buffer radius, a sample size, and a mask and returns randomly sampled points from within that buffer radius. Code modified from Elith and Hijmans SDM with R tutorial

**Usage**

```
background.points.buffer(points, radius, n, mask)
```

**Arguments**

<code>points</code>	A two column data frame with X and Y coordinates
<code>radius</code>	Radius for circular buffers to draw around points, in meters.
<code>n</code>	Sample size for number of background points to return
<code>mask</code>	A raster to use as a mask for drawing points

**Value**

A data frame of points drawn at random from circular buffers around the occurrence points.

---

`background.raster.buffer`

*Takes a set of points, a buffer radius, and a mask and returns a raster based on that buffer radius. Code modified from Elith and Hijmans SDM with R tutorial*

---

**Description**

Takes a set of points, a buffer radius, and a mask and returns a raster based on that buffer radius. Code modified from Elith and Hijmans SDM with R tutorial

**Usage**

```
background.raster.buffer(points, radius, mask)
```

**Arguments**

points	A two column data frame with X and Y coordinates
radius	Radius for circular buffers to draw around points, in meters.
mask	A raster to use as a mask

**Value**

A raster object with values of 1 in every grid cell falling within the buffer.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
background.raster.buffer(iberolacerta.clade$species$cyreni$presence.points, 100000, euro.worldclim)
```

---

```
background.shape.buffer
```

*Takes a set of points and a buffer radius, and returns a polygon. Code modified from Elith and Hijmans SDM with R tutorial*

---

**Description**

Takes a set of points and a buffer radius, and returns a polygon. Code modified from Elith and Hijmans SDM with R tutorial

**Usage**

```
background.shape.buffer(points, radius)
```

**Arguments**

points	A two column data frame with X and Y coordinates
radius	Radius for circular buffers to draw around points, in meters.

**Value**

A polygon shapefile.

---

background.test	<i>background.test</i> Conduct a background test (also called a similarity test), as described in Warren et al. 2008. This test can either be run as an asymmetric test (species.1 vs background of species.2) or as a symmetric test (background of species.1 vs background of species.2). For GLM, Bioclim, and Domain models the replicates will be constructed from the background points supplied for each species. For Maxent, the replicates will be constructed from the range rasters stored in the <i>enmtools.species</i> objects.
-----------------	---

---

## Description

background.test Conduct a background test (also called a similarity test), as described in Warren et al. 2008. This test can either be run as an asymmetric test (species.1 vs background of species.2) or as a symmetric test (background of species.1 vs background of species.2). For GLM, Bioclim, and Domain models the replicates will be constructed from the background points supplied for each species. For Maxent, the replicates will be constructed from the range rasters stored in the *enmtools.species* objects.

## Usage

```
background.test(
  species.1,
  species.2,
  env,
  type,
  f = NULL,
  nreps = 99,
  test.type = "asymmetric",
  nback = 1000,
  bg.source = "default",
  low.memory = FALSE,
  rep.dir = NA,
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

## Arguments

species.1	An <i>enmtools.species</i> object from which presence points (asymmetric) or background (symmetric) will be sampled.
species.2	An <i>enmtools.species</i> object from which background will be sampled.
env	A <i>RasterLayer</i> or <i>RasterStack</i> object containing environmental data
type	The type of model to construct, currently accepts "glm", "mx", "bc", "gam", or "dm"

f	A function to use for model fitting. Only required for GLM models at the moment.
nreps	Number of replicates to perform
test.type	Controls whether the background test will be "symmetric" or "asymmetric"
nback	Number of background points for models
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
low.memory	When set to TRUE, replicate models are written to disc instead of being stored in the output object. Replicate models stored in the output object contain paths to the replicate models on disk instead of the rasters themselves.
rep.dir	Directory for storing replicate models when low.memory is set to TRUE. If not specified, the working directory will be used.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	Controls whether empirical and replicate models should be clamped to the environment space used for training.
...	Additional arguments to be passed to model fitting functions.

### Value

results A list containing replicates, models for the empirical data, and summary statistics and plots.

### Examples

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
monticola <- iberolacerta.clade$species$monticola
cyreni$range <- background.raster.buffer(cyreni$presence.points, 100000, euro.worldclim)
monticola$range <- background.raster.buffer(monticola$presence.points, 100000, euro.worldclim)
background.test(cyreni, monticola, env = euro.worldclim, type = "glm",
f = pres ~ bio1 + bio12, nreps = 10)
```

---

calc.B1	<i>calc.B1, Calculates standardized version of Levins (1968) B1 measure of niche breadth given a vector of suitabilities</i>
---------	--

---

### Description

calc.B1, Calculates standardized version of Levins (1968) B1 measure of niche breadth given a vector of suitabilities

**Usage**

```
calc.B1(x)
```

**Arguments**

x                      A numeric vector

**Value**

B1 A calculation of Levins (1968) B1 metric

**Examples**

```
calc.B1(c(1, .001, .001))
```

---

calc.B2	<i>calc.B2, Calculates standardized version of Levins (1968) B2 measure of niche breadth given a vector of suitabilities</i>
---------	--

---

**Description**

calc.B2, Calculates standardized version of Levins (1968) B2 measure of niche breadth given a vector of suitabilities

**Usage**

```
calc.B2(x)
```

**Arguments**

x                      A numeric vector

**Value**

B2 A calculation of Levins (1968) B2 metric

**Examples**

```
calc.B2(c(1, .001, .001))
```

---

check.bg	<i>Takes an emtools.species object and adds background points if they're missing. Looks for range raster first, then goes for environmental layers.</i>
----------	---

---

### Description

Takes an emtools.species object and adds background points if they're missing. Looks for range raster first, then goes for environmental layers.

### Usage

```
check.bg(
  species,
  env = NA,
  nback = 1000,
  bg.source = "default",
  verbose = FALSE
)
```

### Arguments

species	An emtools.species object
env	A raster or raster stack of environmental data.
nback	Number of background points to generate, if any
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.

### Value

An emtools.species object with background points.

---

check.clade	<i>Checking for complians of an emtools.clade object</i>
-------------	--

---

### Description

Checking for complians of an emtools.clade object

### Usage

```
check.clade(this.clade)
```

**Arguments**

`this.clade`      An `enmttools.clade` object

**Value**

An `enmttools.clade` object with appropriate formatting.

**Examples**

```
data(iberolacerta.clade)
check.clade(iberolacerta.clade)
```

---

<code>check.species</code>	<i>Checking compliance for an object of class <code>enmttools.species</code>.</i>
----------------------------	---

---

**Description**

Checking compliance for an object of class `enmttools.species`.

**Usage**

```
check.species(this.species)
```

**Arguments**

`this.species`      An `enmttools.species` object to be checked.

**Value**

An `enmttools.species` object with appropriate formatting.

**Examples**

```
data(iberolacerta.clade)
check.species(iberolacerta.clade$species$monticola)
```

---

clamp.env	<i>Takes an emtools.model object and a set of environment layers and clamps the environment layers so that no variable falls outside of the range available in the training data.</i>
-----------	---

---

### Description

Takes an emtools.model object and a set of environment layers and clamps the environment layers so that no variable falls outside of the range available in the training data.

### Usage

```
clamp.env(model, env)
```

### Arguments

model	An enmtools.model object. Alternatively the analysis.df component of an enmtools.model object.
env	A raster or raster stack of environmental data.

### Value

An enmtools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

### Examples

```
data(euro.worldclim)
data(iberolacerta.clade)
monticola.gam <- enmtools.gam(iberolacerta.clade$species$monticola, euro.worldclim[[c(1,5,9,13)]])
euro.clamped <- clamp.env(monticola.gam, euro.worldclim)
clamped.prediction <- predict(monticola.gam, euro.clamped)
raster::plot(clamped.prediction$suitability - monticola.gam$suitability)
```

---

combine.species	<i>Takes a list of enmtools.species objects and combines them into a single enmtools.species object</i>
-----------------	---

---

### Description

Takes a list of enmtools.species objects and combines them into a single enmtools.species object

### Usage

```
combine.species(species.list)
```

**Arguments**

`species.list` List of `enmttools.species` objects that you want to combine together

**Value**

An `enmttools.species` object with the occurrence data, names, and range rasters for the species list combined into one.

**Examples**

```
data(iberolacerta.clade)
combine.species(iberolacerta.clade$species)
```

---

<code>drop.species</code>	<i>Takes a an ENMTools clade object and a vector of species names. Drops the species from the tree and removes data from the clade object.</i>
---------------------------	--

---

**Description**

Takes a an ENMTools clade object and a vector of species names. Drops the species from the tree and removes data from the clade object.

**Usage**

```
drop.species(clade, species)
```

**Arguments**

`clade` An ENMTools clade object

`species` A name or vector of names of species within the `enmttools.clade` object.

**Value**

An `enmttools.clade` object with the provided species dropped both from the tree and from the set of `enmttools.species` objects.

**Examples**

```
## Not run:
data(iberolacerta.clade)
if(requireNamespace("ape", quietly = TRUE)) {
  new.clade <- drop.species(iberolacerta.clade, c("cyreni", "monticola"))
}

## End(Not run)
```

---

enmtools.aoc	<i>Takes an overlap matrix and a tree and runs permutation tests to determine the statistical significance of the relationship between overlap and time</i>
--------------	---

---

## Description

Takes an overlap matrix and a tree and runs permutation tests to determine the statistical significance of the relationship between overlap and time

## Usage

```
enmtools.aoc(
  clade,
  env = NULL,
  overlap.source,
  nreps = 100,
  f = NULL,
  overlap.matrix = NULL,
  metric = "D"
)
```

## Arguments

clade	An enmtools.clade object containing species data and a phylogeny
env	Environmental layers for use when overlap is calculated using niche models.
overlap.source	The source of the overlaps to calculate. Choices are "bc", "dm", "gam", "glm", "mx", "range", and "point"
nreps	A number of reps to do
f	The model to be used for GLM and GAM comparisons
overlap.matrix	A matrix of overlaps to use, for option overlap.source = "matrix"
metric	The overlap metric to use. For ENM sources, this can be any combination of "D", "I", "cor", "env.D", "env.I", and "env.cor". for range and point overlap this argument is ignored.

## Value

A list containing a data frame of coefficients from the empirical regression of overlap on time along with the coefficients from all Monte Carlo replicates, along with plots and p values for the accompanying statistical tests.

---

enmtools.bc	<i>Takes an emtools.species object with presence and background points, and builds a Bioclim model</i>
-------------	--

---

## Description

Takes an emtools.species object with presence and background points, and builds a Bioclim model

## Usage

```
enmtools.bc(
  species,
  env = NA,
  test.prop = 0,
  report = NULL,
  overwrite = FALSE,
  nback = 1000,
  env.nback = 10000,
  rts.reps = 0,
  bg.source = "default",
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

## Arguments

species	An enmtools.species object
env	A raster or raster stack of environmental data.
test.prop	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
report	Optional name of an html file for generating reports
overwrite	TRUE/FALSE whether to overwrite a report file if it already exists
nback	Number of background points for models. In the case of bioclim models these are only used for evaluation.
env.nback	Number of points to draw from environment space for environment space discrimination metrics.
rts.reps	The number of replicates to do for a Raes and ter Steege-style test of significance
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.

clamp	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
...	Arguments to be passed to bioclim()

### Value

An enmtools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

### Examples

```
data(euro.worldclim)
data(iberolacerta.clade)
enmtools.bc(iberolacerta.clade$species$monticola, env = euro.worldclim)
```

---

enmtools.calibrate	<i>Takes an emtools.model object, and reformats it to run through the CalibratR package, calculates Continuous Boyce Index, and runs a Hosmer-Lemeshow goodness-of-fit test. Can either do a full CalibratR run or just return ECE/MCE statistics and plots.</i>
--------------------	--

---

### Description

Takes an emtools.model object, and reformats it to run through the CalibratR package, calculates Continuous Boyce Index, and runs a Hosmer-Lemeshow goodness-of-fit test. Can either do a full CalibratR run or just return ECE/MCE statistics and plots.

### Usage

```
enmtools.calibrate(
  model,
  recalibrate = FALSE,
  cuts = 11,
  env = NA,
  n.background = 10000,
  ...
)
```

**Arguments**

model	An enmtools.model object
recalibrate	When TRUE, does a full CalibratR "calibrate" run to recalibrate the model. When FALSE, just returns metrics and plots measuring calibration of the model as is.
cuts	The number of bins to split suitability scores into for calculating calibration.
env	A set of environment layers to be used for optional env space metrics
n.background	Number of background points to be used for env space metrics
...	Further arguments to be passed to CalibratR's "calibrate" function.

**Value**

An enmtools.calibrate object containing calibration and classification plots, metrics of model calibration, and (optionally) versions of the model that were recalibrated using various methods.

**Examples**

```
install.extras(repos='http://cran.us.r-project.org')
data(euro.worldclim)
data(iberolacerta.clade)
monticola.glm <- enmtools.glm(iberolacerta.clade$species$monticola,
                             env = euro.worldclim,
                             f = pres ~ bio1 + bio9,
                             test.prop = 0.3)
enmtools.calibrate(monticola.glm)
```

---

enmtools.clade	<i>Defining a class for enmtools.clade. Each clade gets:</i>
----------------	--

---

**Description**

Defining a class for enmtools.clade. Each clade gets:

**Usage**

```
enmtools.clade(species = NA, tree = NA)
```

**Arguments**

species	A list of enmtools.species objects
tree	A tree showing the relationships between the species

**Value**

An enmtools.clade object, either empty or containing a formatted version of the data that was passed into the function.

---

enmtools.dm	<i>Takes an emtools.species object with presence and background points, and builds a Domain model</i>
-------------	---

---

## Description

Takes an emtools.species object with presence and background points, and builds a Domain model

## Usage

```
enmtools.dm(
  species,
  env = NA,
  test.prop = 0,
  report = NULL,
  nback = 1000,
  env.nback = 10000,
  overwrite = FALSE,
  rts.reps = 0,
  bg.source = "default",
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

## Arguments

species	An enmtools.species object
env	A raster or raster stack of environmental data.
test.prop	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
report	Optional name of an html file for generating reports
nback	Number of background points for models. In the case of Domain, these are only used for evaluation.
env.nback	Number of points to draw from environment space for environment space discrimination metrics.
overwrite	TRUE/FALSE whether to overwrite a report file if it already exists
rts.reps	The number of replicates to do for a Raes and ter Steege-style test of significance
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.

clamp	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
...	Arguments to be passed to domain()

### Value

An enmttools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

### Examples

```
data(euro.worldclim)
data(iberolacerta.clade)
enmttools.dm(iberolacerta.clade$species$monticola, env = euro.worldclim)
```

---

enmttools.ecospat.bg	<i>enmttools.ecospat.bg, Runs an ecospat background/similarity test using enmttool.species objects.</i>
----------------------	---

---

### Description

enmttools.ecospat.bg, Runs an ecospat background/similarity test using enmttool.species objects.

### Usage

```
enmttools.ecospat.bg(
  species.1,
  species.2,
  env,
  nreps = 99,
  layers = NULL,
  test.type = "asymmetric",
  th.sp = 0,
  th.env = 0,
  R = 100,
  nback = 1000,
  bg.source = "default",
  verbose = FALSE,
  ...
)
```

**Arguments**

<code>species.1</code>	An <code>enmtools.species</code> object
<code>species.2</code>	An <code>enmtools.species</code> object
<code>env</code>	A set of environmental layers
<code>nreps</code>	The number of pseudoreplicates to perform
<code>layers</code>	A vector of length 2 containing the names of the layers to be used. If no layer names are provided and there are more than two layers in <code>env</code> , <code>enmtools</code> will perform a <code>pca</code> and use the top two layers from that.
<code>test.type</code>	Symmetric or asymmetric test. An asymmetric test is bguivalent to the "one.sided" option in the <code>ecospat</code> documentation, while a symmetric one would be two-sided.
<code>th.sp</code>	Quantile of species densities used as a threshold to exclude low species density values. See documentation for <code>ecospat.grid.clim.dyn</code> .
<code>th.env</code>	Quantile of environmental densities across study sites used as threshold to exclude low environmental density values. See documentation for <code>ecospat.grid.clim.dyn</code> .
<code>R</code>	Resolution of the grid. See documentation for <code>ecospat.grid.clim.dyn</code> .
<code>nback</code>	Number of background points to use for density calculations.
<code>bg.source</code>	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at randome from the entire study area outlined by the first environmental layer.
<code>verbose</code>	Controls printing of various messages progress reports. Defaults to <code>FALSE</code> .
<code>...</code>	Further arguments to be passed to <code>check.bg</code>

**Value**

A list containing the `ecospat` output kernel density estimates for each species and their background, as well as the results of hypothesis tests and their accompanying plots.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
monticola <- iberolacerta.clade$species$monticola
cyreni <- iberolacerta.clade$species$cyreni
enmtools.ecospat.bg(monticola, cyreni, euro.worldclim[[1:2]], nback = 500)
```

---

enmtools.ecospat.id     *enmtools.ecospat.id, Runs an ecospat identity test using enmtool.species objects.*

---

## Description

enmtools.ecospat.id, Runs an ecospat identity test using enmtool.species objects.

## Usage

```
enmtools.ecospat.id(
  species.1,
  species.2,
  env,
  nreps = 99,
  layers = NULL,
  th.sp = 0,
  th.env = 0,
  R = 100,
  nback = 1000,
  bg.source = "default",
  verbose = FALSE
)
```

## Arguments

species.1	An enmtools.species object
species.2	An enmtools.species object
env	A set of environmental layers
nreps	The number of pseudoreplicates to perform
layers	A vector of length 2 containing the names of the layers to be used. If no layer names are provided and there are more than two layers in env, enmtools will perform a pca and use the top two layers from that.
th.sp	Quantile of species densities used as a threshold to exclude low species density values. See documentation for ecospat.grid.clim.dyn.
th.env	Quantile of environmental densities across study sites used as threshold to exclude low environmental density values. See documentation for ecospat.grid.clim.dyn.
R	Resolution of the grid. See documentation for ecospat.grid.clim.dyn.
nback	Number of background points to use for density calculations.
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.

**Value**

A list containing the ecospat output kernel density estimates for each species and their background, as well as the results of hypothesis tests and their accompanying plots.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
monticola <- iberolacerta.clade$species$monticola
cyreni <- iberolacerta.clade$species$cyreni
enmtools.ecospat.id(monticola, cyreni, euro.worldclim[[1:2]], nback = 500)
```

---

enmtools.gam	<i>Takes an emtools.species object with presence and background points, and builds a gam</i>
--------------	--

---

**Description**

Takes an emtools.species object with presence and background points, and builds a gam

**Usage**

```
enmtools.gam(
  species,
  env,
  f = NULL,
  test.prop = 0,
  k = 4,
  nback = 1000,
  env.nback = 10000,
  report = NULL,
  overwrite = FALSE,
  rts.reps = 0,
  weights = "equal",
  gam.method = "REML",
  gam.select = TRUE,
  bg.source = "default",
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

**Arguments**

<code>species</code>	An <code>enmtools.species</code> object
<code>env</code>	A raster or raster stack of environmental data.
<code>f</code>	Standard gam formula
<code>test.prop</code>	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
<code>k</code>	Dimension of the basis used to represent the smooth term. See documentation for <code>s()</code> for details.
<code>nback</code>	Number of background points to draw from <code>range</code> or <code>env</code> , if background points aren't provided
<code>env.nback</code>	Number of points to draw from environment space for environment space discrimination metrics.
<code>report</code>	Optional name of an html file for generating reports
<code>overwrite</code>	TRUE/FALSE whether to overwrite a report file if it already exists
<code>rts.reps</code>	The number of replicates to do for a Raes and ter Steege-style test of significance
<code>weights</code>	If this is set to "equal", presences and background data will be assigned weights so that the sum of all presence points weights equals the sum of all background point weights. Otherwise, weights are not provided to the model.
<code>gam.method</code>	Defaults to restricted maximum likelihood to facilitate predictor selection, but if you want to use another method you can pass anything here that gam's "method" argument understands.
<code>gam.select</code>	Controls whether gam algorithm attempts to optimize smoothness and reduce model complexity. See <code>help("gam.selection")</code> for details.
<code>bg.source</code>	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
<code>verbose</code>	Controls printing of various messages progress reports. Defaults to FALSE.
<code>clamp</code>	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
<code>...</code>	Arguments to be passed to <code>gam()</code>

**Value**

An `enmtools` model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

## Examples

```
data(euro.worldclim)
data(iberolacerta.clade)
if(requireNamespace("mgcv", quietly = TRUE)) {
  enmtools.gam(iberolacerta.clade$species$monticola, env = euro.worldclim, f = pres ~ bio1 + bio9)
}
```

---

enmtools.glm	<i>Takes an emtools.species object with presence and background points, and builds a GLM</i>
--------------	--

---

## Description

Takes an emtools.species object with presence and background points, and builds a GLM

## Usage

```
enmtools.glm(
  species,
  env,
  f = NULL,
  test.prop = 0,
  eval = TRUE,
  nback = 1000,
  env.nback = 10000,
  report = NULL,
  overwrite = FALSE,
  rts.reps = 0,
  weights = "equal",
  bg.source = "default",
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

## Arguments

species	An enmtools.species object
env	A raster or raster stack of environmental data.
f	Standard GLM formula
test.prop	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
eval	Determines whether model evaluation should be done. Turned on by default, but moose turns it off to speed things up.

nback	Number of background points to draw from range or env, if background points aren't provided
env.nback	Number of points to draw from environment space for environment space discrimination metrics.
report	Optional name of an html file for generating reports
overwrite	TRUE/FALSE whether to overwrite a report file if it already exists
rts.reps	The number of replicates to do for a Raes and ter Steege-style test of significance
weights	If this is set to "equal", presences and background data will be assigned weights so that the sum of all presence points weights equals the sum of all background point weights. Otherwise, weights are not provided to the model.
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
...	Arguments to be passed to glm()

### Value

An enmtools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

### Examples

```
data(euro.worldclim)
data(iberolacerta.clade)
enmtools.glm(iberolacerta.clade$species$monticola, env = euro.worldclim, f = pres ~ bio1 + bio9)
```

---

enmtools.hypervolume	<i>Takes an emtools.species object and environmental layers, and constructs a hypervolume using the R package hypervolume</i>
----------------------	---

---

### Description

Takes an emtools.species object and environmental layers, and constructs a hypervolume using the R package hypervolume

**Usage**

```
enmtools.hypervolume(
  species,
  env,
  samples.per.point = 10,
  reduction.factor = 0.1,
  method = "gaussian",
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

**Arguments**

species	An enmtools.species object
env	A stack of environmental rasters
samples.per.point	To be passed to hypervolume_gaussian
reduction.factor	To be passed to hypervolume_project
method	Method for constructing hypervolumes, defaults to "gaussian"
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
...	Extra parameters to be passed to hypervolume_gaussian

**Value**

An enmtools hypervolume object containing a hypervolume object, a raster of suitability scores, the species name, and the occurrence data frame.

**Examples**

```
## Not run:
install.extras(repos='http://cran.us.r-project.org')
data(euro.worldclim)
data(iberolacerta.clade)
env <- euro.worldclim[[c(1,8,12,17)]]
if(requireNamespace("hypervolume", quietly = TRUE)) {
  monticola.hv <- enmtools.hypervolume(iberolacerta.clade$species$monticola, env = env)
}

## End(Not run)
```

---

enmtools.maxent	<i>Takes an emtools.species object with presence and background points, and builds a maxent model</i>
-----------------	---

---

## Description

Takes an emtools.species object with presence and background points, and builds a maxent model

## Usage

```
enmtools.maxent(
  species,
  env,
  test.prop = 0,
  nback = 1000,
  env.nback = 10000,
  report = NULL,
  overwrite = FALSE,
  rts.reps = 0,
  bg.source = "default",
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

## Arguments

species	An enmtools.species object
env	A raster or raster stack of environmental data.
test.prop	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
nback	Number of background points to draw from range or env, if background points aren't provided
env.nback	Number of points to draw from environment space for environment space discrimination metrics.
report	Optional name of an html file for generating reports
overwrite	TRUE/FALSE whether to overwrite a report file if it already exists
rts.reps	The number of replicates to do for a Raes and ter Steege-style test of significance
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.

clamp	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
...	Arguments to be passed to maxent()

### Value

An enmtools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

### Examples

```
## Not run:
install.extras(repos='http://cran.us.r-project.org')
data(euro.worldclim)
data(iberolacerta.clade)
if(requireNamespace("rJava", quietly = TRUE)) {
  enmtools.maxent(iberolacerta.clade$species$monticola, env = euro.worldclim)
}

## End(Not run)
```

---

enmtools.ppmlasso	<i>Takes an emtools.species object with presence and background points, and builds a Point Process Model (with Lasso penalty)</i>
-------------------	---

---

### Description

Takes an emtools.species object with presence and background points, and builds a Point Process Model (with Lasso penalty)

### Usage

```
enmtools.ppmlasso(
  species,
  env,
  f = NULL,
  test.prop = 0,
  eval = TRUE,
  nback = 1000,
  env.nback = 10000,
  normalise = FALSE,
  report = NULL,
  overwrite = FALSE,
  rts.reps = 0,
```

```

    bg.source = "default",
    verbose = FALSE,
    clamp = TRUE,
    ...
  )

```

## Arguments

<code>species</code>	An <code>enmtools.species</code> object
<code>env</code>	A raster or raster stack of environmental data.
<code>f</code>	Standard R formula
<code>test.prop</code>	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
<code>eval</code>	Determines whether model evaluation should be done. Turned on by default, but <code>moses</code> turns it off to speed things up.
<code>nback</code>	Number of background points to draw from <code>range</code> or <code>env</code> , if background points aren't provided
<code>env.nback</code>	Number of points to draw from environment space for environment space discrimination metrics.
<code>normalise</code>	Should the suitability of the model be normalised? If <code>FALSE</code> (the default), suitability is returned as the predicted number of presence points in each grid cell (occurrence density). If <code>TRUE</code> , occurrence densities are divided by the total predicted density, to give a value ranging from 0 to 1, which represents the proportion of the predicted density for a species that occurs in each grid cell.
<code>report</code>	Optional name of an html file for generating reports
<code>overwrite</code>	<code>TRUE/FALSE</code> whether to overwrite a report file if it already exists
<code>rts.reps</code>	The number of replicates to do for a Raes and ter Steege-style test of significance
<code>bg.source</code>	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
<code>verbose</code>	Controls printing of various messages progress reports. Defaults to <code>FALSE</code> .
<code>clamp</code>	When set to <code>TRUE</code> , clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
<code>...</code>	Arguments to be passed to <code>ppmlasso()</code>

## Details

This runs a `ppmlasso` model of a species' distribution. It is generally recommended that background points should be on a grid for this method, as the background points are considered 'quadrature' points, used to estimate an integral. If background points are not provided, the function will generate them on a grid, rather than randomly, as is more usual for other SDM methods.

**Value**

An enmtools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

**Examples**

```
## Not run:
install.extras(repos='http://cran.us.r-project.org')
data(euro.worldclim)
data(iberolacerta.clade)
enmtools.ppmlasso(iberolacerta.clade$species$monticola, env = euro.worldclim[[1:3]])

## End(Not run)
```

---

enmtools.rf	<i>Takes an emtools.species object with presence and background points, and builds a random forest model</i>
-------------	--

---

**Description**

Takes an emtools.species object with presence and background points, and builds a random forest model

**Usage**

```
enmtools.rf(
  species,
  env,
  f = NULL,
  test.prop = 0,
  eval = TRUE,
  nback = 1000,
  env.nback = 10000,
  report = NULL,
  overwrite = FALSE,
  rts.reps = 0,
  bg.source = "default",
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

**Arguments**

species	An enmtools.species object
env	A raster or raster stack of environmental data.
f	A formula for fitting the model

test.prop	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
eval	Determines whether model evaluation should be done. Turned on by default, but moses turns it off to speed things up.
nback	Number of background points to draw from range or env, if background points aren't provided
env.nback	Number of points to draw from environment space for environment space discrimination metrics.
report	Optional name of an html file for generating reports
overwrite	TRUE/FALSE whether to overwrite a report file if it already exists
rts.reps	The number of replicates to do for a Raes and ter Steege-style test of significance
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
...	Arguments to be passed to rf()

### Value

An enmtools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

### Examples

```
data(euro.worldclim)
data(iberolacerta.clade)
enmtools.rf(iberolacerta.clade$species$monticola, env = euro.worldclim, nback = 500)
```

---

enmtools.rf.ranger	<i>Takes an emtools.species object with presence and background points, and builds a random forest model using the 'probability mode' in package 'ranger'</i>
--------------------	---

---

### Description

Takes an emtools.species object with presence and background points, and builds a random forest model using the 'probability mode' in package 'ranger'

**Usage**

```

enmtools.rf.ranger(
  species,
  env,
  f = NULL,
  test.prop = 0,
  eval = TRUE,
  nback = 1000,
  env.nback = 10000,
  report = NULL,
  overwrite = FALSE,
  rts.reps = 0,
  bg.source = "default",
  verbose = FALSE,
  clamp = TRUE,
  ...
)

```

**Arguments**

species	An enmtools.species object
env	A raster or raster stack of environmental data.
f	A formula for fitting the model
test.prop	Proportion of data to withhold randomly for model evaluation, or "block" for spatially structured evaluation.
eval	Determines whether model evaluation should be done. Turned on by default, but moses turns it off to speed things up.
nback	Number of background points to draw from range or env, if background points aren't provided
env.nback	Number of points to draw from environment space for environment space discrimination metrics.
report	Optional name of an html file for generating reports
overwrite	TRUE/FALSE whether to overwrite a report file if it already exists
rts.reps	The number of replicates to do for a Raes and ter Steege-style test of significance
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	When set to TRUE, clamps the environmental layers so that predictions made outside the min/max of the training data for each predictor are set to the value for the min/max for that predictor. Prevents the model from extrapolating beyond the min/max bounds of the predictor space the model was trained in, although there could still be projections outside the multivariate training space if predictors are strongly correlated.
...	Arguments to be passed to <a href="#">ranger</a>

**Value**

An enmtools model object containing species name, model formula (if any), model object, suitability raster, marginal response plots, and any evaluation objects that were created.

**Examples**

```
data(euro.worldclim)
data(iberolacerta.clade)
enmtools.rf.ranger(iberolacerta.clade$species$monticola, env = euro.worldclim, nback = 500)
```

---

enmtools.species	<i>Defining a class for enmtools.species.</i>
------------------	---

---

**Description**

Each species gets:

**Usage**

```
enmtools.species(
  range = NA,
  presence.points = NA,
  background.points = NA,
  species.name = NA,
  models = NA
)
```

**Arguments**

range	A raster or SpatialPolygon with the actual range they occur in
presence.points	A data frame with sampled localities
background.points	A data frame with absence/pseudoabsence/background localities
species.name	A character vector with the species name
models	A list of models that are made for the species, which will be stuffed in there as we go along to pass the check. This is used by internal enmtools functions to make sure the necessary data is present before processing anything.

**Value**

Returns an enmtools.species object, either empty or populated with the parameter values that were passed into the function.

---

enmtools.vip	<i>Takes an enmtools.model object, and performs variable importance analyses on it using methods from the vip package</i>
--------------	---

---

## Description

Takes an enmtools.model object, and performs variable importance analyses on it using methods from the vip package

## Usage

```
enmtools.vip(model, metric = "auc", nsim = 10, method = "permute", ...)
```

## Arguments

model	An enmtools.model object
metric	The metric to use for measuring how variables affect model predictions
nsim	The number of simulations to be run for method "permute"
method	A character string or vector containing any combination of "model", "permute", "shap", or "firm". For details on what these mean, see the vip package help.
...	Further arguments to be passed to vip's "vi" functions.

## Value

An enmtools.vip object

## Examples

```
## Not run:
install.extras(repos='http://cran.us.r-project.org')
data(euro.worldclim)
data(iberolacerta.clade)
monticola.glm <- enmtools.glm(iberolacerta.clade$species$monticola,
                             env = euro.worldclim,
                             test.prop = 0.3)

enmtools.vip(monticola.glm)

## End(Not run)
```

---

env.breadth	<i>Calculates breadth of a model in environment space using latin hypercube sampling</i>
-------------	--

---

## Description

Calculates breadth of a model in environment space using latin hypercube sampling

## Usage

```
env.breadth(model, env, tolerance = 1e-04, max.reps = 10, chunk.size = 1e+05)
```

## Arguments

model	An <code>enmtools.model</code> object or a model object that can be projected using the <code>predict()</code> function
env	A raster, raster stack of environmental data, or a list of minima and maxima for the environmental space to evaluate models over.
tolerance	How close do successive overlap metrics have to be before we decide we're close enough to the final answer
max.reps	Maximum number of attempts that will be made to find suitable starting conditions
chunk.size	How many combinations of environmental variables to try at a time. If your niche breadth in environment space is small, increasing this value may help you get a result.

## Value

A list containing the environmental space version of the B2 metric and a plot of B2 estimates as a function of sample size, used as a convergence diagnostic.

## Examples

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
cyreni.glm <- enmtools.glm(cyreni, euro.worldclim, test.prop = 0.2,
  f = pres ~ bio1 + bio12, nback = 500)
env.breadth(cyreni.glm, euro.worldclim)
```

---

env.evaluate	<i>Calculates evaluation metrics (AUC, etc.) using latin hypercube sampling in environment space</i>
--------------	--

---

### Description

Calculates evaluation metrics (AUC, etc.) using latin hypercube sampling in environment space

### Usage

```
env.evaluate(
  species,
  model,
  env,
  bg.source = "background",
  n.background = 10000,
  test.eval = FALSE,
  verbose = FALSE,
  ...
)
```

### Arguments

species	An enmtools.species object
model	An enmtools.model object or a model that can be projected using the predict() function of dismo
env	A raster or raster stack of environmental data.
bg.source	Determines whether minima and maxima of the environment space should be picked using the environment layers or the background points.
n.background	The number of background points to sample from the environment space.
test.eval	When set to "true", env.evaluate evaluates the test data stored in the model object instead of the training data.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
...	Arguments to be passed to other functions

### Value

A dismo evaluate object measuring the performance of model predictions in environment space.

### Examples

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
cyreni.glm <- enmtools.glm(cyreni, euro.worldclim, test.prop = 0.2,
```

```
f = pres ~ bio1 + bio12, nback = 500)
env.evaluate(cyreni, cyreni.glm, euro.worldclim)
```

---

env.overlap	<i>Calculates overlap between models in environment space using latin hypercube sampling</i>
-------------	--

---

## Description

Calculates overlap between models in environment space using latin hypercube sampling

## Usage

```
env.overlap(
  model.1,
  model.2,
  env,
  tolerance = 0.001,
  max.reps = 10,
  cor.method = "spearman",
  chunk.size = 1e+05,
  recal.model.1 = NA,
  recal.model.2 = NA,
  verbose = FALSE
)
```

## Arguments

model.1	An <code>enmtools.model</code> object model object that can be projected using the <code>predict()</code> function
model.2	Another <code>enmtools.model</code> object or other model object that can be projected using the <code>predict()</code> function
env	A raster, raster stack of environmental data, or a list of minima and maxima for the environmental space to evaluate models over
tolerance	How close do successive overlap metrics have to be before we decide we're close enough to the final answer
max.reps	Maximum number of attempts that will be made to find suitable starting conditions
cor.method	Which method to use for calculating correlations between models
chunk.size	How many combinations of environmental variables to try at a time. If your niche breadth in environment space is small, increasing this value may help you get a result.
recal.model.1	Optional. The output of <code>enmtools.recalibrate</code> for model 1, which needs to have been run with <code>"recalibrate = TRUE"</code> .

- recal.model.2    Optional. The output of enmtools.recalibrate for model 2, which needs to have been run with "recalibrate = TRUE".
- verbose           Controls printing of various messages progress reports. Defaults to FALSE.

**Value**

A list of values measuring the overlap between models in environment space, as well as some plots depicting change of the estimates as a function of how many samples were used, which are included as a sort of convergence diagnostic.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
monticola <- iberolacerta.clade$species$monticola
cyreni.glm <- enmtools.glm(cyreni, euro.worldclim, f = pres ~ bio1 + bio12, nback = 500)
monticola.glm <- enmtools.glm(monticola, euro.worldclim, f = pres ~ bio1 + bio12, nback = 500)
env.overlap(cyreni.glm, monticola.glm, euro.worldclim)
```

---

euro.worldclim	<i>Worldclim data for Europe</i>
----------------	----------------------------------

---

**Description**

This is a fairly low-resolution set of Worldclim layers for Europe to be used in demonstrating ENMTools functions.

**Usage**

```
data(euro.worldclim)
```

**Format**

A raster brick with 19 worldclim layers.

---

<code>geog.range.overlap</code>	<i>Takes two <code>emtools.species</code> objects with range rasters, calculates overlap between them as in Fitzpatrick and Turelli 2006</i>
---------------------------------	--

---

### Description

Takes two `emtools.species` objects with range rasters, calculates overlap between them as in Fitzpatrick and Turelli 2006

### Usage

```
geog.range.overlap(x, y)
```

### Arguments

<code>x</code>	An <code>emtools.species</code> object containing a range raster
<code>y</code>	An <code>emtools.species</code> object containing a range raster

### Value

A numeric value measuring range overlap.

### Examples

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
monticola <- iberolacerta.clade$species$monticola
cyreni$range <- background.raster.buffer(cyreni$presence.points, 100000, euro.worldclim)
monticola$range <- background.raster.buffer(monticola$presence.points, 100000, euro.worldclim)
geog.range.overlap(cyreni, monticola)
```

---

<code>hypervolume.overlap</code>	<i>Takes an <code>emtools.species</code> object and environmental layers, and constructs a hypervolume using the R package <code>hypervolume</code></i>
----------------------------------	---

---

### Description

Takes an `emtools.species` object and environmental layers, and constructs a hypervolume using the R package `hypervolume`

**Usage**

```
hypervolume.overlap(
  species.1,
  species.2,
  env = NA,
  reduction.factor = 0.1,
  ...
)
```

**Arguments**

species.1	An enmtools.species or enmtools.hypervolume object
species.2	An enmtools.species or enmtools.hypervolume object
env	A stack of environmental rasters, required when enmtools.species objects are passed
reduction.factor	Passed to hypervolume functions
...	Extra parameters to be passed to enmtools.hypervolume

**Value**

A list containing a set of hypervolume objects and the overlap that was measured between them.

**Examples**

```
## Not run:
install.extras(repos='http://cran.us.r-project.org')
data(euro.worldclim)
data(iberolacerta.clade)
mont <- iberolacerta.clade$species$monticola
cyr <- iberolacerta.clade$species$cyreni
env <- euro.worldclim[[c(1,8,12,17)]]
if(requireNamespace("hypervolume", quietly = TRUE)) {
  hypervolume.overlap(mont, cyr, env = env)
}

## End(Not run)
```

---

iberolacerta.clade	<i>GBIF data for a clade of Iberolacerta lizards from Spain</i>
--------------------	---

---

**Description**

This is some sample data downloaded from GBIF for the purposes of demonstrating ENMTools functionality.

**Usage**

```
data(iberolacerta.clade)
```

**Format**

An `enmtools.clade` object with seven species and a phylogeny.

---

<code>identity.test</code>	<i>identity.test</i> Conduct a niche identity/equivalency test as described in Warren et al. 2008.
----------------------------	--

---

**Description**

`identity.test` Conduct a niche identity/equivalency test as described in Warren et al. 2008.

**Usage**

```
identity.test(
  species.1,
  species.2,
  env,
  type,
  f = NULL,
  nreps = 99,
  nback = 1000,
  bg.source = "default",
  low.memory = FALSE,
  rep.dir = NA,
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

**Arguments**

<code>species.1</code>	An <code>enmtools.species</code> object
<code>species.2</code>	An <code>enmtools.species</code> object
<code>env</code>	A <code>RasterLayer</code> or <code>RasterStack</code> object containing environmental data
<code>type</code>	The type of model to construct, currently accepts "glm", "mx", "bc", "gam", "rf", or "dm"
<code>f</code>	A function to use for model fitting. Only required for GLM models at the moment.
<code>nreps</code>	Number of replicates to perform
<code>nback</code>	Number of background points for models

bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
low.memory	When set to TRUE, replicate models are written to disc instead of being stored in the output object. Replicate models stored in the output object contain paths to the replicate models on disk instead of the rasters themselves.
rep.dir	Directory for storing replicate models when low.memory is set to TRUE. If not specified, the working directory will be used.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	Controls whether empirical and replicate models should be clamped to the environment space used for training.
...	Additional arguments to be passed to model fitting functions.

### Value

results A list containing the replicates, models for the empirical data, and summary statistics and plots.

### Examples

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
monticola <- iberolacerta.clade$species$monticola
cyreni$range <- background.raster.buffer(cyreni$presence.points, 100000, euro.worldclim)
monticola$range <- background.raster.buffer(monticola$presence.points, 100000, euro.worldclim)
identity.test(cyreni, monticola, env = euro.worldclim, type = "glm",
f = pres ~ bio1 + bio12, nreps = 10)
```

---

install.extras	<i>install.extras</i>
----------------	-----------------------

---

### Description

Convenience function that installs all extra packages used in ENMTools. ENMTools uses functions from a lot of external packages, and due to CRAN best practices it doesn't install those packages by default. The function `install.extras()` just calls `install.packages` with a list of all of the extra packages. At present this list includes `mgcv`, `ecospat`, `randomForest`, `hypervolume`, `ape`, `ppmlasso`, `leaflet`, `ranger`, `CalibratR`, `caret`, and `ResourceSelection`.

### Usage

```
install.extras(repos = "http://cran.us.r-project.org", ...)
```

**Arguments**

repos	URL for the repository to use for installing R packages
...	Other parameters to be passed to <code>install.packages</code>

**Value**

No return value.

**Examples**

```
install.extras()
```

---

interactive.plot	<i>Generic function for making interactive plots of ENMTools models and species</i>
------------------	---

---

**Description**

Function that takes an `enmtools.model` or `enmtools.species` object and calls the class-appropriate `interactive.plot.xx` function for it. These functions use [leaflet](#) for mapping and will only function properly if you have an active internet connection.

**Usage**

```
interactive.plot(x, ...)
```

**Arguments**

x	enmtools.model or species object to plot
...	other arguments passed to <code>interactive.plot.enmtools.model</code> or <code>interactive.plot.enmtools.species</code>

**Value**

An interactive leaflet plot depicting the predictions and data from the `enmtools.model` object.

---

`interactive.plot.enmtools.model`*Plot an enmtools.model object on an interactive map*

---

## Description

Function that take an `enmtools.model` object and plots an interactive map of the presence points, background points (if applicable), and species suitability map. This function uses [leaflet](#) for mapping and will only function properly if you have an active internet connection.

## Usage

```
## S3 method for class 'enmtools.model'
interactive.plot(
  x,
  map.provider = "Esri.WorldPhysical",
  cluster.points = FALSE,
  raster.opacity = 1,
  ...
)
```

## Arguments

<code>x</code>	<code>enmtools.model</code> object to plot
<code>map.provider</code>	Name of a map provider for the underlying interactive base map. Default is "Esri.WorldPhysical", and attractive topographic map with no place labels. A preview of all map provider options can be viewed at <a href="http://leaflet-extras.github.io/leaflet-providers/preview/">http://leaflet-extras.github.io/leaflet-providers/preview/</a>
<code>cluster.points</code>	Should points be clustered? If TRUE, points close together will be grouped into clusters that can be interactively expanded by clicking on them.
<code>raster.opacity</code>	Specifies the opacity level of the suitability raster.
<code>...</code>	other arguments (not used currently)

## Value

An interactive leaflet plot depicting the predictions and data from the `enmtools.model` object.

---

```
interactive.plot.enmtools.species
```

*Plot an enmtools.species object on an interactive map*

---

### Description

Function that take an `enmtools.species` object and plots an interactive map of the presence points, background points (if applicable), and species range raster (if applicable). This function uses `leaflet` for mapping and will only function properly if you have an active internet connection.

### Usage

```
## S3 method for class 'enmtools.species'
interactive.plot(
  x,
  map.provider = "Esri.WorldPhysical",
  cluster.points = FALSE,
  ...
)
```

### Arguments

<code>x</code>	entools.species object to plot
<code>map.provider</code>	Name of a map provider for the underlying interactive base map. Default is "Esri.WorldPhysical", and attractive topographic map with no place labels. A preview of all map provider options can be viewed at <a href="http://leaflet-extras.github.io/leaflet-providers/preview/">http://leaflet-extras.github.io/leaflet-providers/preview/</a>
<code>cluster.points</code>	Should points be clustered? If TRUE, points close together will be grouped into clusters that can be interactively expanded by clicking on them.
<code>...</code>	other arguments (not used currently)

### Value

An interactive leaflet plot visualizing the data present in the species object.

---

<code>marginal.plots</code>	<i>marginal.plots</i> Plots the marginal response of a model to an environmental variable with all other variables held at their mean in env
-----------------------------	--

---

### Description

`marginal.plots` Plots the marginal response of a model to an environmental variable with all other variables held at their mean in env

**Usage**

```
marginal.plots(model, env, layer, standardize = TRUE)
```

**Arguments**

model	An enmtools model object
env	A RasterLayer or RasterStack object containing environmental data
layer	The name of the layer to plot
standardize	Whether to set the maximum of the response function to 1, or to instead use the raw values.

**Value**

results A plot of the marginal response of the model to the environmental variable.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni.glm <- enmtools.glm(iberolacerta.clade$species$cyreni,
  f = pres ~ bio1 + bio12, euro.worldclim)
marginal.plots(cyreni.glm, euro.worldclim, "bio1")
```

---

moses.list	<i>Takes a list of enmtools.species objects and uses model selection to ask whether they're better treated jointly or separately</i>
------------	--

---

**Description**

Takes a list of enmtools.species objects and uses model selection to ask whether they're better treated jointly or separately

**Usage**

```
moses.list(
  species.list,
  env,
  f = NULL,
  eval = FALSE,
  nback = 1000,
  bg.source = "default",
  verbose = FALSE,
  ...
)
```

**Arguments**

<code>species.list</code>	A list of <code>enmtools.species</code> objects, or an <code>enmtools.clade</code> object.
<code>env</code>	A raster or raster stack of environmental data.
<code>f</code>	A GLM-style function for model fitting
<code>eval</code>	Boolean indicating whether or not GLMs should be evaluated using AUC/TSS/etc.
<code>nback</code>	Number of background points to generate, if any
<code>bg.source</code>	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
<code>verbose</code>	Controls printing of various messages progress reports. Defaults to FALSE.
<code>...</code>	further arguments to be passed to <code>enmtools.glm</code>

**Value**

A list containing GLMs for the groups separately and together, as well as AIC values for those models.

---

<code>multistack.pca</code>	<i>multistack.pca, simultaneous PCA on more than one stack of environmental rasters</i>
-----------------------------	---

---

**Description**

`multistack.pca`, simultaneous PCA on more than one stack of environmental rasters

**Usage**

```
multistack.pca(..., n = 2)
```

**Arguments**

<code>...</code>	Any number of environmental raster stacks or bricks
<code>n</code>	The number of PCA layers to return

**Value**

A list containing a stack or brick of rasters for each input set representing the top `n` pca axes of the initial environmental variables, as well as the `pca` object from the analysis that produced them and some useful plots showing the distribution of each PC in the different stacks.

## Examples

```
world <- raster::getData(name = "worldclim", download = TRUE, var = "bio", res = 5)
test1 <- crop(world, extent(10, 15, 10, 15))
test2 <- crop(world, extent(17, 22, 17, 22))
test3 <- crop(world, extent(24, 26, 24, 26))
multistack.pca(test1, test2, test3)
```

---

node.overlap	<i>Takes an overlap matrix and a tree and returns average overlap at nodes using Fitzpatrick &amp; Turelli averaging method. Typicall called via enmtools.aoc rather than used directly.</i>
--------------	--

---

## Description

Takes an overlap matrix and a tree and returns average overlap at nodes using Fitzpatrick & Turelli averaging method. Typicall called via enmtools.aoc rather than used directly.

## Usage

```
node.overlap(overlap, tree)
```

## Arguments

overlap	An overlap matrix
tree	A tree

## Value

A data frame of node ages and overlaps

---

point.overlap	<i>Takes two emtools.species objects with range rasters, calculates overlap between them as in Cardillo and Warren 2016</i>
---------------	---

---

## Description

Takes two emtools.species objects with range rasters, calculates overlap between them as in Cardillo and Warren 2016

## Usage

```
point.overlap(x, y)
```

**Arguments**

x                    An enmtools.species object containing presence points  
 y                    An enmtools.species object containing presence points

**Value**

A numeric value measuring the overlap between point distributions.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
monticola <- iberolacerta.clade$species$monticola
if(requireNamespace("fields", quietly = TRUE)) {
  point.overlap(cyreni, monticola)
}
```

---

rangebreak.blob	<i>rangebreak.blob</i> Conduct a blob rangebreak test as described in Glor and Warren 2011.
-----------------	---

---

**Description**

rangebreak.blob Conduct a blob rangebreak test as described in Glor and Warren 2011.

**Usage**

```
rangebreak.blob(
  species.1,
  species.2,
  env,
  type,
  f = NULL,
  nreps = 99,
  nback = 1000,
  bg.source = "default",
  low.memory = FALSE,
  rep.dir = NA,
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

**Arguments**

<code>species.1</code>	An <code>emtools.species</code> object
<code>species.2</code>	An <code>enmtools.species</code> object
<code>env</code>	A <code>RasterLayer</code> or <code>RasterStack</code> object containing environmental data
<code>type</code>	The type of model to construct, currently accepts "glm", "mx", "bc", "gam", or "dm"
<code>f</code>	A function to use for model fitting. Only required for GLM models at the moment.
<code>nreps</code>	Number of replicates to perform
<code>nback</code>	Number of background points for models
<code>bg.source</code>	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
<code>low.memory</code>	When set to TRUE, replicate models are written to disc instead of being stored in the output object. Replicate models stored in the output object contain paths to the replicate models on disk instead of the rasters themselves.
<code>rep.dir</code>	Directory for storing replicate models when <code>low.memory</code> is set to TRUE. If not specified, the working directory will be used.
<code>verbose</code>	Controls printing of various messages progress reports. Defaults to FALSE.
<code>clamp</code>	Controls whether empirical and replicate models should be clamped to the environment space used for training.
<code>...</code>	Additional arguments to be passed to model fitting functions.

**Value**

`results` A list containing the replicates, models for the empirical data, and summary statistics and plots.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
aranica <- iberolacerta.clade$species$aranica
if(requireNamespace("fields", quietly = TRUE)) {
  rangebreak.blob(cyreni, aranica, env = euro.worldclim, type = "glm",
f= pres ~ bio1 + bio12, nreps = 10)
}
```

---

rangebreak.linear	<i>rangebreak.linear</i> Conduct a linear rangebreak test as described in Glor and Warren 2011.
-------------------	---

---

## Description

rangebreak.linear Conduct a linear rangebreak test as described in Glor and Warren 2011.

## Usage

```
rangebreak.linear(
  species.1,
  species.2,
  env,
  type,
  f = NULL,
  nreps = 99,
  nback = 1000,
  bg.source = "default",
  low.memory = FALSE,
  rep.dir = NA,
  verbose = FALSE,
  clamp = TRUE,
  ...
)
```

## Arguments

species.1	An emtools.species object
species.2	An enmtools.species object
env	A RasterLayer or RasterStack object containing environmental data
type	The type of model to construct, currently accepts "glm", "mx", "bc", "gam", or "dm"
f	A function to use for model fitting. Only required for GLM models at the moment.
nreps	Number of replicates to perform
nback	Number of background points for models
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
low.memory	When set to TRUE, replicate models are written to disc instead of being stored in the output object. Replicate models stored in the output object contain paths to the replicate models on disk instead of the rasters themselves.

rep.dir	Directory for storing replicate models when low.memory is set to TRUE. If not specified, the working directory will be used.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	Controls whether empirical and replicate models should be clamped to the environment space used for training.
...	Additional arguments to be passed to model fitting functions.

**Value**

results A list containing the replicates, models for the empirical data, and summary statistics and plots.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
aranica <- iberolacerta.clade$species$aranica
rangebreak.linear(cyreni, aranica, env = euro.worldclim, type = "glm",
f= pres ~ bio1 + bio12, nreps = 10)
```

---

rangebreak.ribbon	<i>rangebreak.ribbon</i> Conduct a ribbon rangebreak test as described in Glor and Warren 2011.
-------------------	---

---

**Description**

rangebreak.ribbon Conduct a ribbon rangebreak test as described in Glor and Warren 2011.

**Usage**

```
rangebreak.ribbon(
  species.1,
  species.2,
  ribbon,
  env,
  type,
  f = NULL,
  width = 1,
  nreps = 99,
  nback = 1000,
  bg.source = "default",
  low.memory = FALSE,
  rep.dir = NA,
  verbose = FALSE,
```

```

    clamp = TRUE,
    ...
)

```

### Arguments

species.1	An emtools.species object
species.2	An enmtools.species object
ribbon	An enmtools.species object representing the region of marginal habitat in the overlap between the species' ranges
env	A RasterLayer or RasterStack object containing environmental data
type	The type of model to construct, currently accepts "glm", "mx", "bc", or "dm"
f	A function to use for model fitting. Only required for GLM models at the moment.
width	Width of the ribbon, in the same units as the occurrence points (e.g, decimal degrees)
nreps	Number of replicates to perform
nback	Number of background points for models
bg.source	Source for drawing background points. If "points", it just uses the background points that are already in the species object. If "range", it uses the range raster. If "env", it draws points at random from the entire study area outlined by the first environmental layer.
low.memory	When set to TRUE, replicate models are written to disc instead of being stored in the output object. Replicate models stored in the output object contain paths to the replicate models on disk instead of the rasters themselves.
rep.dir	Directory for storing replicate models when low.memory is set to TRUE. If not specified, the working directory will be used.
verbose	Controls printing of various messages progress reports. Defaults to FALSE.
clamp	Controls whether empirical and replicate models should be clamped to the environment space used for training.
...	Additional arguments to be passed to model fitting functions.

### Value

results A list containing models for the replicates, models for the empirical data, and summary statistics and plots.

### Examples

```

data(iberolacerta.clade)
data(euro.worldclim)
cyreni <- iberolacerta.clade$species$cyreni
aranica <- iberolacerta.clade$species$aranica

```

```
# We're just going to fudge together occurrence data from a ribbon here
# from random points between the two species' ranges
p <- data.frame(Longitude = runif(50, -4, -2), Latitude = runif(50, 40, 43))
bg <- background.points.buffer(p, 100000, 100, euro.worldclim[[1]])
ribbon <- enmtools.species(species.name = "ribbon", presence.points = p, background.points = bg)

rangebreak.ribbon(cyreni, aranica, ribbon = ribbon, env = euro.worldclim,
type = "glm", f= pres ~ bio1 + bio12, nreps = 10)
```

---

raster.breadth	<i>raster.breadth, applies measures of niche breadth to an ENM</i>
----------------	--

---

## Description

This function measures the spatial heterogeneity of the distribution of suitability scores from an ENM. It returns Levins' two metrics of niche breadth.

## Usage

```
raster.breadth(x, verbose = FALSE)
```

## Arguments

x	An object of class raster or RasterLayer, or an ENMTools model object containing a suitability raster.
verbose	Controls printing of diagnostic messages

## Value

results A vector containing the two metrics B1 and B2 for niche breadth.

## Examples

```
data(iberolacerta)
data(euro.worldclim)
aurelioi.glm <- enmtools.glm(iberolacerta.clade$species$aurelioi, euro.worldclim,
f = pres ~ bio1 + bio12)
raster.breadth(aurelioi.glm)
```

---

raster.cor	<i>Calculates the correlation coefficient between two rasters.</i>
------------	--

---

**Description**

Calculates the correlation coefficient between two rasters.

**Usage**

```
raster.cor(x, y, method = "spearman")
```

**Arguments**

x	Either a raster or an ENMTools model object with a suitability raster.
y	Either a raster or an ENMTools model object with a suitability raster.
method	The method to be used for calculating correlations. Defaults to spearman, but can take "kendall" or "pearson" as well.

**Value**

A numeric correlation coefficient.

**Examples**

```
data(euro.worldclim)
raster.cor(euro.worldclim[[1]], euro.worldclim[[2]])
```

---

raster.cor.matrix	<i>Takes a raster stack and returns a data frame containing Pearson correlation coefficients between the included rasters</i>
-------------------	---

---

**Description**

Takes a raster stack and returns a data frame containing Pearson correlation coefficients between the included rasters

**Usage**

```
raster.cor.matrix(env, method = "pearson")
```

**Arguments**

env	A RasterStack object containing two or more rasters
method	Type of correlation to measure. Can do "pearson", "kendall", or "spearman"

**Value**

A data frame of correlation coefficients for a set of rasters.

**Examples**

```
data(euro.worldclim)
raster.cor.matrix(euro.worldclim)
```

---

raster.cor.plot	<i>Takes a raster stack and returns a data frame containing Pearson correlation coefficients between the included rasters</i>
-----------------	---

---

**Description**

Takes a raster stack and returns a data frame containing Pearson correlation coefficients between the included rasters

**Usage**

```
raster.cor.plot(env, method = "pearson")
```

**Arguments**

env	A RasterStack object containing two or more rasters
method	Type of correlation to measure. Can do "pearson", "kendall", or "spearman"

**Value**

A list of two plots. The first maps the correlations between rasters into an MDS space, so that predictors that fall close together in that space are more correlated. The second plot is a heatmap depicting the correlations between pairs of layers.

**Examples**

```
data(euro.worldclim)
raster.cor.plot(euro.worldclim)
```

---

raster.overlap	<i>raster.overlap, measures overlap between two ENMs</i>
----------------	--

---

### Description

This function measures similarity in the geographic distribution of suitability scores from two ENMs. It returns two metrics, I and D. These metrics are described in Warren et al. 2008.

### Usage

```
raster.overlap(x, y, verbose = FALSE)
```

### Arguments

x	A raster or RasterLayer object, or ENMTools model object containing a suitability raster.
y	Another raster or RasterLayer object, or ENMTools model object containing a suitability raster.
verbose	Controls printing of diagnostic messages

### Value

results A vector containing the three metrics (I, D, and Spearman rank correlation)

### Examples

```
data(iberolacerta.clade)
data(euro.worldclim)
aurelioi.glm <- enmtools.glm(iberolacerta.clade$species$aurelioi,
euro.worldclim, f = pres ~ bio1 + bio12)
aranica.glm <- enmtools.glm(iberolacerta.clade$species$aranica,
euro.worldclim, f = pres ~ bio1 + bio12)
raster.overlap(aurelioi.glm, aranica.glm)
```

---

raster.pca	<i>raster.pca, PCA on a set of environmental rasters</i>
------------	--

---

### Description

raster.pca, PCA on a set of environmental rasters

### Usage

```
raster.pca(env, n)
```

**Arguments**

env                    A set of environmental layers  
 n                      The number of PCA layers to return

**Value**

A list containing a stack of rasters representing the top n pca axes of the initial environmental variables, as well as the pca object from the analysis that produced them.

**Examples**

```
env.pca <- raster.pca(euro.worldclim, 2)
```

---

raster.resid	<i>raster.resid Measure standardized residuals from a linear regression between two rasters.</i>
--------------	--

---

**Description**

This function builds a linear model for the relationship between two rasters, and returns the linear model and a spatial raster of the residuals from that model.

**Usage**

```
raster.resid(x, y)
```

**Arguments**

x                      A raster or RasterLayer object, or ENMTools model object containing a suitability raster.  
 y                      Another raster or RasterLayer object, or ENMTools model object containing a suitability raster.

**Value**

results A list containing a raster of residuals from a linear regression between the two supplied rasters and the linear model itself.

**Examples**

```
data(euro.worldclim)
raster.resid(euro.worldclim[[1]], euro.worldclim[[2]])
```

---

raster.standardize	<i>raster.standardize, standardizes all values in a raster file</i>
--------------------	---

---

### Description

This function is used by a lot of the metrics calculated by ENMTools, in order to standardize suitability scores so they sum to 1 over a geographic space.

### Usage

```
raster.standardize(x, verbose = FALSE)
```

### Arguments

x	A raster or RasterLayer object, or an ENMTools model object containing a suitability raster.
verbose	Controls printing of diagnostic messages

### Value

A new raster object, standardized so that values sum to 1

### Examples

```
data(euro.worldclim)
raster.standardize(euro.worldclim[[1]])
```

---

sim.points	<i>Simulate a point process from an enmtools.model object</i>
------------	---

---

### Description

Function that takes an `enmtools.model` object and simulates points from it using a point process.

### Usage

```
sim.points(
  object,
  n.points = 1000,
  seed = NA,
  sample.type = "ppp",
  replace = FALSE,
  threshold = NA,
  ...
)
```

**Arguments**

object	entools.model object to simulate from
n.points	approximate number of points to simulate. You may get small number fewer or greater. If you need an exact number of points, generate too many, then drop the extra ones.
seed	optional seed for the random number generator
sample.type	method for sampling occurrence points. Default is "ppp", which is a poisson point process. Also accepts "binomial" for treating suitabilities as binomial trials, "thresh.pa" for sampling with equal probability every grid cell above a certain threshold value, and "thresh.con" for sampling in proportion to suitability above a certain threshold value.
replace	whether to sample with replacement.
threshold	a threshold suitability below which probability of sampling drops to zero. Used for "thresh.pa" and "thresh.con" sampling.
...	additional parameters, not currently used but included for S3 compatability

**Value**

A data frame of simulated points from the entools.model object

---

species.from.file	<i>Takes a csv file and uses it to construct one or more entools.species objects. It constructs one object per unique value in the "species.col" column.</i>
-------------------	--

---

**Description**

Takes a csv file and uses it to construct one or more entools.species objects. It constructs one object per unique value in the "species.col" column.

**Usage**

```
species.from.file(filename, species.col = "species")
```

**Arguments**

filename	Name of a .csv file
species.col	Name of the column from the csv file to use for species names. Default is "species".

**Value**

A list containing species objects, one for each unique value in species.col.

---

<code>threespace.plot</code>	<i>threespace.plot, A plot that compares the environmental distribution of presence points, background points, and the set of supplied environmental layers.</i>
------------------------------	--

---

### Description

`threespace.plot`, A plot that compares the environmental distribution of presence points, background points, and the set of supplied environmental layers.

### Usage

```
threespace.plot(model, env, maxpts = NA)
```

### Arguments

<code>model</code>	An <code>enmtools.model</code> object
<code>env</code>	A set of environment layers
<code>maxpts</code>	Maximum number of points to plot from env layers

### Value

A `ggplot2` object that plots the distribution of environments in the climate layers to the distribution of environments at background and presence localities.

### Examples

```
my.model<- enmtools.gam(iberolacerta.clade$species$monticola, euro.worldclim)
threespace.plot(my.model, euro.worldclim)
```

---

<code>trimdups.by.raster</code>	<i>Takes a set of points and a raster mask and returns a data frame trimmed so that only one point is returned per grid cell in the mask raster.</i>
---------------------------------	--

---

### Description

Takes a set of points and a raster mask and returns a data frame trimmed so that only one point is returned per grid cell in the mask raster.

### Usage

```
trimdups.by.raster(points, mask)
```

**Arguments**

points	A two column data frame with X and Y coordinates
mask	A raster to use as a mask for drawing points

**Value**

A new data frame with one point per grid cell.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
pts <- iberolacerta.clade$species$monticola$presence.points
trimdups.by.raster(pts, euro.worldclim)
```

---

visualize.enm	<i>visualize.enm, Makes a heatmap of suitability of habitat in environment space according to a given model</i>
---------------	---

---

**Description**

visualize.enm, Makes a heatmap of suitability of habitat in environment space according to a given model

**Usage**

```
visualize.enm(
  model,
  env,
  nbins = 100,
  layers = names(env)[1:2],
  plot.test.data = FALSE,
  plot.points = TRUE,
  minmax = NA
)
```

**Arguments**

model	An enmtools.model object
env	A set of environmental layers
nbins	The number of bins per layer to use for drawing environment space
layers	A vector of layer names to use for drawing environment space
plot.test.data	Logical determining whether test data should be plotted, if present. If test data is plotted, it will appear as translucent green triangles.
plot.points	Logical determining whether presence points should be plotted on suitability plot
minmax	A named list of minima and maxima for each axis, in case the user wants to constrain or expand the space over which models are plotted.

**Value**

suit.plot A list containing two dimensional plot of an ENM in environment space and a plot of the available environments.

**Examples**

```
data(iberolacerta.clade)
data(euro.worldclim)
aurelioi.glm <- enmtools.glm(iberolacerta.clade$species$aurelioi, euro.worldclim,
f = pres ~ poly(bio1, 4) + poly(bio12, 4))
visualize.enm(aurelioi.glm, euro.worldclim, layers = c("bio1", "bio12"))
```

---

visualize.overlap	<i>visualize.overlap, Makes a contour map of suitability of habitat in environment space for two models</i>
-------------------	---

---

**Description**

visualize.overlap, Makes a contour map of suitability of habitat in environment space for two models

**Usage**

```
visualize.overlap(
  model.1,
  model.2,
  env,
  nbins = 100,
  layers,
  plot.points = TRUE
)
```

**Arguments**

model.1	An enmtools.model object
model.2	An enmtools.model object
env	A set of environmental layers
nbins	The number of bins per layer to use for drawing environment space
layers	A vector of layer names to use for drawing environment space
plot.points	Logical determining whether presence points should be plotted on suitability plot

**Value**

overlap.plot A two dimensional plot of an ENM

**Examples**

```
data(iberolacerta.clade)
ar <- iberolacerta.clade$species$aranica
au <- iberolacerta.clade$species$aurelioi
data(euro.worldclim)
aranica.bc <- enmtools.bc(ar, euro.worldclim)
aurelioi.bc <- enmtools.bc(au, euro.worldclim)
visualize.overlap(aranica.bc, aurelioi.bc, euro.worldclim, layers = c("bio1", "bio9"))
```

# Index

- \* **background**
  - background.test, 6
  - threespace.plot, 60
- \* **barrier**
  - rangebreak.blob, 48
  - rangebreak.linear, 50
  - rangebreak.ribbon, 51
- \* **biogeography**
  - rangebreak.blob, 48
  - rangebreak.linear, 50
  - rangebreak.ribbon, 51
- \* **breadth**
  - calc.B1, 7
  - calc.B2, 8
- \* **comparison**
  - threespace.plot, 60
- \* **correlation**
  - raster.resid, 57
- \* **datasets**
  - euro.worldclim, 37
  - iberolacerta.clade, 39
- \* **enmtools**
  - background.test, 6
  - identity.test, 40
  - rangebreak.blob, 48
  - rangebreak.linear, 50
  - rangebreak.ribbon, 51
- \* **enm**
  - calc.B1, 7
  - calc.B2, 8
  - enmtools.ecospat.bg, 18
  - enmtools.ecospat.id, 20
  - marginal.plots, 44
  - visualize.enm, 61
  - visualize.overlap, 62
- \* **environment**
  - multistack.pca, 46
  - raster.pca, 56
  - threespace.plot, 60
- \* **equivalency**
  - background.test, 6
  - identity.test, 40
- \* **extrapolation**
  - threespace.plot, 60
- \* **hypothesis-testing**
  - identity.test, 40
  - rangebreak.blob, 48
  - rangebreak.linear, 50
  - rangebreak.ribbon, 51
- \* **hypothesis**
  - background.test, 6
- \* **identity**
  - identity.test, 40
- \* **keywords**
  - raster.breadth, 53
  - raster.overlap, 56
  - raster.standardize, 58
- \* **niche**
  - calc.B1, 7
  - calc.B2, 8
  - enmtools.ecospat.bg, 18
  - enmtools.ecospat.id, 20
  - visualize.enm, 61
  - visualize.overlap, 62
- \* **overlap**
  - visualize.overlap, 62
- \* **pca**
  - multistack.pca, 46
  - raster.pca, 56
  - threespace.plot, 60
- \* **plot**
  - enmtools.ecospat.bg, 18
  - enmtools.ecospat.id, 20
  - marginal.plots, 44
  - visualize.enm, 61
  - visualize.overlap, 62
- \* **presence**
  - threespace.plot, 60

- \* **rangebreak**
  - rangebreak.blob, 48
  - rangebreak.linear, 50
  - rangebreak.ribbon, 51
- \* **raster**
  - multistack.pca, 46
  - raster.pca, 56
  - raster.resid, 57
- \* **residuals**
  - raster.resid, 57
- \* **response**
  - marginal.plots, 44
- \* **sdm**
  - calc.B1, 7
  - calc.B2, 8
  - enmttools.ecospat.bg, 18
  - enmttools.ecospat.id, 20
  - marginal.plots, 44
  - visualize.enm, 61
  - visualize.overlap, 62
- \* **testing**
  - background.test, 6
- add.env, 3
- background.points.buffer, 4
- background.raster.buffer, 4
- background.shape.buffer, 5
- background.test, 6
- calc.B1, 7
- calc.B2, 8
- check.bg, 9
- check.clade, 9
- check.species, 10
- clamp.env, 11
- combine.species, 11
- drop.species, 12
- enmttools.aoc, 13
- enmttools.bc, 14
- enmttools.calibrate, 15
- enmttools.clade, 16
- enmttools.dm, 17
- enmttools.ecospat.bg, 18
- enmttools.ecospat.id, 20
- enmttools.gam, 21
- enmttools.glm, 23
- enmttools.hypervolume, 24
- enmttools.maxent, 26
- enmttools.ppmlasso, 27
- enmttools.rf, 29
- enmttools.rf.ranger, 30
- enmttools.species, 32, 44
- enmttools.vip, 33
- env.breadth, 34
- env.evaluate, 35
- env.overlap, 36
- euro.worldclim, 37
- geog.range.overlap, 38
- hypervolume.overlap, 38
- iberolacerta.clade, 39
- identity.test, 40
- install.extras, 41
- interactive.plot, 42
- interactive.plot.enmttools.model, 43
- interactive.plot.enmttools.species, 44
- leaflet, 42–44
- marginal.plots, 44
- moses.list, 45
- multistack.pca, 46
- node.overlap, 47
- point.overlap, 47
- rangebreak.blob, 48
- rangebreak.linear, 50
- rangebreak.ribbon, 51
- ranger, 31
- raster.breadth, 53
- raster.cor, 54
- raster.cor.matrix, 54
- raster.cor.plot, 55
- raster.overlap, 56
- raster.pca, 56
- raster.resid, 57
- raster.standardize, 58
- sim.points, 58
- species.from.file, 59
- threespace.plot, 60

`trimdups.by.raster`, [60](#)

`visualize.enm`, [61](#)

`visualize.overlap`, [62](#)