

Package ‘PNADcIBGE’

March 6, 2020

Type Package

Title Downloading, Reading and Analysing PNADC Microdata

Version 0.6.0

Description Provides tools for downloading, reading, and analysing the PNADC household survey from Brazilian Institute of Geography and Statistics - IBGE. The data must be downloaded from the official website <<https://www.ibge.gov.br/>>. Further analyses must be made using package 'survey'.

Depends R (>= 3.2.0)

Imports survey, readr, dplyr, magrittr, RCurl, utils, timeDate, readxl, tibble

Suggests tidyverse, convey

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.0.1

NeedsCompilation no

Author Douglas Braga [aut],
Gabriel Assuncao [aut, cre],
Luna Hidalgo [ctb]

Maintainer Gabriel Assuncao <pacotepnadc@ibge.gov.br>

Repository CRAN

Date/Publication 2020-03-06 16:00:18 UTC

R topics documented:

| | |
|--------------------------|---|
| get_pnadc | 2 |
| pnadc_deflator | 4 |
| pnadc_design | 5 |
| pnadc_example | 6 |
| pnadc_labeller | 7 |
| read_pnadc | 9 |

Index**11**

| | |
|-----------|---|
| get_pnadc | <i>Download, label, deflate and create survey design object for PNADC microdata</i> |
|-----------|---|

Description

Core function of package. With this function only, the user can download a PNADC microdata from a year or quarter and get a sample design object ready to use with survey package functions.

Usage

```
get_pnadc(
  year,
  quarter = NULL,
  interview = NULL,
  topic = NULL,
  vars = NULL,
  defyear = NULL,
  defperiod = NULL,
  labels = TRUE,
  deflator = TRUE,
  design = TRUE,
  savedir = tempdir()
)
```

Arguments

| | |
|-----------|---|
| year | The year of the data to be downloaded. Must be a number between 2012 and current year. Vector not accepted. |
| quarter | The quarter of the year of the data to be downloaded. Must be number from 1 to 4. Vector not accepted. If NULL, interview or topic number must be provided. |
| interview | The interview number of the data to be downloaded. Must be number from 1 to 5. Vector not accepted. Using this option will get annual per interview data. If NULL, quarter or topic number must be provided. |
| topic | The quarter related to the topic of the data to be downloaded. Must be number from 1 to 4. Vector not accepted. Using this option will get annual per topic data. If NULL, quarter or interview number must be provided. |
| vars | Vector of variable names to be kept for analysis. Default is to keep all variables. |
| defyear | The year of the deflator data to be downloaded for annual microdata. Must be a number between 2017 and the last available year. Vector not accepted. If NULL, the deflator year will be defined as the last year available for interview microdata, or as equal to year for topic microdata. When quarter is defined, this argument will be ignored. This argument will be used only if deflator was set as TRUE. |

| | |
|-----------|---|
| defperiod | The quarter period of the deflator data to be downloaded for annual per topic microdata. Must be number from 1 to 4. Vector not accepted. If NULL, the deflator period will be defined as equal to topic. When quarter or interview is defined, this argument will be ignored. This argument will be used only if deflator was set as TRUE. |
| labels | Logical value. If TRUE, categorical variables will presented as factors with labels corresponding to the survey's dictionary. |
| deflator | Logical value. If TRUE, deflators variables will be available for use in the microdata. |
| design | Logical value. If TRUE, will return an object of class survey.design. It is strongly recommended to keep this parameter as TRUE for further analysis. If FALSE, only the microdata will be returned. |
| savedir | Directory to save the downloaded data. Default is to use a temporary directory. |

Value

An object of class survey.design with the data from PNADC and its sample design, or a tibble with selected variables of the microdata, including the necessary survey design ones.

Note

For more information, visit the survey official website <<https://www.ibge.gov.br/estatisticas/sociais/trabalho/9171-pesquisa-nacional-por-amostra-de-domicilios-continua-mensal.html?&t=o-que-e>> and consult the other functions of this package, described below.

See Also

[read_pnadc](#) for reading PNADC microdata.
[pnadc_labeller](#) for labelling categorical variables from PNADC microdata.
[pnadc_deflator](#) for adding deflators variables to PNADC microdata.
[pnadc_design](#) for creating PNADC survey design object.
[pnadc_example](#) for getting the path of the quarter PNADC example files.

Examples

```
## Not run:
pnadc.svy <- get_pnadc(year=2017, quarter=4, vars=c("VD4001", "VD4002"), defyear=2017, defperiod=4,
                    labels=TRUE, deflator=TRUE, design=TRUE, savedir=tempdir())
survey::svymean(x=~VD4002, design=pnadc.svy, na.rm=TRUE)
pnadc.svy2 <- get_pnadc(year=2017, interview=5, vars=c("V4112", "V4121B"), defyear=2017, defperiod=4,
                    labels=TRUE, deflator=TRUE, design=TRUE, savedir=tempdir())
survey::svymean(x=~V4121B, design=pnadc.svy2, na.rm=TRUE)
pnadc.svy3 <- get_pnadc(year=2017, topic=4, vars=c("S01022", "S01025"), defyear=2017, defperiod=4,
                    labels=TRUE, deflator=TRUE, design=TRUE, savedir=tempdir())
survey::svymean(x=~S01022, design=pnadc.svy3, na.rm=TRUE)
## End(Not run)
```

pnadc_deflator *Add deflators variables to PNADC microdata*

Description

This function adds deflators variables to PNADC microdata. For deflation of income variables, the documentation provided through the following addresses must be used:

Quarter - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Trimestral/Microdados/Documentacao/PNADCIBGE_Deflator_Trimestral.pdf.

Annual per Interview - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Visita/Documentacao_Geral/PNADCIBGE_Deflator_Anual_Visita.pdf.

Annual per Topic - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Trimestre/Documentacao_Geral/PNADCIBGE_Deflator_Anual_Trimestre.pdf.

Usage

```
pnadc_deflator(data_pnadc, deflator.file)
```

Arguments

| | |
|---------------|---|
| data_pnadc | A tibble of PNADC microdata read with read_pnadc function. |
| deflator.file | The deflator file for selected survey available on official website: Quarter - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Trimestral/Microdados/Documentacao/Deflatores.zip . Annual per Interview (select a deflator xls file, according to the appropriated year) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Visita/Documentacao_Geral/ . Annual per Topic (select a deflator xls file, according to the appropriated period and, then, inside the documentation folder, choose the desired year) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Trimestre/ . |

Value

A tibble with the data provided from PNADC survey and the deflators variables added for use.

Note

For more information, visit the survey official website <<https://www.ibge.gov.br/estatisticas/sociais/trabalho/9171-pesquisa-nacional-por-amostra-de-domicilios-continua-mensal.html?&t=o-que-e>> and consult the other functions of this package, described below.

See Also

[get_pnadc](#) for downloading, labelling, deflating and creating survey design object for PNADC microdata.

[read_pnadc](#) for reading PNADC microdata.

[pnadc_labeller](#) for labelling categorical variables from PNADC microdata.

[pnadc_design](#) for creating PNADC survey design object.

[pnadc_example](#) for getting the path of the quarter PNADC example files.

Examples

```
# Using data read from disk
input_path <- pnadc_example(path="input_example.txt")
data_path <- pnadc_example(path="exampledata.txt")
dictionary.path <- pnadc_example(path="dictionaryexample.xls")
deflator.path <- pnadc_example(path="deflatorexample.xls")
pnadc.df <- read_pnadc(microdata=data_path, input_txt=input_path, vars="VD4002")
pnadc.df <- pnadc_labeller(data_pnadc=pnadc.df, dictionary.file=dictionary.path)
pnadc.df <- pnadc_deflator(data_pnadc=pnadc.df, deflator.file=deflator.path)
## Not run:
# Downloading data
pnadc.df2 <- get_pnadc(year=2017, quarter=4, vars="VD4002", defyear=2017, defperiod=4,
  labels=TRUE, deflator=FALSE, design=FALSE, savedir=tempdir())
deflator.path2 <- pnadc_example(path="deflatorexample.xls")
pnadc.df2 <- pnadc_deflator(data_pnadc=pnadc.df2, deflator.file=deflator.path2)
## End(Not run)
```

pnadc_design

Create PNADC survey object with its sample design

Description

This function creates PNADC survey object with its sample design for analysis using survey package functions.

Usage

```
pnadc_design(data_pnadc)
```

Arguments

`data_pnadc` A tibble of PNADC microdata read with `read_pnadc` function.

Value

An object of class `survey.design` with the data from PNADC and its sample design.

Note

For more information, visit the survey official website <<https://www.ibge.gov.br/estatisticas/sociais/trabalho/9171-pesquisa-nacional-por-amostra-de-domicilios-continua-mensal.html?=&t=o-que-e>> and consult the other functions of this package, described below.

See Also

[get_pnadc](#) for downloading, labelling, deflating and creating survey design object for PNADC microdata.

[read_pnadc](#) for reading PNADC microdata.

[pnadc_labeller](#) for labelling categorical variables from PNADC microdata.

[pnadc_deflator](#) for adding deflators variables to PNADC microdata.

[pnadc_example](#) for getting the path of the quarter PNADC example files.

Examples

```
# Using data read from disk
input_path <- pnadc_example(path="input_example.txt")
data_path <- pnadc_example(path="exampledata.txt")
dictionary.path <- pnadc_example(path="dictionaryexample.xls")
deflator.path <- pnadc_example(path="deflatorexample.xls")
pnadc.df <- read_pnadc(microdata=data_path, input_txt=input_path, vars="VD4002")
pnadc.df <- pnadc_labeller(data_pnadc=pnadc.df, dictionary.file=dictionary.path)
pnadc.df <- pnadc_deflator(data_pnadc=pnadc.df, deflator.file=deflator.path)
## Not run:
pnadc.svy <- pnadc_design(data_pnadc=pnadc.df)
# Calculating unemployment rate
survey::svymean(x=~VD4002, design=pnadc.svy, na.rm=TRUE)
## End(Not run)
## Not run:
# Downloading data
pnadc.df2 <- get_pnadc(year=2017, quarter=4, vars="VD4002", defyear=2017, defperiod=4,
                      labels=TRUE, deflator=TRUE, design=FALSE, savedir=tempdir())
pnadc.svy2 <- pnadc_design(data_pnadc=pnadc.df2)
# Calculating unemployment rate
survey::svymean(x=~VD4002, design=pnadc.svy2, na.rm=TRUE)
## End(Not run)
```

pnadc_example

Get the path of the quarter PNADC example files

Description

This function provides the path of the quarter PNADC example files, loaded with this package.

Usage

```
pnadc_example(path = NULL)
```

Arguments

path Name of file. If NULL, the quarter PNADC example files names will be listed.

Value

A vector with names of all the available quarter PNADC example files or the path for specific requested quarter PNADC example file.

Note

For more information, visit the survey official website <<https://www.ibge.gov.br/estatisticas/sociais/trabalho/9171-pesquisa-nacional-por-amostra-de-domicilios-continua-mensal.html?=&t=o-que-e>> and consult the other functions of this package, described below.

See Also

[get_pnadc](#) for downloading, labelling, deflating and creating survey design object for PNADC microdata.

[read_pnadc](#) for reading PNADC microdata.

[pnadc_labeller](#) for labelling categorical variables from PNADC microdata.

[pnadc_deflator](#) for adding deflators variables to PNADC microdata.

[pnadc_design](#) for creating PNADC survey design object.

Examples

```
pnadc_example()  
pnadc_example(path="exempladata.txt")  
pnadc_example(path="input_example.txt")  
pnadc_example(path="dictionaryexample.xls")  
pnadc_example(path="deflatorexample.xls")
```

pnadc_labeller *Label categorical variables from PNADC microdata*

Description

This function labels categorical variables from PNADC microdata.

Usage

```
pnadc_labeller(data_pnadc, dictionary.file)
```

Arguments

`data_pnadc` A tibble of PNADC microdata read with `read_pnadc` function.

`dictionary.file` The dictionary file for selected survey available on official website:
 Quarter - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Trimestral/Microdados/Documentacao/Dicionario_e_input.zip.
 Annual per Interview (select a dictionary xls file, according to the appropriated interview and, then, inside the documentation folder, choose the desired year) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Visita/.
 Annual per Topic (select a dictionary xls file, according to the appropriated quarter related to the topic, inside the documentation folder) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Trimestre/.

Value

A tibble with the data provided from PNADC survey and its categorical variables as factors with related labels.

Note

For more information, visit the survey official website <<https://www.ibge.gov.br/estatisticas/sociais/trabalho/9171-pesquisa-nacional-por-amostra-de-domicilios-continua-mensal.html?=&t=o-que-e>> and consult the other functions of this package, described below.

See Also

[get_pnadc](#) for downloading, labelling, deflating and creating survey design object for PNADC microdata.

[read_pnadc](#) for reading PNADC microdata.

[pnadc_deflator](#) for adding deflators variables to PNADC microdata.

[pnadc_design](#) for creating PNADC survey design object.

[pnadc_example](#) for getting the path of the quarter PNADC example files.

Examples

```
# Using data read from disk
input_path <- pnadc_example(path="input_example.txt")
data_path <- pnadc_example(path="exampledata.txt")
dictionary.path <- pnadc_example(path="dictionaryexample.xls")
pnadc.df <- read_pnadc(microdata=data_path, input_txt=input_path, vars="VD4002")
pnadc.df <- pnadc_labeller(data_pnadc=pnadc.df, dictionary.file=dictionary.path)
## Not run:
# Downloading data
pnadc.df2 <- get_pnadc(year=2017, quarter=4, vars="VD4002", defyear=2017, defperiod=4,
  labels=FALSE, deflator=FALSE, design=FALSE, savedir=tempdir())
dictionary.path2 <- pnadc_example(path="dictionaryexample.xls")
pnadc.df2 <- pnadc_labeller(data_pnadc=pnadc.df2, dictionary.file=dictionary.path2)
```



```
## End(Not run)
```

| | |
|------------|-----------------------------|
| read_pnadc | <i>Read PNADC microdata</i> |
|------------|-----------------------------|

Description

This function reads PNADC microdata.

Usage

```
read_pnadc(microdata, input_txt, vars = NULL)
```

Arguments

| | |
|-----------|---|
| microdata | <p>A text file containing microdata from PNADC survey, available on official website:</p> <p>Quarter (select a microdata file, according to the appropriated year and, then, quarter) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Trimestral/Microdados/.</p> <p>Annual per Interview (select a microdata file, according to the appropriated interview and, then, inside the data folder, choose the desired year) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Visita/.</p> <p>Annual per Topic (select a microdata file, according to the appropriated quarter related to the topic and, then, inside the data folder, choose the desired year) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Trimestre/.</p> |
| input_txt | <p>A text file, related to the microdata, containing the input script for SAS, available on official website:</p> <p>Quarter - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Trimestral/Microdados/Documentacao/Dicionario_e_input.zip.</p> <p>Annual per Interview (select a input txt file, according to the appropriated interview and, then, inside the documentation folder, choose the desired year) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Visita/.</p> <p>Annual per Topic (select a input txt file, according to the appropriated quarter related to the topic, inside the documentation folder) - ftp://ftp.ibge.gov.br/Trabalho_e_Rendimento/Pesquisa_Nacional_por_Amostra_de_Domicilios_continua/Anual/Microdados/Trimestre/.</p> |
| vars | Vector of variable names to be kept for analysys. Default is to keep all variables. |

Value

A tibble with selected variables of the microdata, including the necessary survey design ones.

Note

For more information, visit the survey official website <<https://www.ibge.gov.br/estatisticas/sociais/trabalho/9171-pesquisa-nacional-por-amostra-de-domicilios-continua-mensal.html?=&t=o-que-e>> and consult the other functions of this package, described below.

See Also

[get_pnadc](#) for downloading, labelling, deflating and creating survey design object for PNADC microdata.

[pnadc_labeller](#) for labelling categorical variables from PNADC microdata.

[pnadc_deflator](#) for adding deflators variables to PNADC microdata.

[pnadc_design](#) for creating PNADC survey design object.

[pnadc_example](#) for getting the path of the quarter PNADC example files.

Examples

```
input_path <- pnadc_example(path="input_example.txt")
data_path <- pnadc_example(path="exempladata.txt")
pnadc.df <- read_pnadc(microdata=data_path, input_txt=input_path, vars="VD4002")
```

Index

`get_pnadc`, 2, 5–8, 10

`pnadc_deflator`, 3, 4, 6–8, 10

`pnadc_design`, 3, 5, 5, 7, 8, 10

`pnadc_example`, 3, 5, 6, 6, 8, 10

`pnadc_labeller`, 3, 5–7, 7, 10

`read_pnadc`, 3, 5–8, 9