

# Package ‘RSQlite’

May 6, 2018

**Title** 'SQLite' Interface for R

**Version** 2.1.1

**Date** 2018-05-05

**Description** Embeds the 'SQLite' database engine in R and provides an interface compliant with the 'DBI' package. The source for the 'SQLite' engine is included.

**License** LGPL (>= 2)

**URL** <https://github.com/r-dbi/RSQlite>

**BugReports** <https://github.com/r-dbi/RSQlite/issues>

**Depends** R (>= 3.1.0)

**Imports** bit64, blob (>= 1.1.1), DBI (>= 1.0.0), memoise, methods, pkgconfig, Rcpp (>= 0.12.7)

**Suggests** DBITest, knitr, rmarkdown, testthat

**LinkingTo** BH, plogr (>= 0.2.0), Rcpp

**VignetteBuilder** knitr

**Encoding** UTF-8

**RoxygenNote** 6.0.1.9000

**Collate** 'RcppExports.R' 'SQLiteConnection.R' 'SQLiteDriver.R'  
'SQLiteResult.R' 'coerce.R' 'connect.R' 'copy.R' 'datasetsDb.R'  
'deprecated.R' 'export.R' 'extensions.R' 'names.R' 'query.R'  
'rownames.R' 'table.R' 'transactions.R' 'utils.R' 'zzz.R'

**NeedsCompilation** yes

**Author** Kirill Müller [aut, cre] (<<https://orcid.org/0000-0002-1416-3412>>),  
Hadley Wickham [aut],  
David A. James [aut],  
Seth Falcon [aut],  
SQLite Authors [ctb] (for the included SQLite sources),  
Liam Healy [ctb] (for the included SQLite sources),  
R Consortium [fnd],  
RStudio [cph]

**Maintainer** Kirill Müller <krlmlr+r@mailbox.org>

**Repository** CRAN

**Date/Publication** 2018-05-06 17:55:15 UTC

## R topics documented:

<i>datasetsDb</i> . . . . .	2
<i>dbReadTable</i> , <i>SQLiteConnection</i> , <i>character-method</i> . . . . .	3
<i>dbWriteTable</i> , <i>SQLiteConnection</i> , <i>character</i> , <i>data.frame-method</i> . . . . .	4
<i>initExtension</i> . . . . .	6
<i>rssqliteVersion</i> . . . . .	6
<i>SQLite</i> . . . . .	7
<i>sqlite-transaction</i> . . . . .	9
<i>sqliteCopyDatabase</i> . . . . .	10

<b>Index</b>	12
--------------	----

*datasetsDb*                   *A sample sqlite database*

### Description

This database is bundled with the package, and contains all data frames in the datasets package.

### Usage

```
datasetsDb()
```

### Examples

```
library(DBI)
db <- RSQLite:::datasetsDb()
dbListTables(db)

dbReadTable(db, "CO2")
dbGetQuery(db, "SELECT * FROM CO2 WHERE conc < 100")

dbDisconnect(db)
```

---

**dbReadTable,SQLiteConnection,character-method**

*Read a database table*

---

## Description

Returns the contents of a database table given by name as a data frame.

## Usage

```
## S4 method for signature 'SQLiteConnection,character'  
dbReadTable(conn, name, ...,  
           row.names = pkgconfig::get_config("RSQLite:::row.names.table", FALSE),  
           check.names = TRUE, select.cols = NULL)
```

## Arguments

conn	a <a href="#">SQLiteConnection</a> object, produced by <a href="#">DBI:::dbConnect()</a>
name	a character string specifying a table name. SQLite table names are <i>not</i> case sensitive, e.g., table names ABC and abc are considered equal.
...	Needed for compatibility with generic. Otherwise ignored.
row.names	Either TRUE, FALSE, NA or a string. If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector. A string is equivalent to TRUE, but allows you to override the default name. For backward compatibility, NULL is equivalent to FALSE.
check.names	If TRUE, the default, column names will be converted to valid R identifiers.
select.cols	Deprecated, do not use.

## Details

Note that the data frame returned by dbReadTable() only has primitive data, e.g., it does not coerce character data to factors.

## Value

A data frame.

## See Also

The corresponding generic function [DBI:::dbReadTable\(\)](#).

## Examples

```
library(DBI)
db <- RSQLite:::datasetsDb()
dbReadTable(db, "mtcars")
dbReadTable(db, "mtcars", row.names = FALSE)
dbDisconnect(db)
```

`dbWriteTable,SQLiteConnection,character,data.frame-method`  
*Write a local data frame or file to the database*

## Description

Functions for writing data frames or delimiter-separated files to database tables.

## Usage

```
## S4 method for signature 'SQLiteConnection,character,data.frame'
dbWriteTable(conn, name,
             value, ..., row.names = pkgconfig::get_config("RSQLite:::row.names.table",
             FALSE), overwrite = FALSE, append = FALSE, field.types = NULL,
             temporary = FALSE)

## S4 method for signature 'SQLiteConnection,character,character'
dbWriteTable(conn, name, value,
             ..., field.types = NULL, overwrite = FALSE, append = FALSE,
             header = TRUE, colClasses = NA, row.names = FALSE, nrow = 50,
             sep = ",", eol = "\n", skip = 0, temporary = FALSE)
```

## Arguments

conn	a <a href="#">SQLiteConnection</a> object, produced by <a href="#">DBI::dbConnect()</a>
name	a character string specifying a table name. SQLite table names are <i>not</i> case sensitive, e.g., table names ABC and abc are considered equal.
value	a data.frame (or coercible to data.frame) object or a file name (character). In the first case, the data.frame is written to a temporary file and then imported to SQLite; when value is a character, it is interpreted as a file name and its contents imported to SQLite.
...	Needed for compatibility with generic. Otherwise ignored.
row.names	A logical specifying whether the <code>row.names</code> should be output to the output DBMS table; if TRUE, an extra field whose name will be whatever the R identifier "row.names" maps to the DBMS (see <a href="#">DBI::make.db.names()</a> ). If NA will add rows names if they are characters, otherwise will ignore.
overwrite	a logical specifying whether to overwrite an existing table or not. Its default is FALSE.

append	a logical specifying whether to append to an existing table in the DBMS. Its default is FALSE.
field.types	character vector of named SQL field types where the names are the names of new table's columns. If missing, types inferred with <a href="#">DBI::dbDataType()</a> .
temporary	a logical specifying whether the new table should be temporary. Its default is FALSE.
header	is a logical indicating whether the first data line (but see skip) has a header or not. If missing, its value is determined following <a href="#">read.table()</a> convention, namely, it is set to TRUE if and only if the first row has one fewer field than the number of columns.
colClasses	Character vector of R type names, used to override defaults when imputing classes from on-disk file.
nrows	Number of rows to read to determine types.
sep	The field separator, defaults to ',', '.
eol	The end-of-line delimiter, defaults to '\n'.
skip	number of lines to skip before reading the data. Defaults to 0.

## Details

In a primary key column qualified with **AUTOINCREMENT**, missing values will be assigned the next largest positive integer, while nonmissing elements/cells retain their value. If the autoincrement column exists in the data frame passed to the value argument, the NA elements are overwritten. Similarly, if the key column is not present in the data frame, all elements are automatically assigned a value.

## See Also

The corresponding generic function [DBI::dbWriteTable\(\)](#).

## Examples

```
con <- dbConnect(SQLite())
dbWriteTable(con, "mtcars", mtcars)
dbReadTable(con, "mtcars")

# A zero row data frame just creates a table definition.
dbWriteTable(con, "mtcars2", mtcars[0, ])
dbReadTable(con, "mtcars2")

dbDisconnect(con)
```

<code>initExtension</code>	<i>Add useful extension functions</i>
----------------------------	---------------------------------------

## Description

These extension functions are written by Liam Healy and made available through the SQLite website (<http://www.sqlite.org/contrib>).

## Usage

```
initExtension(db)
```

## Arguments

`db` A [SQLiteConnection](#) object to load these extensions into.

## Available extension functions

**Math functions** `acos`, `acosh`, `asin`, `asinh`, `atan`, `atan2`, `atanh`, `atn2`, `ceil`, `cos`, `cosh`, `cot`, `coth`, `degrees`, `difference`, `exp`, `floor`, `log`, `log10`, `pi`, `power`, `radians`, `sign`, `sin`, `sinh`, `sqrt`, `square`, `tan`, `tanh`

**String functions** `charindex`, `leftstr`, `ltrim`, `padc`, `padl`, `padr`, `proper`, `replace`, `replicate`, `reverse`, `rightstr`, `rtrim`, `strfilter`, `trim`

**Aggregate functions** `stdev`, `variance`, `mode`, `median`, `lower_quartile`, `upper_quartile`

## Examples

```
library(DBI)
db <- RSQLite:::datasetsDb()
RSQLite:::initExtension(db)

dbGetQuery(db, "SELECT stdev(mpg) FROM mtcars")
sd(mtcars$mpg)
dbDisconnect(db)
```

<code>rssqliteVersion</code>	<i>RSQLite version</i>
------------------------------	------------------------

## Description

RSQLite version

## Usage

```
rssqliteVersion()
```

**Value**

A character vector containing header and library versions of RSQLite.

**Examples**

```
RSQLite:::rsqliteVersion()
```

`SQLite`

*Connect to an SQLite database*

**Description**

Together, `SQLite()` and `dbConnect()` allow you to connect to a SQLite database file. See [DBI:::dbSendQuery\(\)](#) for how to issue queries and receive results.

**Usage**

```
SQLite(...)

## S4 method for signature 'SQLiteDriver'
dbConnect(drv, dbname = "", ...,
          loadable.extensions = TRUE, default.extensions = loadable.extensions,
          cache_size = NULL, synchronous = "off", flags = SQLITE_RWC,
          vfs = NULL, bigint = c("integer64", "integer", "numeric", "character"))

## S4 method for signature 'SQLiteConnection'
dbConnect(drv, ...)

## S4 method for signature 'SQLiteConnection'
dbDisconnect(conn, ...)
```

**Arguments**

<code>...</code>	In previous versions, <code>SQLite()</code> took arguments. These have now all been moved to <a href="#">dbConnect()</a> , and any arguments here will be ignored with a warning.
<code>drv, conn</code>	An object generated by <a href="#">SQLite()</a> , or an existing <a href="#">SQLiteConnection</a> . If an connection, the connection will be cloned.
<code>dbname</code>	The path to the database file. SQLite keeps each database instance in one single file. The name of the database <i>is</i> the file name, thus database names should be legal file names in the running platform. There are two exceptions: <ul style="list-style-type: none"> <li>• <code>" "</code> will create a temporary on-disk database. The file will be deleted when the connection is closed.</li> <li>• <code">":memory:" or <code>"file::memory:"</code> will create a temporary in-memory database.</code"></li> </ul>
<code>loadable.extensions</code>	When <code>TRUE</code> (default) SQLite3 loadable extensions are enabled. Setting this value to <code>FALSE</code> prevents extensions from being loaded.

**default.extensions**

When TRUE (default) the `initExtension()` function will be called on the new connection. Setting this value to FALSE requires calling `initExtension()` manually.

**cache\_size**

Advanced option. A positive integer to change the maximum number of disk pages that SQLite holds in memory (SQLite's default is 2000 pages). See [http://www.sqlite.org/pragma.html#pragma\\_cache\\_size](http://www.sqlite.org/pragma.html#pragma_cache_size) for details.

**synchronous**

Advanced options. Possible values for `synchronous` are "off" (the default), "normal", or "full". Users have reported significant speed ups using `synchronous = "off"`, and the SQLite documentation itself implies considerable improved performance at the very modest risk of database corruption in the unlikely case of the operating system (*not* the R application) crashing. See [http://www.sqlite.org/pragma.html#pragma\\_synchronous](http://www.sqlite.org/pragma.html#pragma_synchronous) for details.

**flags**

`SQLITE_RWC`: open the database in read/write mode and create the database file if it does not already exist; `SQLITE_RW`: open the database in read/write mode. Raise an error if the file does not already exist; `SQLITE_RO`: open the database in read only mode. Raise an error if the file does not already exist

**vfs**

Select the SQLite3 OS interface. See <http://www.sqlite.org/vfs.html> for details. Allowed values are "unix-posix", "unix-unix-afp", "unix-unix-flock", "unix-dotfile", and "unix-none".

**bigint**

The R type that 64-bit integer types should be mapped to, default is `bit64::integer64`, which allows the full range of 64 bit integers.

**Details**

Connections are automatically cleaned-up after they're deleted and reclaimed by the GC. You can use `DBI::dbDisconnect()` to terminate the connection early, but it will not actually close until all open result sets have been closed (and you'll get a warning message to this effect).

**Value**

`SQLite()` returns an object of class `SQLiteDriver`.

`dbConnect()` returns an object of class `SQLiteConnection`.

**See Also**

The corresponding generic functions `DBI::dbConnect()` and `DBI::dbDisconnect()`.

**Examples**

```
library(DBI)
# Initialize a temporary in memory database and copy a data.frame into it
con <- dbConnect(RSQLite::SQLite(), ":memory:")
data(USArrests)
dbWriteTable(con, "USArrests", USArrests)
dbListTables(con)

# Fetch all query results into a data frame:
```

```
dbGetQuery(con, "SELECT * FROM USArests")

# Or do it in batches
rs <- dbSendQuery(con, "SELECT * FROM USArests")
d1 <- dbFetch(rs, n = 10)      # extract data in chunks of 10 rows
dbHasCompleted(rs)
d2 <- dbFetch(rs, n = -1)      # extract all remaining data
dbHasCompleted(rs)
dbClearResult(rs)

# clean up
dbDisconnect(con)
```

---

**sqlite-transaction**     *SQLLite transaction management*

---

## Description

By default, SQLite is in auto-commit mode. dbBegin() starts a SQLite transaction and turns auto-commit off. dbCommit() and dbRollback() commit and rollback the transaction, respectively and turn auto-commit on. [DBI::dbWithTransaction\(\)](#) is a convenient wrapper that makes sure that dbCommit() or dbRollback() is called.

## Usage

```
## S4 method for signature 'SQLiteConnection'
dbBegin(conn, .name = NULL, ..., name = NULL)

## S4 method for signature 'SQLiteConnection'
dbCommit(conn, .name = NULL, ..., name = NULL)

## S4 method for signature 'SQLiteConnection'
dbRollback(conn, .name = NULL, ...,
           name = NULL)
```

## Arguments

conn	a <a href="#">SQLiteConnection</a> object, produced by <a href="#">DBI::dbConnect()</a>
.name	For backward compatibility, do not use.
...	Needed for compatibility with generic. Otherwise ignored.
name	Supply a name to use a named savepoint. This allows you to nest multiple transaction

## See Also

The corresponding generic functions [DBI::dbBegin\(\)](#), [DBI::dbCommit\(\)](#), and [DBI::dbRollback\(\)](#).

## Examples

```
library(DBI)
con <- dbConnect(SQLite(), ":memory:")
dbWriteTable(con, "arrests", datasets::USArrests)
dbGetQuery(con, "select count(*) from arrests")

dbBegin(con)
rs <- dbSendStatement(con, "DELETE from arrests WHERE Murder > 1")
dbGetRowsAffected(rs)
dbClearResult(rs)

dbGetQuery(con, "select count(*) from arrests")

dbRollback(con)
dbGetQuery(con, "select count(*) from arrests")[1, ]

dbBegin(con)
rs <- dbSendStatement(con, "DELETE FROM arrests WHERE Murder > 5")
dbClearResult(rs)
dbCommit(con)
dbGetQuery(con, "SELECT count(*) FROM arrests")[1, ]

# Named savepoints can be nested -----
dbBegin(con, name = "a")
dbBegin(con, name = "b")
dbRollback(con, name = "b")
dbCommit(con, name = "a")

dbDisconnect(con)
```

*sqliteCopyDatabase*      *Copy a SQLite database*

## Description

Copies a database connection to a file or to another database connection. It can be used to save an in-memory database (created using `dbname = ":memory:"` or `dbname = "file::memory:"`) to a file or to create an in-memory database a copy of another database.

## Usage

```
sqliteCopyDatabase(from, to)
```

## Arguments

- |                   |  |
|-------------------|--|
| <code>from</code> | A <code>SQLiteConnection</code> object. The main database in <code>from</code> will be copied to <code>to</code> . |
| <code>to</code>   | A <code>SQLiteConnection</code> object pointing to an empty database.  |

**Author(s)**

Seth Falcon

**References**

<http://www.sqlite.org/backup.html>

**Examples**

```
library(DBI)
# Copy the built in databaseDb() to an in-memory database
con <- dbConnect(RSQLite::SQLite(), ":memory:")
dbListTables(con)

db <- RSQLite::datasetsDb()
RSQLite::sqliteCopyDatabase(db, con)
dbDisconnect(db)
dbListTables(con)

dbDisconnect(con)
```

# Index

bit64::integer64, 8  
datasetsDb, 2  
dbBegin, SQLiteConnection-method  
    (sqlite-transaction), 9  
dbCommit, SQLiteConnection-method  
    (sqlite-transaction), 9  
dbConnect(), 7  
dbConnect, SQLiteConnection-method  
    (SQLite), 7  
dbConnect, SQLiteDriver-method (SQLite),  
    7  
dbDisconnect, SQLiteConnection-method  
    (SQLite), 7  
DBI::dbBegin(), 9  
DBI::dbCommit(), 9  
DBI::dbConnect(), 3, 4, 8, 9  
DBI::dbDataType(), 5  
DBI::dbDisconnect(), 8  
DBI::dbReadTable(), 3  
DBI::dbRollback(), 9  
DBI::dbSendQuery(), 7  
DBI::dbWithTransaction(), 9  
DBI::dbWriteTable(), 5  
DBI::make.db.names(), 4  
dbReadTable, SQLiteConnection, character-method,  
    3  
dbRollback, SQLiteConnection-method  
    (sqlite-transaction), 9  
dbWriteTable, SQLiteConnection, character, character-method  
    (dbWriteTable, SQLiteConnection, character, data.frame-method),  
    4  
dbWriteTable, SQLiteConnection, character, data.frame-method,  
    4  
  
initExtension, 6  
initExtension(), 8  
  
read.table(), 5  
RSSQLite (SQLite), 7