

Package ‘arrow’

October 20, 2020

Title Integration to 'Apache' 'Arrow'

Version 2.0.0

Description 'Apache' 'Arrow' <<https://arrow.apache.org/>> is a cross-language development platform for in-memory data. It specifies a standardized language-independent columnar memory format for flat and hierarchical data, organized for efficient analytic operations on modern hardware. This package provides an interface to the 'Arrow C++' library.

Depends R (>= 3.1)

License Apache License (>= 2.0)

URL <https://github.com/apache/arrow/>, <https://arrow.apache.org/docs/r/>

BugReports <https://issues.apache.org/jira/projects/ARROW/issues>

Encoding UTF-8

Language en-US

LazyData true

SystemRequirements C++11; for AWS S3 support on Linux, libcurl and openssl (optional)

Biarch true

Imports assertthat, bit64 (>= 0.9-7), methods, purrr, R6, rlang, tidyselect, utils, vctrs

RoxygenNote 7.1.1

VignetteBuilder knitr

Suggests decor, dplyr, hms, knitr, lubridate, pkgload, reticulate, rmarkdown, testthat, tibble

LinkingTo cpp11

Collate 'enums.R' 'arrow-package.R' 'type.R' 'array-data.R' 'array.R' 'arrowExports.R' 'buffer.R' 'chunked-array.R' 'io.R' 'compression.R' 'scalar.R' 'compute.R' 'config.R' 'csv.R' 'dataset.R' 'dataset-factory.R' 'dataset-format.R' 'dataset-partition.R' 'dataset-scan.R' 'dataset-write.R' 'deprecated.R' 'dictionary.R' 'record-batch.R' 'table.R'

'expression.R' 'dplyr.R' 'feather.R' 'field.R' 'filesystem.R'
 'flight.R' 'install-arrow.R' 'ipc_stream.R' 'json.R' 'list.R'
 'memory-pool.R' 'message.R' 'parquet.R' 'python.R'
 'record-batch-reader.R' 'record-batch-writer.R'
 'reexports-bit64.R' 'reexports-tidysselect.R' 'schema.R'
 'struct.R' 'util.R'

NeedsCompilation yes

Author Romain François [aut] (<<https://orcid.org/0000-0002-2444-4226>>),
 Jeroen Ooms [aut],
 Neal Richardson [aut, cre],
 Javier Luraschi [ctb],
 Jeffrey Wong [ctb],
 Apache Arrow [aut, cph]

Maintainer Neal Richardson <neal@ursalabs.org>

Repository CRAN

Date/Publication 2020-10-20 20:50:06 UTC

R topics documented:

array	4
ArrayData	5
arrow_available	5
buffer	6
cast_options	7
ChunkedArray	7
Codec	8
codec_is_available	9
compression	9
copy_files	10
cpu_count	10
CsvReadOptions	11
CsvTableReader	12
data-type	13
Dataset	16
dataset_factory	17
DataType	18
dictionary	19
DictionaryType	19
Expression	20
FeatherReader	20
Field	21
FileFormat	21
FileInfo	22
FileSelector	23
FileSystem	23
FileWriteOptions	25

FixedWidthType	25
flight_connect	25
flight_get	26
hive_partition	26
InputStream	27
install_arrow	28
install_pyarrow	29
load_flight_server	29
map_batches	30
match_arrow	30
Message	31
MessageReader	31
mmap_create	31
mmap_open	32
open_dataset	32
OutputStream	33
ParquetFileReader	34
ParquetFileWriter	35
ParquetReaderProperties	35
ParquetWriterProperties	36
Partitioning	37
push_data	37
read_arrow	38
read_delim_arrow	39
read_feather	43
read_json_arrow	44
read_message	45
read_parquet	45
read_schema	46
RecordBatch	46
RecordBatchReader	48
RecordBatchWriter	49
s3_bucket	51
Scalar	52
Scanner	52
Schema	53
Table	54
type	55
unify_schemas	56
write_arrow	56
write_dataset	57
write_feather	58
write_parquet	59
write_to_raw	62

array

*Arrow Arrays***Description**

An Array is an immutable data array with some logical type and some length. Most logical types are contained in the base Array class; there are also subclasses for DictionaryArray, ListArray, and StructArray.

Factory

The Array\$create() factory method instantiates an Array and takes the following arguments:

- x: an R vector, list, or data.frame
- type: an optional [data type](#) for x. If omitted, the type will be inferred from the data.

Array\$create() will return the appropriate subclass of Array, such as DictionaryArray when given an R factor.

To compose a DictionaryArray directly, call DictionaryArray\$create(), which takes two arguments:

- x: an R vector or Array of integers for the dictionary indices
- dict: an R vector or Array of dictionary values (like R factor levels but not limited to strings only)

Usage

```
a <- Array$create(x)
length(a)

print(a)
a == a
```

Methods

- \$IsNull(i): Return true if value at index is null. Does not boundscheck
- \$IsValid(i): Return true if value at index is valid. Does not boundscheck
- \$length(): Size in the number of elements this array contains
- \$offset(): A relative position into another array's data, to enable zero-copy slicing
- \$null_count(): The number of null entries in the array
- \$type(): logical type of data
- \$type_id(): type id
- \$Equals(other) : is this array equal to other
- \$ApproxEquals(other) :
- \$data(): return the underlying [ArrayData](#)
- \$as_vector(): convert to an R vector

- `$ToString()`: string representation of the array
- `$Slice(offset, length = NULL)`: Construct a zero-copy slice of the array with the indicated offset and length. If length is NULL, the slice goes until the end of the array.
- `$Take(i)`: return an Array with values at positions given by integers (R vector or Array Array) `i`.
- `$Filter(i, keep_na = TRUE)`: return an Array with values at positions where logical vector (or Arrow boolean Array) `i` is TRUE.
- `$RangeEquals(other, start_idx, end_idx, other_start_idx)` :
- `$cast(target_type, safe = TRUE, options = cast_options(safe))`: Alter the data in the array to change its type.
- `$View(type)`: Construct a zero-copy view of this array with the given type.
- `$Validate()` : Perform any validation checks to determine obvious inconsistencies within the array's internal data. This can be an expensive check, potentially $O(\text{length})$

 ArrayData

ArrayData class

Description

The ArrayData class allows you to get and inspect the data inside an arrow: `:Array`.

Usage

```
data <- Array$create(x)$data()
```

```
data$type()
data$length()
data$null_count()
data$offset()
data$buffers()
```

Methods

...

 arrow_available

Is the C++ Arrow library available?

Description

You won't generally need to call these function, but they're made available for diagnostic purposes.

Usage

```
arrow_available()
```

```
arrow_with_s3()
```

Value

TRUE or FALSE depending on whether the package was installed with the Arrow C++ library (check with `arrow_available()`) or with S3 support enabled (check with `arrow_with_s3()`).

See Also

If either of these are FALSE, see `vignette("install", package = "arrow")` for guidance on reinstalling the package.

Examples

```
arrow_available()
arrow_with_s3()
```

 buffer

Buffer class

Description

A Buffer is an object containing a pointer to a piece of contiguous memory with a particular size.

Usage

```
buffer(x)
```

Arguments

x R object. Only raw, numeric and integer vectors are currently supported

Value

an instance of Buffer that borrows memory from x

Factory

`buffer()` lets you create an `arrow::Buffer` from an R object

Methods

- `$is_mutable()` :
- `$ZeroPadding()` :
- `$size()` :
- `$capacity()`:

cast_options	<i>Cast options</i>
--------------	---------------------

Description

Cast options

Usage

```
cast_options(
  safe = TRUE,
  allow_int_overflow = !safe,
  allow_time_truncate = !safe,
  allow_float_truncate = !safe
)
```

Arguments

safe	enforce safe conversion
allow_int_overflow	allow int conversion, !safe by default
allow_time_truncate	allow time truncate, !safe by default
allow_float_truncate	allow float truncate, !safe by default

ChunkedArray	<i>ChunkedArray class</i>
--------------	---------------------------

Description

A ChunkedArray is a data structure managing a list of primitive Arrow [Arrays](#) logically as one large array. Chunked arrays may be grouped together in a [Table](#).

Usage

```
chunked_array(..., type = NULL)
```

Arguments

...	Vectors to coerce
type	currently ignored

Factory

The `ChunkedArray$create()` factory method instantiates the object from various Arrays or R vectors. `chunked_array()` is an alias for it.

Methods

- `$length()`: Size in the number of elements this array contains
- `$chunk(i)`: Extract an Array chunk by integer position
- `$as_vector()`: convert to an R vector
- `$Slice(offset, length = NULL)`: Construct a zero-copy slice of the array with the indicated offset and length. If length is NULL, the slice goes until the end of the array.
- `$Take(i)`: return a `ChunkedArray` with values at positions given by integers `i`. If `i` is an Arrow Array or `ChunkedArray`, it will be coerced to an R vector before taking.
- `$Filter(i, keep_na = TRUE)`: return a `ChunkedArray` with values at positions where logical vector or Arrow boolean-type (`Chunked`)Array `i` is TRUE.
- `$cast(target_type, safe = TRUE, options = cast_options(safe))`: Alter the data in the array to change its type.
- `$null_count()`: The number of null entries in the array
- `$chunks()`: return a list of Arrays
- `$num_chunks()`: integer number of chunks in the `ChunkedArray`
- `$type()`: logical type of data
- `$View(type)`: Construct a zero-copy view of this `ChunkedArray` with the given type.
- `$Validate()`: Perform any validation checks to determine obvious inconsistencies within the array's internal data. This can be an expensive check, potentially $O(\text{length})$

See Also

[Array](#)

Codec

Compression Codec class

Description

Codecs allow you to create [compressed input and output streams](#).

Factory

The `Codec$create()` factory method takes the following arguments:

- `type`: string name of the compression method. Possible values are "uncompressed", "snappy", "gzip", "brotli", "zstd", "lz4", "lzo", or "bz2". `type` may be upper- or lower-cased. Not all methods may be available; support depends on build-time flags for the C++ library. See [codec_is_available\(\)](#). Most builds support at least "snappy" and "gzip". All support "uncompressed".
- `compression_level`: compression level, the default value (NA) uses the default compression level for the selected compression type.

codec_is_available	<i>Check whether a compression codec is available</i>
--------------------	---

Description

Support for compression libraries depends on the build-time settings of the Arrow C++ library. This function lets you know which are available for use.

Usage

```
codec_is_available(type)
```

Arguments

type	A string, one of "uncompressed", "snappy", "gzip", "brotli", "zstd", "lz4", "lzo", or "bz2", case insensitive.
------	--

Value

Logical: is type available?

compression	<i>Compressed stream classes</i>
-------------	----------------------------------

Description

CompressedInputStream and CompressedOutputStream allow you to apply a compression [Codec](#) to an input or output stream.

Factory

The CompressedInputStream\$create() and CompressedOutputStream\$create() factory methods instantiate the object and take the following arguments:

- stream An [InputStream](#) or [OutputStream](#), respectively
- codec A Codec, either a [Codec](#) instance or a string
- compression_level compression level for when the codec argument is given as a string

Methods

Methods are inherited from [InputStream](#) and [OutputStream](#), respectively

copy_files	<i>Copy files between FileSystems</i>
------------	---------------------------------------

Description

Copy files between FileSystems

Usage

```
copy_files(from, to, chunk_size = 1024L * 1024L)
```

Arguments

from	A string path to a local directory or file, a URI, or a SubTreeFileSystem. Files will be copied recursively from this path.
to	A string path to a local directory or file, a URI, or a SubTreeFileSystem. Directories will be created as necessary
chunk_size	The maximum size of block to read before flushing to the destination file. A larger chunk_size will use more memory while copying but may help accommodate high latency FileSystems.

Value

Nothing: called for side effects in the file system

Examples

```
## Not run:
# Copy an S3 bucket's files to a local directory:
copy_files("s3://your-bucket-name", "local-directory")
# Using a FileSystem object
copy_files(s3_bucket("your-bucket-name"), "local-directory")
# Or go the other way, from local to S3
copy_files("local-directory", s3_bucket("your-bucket-name"))

## End(Not run)
```

cpu_count	<i>Manage the global CPU thread pool in libarrow</i>
-----------	--

Description

Manage the global CPU thread pool in libarrow

Usage

```
cpu_count()
```

```
set_cpu_count(num_threads)
```

Arguments

num_threads integer: New number of threads for thread pool

CsvReadOptions	<i>File reader options</i>
----------------	----------------------------

Description

CsvReadOptions, CsvParseOptions, CsvConvertOptions, JsonReadOptions, JsonParseOptions, and TimestampParser are containers for various file reading options. See their usage in [read_csv_arrow\(\)](#) and [read_json_arrow\(\)](#), respectively.

Factory

The CsvReadOptions\$create() and JsonReadOptions\$create() factory methods take the following arguments:

- use_threads Whether to use the global CPU thread pool
- block_size Block size we request from the IO layer; also determines the size of chunks when use_threads is TRUE. NB: if FALSE, JSON input must end with an empty line.

CsvReadOptions\$create() further accepts these additional arguments:

- skip_rows Number of lines to skip before reading data (default 0)
- column_names Character vector to supply column names. If length-0 (the default), the first non-skipped row will be parsed to generate column names, unless autogenerate_column_names is TRUE.
- autogenerate_column_names Logical: generate column names instead of using the first non-skipped row (the default)? If TRUE, column names will be "f0", "f1", ..., "fN".

CsvParseOptions\$create() takes the following arguments:

- delimiter Field delimiting character (default ", ")
- quoting Logical: are strings quoted? (default TRUE)
- quote_char Quoting character, if quoting is TRUE
- double_quote Logical: are quotes inside values double-quoted? (default TRUE)
- escaping Logical: whether escaping is used (default FALSE)
- escape_char Escaping character, if escaping is TRUE
- newlines_in_values Logical: are values allowed to contain CR (0x0d) and LF (0x0a) characters? (default FALSE)

- `ignore_empty_lines` Logical: should empty lines be ignored (default) or generate a row of missing values (if FALSE)?

`JsonParseOptions$create()` accepts only the `newlines_in_values` argument.

`CsvConvertOptions$create()` takes the following arguments:

- `check_utf8` Logical: check UTF8 validity of string columns? (default TRUE)
- `null_values` character vector of recognized spellings for null values. Analogous to the `na.strings` argument to `read.csv()` or `na` in `readr::read_csv()`.
- `strings_can_be_null` Logical: can string / binary columns have null values? Similar to the `quoted_na` argument to `readr::read_csv()`. (default FALSE)
- `true_values` character vector of recognized spellings for TRUE values
- `false_values` character vector of recognized spellings for FALSE values
- `col_types` A Schema or NULL to infer types
- `auto_dict_encode` Logical: Whether to try to automatically dictionary-encode string / binary data (think `stringsAsFactors`). Default FALSE. This setting is ignored for non-inferred columns (those in `col_types`).
- `auto_dict_max_cardinality` If `auto_dict_encode`, string/binary columns are dictionary-encoded up to this number of unique values (default 50), after which it switches to regular encoding.
- `include_columns` If non-empty, indicates the names of columns from the CSV file that should be actually read and converted (in the vector's order).
- `include_missing_columns` Logical: if `include_columns` is provided, should columns named in it but not found in the data be included as a column of type `null()`? The default (FALSE) means that the reader will instead raise an error.
- `timestamp_parsers` User-defined timestamp parsers. If more than one parser is specified, the CSV conversion logic will try parsing values starting from the beginning of this vector. Possible values are (a) NULL, the default, which uses the ISO-8601 parser; (b) a character vector of `strptime` parse strings; or (c) a list of `TimestampParser` objects.

`TimestampParser$create()` takes an optional format string argument. See `strptime()` for example syntax. The default is to use an ISO-8601 format parser.

Active bindings

- `column_names`: from `CsvReadOptions`

CsvTableReader

Arrow CSV and JSON table reader classes

Description

`CsvTableReader` and `JsonTableReader` wrap the Arrow C++ CSV and JSON table readers. See their usage in `read_csv_arrow()` and `read_json_arrow()`, respectively.

Factory

The `CsvTableReader#create()` and `JsonTableReader#create()` factory methods take the following arguments:

- file An Arrow [InputStream](#)
- convert_options (CSV only), parse_options, read_options: see [CsvReadOptions](#)
- ... additional parameters.

Methods

- `$Read()`: returns an Arrow Table.

data-type

Apache Arrow data types

Description

These functions create type objects corresponding to Arrow types. Use them when defining a [schema\(\)](#) or as inputs to other types, like `struct`. Most of these functions don't take arguments, but a few do.

Usage

`int8()`

`int16()`

`int32()`

`int64()`

`uint8()`

`uint16()`

`uint32()`

`uint64()`

`float16()`

`halffloat()`

`float32()`

`float()`

```
float64()
boolean()
bool()
utf8()
large_utf8()
binary()
large_binary()
fixed_size_binary(byte_width)
string()
date32()
date64()
time32(unit = c("ms", "s"))
time64(unit = c("ns", "us"))
null()
timestamp(unit = c("s", "ms", "us", "ns"), timezone = "")
decimal(precision, scale)
list_of(type)
large_list_of(type)
fixed_size_list_of(type, list_size)
struct(...)
```

Arguments

byte_width	byte width for FixedSizeBinary type.
unit	For time/timestamp types, the time unit. <code>time32()</code> can take either "s" or "ms", while <code>time64()</code> can be "us" or "ns". <code>timestamp()</code> can take any of those four values.
timezone	For <code>timestamp()</code> , an optional time zone string.

precision	For <code>decimal()</code> , precision
scale	For <code>decimal()</code> , scale
type	For <code>list_of()</code> , a data type to make a list-of-type
list_size	list size for <code>FixedSizeList</code> type.
...	For <code>struct()</code> , a named list of types to define the struct columns

Details

A few functions have aliases:

- `utf8()` and `string()`
- `float16()` and `halffloat()`
- `float32()` and `float()`
- `bool()` and `boolean()`
- Called from `schema()` or `struct()`, `double()` also is supported as a way of creating a `float64()`

`date32()` creates a datetime type with a "day" unit, like the R Date class. `date64()` has a "ms" unit.

Value

An Arrow type object inheriting from `DataType`.

See Also

[dictionary\(\)](#) for creating a dictionary (factor-like) type.

Examples

```
bool()
struct(a = int32(), b = double())
timestamp("ms", timezone = "CEST")
time64("ns")
```

 Dataset

 Multi-file datasets

Description

Arrow Datasets allow you to query against data that has been split across multiple files. This sharding of data may indicate partitioning, which can accelerate queries that only touch some partitions (files).

A Dataset contains one or more Fragments, such as files, of potentially differing type and partitioning.

For `Dataset$create()`, see [open_dataset\(\)](#), which is an alias for it.

`DatasetFactory` is used to provide finer control over the creation of Datasets.

Factory

`DatasetFactory` is used to create a Dataset, inspect the [Schema](#) of the fragments contained in it, and declare a partitioning. `FileSystemDatasetFactory` is a subclass of `DatasetFactory` for discovering files in the local file system, the only currently supported file system.

For the `DatasetFactory$create()` factory method, see [dataset_factory\(\)](#), an alias for it. A `DatasetFactory` has:

- `$Inspect(unify_schemas)`: If `unify_schemas` is `TRUE`, all fragments will be scanned and a unified [Schema](#) will be created from them; if `FALSE` (default), only the first fragment will be inspected for its schema. Use this fast path when you know and trust that all fragments have an identical schema.
- `$Finish(schema, unify_schemas)`: Returns a Dataset. If `schema` is provided, it will be used for the Dataset; if omitted, a [Schema](#) will be created from inspecting the fragments (files) in the dataset, following `unify_schemas` as described above.

`FileSystemDatasetFactory$create()` is a lower-level factory method and takes the following arguments:

- `filesystem`: A [FileSystem](#)
- `selector`: A [FileSelector](#)
- `format`: A [FileFormat](#)
- `partitioning`: Either `Partitioning`, `PartitioningFactory`, or `NULL`

Methods

A Dataset has the following methods:

- `$NewScan()`: Returns a [ScannerBuilder](#) for building a query
- `$schema`: Active binding that returns the [Schema](#) of the Dataset; you may also replace the dataset's schema by using `ds$schema <- new_schema`. This method currently supports only adding, removing, or reordering fields in the schema: you cannot alter or cast the field types.

`FileSystemDataset` has the following methods:

- `$files`: Active binding, returns the files of the `FileSystemDataset`
- `$format`: Active binding, returns the [FileFormat](#) of the `FileSystemDataset`

`UnionDataset` has the following methods:

- `$children`: Active binding, returns all child `Datasets`.

See Also

[open_dataset\(\)](#) for a simple interface to creating a `Dataset`

dataset_factory *Create a DatasetFactory*

Description

A [Dataset](#) can be constructed using one or more [DatasetFactories](#). This function helps you construct a `DatasetFactory` that you can pass to [open_dataset\(\)](#).

Usage

```
dataset_factory(
  x,
  filesystem = NULL,
  format = c("parquet", "arrow", "ipc", "feather", "csv", "tsv", "text"),
  partitioning = NULL,
  ...
)
```

Arguments

<code>x</code>	A string file <code>x</code> containing data files, or a list of <code>DatasetFactory</code> objects whose datasets should be grouped. If this argument is specified it will be used to construct a <code>UnionDatasetFactory</code> and other arguments will be ignored.
<code>filesystem</code>	A FileSystem object; if omitted, the <code>FileSystem</code> will be detected from <code>x</code>
<code>format</code>	A FileFormat object, or a string identifier of the format of the files in <code>x</code> . Currently supported values: <ul style="list-style-type: none"> • "parquet" • "ipc"/"arrow"/"feather", all aliases for each other; for Feather, note that only version 2 files are supported • "csv"/"text", aliases for the same thing (because comma is the default delimiter for text files) • "tsv", equivalent to passing <code>format = "text"</code>, <code>delimiter = "\t"</code> Default is "parquet", unless a <code>delimiter</code> is also specified, in which case it is assumed to be "text".
<code>partitioning</code>	One of

- A Schema, in which case the file paths relative to sources will be parsed, and path segments will be matched with the schema fields. For example, `schema(year = int16(), month = int8())` would create partitions for file paths like "2019/01/file.parquet", "2019/02/file.parquet", etc.
 - A character vector that defines the field names corresponding to those path segments (that is, you're providing the names that would correspond to a Schema but the types will be autodetected)
 - A `HivePartitioning` or `HivePartitioningFactory`, as returned by `hive_partition()` which parses explicit or autodetected fields from Hive-style path segments
 - NULL for no partitioning
- ... Additional format-specific options, passed to `FileFormat$create()`. For CSV options, note that you can specify them either with the Arrow C++ library naming ("delimiter", "quoting", etc.) or the readr-style naming used in `read_csv_arrow()` ("delim", "quote", etc.)

Details

If you would only have a single `DatasetFactory` (for example, you have a single directory containing Parquet files), you can call `open_dataset()` directly. Use `dataset_factory()` when you want to combine different directories, file systems, or file formats.

Value

A `DatasetFactory` object. Pass this to `open_dataset()`, in a list potentially with other `DatasetFactory` objects, to create a `Dataset`.

DataType	<i>class arrow::DataType</i>
----------	------------------------------

Description

class arrow::DataType

Methods

TODO

dictionary	<i>Create a dictionary type</i>
------------	---------------------------------

Description

Create a dictionary type

Usage

```
dictionary(index_type = int32(), value_type = utf8(), ordered = FALSE)
```

Arguments

index_type	A DataType for the indices (default int32())
value_type	A DataType for the values (default utf8())
ordered	Is this an ordered dictionary (default FALSE)?

Value

A [DictionaryType](#)

See Also

[Other Arrow data types](#)

DictionaryType	<i>class DictionaryType</i>
----------------	-----------------------------

Description

class DictionaryType

Methods

TODO

Expression	<i>Arrow expressions</i>
------------	--------------------------

Description

Expressions are used to define filter logic for passing to a [Dataset Scanner](#).

`Expression$scalar(x)` constructs an Expression which always evaluates to the provided scalar (length-1) R value.

`Expression$field_ref(name)` is used to construct an Expression which evaluates to the named column in the Dataset against which it is evaluated.

`Expression$compare(OP, e1, e2)` takes two Expression operands, constructing an Expression which will evaluate these operands then compare them with the relation specified by OP (e.g. "=", "!=", ">", etc.) For example, to filter down to rows where the column named "alpha" is less than 5: `Expression$compare("<", Expression$field_ref("alpha"), Expression$scalar(5))`

`Expression$and(e1, e2)`, `Expression$or(e1, e2)`, and `Expression$not(e1)` construct an Expression combining their arguments with Boolean operators.

`Expression$is_valid(x)` is essentially (an inversion of) `is.na()` for Expressions.

`Expression$in_(x, set)` evaluates x and returns whether or not it is a member of the set.

FeatherReader	<i>FeatherReader class</i>
---------------	----------------------------

Description

This class enables you to interact with Feather files. Create one to connect to a file or other Input-Stream, and call `Read()` on it to make an arrow: `:Table`. See its usage in [read_feather\(\)](#).

Factory

The `FeatherReader$create()` factory method instantiates the object and takes the following arguments:

- `file` an Arrow file connection object inheriting from `RandomAccessFile`.
- `mmap Logical`: whether to memory-map the file (default TRUE)
- ... Additional arguments, currently ignored

Methods

- `$Read(columns)`: Returns a `Table` of the selected columns, a vector of integer indices
- `$version`: Active binding, returns 1 or 2, according to the Feather file version

Field	<i>Field class</i>
-------	--------------------

Description

`field()` lets you create an `arrow::Field` that maps a [DataType](#) to a column name. Fields are contained in [Schemas](#).

Usage

```
field(name, type, metadata)
```

Arguments

name	field name
type	logical type, instance of DataType
metadata	currently ignored

Methods

- `f$ToString()`: convert to a string
- `f$Equals(other)`: test for equality. More naturally called as `f == other`

Examples

```
field("x", int32())
```

FileFormat	<i>Dataset file formats</i>
------------	-----------------------------

Description

A `FileFormat` holds information about how to read and parse the files included in a `Dataset`. There are subclasses corresponding to the supported file formats (`ParquetFileFormat` and `IpcFileFormat`).

Factory

`FileFormat$create()` takes the following arguments:

- `format`: A string identifier of the file format. Currently supported values:
 - "parquet"
 - "ipc"/"arrow"/"feather", all aliases for each other; for Feather, note that only version 2 files are supported

- "csv"/"text", aliases for the same thing (because comma is the default delimiter for text files)
 - "tsv", equivalent to passing format = "text", delimiter = "\t"
 - ...: Additional format-specific options
 - ‘format = "parquet"‘:
 - use_buffered_stream: Read files through buffered input streams rather than loading entire row groups at once. This may be enabled to reduce memory overhead. Disabled by default.
 - buffer_size: Size of buffered stream, if enabled. Default is 8KB.
 - dict_columns: Names of columns which should be read as dictionaries.
- format = "text": see [CsvReadOptions](#). Note that you can specify them either with the Arrow C++ library naming ("delimiter", "quoting", etc.) or the readr-style naming used in [read_csv_arrow\(\)](#) ("delim", "quote", etc.)

It returns the appropriate subclass of FileFormat (e.g. ParquetFileFormat)

FileInfo

FileSystem entry info

Description

FileSystem entry info

Methods

- base_name() : The file base name (component after the last directory separator).
- extension() : The file extension

Active bindings

- \$type: The file type
- \$path: The full file path in the filesystem
- \$size: The size in bytes, if available. Only regular files are guaranteed to have a size.
- \$mtime: The time of last modification, if available.

FileSelector	<i>file selector</i>
--------------	----------------------

Description

file selector

Factory

The \$create() factory method instantiates a FileSelector given the 3 fields described below.

Fields

- `base_dir`: The directory in which to select files. If the path exists but doesn't point to a directory, this should be an error.
- `allow_not_found`: The behavior if `base_dir` doesn't exist in the filesystem. If `FALSE`, an error is returned. If `TRUE`, an empty selection is returned
- `recursive`: Whether to recurse into subdirectories.

FileSystem	<i>FileSystem classes</i>
------------	---------------------------

Description

FileSystem is an abstract file system API, LocalFileSystem is an implementation accessing files on the local machine. SubTreeFileSystem is an implementation that delegates to another implementation after prepending a fixed base path

Factory

LocalFileSystem\$create() returns the object and takes no arguments.

SubTreeFileSystem\$create() takes the following arguments:

- `base_path`, a string path
- `base_fs`, a FileSystem object

S3FileSystem\$create() optionally takes arguments:

- `anonymous`: logical, default `FALSE`. If true, will not attempt to look up credentials using standard AWS configuration methods.
- `access_key`, `secret_key`: authentication credentials. If one is provided, the other must be as well. If both are provided, they will override any AWS configuration set at the environment level.
- `session_token`: optional string for authentication along with `access_key` and `secret_key`

- `role_arn`: string AWS ARN of an `AccessRole`. If provided instead of `access_key` and `secret_key`, temporary credentials will be fetched by assuming this role.
- `session_name`: optional string identifier for the assumed role session.
- `external_id`: optional unique string identifier that might be required when you assume a role in another account.
- `load_frequency`: integer, frequency (in seconds) with which temporary credentials from an assumed role session will be refreshed. Default is 900 (i.e. 15 minutes)
- `region`: AWS region to connect to. If omitted, the AWS library will provide a sensible default based on client configuration, falling back to "us-east-1" if no other alternatives are found.
- `endpoint_override`: If non-empty, override region with a connect string such as "localhost:9000". This is useful for connecting to file systems that emulate S3.
- `scheme`: S3 connection transport (default "https")
- `background_writes`: logical, whether `OutputStream` writes will be issued in the background, without blocking (default TRUE)

Methods

- `$GetFileInfo(x)`: `x` may be a `FileSelector` or a character vector of paths. Returns a list of `FileInfo`
- `$CreateDir(path, recursive = TRUE)`: Create a directory and subdirectories.
- `$DeleteDir(path)`: Delete a directory and its contents, recursively.
- `$DeleteDirContents(path)`: Delete a directory's contents, recursively. Like `$DeleteDir()`, but doesn't delete the directory itself. Passing an empty path ("") will wipe the entire filesystem tree.
- `$DeleteFile(path)` : Delete a file.
- `$DeleteFiles(paths)` : Delete many files. The default implementation issues individual delete operations in sequence.
- `$Move(src, dest)`: Move / rename a file or directory. If the destination exists: if it is a non-empty directory, an error is returned otherwise, if it has the same type as the source, it is replaced otherwise, behavior is unspecified (implementation-dependent).
- `$CopyFile(src, dest)`: Copy a file. If the destination exists and is a directory, an error is returned. Otherwise, it is replaced.
- `$OpenInputStream(path)`: Open an `input stream` for sequential reading.
- `$OpenInputFile(path)`: Open an `input file` for random access reading.
- `$OpenOutputStream(path)`: Open an `output stream` for sequential writing.
- `$OpenAppendStream(path)`: Open an `output stream` for appending.

Active bindings

- `$type_name`: string filesystem type name, such as "local", "s3", etc.
- `$region`: string AWS region, for `S3FileSystem` and `SubTreeFileSystem` containing a `S3FileSystem`
- `$base_fs`: for `SubTreeFileSystem`, the `FileSystem` it contains
- `$base_path`: for `SubTreeFileSystem`, the path in `$base_fs` which is considered root in this `SubTreeFileSystem`.

FileWriteOptions	<i>Format-specific write options</i>
------------------	--------------------------------------

Description

A FileWriteOptions holds write options specific to a FileFormat.

FixedWidthType	<i>class arrow::FixedWidthType</i>
----------------	------------------------------------

Description

class arrow::FixedWidthType

Methods

TODO

flight_connect	<i>Connect to a Flight server</i>
----------------	-----------------------------------

Description

Connect to a Flight server

Usage

```
flight_connect(host = "localhost", port, scheme = "grpc+tcp")
```

Arguments

host	string hostname to connect to
port	integer port to connect on
scheme	URL scheme, default is "grpc+tcp"

Value

A pyarrow.flight.FlightClient.

flight_get	<i>Get data from a Flight server</i>
------------	--------------------------------------

Description

Get data from a Flight server

Usage

```
flight_get(client, path)
```

Arguments

client	pyarrow.flight.FlightClient, as returned by flight_connect()
path	string identifier under which the data is stored

Value

A [RecordBatch](#)

hive_partition	<i>Construct Hive partitioning</i>
----------------	------------------------------------

Description

Hive partitioning embeds field names and values in path segments, such as `"/year=2019/month=2/data.parquet"`.

Usage

```
hive_partition(...)
```

Arguments

...	named list of data types , passed to schema()
-----	---

Details

Because fields are named in the path segments, order of fields passed to `hive_partition()` does not matter.

Value

A [HivePartitioning](#), or a `HivePartitioningFactory` if calling `hive_partition()` with no arguments.

Examples

```
hive_partition(year = int16(), month = int8())
```

InputStream

InputStream classes

Description

RandomAccessFile inherits from InputStream and is a base class for: ReadableFile for reading from a file; MemoryMappedFile for the same but with memory mapping; and BufferedReader for reading from a buffer. Use these with the various table readers.

Factory

The \$create() factory methods instantiate the InputStream object and take the following arguments, depending on the subclass:

- path For ReadableFile, a character file name
- x For BufferedReader, a [Buffer](#) or an object that can be made into a buffer via `buffer()`.

To instantiate a MemoryMappedFile, call `mmap_open()`.

Methods

- `$GetSize()`:
- `$supports_zero_copy()`: Logical
- `$seek(position)`: go to that position in the stream
- `$tell()`: return the position in the stream
- `$close()`: close the stream
- `$Read(nbytes)`: read data from the stream, either a specified nbytes or all, if nbytes is not provided
- `$ReadAt(position, nbytes)`: similar to `$seek(position)$Read(nbytes)`
- `$Resize(size)`: for a MemoryMappedFile that is writeable

install_arrow	<i>Install or upgrade the Arrow library</i>
---------------	---

Description

Use this function to install the latest release of arrow, to switch to or from a nightly development version, or on Linux to try reinstalling with all necessary C++ dependencies.

Usage

```
install_arrow(
  nightly = FALSE,
  binary = Sys.getenv("LIBARROW_BINARY", TRUE),
  use_system = Sys.getenv("ARROW_USE_PKG_CONFIG", FALSE),
  minimal = Sys.getenv("LIBARROW_MINIMAL", FALSE),
  repos = getOption("repos"),
  ...
)
```

Arguments

nightly	logical: Should we install a development version of the package, or should we install from CRAN (the default).
binary	On Linux, value to set for the environment variable LIBARROW_BINARY, which governs how C++ binaries are used, if at all. The default value, TRUE, tells the installation script to detect the Linux distribution and version and find an appropriate C++ library. FALSE would tell the script not to retrieve a binary and instead build Arrow C++ from source. Other valid values are strings corresponding to a Linux distribution-version, to override the value that would be detected. See <code>vignette("install", package = "arrow")</code> for further details.
use_system	logical: Should we use pkg-config to look for Arrow system packages? Default is FALSE. If TRUE, source installation may be faster, but there is a risk of version mismatch.
minimal	logical: If building from source, should we build without optional dependencies (compression libraries, for example)? Default is FALSE.
repos	character vector of base URLs of the repositories to install from (passed to <code>install.packages()</code>)
...	Additional arguments passed to <code>install.packages()</code>

See Also

[arrow_available\(\)](#) to see if the package was configured with necessary C++ dependencies. `vignette("install", package = "arrow")` for more ways to tune installation on Linux.

install_pyarrow	<i>Install pyarrow for use with reticulate</i>
-----------------	--

Description

pyarrow is the Python package for Apache Arrow. This function helps with installing it for use with reticulate.

Usage

```
install_pyarrow(envname = NULL, nightly = FALSE, ...)
```

Arguments

envname	The name or full path of the Python environment to install into. This can be a virtualenv or conda environment created by reticulate. See <code>reticulate::py_install()</code> .
nightly	logical: Should we install a development version of the package? Default is to use the official release version.
...	additional arguments passed to <code>reticulate::py_install()</code> .

load_flight_server	<i>Load a Python Flight server</i>
--------------------	------------------------------------

Description

Load a Python Flight server

Usage

```
load_flight_server(name, path = system.file(package = "arrow"))
```

Arguments

name	string Python module name
path	file system path where the Python module is found. Default is to look in the <code>inst/</code> directory for included modules.

map_batches	<i>Apply a function to a stream of RecordBatches</i>
-------------	--

Description

As an alternative to calling `collect()` on a Dataset query, you can use this function to access the stream of `RecordBatches` in the Dataset. This lets you aggregate on each chunk and pull the intermediate results into a `data.frame` for further aggregation, even if you couldn't fit the whole Dataset result in memory.

Usage

```
map_batches(X, FUN, ..., .data.frame = TRUE)
```

Arguments

X	A Dataset or <code>arrow_dplyr_query</code> object, as returned by the <code>dplyr</code> methods on Dataset.
FUN	A function or <code>purrr</code> -style lambda expression to apply to each batch
...	Additional arguments passed to FUN
.data.frame	logical: collect the resulting chunks into a single <code>data.frame</code> ? Default TRUE

Details

This is experimental and not recommended for production use.

match_arrow	<i>match for Arrow objects</i>
-------------	--------------------------------

Description

`base::match()` is not a generic, so we can't just define Arrow methods for it. This function exposes the analogous function in the Arrow C++ library.

Usage

```
match_arrow(x, table, ...)
```

Arguments

x	Array or <code>ChunkedArray</code>
table	Array, <code>ChunkedArray</code> , or R vector lookup table.
...	additional arguments, ignored

Value

An `int32`-type Array of the same length as `x` with the (0-based) indexes into `table`.

Message	<i>class arrow::Message</i>
---------	-----------------------------

Description

class arrow::Message

Methods

TODO

MessageReader	<i>class arrow::MessageReader</i>
---------------	-----------------------------------

Description

class arrow::MessageReader

Methods

TODO

mmap_create	<i>Create a new read/write memory mapped file of a given size</i>
-------------	---

Description

Create a new read/write memory mapped file of a given size

Usage

```
mmap_create(path, size)
```

Arguments

path	file path
size	size in bytes

Value

a [arrow::io::MemoryMappedFile](#)

mmap_open	<i>Open a memory mapped file</i>
-----------	----------------------------------

Description

Open a memory mapped file

Usage

```
mmap_open(path, mode = c("read", "write", "readwrite"))
```

Arguments

path	file path
mode	file mode (read/write/readwrite)

open_dataset	<i>Open a multi-file dataset</i>
--------------	----------------------------------

Description

Arrow Datasets allow you to query against data that has been split across multiple files. This sharding of data may indicate partitioning, which can accelerate queries that only touch some partitions (files). Call `open_dataset()` to point to a directory of data files and return a Dataset, then use `dplyr` methods to query it.

Usage

```
open_dataset(
  sources,
  schema = NULL,
  partitioning = hive_partition(),
  unify_schemas = NULL,
  ...
)
```

Arguments

sources	Either: <ul style="list-style-type: none"> • a string path to a directory containing data files • a list of Dataset objects as created by this function • a list of DatasetFactory objects as created by <code>dataset_factory()</code>.
schema	Schema for the dataset. If NULL (the default), the schema will be inferred from the data sources.

partitioning	<p>When sources is a file path, one of</p> <ul style="list-style-type: none"> • a Schema, in which case the file paths relative to sources will be parsed, and path segments will be matched with the schema fields. For example, <code>schema(year = int16(), month = int8())</code> would create partitions for file paths like "2019/01/file.parquet", "2019/02/file.parquet", etc. • a character vector that defines the field names corresponding to those path segments (that is, you're providing the names that would correspond to a Schema but the types will be autodetected) • a <code>HivePartitioning</code> or <code>HivePartitioningFactory</code>, as returned by <code>hive_partition()</code> which parses explicit or autodetected fields from Hive-style path segments • NULL for no partitioning <p>The default is to autodetect Hive-style partitions.</p>
unify_schemas	<p>logical: should all data fragments (files, Datasets) be scanned in order to create a unified schema from them? If FALSE, only the first fragment will be inspected for its schema. Use this fast path when you know and trust that all fragments have an identical schema. The default is FALSE when creating a dataset from a file path (because there may be many files and scanning may be slow) but TRUE when sources is a list of Datasets (because there should be few Datasets in the list and their Schemas are already in memory).</p>
...	<p>additional arguments passed to <code>dataset_factory()</code> when sources is a file path, otherwise ignored. These may include "format" to indicate the file format, or other format-specific options.</p>

Value

A `Dataset` R6 object. Use `dplyr` methods on it to query the data, or call `$NewScan()` to construct a query directly.

See Also

`vignette("dataset", package = "arrow")`

OutputStream

OutputStream classes

Description

`FileOutputStream` is for writing to a file; `BufferOutputStream` writes to a buffer; You can create one and pass it to any of the table writers, for example.

Factory

The `$create()` factory methods instantiate the `OutputStream` object and take the following arguments, depending on the subclass:

- `path` For `FileOutputStream`, a character file name
- `initial_capacity` For `BufferOutputStream`, the size in bytes of the buffer.

Methods

- `$tell()`: return the position in the stream
- `$close()`: close the stream
- `$write(x)`: send `x` to the stream
- `$capacity()`: for `BufferOutputStream`
- `$finish()`: for `BufferOutputStream`
- `$GetExtentBytesWritten()`: for `MockOutputStream`, report how many bytes were sent.

ParquetFileReader *ParquetFileReader class*

Description

This class enables you to interact with Parquet files.

Factory

The `ParquetFileReader.create()` factory method instantiates the object and takes the following arguments:

- `file` A character file name, raw vector, or Arrow file connection object (e.g. `RandomAccessFile`).
- `props` Optional [ParquetReaderProperties](#)
- `mmap` Logical: whether to memory-map the file (default `TRUE`)
- ... Additional arguments, currently ignored

Methods

- `$ReadTable(column_indices)`: get an `arrow::Table` from the file. The optional `column_indices=` argument is a 0-based integer vector indicating which columns to retain.
- `$ReadRowGroup(i, column_indices)`: get an `arrow::Table` by reading the `i`th row group (0-based). The optional `column_indices=` argument is a 0-based integer vector indicating which columns to retain.
- `$ReadRowGroups(row_groups, column_indices)`: get an `arrow::Table` by reading several row groups (0-based integers). The optional `column_indices=` argument is a 0-based integer vector indicating which columns to retain.
- `$GetSchema()`: get the `arrow::Schema` of the data in the file
- `$ReadColumn(i)`: read the `i`th column (0-based) as a [ChunkedArray](#).

Active bindings

- `$num_rows`: number of rows.
- `$num_columns`: number of columns.
- `$num_row_groups`: number of row groups.

Examples

```
f <- system.file("v0.7.1.parquet", package="arrow")
pq <- ParquetFileReader$create(f)
pq$GetSchema()
if (codec_is_available("snappy")) {
  # This file has compressed data columns
  tab <- pq$ReadTable()
  tab$Schema
}
```

ParquetFileWriter *ParquetFileWriter class*

Description

This class enables you to interact with Parquet files.

Factory

The `ParquetFileWriter$create()` factory method instantiates the object and takes the following arguments:

- schema A [Schema](#)
- sink An [arrow::io::OutputStream](#)
- properties An instance of [ParquetWriterProperties](#)
- arrow_properties An instance of [ParquetArrowWriterProperties](#)

Methods

- WriteTable Write a [Table](#) to sink
- Close Close the writer. Note: does not close the sink. [arrow::io::OutputStream](#) has its own `close()` method.

ParquetReaderProperties
ParquetReaderProperties class

Description

This class holds settings to control how a Parquet file is read by [ParquetFileReader](#).

Factory

The `ParquetReaderProperties$create()` factory method instantiates the object and takes the following arguments:

- `use_threads` Logical: whether to use multithreading (default TRUE)

Methods

- `$read_dictionary(column_index)`
- `$set_read_dictionary(column_index, read_dict)`
- `$use_threads(use_threads)`

ParquetWriterProperties

ParquetWriterProperties class

Description

This class holds settings to control how a Parquet file is read by [ParquetFileWriter](#).

Details

The parameters `compression`, `compression_level`, `use_dictionary` and `write_statistics` support various patterns:

- The default NULL leaves the parameter unspecified, and the C++ library uses an appropriate default for each column (defaults listed above)
- A single, unnamed, value (e.g. a single string for `compression`) applies to all columns
- An unnamed vector, of the same size as the number of columns, to specify a value for each column, in positional order
- A named vector, to specify the value for the named columns, the default value for the setting is used when not supplied

Unlike the high-level [write_parquet](#), `ParquetWriterProperties` arguments use the C++ defaults. Currently this means "uncompressed" rather than "snappy" for the `compression` argument.

Factory

The `ParquetWriterProperties$create()` factory method instantiates the object and takes the following arguments:

- `table`: table to write (required)
- `version`: Parquet version, "1.0" or "2.0". Default "1.0"
- `compression`: Compression type, algorithm "uncompressed"
- `compression_level`: Compression level; meaning depends on compression algorithm
- `use_dictionary`: Specify if we should use dictionary encoding. Default TRUE
- `write_statistics`: Specify if we should write statistics. Default TRUE
- `data_page_size`: Set a target threshold for the approximate encoded size of data pages within a column chunk (in bytes). Default 1 MiB.

See Also[write_parquet](#)

Partitioning*Define Partitioning for a Dataset*

Description

Pass a Partitioning object to a [FileSystemDatasetFactory](#)'s `$create()` method to indicate how the file's paths should be interpreted to define partitioning.

`DirectoryPartitioning` describes how to interpret raw path segments, in order. For example, `schema(year = int16(), month = int8())` would define partitions for file paths like "2019/01/file.parquet", "2019/02/file.parquet", etc.

`HivePartitioning` is for Hive-style partitioning, which embeds field names and values in path segments, such as `"/year=2019/month=2/data.parquet"`. Because fields are named in the path segments, order does not matter.

`PartitioningFactory` subclasses instruct the `DatasetFactory` to detect partition features from the file paths.

Factory

Both `DirectoryPartitioning$create()` and `HivePartitioning$create()` methods take a [Schema](#) as a single input argument. The helper function `hive_partition(...)` is shorthand for `HivePartitioning$create(schema)`.

With `DirectoryPartitioningFactory$create()`, you can provide just the names of the path segments (in our example, `c("year", "month")`), and the `DatasetFactory` will infer the data types for those partition variables. `HivePartitioningFactory$create()` takes no arguments: both variable names and their types can be inferred from the file paths. `hive_partition()` with no arguments returns a `HivePartitioningFactory`.

push_data*Send data to a Flight server*

Description

Send data to a Flight server

Usage

```
push_data(client, data, path)
```

Arguments

<code>client</code>	<code>pyarrow.flight.FlightClient</code> , as returned by <code>flight_connect()</code>
<code>data</code>	<code>data.frame</code> or RecordBatch to upload
<code>path</code>	string identifier to store the data under

Value

client, invisibly.

read_arrow	<i>Read Arrow IPC stream format</i>
------------	-------------------------------------

Description

Apache Arrow defines two formats for [serializing data for interprocess communication \(IPC\)](#): a "stream" format and a "file" format, known as Feather. `read_ipc_stream()` and `read_feather()` read those formats, respectively.

Usage

```
read_arrow(file, ...)
```

```
read_ipc_stream(file, as_data_frame = TRUE, ...)
```

Arguments

file	A character file name or URI, raw vector, an Arrow input stream, or a <code>FileSystem</code> with path (<code>SubTreeFileSystem</code>). If a file name or URI, an Arrow InputStream will be opened and closed when finished. If an input stream is provided, it will be left open.
...	extra parameters passed to <code>read_feather()</code> .
as_data_frame	Should the function return a <code>data.frame</code> (default) or an Arrow Table ?

Details

`read_arrow()`, a wrapper around `read_ipc_stream()` and `read_feather()`, is deprecated. You should explicitly choose the function that will read the desired IPC format (stream or file) since a file or `InputStream` may contain either.

Value

A `data.frame` if `as_data_frame` is `TRUE` (the default), or an Arrow [Table](#) otherwise

See Also

[read_feather\(\)](#) for writing IPC files. [RecordBatchReader](#) for a lower-level interface.

read_delim_arrow	<i>Read a CSV or other delimited file with Arrow</i>
------------------	--

Description

These functions uses the Arrow C++ CSV reader to read into a `data.frame`. Arrow C++ options have been mapped to argument names that follow those of `readr::read_delim()`, and `col_select` was inspired by `vroom::vroom()`.

Usage

```
read_delim_arrow(  
  file,  
  delim = ",",  
  quote = "\"",  
  escape_double = TRUE,  
  escape_backslash = FALSE,  
  schema = NULL,  
  col_names = TRUE,  
  col_types = NULL,  
  col_select = NULL,  
  na = c("", "NA"),  
  quoted_na = TRUE,  
  skip_empty_rows = TRUE,  
  skip = 0L,  
  parse_options = NULL,  
  convert_options = NULL,  
  read_options = NULL,  
  as_data_frame = TRUE,  
  timestamp_parsers = NULL  
)
```

```
read_csv_arrow(  
  file,  
  quote = "\"",  
  escape_double = TRUE,  
  escape_backslash = FALSE,  
  schema = NULL,  
  col_names = TRUE,  
  col_types = NULL,  
  col_select = NULL,  
  na = c("", "NA"),  
  quoted_na = TRUE,  
  skip_empty_rows = TRUE,  
  skip = 0L,  
  parse_options = NULL,  
  convert_options = NULL,
```

```

    read_options = NULL,
    as_data_frame = TRUE,
    timestamp_parsers = NULL
  )

read_tsv_arrow(
  file,
  quote = "\"",
  escape_double = TRUE,
  escape_backslash = FALSE,
  schema = NULL,
  col_names = TRUE,
  col_types = NULL,
  col_select = NULL,
  na = c("", "NA"),
  quoted_na = TRUE,
  skip_empty_rows = TRUE,
  skip = 0L,
  parse_options = NULL,
  convert_options = NULL,
  read_options = NULL,
  as_data_frame = TRUE,
  timestamp_parsers = NULL
)

```

Arguments

file	A character file name or URI, raw vector, an Arrow input stream, or a <code>FileSystem</code> with path (<code>SubTreeFileSystem</code>). If a file name, a memory-mapped Arrow InputStream will be opened and closed when finished; compression will be detected from the file extension and handled automatically. If an input stream is provided, it will be left open.
delim	Single character used to separate fields within a record.
quote	Single character used to quote strings.
escape_double	Does the file escape quotes by doubling them? i.e. If this option is <code>TRUE</code> , the value <code>""""</code> represents a single quote, <code>\</code> .
escape_backslash	Does the file use backslashes to escape special characters? This is more general than <code>escape_double</code> as backslashes can be used to escape the delimiter character, the quote character, or to add special characters like <code>\n</code> .
schema	Schema that describes the table. If provided, it will be used to satisfy both <code>col_names</code> and <code>col_types</code> .
col_names	If <code>TRUE</code> , the first row of the input will be used as the column names and will not be included in the data frame. If <code>FALSE</code> , column names will be generated by Arrow, starting with <code>"f0"</code> , <code>"f1"</code> , ..., <code>"fN"</code> . Alternatively, you can specify a character vector of column names.

col_types	A compact string representation of the column types, or NULL (the default) to infer types from the data.
col_select	A character vector of column names to keep, as in the "select" argument to <code>data.table::fread()</code> , or a tidy selection specification of columns, as used in <code>dplyr::select()</code> .
na	A character vector of strings to interpret as missing values.
quoted_na	Should missing values inside quotes be treated as missing values (the default) or strings. (Note that this is different from the the Arrow C++ default for the corresponding convert option, <code>strings_can_be_null</code> .)
skip_empty_rows	Should blank rows be ignored altogether? If TRUE, blank rows will not be represented at all. If FALSE, they will be filled with missings.
skip	Number of lines to skip before reading data.
parse_options	see file reader options . If given, this overrides any parsing options provided in other arguments (e.g. <code>delim</code> , <code>quote</code> , etc.).
convert_options	see file reader options
read_options	see file reader options
as_data_frame	Should the function return a <code>data.frame</code> (default) or an Arrow Table ?
timestamp_parsers	User-defined timestamp parsers. If more than one parser is specified, the CSV conversion logic will try parsing values starting from the beginning of this vector. Possible values are: <ul style="list-style-type: none"> • NULL: the default, which uses the ISO-8601 parser • a character vector of strptime parse strings • a list of TimestampParser objects

Details

`read_csv_arrow()` and `read_tsv_arrow()` are wrappers around `read_delim_arrow()` that specify a delimiter.

Note that not all readr options are currently implemented here. Please file an issue if you encounter one that arrow should support.

If you need to control Arrow-specific reader parameters that don't have an equivalent in `readr::read_csv()`, you can either provide them in the `parse_options`, `convert_options`, or `read_options` arguments, or you can use [CsvTableReader](#) directly for lower-level access.

Value

A `data.frame`, or a `Table` if `as_data_frame = FALSE`.

Specifying column types and names

By default, the CSV reader will infer the column names and data types from the file, but there are a few ways you can specify them directly.

One way is to provide an Arrow [Schema](#) in the schema argument, which is an ordered map of column name to type. When provided, it satisfies both the col_names and col_types arguments. This is good if you know all of this information up front.

You can also pass a Schema to the col_types argument. If you do this, column names will still be inferred from the file unless you also specify col_names. In either case, the column names in the Schema must match the data's column names, whether they are explicitly provided or inferred. That said, this Schema does not have to reference all columns: those omitted will have their types inferred.

Alternatively, you can declare column types by providing the compact string representation that readr uses to the col_types argument. This means you provide a single string, one character per column, where the characters map to Arrow types analogously to the readr type mapping:

- "c": utf8()
- "i": int32()
- "n": float64()
- "d": float64()
- "l": bool()
- "f": dictionary()
- "D": date32()
- "T": time32()
- "t": timestamp()
- "_": null()
- "-": null()
- "?": infer the type from the data

If you use the compact string representation for col_types, you must also specify col_names.

Regardless of how types are specified, all columns with a null() type will be dropped.

Note that if you are specifying column names, whether by schema or col_names, and the CSV file has a header row that would otherwise be used to identify column names, you'll need to add skip = 1 to skip that row.

Examples

```
tf <- tempfile()
on.exit(unlink(tf))
write.csv(mtcars, file = tf)
df <- read_csv_arrow(tf)
dim(df)
# Can select columns
df <- read_csv_arrow(tf, col_select = starts_with("d"))
```

read_feather	<i>Read a Feather file</i>
--------------	----------------------------

Description

Feather provides binary columnar serialization for data frames. It is designed to make reading and writing data frames efficient, and to make sharing data across data analysis languages easy. This function reads both the original, limited specification of the format and the version 2 specification, which is the Apache Arrow IPC file format.

Usage

```
read_feather(file, col_select = NULL, as_data_frame = TRUE, ...)
```

Arguments

file	A character file name or URI, raw vector, an Arrow input stream, or a <code>FileSystem</code> with path (<code>SubTreeFileSystem</code>). If a file name or URI, an Arrow InputStream will be opened and closed when finished. If an input stream is provided, it will be left open.
col_select	A character vector of column names to keep, as in the "select" argument to <code>data.table::fread()</code> , or a tidy selection specification of columns, as used in <code>dplyr::select()</code> .
as_data_frame	Should the function return a <code>data.frame</code> (default) or an Arrow Table ?
...	additional parameters, passed to FeatherReader\$create()

Value

A `data.frame` if `as_data_frame` is `TRUE` (the default), or an Arrow [Table](#) otherwise

See Also

[FeatherReader](#) and [RecordBatchReader](#) for lower-level access to reading Arrow IPC data.

Examples

```
tf <- tempfile()
on.exit(unlink(tf))
write_feather(mtcars, tf)
df <- read_feather(tf)
dim(df)
# Can select columns
df <- read_feather(tf, col_select = starts_with("d"))
```

read_json_arrow *Read a JSON file*

Description

Using [JsonTableReader](#)

Usage

```
read_json_arrow(file, col_select = NULL, as_data_frame = TRUE, ...)
```

Arguments

file	A character file name or URI, raw vector, an Arrow input stream, or a <code>FileSystem</code> with path (<code>SubTreeFileSystem</code>). If a file name, a memory-mapped Arrow InputStream will be opened and closed when finished; compression will be detected from the file extension and handled automatically. If an input stream is provided, it will be left open.
col_select	A character vector of column names to keep, as in the "select" argument to <code>data.table::fread()</code> , or a tidy selection specification of columns, as used in <code>dplyr::select()</code> .
as_data_frame	Should the function return a <code>data.frame</code> (default) or an Arrow Table ?
...	Additional options, passed to <code>json_table_reader()</code>

Value

A `data.frame`, or an `Table` if `as_data_frame = FALSE`.

Examples

```
tf <- tempfile()
on.exit(unlink(tf))
writeLines('
  { "hello": 3.5, "world": false, "yo": "thing" }
  { "hello": 3.25, "world": null }
  { "hello": 0.0, "world": true, "yo": null }
', tf, useBytes=TRUE)
df <- read_json_arrow(tf)
```

read_message	<i>Read a Message from a stream</i>
--------------	-------------------------------------

Description

Read a Message from a stream

Usage

```
read_message(stream)
```

Arguments

stream	an <code>InputStream</code>
--------	-----------------------------

read_parquet	<i>Read a Parquet file</i>
--------------	----------------------------

Description

'[Parquet](#)' is a columnar storage file format. This function enables you to read Parquet files into R.

Usage

```
read_parquet(
  file,
  col_select = NULL,
  as_data_frame = TRUE,
  props = ParquetReaderProperties$create(),
  ...
)
```

Arguments

file	A character file name or URI, raw vector, an Arrow input stream, or a <code>FileSystem</code> with path (<code>SubTreeFileSystem</code>). If a file name or URI, an Arrow InputStream will be opened and closed when finished. If an input stream is provided, it will be left open.
col_select	A character vector of column names to keep, as in the "select" argument to <code>data.table::fread()</code> , or a tidy selection specification of columns, as used in <code>dplyr::select()</code> .
as_data_frame	Should the function return a <code>data.frame</code> (default) or an Arrow Table ?
props	ParquetReaderProperties
...	Additional arguments passed to <code>ParquetFileReader\$create()</code>

Value

A [arrow::Table](#), or a `data.frame` if `as_data_frame` is `TRUE` (the default).

Examples

```
tf <- tempfile()
on.exit(unlink(tf))
write_parquet(mtcars, tf)
df <- read_parquet(tf, col_select = starts_with("d"))
head(df)
```

<code>read_schema</code>	<i>read a Schema from a stream</i>
--------------------------	------------------------------------

Description

read a Schema from a stream

Usage

```
read_schema(stream, ...)
```

Arguments

<code>stream</code>	a Message, InputStream, or Buffer
<code>...</code>	currently ignored

Value

A [Schema](#)

<code>RecordBatch</code>	<i>RecordBatch class</i>
--------------------------	--------------------------

Description

A record batch is a collection of equal-length arrays matching a particular [Schema](#). It is a table-like data structure that is semantically a sequence of [fields](#), each a contiguous [Arrow Array](#).

Usage

```
record_batch(..., schema = NULL)
```

Arguments

...	A <code>data.frame</code> or a named set of Arrays or vectors. If given a mixture of <code>data.frames</code> and vectors, the inputs will be autospliced together (see examples). Alternatively, you can provide a single Arrow IPC <code>InputStream</code> , <code>Message</code> , <code>Buffer</code> , or R raw object containing a <code>Buffer</code> .
schema	a Schema , or <code>NULL</code> (the default) to infer the schema from the data in ... When providing an Arrow IPC buffer, schema is required.

S3 Methods and Usage

Record batches are data-frame-like, and many methods you expect to work on a `data.frame` are implemented for `RecordBatch`. This includes `[], [[, $, names, dim, nrow, ncol, head, and tail`. You can also pull the data from an Arrow record batch into R with `as.data.frame()`. See the examples.

A caveat about the `$` method: because `RecordBatch` is an R6 object, `$` is also used to access the object's methods (see below). Methods take precedence over the table's columns. So, `batch$Slice` would return the "Slice" method function even if there were a column in the table called "Slice".

R6 Methods

In addition to the more R-friendly S3 methods, a `RecordBatch` object has the following R6 methods that map onto the underlying C++ methods:

- `$Equals(other)`: Returns `TRUE` if the other record batch is equal
- `$column(i)`: Extract an `Array` by integer position from the batch
- `$column_name(i)`: Get a column's name by integer position
- `$names()`: Get all column names (called by `names(batch)`)
- `$GetColumnByName(name)`: Extract an `Array` by string name
- `$RemoveColumn(i)`: Drops a column from the batch by integer position
- `$selectColumns(indices)`: Return a new record batch with a selection of columns, expressed as 0-based integers.
- `$Slice(offset, length = NULL)`: Create a zero-copy view starting at the indicated integer offset and going for the given length, or to the end of the table if `NULL`, the default.
- `$Take(i)`: return an `RecordBatch` with rows at positions given by integers (R vector or `Array` `i`).
- `$Filter(i, keep_na = TRUE)`: return an `RecordBatch` with rows at positions where logical vector (or Arrow boolean `Array` `i`) is `TRUE`.
- `$serialize()`: Returns a raw vector suitable for interprocess communication
- `$cast(target_schema, safe = TRUE, options = cast_options(safe))`: Alter the schema of the record batch.

There are also some active bindings

- `$num_columns`
- `$num_rows`
- `$schema`

- `$metadata`: Returns the key-value metadata of the Schema as a named list. Modify or replace by assigning in `(batch$metadata <- new_metadata)`. All list elements are coerced to string.
- `$columns`: Returns a list of Arrays

Examples

```
batch <- record_batch(name = rownames(mtcars), mtcars)
dim(batch)
dim(head(batch))
names(batch)
batch$mpg
batch[["cyl"]]
as.data.frame(batch[4:8, c("gear", "hp", "wt")])
```

RecordBatchReader *RecordBatchReader classes*

Description

Apache Arrow defines two formats for **serializing data for interprocess communication (IPC)**: a "stream" format and a "file" format, known as Feather. `RecordBatchStreamReader` and `RecordBatchFileReader` are interfaces for accessing record batches from input sources those formats, respectively.

For guidance on how to use these classes, see the examples section.

Factory

The `RecordBatchFileReader$create()` and `RecordBatchStreamReader$create()` factory methods instantiate the object and take a single argument, named according to the class:

- `file` A character file name, raw vector, or Arrow file connection object (e.g. [RandomAccessFile](#)).
- `stream` A raw vector, [Buffer](#), or [InputStream](#).

Methods

- `$read_next_batch()`: Returns a `RecordBatch`, iterating through the Reader. If there are no further batches in the Reader, it returns `NULL`.
- `$schema`: Returns a [Schema](#) (active binding)
- `$batches()`: Returns a list of `RecordBatches`
- `$read_table()`: Collects the reader's `RecordBatches` into a [Table](#)
- `$get_batch(i)`: For `RecordBatchFileReader`, return a particular batch by an integer index.
- `$num_record_batches()`: For `RecordBatchFileReader`, see how many batches are in the file.

See Also

[read_ipc_stream\(\)](#) and [read_feather\(\)](#) provide a much simpler interface for reading data from these formats and are sufficient for many use cases.

Examples

```

tf <- tempfile()
on.exit(unlink(tf))

batch <- record_batch(chickwts)

# This opens a connection to the file in Arrow
file_obj <- FileOutputStream$create(tf)
# Pass that to a RecordBatchWriter to write data conforming to a schema
writer <- RecordBatchFileWriter$create(file_obj, batch$schema)
writer$write(batch)
# You may write additional batches to the stream, provided that they have
# the same schema.
# Call "close" on the writer to indicate end-of-file/stream
writer$close()
# Then, close the connection--closing the IPC message does not close the file
file_obj$close()

# Now, we have a file we can read from. Same pattern: open file connection,
# then pass it to a RecordBatchReader
read_file_obj <- ReadableFile$create(tf)
reader <- RecordBatchFileReader$create(read_file_obj)
# RecordBatchFileReader knows how many batches it has (StreamReader does not)
reader$num_record_batches
# We could consume the Reader by calling $read_next_batch() until all are,
# consumed, or we can call $read_table() to pull them all into a Table
tab <- reader$read_table()
# Call as.data.frame to turn that Table into an R data.frame
df <- as.data.frame(tab)
# This should be the same data we sent
all.equal(df, chickwts, check.attributes = FALSE)
# Unlike the Writers, we don't have to close RecordBatchReaders,
# but we do still need to close the file connection
read_file_obj$close()

```

RecordBatchWriter

RecordBatchWriter classes

Description

Apache Arrow defines two formats for **serializing data for interprocess communication (IPC)**: a "stream" format and a "file" format, known as Feather. RecordBatchStreamWriter and RecordBatchFileWriter are interfaces for writing record batches to those formats, respectively.

For guidance on how to use these classes, see the examples section.

Factory

The `RecordBatchFileWriter$create()` and `RecordBatchStreamWriter$create()` factory methods instantiate the object and take the following arguments:

- `sink` An `OutputStream`
- `schema` A [Schema](#) for the data to be written
- `use_legacy_format` logical: write data formatted so that Arrow libraries versions 0.14 and lower can read it. Default is `FALSE`. You can also enable this by setting the environment variable `ARROW_PRE_0_15_IPC_FORMAT=1`.
- `metadata_version`: A string like "V5" or the equivalent integer indicating the Arrow IPC `MetadataVersion`. Default (`NULL`) will use the latest version, unless the environment variable `ARROW_PRE_1_0_METADATA_VERSION=1`, in which case it will be V4.

Methods

- `$write(x)`: Write a [RecordBatch](#), [Table](#), or `data.frame`, dispatching to the methods below appropriately
- `$write_batch(batch)`: Write a `RecordBatch` to stream
- `$write_table(table)`: Write a `Table` to stream
- `$close()`: close stream. Note that this indicates end-of-file or end-of-stream—it does not close the connection to the sink. That needs to be closed separately.

See Also

[write_ipc_stream\(\)](#) and [write_feather\(\)](#) provide a much simpler interface for writing data to these formats and are sufficient for many use cases. [write_to_raw\(\)](#) is a version that serializes data to a buffer.

Examples

```
tf <- tempfile()
on.exit(unlink(tf))

batch <- record_batch(chickwts)

# This opens a connection to the file in Arrow
file_obj <- FileOutputStream$create(tf)
# Pass that to a RecordBatchWriter to write data conforming to a schema
writer <- RecordBatchFileWriter$create(file_obj, batch$schema)
writer$write(batch)
# You may write additional batches to the stream, provided that they have
# the same schema.
# Call "close" on the writer to indicate end-of-file/stream
writer$close()
# Then, close the connection--closing the IPC message does not close the file
file_obj$close()

# Now, we have a file we can read from. Same pattern: open file connection,
```

```

# then pass it to a RecordBatchReader
read_file_obj <- ReadableFile$create(tf)
reader <- RecordBatchFileReader$create(read_file_obj)
# RecordBatchFileReader knows how many batches it has (StreamReader does not)
reader$num_record_batches
# We could consume the Reader by calling $read_next_batch() until all are,
# consumed, or we can call $read_table() to pull them all into a Table
tab <- reader$read_table()
# Call as.data.frame to turn that Table into an R data.frame
df <- as.data.frame(tab)
# This should be the same data we sent
all.equal(df, chickwts, check.attributes = FALSE)
# Unlike the Writers, we don't have to close RecordBatchReaders,
# but we do still need to close the file connection
read_file_obj$close()

```

s3_bucket

Connect to an AWS S3 bucket

Description

`s3_bucket()` is a convenience function to create an `S3FileSystem` object that automatically detects the bucket's AWS region and holding onto the its relative path.

Usage

```
s3_bucket(bucket, ...)
```

Arguments

bucket	string S3 bucket name or path
...	Additional connection options, passed to <code>S3FileSystem\$create()</code>

Value

A `SubTreeFileSystem` containing an `S3FileSystem` and the bucket's relative path. Note that this function's success does not guarantee that you are authorized to access the bucket's contents.

Examples

```

if (arrow_with_s3()) {
  bucket <- s3_bucket("ursa-labs-taxi-data")
}

```

Scalar	<i>Arrow scalars</i>
--------	----------------------

Description

A Scalar holds a single value of an Arrow type.

Scanner	<i>Scan the contents of a dataset</i>
---------	---------------------------------------

Description

A Scanner iterates over a [Dataset](#)'s fragments and returns data according to given row filtering and column projection. A `ScannerBuilder` can help create one.

Factory

`Scanner$create()` wraps the `ScannerBuilder` interface to make a `Scanner`. It takes the following arguments:

- `dataset`: A `Dataset` or `arrow_dplyr_query` object, as returned by the `dplyr` methods on `Dataset`.
- `projection`: A character vector of column names to select
- `filter`: A `Expression` to filter the scanned rows by, or `TRUE` (default) to keep all rows.
- `use_threads`: logical: should scanning use multithreading? Default `TRUE`
- `...`: Additional arguments, currently ignored

Methods

`ScannerBuilder` has the following methods:

- `$Project(cols)`: Indicate that the scan should only return columns given by `cols`, a character vector of column names
- `$Filter(expr)`: Filter rows by an [Expression](#).
- `$UseThreads(threads)`: logical: should the scan use multithreading? The method's default input is `TRUE`, but you must call the method to enable multithreading because the scanner default is `FALSE`.
- `$BatchSize(batch_size)`: integer: Maximum row count of scanned record batches, default is 32K. If scanned record batches are overflowing memory then this method can be called to reduce their size.
- `$schema`: Active binding, returns the [Schema](#) of the `Dataset`
- `$Finish()`: Returns a `Scanner`

`Scanner` currently has a single method, `$ToTable()`, which evaluates the query and returns an [Arrow Table](#).

Schema

Schema class

Description

A Schema is a list of [Fields](#), which map names to Arrow [data types](#). Create a Schema when you want to convert an R `data.frame` to Arrow but don't want to rely on the default mapping of R types to Arrow types, such as when you want to choose a specific numeric precision, or when creating a [Dataset](#) and you want to ensure a specific schema rather than inferring it from the various files.

Many Arrow objects, including [Table](#) and [Dataset](#), have a `$schema` method (active binding) that lets you access their schema.

Usage

```
schema(...)
```

Arguments

```
...          named list of data types
```

Methods

- `$ToString()`: convert to a string
- `$field(i)`: returns the field at index `i` (0-based)
- `$GetFieldByName(x)`: returns the field with name `x`
- `$WithMetadata(metadata)`: returns a new Schema with the key-value metadata set. Note that all list elements in metadata will be coerced to character.

Active bindings

- `$names`: returns the field names (called in `names(Schema)`)
- `$num_fields`: returns the number of fields (called in `length(Schema)`)
- `$fields`: returns the list of `Fields` in the Schema, suitable for iterating over
- `$HasMetadata`: logical: does this Schema have extra metadata?
- `$metadata`: returns the key-value metadata as a named list. Modify or replace by assigning in (`sch$metadata <- new_metadata`). All list elements are coerced to string.

Examples

```
df <- data.frame(col1 = 2:4, col2 = c(0.1, 0.3, 0.5))
tab1 <- Table$create(df)
tab1$schema
tab2 <- Table$create(df, schema = schema(col1 = int8(), col2 = float32()))
tab2$schema
```

Table	<i>Table class</i>
-------	--------------------

Description

A Table is a sequence of [chunked arrays](#). They have a similar interface to [record batches](#), but they can be composed from multiple record batches or chunked arrays.

Factory

The `Table$create()` function takes the following arguments:

- ... arrays, chunked arrays, or R vectors, with names; alternatively, an unnamed series of [record batches](#) may also be provided, which will be stacked as rows in the table.
- schema a [Schema](#), or NULL (the default) to infer the schema from the data in ...

S3 Methods and Usage

Tables are data-frame-like, and many methods you expect to work on a `data.frame` are implemented for Table. This includes `[], [[, $, names, dim, nrow, ncol, head, and tail`. You can also pull the data from an Arrow table into R with `as.data.frame()`. See the examples.

A caveat about the `$` method: because Table is an R6 object, `$` is also used to access the object's methods (see below). Methods take precedence over the table's columns. So, `tab$Slice` would return the "Slice" method function even if there were a column in the table called "Slice".

R6 Methods

In addition to the more R-friendly S3 methods, a Table object has the following R6 methods that map onto the underlying C++ methods:

- `$column(i)`: Extract a `ChunkedArray` by integer position from the table
- `$columnNames()`: Get all column names (called by `names(tab)`)
- `$getColumnByName(name)`: Extract a `ChunkedArray` by string name
- `$field(i)`: Extract a `Field` from the table schema by integer position
- `$selectColumns(indices)`: Return new Table with specified columns, expressed as 0-based integers.
- `$slice(offset, length = NULL)`: Create a zero-copy view starting at the indicated integer offset and going for the given length, or to the end of the table if NULL, the default.
- `$take(i)`: return an Table with rows at positions given by integers `i`. If `i` is an Arrow Array or `ChunkedArray`, it will be coerced to an R vector before taking.
- `$filter(i, keep_na = TRUE)`: return an Table with rows at positions where logical vector or Arrow boolean-type (`ChunkedArray`) `i` is TRUE.
- `$serialize(output_stream, ...)`: Write the table to the given [OutputStream](#)
- `$cast(target_schema, safe = TRUE, options = cast_options(safe))`: Alter the schema of the record batch.

There are also some active bindings:

- `$num_columns`
- `$num_rows`
- `$schema`
- `$metadata`: Returns the key-value metadata of the Schema as a named list. Modify or replace by assigning in (`tab$metadata <- new_metadata`). All list elements are coerced to string.
- `$columns`: Returns a list of `ChunkedArrays`

Examples

```
tab <- Table$create(name = rownames(mtcars), mtcars)
dim(tab)
dim(head(tab))
names(tab)
tab$mpg
tab[["cyl"]]
as.data.frame(tab[4:8, c("gear", "hp", "wt")])
```

type

infer the arrow Array type from an R vector

Description

infer the arrow Array type from an R vector

Usage

```
type(x)
```

Arguments

x an R vector

Value

an arrow logical type

unify_schemas	<i>Combine and harmonize schemas</i>
---------------	--------------------------------------

Description

Combine and harmonize schemas

Usage

```
unify_schemas(..., schemas = list(...))
```

Arguments

...	Schemas to unify
schemas	Alternatively, a list of schemas

Value

A Schema with the union of fields contained in the inputs

Examples

```
## Not run:
a <- schema(b = double(), c = bool())
z <- schema(b = double(), k = utf8())
unify_schemas(a, z)

## End(Not run)
```

write_arrow	<i>Write Arrow IPC stream format</i>
-------------	--------------------------------------

Description

Apache Arrow defines two formats for **serializing data for interprocess communication (IPC)**: a "stream" format and a "file" format, known as Feather. `write_ipc_stream()` and `write_feather()` write those formats, respectively.

Usage

```
write_arrow(x, sink, ...)

write_ipc_stream(x, sink, ...)
```


Arguments

x data.frame, [RecordBatch](#), or [Table](#)

sink A string file path, URI, or [OutputStream](#), or path in a file system (SubTreeFileSystem)

... extra parameters passed to write_feather().

Details

write_arrow(), a wrapper around write_ipc_stream() and write_feather() with some non-standard behavior, is deprecated. You should explicitly choose the function that will write the desired IPC format (stream or file) since either can be written to a file or OutputStream.

Value

x, invisibly.

See Also

[write_feather\(\)](#) for writing IPC files. [write_to_raw\(\)](#) to serialize data to a buffer. [RecordBatchWriter](#) for a lower-level interface.

write_dataset

Write a dataset

Description

This function allows you to write a dataset. By writing to more efficient binary storage formats, and by specifying relevant partitioning, you can make it much faster to read and query.

Usage

```
write_dataset(
  dataset,
  path,
  format = dataset$format,
  partitioning = dplyr::group_vars(dataset),
  basename_template = paste0("part-i.", as.character(format)),
  hive_style = TRUE,
  ...
)
```

Arguments

dataset [Dataset](#), [RecordBatch](#), [Table](#), arrow_dplyr_query, or data.frame. If an arrow_dplyr_query or grouped_df, schema and partitioning will be taken from the result of any select() and group_by() operations done on the dataset. filter() queries will be applied to restrict written rows. Note that select()-ed columns may not be renamed.

path	string path, URI, or SubTreeFileSystem referencing a directory to write to (directory will be created if it does not exist)
format	file format to write the dataset to. Currently supported formats are "feather" (aka "ipc") and "parquet". Default is to write to the same format as dataset.
partitioning	Partitioning or a character vector of columns to use as partition keys (to be written as path segments). Default is to use the current group_by() columns.
basename_template	string template for the names of files to be written. Must contain "{i}", which will be replaced with an autoincremented integer to generate basenames of datafiles. For example, "part-{i}.feather" will yield "part-0.feather", ...
hive_style	logical: write partition segments as Hive-style (key1=value1/key2=value2/file.ext) or as just bare values. Default is TRUE.
...	additional format-specific arguments. For available Parquet options, see write_parquet() . The available Feather options are <ul style="list-style-type: none"> • use_legacy_format logical: write data formatted so that Arrow libraries versions 0.14 and lower can read it. Default is FALSE. You can also enable this by setting the environment variable ARROW_PRE_0_15_IPC_FORMAT=1. • metadata_version: A string like "V5" or the equivalent integer indicating the Arrow IPC MetadataVersion. Default (NULL) will use the latest version, unless the environment variable ARROW_PRE_1_0_METADATA_VERSION=1, in which case it will be V4. • codec: A Codec which will be used to compress body buffers of written files. Default (NULL) will not compress body buffers.

Value

The input dataset, invisibly

write_feather	<i>Write data in the Feather format</i>
---------------	---

Description

Feather provides binary columnar serialization for data frames. It is designed to make reading and writing data frames efficient, and to make sharing data across data analysis languages easy. This function writes both the original, limited specification of the format and the version 2 specification, which is the Apache Arrow IPC file format.

Usage

```
write_feather(
  x,
  sink,
  version = 2,
  chunk_size = 65536L,
```

```

    compression = c("default", "lz4", "uncompressed", "zstd"),
    compression_level = NULL
  )

```

Arguments

x	data.frame, RecordBatch , or Table
sink	A string file path, URI, or OutputStream , or path in a file system (SubTreeFileSystem)
version	integer Feather file version. Version 2 is the current. Version 1 is the more limited legacy format.
chunk_size	For V2 files, the number of rows that each chunk of data should have in the file. Use a smaller chunk_size when you need faster random row access. Default is 64K. This option is not supported for V1.
compression	Name of compression codec to use, if any. Default is "lz4" if LZ4 is available in your build of the Arrow C++ library, otherwise "uncompressed". "zstd" is the other available codec and generally has better compression ratios in exchange for slower read and write performance See codec_is_available() . This option is not supported for V1.
compression_level	If compression is "zstd", you may specify an integer compression level. If omitted, the compression codec's default compression level is used.

Value

The input x, invisibly. Note that if sink is an [OutputStream](#), the stream will be left open.

See Also

[RecordBatchWriter](#) for lower-level access to writing Arrow IPC data.

Examples

```

tf <- tempfile()
on.exit(unlink(tf))
write_feather(mtcars, tf)

```

write_parquet

Write Parquet file to disk

Description

Parquet is a columnar storage file format. This function enables you to write Parquet files from R.

Usage

```
write_parquet(
  x,
  sink,
  chunk_size = NULL,
  version = NULL,
  compression = default_parquet_compression(),
  compression_level = NULL,
  use_dictionary = NULL,
  write_statistics = NULL,
  data_page_size = NULL,
  use_deprecated_int96_timestamps = FALSE,
  coerce_timestamps = NULL,
  allow_truncated_timestamps = FALSE,
  properties = NULL,
  arrow_properties = NULL
)
```

Arguments

<code>x</code>	data.frame, RecordBatch , or Table
<code>sink</code>	A string file path, URI, or OutputStream , or path in a file system (SubTreeFileSystem)
<code>chunk_size</code>	chunk size in number of rows. If NULL, the total number of rows is used.
<code>version</code>	parquet version, "1.0" or "2.0". Default "1.0". Numeric values are coerced to character.
<code>compression</code>	compression algorithm. Default "snappy". See details.
<code>compression_level</code>	compression level. Meaning depends on compression algorithm
<code>use_dictionary</code>	Specify if we should use dictionary encoding. Default TRUE
<code>write_statistics</code>	Specify if we should write statistics. Default TRUE
<code>data_page_size</code>	Set a target threshold for the approximate encoded size of data pages within a column chunk (in bytes). Default 1 MiB.
<code>use_deprecated_int96_timestamps</code>	Write timestamps to INT96 Parquet format. Default FALSE.
<code>coerce_timestamps</code>	Cast timestamps a particular resolution. Can be NULL, "ms" or "us". Default NULL (no casting)
<code>allow_truncated_timestamps</code>	Allow loss of data when coercing timestamps to a particular resolution. E.g. if microsecond or nanosecond data is lost when coercing to "ms", do not raise an exception
<code>properties</code>	A <code>ParquetWriterProperties</code> object, used instead of the options enumerated in this function's signature. Providing <code>properties</code> as an argument is deprecated; if you need to assemble <code>ParquetWriterProperties</code> outside of <code>write_parquet()</code> , use <code>ParquetFileWriter</code> instead.

arrow_properties

A ParquetArrowWriterProperties object. Like properties, this argument is deprecated.

Details

Due to features of the format, Parquet files cannot be appended to. If you want to use the Parquet format but also want the ability to extend your dataset, you can write to additional Parquet files and then treat the whole directory of files as a [Dataset](#) you can query. See `vignette("dataset", package = "arrow")` for examples of this.

The parameters `compression`, `compression_level`, `use_dictionary` and `write_statistics` support various patterns:

- The default NULL leaves the parameter unspecified, and the C++ library uses an appropriate default for each column (defaults listed above)
- A single, unnamed, value (e.g. a single string for compression) applies to all columns
- An unnamed vector, of the same size as the number of columns, to specify a value for each column, in positional order
- A named vector, to specify the value for the named columns, the default value for the setting is used when not supplied

The `compression` argument can be any of the following (case insensitive): "uncompressed", "snappy", "gzip", "brotli", "zstd", "lz4", "lzo" or "bz2". Only "uncompressed" is guaranteed to be available, but "snappy" and "gzip" are almost always included. See `codec_is_available()`. The default "snappy" is used if available, otherwise "uncompressed". To disable compression, set `compression = "uncompressed"`. Note that "uncompressed" columns may still have dictionary encoding.

Value

the input `x` invisibly.

Examples

```
tf1 <- tempfile(fileext = ".parquet")
write_parquet(data.frame(x = 1:5), tf1)

# using compression
if (codec_is_available("gzip")) {
  tf2 <- tempfile(fileext = ".gz.parquet")
  write_parquet(data.frame(x = 1:5), tf2, compression = "gzip", compression_level = 5)
}
```

write_to_raw	<i>Write Arrow data to a raw vector</i>
--------------	---

Description

`write_ipc_stream()` and `write_feather()` write data to a sink and return the data (`data.frame`, `RecordBatch`, or `Table`) they were given. This function wraps those so that you can serialize data to a buffer and access that buffer as a raw vector in R.

Usage

```
write_to_raw(x, format = c("stream", "file"))
```

Arguments

x	<code>data.frame</code> , <code>RecordBatch</code> , or <code>Table</code>
format	one of <code>c("stream", "file")</code> , indicating the IPC format to use

Value

A raw vector containing the bytes of the IPC serialized data.

Index

`$NewScan()`, 33

Array, 8, 46
Array (array), 4
array, 4
ArrayData, 4, 5
Arrays, 7
arrow::io::MemoryMappedFile, 31
arrow::io::OutputStream, 35
arrow::Table, 46
arrow_available, 5
arrow_available(), 28
arrow_with_s3 (arrow_available), 5

binary (data-type), 13
bool (data-type), 13
boolean (data-type), 13
Buffer, 27, 48
Buffer (buffer), 6
buffer, 6
BufferOutputStream (OutputStream), 33
BufferedReader (InputStream), 27

cast_options, 7
chunked arrays, 54
chunked_array (ChunkedArray), 7
ChunkedArray, 7, 34
Codec, 8, 9, 58
codec_is_available, 9
codec_is_available(), 8, 59, 61
compressed input and output streams, 8
CompressedInputStream (compression), 9
CompressedOutputStream (compression), 9
compression, 9
copy_files, 10
cpu_count, 10
CsvConvertOptions (CsvReadOptions), 11
CsvFileFormat (FileFormat), 21
CsvParseOptions (CsvReadOptions), 11
CsvReadOptions, 11, 13, 22

CsvTableReader, 12, 41

data type, 4
data types, 26, 53
data-type, 13
Dataset, 16, 17, 20, 33, 52, 53, 57, 61
dataset_factory, 17
dataset_factory(), 16, 32
DatasetFactory, 17
DatasetFactory (Dataset), 16
DataType, 18, 21
date32 (data-type), 13
date64 (data-type), 13
decimal (data-type), 13
dictionary, 19
dictionary(), 15
DictionaryArray (array), 4
DictionaryType, 19, 19
DirectoryPartitioning (Partitioning), 37
DirectoryPartitioningFactory (Partitioning), 37

Expression, 20, 52

FeatherReader, 20, 43
FeatherReader\$create(), 43
Field, 21, 53
field (Field), 21
fields, 46
file reader options, 41
FileFormat, 16, 17, 21
FileInfo, 22, 24
FileOutputStream (OutputStream), 33
FileSelector, 16, 23, 24
FileSystem, 16, 17, 23
FileSystemDataset (Dataset), 16
FileSystemDatasetFactory, 37
FileSystemDatasetFactory (Dataset), 16
FileWriteOptions, 25
fixed_size_binary (data-type), 13

- fixed_size_list_of (data-type), 13
- FixedSizeListArray (array), 4
- FixedSizeListType (data-type), 13
- FixedWidthType, 25
- flight_connect, 25
- flight_connect(), 26, 37
- flight_get, 26
- float (data-type), 13
- float16 (data-type), 13
- float32 (data-type), 13
- float64 (data-type), 13

- halffloat (data-type), 13
- hive_partition, 26
- hive_partition(), 18, 33
- hive_partition(...), 37
- HivePartitioning, 26
- HivePartitioning (Partitioning), 37
- HivePartitioningFactory (Partitioning), 37

- InMemoryDataset (Dataset), 16
- input file, 24
- input stream, 24
- InputStream, 9, 13, 27, 38, 40, 43–45, 48
- install_arrow, 28
- install_pyarrow, 29
- int16 (data-type), 13
- int32 (data-type), 13
- int32(), 19
- int64 (data-type), 13
- int8 (data-type), 13
- IpcFileFormat (FileFormat), 21

- JsonParseOptions (CsvReadOptions), 11
- JsonReadOptions (CsvReadOptions), 11
- JsonTableReader, 44
- JsonTableReader (CsvTableReader), 12

- large_binary (data-type), 13
- large_list_of (data-type), 13
- large_utf8 (data-type), 13
- LargeListArray (array), 4
- list_of (data-type), 13
- ListArray (array), 4
- load_flight_server, 29
- LocalFileSystem (FileSystem), 23

- map_batches, 30

- match_arrow, 30
- MemoryMappedFile (InputStream), 27
- Message, 31
- MessageReader, 31
- mmap_create, 31
- mmap_open, 32
- mmap_open(), 27

- null (data-type), 13

- open_dataset, 32
- open_dataset(), 16–18
- Other Arrow data types, 19
- output stream, 24
- OutputStream, 9, 33, 54, 57, 59, 60

- ParquetFileFormat (FileFormat), 21
- ParquetFileReader, 34, 35
- ParquetFileWriter, 35, 36
- ParquetReaderProperties, 34, 35, 45
- ParquetWriterProperties, 35, 36
- Partitioning, 37
- push_data, 37

- RandomAccessFile, 48
- RandomAccessFile (InputStream), 27
- read.csv(), 12
- read_arrow, 38
- read_csv_arrow (read_delim_arrow), 39
- read_csv_arrow(), 11, 12, 18, 22
- read_delim_arrow, 39
- read_feather, 43
- read_feather(), 20, 38, 48
- read_ipc_stream (read_arrow), 38
- read_ipc_stream(), 48
- read_json_arrow, 44
- read_json_arrow(), 11, 12
- read_message, 45
- read_parquet, 45
- read_schema, 46
- read_tsv_arrow (read_delim_arrow), 39
- ReadableFile (InputStream), 27
- record batches, 54
- record_batch (RecordBatch), 46
- RecordBatch, 26, 37, 46, 50, 57, 59, 60, 62
- RecordBatchFileReader
 - (RecordBatchReader), 48
- RecordBatchFileWriter
 - (RecordBatchWriter), 49

RecordBatchReader, [38](#), [43](#), [48](#)
RecordBatchStreamReader
 (RecordBatchReader), [48](#)
RecordBatchStreamWriter
 (RecordBatchWriter), [49](#)
RecordBatchWriter, [49](#), [57](#), [59](#)

s3_bucket, [51](#)
S3FileSystem (FileSystem), [23](#)
Scalar, [52](#)
Scanner, [20](#), [52](#)
ScannerBuilder, [16](#)
ScannerBuilder (Scanner), [52](#)
Schema, [16](#), [32](#), [35](#), [37](#), [40](#), [42](#), [46–48](#), [50](#), [52](#),
 [53](#), [54](#), [56](#)
schema (Schema), [53](#)
schema(), [13](#), [26](#)
Schemas, [21](#)
set_cpu_count (cpu_count), [10](#)
string (data-type), [13](#)
strptime, [12](#), [41](#)
strptime(), [12](#)
struct (data-type), [13](#)
StructArray (array), [4](#)
StructScalar (array), [4](#)
SubTreeFileSystem (FileSystem), [23](#)

Table, [7](#), [35](#), [38](#), [41](#), [43–45](#), [48](#), [50](#), [52](#), [53](#), [54](#),
 [57](#), [59](#), [60](#), [62](#)
tidy selection specification, [41](#), [43–45](#)
time32 (data-type), [13](#)
time64 (data-type), [13](#)
timestamp (data-type), [13](#)
TimestampParser, [12](#), [41](#)
TimestampParser (CsvReadOptions), [11](#)
type, [55](#)

uint16 (data-type), [13](#)
uint32 (data-type), [13](#)
uint64 (data-type), [13](#)
uint8 (data-type), [13](#)
unify_schemas, [56](#)
UnionDataset (Dataset), [16](#)
utf8 (data-type), [13](#)
utf8(), [19](#)

write_arrow, [56](#)
write_dataset, [57](#)
write_feather, [58](#)
write_feather(), [50](#), [56](#), [57](#), [62](#)
write_ipc_stream (write_arrow), [56](#)
write_ipc_stream(), [50](#), [62](#)
write_parquet, [36](#), [37](#), [59](#)
write_parquet(), [58](#)
write_to_raw, [62](#)
write_to_raw(), [50](#), [57](#)