

Package ‘assignR’

January 10, 2021

Type Package

Title Infer Geographic Origin from Isotopic Data

Version 2.0.0

Author Chao Ma, Gabe Bowen

Maintainer Gabe Bowen <gabe.bowen@utah.edu>

Description Routines for re-scaling isotope maps using known-origin tissue isotope data, assigning origin of unknown samples, and summarizing and assessing assignment results. Methods are adapted from Wunder (2010, in ISBN:9789048133536) and Vander Zanden, H. B. et al. (2014) <doi:10.1111/2041-210X.12229> as described in Ma, C. et al. (2020) <doi:10.1111/2041-210X.13426>.

Imports raster, sp, rgdal, maptools

Depends R (>= 3.5)

Suggests knitr, rmarkdown, testthat, covr

VignetteBuilder knitr

License GPL-3

Language en-US

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2021-01-10 04:00:02 UTC

R topics documented:

assignR	2
calRaster	2
d18o_world	4
d2h_lrNA	4
d2h_world	5

jointP	6
knownOrig	6
naMap	8
oddsRatio	9
pdRaster	10
plot.QA	11
QA	12
qtlRaster	15
refTrans	16
states	17
stds	18
subOrigData	19
unionP	21

Index	23
--------------	-----------

assignR	<i>Tools for inferring geographic origin from isotopic data</i>
---------	---

Description

Routines for rescaling isoscapes using known-origin tissue isotope data, assigning origin of unknown samples, and summarizing and assessing assignment results.

Author(s)

Maintainer: Gabe Bowen <gabe.bowen@utah.edu> **Authors:** Chao Ma, Gabe Bowen

See Also

<https://spatial-lab.github.io/assignR/>

calRaster	<i>Rescale isoscape using linear regression</i>
-----------	---

Description

This function uses known-origin tissue data to rescale a map of environmental isotope values to a map of tissue value (and associated uncertainty) using a linear regression model.

Usage

```
calRaster(known, isoscape, mask = NULL, interpMethod = 2, NA.value = NA,
  ignore.NA = TRUE, genplot = TRUE, outDir = NULL, verboseLM = TRUE)
```

Arguments

known	subOrigData or SpatialPointsDataFrame. Known-origin tissue isotope data from the subOrigData function or provided by user. User-provided data must be formatted as a subOrigData object (see subOrigData or a SpatialPointsDataFrame in which the first data field contains the measured tissue isotope value and the second the 1 standard deviation uncertainty on that value.
isoscape	raster. Isoscape raster with two layers. The first one is the mean and the second is one standard deviation.
mask	SpatialPolygonsDataFrame. Constrains the area of the output rasters. If this is not provided, the entire area of isoscape is returned.
interpMethod	numeric. 1 or 2. Designate one of two methods for extracting values from isoscape. If 1, values for the cell in which a point falls are returned. If 2 the returned values are interpolated (bilinear interpolation) from the values of the four adjacent grid cells.
NA.value	NA or numeric. Value representing the absence of data in isoscape. Commonly used values include NA, -9999, and 9999.
ignore.NA	logical. If NA values are extracted from isoscape at the location of samples in known, ignore these values and proceed with calRaster.
genplot	logical. Plot the results.
outDir	character string. Directory path to which output will be saved. If NULL no files are written.
verboseLM	logical. Print out the linear regression results.

Value

isoscape.rescale	RasterBrick. isoscape rescaled using a linear regression model between values of known and isoscape. The first layer is the mean prediction and the second the standard deviation.
lm.data	data.frame. Known origin data and extracted isoscape values used for linear regression modeling.
lm.model	list. Linear regression model.

See Also

[pdRaster](#)

Examples

```
# load North America boundary and global isoscape
data("naMap")
data("d2h_lrNA")

# load hydrogen isotope data for human hair in North America
d = subOrigData(group = "Modern human", mask = naMap, niter = 100)

# rescale from environmental isoscape to tissue isoscape
r = calRaster(known = d, isoscape = d2h_lrNA, mask = naMap)
```

d18o_world

data: global growing season O isoscape

Description

Global growing season precipitation O isoscape from waterisotopes.org

Usage

```
data("d18o_world")
```

Format

RasterStack with two layers. The first layer is the mean prediction and the second is 1 standard deviation

References

- Bowen, G. J. (2018) Gridded maps of the isotopic composition of meteoric waters. <http://www.waterisotopes.org>.
- Bowen, G. J., Wassenaar, L. I. and Hobson, K. A. (2005) Global application of stable hydrogen and oxygen isotopes to wildlife forensics. *Oecologia*, **143**, 337–348.
- IAEA/WMO (2018) Global Network of Isotopes in Precipitation. The GNIP Database. <https://nucleus.iaea.org/wiser>.

Examples

```
library(raster)

data("d18o_world")
plot(d18o_world)
```

d2h_lrNA

data: low resolution North American growing season H isoscape

Description

Interpolated growing season precipitation H isoscape from waterisotopes.org

Usage

```
data("d2h_lrNA")
```

Format

RasterBrick with two layers. The first layer is the mean prediction and the second is 1 standard deviation

References

- Bowen, G. J. (2018) Gridded maps of the isotopic composition of meteoric waters. <http://www.waterisotopes.org>.
- Bowen, G. J., Wassenaar, L. I. and Hobson, K. A. (2005) Global application of stable hydrogen and oxygen isotopes to wildlife forensics. *Oecologia*, **143**, 337–348.
- IAEA/WMO (2018) Global Network of Isotopes in Precipitation. The GNIP Database. <https://nucleus.iaea.org/wiser>.

Examples

```
library(raster)

data("d2h_1rNA")
plot(d2h_1rNA)
```

d2h_world	<i>data: global growing season H isoscape</i>
-----------	---

Description

Interpolated global growing season precipitation H isoscape from waterisotopes.org

Usage

```
data("d2h_world")
```

Format

RasterStack with two layers. The first layer is the mean prediction and the second is 1 standard deviation

References

- Bowen, G. J. (2018) Gridded maps of the isotopic composition of meteoric waters. <http://www.waterisotopes.org>.
- Bowen, G. J., Wassenaar, L. I. and Hobson, K. A. (2005) Global application of stable hydrogen and oxygen isotopes to wildlife forensics. *Oecologia*, **143**, 337–348.
- IAEA/WMO (2018) Global Network of Isotopes in Precipitation. The GNIP Database. <https://nucleus.iaea.org/wiser>.

Examples

```
library(raster)

data("d2h_world")
plot(d2h_world)
```

jointP *Joint probability of origin*

Description

Joint probability for individuals of common origin (product of probabilities)

Usage

```
jointP(pdR)
```

Arguments

pdR RasterStack or RasterBrick of probability density maps, e.g., as produced by calRaster. All layers must have common spatial extent and projection.

Examples

```
# load North America boundary and global isoscape
data("naMap")
data("d2h_lrNA")

# load hydrogen isotope data for human hair in North America
d = subOrigData(group = "Modern human", mask = naMap, niter = 100)

# rescale from environmental isoscape to tissue isoscape
r = calRaster(known = d, isoscape = d2h_lrNA, mask = naMap)

# four unknown-origin examples
id = c("A", "B", "C", "D")
d2H = c(-110, -90, -105, -102)
un = data.frame(id,d2H)

# assignment
asn = pdRaster(r, unknown = un, mask = naMap)

# joint probability for individuals of common origin
jointP(asn)
```

knownOrig *data: database of H and O isotope data for tissues of known origin*

Description

This dataset consists of hydrogen and oxygen isotope values and metadata for human hair, insect wings, and bird feathers of known geographic origin.

Usage

```
data("knownOrig")
```

Format

list.

sites SpatialPointsDataFrame with 5 fields. WGS84 unprojected geometry.

- [, 1] Site_ID: Unique ID
- [, 2] Site_name: Site name or descriptor
- [, 3] State: State or province of collection site, where recorded
- [, 4] Country: Country of collection site, where recorded
- [, 5] Site_comments: Site comments

samples data.frame with 15 fields.

- [, 1] Sample_ID: Unique ID
- [, 2] Sample_ID_orig: ID used in original data report
- [, 3] Site_ID: ID for sample collection site
- [, 4] Dataset_ID: ID for dataset from which sample is derived
- [, 5] Taxon: Genus and species name
- [, 6] Group: Biological group (informal)
- [, 7] Source_quality: Code indicating level of certainty in geographic origin
- [, 8] Age_class: Code for age of individual
- [, 9] Material_type: Tissue sampled, e.g., "Hair"
- [, 10] Matrix: Compound measured, e.g., "Keratin"
- [, 11] d2H: Hydrogen isotope value (permil)
- [, 12] d2H.sd: Reported analytical uncertainty for hydrogen isotope value (permil)
- [, 13] d18O: Oxygen isotope value (permil)
- [, 14] d18O.sd: Reported analytical uncertainty for oxygen isotope value (permil)
- [, 15] Sample_comments: Sample comments

sources data.frame with 17 fields.

- [, 1] Dataset_ID: Unique ID
- [, 2] Dataset_name: Short name or descriptor
- [, 3] Citation: Bibliographic citation for study
- [, 4] Sampling_method: How material was subsampled for analysis, if reported
- [, 5] Sample_powdered: Was sample powdered prior to analysis (Y/N/NA)?
- [, 6] Lipid_extraction: Were lipids chemically extracted prior to analysis (Y/N/NA)?
- [, 7] Lipid_extraction_method: Solvent used to extract lipids
- [, 8] Exchange: Was a correction for exchangeable H made (Y/N/NA)?
- [, 9] Exchange_method: Method used to correct for exchangeable H
- [, 10] Exchange_T: Was H exchange carried out at ambient or high temperature (Ambient/High/NA)?
- [, 11] H_cal: Reference scale used to calibrate H isotope data, see [stds](#) object hstds

- [, 12] O_cal: Reference scale used to calibrate O isotope data, see [stds](#) object ostds
- [, 13] Std_powdered: Were calibration standards powdered (Y/N/NA)?
- [, 14] Drying: Did the study document how samples were fully dried and transferred dry to instrument (Y/N/NA)?
- [, 15] Analysis_method: Instrument configuration used for analysis
- [, 16] Analysis_type: What elements were analyzed for stable isotope ratios (H/O/H₂O)?
- [, 17] Source_comments: Data source comments

See Also

[subOrigData](#)

Examples

```
library(sp)
data("knownOrig")
class(knownOrig$sites)
class(knownOrig$samples); class(knownOrig$sources)
summary(knownOrig$samples)
print(knownOrig$sources[, 1:2])
plot(assignR:::wrl_d_simpl, border = "grey")
plot(knownOrig$sites, add = TRUE)
```

naMap

data: naMap

Description

Simplified North American boundaries polygon

Usage

```
data("naMap")
```

Format

SpatialPolygonsDataFrame

Examples

```
library(sp)

data("naMap")
plot(naMap)
```

oddsRatio	<i>Odds ratio of points or regions</i>
-----------	--

Description

Calculate ratio of odds for two locations (points or polygons)

Usage

```
oddsRatio(pdR, inputP)
```

Arguments

pdR	RasterStack or RasterBrick of probability density maps, e.g., as produced by calRaster. All layers must have common projection.
inputP	SpatialPoints or SpatialPolygons (or *DataFrame equivalent) of length 2

Examples

```
library(sp)

# load North America boundary and global isoscape
data("naMap")
data("d2h_lrNA")

# load hydrogen isotope data for human hair in North America
d = subOrigData(group = "Modern human", mask = naMap, niter = 100)

# rescale from environmental isoscape to tissue isoscape
r = calRaster(known = d, isoscape = d2h_lrNA, mask = naMap)

# four unknown-origin examples
id = c("A", "B", "C", "D")
d2H = c(-110, -90, -105, -102)
un = data.frame(id,d2H)

# assignment
asn = pdRaster(r, unknown = un, mask = naMap)

# SpatialPolygons for two regions of interest
data("states")
s1 = states[states$STATE_ABBR == "UT",]
s2 = states[states$STATE_ABBR == "NM",]
plot(naMap)
plot(s1, border = "red", add=TRUE)
plot(s2, border = "blue", add=TRUE)

# Get odds ratio for two regions using SpatialPolygon method
s12 = rbind(s1, s2)
```

```

oddsRatio(asn, s12)

# Create SpatialPoints for two points of interest
pp1 = c(-112,40)
pp2 = c(-105,33)
pp12 = SpatialPoints(coords = rbind(pp1,pp2),
  proj4string=CRS("+proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0"))
points(pp12, pch = 21, bg = "light blue")

# Get odds ratio for two points using SpatialPoints method
oddsRatio(asn, pp12)

```

pdRaster

Probability of origin surfaces

Description

Calculate posterior probabilities of origin for a sample based on its isotope ratio.

Usage

```
pdRaster(r, unknown, prior = NULL, mask = NULL, genplot = TRUE, outDir = NULL)
```

Arguments

r	RasterStack or RasterBrick with two layers, e.g., as created by calRaster . The first layer is the tissue-specific isoscape and the second the isoscape prediction uncertainty (1 standard deviation).
unknown	data.frame. First column should be unique sample IDs, and second column should be tissue isotope values for the individuals for which the assignments will be made.
prior	raster. Optional raster layer with prior probabilities, which has the same projection, resolution and extent as r.
mask	SpatialPolygonsDataFrame. This mask will constrain the assignment area. If this is not provided, a default of mask of the extent of r is used.
genplot	logical. Plot results in R.
outDir	character string. Directory path to which output will be saved. If NULL no files are written.

Value

RasterStack or RasterLayer including a probability density surface for each individual in unknown. If outDir is not NULL, writes individual rasters in GeoTIFF format and a single PDF file with images for each probability density raster to the designated directory.

See Also

[calRaster](#)

Examples

```

# load North America boundary and global isoscape
data("naMap")
data("d2h_world")

# load hydrogen isotope data for human hair in North America
d = subOrigData(group = "Modern human", mask = naMap)

# rescale from environmental isoscape to tissue isoscape
r = calRaster(known = d, isoscape = d2h_world, mask = naMap)

# sample to assign
id = "smile"
d2H = -80
un = data.frame(id, d2H)

# posterior probability surface
asn = pdRaster(r, unknown = un, mask = naMap)

```

plot.QA

*Plot quality metrics for geographic assignments***Description**

Plot the output from [QA](#), including spatial precision, bias, sensitivity and odds ratio of known locations for validation samples.

Usage

```

## S3 method for class 'QA'
plot(x, ..., outDir = NULL)

```

Arguments

x	One or more QA objects
...	Other arguments to be passed to plot
outDir	character string. Directory path to which output will be saved. If NULL no files are written.

References

Ma, C. et al. (2020) assignR : An R package for isotope-based geographic assignment. *Methods in Ecology and Evolution* **11** 996–1001. doi: [10.1111/2041210X.13426](https://doi.org/10.1111/2041210X.13426).

Vander Zanden, H. B. et al. (2014) Contrasting assignment of migratory organisms to geographic origins using long-term versus year-specific precipitation isotope maps. *Methods in Ecology and Evolution* **5** 891–900. doi: [10.1111/2041210X.12229](https://doi.org/10.1111/2041210X.12229)

See Also[QA](#)**Examples**

```

# load data
data("naMap") # North America
data("d2h_lrNA") # precipitation hydrogen isoscape of North America
data("knownOrig") # isotopes of known-origin samples

# extract some known-origin data
d1 = subOrigData(taxon = "Buteo lagopus")

# run quality assessment based on precipitation hydrogen isotopes and
# known-origin samples; small values of valiStation and valiTime
# are used in example to reduce run time

# first with one example
# gives warning because a small number of samples are available
qa1 = QA(isoscape = d2h_lrNA, known = d1, valiStation = 1,
        valiTime = 2, by = 10, mask = naMap, name = "Buteo")

# plot the qa result
plot(qa1)

# now compare with a second data set
d2 = subOrigData(taxon = "Charadrius montanus")
qa2 = QA(isoscape = d2h_lrNA, known = d2, valiStation = 1,
        valiTime = 2, by = 10, mask = naMap, name = "Charadrius")
plot(qa1, qa2)

```

QA

*Quality assessment of geographic assignments***Description**

How well does a given isoscape and known origin data set constrain the geographic origin of samples? Uses iterative re-sampling of the known origin data set to evaluate sample assignments and reports a suite of quality metrics.

Usage

```
QA(known, isoscape, bySite = TRUE, valiStation = 1, valiTime = 50,
   by = 2, mask = NULL, setSeed = TRUE, name = NULL)
```

Arguments

known	subOrigData or SpatialPointsDataFrame. Known-origin tissue isotope data from the subOrigData function or provided by user. User-provided data must be formatted as a subOrgData object (see subOrigData) or a SpatialPointsDataFrame in which the first data field contains the measured tissue isotope value and the second the one standard deviation uncertainty on that value. A user-provided SpatialPointsDataFrame must include a field named “Site_ID” containing unique values for each sampling site to support the “bySite” option, otherwise use bySite = FALSE.
isoscape	RasterStack or RasterBrick with two layers. The first layer is mean isoscape prediction and the second the isoscape prediction uncertainty (one standard deviation).
bySite	logical. Resample known by site (TRUE) or by sample (FALSE)?
valiStation	numeric. How many sites or samples from known are withheld for validation? Must be two or more smaller than the length of known.
valiTime	numeric. How many times do you want to randomly draw validation samples and run the validation? Must be an integer equal to or greater than one.
by	integer. Threshold increment to use in evaluating assignment performance. Must be between 1 and 25.
mask	SpatialPolygonsDataFrame. Constrains the area of the output rasters. If this is not provided, the entire area of isoscape is returned.
setSeed	logical. Do you want to set.seed() when you randomly draw validation stations? “TRUE” gives the same sequence of random draws each time the function is called.
name	character. Useful for identifying the QA output in subsequent plotting.

Value

Returns an object of class “QA”.

val_stations	numeric. An X*Y data.frame of validation station IDs for all valiTime. X = valiTime and Y = valiStation.
pd_val	numeric. An X*Y data.frame containing the posterior probability density for the validation stations. X = valiTime and Y = valiStation.
prption_byArea	numeric. An X*Y data.frame showing the proportion of validation individuals for which the known origin is contained within the top 0.00 to 1.00 area quantile (with increment of by / 100; Y = ceiling(100 / by) + 1). X = valiTime.
prption_byProb	numeric. An X*Y data.frame showing the proportion of validation individuals for which the known origin is contained within the top 0.00 to 1.00 probability quantile (with increment of by / 100; Y = ceiling(100 / by) + 1). X = valiTime.
precision	list. The length of the list is valiTime. Each element is an X*Y matrix showing the proportional area of the total assignment surface covered by the assignment region at a given probability quantile from 0.00 to 1.00 (with increment of by / 100; X = ceiling(100 / by) + 1) for each validation sample (Y = valiStation).

random_prob_density Random probability of assignment to any given grid cell on the assignment surface (i.e. 1 divided by the total number of grid cells).

name character. Name assigned to the QA object.

by integer. Value of by used.

Note

See Ma et al. (2020) for methodological details.

References

Ma, C. et al. (2020) assignR : An R package for isotope-based geographic assignment. *Methods in Ecology and Evolution* **11** 996–1001. doi: [10.1111/2041210X.13426](https://doi.org/10.1111/2041210X.13426).

Vander Zanden, H. B. et al. (2014) Contrasting assignment of migratory organisms to geographic origins using long-term versus year-specific precipitation isotope maps. *Methods in Ecology and Evolution* **5** 891–900. doi: [10.1111/2041210X.12229](https://doi.org/10.1111/2041210X.12229)

See Also

[plot.QA](#)

Examples

```
# load data
data("naMap") # North America
data("d2h_lrNA") # precipitation hydrogen isoscape for North America
data("knownOrig") # hydrogen isotopes of known-origin samples

# extract some known-origin data
d1 = subOrigData(taxon = "Buteo lagopus")

# run quality assessment based on precipitation hydrogen isotopes and
# known-origin samples; small values of valiStation and valiTime
# are used in example to reduce run time

# first with one example
# gives warning because a small number of samples are available
qa1 = QA(known = d1, isoscape = d2h_lrNA, valiTime = 2, by = 10,
        mask = naMap, name = "Buteo")

# plot the qa result
plot(qa1)

# now compare with a second data set
d2 = subOrigData(taxon = "Charadrius montanus")
qa2 = QA(known = d2, isoscape = d2h_lrNA, valiTime = 2, by = 10,
        mask = naMap, name = "Charadrius")
plot(qa1, qa2)
```

qtlRaster

*Sample assignment using thresholds***Description**

Selects the grid cells of probability density rasters with the highest probability and returns rasters with these cell values set to 1. Cells are selected based on the user-specified quantile threshold so that the most-probable cells representing a given fraction of the assignment area or posterior probability are returned.

Usage

```
qtlRaster(pdR, threshold, thresholdType = "area", genplot = TRUE, outDir = NULL)
```

Arguments

pdR	RasterLayer, RasterStack, or RasterBrick. Probability density maps for individual samples, e.g., as output by pdRaster.
threshold	numeric from 0 to 1. Quantile to be selected.
thresholdType	character. Either "area" (default) or "prob". If "area", the most probable cells constituting threshold percent of the assignment area are selected. If "prob", the most probable cells constituting threshold percent of the posterior probability are selected.
genplot	logical. Plot results in R.
outDir	character string. Directory path to which output will be saved. If NULL no files are written.

Value

RasterStack or RasterLayer including a binary assignment surface for each individual in pdR. If outDir is not NULL, writes individual rasters in GeoTIFF format and a single PDF file with images for each raster to the designated directory.

Examples

```
# load North America boundary and global isoscape
data("naMap")
data("d2h_lrNA")

# load hydrogen isotope data for human hair in North America
d = subOrigData(group = "Modern human", mask = naMap, niter = 100)

# rescale from environmental isoscape to tissue isoscape
r = calRaster(known = d, isoscape = d2h_lrNA, mask = naMap)

# four unknown-origin examples
id = c("A", "B", "C", "D")
```

```

d2H = c(-110, -90, -105, -102)
un = data.frame(id, d2H)

# posterior probability surface
asn = pdRaster(r, unknown=un, mask=naMap)

# assign to most probable 10 percent of area
## Not run: qtlRaster(asn, threshold = 0.1)

# assign to most probable 10 percent of probability distribution
qtlRaster(asn, threshold = 0.1, thresholdType = "prob")

```

refTrans

Transform reference scale of data

Description

This function conducts transformations to convert isotope measurements between reference scales.

Usage

```
refTrans(samples, marker = "d2H", ref_scale = "VSMOW_H", niter = 5000)
```

Arguments

samples	data.frame. Must include a field with data to be transformed, analytical reproducibility of sample data (1 standard deviation), and original reference scale for calibration of data. These fields must be named <i>marker</i> , <i>marker.sd</i> , and <i>marker_cal</i> , respectively, where <i>marker</i> is “d2H” or “d18O”. Values for the cal field should correspond to <i>Calibration</i> codes found in stds tables <i>hstds</i> and <i>ostds</i> .
marker	character string. Column name for isotopic data to be extracted, either “d2H” or “d18O”.
ref_scale	character string. Text identifier for reference scale to which all isotope values will be transformed. See stds .
niter	integer. Number of random samples used to propagate uncertainty in calibration hierarchy transformations.

Value

list.	
data	data.frame. Formatted identically to input object <i>samples</i> , with values for the data and data uncertainty fields replaced with transformed values.
chains	list. Each item is a character string vector containing the hierarchy of calibrations used in the transformation for a set of selected samples. See stds .

References

Magozzi, S. et al. (in press) Calibration chain transformation to improve the comparability of organic hydrogen and oxygen isotope data. *Methods in Ecology and Evolution*

Examples

```
# Some fake sample data
s = data.frame("d2H" = seq(-100, -10, by=10), "d2H.sd" = rep(2), "d2H_cal" = rep("01dUT_H_1"))

# Transform to VSMOW-SLAP scale using default arguments
d1 = refTrans(s)

# Transformed values
d1$data$d2H

# error - target scale not valid for marker
## Not run: d2 = refTrans(s, ref_scale = "VSMOW_0")
```

states

data: states

Description

Spatial Polygon Data Frame of lower 48 U.S. states

Usage

```
data("states")
```

Format

SpatialPolygonsDataFrame

Examples

```
library(sp)

data("states")
plot(states)
```

 stds

data: documentation of keratin H and O isotope standard calibrations

Description

This data object contains information on keratin H and O isotope standard materials and calibrations used across multiple laboratories since the year 2000.

Usage

```
data("stds")
```

Format

list.

hstds data.frame with 18 fields.

- [, 1] Calibration: Calibration code
- [, 2] High_ID: Identifier for high-value standard
- [, 3] High_material: Description of high-value standard material
- [, 4] High: Mean hydrogen isotope value of high-value standard
- [, 5] High_sd: Standard deviation of calibration data for high-value standard
- [, 6] High_n: Number of calibration data for high-value standard
- [, 7] High_se: Standard error of the calibrated mean for high-value standard
- [, 8] Low_ID: Identifier for low-value standard
- [, 9] Low_material: Description of low-value standard material
- [, 10] Low: Mean hydrogen isotope value of low-value standard
- [, 11] Low_sd: Standard deviation of calibration data for low-value standard
- [, 12] Low_n: Number of calibration data for low-value standard
- [, 13] Low_se: Standard error of the calibrated mean for low-value standard
- [, 14] Ref_scale: Calibration scale against which the values for this calibration are anchored
- [, 15] Citation_val: Source for the calibrated values
- [, 16] Citation_cal: Source for the methodology used for this calibration
- [, 17] Treatment: Description of calibration procedure
- [, 18] H_calibration_comments: Comments

ostds data.frame with 18 fields.

- [, 1] Calibration: Calibration code
- [, 2] High_ID: Identifier for high-value standard
- [, 3] High_material: Description of high-value standard material
- [, 4] High: Mean oxygen isotope value of high-value standard
- [, 5] High_sd: Standard deviation of calibration data for high-value standard
- [, 6] High_n: Number of calibration data for high-value standard
- [, 7] High_se: Standard error of the calibrated mean for high-value standard

- [, 8] Low_ID: Identifier for low-value standard
- [, 9] Low_material: Description of low-value standard material
- [, 10] Low: Mean oxygen isotope value of low-value standard
- [, 11] Low_sd: Standard deviation of calibration data for low-value standard
- [, 12] Low_n: Number of calibration data for low-value standard
- [, 13] Low_se: Standard error of the calibrated mean for low-value standard
- [, 14] Ref_scale: Calibration scale against which the values for this calibration are anchored
- [, 15] Citation_val: Source for the calibrated values
- [, 16] Citation_cal: Source for the methodology used for this calibration
- [, 17] Treatment: Description of calibration procedure
- [, 18] O_calibration_comments: Comments

ham matrix. $n \times n$ symmetric, where n is the number of calibrations represented here and in `stds$hstds`.

oam matrix. $n \times n$ symmetric, where n is the number of calibrations represented here and in `stds$ostds`.

References

Magozzi, S. et al. (in press) Calibration chain transformation to improve the comparability of organic hydrogen and oxygen isotope data. *Methods in Ecology and Evolution*

Examples

```
library(raster)
data("stds")

print(stds$hstds[, 1:5])
print(stds$ostds[, 1:5])
image(stds$ham)
image(stds$oam)
```

subOrigData

Extract known origin sample data

Description

This function subsets the known-origin isotope dataset included in this package and conducts optional transformations to convert isotope measurements to a common reference scale.

Usage

```
subOrigData(marker = "d2H", taxon = NULL, group = NULL, dataset = NULL,
            age_code = NULL, mask = NULL, ref_scale = "VSMOW_H", niter = 5000)
```

Arguments

marker	character string. Column name for isotopic data to be extracted, either “d2H” or “d18O”.
taxon	character string or string vector. Species name(s) for data to be extracted.
group	character string or string vector. Taxonomic groups for data to be extracted.
dataset	integer or integer vector. Dataset_ID(s) for data to be extracted. See knownOrig feature <i>sources</i> .
age_code	character string or string vector. Animal age code for data to be extracted.
mask	SpatialPolygons or SpatialPolygonsDataFrame. Constrains the geographic area from which data are extracted. If not provided, global.
ref_scale	character string. Text identifier for reference scale to which all isotope values will be transformed. See stds . Use “NULL” to obtain untransformed values on the originally reported scale.
niter	integer. Number of random samples used to propagate uncertainty in calibration hierarchy transformations.

Value

Returns an object of class “subOrigData”, formatted for use in [calRaster](#) or [QA](#) functions.

data	SpatialPointsDataFrame including one feature for each selected sample. data.frame fields are described in knownOrig feature <i>samples</i> .
sources	data.frame. Information for all data sources for the selected samples. Fields are described in knownOrig feature <i>sources</i>
chains	list. Each item is a character string vector containing the hierarchy of calibrations used in the transformation for a set of selected samples. See stds .
marker	character string. The isotopic marker specified in the call to subOrigData

References

Magozzi, S. et al. (in press) Calibration chain transformation to improve the comparability of organic hydrogen and oxygen isotope data. *Methods in Ecology and Evolution*

Examples

```
## WITHOUT mask
# extract d2H data for Jackdaw, Partridge and Willow Grouse, transformed
# to the VSMOW/SLAP H reference scale by default
d1 = subOrigData(taxon = c("Danaus plexippus", "Setophaga ruticilla",
  "Turdus migratorius"), niter = 100)
summary(d1)

# extract d2H data for insects and passerine birds without transformation
d2 = subOrigData(group = c("Insect","Passerine"), ref_scale = NULL)
summary(d2)

# extract d180 data for all humans, transformed to the VSMOW/SLAP 0 reference scale
```

```

d3 = subOrigData(marker = "d180",
  group = c("Modern human", "Indigenous human"), ref_scale = "VSMOW_0",
  niter = 100)
summary(d3)

# extract d2H data for humans using taxon, transformed to the VSMOW/SLAP H reference scale
d4 = subOrigData(marker = "d2H", taxon = "Homo sapiens", ref_scale =
  "VSMOW_H", niter = 100)
summary(d4)

## WITH mask
# error - no samples found
## Not run: d5 = subOrigData(taxon = "Turdus philomelos", mask = naMap)
# this works OK
d6 = subOrigData(taxon = c("Danaus plexippus", "Setophaga ruticilla",
  "Turdus migratorius"), mask = naMap)

```

unionP

Union probability of origin

Description

Probabilities that at least one individual came from each location in the assignment area (union of probabilities)

Usage

```
unionP(pdR)
```

Arguments

pdR RasterStack or RasterBrick of probability density maps, e.g., as produced by calRaster. All layers must have common spatial extent and projection.

Examples

```

# load North America boundary and global isoscape
data("naMap")
data("d2h_lrNA")

# load hydrogen isotope data for human hair in North America
d = subOrigData(group = "Modern human", mask = naMap, niter = 100)

# rescale from environmental isoscape to tissue isoscape
r = calRaster(known = d, isoscape = d2h_lrNA, mask = naMap)

# four unknown-origin examples
id = c("A", "B", "C", "D")
d2H = c(-110, -90, -105, -102)
un = data.frame(id, d2H)

```

```
# assignment
asn = pdRaster(r, unknown = un, mask = naMap)

# probability that one or more individuals are from a given location
unionP(asn)
```

Index

* datasets

knownOrig, 6
stds, 18

assignR, 2

calRaster, 2, 10, 20

d18o_world, 4
d2h_lrNA, 4
d2h_world, 5

jointP, 6

knownOrig, 6, 20

naMap, 8

oddsRatio, 9

pdRaster, 3, 10
plot.QA, 11, 14

QA, 11, 12, 12, 20
qtlRaster, 15

refTrans, 16

states, 17
stds, 7, 8, 16, 18, 20
subOrigData, 3, 8, 13, 19

unionP, 21