

# Package ‘automl’

September 13, 2018

**Type** Package

**Title** Deep Learning with Metaheuristic

**Version** 1.0.5

**Author** Alex Boulangé <aboul@free.fr>

**Maintainer** Alex Boulangé <alex@socialintelligence.fr>

**Description** Fits from simple regression to highly customizable deep neural networks either with gradient descent or metaheuristic, using automatic hyper parameters tuning and custom cost function.

A mix inspired by the common tricks on Deep Learning and Particle Swarm Optimization.

**License** GNU General Public License

**Encoding** UTF-8

**LazyData** TRUE

**Imports** stats, utils, parallel

**Suggests** datasets

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-09-13 16:50:09 UTC

## R topics documented:

automl_predict . . . . .	2
automl_train . . . . .	3
automl_train_manual . . . . .	4
autopar . . . . .	5
hpar . . . . .	7
pso . . . . .	9

<b>Index</b>	<b>10</b>
--------------	-----------

---

automl\_predict      *automl\_predict*

---

## Description

Predictions function, to apply a trained model on datas

## Usage

```
automl_predict(model, X, layoutputnum)
```

## Arguments

model	model trained previously with <a href="#">automl_train</a> or <a href="#">automl_train_manual</a>
X	inputs matrix or data.frame (containing numerical values only)
layoutputnum	which layer number to output (default 0 for last layer)

## Examples

```
##REGRESSION (predict Sepal.Length given other parameters)
data(iris)
xmat <- as.matrix(cbind(iris[,2:4], as.numeric(iris$Species)))
ymat <- iris[,1]
amlmodel <- automl_train_manual(Xref = xmat, Yref = ymat,
  hpar = list(modexec = 'trainwpso', verbose = FALSE))
res <- cbind(ymat, automl_predict(model = amlmodel, X = xmat))
colnames(res) <- c('actual', 'predict')
head(res)
#
##CLASSIFICATION (predict Species given other Iris parameters)
data(iris)
xmat = iris[,1:4]
lab2pred <- levels(iris$Species)
lghlab <- length(lab2pred)
iris$Species <- as.numeric(iris$Species)
ymat <- matrix(seq(from = 1, to = lghlab, by = 1), nrow(xmat),
  lghlab, byrow = TRUE)
ymat <- (ymat == as.numeric(iris$Species)) + 0
amlmodel <- automl_train_manual(Xref = xmat, Yref = ymat,
  hpar = list(modexec = 'trainwpso', verbose = FALSE))
res <- cbind(ymat, round(automl_predict(model = amlmodel, X = xmat)))
colnames(res) <- c(paste('act',lab2pred, sep = '_'),
  paste('pred',lab2pred, sep = '_'))
head(res)
```





```

##CLASSIFICATION (predict Species given other Iris parameters)
data(iris)
xmat = iris[,1:4]
lab2pred <- levels(iris$Species)
lghlab <- length(lab2pred)
iris$Species <- as.numeric(iris$Species)
ymat <- matrix(seq(from = 1, to = lghlab, by = 1), nrow(xmat), lghlab, byrow = TRUE)
ymat <- (ymat == as.numeric(iris$Species)) + 0
#with gradient descent and 2 hidden layers
amlmodel <- automl_train_manual(Xref = xmat, Yref = ymat,
                               hpar = list(layersshape = c(10, 10, 0),
                                             layersacttype = c('tanh', 'relu', 'sigmoid'),
                                             layersdropoprob = c(0, 0, 0)))
#with gradient descent and no hidden layer (logistic regression)
amlmodel <- automl_train_manual(Xref = xmat, Yref = ymat,
                               hpar = list(layersshape = c(0),
                                             layersacttype = c('sigmoid'),
                                             layersdropoprob = c(0)))
#with PSO and softmax
amlmodel <- automl_train_manual(Xref = xmat, Yref = ymat,
                               hpar = list(modexec = 'trainwpso',
                                             layersshape = c(10, 0),
                                             layersacttype = c('relu', 'softmax'),
                                             layersdropoprob = c(0, 0),
                                             numiterations = 50,
                                             psopartpopsize = 50))

## End(Not run)

```

---

autopar

*parameters for automatic hyperparameters optimization*

---

## Description

List of parameters to allow multi deep neural network automatic hyperparameters tuning with Particle Swarm Optimization

Not mandatory (the list is preset and all arguments are initialized with default value) but it is advisable to adjust some important arguments for performance reasons (including processing time)

## Arguments

psopartpopsize	number of particles in swarm, the main argument that should be tuned #tuning priority 1
psosxxx	see <a href="#">pso</a> for other PSO specific arguments details
numiterations	number of convergence steps between particles (hyperparameters), default value 3) #tuning priority 1

auto_modexec	if 'TRUE' the type of Neural Net optimization will be randomly chosen between 'trainwgrad' and 'trainwps0' for each particle default value is 'FALSE' (so default value of argument 'modexec' in <a href="#">automl_train_manual</a> function) the value can be forced if defined in <a href="#">hpar</a> list
auto_minibatchsize	see below
auto_minibatchsize_min	see below
auto_minibatchsize_max	'auto_minibatch' default value 'TRUE' for automatic adjustment of 'minibatchsize' argument in <a href="#">automl_train_manual</a> function the minimum and maximum value for 'minibatchsize' correspond to 2 to the power value (default 0 for 'auto_minibatchsize_min' and 9 for 'auto_minibatchsize_max')
auto_learningrate	see below
auto_learningrate_min	see below
auto_learningrate_max	'auto_learningrate' default value 'TRUE' for automatic adjustment of 'learningrate' argument in <a href="#">automl_train_manual</a> function the minimum and maximum value for 'learningrate' correspond to 10 to the power negative value (default -5 for 'auto_learningrate_min' and -2 for 'auto_learningrate_max')
auto_beta1	see below
auto_beta2	'auto_beta1' and 'auto_beta2' default value 'TRUE' for automatic adjustment of 'beta1' and 'beta2' argument in <a href="#">automl_train_manual</a> function
auto_psopartpopsize	see below
auto_psopartpopsize_min	see below
auto_psopartpopsize_max	'auto_psopartpopsize' default value 'TRUE' for automatic adjustment of 'psopartpopsize' argument in <a href="#">automl_train_manual</a> function the minimum and maximum value for 'learningrate' ; default 2 for 'auto_psopartpopsize_min' and 50 for 'auto_psopartpopsize_max')
seed	seed for reproductibility (default 4)
nbcores	number of cores used to parallelize particles optimization, not available on Windows (default 1, automatically reduced if not enough cores)
verbose	to display or not the costs at each iteration for each particle (default TRUE)

*back to [automl\\_train](#)*

**Description**

List of Neural Network parameters and hyperparameters to train with gradient descent or particle swarm optimization

Not mandatory (the list is preset and all arguments are initialized with default value) but it is advisable to adjust some important arguments for performance reasons (including processing time)

**Arguments**

modexec	‘trainwgrad’ (the default value) to train with gradient descent ‘trainwpso’ to train using Particle Swarm Optimization, each particle represents a set of neural network weights
	<i>Below specific arguments to ‘trainwgrad’ execution mode</i>
learningrate	learningrate alpha (default value 0.001) #tuning priority 1
beta1	see below
beta2	‘Momentum’ if beta1 different from 0 and beta2 equal 0 ) ‘RMSprop’ if beta1 equal 0 and beta2 different from 0 ‘adam optimization’ if beta1 different from 0 and beta2 different from 0 (default) (default value beta1 equal 0.9 and beta2 equal 0.999) #tuning priority 2
lrdecayrate	learning rate decay value (default value 0, no learning rate decay, 1e-6 should be a good value to start with) #tuning priority 4
chkgradevery	epoch interval to run gradient check function (default value 0, for debug only)
chkgradeepsilon	epsilon value for derivative calculations and threshold test in gradient check function (default 0.0000001)
	<i>Below specific arguments to ‘trainwpso’ execution mode</i>
psosxxx	see <a href="#">pso</a> for PSO specific arguments details
costcustformul	custom cost formula (default ‘’, no custom cost function) standard input variables: yhat (prediction), y (target actual value) custom input variables: any variable declared in hpar may be used via alias mydl (ie: hpar(list = (foo = 1.5)) will be used in custom cost formula as mydl\$foo) result: J see ‘automl_train_manual’ example using Mean Average Percentage Error cost function nb: X and Y matrices used as input into automl_train_manual or automl_train_manual functions are transposed (features in rows and cases in columns)

*Below arguments for both execution modes*

numiterations	number of training epochs (default value 50)) #tuning priority 1
seed	seed for reproductibility (default 4)
minibatchsize	mini batch size, 2 to the power 0 for stochastic gradient descent (default 2 to the power 5) #tuning priority 3
layersshape	number of nodes per layer, each nodes number initialize a hidden layer output layer nodes number, may be left to 0 it will be automatically set by Y matrix shape default value one hidden layer with 10 nodes: c(10, 0) #tuning priority 4
layersacttype	activation function for each layer; 'linear' for no activation or 'sigmoid', 'relu' or 'reluleaky' or 'tanh' or 'softmax' (softmax for output layer only supported in trainwpsso exec mode) output layer activation function may be left to '', default value 'linear' for regression, 'sigmoid' for classification nb: layersacttype parameter vector must have same length as layersshape parameter vector default value c('relu', '') #tuning priority 4
layersdropoprob	drop out probability for each layer, continuous value from 0 to less than 1 (give the percentage of matrix weight values to drop out randomly) nb: layersdropoprob parameter vector must have same length as layersshape parameter vector default value no drop out: c(0, 0) #tuning priority for regularization
printcostevery	epoch interval to test and print costs (train and cross validation cost: default value 10, for 1 test every 10 epochs)
testcvsize	size of cross validation sample, 0 for no cross validation sample (default 10, for 10 percent)
testgainunder	threshold to stop the training if the gain between last train or cross validation cost is smaller than the threshold, 0 for no stop test (default 0.000001)
costtype	cost type function name 'mse' or 'crossentropy' or 'custom' 'mse' for Mean Squared Error, set automatically for continuous target type 'crossentropy' set automatically for binary target type 'custom' set automatically if 'costcustformul' different from ''
lambda	regularization term added to cost function (default value 0, no regularization)
batchnor_mom	batch normalization momentum for j and B (default value 0.9, no batch normalization if equal to 0)
epsil	epsilon the low value to avoid dividing by 0 or log(0) in cost function, etc ... (default value 1e-12)

*back to [automl\\_train](#), [automl\\_train\\_manual](#)*



**See Also**

Deep Learning specialization from Andrew NG on Coursera

---

 ps0

*PSO parameters and hyperparameters*


---

**Description**

List of parameters and hyperparameters for Particle Swarm Optimization

**Arguments**

All PSO parameters and hyperparameters are preset with default value

number of particles in swarm (discrete value)

(‘autopar’ context: default value 8, which means that 8 different neural net hyperparameters sets will be tested

(‘hpar’ context: default value 50, which means that 50 neural net weights sets will be tested

#tuning priority 1

*CAUTION: you should only change the values below if you know what you are doing*

`psopartpopsize` Minimum value for particles positions (default value -10)

`psovarvalmax` maximum value for particles positions (default value 10)

`psovelocitymaxratio`

ratio applied to limit velocities (continuous value between 0 and 1, default value 0.2)

`psoinertiadampratio`

inertia damp ratio (continuous value between 0 and 1, default value 1 equivalent to OFF)

`psokappa` kappa (default value 1)

`psophi1` Phi 1 (default value 2.05)

`psophi2` Phi 2 (default value 2.05)

*back to [autopar](#), [hpar](#)*

**See Also**

PSO video tutorial from Yarpiz

# Index

automl\_predict, 2  
automl\_train, 2, 3, 6, 8  
automl\_train\_manual, 2, 3, 4, 6, 8  
autopar, 3, 5, 9  
  
hpar, 3, 4, 6, 7, 9  
  
pso, 5, 7, 9