

Package ‘bibliometrix’

May 15, 2018

Type Package

Title An R-Tool for Comprehensive Science Mapping Analysis

Version 1.9.3

Date 2018-05-15

Description Tool for quantitative research in scientometrics and bibliometrics.

It provides various routines for importing bibliographic data from SCOPUS (<<http://scopus.com>>), Clarivate Analytics Web of Science (<<http://www.webofknowledge.com/>>), Cochrane Library (<<http://www.cochranelibrary.com/>>) and PubMed (<<https://www.ncbi.nlm.nih.gov/pubmed/>>) databases, performing bibliometric analysis and building networks for co-citation, coupling, scientific collaboration and co-word analysis.

License GPL-3

URL <http://www.bibliometrix.org>

LazyData FALSE

Encoding latin1

Depends R (>= 3.3.0)

Imports stats, factoextra, FactoMineR, ggplot2, ggrepel, igraph, Matrix, RColorBrewer, RISmed, rscopus, SnowballC, stringdist, stringr

Suggests knitr, rmarkdown,

RoxygenNote 6.0.1

NeedsCompilation no

Author Massimo Aria [cre, aut],
Corrado Cuccurullo [aut]

Maintainer Massimo Aria <aria@unina.it>

VignetteBuilder knitr,

Repository CRAN

Date/Publication 2018-05-15 10:24:21 UTC

R topics documented:

bibliometrix-package	3
biblio	4
biblioAnalysis	5
biblioNetwork	6
biblio_df	8
citations	9
cochrane2df	10
cocMatrix	11
conceptualStructure	12
convert2df	14
countries	16
dominance	16
duplicatedMatching	17
garfield	18
Hindex	19
histNetwork	20
histPlot	21
idByAuthor	22
isi2df	23
isibib2df	24
isiCollection	25
keywordAssoc	26
KeywordGrowth	27
localCitations	28
lotka	29
mergeDbSources	29
metaTagExtraction	31
networkPlot	32
normalizeSimilarity	34
plot.bibliometrix	35
pubmed2df	36
readFiles	37
retrievalByAuthorID	38
scientometrics	39
scientometrics_text	40
scopus2df	41
scopusCollection	42
stopwords	43
summary.bibliometrix	43
tableTag	44
termExtraction	45
thematicEvolution	47
thematicMap	48
timeslice	49
trim	50
trim.leading	51

bibliometrix-package *Tool for quantitative research in scientometrics and bibliometrics.*

Description

It provides various routines for importing bibliographic data from SCOPUS and Thomson Reuters' ISI Web of Knowledge databases, performing bibliometric analysis and building data matrices for co-citation, coupling and scientific collaboration analysis.

Details

Package: bibliometrix
Type: Package
Version: 0.1
Date: 2016-05-05
License: GPL-3

Author(s)

Massimo Aria <massimo.aria@unina.it>, Corrado Cuccurullo <corrado.cuccurullo@unina2.it>
Maintainer: Massimo Aria <massimo.aria@unina.it>

References

- Cuccurullo C., Aria M., Sarto F. (2016) Foundations and Trends in Performance Management. A Twenty-five Years Bibliometric Analysis in Business and Public Administration Domains, Scientometrics, DOI: 10.1007/s11192-016-1948-8.
- Koseoglu, M. A. (2016). Growth and structure of authorship and co-authorship network in the strategic management realm: Evidence from the Strategic Management Journal. BRQ Business Research Quarterly.
- Batagelj, V., Cerinsek, M. (2013). On bibliographic networks. Scientometrics, 96(3), 845-864.
- Yan, E., Ding, Y. (2012). Scholarly network similarities: How bibliographic coupling networks, citation networks, cocitation networks, topical networks, coauthorship networks, and coword networks relate to each other. Journal of the American Society for Information Science and Technology, 63(7), 1313-1326.
- Rousseau, R. (2010). Bibliographic coupling and co-citation as dual notions. The Janus faced scholar. A Festschrift in honour of Peter Ingwersen, 173-183.
- Leydesdorff, L., Vaughan, L. (2006). Co-occurrence matrices and their applications in information science: Extending ACA to the Web environment. Journal of the American Society for Information Science and technology, 57(12), 1616-1628.

Examples

```
## load scientometrics data set
# data scientometrics_text)

## Convert text data into a bibliographic data frame
# scient_df <- convert2df scientometrics_text, dbsource="isi", format="plaintext")

## Perform a bibliometric analysis of the bibliographic data frame
# results <- biblioAnalysis scient_df)

## summarize results
# summary results, k=10, pause=FALSE)

## plot results
# plot results, k=10, pause=FALSE)

## Estimate Lotka's law coefficients
# L=lotka results)
# L

## Perform authors' dominance analysis
#DF=dominance results)
#DF
```

biblio

Dataset of "Bibliometrics" scientific documents.

Description

The set of manuscripts which the title containing the word "bibliometrics" and published in a journal indexed by ISI WoK database.

Period: 2006 - 2015

Database: [ISI Web of Knowledge](http://www.webofknowledge.com)

Format

A large character with 9014 rows.

Data has been imported by an ISI Export file in bibtex format using the function [readLines](#).

Source

<http://www.webofknowledge.com>

biblioAnalysis	<i>Bibliometric Analysis</i>
----------------	------------------------------

Description

It performs a bibliometric analysis of a dataset imported from SCOPUS and Thomson Reuters' ISI Web of Knowledge databases.

Usage

```
biblioAnalysis(M, sep = ";")
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
sep	is the field separator character. This character separates strings in each column of the data frame. The default is sep = ";".

Value

biblioAnalysis returns an object of class "bibliometrix".

The functions [summary](#) and [plot](#) are used to obtain or print a summary and some useful plots of the results.

An object of class "bibliometrix" is a list containing the following components:

Articles	the total number of manuscripts
Authors	the authors' frequency distribution
AuthorsFrac	the authors' frequency distribution (fractionalized)
FirstAuthors	first author of each manuscript
nAUpperPaper	the number of authors per manuscript
Appearances	the number of author appearances
nAuthors	the number of authors
AuMultiAuthoredArt	the number of authors of multi-authored articles
MostCitedPapers	The list of manuscripts sorted by citations
Years	publication year of each manuscript
FirstAffiliation	the affiliation of the first author
Affiliations	the frequency distribution of affiliations (of all co-authors for each paper)
Aff_frac	the fractionalized frequency distribution of affiliations (of all co-authors for each paper)
CO	the affiliation country of the first author
Countries	the affiliation countries' frequency distribution
CountryCollaboration	Intracountry (SCP) and intercountry (MCP) collaboration indices
TotalCitation	the number of times each manuscript has been cited
TCperYear	the yearly average number of times each manuscript has been cited
Sources	the frequency distribution of sources (journals, books, etc.)
DE	the frequency distribution of authors' keywords
ID	the frequency distribution of keywords associated to the manuscript by SCOPUS and Thomson Reuters

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

Examples

```
data(scientometrics)

results <- biblioAnalysis(scientometrics)

summary(results, k = 10, pause = FALSE)
```

 biblioNetwork

Creating Bibliographic networks

Description

biblioNetwork creates different bibliographic networks from a bibliographic data frame.

Usage

```
biblioNetwork(M, analysis = "coupling", network = "authors", sep = ";")
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
analysis	is a character object. It indicates the type of analysis have to be performed. analysis argument can be "collaboration", "coupling", "co-occurrences" or "co-citation". Default is analysis = "coupling".
network	is a character object. It indicates the network typology. The network argument can be "authors", "references", "sources", "countries", "keywords", "author_keywords", "titles", or "abstracts". Default is network = "authors".
sep	is the field separator character. This character separates strings in each column of the data frame. The default is sep = ";".

Details

The function [biblioNetwork](#) can create a collection of bibliographic networks following the approach proposed by Batagely and Cerinsek (2013).

Typical networks output of biblioNetwork are:

```
#### Collaboration Networks #####
- Authors collaboration (analysis = "collaboration", network = "authors")
- University collaboration (analysis = "collaboration", network = "universities")
- Country collaboration (analysis = "collaboration", network = "countries")

#### Co-citation Networks #####
- Authors co-citation (analysis = "co-citation", network = "authors")
- Reference co-citation (analysis = "co-citation", network = "references")
- Source co-citation (analysis = "co-citation", network = "sources")

#### Coupling Networks #####
- Manuscript coupling (analysis = "coupling", network = "references")
- Authors coupling (analysis = "coupling", network = "authors")
- Source coupling (analysis = "coupling", network = "sources")
- Country coupling (analysis = "coupling", network = "countries")

#### Co-occurrences Networks #####
- Authors co-occurrences (analysis = "co-occurrences", network = "authors")
- Source co-occurrences (analysis = "co-occurrences", network = "sources")
- Keyword co-occurrences (analysis = "co-occurrences", network = "keywords")
- Author-Keyword co-occurrences (analysis = "co-occurrences", network = "author_keywords")
- Title content co-occurrences (analysis = "co-occurrences", network = "titles")
- Abstract content co-occurrences (analysis = "co-occurrences", network = "abstracts")
```

Value

It is a squared network matrix. It is an object of class `dgMatrix` of the package [Matrix](#).

See Also

[convert2df](#) to import and convert a SCOPUS and Thomson Reuters' ISI Web of Knowledge export file in a data frame.

[cocMatrix](#) to compute a co-occurrence matrix.

[biblioAnalysis](#) to perform a bibliometric analysis.

Examples

```
# EXAMPLE 1: Authors collaboration network

# data(scientometrics)

# NetMatrix <- biblioNetwork(scientometrics, analysis = "collaboration",
# network = "authors", sep = ";")

# net <- networkPlot(NetMatrix, n = 30, type = "kamada", Title = "Collaboration", labelsSize=0.5)
```

```
# EXAMPLE 2: Co-citation network

data scientometrics

NetMatrix <- biblioNetwork(scientometrics, analysis = "co-citation",
network = "references", sep = ";")

net <- networkPlot(NetMatrix, n = 30, type = "kamada", Title = "Co-Citation", labelsize=0.5)
```

biblio_df

Dataset of "Bibliometrics" manuscripts.

Description

The set of manuscripts which the title containing the word "bibliometrics" and published in a journal indexed by ISI WoK database.

Period: 2006 - 2015

Database: [ISI Web of Knowledge](http://www.webofknowledge.com)

Format

#' A data frame with 99 rows (manuscripts) and 16 variables (ISI tag field):

AU Authors

TI Document Title

SO Publication Name (or Source)

JI ISO Source Abbreviation

DT Document Type

DE Author Keywords

ID Keywords associated by ISI or SCOPUS database

AB Abstract

C1 Author Address

RP Reprint Address

CR Cited References

TC Times Cited

PY Year

SC Subject Category

UT Unique Article Identifier

DB Database

Source

<http://www.webofknowledge.com>

citations	<i>Citation frequency distribution</i>
-----------	--

Description

It calculates frequency distribution of citations.

Usage

```
citations(M, field = "article", sep = ";")
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
field	is a character. It can be "article" or "author" to obtain frequency distribution of cited citations or cited authors (only first authors for ISI database) respectively. The default is field = "article".
sep	is the field separator character. This character separates citations in each string of CR column of the bibliographic data frame. The default is sep = ";".

Value

an object of class "list" containing the following components:

Cited	the most frequent cited manuscripts or authors
Year	the publication year (only for cited article analysis)
Source	the journal (only for cited article analysis)

See Also

[biblioAnalysis](#) function for bibliometric analysis.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

Examples

```
## EXAMPLE 1: Cited articles

data(scientometrics)

CR <- citations(scientometrics, field = "article", sep = ";")

CR$Cited[1:10]
CR$Year[1:10]
CR$Source[1:10]
```

```
## EXAMPLE 2: Cited first authors

data scientometrics

CR <- citations(scientometrics, field = "author", sep = ";")

CR$Cited[1:10]
```

cochrane2df

Convert a Cochrane Database Export file into a data frame

Description

It converts a Cochrane Database Export file and create a data frame from it, with cases corresponding to articles and variables to Field Tag in the original file.

Usage

```
cochrane2df(D)
```

Arguments

D is a character array containing data read from a ISI Export file (in plain text format).

Value

a data frame with cases corresponding to articles and variables to Field Tag in the original ISI file.

See Also

[scopus2df](#) for converting SCOPUS Export file (in bibtex format)

Other converting functions: [convert2df](#), [isi2df](#), [isibib2df](#), [pubmed2df](#), [scopus2df](#)

Examples

```
# A group of Cochrane Database Export files can be read using \link{readFiles} function:

# largechar <- readFiles('filename1.txt', 'filename2.txt', 'filename3.txt')

# filename.txt is a Cochrane Database Export file in plain text format.

# scientometrics_text <- readFiles('http://www.bibliometrix.org/datasets/cochrane.txt')
# scient_df <- cochrane2df(cochrane_text)
```

cocMatrix	<i>Co-occurrence matrix</i>
-----------	-----------------------------

Description

cocMatrix computes co-occurrences between elements of a Tag Field from a bibliographic data frame. Manuscript is the unit of analysis.

Usage

```
cocMatrix(M, Field = "AU", type = "sparse", sep = ";", binary = TRUE)
```

Arguments

M is a data frame obtained by the converting function [convert2df](#). It is a data matrix with cases corresponding to articles and variables to Field Tag in the original ISI or SCOPUS file.

Field is a character object. It indicates one of the field tags of the standard ISI WoS Field Tag codify. Field can be equal to one of this tags:

AU	Authors
SO	Publication Name (or Source)
JI	ISO Source Abbreviation
DE	Author Keywords
ID	Keywords associated by ISI or SCOPUS database
CR	Cited References

for a complete list of filed tags see: [Field Tags used in bibliometrix](#)

type indicates the output format of co-occurrences:

type = "matrix" produces an object of class `matrix`

type = "sparse" produces an object of class `dgMatrix` of the package [Matrix](#). "sparse" argument generates a compact

sep is the field separator character. This character separates strings in each column of the data frame. The default is sep = ";".

binary is a logical. If TRUE each cell contains a 0/1. if FALSE each cell contains the frequency.

Details

This co-occurrence matrix can be tranformed into a collection of compatible networks. Through matrix multiplication you can obtain different networks. The fuction follows the approach proposed by Batagely and Cerinsek (2013).

Value

a co-occurrence matrix with cases corresponding to manuscripts and variables to the objects extracted from the Tag Field.

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a data frame.

[biblioAnalysis](#) to perform a bibliometric analysis.

[biblioNetwork](#) to compute a bibliographic network.

Examples

```
# EXAMPLE 1: Articles x Authors co-occurrence matrix

data(scientometrics)
WA <- cocMatrix(scientometrics, Field = "AU", type = "sparse", sep = ";")

# EXAMPLE 2: Articles x Cited References co-occurrence matrix

# data(scientometrics)

# WCR <- cocMatrix(scientometrics, Field = "CR", type = "sparse", sep = ";")

# EXAMPLE 3: Articles x Cited First Authors co-occurrence matrix

# data(scientometrics)
# scientometrics <- metaTagExtraction(scientometrics, Field = "CR_AU", sep = ";")
# WCR <- cocMatrix(scientometrics, Field = "CR_AU", type = "sparse", sep = ";")
```

conceptualStructure *Creating and plotting conceptual structure map of a scientific field*

Description

The function `conceptualStructure` creates a conceptual structure map of a scientific field performing Correspondence Analysis (CA) or Multiple Correspondence Analysis (MCA) and Clustering of a bipartite network of terms extracted from keyword, title or abstract fields.

Usage

```
conceptualStructure(M, field = "ID", method = "MCA", quali.supp = NULL,
  quanti.supp = NULL, minDegree = 2, k.max = 5, stemming = FALSE,
  labelsize = 10, documents = 10)
```

Arguments

M	is a data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to articles and variables to Field Tag in the original ISI or SCOPUS file.
field	is a character object. It indicates one of the field tags of the standard ISI WoS Field Tag codify. field can be equal to one of this tags:
ID	Keywords Plus associated by ISI or SCOPUS database
DE	Author's keywords
ID_TM	Keywords Plus stemmed through the Porter's stemming algorithm
DE_TM	Author's Keywords stemmed through the Porter's stemming algorithm
TI	Terms extracted from titles
AB	Terms extracted from abstracts
method	is a character object. It indicates the factorial method used to create the factorial map. Use method="CA" for Correspondence Analysis or method="MCA" for Multiple Correspondence Analysis. The default is method="MCA"
quali.sup	is a vector indicating the indexes of the categorical supplementary variables.
quanti.sup	is a vector indicating the indexes of the quantitative supplementary variables.
minDegree	is an integer. It indicates the minimum occurrences of terms to analyze and plot. The default value is 2.
k.max	is an integer. It indicates the maximum number of cluster to keep. The default value is 5. The max value is 8.
stemming	is logical. If TRUE the Porter's Stemming algorithm is applied to all extracted terms. The default is stemming = FALSE.
labelsize	is an integer. It indicates the label size in the plot. Default is labelsize=10
documents	is an integer. It indicates the number of documents to plot in the factorial map. The default value is 10.

Value

It is an object of the class `list` containing the following components:

net	bipartite network
res	Results of CA or MCA method
km.res	Results of cluster analysis
graph_terms	Conceptual structure map (class "ggplot2")
graph_documents_Contrib	Factorial map of the documents with the highest contributes (class "ggplot2")
graph_documents_TC	Factorial map of the most cited documents (class "ggplot2")

See Also

[termExtraction](#) to extract terms from a textual field (abstract, title, author's keywords, etc.) of a bibliographic data frame.

[biblioNetwork](#) to compute a bibliographic network.

`cocMatrix` to compute a co-occurrence matrix.

`biblioAnalysis` to perform a bibliometric analysis.

Examples

```
# EXAMPLE Conceptual Structure using Keywords Plus

data(scientometrics)

CS <- conceptualStructure(scientometrics, field="ID", method="CA",
  stemming=FALSE, minDegree=3, k.max = 5)
```

convert2df	<i>Convert a Clarivate Analytics WoS, SCOPUS and COCHRANE Database Export files or RISmed PubMed/MedLine object into a data frame</i>
------------	---

Description

It converts a SCOPUS, Clarivate Analytics WoS and COCHRANE Database export files or RISmed PubMed/MedLine object into a data frame, with cases corresponding to articles and variables to Field Tags as used in WoS.

Usage

```
convert2df(file, dbsource = "isi", format = "plaintext")
```

Arguments

file	can be: a) a character array containing data read from a Clarivate Analytics WoS Export file (in plain text or bibtex format) or SCOPUS Export file (exclusively in bibtex format); b) an object of the class <code>pubmed</code> (package <code>RISmed</code>) containing a collection obtained from a query performed with <code>RISmed</code> package.
dbsource	is a character indicating the bibliographic database. <code>dbsource</code> can be <code>"isi"</code> , <code>"scopus"</code> or <code>pubmed</code> . Default is <code>dbsource = "isi"</code> .
format	is a character indicating the format of the SCOPUS and Clarivate Analytics WoS export file. <code>format</code> can be <code>"bibtex"</code> or <code>"plaintext"</code> . Default is <code>format = "plaintext"</code> .

Details

Actually the function allows to convert both SCOPUS/WoS files in bibtex format and just WoS files in plain text format.

Value

a data frame with cases corresponding to articles and variables to Field Tags in the original export file.

data frame columns are named using the standard Clarivate Analytics WoS Field Tag codify. The main field tags are:

AU	Authors
TI	Document Title
SO	Publication Name (or Source)
JI	ISO Source Abbreviation
DT	Document Type
DE	Authors' Keywords
ID	Keywords associated by SCOPUS or WoS database
AB	Abstract
C1	Author Address
RP	Reprint Address
CR	Cited References
TC	Times Cited
PY	Year
SC	Subject Category
UT	Unique Article Identifier
DB	Database

for a complete list of field tags see: [Field Tags used in bibliometrix](#)

See Also

[scopus2df](#) for converting SCOPUS Export file (in bibtex format)

[isibib2df](#) for converting ISI Export file (in bibtex format)

[isi2df](#) for converting ISI Export file (in plain text format)

[pubmed2df](#) for converting an object of the class pubmed (RISmed package)

Other converting functions: [cochrane2df](#), [isi2df](#), [isibib2df](#), [pubmed2df](#), [scopus2df](#)

Examples

```
# An ISI or SCOPUS Export file can be read using \link{readLines} function:

# D <- readFiles('filename1.txt','filename2.txt','filename3.txt')

# filename1.txt, filename2.txt and filename3.txt are WoS or SCOPUS Export file
# in plain text or bibtex format.

# biblio <- readFiles('http://www.bibliometrix.org/datasets/bibliometrics_articles.txt')

data(biblio)
```

```
biblio_df_df <- convert2df(file = biblio, dbsource = "isi", format = "bibtex")
```

countries	<i>Index of Countries.</i>
-----------	----------------------------

Description

Data frame containing a normalized index of countries.

Data are used by `biblioAnalysis` function to extract Country Field of Cited References and Authors.

Format

A data frame with 198 rows and 1 variable:

countries country names

dominance	<i>Authors' dominance ranking</i>
-----------	-----------------------------------

Description

It calculates the authors' dominance ranking from an object of the class 'bibliometrix' as proposed by Kumar & Kumar, 2008.

Usage

```
dominance(results, k = 10)
```

Arguments

results is an object of the class 'bibliometrix' for which the analysis of the authors' dominance ranking is desired.

k is an integer, used for table formatting (number of authors). Default value is 10.

Value

The function `dominance` returns a data frame with cases corresponding to the first k most productive authors and variables to typical field of a dominance analysis.

the data frame variables are:

Dominance Factor	Dominance Factor (DF = FAA / MAA)
Multi Authored	N. of Multi-Authored Articles (MAA)
First Authored	N. of First Authored Articles (FAA)
Rank by Articles	Author Ranking by N. of Articles
Rank by DF	Author Ranking by Dominance Factor

See Also

[biblioAnalysis](#) function for bibliometric analysis
[summary](#) method for class 'bibliometrix'

Examples

```
data(scientometrics)
results <- biblioAnalysis(scientometrics)
DF=dominance(results)
DF
```

duplicatedMatching *Searching of duplicated records in a bibliographic database*

Description

Search duplicated records in a dataframe.

Usage

```
duplicatedMatching(M, Field = "TI", tol = 0.95)
```

Arguments

M	is the bibliographic data frame.
Field	is a character object. It indicates one of the field tags used to identify duplicated records. Field can be equal to one of this tags: TI (title), AB (abstract), UT (manuscript ID).
tol	is a numeric value giving the minimum relative similarity to match two manuscripts. Default value is tol = 0.95.

Details

A bibliographic data frame is obtained by the converting function [convert2df](#). It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file. The function identifies duplicated records in a bibliographic data frame and deletes them. Duplicate entries are identified through the restricted Damerau-Levenshtein distance. Two manuscripts that have a relative similarity measure greater than tol argument are stored in the output data frame only once.

Value

the value returned from duplicatedMatching is a data frame without duplicated records.

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.

[biblioAnalysis](#) function for bibliometric analysis.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

Examples

```
data(scientometrics)

M=rbind(scientometrics[1:20,],scientometrics[10:30,])

newM <- duplicatedMatching(M, Field = "TI", tol = 0.95)

dim(newM)
```

garfield

Eugene Garfield's manuscripts.

Description

All manuscripts published by Eugene Garfield.

Period: 1954 - 2014

Database: [SCOPUS source](#)

Format

A data frame with 147 rows and 15 variables:

AU Authors

TI Document Title

SO Publication Name (or Source)

JI ISO Source Abbreviation

DT Document Type

DE Author Keywords

ID Keywords associated by ISI or SCOPUS database

AB Abstract

C1 Author Address

RP Reprint Address

CR Cited References

TC Times Cited
PY Year
UT Unique Article Identifier
DB Database

Source

<http://www.scopus.com>

Hindex	<i>h-index calculation</i>
--------	----------------------------

Description

It calculates the authors' h-index and its variants.

Usage

```
Hindex(M, authors, sep = ";", years = 10)
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
authors	is a character vector. It contains the the authors' names list for which you want to calculate the H-index. The argument has the form C("SURNAME1 N","SURNAME2 N",...), in other words, for each author: surname and initials separated by one blank space. i.e for the authors SEMPRONIO TIZIO CAIO and ARIA MASSIMO authors argument is authors = c("SEMPRONIO TC", "ARIA M").
sep	is the field separator character. This character separates authors in each string of AU column of the bibliographic data frame. The default is sep = ";".
years	is a integer. It indicates the number of years to consider for Hindex calculation. Default is 10.

Value

an object of class "list". It contains two elements: H is a data frame with h-index, g-index and m-index for each author; CitationList is a list with the bibliographic collection for each author.

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.
[biblioAnalysis](#) function for bibliometric analysis.
[summary](#) to obtain a summary of the results.
[plot](#) to draw some useful plots of the results.

Examples

```

### EXAMPLE 1: ###

data(scientometrics)

authors <- c("SMALL H", "CHEN DZ")

Hindex(scientometrics, authors, sep = ";")$H

### EXAMPLE 2: Garfield h-index###

data(garfield)

indices=Hindex(garfield, authors="GARFIELD E", sep = ";")

# h-index, g-index and m-index of Eugene Garfield
indices$H

# Papers and total citations
indices$CitationList[[1]]

```

histNetwork

Historical co-citation network

Description

histNetwork creates a historical citation network from a bibliographic data frame.

Usage

```
histNetwork(M, n = 10, sep = ";")
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
n	is an integer, indicating the number of most cited references to select. Default value is 10.
sep	is the field separator character. This character separates strings in CR column of the data frame. The default is sep = ";".

Value

histNetwork returns an object of class "list" containing the following components:

NetMatrix	the historical co-citation network matrix
Degree	the min degree of the network
histData	the set of n most cited references
M	the bibliographic data frame

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

[biblioNetwork](#) to compute a bibliographic network.

Examples

```
data(scientometrics)
```

```
histResults <- histNetwork(scientometrics, n = 10, sep = ";")
```

histPlot

Plotting historical co-citation network

Description

histPlot plots a historical co-citation network.

Usage

```
histPlot(histResults, remove.isolates = FALSE, size = F, labelsize = 0.8,
         label = TRUE, arrowsize = 0.1)
```

Arguments

histResults is an object of class "list" containing the following components:

NetMatrix	the historical citation network matrix
Degree	the min degree of the network
histData	the set of n most cited references
M	the bibliographic data frame

is a network matrix obtained by the function [histNetwork](#).

remove.isolates

is logical. If TRUE isolates vertices are not plotted.

size

is logical. If TRUE the point size of each vertex is proportional to its degree.

labelsize

is an integer. It indicates the label size in the plot. Default is labelsize=1

label is logical. If TRUE vertex labels are plotted.
 arrowsize is numerical. It indicates the edge arrow size.

Details

The function `histPlot` can plot a historical co-citation network previously created by `histNetwork`.

Value

It is a network object of the class `igraph`.

See Also

`histNetwork` to compute a historical co-citation network.

`cocMatrix` to compute a co-occurrence matrix.

`biblioAnalysis` to perform a bibliometric analysis.

Examples

```
# EXAMPLE Citation network

data(scientometrics)

histResults <- histNetwork(scientometrics, n = 20, sep = ";")

net <- histPlot(histResults, size = TRUE)
```

idByAuthor

Get Complete Author Information and ID from Scopus

Description

Uses SCOPUS API author search to identify author identification information.

Usage

```
idByAuthor(df, api_key)
```

Arguments

df is a dataframe composed of three columns:

lastname	author's last name
firstname	author's first name
affiliation	Part of the affiliation name (university name, city, etc.)

i.e. `df[1,1:3]<-c("aria","massimo","naples")` When affiliation is not specified,

the field `df$affiliation` have to be NA. i.e. `df[2,1:3]<-c("cuccurullo","corrado", NA)`

`api_key` is a character. It contains the Elsevier API key. Information about how to obtain an API Key [Elsevier API website](#)

Value

a data frame with cases corresponding to authors and variables to author's information and ID got from SCOPUS.

See Also

[retrievalByAuthorID](#) for downloading the complete author bibliographic collection from SCOPUS

Examples

```
## Request a personal API Key to Elsevier web page https://dev.elsevier.com/sc_apis.html
#
# api_key="your api key"

## create a data frame with the list of authors to get information and IDs
# i.e. df[1,1:3]<-c("aria","massimo","naples")
#      df[2,1:3]<-c("cuccurullo","corrado", NA)

## run idByAuthor function
#
# authorsID <- idByAuthor(df, api_key)
```

isi2df

Convert an ISI WoK Export file into a data frame

Description

It converts an ISI Wok Export file and create a data frame from it, with cases corresponding to articles and variables to Field Tag in the original file.

Usage

```
isi2df(D)
```

Arguments

`D` is a character array containing data read from a ISI Export file (in plain text format).

Value

a data frame with cases corresponding to articles and variables to Field Tag in the original ISI file.

See Also

[scopus2df](#) for converting SCOPUS Export file (in bibtex format)

Other converting functions: [cochrane2df](#), [convert2df](#), [isibib2df](#), [pubmed2df](#), [scopus2df](#)

Examples

```
# A group of ISI Export files can be read using \link{readFiles} function:  
  
# largechar <- readFiles('filename1.txt','filename2.txt','filename3.txt')  
  
# scientometrics_text <- readFiles('http://www.bibliometrix.org/datasets/scientometrics.txt')  
# data scientometrics_text  
# scient_df <- isi2df(scientometrics_text)
```

isibib2df

Convert an Clarivate Analytics WoS Export file into a data frame

Description

It converts an Clarivate Analytics WoS Export file and create a data frame from it, with cases corresponding to articles and variables to Field Tag in the original file.

Usage

```
isibib2df(D)
```

Arguments

D is a character array containing data read from an WoS Export file (in bibtex format).

Value

a data frame with cases corresponding to articles and variables to Field Tag in the original SCOPUS file.

See Also

[isi2df](#) for converting ISI Export file (in plain text format)

Other converting functions: [cochrane2df](#), [convert2df](#), [isi2df](#), [pubmed2df](#), [scopus2df](#)

Examples

```
# A ISI Export file can be read using \code{\link{readLines}} function:  
  
# largechar <- readFiles('filename1.bib','filename2.bib2,...')  
  
# filename.bib is a Clarivate Analytics WoS Export file in plain text format.  
  
# largechar <- readFiles('http://www.bibliometrix.org/datasets/ranking.bib')  
  
# ranking <- isibib2df(largechar)
```

isiCollection

"Bibliometrics" manuscripts from ISI WOS.

Description

Manuscripts including the term "bibliometrics" in the title.
Period: 1985 - 2017
Database: **ISI Web of Knowledge**
Format: bibtex

Format

A data frame with 329 rows and 16 variables:

AU Authors

TI Document Title

SO Publication Name (or Source)

JI ISO Source Abbreviation

DT Document Type

DE Author Keywords

ID Keywords associated by ISI or SCOPUS database

AB Abstract

C1 Author Address

RP Reprint Address

CR Cited References

TC Times Cited

PY Year

SC Subject Category

UT Unique Article Identifier

DB Database

Source

<http://www.webofknowledge.com>

keywordAssoc	<i>ID and DE keyword associations</i>
--------------	---------------------------------------

Description

It associates authors' keywords to keywords plus.

Usage

```
keywordAssoc(M, sep = ";", n = 10, excludeKW = NA)
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
sep	is the field separator character. This character separates keywords in each string of ID and DE columns of the bibliographic data frame. The default is sep = ";".
n	is a integer. It indicates the number of authors' keywords to associate to each keyword plus. The default is n = 10.
excludeKW	is character vector. It contains authors' keywords to exclude from the analysis.

Value

an object of class "list".

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.

[biblioAnalysis](#) function for bibliometric analysis.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

Examples

```
data(scientometrics)

KWlist <- keywordAssoc(scientometrics, sep = ";",n = 10, excludeKW = NA)

# list of first 10 Keywords plus
names(KWlist)
```

```
# list of first 10 authors' keywords associated to the first Keyword plus
KWlist[[1]][1:10]
```

KeywordGrowth	<i>Yearly occurrences of top keywords/terms</i>
---------------	---

Description

It calculates yearly occurrences of top keywords/terms.

Usage

```
KeywordGrowth(M, Tag = "ID", sep = ";", top = 10, cdf = TRUE)
```

Arguments

M	is a data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to articles and variables to Field Tag in the original ISI or SCOPUS file.
Tag	is a character object. It indicates one of the keyword field tags of the standard ISI WoS Field Tag codify (ID or DE) or a field tag created by termExtraction function (TI_TM, AB_TM, etc.).
sep	is the field separator character. This character separates strings in each keyword column of the data frame. The default is sep = ";".
top	is a numeric. It indicates the number of top keywords to analyze. The default value is 10.
cdf	is a logical. If TRUE, the function calculates the cumulative occurrences distribution.

Value

an object of class data.frame

Examples

```
data(scientometrics)
topKW=KeywordGrowth(scientometrics, Tag = "ID", sep = ";", top=5, cdf=TRUE)
topKW

# Plotting results
#
# library(reshape2)
# library(ggplot2)
# DF=melt(topKW, id='Year')
# ggplot(DF,aes(Year,value, group=variable, color=variable))+geom_line()
```

localCitations	<i>Author local citations</i>
----------------	-------------------------------

Description

It calculates local citations (LCS) of authors and documents of a bibliographic collection.

Usage

```
localCitations(M, sep = ";")
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
sep	is the field separator character. This character separates citations in each string of CR column of the bibliographic data frame. The default is sep = ";".

Details

Local citations measure how many times an author (or a document) included in this collection have been cited by the documents also included in the collection.

Value

an object of class "list" containing author local citations and docuemnt local citations.

See Also

[citations](#) function for citation frequency distribution.

[biblioAnalysis](#) function for bibliometric analysis.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

Examples

```
data(scientometrics)

CR <- localCitations(scientometrics, sep = ";")

CR$Authors[1:10,]
CR$Papers[1:10,]
```

lotka	<i>Lotka's law coefficient estimation</i>
-------	---

Description

It estimates Lotka's law coefficients for scientific productivity (*Lotka A.J., 1926*)

Usage

```
lotka(results)
```

Arguments

results is an object of the class 'bibliometrix' for which the analysis of the authors' dominance ranking is desired.

Value

The function lotka returns a list of summary statistics of the Lotka's law estimation of an object of class bibliometrix.

the list contains the following objects:

Beta	Beta coefficient
C	Constant coefficient
R2	Goodness of Fit
fitted	Fitted Values
p.value	Pvalue of two-sample Kolmogorov-Smirnov test between the empirical and the theoretical Lotka's Law distribution
AuthorProd	Authors' Productivity frequency table

See Also

[biblioAnalysis](#) function for bibliometric analysis

[summary](#) method for class 'bibliometrix'

Examples

```
data(scientometrics)
results <- biblioAnalysis(scientometrics)
L=lotka(results)
L
```

Description

Merge bibliographic data frames from different databases (ISI and SCOPUS) into a single one.

Usage

```
mergeDbSources(..., remove.duplicated = TRUE)
```

Arguments

`...` are the bibliographic data frames to merge.
`remove.duplicated` is logical. If TRUE duplicated documents will be deleted from the bibliographic collection.

Details

bibliographic data frames are obtained by the converting function [convert2df](#). The function merges data frames identifying common tag fields and duplicated records.

Value

the value returned from `mergeDbSources` is a bibliographic data frame.

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.

[biblioAnalysis](#) function for bibliometric analysis.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

Examples

```
data(isiCollection)
```

```
data(scopusCollection)
```

```
M <- mergeDbSources(isiCollection, scopusCollection, remove.duplicated=TRUE)
```

```
dim(M)
```

metaTagExtraction	<i>Meta-Field Tag Extraction</i>
-------------------	----------------------------------

Description

It extracts other field tags, different from the standard ISI/SCOPUS codify.

Usage

```
metaTagExtraction(M, Field = "CR_AU", sep = ";")
```

Arguments

M	is a data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to articles and variables to Field Tag in the original ISI or SCOPUS file.
Field	is a character object. New tag extracted from aggregated data is specified by this string. Field can be equal to one of this tags:
"CR_AU"	First Author of each cited reference
"CR_SO"	Source of each cited reference
"AU_CO"	Country of affiliation for each co-author
"AU1_CO"	Country of affiliation for the first author
"AU_UN"	University of affiliation for each co-author and the corresponding author (AU1_UN)
"SR"	Short tag of the document (as used in reference lists)
sep	is the field separator character. This character separates strings in each column of the data frame. The default is sep = ";".

Value

the bibliometric data frame with a new column containing data about new field tag indicated in the argument Field.

See Also

[scopus2df](#) for converting ISO or SCOPUS Export file into a data frame.

[biblioAnalysis](#) function for bibliometric analysis

Examples

```
# Example 1: First Authors for each cited reference

data(scientometrics)
scientometrics <- metaTagExtraction(scientometrics, Field = "CR_AU", sep = ";")
unlist(strsplit(scientometrics$CR_AU[1], ";"))
```

```
#Example 2: Source for each cited reference

data(scientometrics)
scientometrics <- metaTagExtraction(scientometrics, Field = "CR_SO", sep = ";")
unlist(strsplit(scientometrics$CR_SO[1], ";"))

#Example 3: Affiliation country for co-author

data(scientometrics)
scientometrics <- metaTagExtraction(scientometrics, Field = "AU_CO", sep = ";")
scientometrics$AU_CO[1:10]
```

networkPlot

Plotting Bibliographic networks

Description

networkPlot plots a bibliographic network.

Usage

```
networkPlot(NetMatrix, normalize = NULL, n = NULL, degree = NULL,
  Title = "Plot", type = "kamada", label = TRUE, labelsize = 1,
  label.cex = FALSE, label.short = TRUE, label.n = NULL, halo = FALSE,
  cluster = "walktrap", vos.path = NULL, size = 3, curved = FALSE,
  noloops = TRUE, remove.multiple = TRUE, remove.isolates = FALSE,
  weighted = NULL, edgesize = 1, edges.min = 0)
```

Arguments

NetMatrix	is a network matrix obtained by the function biblioNetwork .
normalize	is a character. It can be "association", "jaccard", "inclusion", "salton" or "equivalence" to obtain Association Strength, Jaccard, Inclusion, Salton or Equivalence similarity index respectively. The default is type = NULL.
n	is an integer. It indicates the number of vertices to plot.
degree	is an integer. It indicates the min frequency of a vertex. If degree is not NULL, n is ignored.
Title	is a character indicating the plot title.
type	is a character object. It indicates the network map layout:
type="circle"	Circle layout
type="sphere"	Sphere layout
type="mds"	Multidimensional Scaling layout
type="fruchterman"	Fruchterman-Reingold layout
type="kamada"	Kamada-Kawai layout
type="vosviewer"	Network is plotted using VOSviewer software

label	is logical. If TRUE vertex labels are plotted.
labelsize	is an integer. It indicates the label size in the plot. Default is labelsize=1
label.cex	is logical. If TRUE the label size of each vertex is proportional to its degree.
label.short	is a logical. If TRUE label are plotted in short format.
label.n	is an integer. It indicates the number of vertex labels to draw.
halo	is logical. If TRUE communities are plotted using different colors. Default is halo=FALSE
cluster	is a character. It indicates the type of cluster to perform among ("none", "optimal", "lovain", "infomap", "edge_betweenness", "walktrap").
vos.path	is a character indicating the full path where VOSviewer.jar is located.
size	is integer or logical. If TRUE the point size of each vertex is proportional to its degree. If it is a integer, the point size of each vertex is constant equal to size. Default is size=3.
curved	is a logical. If TRUE edges are plotted with an optimal curvature. Default is curved=FALSE
noloops	is logical. If TRUE loops in the network are deleted.
remove.multiple	is logical. If TRUE multiple links are plotted using just one edge.
remove.isolates	is logical. If TRUE isolates vertices are not plotted.
weighted	This argument specifies whether to create a weighted graph from an adjacency matrix. If it is NULL then an unweighted graph is created and the elements of the adjacency matrix gives the number of edges between the vertices. If it is a character constant then for every non-zero matrix entry an edge is created and the value of the entry is added as an edge attribute named by the weighted argument. If it is TRUE then a weighted graph is created and the name of the edge attribute will be weight.
edgesize	is an integer. It indicates the network edge size.
edges.min	is an integer. It indicates the min frequency of edges between two vertices. If edge.min=0, all edges are plotted.

Details

The function `networkPlot` can plot a bibliographic network previously created by `biblioNetwork`. The network map can be plotted using internal R routines or using `VOSviewer` by Nees Jan van Eck and Ludo Waltman.

Value

It is a list containing the following elements:

graph	a network object of the class <code>igraph</code>
cluster_obj	a <code>communities</code> object of the package <code>igraph</code>
cluster_res	a data frame with main results of clustering procedure.

See Also

[biblioNetwork](#) to compute a bibliographic network.

[cocMatrix](#) to compute a co-occurrence matrix.

[biblioAnalysis](#) to perform a bibliometric analysis.

Examples

```
# EXAMPLE Co-citation network

data(scientometrics)

NetMatrix <- biblioNetwork(scientometrics, analysis = "co-citation",
network = "references", sep = ";")

net <- networkPlot(NetMatrix, n = 30, type = "kamada", Title = "Co-Citation",labelsize=0.5)
```

normalizeSimilarity *Calculate similarity indices*

Description

It calculates a relative measure of bibliographic co-occurrences.

Usage

```
normalizeSimilarity(NetMatrix, type = "association")
```

Arguments

NetMatrix	is a coupling matrix obtained by the network functions biblioNetwork or cocMatrix .
type	is a character. It can be "association", "jaccard", "inclusion", "salton" or "equivalence" to obtain Association Strength, Jaccard, Inclusion, Salton or Equivalence similarity index respectively. The default is type = "association".

Details

couplingSimilarity calculates Association strength, Inclusion, Jaccard or Salton similarity from a co-occurrence bibliographic matrix.

The association strength is used by Van Eck and Waltman (2007) and Van Eck et al. (2006). Several works refer to the measure as the proximity index, while Leydesdorff (2008) and Zitt et al. (2000) refer to it as the probabilistic affinity (or activity) index.

The inclusion index, also called Simpson coefficient, is an overlap measure used in information retrieval.

The Jaccard index (or Jaccard similarity coefficient) gives us a relative measure of the overlap of two sets. It is calculated as the ratio between the intersection and the union of the reference lists (of two manuscripts).

The Salton index, instead, relates the intersection of the two lists to the geometric mean of the size of both sets. The square of Salton index is also called Equivalence index.

The indices are equal to zero if the intersection of the reference lists is empty.

Value

a similarity matrix.

See Also

[biblioNetwork](#) function to compute a bibliographic network.

[cocMatrix](#) to compute a bibliographic bipartite network.

Examples

```
data(scientometrics)
NetMatrix <- biblioNetwork(scientometrics, analysis = "co-occurrences",
  network = "keywords", sep = ";")
S=normalizeSimilarity(NetMatrix, type = "association")
```

plot.bibliometrix *Plotting bibliometric analysis results*

Description

plot method for class 'bibliometrix'

Usage

```
## S3 method for class 'bibliometrix'
plot(x, ...)
```

Arguments

x is the object for which plots are desired.

... can accept two arguments:
k is an integer, used for plot formatting (number of objects). Default value is 10.
pause is a logical, used to allow pause in screen scrolling of results. Default value is pause = FALSE.

Value

none. The function plot returns a set of plots of the object of class bibliometrix.

See Also

The bibliometric analysis function [biblioAnalysis](#).
[summary](#) to compute a list of summary statistics of the object of class `bibliometrix`.

Examples

```
data(scientometrics)

results <- biblioAnalysis(scientometrics)

plot(results, k = 10, pause = FALSE)
```

pubmed2df

Convert a PubMed/MedLine collection into a data frame

Description

It converts a PubMed/MedLine collection (obtained through a query performed with `RISmed` package) and create a data frame from it, with cases corresponding to articles and variables to Field Tags as proposed by Clarivate Analytics WoS.

Usage

```
pubmed2df(D)
```

Arguments

`D` is an object of class `MedLine` (package "RISmed") containing data resulting of a query performed on MedLine using the package `RISmed`.

Value

a data frame with cases corresponding to articles and variables to Field Tags as proposed by Clarivate Analytics WoS.

See Also

[scopus2df](#) for converting SCOPUS Export file (in bibtex format)
[isi2df](#) for converting Clarivate Analitics WoS Export file (in plaintext format)
[isibib2df](#) for converting Clarivate Analitics WoS Export file (in bibtex format)
Other converting functions: [cochrane2df](#), [convert2df](#), [isi2df](#), [isibib2df](#), [scopus2df](#)

Examples

```
# library(RISmed)
# search_topic <- 'epidermolysis bullosa'
# search_query <- EUtilsSummary(search_topic, retmax=200, mindate=2014, maxdate=2014)
# summary(search_query)
# D <- EUtilsGet(search_query)

# M <- pubmed2df(D)
```

readFiles	<i>Load a sequence of ISI or SCOPUS Export files into a large character object</i>
-----------	--

Description

It loads a sequence of SCOPUS and Thomson Reuters' ISI Web of Knowledge export files and create a large character vector from it.

Usage

```
readFiles(...)
```

Arguments

... is a sequence of names of files downloaded from ISI WOS.(in plain text or bibtex format) or SCOPUS Export file (exclusively in bibtex format).

Value

a character vector of length the number of lines read.

See Also

[convert2df](#) for converting SCOPUS of ISI Export file into a dataframe

Examples

```
# ISI or SCOPUS Export files can be read using \link{readFiles} function:

# largechar <- readFiles('filename1.txt','filename2.txt','filename3.txt')

# filename1.txt, filename2.txt and filename3.txt are ISI or SCOPUS Export file
# in plain text or bibtex format.

# D <- readFiles('http://www.bibliometrix.org/datasets/bibliometrics_articles.txt')
```

retrievalByAuthorID *Get Author Content on SCOPUS by ID*

Description

Uses SCOPUS API search to get information about documents on a set of authors using SCOPUS ID.

Usage

```
retrievalByAuthorID(id, api_key, remove.duplicated = TRUE)
```

Arguments

`id` is a vector of characters containing the author's SCOPUS IDs. SCOPUS IDs can be obtained using the function `idByAuthor`.

`api_key` is a character. It contains the Elsevier API key. Information about how to obtain an API Key [Elsevier API website](#)

`remove.duplicated` is logical. If TRUE duplicated documents will be deleted from the bibliographic collection.

Value

a list containing two objects: (i) `M` which is a data frame with cases corresponding to articles and variables to main Field Tags named using the standard ISI WoS Field Tag codify. `M` includes the entire bibliographic collection downloaded from SCOPUS. The main field tags are:

AU	Authors
TI	Document Title
SO	Publication Name (or Source)
DT	Document Type
DE	Authors' Keywords
ID	Keywords associated by SCOPUS or ISI database
AB	Abstract
C1	Author Address
RP	Reprint Address
TC	Times Cited
PY	Year
UT	Unique Article Identifier
DB	Database

(ii) `authorDocuments` which is a list containing a bibliographic data frame for each author.

LIMITATIONS: Currently, SCOPUS API does not allow to download document references. As consequence, it is not possible to perform co-citation analysis (the field `CR` is empty).

See Also

[idByAuthor](#) for downloading author information and SCOPUS ID.

Examples

```
## Request a personal API Key to Elsevier web page https://dev.elsevier.com/sc_apis.html

## api_key="your api key"

## create a data frame with the list of authors to get information and IDs
# i.e. df[1,1:3] <- c("aria","massimo","naples")
#       df[2,1:3] <- c("cuccurullo","corrado", "naples")

## run idByAuthor function
#
# authorsID <- idByAuthor(df, api_key)
#

## extract the IDs
#
# id <- authorsID[,3]
#

## create the bibliographic collection
#
# res <- retrievalByAuthor(id, api_key)
#
# M <- res$M # the entire bibliographic data frame
# M <- res$authorDocuments # the list containing a bibliographic data frame for each author
```

 scientometrics

"Co-citation analysis" and "Coupling analysis" manuscripts.

Description

Manuscripts about the topics "co-citation analysis" and "coupling analysis" published on Scientometrics Journal.

Period: 1985 - 2015

Database: [ISI Web of Knowledge](#)

Format

A data frame with 147 rows and 17 variables:

AU Authors

TI Document Title

SO Publication Name (or Source)

JI ISO Source Abbreviation
DT Document Type
DE Author Keywords
ID Keywords associated by ISI or SCOPUS database
AB Abstract
C1 Author Address
RP Reprint Address
CR Cited References
TC Times Cited
PY Year
SC Subject Category
UT Unique Article Identifier
DB Database
SR Short Reference

Source

<http://www.webofknowledge.com>

scientometrics_text *"Co-citation analysis" and "Coupling analysis" manuscripts.*

Description

Manuscripts about the topics "co-citation analysis" and "coupling analysis" published on Scientometrics Journal.

Period: 1985 - 2015

Database: [ISI Web of Knowledge](#)

Format

A large character with 12731 rows.

Data has been imported by an ISI Export file in plain text format using the function [readLines](#).

Source

<http://www.webofknowledge.com>

`scopus2df`*Convert a SCOPUS Export file into a data frame*

Description

It converts a SCOPUS Export file and create a data frame from it, with cases corresponding to articles and variables to Field Tag in the original file.

Usage

```
scopus2df(D)
```

Arguments

`D` is a character array containing data read from a SCOPUS Export file (in bibtext format).

Value

a data frame with cases corresponding to articles and variables to Field Tag in the original SCOPUS file.

See Also

[isi2df](#) for converting ISI Export file (in plain text format)

Other converting functions: [cochrane2df](#), [convert2df](#), [isi2df](#), [isibib2df](#), [pubmed2df](#)

Examples

```
# A SCOPUS Export file can be read using \link{readFiles} function:
# largechar <- readFiles('filename1.bib', 'filename2.bib2', ...)
# filename.bib is a SCOPUS Export file in plain text format.
#largechar <- readFiles('http://www.bibliometrix.org/datasets/scopus.bib')

#scopus_df <- scopus2df(largechar)
```

scopusCollection *"Bibliometrics" manuscripts from SCOPUS.*

Description

Manuscripts including the term "bibliometrics" in the title.
Period: 1975 - 2017
Database: **SCOPUS**
Format: bibtex

Format

A data frame with 487 rows and 15 variables:

AU Authors

TI Document Title

SO Publication Name (or Source)

JI ISO Source Abbreviation

DT Document Type

DE Author Keywords

ID Keywords associated by ISI or SCOPUS database

AB Abstract

C1 Author Address

RP Reprint Address

CR Cited References

TC Times Cited

PY Year

UT Unique Article Identifier

DB Database

Source

<http://www.scopus.com>

stopwords *List of English stopwords.*

Description

A character vector containing a complete list of English stopwords
Data are used by `biblioAnalysis` function to extract Country Field of Cited References and Authors.

Format

A character vector with 665 rows.

summary.bibliometrix *Summarizing bibliometric analysis results*

Description

summary method for class 'bibliometrix'

Usage

```
## S3 method for class 'bibliometrix'
summary(object, ...)
```

Arguments

object is the object for which a summary is desired.
... can accept two arguments:
 k integer, used for table formatting (number of rows). Default value is 10.
 pause logical, used to allow pause in screen scrolling of results. Default value is pause = FALSE.

Value

The function `summary` computes and returns a list of summary statistics of the object of class `bibliometrics`.

the list contains the following objects:

MainInformation	Main Information about Data
AnnualProduction	Annual Scientific Production
AnnualGrowthRate	Annual Percentage Growth Rate
MostProdAuthors	Most Productive Authors
MostCitedPapers	Top manuscripts per number of citations

MostProdCountries	Most Productive Countries
TCperCountries	Total Citation per Countries
MostRelSources	Most Relevant Sources
MostRelKeywords	Most Relevant Keywords

See Also

[biblioAnalysis](#) function for bibliometric analysis

[plot](#) to draw some useful plots of the results.

Examples

```
data(scientometrics)

results <- biblioAnalysis(scientometrics)

summary(results)
```

tableTag	<i>Tabulate elements from a Tag Field column</i>
----------	--

Description

It tabulates elements from a Tag Field column of a bibliographic data frame.

Usage

```
tableTag(M, Tag = "CR", sep = ";")
```

Arguments

M	is a data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to articles and variables to Field Tag in the original ISI or SCOPUS file.
Tag	is a character object. It indicates one of the field tags of the standard ISI WoS Field Tag codify.
sep	is the field separator character. This character separates strings in each column of the data frame. The default is sep = ";".

Details

tableTag is an internal routine of main function [biblioAnalysis](#).

Value

an object of class table

Examples

```
data(scientometrics)
Tab <- tableTag(scientometrics, Tag = "CR", sep = ";")
Tab[1:10]
```

termExtraction	<i>Term extraction tool from textual fields of a manuscript</i>
----------------	---

Description

It extracts terms from a textual field (abstract, title, author's keywords, etc.) of a bibliographic data frame.

Usage

```
termExtraction(M, Field = "TI", stemming = FALSE, language = "english",
  remove.numbers = TRUE, remove.terms = NULL, keep.terms = NULL,
  synonyms = NULL, verbose = TRUE)
```

Arguments

M is a data frame obtained by the converting function [convert2df](#). It is a data matrix with cases corresponding to articles and variables to Field Tag in the original ISI or SCOPUS file.

Field is a character object. It indicates the field tag of textual data :

"TI"	Manuscript title
"AB"	Manuscript abstract
"ID"	Manuscript keywords plus
"DE"	Manuscript author's keywords

The default is `Field = "TI"`.

stemming is logical. If TRUE the Porter Stemming algorithm is applied to all extracted terms. The default is `stemming = FALSE`.

language is a character. It is the language of textual contents ("english", "german", "italian", "french", "spanish"). The default is `language="english"`.

remove.numbers is logical. If TRUE all numbers are deleted from the documents before term extraction. The default is `remove.numbers = TRUE`.

remove.terms is a character vector. It contains a list of additional terms to delete from the documents before term extraction. The default is `remove.terms = NULL`.

keep.terms is a character vector. It contains a list of compound words "formed by two or more terms" to keep in their original form in the term extraction process. The default is `keep.terms = NULL`.

synonyms	is a character vector. Each element contains a list of synonyms, separated by ";", that will be merged into a single term (the first word contained in the vector element). The default is synonyms = NULL.
verbose	is logical. If TRUE the function prints the most frequent terms extracted from documents. The default is verbose=TRUE.

Value

the bibliometric data frame with a new column containing terms about the field tag indicated in the argument Field.

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.
[biblioAnalysis](#) function for bibliometric analysis

Examples

```
# Example 1: Term extraction from titles

data(scientometrics)

# vector of compound words
keep.terms <- c("co-citation analysis","bibliographic coupling")

# term extraction
scientometrics <- termExtraction(scientometrics, Field = "TI",
remove.numbers=TRUE, remove.terms=NULL, keep.terms=keep.terms, verbose=TRUE)

# terms extracted from the first 10 titles
scientometrics$TI_TM[1:10]

#Example 2: Term extraction from abstracts

data(scientometrics)

# vector of terms to remove
remove.terms=c("analysis","bibliographic")

# term extraction
scientometrics <- termExtraction(scientometrics, Field = "AB", stemming=TRUE,language="english",
remove.numbers=TRUE, remove.terms=remove.terms, keep.terms=NULL, verbose=TRUE)

# terms extracted from the first abstract
scientometrics$AB_TM[1]

# Example 3: Term extraction from keywords with synonyms

data(scientometrics)
```

```
# vector of synonyms
synonyms <- c("citation; citation analysis", "h-index; index; impact factor")

# term extraction
scientometrics <- termExtraction(scientometrics, Field = "ID",
synonyms=synonyms, verbose=TRUE)
```

thematicEvolution *Create an Evolution Thematic Map*

Description

It creates an Evolution thematic map based on co-word network analysis and clustering. The methodology is inspired by the proposal of Cobo et al. (2011).

Usage

```
thematicEvolution(..., weighted = FALSE)
```

Arguments

... is a sequence of names of thematic maps created by [thematicMap](#) function.

weighted is a logical. If FALSE, a thematic nexus is measures by the classical inclusion index (calculated using the number of keywords). If TRUE, the inclusion index is calculated considering the occurrences of keywords.

Details

[thematicEvolution](#) starts from two or more thematic maps created by [thematicMap](#) function.

Value

a list containing:

nets	The thematic nexus graph for each comparison
incMatrix	Some useful statistics about the thematic nexus

See Also

[thematicMap](#) function to create a thematic map based on co-word network analysis and clustering.

[cocMatrix](#) to compute a bibliographic bipartite network.

[networkPlot](#) to plot a bibliographic network.

Examples

```

data(scientometrics)
years=c(2000)
list_df=timeslice(scientometrics, breaks = years)
M1=list_df[[1]]
M2=list_df[[2]]
NetMatrix1 <- biblioNetwork(M1, analysis = "co-occurrences",
                           network = "keywords", sep = ";")
S1 <- normalizeSimilarity(NetMatrix1, type = "association")
net1 <- networkPlot(NetMatrix1, normalize = "association",n = 50,
                  Title = "co-occurrence network",type="fruchterman",
                  labelsize = 0.7, halo = FALSE, cluster = "walktrap",remove.isolates=FALSE,
                  remove.multiple=FALSE, noloops=TRUE, weighted=TRUE)
res1 <- thematicMap(net1, NetMatrix1, S1)
#plot(res1$map)

NetMatrix2 <- biblioNetwork(M2, analysis = "co-occurrences",
                           network = "keywords", sep = ";")
S2 <- normalizeSimilarity(NetMatrix2, type = "association")
net2 <- networkPlot(NetMatrix2, normalize = "association",n = 50,
                  Title = "co-occurrence network",type="fruchterman",
                  labelsize = 0.7, halo = FALSE, cluster = "walktrap",remove.isolates=FALSE,
                  remove.multiple=FALSE, noloops=TRUE, weighted=TRUE)
res2 <- thematicMap(net2, NetMatrix2, S2)
#plot(res2$map)

nexus <- thematicEvolution(res1,res2,weighted=FALSE)

```

thematicMap

Create a thematic map

Description

It creates a thematic map based on co-word network analysis and clustering. The methodology is inspired by the proposal of Cobo et al. (2011).

Usage

```
thematicMap(Net, NetMatrix, S = NULL, minfreq = 5)
```

Arguments

Net	is a igraph object created by networkPlot function.
NetMatrix	is a co-occurrence matrix obtained by the network functions biblioNetwork or cocMatrix .
S	is a similarity matrix obtained by the normalizeSimilarity function. If S is NULL, map is created using co-occurrence counts.
minfreq	is a integer. It indicates the minimum frequency of a cluster.

Details

thematicMap starts from a co-occurrence keyword network to plot in a two-dimensional map the typological themes of a domain.

Value

a list containing:

map	The thematic map as ggplot2 object
clusters	Centrality and Density values for each cluster.
words	A list of words following in each cluster

See Also

[biblioNetwork](#) function to compute a bibliographic network.

[cocMatrix](#) to compute a bibliographic bipartite network.

[networkPlot](#) to plot a bibliographic network.

Examples

```
data(scientometrics)
NetMatrix <- biblioNetwork(scientometrics, analysis = "co-occurrences",
  network = "keywords", sep = ";")
S <- normalizeSimilarity(NetMatrix, type = "association")
net <- networkPlot(S, n = 100, Title = "co-occurrence network", type="fruchterman",
  labelsSize = 0.7, halo = FALSE, cluster = "walktrap", remove.isolates=FALSE,
  remove.multiple=FALSE, noloops=TRUE, weighted=TRUE)
res <- thematicMap(net, NetMatrix, S)
plot(res$map)
```

timeslice

Bibliographic data frame time slice

Description

Divide a bibliographic data frame into time slice

Usage

```
timeslice(M, breaks = NA, k = 5)
```

Arguments

M	is a bibliographic data frame obtained by the converting function convert2df . It is a data matrix with cases corresponding to manuscripts and variables to Field Tag in the original SCOPUS and Thomson Reuters' ISI Web of Knowledge file.
breaks	is a numeric vector of two or more unique cut points.
k	is a integer value giving the number of intervals into which the data frame is to be cut. k is used only in case breaks argument is not provided. The default is k = 5.

Value

the value returned from `split` is a list containing the data frames for each sub-period.

See Also

[convert2df](#) to import and convert an ISI or SCOPUS Export file in a bibliographic data frame.

[biblioAnalysis](#) function for bibliometric analysis.

[summary](#) to obtain a summary of the results.

[plot](#) to draw some useful plots of the results.

Examples

```
data(scientometrics)
list_df <- timeslice(scientometrics, breaks = c(1995, 2005))
names(list_df)
```

trim

Deleting leading and ending white spaces

Description

Deleting leading and ending white spaces from a character object.

Usage

```
trim(x)
```

Arguments

x is a character object.

Details

tableTag is an internal routine of bibliometrics package.

Value

an object of class character

Examples

```
char <- c(" Alfred", "Mary", " John")
char
trim(char)
```

trim.leading	<i>Deleting leading white spaces</i>
--------------	--------------------------------------

Description

Deleting leading white spaces from a character object.

Usage

```
trim.leading(x)
```

Arguments

x is a character object.

Details

tableTag is an internal routine of bibliometrics package.

Value

an object of class character

Examples

```
char <- c(" Alfred", "Mary", " John")
char
trim.leading(char)
```

Index

*Topic **package**

- bibliometrix-package, 3

- biblio, 4
- biblio_df, 8
- biblioAnalysis, 5, 7, 9, 12, 14, 16–19, 22, 26, 28–31, 34, 36, 43, 44, 46, 50
- bibliometrix (bibliometrix-package), 3
- bibliometrix-package, 3
- biblioNetwork, 6, 6, 12, 13, 21, 32–35, 48, 49

- citations, 9, 28
- cochrane2df, 10, 15, 24, 36, 41
- cocMatrix, 7, 11, 14, 22, 34, 35, 47–49
- communities, 33
- conceptualStructure, 12
- convert2df, 5–7, 9–13, 14, 17–21, 24, 26–28, 30, 31, 36, 37, 41, 44–46, 50
- countries, 16

- dominance, 16
- duplicatedMatching, 17

- garfield, 18

- Hindex, 19
- histNetwork, 20, 21, 22
- histPlot, 21, 22

- idByAuthor, 22, 38, 39
- isi2df, 10, 15, 23, 24, 36, 41
- isibib2df, 10, 15, 24, 24, 36, 41
- isiCollection, 25

- keywordAssoc, 26
- KeywordGrowth, 27

- localCitations, 28
- lotka, 29

- Matrix, 7, 11

- mergeDbSources, 29
- metaTagExtraction, 31

- networkPlot, 32, 33, 47–49
- normalizeSimilarity, 34, 48

- plot, 5, 6, 9, 18, 19, 21, 26, 28, 30, 44, 50
- plot.bibliometrix, 35
- pubmed2df, 10, 15, 24, 36, 41

- readFiles, 37
- readLines, 4, 40
- retrievalByAuthorID, 23, 38

- scientometrics, 39
- scientometrics_text, 40
- scopus2df, 10, 15, 24, 31, 36, 41
- scopusCollection, 42
- stopwords, 43
- summary, 5, 6, 9, 17–19, 21, 26, 28–30, 36, 50
- summary.bibliometrix, 43

- tableTag, 44
- termExtraction, 13, 27, 45
- thematicEvolution, 47, 47
- thematicMap, 47, 48
- timeslice, 49
- trim, 50
- trim.leading, 51