

Package ‘coro’

December 17, 2020

Title 'Coroutines' for R

Version 1.0.1

Description Provides 'coroutines' for R, a family of functions that can be suspended and resumed later on. This includes 'async' functions (which await) and generators (which yield). 'Async' functions are based on the concurrency framework of the 'promises' package. Generators are based on a dependency free iteration protocol defined in 'coro' and are compatible with iterators from the 'reticulate' package.

Depends R (>= 3.5.0)

Imports rlang (>= 0.4.9)

Suggests knitr, later (>= 1.1.0), magrittr (>= 2.0.0), promises, reticulate, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

License MIT + file LICENSE

URL <https://github.com/r-lib/coro>

BugReports <https://github.com/r-lib/coro/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Config/testthat/edition 3

NeedsCompilation no

Author Lionel Henry [aut, cre],
RStudio [cph]

Maintainer Lionel Henry <lionel@rstudio.com>

Repository CRAN

Date/Publication 2020-12-17 20:10:02 UTC

R topics documented:

coro-package	2
async	3
async_collect	4
async_generator	5
async_sleep	6
as_iterator	6
collect	7
coro_debug	8
generator	9
iterator	11
yield	12

Index	13
--------------	-----------

coro-package	<i>coro: 'Coroutines' for R</i>
--------------	---------------------------------

Description

Provides 'coroutines' for R, a family of functions that can be suspended and resumed later on. This includes 'async' functions (which await) and generators (which yield). 'Async' functions are based on the concurrency framework of the 'promises' package. Generators are based on a dependency free iteration protocol defined in 'coro' and are compatible with iterators from the 'reticulate' package.

Author(s)

Maintainer: Lionel Henry <lionel@rstudio.com>

Other contributors:

- RStudio [copyright holder]

See Also

Useful links:

- <https://github.com/r-lib/coro>
- Report bugs at <https://github.com/r-lib/coro/issues>

`async`*Make an async function*

Description

`async()` functions are building blocks for cooperative concurrency.

- They are *concurrent* because they are jointly managed by a scheduler in charge of running them.
- They are *cooperative* because they decide on their own when they can no longer make quick progress and need to **await** some result. This is done with the `await()` keyword which suspends the async function and gives control back to the scheduler. The scheduler waits until the next async operation is ready to make progress.

The async framework used by `async()` functions is implemented in the `later` and `promises` packages:

- You can chain async functions created with `coro` to promises.
- You can await promises. You can also await futures created with the `future` package because they are coercible to promises.

Usage

```
async(fn)
```

```
await(x)
```

Arguments

<code>fn</code>	An anonymous function within which <code>await()</code> calls are allowed.
<code>x</code>	An awaitable value, i.e. a promise .

Value

A function that returns a `promises::promise()`.

See Also

[async_generator\(\)](#) and [await_each\(\)](#); [coro_debug\(\)](#) for step-debugging.

Examples

```
# This async function counts down from `n`, sleeping for 2 seconds
# at each iteration:
async_count_down <- async(function(n) {
  while (n > 0) {
    cat("Down", n, "\n")
    await(async_sleep(2))
  }
})
```

```

    n <- n - 1
  }
})

# This async function counts up until `stop`, sleeping for 0.5
# seconds at each iteration:
async_count_up <- async(function(stop) {
  n <- 1
  while (n <= stop) {
    cat("Up", n, "\n")
    await(async_sleep(0.5))
    n <- n + 1
  }
})

# You can run these functions concurrently using `promise_all()`
if (interactive()) {
  promises::promise_all(async_count_down(5), async_count_up(5))
}

```

 async_collect

Collect elements of an asynchronous iterator

Description

async_collect() takes an asynchronous iterator, i.e. an iterable function that is also awaitable. async_collect() returns an awaitable that eventually resolves to a list containing the values returned by the iterator. The values are collected until exhaustion unless n is supplied. The collection is grown geometrically for performance.

Usage

```
async_collect(x, n = NULL)
```

Arguments

x	An iterator function.
n	The number of elements to collect. If x is an infinite sequence, n must be supplied to prevent an infinite loop.

Examples

```

# Emulate an async stream by yielding promises that resolve to the
# elements of the input vector
generate_stream <- async_generator(function(x) for (elt in x) yield(elt))

# You can await `async_collect()` in an async function. Once the
# list of values is resolved, the async function resumes.

```

```
async(function() {
  stream <- generate_stream(1:3)
  values <- await(async_collect(stream))
  values
})
```

async_generator	<i>Construct an async generator</i>
-----------------	-------------------------------------

Description

An async generator constructs iterable functions that are also awaitables. They support both the `yield()` and `await()` syntax. An async iterator can be looped within async functions and iterators using `await_each()` on the input of a for loop.

The iteration protocol is derived from the one described in [iterator](#). An async iterator always returns a promise. When the iterator is exhausted, it returns a resolved promise to the exhaustion sentinel.

Usage

```
async_generator(fn)
```

```
await_each(x)
```

Arguments

fn	An anonymous function describing an async generator within which <code>await()</code> calls are allowed.
x	An awaitable value, i.e. a promise .

Value

A generator factory. Generators constructed with this factory always return `promises::promise()`.

See Also

[async\(\)](#) for creating awaitable functions; [async_collect\(\)](#) for collecting the values of an async iterator; [coro_debug\(\)](#) for step-debugging.

Examples

```
# Creates awaitable functions that transform their inputs into a stream
generate_stream <- async_generator(function(x) for (elt in x) yield(elt))

# Maps a function to a stream
async_map <- async_generator(function(.i, .fn, ...) {
  for (elt in await_each(.i)) {
    yield(.fn(elt, ...))
  }
})
```

```

    }
  })

# Example usage:
if (interactive()) {
  library(magrittr)
  generate_stream(1:3) %>% async_map(`*`, 2) %>% async_collect()
}

```

async_sleep	<i>Sleep asynchronously</i>
-------------	-----------------------------

Description

Sleep asynchronously

Usage

```
async_sleep(seconds)
```

Arguments

seconds The number of second to sleep.

Value

A chainable promise.

as_iterator	<i>Transform an object to an iterator</i>
-------------	---

Description

as_iterator() is a generic function that transforms its input to an [iterator function](#). The default implementation is as follows:

- Functions are returned as is.
- Other objects are assumed to be vectors with length() and [] methods.

Methods must return functions that implement coro's [iterator protocol](#).

as_iterator() is called by coro on the RHS of in in for loops. This applies within [generators](#), [async functions](#), and [loop\(\)](#).

Usage

```
as_iterator(x)

## Default S3 method:
as_iterator(x)
```

Arguments

x An object.

Value

An iterable function.

Examples

```
as_iterator(1:3)

i <- as_iterator(1:3)
loop(for (x in i) print(x))
```

collect

Iterate over iterator functions

Description

loop() and collect() are helpers for iterating over [iterator functions](#) such as [generators](#).

- loop() takes a for loop expression in which the collection can be an iterator function.
- collect() loops over the iterator and collects the values in a list.

Usage

```
collect(x, n = NULL)

loop(loop)
```

Arguments

x An iterator function.

n The number of elements to collect. If x is an infinite sequence, n must be supplied to prevent an infinite loop.

loop A for loop expression.

Value

collect() returns a list of values; loop() returns the [exhausted\(\)](#) sentinel, invisibly.

See Also

[async_collect\(\)](#) for async generators.

Examples

```
generate_abc <- generator(function() for (x in letters[1:3]) yield(x))
abc <- generate_abc()

# Collect 1 element:
collect(abc, n = 1)

# Collect all remaining elements:
collect(abc)

# With exhausted iterators collect() returns an empty list:
collect(abc)

# With loop() you can use `for` loops with iterators:
abc <- generate_abc()
loop(for (x in abc) print(x))
```

coro_debug

Debug a generator or async function

Description

- Call `coro_debug()` on a [generator\(\)](#), [async\(\)](#), or [async_generator\(\)](#) function to enable step-debugging.
- Alternatively, set `options(coro_debug = TRUE)` for step-debugging through all functions created with `coro`.

Usage

```
coro_debug(fn, value = TRUE)
```

Arguments

<code>fn</code>	A generator factory or an async function.
<code>value</code>	Whether to debug the function.

Description

`generator()` creates an generator factory. A generator is an [iterator function](#) that can pause its execution with `yield()` and resume from where it left off. Because they manage state for you, generators are the easiest way to create iterators. See `vignette("generator")`.

The following rules apply:

- Yielded values do not terminate the generator. If you call the generator again, the execution resumes right after the yielding point. All local variables are preserved.
- Returned values terminate the generator. If called again after a `return()`, the generator keeps returning the `exhausted()` sentinel.

Generators are compatible with all features based on the iterator protocol such as `loop()` and `collect()`.

Usage

```
generator(fn)
```

```
gen(expr)
```

Arguments

<code>fn</code>	A function template for generators. The function can <code>yield()</code> values. Within a generator, for loops have iterator support.
<code>expr</code>	A yielding expression.

See Also

[yield\(\)](#), [coro_debug\(\)](#) for step-debugging.

Examples

```
# A generator statement creates a generator factory. The
# following generator yields two times and then returns `c`:
generate_abc <- generator(function() {
  yield("a")
  yield("b")
  "c"
})

# Or equivalently:
generate_abc <- generator(function() {
  for (x in letters[1:3]) {
    yield(x)
  }
})
```

```

    }
  })

# The factory creates generator instances. They are iterators
# that you can call successively to obtain new values:
abc <- generate_abc()
abc()
abc()

# Once a generator has returned it keeps returning `exhausted()`.
# This signals to its caller that new values can no longer be
# produced. The generator is exhausted:
abc()
abc()

# You can only exhaust a generator once but you can always create
# new ones from a factory:
abc <- generate_abc()
abc()

# As generators implement the coro iteration protocol, you can use
# coro tools like `loop()`. It makes it possible to loop over
# iterators with `for` expressions:
loop(for (x in abc) print(x))

# To gather values of an iterator in a list, use `collect()`. Pass
# the `n` argument to collect that number of elements from a
# generator:
abc <- generate_abc()
collect(abc, 1)

# Or drain all remaining elements:
collect(abc)

# coro provides a short syntax `gen()` for creating one-off
# generator _instances_. It is handy to adapt existing iterators:
numbers <- 1:10
odds <- gen(for (x in numbers) if (x %% 2 != 0) yield(x))
squares <- gen(for (x in odds) yield(x^2))
greetings <- gen(for (x in squares) yield(paste("Hey", x)))

collect(greetings)

# Arguments passed to generator instances are returned from the
# `yield()` statement on reentry:
new_tally <- generator(function() {
  count <- 0
  while (TRUE) {
    i <- yield(count)
    count <- count + i
  }
})

```

```
    }  
  })  
  tally <- new_tally()  
  tally(1)  
  tally(2)  
  tally(10)
```

iterator

Iterator protocol

Description

An **iterator** is a function that implements the following protocol:

- Calling the function advances the iterator. The new value is returned.
- When the iterator is exhausted and there are no more elements to return, the symbol `quote(exhausted)` is returned. This signals exhaustion to the caller.
- Once an iterator has signalled exhaustion, all subsequent invocations must consistently return `quote(exhausted)`.

```
iterator <- as_iterator(1:3)  
  
# Calling the iterator advances it  
iterator()  
  
## [1] 1  
  
iterator()  
  
## [1] 2  
  
# This is the last value  
iterator()  
  
## [1] 3  
  
# Subsequent invocations return the exhaustion sentinel  
iterator()  
  
## exhausted
```

Because iteration is defined by a protocol, creating iterators is free of dependency. However, it is often simpler to create iterators with [generators](#), see `vignette("generator")`. To loop over an iterator, it is simpler to use the `loop()` and `collect()` helpers provided in this package.

Usage

```
exhausted()
```

```
is_exhausted(x)
```

Arguments

x An object.

Properties

Iterators are **stateful**. Advancing the iterator creates a persistent effect in the R session. Also iterators are **one-way**. Once you have advanced an iterator, there is no going back and once it is exhausted, it stays exhausted.

Iterators are not necessarily finite. They can also represent infinite sequences, in which case trying to exhaust them is a programming error that causes an infinite loop.

yield	<i>Yield a value from a generator</i>
-------	---------------------------------------

Description

The `yield()` statement suspends [generator\(\)](#) functions. It works like `return()` except that the function continues execution at the yielding point when it is called again.

`yield()` can be called within loops and if-else branches but for technical reasons it can't be used anywhere in R code:

- `yield()` cannot be called as part of a function argument. Code such as `list(yield())` is illegal.
- `yield()` does not cross function boundaries. You can't use it a lambda function passed to `lapply()` for instance.

Usage

```
yield(x)
```

Arguments

x A value to yield.

See Also

[generator\(\)](#) for examples.

Index

`as_iterator`, 6
`async`, 3
`async functions`, 6
`async()`, 5, 8
`async_collect`, 4
`async_collect()`, 5, 8
`async_generator`, 5
`async_generator()`, 3, 8
`async_sleep`, 6
`await (async)`, 3
`await_each (async_generator)`, 5
`await_each()`, 3

`collect`, 7
`collect()`, 9, 11
`coro (coro-package)`, 2
`coro-package`, 2
`coro_debug`, 8
`coro_debug()`, 3, 5, 9

`exhausted (iterator)`, 11
`exhausted()`, 7, 9

`gen (generator)`, 9
`generator`, 9
`generator()`, 8, 12
`generators`, 6, 7, 11

`is_exhausted (iterator)`, 11
`iterator`, 5, 9, 11
`iterator function`, 6, 9
`iterator functions`, 7
`iterator protocol`, 6

`loop (collect)`, 7
`loop()`, 6, 9, 11

`promise`, 3, 5
`promises::promise()`, 3, 5

`yield`, 12
`yield()`, 9