

Package ‘docuSignr’

October 22, 2017

Title Connect to 'DocuSign' API

Version 0.0.3

Description Connect to the 'DocuSign' Rest API <<https://www.docusign.com/p/RESTAPIGuide/RESTAPIGuide.htm>>, which supports embedded signing, and sending of documents.

Depends R (>= 3.2.2)

License GPL-3

Encoding UTF-8

LazyData true

Imports httr, jsonlite, magrittr

RoxygenNote 6.0.1

Suggests testthat, covr, drat

URL <https://github.com/CannaData/docuSignr>

BugReports <https://github.com/CannaData/docuSignr/issues>

NeedsCompilation no

Author Carl Ganz [aut, cre],
CannaData Solutions [cph]

Maintainer Carl Ganz <carl@cannadatasolutions.com>

Repository CRAN

Date/Publication 2017-10-22 03:09:17 UTC

R topics documented:

docu_auth	2
docu_download	2
docu_embedded_sign	3
docu_envelope	4
docu_envelope_status	5
docu_header	6
docu_list_envelopes	6

docu_login	7
docu_templates	8
parse_response	8

Index 9

docu_auth *Create XML authentication string*

Description

Create XML authentication string

Usage

```
docu_auth(username = Sys.getenv("docuSign_username"),
          password = Sys.getenv("docuSign_password"),
          integrator_key = Sys.getenv("docuSign_integrator_key"))
```

Arguments

username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey

docu_download *Download Document from DocuSign*

Description

Download Document from DocuSign

Usage

```
docu_download(file, username = Sys.getenv("docuSign_username"),
             password = Sys.getenv("docuSign_password"),
             integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
             envelope_id)
```

Arguments

file	a character string naming a file
username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey
base_url	base_url
envelope_id	id of envelope

Examples

```
## Not run:
login <- docu_login(demo = TRUE)
envelopes <- docu_list_envelopes(base_url = login$baseUr1[1], from_date = "2017/1/1")
envelope_id <- envelopes[envelopes$status == "completed", "envelopeId"][1]
file <- tempfile()
document <- docu_download(file, base_url = login[1, 3],
                          envelope_id = envelope_id)

## End(Not run)
```

docu_embedded_sign *Embedded docuSign*

Description

Get URL for embedded docuSign

Usage

```
docu_embedded_sign(username = Sys.getenv("docuSign_username"),
                  password = Sys.getenv("docuSign_password"),
                  integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
                  return_url, envelope_id, signer_name, signer_email, client_user_id,
                  authentication_method = "None")
```

```
docu_embedded_send(username = Sys.getenv("docuSign_username"),
                  password = Sys.getenv("docuSign_password"),
                  integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
                  return_url, uri, signer_name, signer_email, client_user_id,
                  authentication_method = "None")
```

Arguments

username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey
base_url	docuSign baseURL
return_url	URL to return to after signing
envelope_id	ID for envelope returned from docu_envelope
signer_name	Name of person signing document
signer_email	Email of person signing document
client_user_id	ID for signer
authentication_method	Method application uses to authenticate user. Defaults to "None".
uri	uri path

Examples

```
## Not run:
# assuming env variables are properly set up
login <- docu_login()
template <- docu_templates(base_url = login[1, "baseUrl"])
env <- docu_envelope(username = Sys.getenv("docuSign_username"),
  password = Sys.getenv("docuSign_password"),
  integrator_key = Sys.getenv("docuSign_integrator_key"),
  account_id = login[1, "accountId"], base_url = login[1, "baseUrl"],
  template_id = template$templateId,
  template_roles = list(name = "Name", email = "email@example.com",
    roleName = "Role", clientUserId = "1"),
  email_subject = "Subject", email_blurb = "Body"
)
URL <- docu_embed(
  base_url = login[1, "baseUrl"], return_url = "www.google.com",
  signer_name = "Name", signer_email = "email@example.com",
  client_user_id = "1",
  envelope_id = env$envelopeId
)

## End(Not run)
```

docu_envelope

Create document for particular instance to be signed

Description

Does envelope stuff

Usage

```
docu_envelope(username = Sys.getenv("docuSign_username"),
  password = Sys.getenv("docuSign_password"),
  integrator_key = Sys.getenv("docuSign_integrator_key"), account_id,
  status = "sent", base_url, template_id, template_roles, email_subject,
  email_blurb)
```

Arguments

username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey
account_id	docuSign accountId
status	envelope status
base_url	docuSign baseURL
template_id	docuSign templateId

```

template_roles list of parameters passed to template
email_subject docuSign emailSubject
email_blurb docuSign emailBlurb

```

Examples

```

## Not run:
# assuming env variables are properly set up
login <- docu_login()
template <- docu_templates(base_url = login[1, "baseUrl"])
(env <- docu_envelope(username = Sys.getenv("docuSign_username"),
  password = Sys.getenv("docuSign_password"),
  integrator_key = Sys.getenv("docuSign_integrator_key"),
  account_id = login[1, "accountId"], base_url = login[1, "baseUrl"],
  template_id = template$templateId,
  template_roles = list(name = "Name", email = "email@example.com",
    roleName = "Role", clientId = "1"),
  email_subject = "Subject", email_blurb = "Body"
))

## End(Not run)

```

docu_envelope_status *Check status of envelope*

Description

Check status of envelope

Usage

```

docu_envelope_status(username = Sys.getenv("docuSign_username"),
  password = Sys.getenv("docuSign_password"),
  integrator_key = Sys.getenv("docuSign_integrator_key"), base_url,
  envelope_id)

```

Arguments

```

username      docuSign username
password      docuSign password
integrator_key docusign integratorKey
base_url      base_url
envelope_id   id of envelope

```

Examples

```
## Not run:
login <- docu_login(demo = TRUE)
envelopes <- docu_list_envelopes(base_url = login$baseUr1[1], from_date = "2017/1/1")
envelope_id <- envelopes[envelopes$status == "completed", "envelopeId"][1]
status <- docu_envelope_status(base_url = login[1, 3],
                              envelope_id = envelope_id)

## End(Not run)
```

docu_header	<i>Create header for docuSign</i>
-------------	-----------------------------------

Description

Create header for authentication with docuSign

Usage

```
docu_header(auth)
```

Arguments

auth	XML object with authentication info
------	-------------------------------------

docu_list_envelopes	<i>List envelopes since date</i>
---------------------	----------------------------------

Description

List envelopes since date

Usage

```
docu_list_envelopes(username = Sys.getenv("docuSign_username"),
                    password = Sys.getenv("docuSign_password"),
                    integrator_key = Sys.getenv("docuSign_integrator_key"), base_url, from_date)
```

Arguments

username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey
base_url	base_url
from_date	character indicating begin date of search

Examples

```
## Not run:
login <- docu_login(demo = TRUE)
envelopes <- docu_list_envelopes(base_url = login$baseUr1[1], from_date = "2017/1/1")

## End(Not run)
```

docu_login	<i>Authenticate DocuSign</i>
------------	------------------------------

Description

Login to DocuSign and get baseURL and accountId

Usage

```
docu_login(username = Sys.getenv("docuSign_username"),
           password = Sys.getenv("docuSign_password"),
           integrator_key = Sys.getenv("docuSign_integrator_key"), demo = FALSE)
```

Arguments

username	docuSign username
password	docuSign password
integrator_key	docusign integratorKey
demo	indicate whether to use DocuSign demo server

Examples

```
## Not run:
# assuming env variables are properly set up
(login <- docu_login())

## End(Not run)
```

docu_templates	<i>View templates</i>
----------------	-----------------------

Description

See all templates associated with account

Usage

```
docu_templates(username = Sys.getenv("docuSign_username"),
  password = Sys.getenv("docuSign_password"),
  integrator_key = Sys.getenv("docuSign_integrator_key"), base_url)
```

Arguments

username	docuSign username
password	docuSign password
integrator_key	docuSign integratorKey
base_url	docuSign baseURL

Examples

```
## Not run:
login <- docu_login()
templates <- docu_templates(base_url = login[1, 3])

## End(Not run)
```

parse_response	<i>Process results from POST or GET</i>
----------------	---

Description

Process results from POST or GET

Usage

```
parse_response(response)
```

Arguments

response	Result of POST or GET
----------	-----------------------

Index

docu_auth, [2](#)
docu_download, [2](#)
docu_embedded_send
 (docu_embedded_sign), [3](#)
docu_embedded_sign, [3](#)
docu_envelope, [4](#)
docu_envelope_status, [5](#)
docu_header, [6](#)
docu_list_envelopes, [6](#)
docu_login, [7](#)
docu_templates, [8](#)

parse_response, [8](#)