

Package ‘ellipsis’

June 20, 2019

Version 0.2.0

Title Tools for Working with ...

Description The ellipsis is a powerful tool for extending functions. Unfortunately this power comes at a cost: misspelled arguments will be silently ignored. The ellipsis package provides a collection of functions to catch problems and alert the user.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

URL <https://github.com/r-lib/ellipsis>

BugReports <https://github.com/r-lib/ellipsis/issues>

Depends R (>= 3.1)

Imports rlang (>= 0.3.0)

Suggests covr, testthat

NeedsCompilation yes

Author Hadley Wickham [aut, cre],
RStudio [cph]

Maintainer Hadley Wickham <hadley@rstudio.com>

Repository CRAN

Date/Publication 2019-06-20 14:50:15 UTC

R topics documented:

check_dots_empty	2
check_dots_unnamed	2
check_dots_used	3
safe_median	4

Index	5
--------------	----------

check_dots_empty *Check that dots are unused*

Description

Sometimes you just want to use ... to force your users to fully name the details arguments. This function warns if ... is not empty.

Usage

```
check_dots_empty(env = parent.frame())
```

Arguments

env Environment in which to look for ...

Examples

```
f <- function(x, ..., foofy = 8) {  
  check_dots_empty()  
  x + foofy  
}  
  
try(f(1, foof = 4))  
f(1, foofy = 4)
```

check_dots_unnamed *Check that all dots are unnamed*

Description

Named arguments in ... are often a sign of misspelled argument names.

Usage

```
check_dots_unnamed(env = parent.frame())
```

Arguments

env Environment in which to look for ...

Examples

```
f <- function(..., foofy = 8) {  
  check_dots_unnamed()  
  c(...)  
}
```

```
f(1, 2, 3, foofy = 4)  
try(f(1, 2, 3, foof = 4))
```

check_dots_used	<i>Check that all dots have been used</i>
-----------------	---

Description

Automatically sets exit handler to run when function terminates, checking that all elements of ... have been evaluated. If you use `on.exit()` elsewhere in your function, make sure to use `add = TRUE` so that you don't override the handler set up by `check_dots_used()`.

Usage

```
check_dots_used(env = parent.frame())
```

Arguments

env Environment in which to look for ... and to set up handler.

Examples

```
f <- function(...) {  
  check_dots_used()  
  g(...)  
}
```

```
g <- function(x, y, ...) {  
  x + y  
}  
f(x = 1, y = 2)
```

```
try(f(x = 1, y = 2, z = 3))  
try(f(x = 1, y = 2, 3, 4, 5))
```

safe_median	<i>Safe version of median</i>
-------------	-------------------------------

Description

safe_median() works `stats::median()` but warns if some elements of ... are never used.

Usage

```
safe_median(x, ...)  
  
## S3 method for class 'numeric'  
safe_median(x, ..., na.rm = TRUE)
```

Arguments

x	Numeric vector
...	Additional arguments passed on to methods.
na.rm	For numeric method, should missing values be removed?

Examples

```
x <- c(1:10, NA)  
safe_median(x, na.rm = TRUE)  
median(x, na.rm = TRUE)  
  
try(median(x, na.rm = TRUE))  
try(safe_median(x, na.rm = TRUE))  
  
try(median(1, 2, 3))  
try(safe_median(1, 2, 3))
```

Index

`check_dots_empty`, 2
`check_dots_unnamed`, 2
`check_dots_used`, 3

`on.exit()`, 3

`safe_median`, 4
`stats::median()`, 4