

Package ‘ftrCOOL’

January 19, 2021

Type Package

Title Feature Extraction from Biological Sequences

Version 1.1.2

Author Sare Amerifar

Maintainer Sare Amerifar <sare.ameri.01@gmail.com>

Description Extracts features from biological sequences. It contains most features which are presented in related work and also includes features which have never been introduced before. It extracts numerous features from nucleotide and peptide sequences. Each feature converts the input sequences to discrete numbers in order to use them as predictors in machine learning models. There are many features and information which are hidden inside a sequence. Utilizing the package, users can convert biological sequences to discrete models based on chosen properties. References: 'iLearn' 'Z. Chen et al.' (2019) <DOI:10.1093/bib/bbz041>. 'iFeature' 'Z. Chen et al.' (2018) <DOI:10.1093/bioinformatics/bty140>. <https://CRAN.R-project.org/package=rDNase>. 'PseKRAAC' 'Y. Zuo et al.' 'PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition' (2017) <DOI:10.1093/bioinformatics/btw564>. 'iDNA6mA-PseKNC' 'P. Feng et al.' 'iDNA6mA-PseKNC: Identifying DNA N6-methyladenosine sites by incorporating nucleotide physicochemical properties into PseKNC' (2019) <DOI:10.1016/j.ygeno.2018.01.005>. 'I. Dubchak et al.' 'Prediction of protein folding class using global description of amino acid sequence' (1995) <DOI:10.1073/pnas.92.19.8700>. 'W. Chen et al.' 'Identification and analysis of the N6-methyladenosine in the Saccharomyces cerevisiae transcriptome' (2015) <DOI:10.1038/srep13859>.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Imports stats, utils

Suggests testthat

NeedsCompilation no

Repository CRAN

Date/Publication 2021-01-19 17:00:02 UTC

R topics documented:

AA2Binary	4
AAindex	6
AAKpartComposition	7
AAutoCor	8
alphabetCheck	10
ANF_DNA	11
ANF_RNA	12
APAAC	13
APkNUCdi_DNA	14
APkNUCdi_RNA	15
APkNUCTri_DNA	17
ASA	18
AutoCorDiNUC_DNA	19
AutoCorDiNUC_RNA	21
AutoCorTriNUC_DNA	22
BLOSUM62	24
CkSAApair	25
CkSGAApair	26
CkSNUCpair_DNA	27
CkSNUCpair_RNA	28
codonAdaptionIndex	30
CodonFraction	31
CodonUsage_DNA	31
CodonUsage_RNA	32
conjointTriad	33
conjointTriadKS	34
CTD	35
CTDC	36
CTDD	37
CTDT	37
DDE	38
DiNUC2Binary_DNA	39
DiNUC2Binary_RNA	40
DiNUCindex_DNA	42
DiNUCindex_RNA	43
DisorderB	44
DisorderC	46
DisorderS	47
EAAComposition	48
EffectiveNumberCodon	49
EGAAComposition	50
EIIP	52
ENUComposition_DNA	53
ENUComposition_RNA	54
ExpectedValKmerNUC_DNA	55
ExpectedValKmerNUC_RNA	56

ExpectedValueAA	58
ExpectedValueGAA	58
ExpectedValueGKmerAA	59
ExpectedValueKmerAA	61
fa.read	62
fickettScore	63
GAAKpartComposition	63
GrpDDE	65
G_Ccontent_DNA	66
G_Ccontent_RNA	67
kAAComposition	68
kGAAComposition	69
KNNPeptide	70
KNNProtein	71
kNUComposition_DNA	73
kNUComposition_RNA	74
LocalPoSpKAAF	75
LocalPoSpKNUCF_DNA	76
LocalPoSpKNUCF_RNA	77
maxORF	79
maxORFlength_DNA	80
maxORFlength_RNA	81
maxORF_RNA	81
nameKmer	82
NCP_DNA	83
NCP_RNA	84
needleman	86
nonStandardSeq	87
NUC2Binary_DNA	87
NUC2Binary_RNA	89
NUCKpartComposition_DNA	90
NUCKpartComposition_RNA	91
PCPseDNC	93
PSEAAC	94
PseEIIP	96
PSEkNUCdi_DNA	97
PSEkNUCdi_RNA	98
PSEkNUCTri_DNA	99
PseKRAAC_T1	101
PseKRAAC_T10	102
PseKRAAC_T11	104
PseKRAAC_T12	106
PseKRAAC_T13	107
PseKRAAC_T14	109
PseKRAAC_T15	110
PseKRAAC_T16	112
PseKRAAC_T2	113
PseKRAAC_T3A	115

PseKRAAC_T3B	116
PseKRAAC_T4	118
PseKRAAC_T5	119
PseKRAAC_T6A	121
PseKRAAC_T6B	122
PseKRAAC_T7	124
PseKRAAC_T8	125
PseKRAAC_T9	127
PSSM	128
PSTNPs	129
PSTNPss_DNA	131
PSTNPss_RNA	132
QOrder	133
readASAdir	134
readDisDir	135
readPSSMdir	136
readss2Dir	136
readTorsionDir	137
revComp	138
SAAC	138
SGAAC	139
SOCNumber	140
SSEB	141
SSEC	143
SSES	143
TorsionAngle	144
TriNUCindex_DNA	145
zSCALE	147

Index**149**

AA2Binary

*Amino Acid To Binary (AA2Binary)***Description**

This function transforms an amino acid to a binary format. The type of the binary format is determined by the `binaryType` parameter. For details about each format, please refer to the description of the `binaryType` parameter.

Usage

```
AA2Binary(
  seqs,
  binaryType = "strBin",
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
binaryType	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin'(String binary): each amino acid is represented by a string containing 20 characters(0-1). For example, A = ALANIN = "1000000...0" 'logicBin'(logical value): Each amino acid is represented by a vector containing 20 logical entries. For example, A = ALANIN = c(T,F,F,F,F,F,...F) 'numBin' (numeric bin): Each amino acid is represented by a numeric (i.e., integer) vector containing 20 numerals. For example, A = ALANIN = c(1,0,0,0,0,0,....,0)
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if binaryType is 'strBin', the number of columns is the length of the sequences. Otherwise, it is equal to (length of the sequences)*20. If outFormat is 'txt', all binary values will be written to a the output is written to a tab-delimited file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
mat<-AA2Binary(seqs = ptmSeqsVect, binaryType="strBin",outFormat="mat")
```

AAindex

Amino Acid Index (AAindex)

Description

This function converts the amino acids of a sequence to a list of physicochemical properties in the aaIndex file. For each amino acid, the function uses a numeric vector which shows the aaIndex of the amino acid.

Usage

```
AAindex(  
  seqs,  
  selectedAAidx = 1:554,  
  standardized = TRUE,  
  threshold = 1,  
  label = c(),  
  outFormat = "mat",  
  outputFileDist = ""  
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
selectedAAidx	AAindex function works based on physicochemical properties. Users select the properties by their ids or indexes in aaIndex2 file.
standardized	is a logical parameter. If it is set to TRUE, amino acid indices will be in the standard format. The default value is TRUE.
threshold	is a number between (0 , 1]. In selectedAAidx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Details

In this function each amino acid is converted to a numeric vector. Elements of the vector represent a physicochemical property for the amino acid. In the aaIndex database, there are 554 amino acid indices. Users can choose the desired aaindex by specifying aaindexes through their ids or indexes in the aaIndex file, via selectedAAidx parameter.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length)*(number of selected amino acid indexes) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
mat<-AAindex(seqs = ptmSeqsVect, selectedAAidx=1:5,outFormat="mat")

ad<-paste0(dir,"/aaidx.txt")
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
AAindex(seqs = filePrs, selectedAAidx=1:5,standardized=TRUE,threshold=1,outFormat="txt",
,outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

AAKpartComposition *Amino Acid to K Part Composition (AAKpartComposition)*

Description

In this function, each sequence is divided into k equal partitions. The length of each part is equal to ceiling(l(length of the sequence)/k). The last part can have a different length containing the residual amino acids. The amino acid composition is calculated for each part.

Usage

```
AAKpartComposition(seqs, k = 3, normalized = TRUE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
k	is an integer value. Each sequence should be divided to k partition(s).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

a feature matrix with $k*20$ number of columns. The number of rows is equal to the number of sequences.

Note

Warning: The length of all sequences should be greater than k.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-AAKpartComposition(seqs=filePrs,k=5,normalized=FALSE)
```

AAutoCor

Amino Acid Autocorrelation-Autocovariance (AAutoCor)

Description

It creates the feature matrix for each function in autocorrelation (i.e., Moran, Greay, NormalizeM-Borto) or autocovariance (i.e., AC, CC,ACC). The user can select any combination of the functions too. In this case, the final matrix will contain features of each selected function.

Usage

```
AAutoCor(
  seqs,
  selectedAAidx = list(c("CIDH920105", "BHAR880101", "CHAM820101", "CHAM820102",
    "CHOC760101", "BIGC670101", "CHAM810101", "DAYM780201")),
  maxlag = 3,
  threshold = 1,
  type = c("Moran", "Geary", "NormalizeMBorto", "AC", "CC", "ACC"),
  label = c()
)
```


Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
selectedAAidx	Function takes as input the physicochemical properties. Users select the properties by their ids or indices in the aaIndex2 file. This parameter could be a vector or a list of amino acid indices. The default values of the vector are the 'CIDH920105','BHAR880101','CHAM820101','CHAM820102','CHOC760101','BIGC670101','CHA' ids in the aaIndex2 file.
maxlag	This parameter shows the maximum gap between two amino acids. The gaps change from 1 to maxlag (the maximum lag).
threshold	is a number between (0 , 1]. In selectedAAidx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
type	could be 'Moran', 'Greay', 'NormalizeMBorto', 'AC', 'CC', or 'ACC'. Also, it could be any combination of them.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

For CC and AAC autocovariance functions, which consider the covariance of the two physicochemical properties, we have provided users with the ability to categorize their selected properties in a list. The binary combination of each group will be taken into account. Note: If all the features are in a group or selectedAAidx parameter is a vector, the binary combination will be calculated for all the physicochemical properties.

Value

This function returns a feature matrix. The number of columns in the matrix changes depending on the chosen autocorrelation or autocovariance types and nlag parameter. The output is a matrix. The number of rows shows the number of sequences.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-AAutoCor(seqs=filePrs,maxlag=20,threshold=0.9,
type=c("Moran","Geary","NormalizeMBorto","AC"))

mat2<-AAutoCor(seqs=filePrs,maxlag=20,threshold=0.9,selectedAAidx=
list(c('CIDH920105','BHAR880101','CHAM820101','CHAM820102'),c('CHOC760101','BIGC670101')
,c('CHAM810101','DAYM780201')),type=c("AC","CC","ACC"))
```

`alphabetCheck`*AlphabetCheck*

Description

This function checks the alphabets in a sequence. If one of the following conditions hold, the sequence will be deleted: 1. A peptide sequence containing non-standard amino acids, 2. A DNA sequence with an alphabet other than A, C, G, or T, 3. An RNA sequence having an alphabet other than A, C, G, or U.

Usage

```
alphabetCheck(sequences, alphabet = "aa", label = c())
```

Arguments

<code>sequences</code>	is a string vector. Each element is a peptide, protein, DNA, or RNA sequences.
<code>alphabet</code>	This parameter shows the alphabet of sequences. If it is set to 'aa', it indicates the alphabet of amino acids. When it is 'dna', it shows the nucleotide alphabet and in case it equals 'rna', it represents ribonucleotide alphabet.
<code>label</code>	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

'alphabetCheck' returns a list with two elements. The first element is a vector which contains valid sequences. The second element is a vector which contains the labels of the sequences (if any exists).

Note

This function receives a sequence vector and the label of sequences (if any). It deletes sequences (and their labels) containing non-standard alphabets.

Examples

```
seq<-alphabetCheck(sequences=c("AGDFLIAACNMLKIVYT","ADXVGAIJK"),alphabet="aa")
```

ANF_DNA	<i>Accumulated Nucleotide Frequency (ANF_DNA)</i>
---------	---

Description

This function replaces nucleotides with a four-length vector. The first three elements represent the nucleotides and the fourth holds the frequency of the nucleotide from the beginning of the sequence until the position of the nucleotide in the sequence. 'A' will be replaced with $c(1, 1, 1, \text{freq})$, 'C' with $c(0, 1, 0, \text{freq})$, 'G' with $c(1, 0, 0, \text{freq})$, and 'T' with $c(0, 0, 1, \text{freq})$.

Usage

```
ANF_DNA(seqs, outFormat = "mat", outputFileDist = "", label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length)*4 and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

References

Chen, W., Tran, H., Liang, Z. et al. Identification and analysis of the N6-methyladenosine in the *Saccharomyces cerevisiae* transcriptome. *Sci Rep* 5, 13859 (2015).

Examples

```
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-ANF_DNA(seqs = LNC50Nuc,outFormat="mat")
```

ANF_RNA

Accumulated riboNucleotide Frequency (ANF_RNA)

Description

This function replaces ribonucleotides with a four-length vector. The first three elements represent the ribonucleotides and the fourth holds the frequency of the ribonucleotide from the beginning of the sequence until the position of the ribonucleotide in the sequence. 'A' will be replaced with $c(1, 1, 1, \text{freq})$, 'C' with $c(0, 1, 0, \text{freq})$, 'G' with $c(1, 0, 0, \text{freq})$, and 'U' with $c(0, 0, 1, \text{freq})$.

Usage

```
ANF_RNA(seqs, outFormat = "mat", outputFileDist = "", label = c())
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length)*(4) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

References

Chen, W., Tran, H., Liang, Z. et al. Identification and analysis of the N6-methyladenosine in the *Saccharomyces cerevisiae* transcriptome. *Sci Rep* 5, 13859 (2015).

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-ANF_RNA(seqs = fileLNC,outFormat="mat")
```

APAAC

Amphiphilic Pseudo-Amino Acid Composition(series) (APAAC)

Description

This function calculates the amphiphilic pseudo amino acid composition (Series) for each sequence.

Usage

```
APAAC(
  seqs,
  aaIDX = c("ARGP820101", "HOPT810101"),
  lambda = 30,
  w = 0.05,
  l = 1,
  threshold = 1,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
aaIDX	is a vector of Ids or indexes of the user-selected physicochemical properties in the aaIndex2 database. The default values of the vector are the hydrophobicity ids and hydrophilicity ids in the amino acid index file.
lambda	is a tuning parameter. Its value indicates the maximum number of spaces between di-nucleotide pairs. The number changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in from 0 to 1. The default value is 0.05.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 20 ^l elements of the APAAC descriptor.
threshold	is a number between (0, 1]. In aaIDX, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo amino acid composition for each physicochemical property. We have provided users with the ability to choose among different properties (i.e., not confined to hydrophobicity or hydrophilicity).

Value

A feature matrix such that the number of columns is $20^{l+1}+(\text{number of chosen aaIndex}*\lambda)$ and the number of rows equals the number of sequences.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-APAAC(seqs=filePrs,l=2,lambda=3,threshold=1)
```

APkNUCdi_DNA	<i>Amphiphilic Pseudo-k Nucleotide Composition-di(series) (AP-kNUCdi_DNA)</i>
--------------	---

Description

This function calculates the amphiphilic pseudo k nucleotide composition(Di) (Series) for each sequence.

Usage

```
APkNUCdi_DNA(
  seqs,
  selectedIdx = c("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist"),
  lambda = 3,
  w = 0.05,
  l = 2,
  ORF = FALSE,
  reverseORF = TRUE,
  threshold = 1,
  label = c()
)
```

Arguments

`seqs` is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, `seqs` could be a string vector. Each element of the vector is a nucleotide sequence.

selectedIdx	is a vector of Ids or indices of the desired physicochemical properties of dinucleotides. Users can choose the desired indices by their ids or their names in the DI_DNA index file. The default value of this parameter is a vector with ("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist") ids.
lambda	is a tuning parameter. This integer value shows the maximum limit of spaces between dinucleotide pairs. The Number of spaces changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in the range of 0 to 1. The default value is 0.05.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 4^l elements of the APkNCdi descriptor.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
threshold	is a number between (0 to 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo nucleotide composition for each physicochemical property of dinucleotides. We have provided users with the ability to choose among the 148 properties in the di-nucleotide index database.

Value

It is a feature matrix. The number of columns is $4^l + (\text{number of the chosen indices} * \text{lambda})$ and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-APkNUCdi_DNA(seqs=fileLNC,ORF=TRUE,threshold=1)
```

APkNUCdi_RNA	<i>Amphiphilic Pseudo-k riboNucleotide Composition-di(series) (AP-kNUCdi_RNA)</i>
--------------	---

Description

This function calculates the amphiphilic pseudo k ribonucleotide composition(Di) (Series) for each sequence.

Usage

```

APkNUCdi_RNA(
  seqs,
  selectedIdx = c("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)",
    "Tilt (RNA)", "Twist (RNA)"),
  lambda = 3,
  w = 0.05,
  l = 2,
  ORF = FALSE,
  reverseORF = TRUE,
  threshold = 1,
  label = c()
)

```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
selectedIdx	is a vector of Ids or indices of the desired physicochemical properties of di-ribonucleotides. Users can choose the desired indices by their ids or their names in the DI_RNA index file. The default value of this parameter is a vector with ("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)", "Tilt (RNA)", "Twist (RNA)") ids.
lambda	is a tuning parameter. This integer value shows the maximum limit of spaces between di-ribonucleotide pairs. The Number of spaces changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in the range of 0 to 1. The default value is 0.05.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 4^l elements of the APkNCdi descriptor.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
threshold	is a number between (0 to 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo ribonucleotide composition for each physicochemical property of di-ribonucleotides. We have provided users with the ability to choose among the 22 properties in the di-ribonucleotide index database.

Value

It is a feature matrix. The number of columns is $4^{\lambda} + (\text{number of the chosen indices} * \lambda)$ and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-APkNUCdi_RNA(seqs=fileLNC,ORF=TRUE,threshold=0.8)
```

APkNUCTri_DNA	<i>Amphiphilic Pseudo-k Nucleotide Composition-Tri(series) (APkNUC-Tri_DNA)</i>
---------------	---

Description

This function calculates the amphiphilic pseudo k nucleotide composition(Tri) (Series) for each sequence.

Usage

```
APkNUCTri_DNA(
  seqs,
  selectedIdx = c("Dnase I", "Bendability (DNase)"),
  lambda = 3,
  w = 0.05,
  l = 3,
  ORF = FALSE,
  reverseORF = TRUE,
  threshold = 1,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
selectedIdx	is a vector of Ids or indices of the desired physicochemical properties of trinucleotides. Users can choose the desired indices by their ids or their names in the TRI_DNA index file. The default value of the parameter is a vector with ("Dnase I", "Bendability (DNase)") ids.
lambda	is a tuning parameter. This integer value shows the maximum limit of spaces between trinucleotide pairs. The Number of spaces changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in the range of 0 to 1. The default value is 0.05.

l	This parameter keeps the value of l in lmer composition. The lmers form the first 4^l of the APkNCTri descriptor.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
threshold	is a number between (0 , 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo nucleotide composition for each physicochemical property of trinucleotides. We have provided users with the ability to choose among the 12 properties in the tri-nucleotide index database.

Value

It is a feature matrix. The number of columns is $4^l + (\text{number of the chosen indices} * \text{lambda})$ and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-APkNUCTri_DNA(seqs=fileLNC,l=3,threshold=1)
```

ASA

Accessible Solvent Accessibility (ASA)

Description

ASA represents an amino acid by a numeric value. This function extracts the ASA from the output of SPINE-X software which predicts ASA for each amino acid in a peptide or protein sequence. The output of SPINE-X is a tab-delimited file. ASAs are in the 11th column of the file.

Usage

```
ASA(dirPath, outFormat = "mat", outputFileDist = "")
```

Arguments

- `dirPath` Path of the directory which contains all output files of SPINE-X. Each file belongs to a sequence.
- `outFormat` It can take two values: 'mat' (which stands for matrix) and 'txt'. The default value is 'mat'.
- `outputFileDist` It shows the path and name of the 'txt' output file.

Value

The output depends on the `outFormat` which can be either 'mat' or 'txt'. If `outFormat` is 'mat', the function returns a feature matrix for sequences with the same lengths such that the number of columns is equal to the length of the sequences and the number of rows is equal to the number of sequences. If the `outFormat` is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in `outFormat` for sequences with different lengths. Warning: If `outFormat` is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
ad<-paste0(dir,"/asa.txt")

PredASAdir<-system.file("testFolder",package="ftrCOOL")
PredASAdir<-paste0(PredASAdir,"/ASAdir/")
ASA(PredASAdir,outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

AutoCorDiNUC_DNA	<i>Di Nucleotide</i>	<i>Autocorrelation-Autocovariance</i>	<i>(Auto-</i>
	<i>CorDiNUC_DNA)</i>		

Description

It creates the feature matrix for each function in autocorrelation (i.e., Moran, Greay, NormalizeM-Borto) or autocovariance (i.e., AC, CC, ACC). The user can select any combination of the functions too. In this case, the final matrix will contain features of each selected function.

Usage

```
AutoCorDiNUC_DNA(
  seqs,
  selectedIdx = c("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist"),
  maxlag = 3,
  threshold = 1,
  type = c("Moran", "Geary", "NormalizeMBorto", "AC", "CC", "ACC"),
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
selectedIdx	function takes as input the physicochemical properties. Users select the properties by their ids or indices in the DI_DNA file. This parameter could be a vector or a list of dinucleotide indices. The default value of this parameter is a vector with ("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist") ids.
maxlag	This parameter shows the maximum gap between two amino acids. The gaps change from 1 to maxlag (the maximum lag).
threshold	is a number between (0 to 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
type	could be 'Moran', 'Geary', 'NormalizeMBorto', 'AC', 'CC', or 'ACC'. Also, it could be any combination of them.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

For CC and AAC autocovariance functions, which consider the covariance of the two physicochemical properties, we have provided users with the ability to categorize their selected properties in a list. The binary combination of each group will be taken into account. Note: If all the features are in a group or selectedAAidx parameter is a vector, the binary combination will be calculated for all the physicochemical properties.

Value

This function returns a feature matrix. The number of columns in the matrix changes depending on the chosen autocorrelation or autocovariance types and nlag parameter. The output is a matrix. The number of rows shows the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat1<-AutoCorDiNUC_DNA(seqs=fileLNC,selectedIdx=c(1:7)
,maxlag=20,type=c("Moran","Geary"))
```

```
mat2<-AutoCorDiNUC_DNA(seqs=fileLNC,selectedIdx=list(10,c(1,3),6:13,c(2:7))
,maxlag=15,type="CC")
```

AutoCorDiNUC_RNA	<i>Di riboNucleotide</i>	<i>Autocorrelation-Autocovariance</i>	<i>(Auto-CorDiNUC_RNA)</i>
------------------	--------------------------	---------------------------------------	----------------------------

Description

It creates the feature matrix for each function in autocorrelation (i.e., Moran, Greay, NormalizeM-Borto) or autocovariance (i.e., AC, CC,ACC). The user can select any combination of the functions too. In this case, the final matrix will contain features of each selected function.

Usage

```
AutoCorDiNUC_RNA(
  seqs,
  selectedIdx = c("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)",
    "Tilt (RNA)", "Twist (RNA)"),
  maxlag = 3,
  threshold = 1,
  type = c("Moran", "Geary", "NormalizeMBorto", "AC", "CC", "ACC"),
  label = c()
)
```

Arguments

seqs	is a FASTA file containing ribonucleic acid(RNA) sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a RNA sequence.
selectedIdx	function takes as input the physicochemical properties. Users select the properties by their ids or indices in the DI_RNA file. This parameter could be a vector or a list of di-ribonucleic acid indices. The default value of this parameter is a vector with ("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)", "Tilt (RNA)", "Twist (RNA)") ids.
maxlag	This parameter shows the maximum gap between two amino acids. The gaps change from 1 to maxlag (the maximum lag).
threshold	is a number between (0 to 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted.The default value is 1.
type	could be 'Moran', 'Greay', 'NormalizeMBorto', 'AC', 'CC', or 'ACC'. Also, it could be any combination of them.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

For CC and AAC autocovariance functions, which consider the covariance of the two physicochemical properties, we have provided users with the ability to categorize their selected properties in a list. The binary combination of each group will be taken into account. Note: If all the features are in a group or selectedAAidx parameter is a vector, the binary combination will be calculated for all the physicochemical properties.

Value

This function returns a feature matrix. The number of columns in the matrix changes depending on the chosen autocorrelation or autocovariance types and nlag parameter. The output is a matrix. The number of rows shows the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
fileLNC<-fa.read(fileLNC,alphabet="rna")
fileLNC<-fileLNC[1:20]
mat1<-AutoCorDiNUC_RNA(seqs=fileLNC,maxlag=20,type=c("Moran","Geary"))
```

AutoCorTriNUC_DNA	<i>Tri Nucleotide</i>	<i>Autocorrelation-Autocovariance</i>	<i>(AutoCorTriNUC_DNA)</i>
-------------------	-----------------------	---------------------------------------	----------------------------

Description

It creates the feature matrix for each function in autocorelation (i.e., Moran, Greay, NormalizeM-Borto) or autocovariance (i.e., AC, CC,ACC). The user can select any combination of the functions too. In this case, the final matrix will contain features of each selected function.

Usage

```
AutoCorTriNUC_DNA(
  seqs,
  selectedNucIdx = c("Dnase I", "Bendability (DNase)"),
  maxlag = 3,
  threshold = 1,
  type = c("Moran", "Geary", "NormalizeMBorto", "AC", "CC", "ACC"),
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
selectedNucIdx	function takes as input the physicochemical properties. Users select the properties by their ids or indices in the TRI_DNA file. This parameter could be a vector or a list of trinucleotide indices. The default value of this parameter is a vector with ("Dnase I", "Bendability (DNase)") ids.
maxlag	This parameter shows the maximum gap between two amino acids. The gaps change from 1 to maxlag (the maximum lag).
threshold	is a number between (0 to 1]. In selectedNucIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
type	could be 'Moran', 'Geary', 'NormalizeMBorto', 'AC', 'CC', or 'ACC'. Also, it could be any combination of them.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

For CC and AAC autocovariance functions, which consider the covariance of the two physicochemical properties, we have provided users with the ability to categorize their selected properties in a list. The binary combination of each group will be taken into account. Note: If all the features are in a group or selectedAAidx parameter is a vector, the binary combination will be calculated for all the physicochemical properties.

Value

This function returns a feature matrix. The number of columns in the matrix changes depending on the chosen autocorrelation or autocovariance types and nlag parameter. The output is a matrix. The number of rows shows the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat1<-AutoCorTriNUC_DNA(seqs=fileLNC,selectedNucIdx=c(1:7),maxlag=20,type=c("Moran","Geary"))

mat2<-AutoCorTriNUC_DNA(seqs=fileLNC,selectedNucIdx=list(c(1,3),6:10,c(2:7)),
maxlag=15,type=c("AC","CC"))
```

BLOSUM62

Blosum62 (BLOSUM62)

Description

This function creates a 20-dimensional numeric vector for each amino acid of a sequence. Each entry of the vector contains the similarity score of the amino acid with other amino acids including itself. The score is extracted from the Blosum62 matrix.

Usage

```
BLOSUM62(seqs, label = c(), outFormat = "mat", outputFileDist = "")
```

Arguments

<code>seqs</code>	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, <code>seqs</code> could be a string vector. Each element of the vector is a peptide/protein sequence.
<code>label</code>	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
<code>outFormat</code>	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
<code>outputFileDist</code>	shows the path and name of the 'txt' output file.

Value

The output depends on the `outFormat` parameter which can be either 'mat' or 'txt'. If `outFormat` is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length)*20 and the number of rows is equal to the number of sequences. If the `outFormat` is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in `outFormat` for sequences with different lengths. Warning: If `outFormat` is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
filePr<-system.file("extdata/protein.fasta",package="ftrCOOL")
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
```



```
ad<-paste0(dir,"/blosum62.txt")
vect<-BLOSUM62(seqs = filePr,outFormat="mat")
BLOSUM62(seqs = filePrs,outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

CkSAApair

Composition of k-Spaced Amino Acids pairs (CkSAApair)

Description

This function calculates the composition of k-spaced amino acid pairs. In other words, it computes the frequency of all amino acid pairs with k spaces.

Usage

```
CkSAApair(seqs, rng = 3, upto = FALSE, normalized = TRUE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
rng	This parameter can be a number or a vector. Each element of the vector shows the number of spaces between amino acid pairs. For each k in the rng vector, a new vector (whose size is 400) is created which contains the frequency of pairs with k gaps.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from [0 to rng].
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is 400*(length of rng vector).

Note

'upto' is enabled only when rng is a number and not a vector.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-CkSAApair(seqs=filePrs,rng=2,upto=TRUE,normalized=TRUE)

mat2<-CkSAApair(seqs=filePrs,rng=c(1,3,5))
```

CkSGAApair

Composition of k-Spaced Grouped Amino Acids pairs (CkSGAApair)

Description

In this function, amino acids are first grouped into a category which is defined by the user. Later, the composition of the k-spaced grouped amino acids is computed. Please note that this function differs from [CkSAApair](#) which works on individual amino acids.

Usage

```
CkSGAApair(
  seqs,
  rng = 3,
  upto = FALSE,
  normalized = TRUE,
  Grp = "locFus",
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
rng	This parameter can be a number or a vector. Each element of the vector shows the number of spaces between amino acid pairs. For each k in the rng vector, a new vector (whose size is (number of categorizes) ²) is created which contains the frequency of pairs with k gaps.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from [0 to rng].
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
Grp	is a list of vectors containig amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.

label is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Column names in the feature matrix follow G(?ss?). For example, G(1ss2) means Group1**Group2, where '**' is a wild character.

Value

This function returns a feature matrix. Row length is equal to the number of sequences and the number of columns is $((\text{number of categorizes})^2) * (\text{length of rng vector})$.

Note

'upto' is enabled only when rng is a number and not a vector.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-CkSGAApair(seqs=filePrs,rng=2,upto=TRUE,Grp="aromatic")

mat2<-CkSGAApair(seqs=filePrs,rng=c(1,3,5),upto=FALSE,Grp=
list(Grp1=c("G","A","V","L","M","I","F","Y","W"),Grp2=c("K","R","H","D","E")
,Grp3=c("S","T","C","P","N","Q")))
```

CkSNUCpair_DNA

Composition of k-Spaced Nucleotides Pairs (CkSNUCpair_DNA)

Description

This function calculates the composition of k-spaced nucleotide pairs. In other words, it computes the frequency of all nucleotide pairs with k spaces.

Usage

```
CkSNUCpair_DNA(
  seqs,
  rng = 3,
  upto = FALSE,
  ORF = FALSE,
  reverseORF = TRUE,
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
rng	This parameter can be a number or a vector. Each element of the vector shows the number of spaces between nucleotide pairs. For each k in the rng vector, a new vector (whose size is 16) is created which contains the frequency of pairs with k gaps.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from [0 to rng].
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $16^{*(\text{length of rng vector})}$.

Note

'upto' is enabled only when rng is a number and not a vector.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat1<-CkSNUCpair_DNA(seqs=fileLNC,rng=2,upto=TRUE,ORF=TRUE,reverseORF=FALSE)
mat2<-CkSNUCpair_DNA(seqs=fileLNC,rng=c(1,3,5))
```

CkSNUCpair_RNA

Composition of k-Spaced riboNucleotides Pairs (CkSNUCpair_RNA)

Description

This function calculates the composition of k-spaced nucleotide pairs. In other words, it computes the frequency of all nucleotide pairs with k spaces.

Usage

```
CkSNUCpair_RNA(
  seqs,
  rng = 3,
  upto = FALSE,
  ORF = FALSE,
  reverseORF = TRUE,
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
rng	This parameter can be a number or a vector. Each element of the vector shows the number of spaces between ribonucleotide pairs. For each k in the rng vector, a new vector (whose size is 16) is created which contains the frequency of pairs with k gaps.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from [0 to rng].
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $16 * (\text{length of rng vector})$.

Note

'upto' is enabled only when rng is a number and not a vector.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
```

```
mat1<-CkSNUCpair_RNA(seqs=fileLNC, rng=2, upto=TRUE, ORF=TRUE, reverseORF=FALSE)
mat2<-CkSNUCpair_RNA(seqs=fileLNC, rng=c(1,3,5))
```

codonAdaptionIndex *Codon Adaption Index (codonAdaptionIndex)*

Description

This function calculates the codon adaption index for each sequence.

Usage

```
codonAdaptionIndex(seqs, ORF = FALSE, reverseORF = TRUE, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature vector. The length of the vector is equal to the number of sequences. Each entry in the vector contains the value of the codon adaption index.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa", package="ftrCOOL")
mat<-codonAdaptionIndex(seqs=fileLNC, ORF=TRUE, reverseORF=FALSE)
```

CodonFraction	<i>Codon Fraction (CodonFraction)</i>
---------------	---------------------------------------

Description

This function calculates the codon fraction for each sequence.

Usage

```
CodonFraction(seqs, ORF = FALSE, reverseORF = TRUE, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A feature matrix such that the number of columns is 4^3 and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-CodonFraction(seqs=fileLNC,ORF=TRUE,reverseORF=FALSE)
```

CodonUsage_DNA	<i>Codon Usage in DNA (CodonUsage_DNA)</i>
----------------	--

Description

This function calculates the codon usage for each sequence.

Usage

```
CodonUsage_DNA(seqs, ORF = FALSE, reverseORF = TRUE, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A feature matrix such that the number of columns is 4^3 and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-CodonUsage_DNA(fileLNC,ORF=TRUE,reverseORF=FALSE)
```

CodonUsage_RNA

Codon Usage in RNA (CodonUsage_RNA)

Description

This function calculates the codon usage for each sequence.

Usage

```
CodonUsage_RNA(seqs, ORF = FALSE, reverseORF = TRUE, label = c())
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A feature matrix such that the number of columns is 4^3 and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-CodonUsage_RNA(seqs=fileLNC,ORF=TRUE,reverseORF=FALSE)
```

conjointTriad	<i>Conjoint Triad (conjointTriad)</i>
---------------	---------------------------------------

Description

This function calculates the grouped tripeptide composition with the conjoint triad grouping type.

Usage

```
conjointTriad(seqs, normalized = TRUE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows equals to the number of sequences and the number of columns is 7^3 .

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-conjointTriad(seqs=filePrs)
```

conjointTriadKS *k-Spaced Conjoint Triad (conjointTriadKS)*

Description

This function calculates the grouped tripeptide composition with conjoint triad grouping type. For each k , it creates a 7^3 feature vector. K is the space between the first and the second amino acids and the second and the third amino acids of the tripeptide.

Usage

```
conjointTriadKS(seqs, rng = 3, upto = FALSE, normalized = FALSE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
rng	This parameter can be a number or a vector. Each element of the vector shows the number of spaces between the first and the second amino acids and the second and the third amino acids of the tripeptide. For each k in the rng vector, a new vector (whose size is 7^3) is created which contains the frequency of trinucleotide with k gaps.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from 0 to rng.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

A tripeptide with k spaces looks like AA1(ss..s)AA2(ss..s)AA3. AA stands for amino acids and s means space.

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(7^3) * (\text{length rng vector})$.

Note

'upto' is enabled only when rng is a number and not a vector.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-conjointTriadKS(filePrs,rng=2,upto=TRUE,normalized=TRUE)

mat2<-conjointTriadKS(filePrs,rng=c(1,3,5))
```

CTD

Composition_Transition_Distribution (CTD)

Description

This function calculates the composition, transition, and distribution for each sequence.

Usage

```
CTD(seqs, normalized = FALSE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

Output is a combination of three different matrices: Composition, Transition, and Distribution. You can obtain any of the three matrices by executing the corresponding function, i.e., [CTDC](#), [CTDT](#), and [CTDD](#).

References

Dubchak, Inna, et al. "Prediction of protein folding class using global description of amino acid sequence." Proceedings of the National Academy of Sciences 92.19 (1995): 8700-8704.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
CTDtotal<-CTD(seqs=filePrs,normalized=FALSE)
```

CTDC

CTD Composition (CTDC)

Description

This function computes the composition part of [CTD](#). Thirteen properties are defined in this function. Each property categorizes the amino acids of the sequences into three groups. The grouped amino acid composition is calculated for each property. For more information, please check the references.

Usage

```
CTDC(seqs, normalized = FALSE, label = c())
```

Arguments

<code>seqs</code>	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, <code>seqs</code> could be a string vector. Each element of the vector is a peptide/protein sequence.
<code>normalized</code>	is a logical parameter. When it is <code>FALSE</code> , the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
<code>label</code>	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is 3*7, where three is the number of groups and thirteen is the number of properties.

References

Dubchak, Inna, et al. "Prediction of protein folding class using global description of amino acid sequence." *Proceedings of the National Academy of Sciences* 92.19 (1995): 8700-8704.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
CTD_C<-CTDC(seqs=filePrs,normalized=FALSE,label=c())
```

CTDD	<i>CTD Distribution (CTDD)</i>
------	--------------------------------

Description

This function computes the distribution part of [CTD](#). It calculates fifteen values for each property. For more information, please check the references.

Usage

```
CTDD(seqs, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is 15*7.

References

Dubchak, Inna, et al. "Prediction of protein folding class using global description of amino acid sequence." Proceedings of the National Academy of Sciences 92.19 (1995): 8700-8704.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
CTD_D<-CTDD(seqs=filePrs)
```

CTDT	<i>CTD Transition (CTDT)</i>
------	------------------------------

Description

This function computes the transition part of [CTD](#). Thirteen properties are defined in this function. Each property categorizes the amino acids of a sequence into three groups. For each property, the grouped amino acid transition (i.e., transitions 1-2, 1-3, and 2-3) is calculated. For more information, please check the references.

Usage

```
CTDT(seqs, normalized = FALSE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is 3*7, where three is the number of transition types (i.e., 1-2, 1-3, and 2-3) and thirteen is the number of properties.

References

Dubchak, Inna, et al. "Prediction of protein folding class using global description of amino acid sequence." *Proceedings of the National Academy of Sciences* 92.19 (1995): 8700-8704.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
CTD_T<-CTDT(seqs=filePrs,normalized=FALSE)
```

DDE

Dipeptide Deviation from Expected Mean value (DDE)

Description

This function computes the dipeptide deviation from the expected mean value.

Usage

```
DDE(seqs, label = c())
```

Arguments

- `seqs` is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, `seqs` could be a string vector. Each element of the vector is a peptide/protein sequence.
- `label` is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A feature matrix with $20^2=400$ number of columns. The number of rows is equal to the number of sequences.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-DDE(seqs=filePrs)
```

DiNUC2Binary_DNA

Dinucleotide To Binary DNA (DiNUC2Binary_DNA)

Description

This function transforms a dinucleotide to a binary number with four bits which is enough to represent all the possible types of dinucleotides. The type of the binary format is determined by the `binaryType` parameter. For details about each format, please refer to the description of the `binaryType` parameter.

Usage

```
DiNUC2Binary_DNA(
  seqs,
  binaryType = "strBin",
  outFormat = "mat",
  outputFileDist = "",
  label = c()
)
```

Arguments

- `seqs` is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, `seqs` could be a string vector. Each element of the vector is a nucleotide sequence.

binaryType	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin' (String binary): each dinucleotide is represented by a string containing 4 characters(0-1). For example, AA = "0000" AC="0001" ... TT="1111" 'logicBin' (logical value): Each amino acid is represented by a vector containing 4 logical entries. For example, AA = c(F,F,F,F) AC=c(F,F,F,T) ... TT=c(T,T,T,T) 'numBin' (numeric bin): Each amino acid is represented by a numeric (i.e., integer) vector containing 4 numeric entries. For example, AA = c(0,0,0,0) AC = c(0,0,0,1) ... TT = c(1,1,1,1)
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if binaryType is 'strBin', the number of columns is the (length of the sequences-1). Otherwise, it is equal to (length of the sequences-1)*4. If outFormat is 'txt', all binary values will be written to a tab-delimited file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-DiNUC2Binary_DNA(seqs = LNC50Nuc, binaryType="strBin",outFormat="mat")
```

DiNUC2Binary_RNA

Di riboNucleotide To Binary RNA (DiNUC2Binary_RNA)

Description

This function transforms a di-ribonucleotide to a binary number with four bits which is enough to represent all the possible types of di-ribonucleotides. The type of the binary format is determined by the binaryType parameter. For details about each format, please refer to the description of the binaryType parameter.

Usage

```
DiNUC2Binary_RNA(
  seqs,
  binaryType = "strBin",
  outFormat = "mat",
  outputFileDist = "",
  label = c()
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
binaryType	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin' (String binary): each di-ribonucleotide is represented by a string containing 4 characters(0-1). For example, AA = "0000" AC="0001" ... TT="1111" 'logicBin' (logical value): Each amino acid is represented by a vector containing 4 logical entries. For example, AA = c(F,F,F,F) AC=c(F,F,F,T) ... TT=c(T,T,T,T) 'numBin' (numeric bin): Each amino acid is represented by a numeric (i.e., integer) vector containing 4 numeric entries. For example, AA = c(0,0,0,0) AC = c(0,0,0,1) ... TT = c(1,1,1,1)
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if binaryType is 'strBin', the number of columns is (length of the sequences-1). Otherwise, it is equal to (length of the sequences-1)*4. If outFormat is 'txt', all binary values will be written to a 'txt' file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-DiNUC2Binary_RNA(seqs = fileLNC, binaryType="strBin",outFormat="mat")
```

DiNUCindex_DNA

Di Nucleotide Index (DiNUCindex_DNA)

Description

This function replaces dinucleotides in a sequence with their physicochemical properties in the dinucleotide index file.

Usage

```
DiNUCindex_DNA(
  seqs,
  selectedIdx = c("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist"),
  threshold = 1,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
selectedIdx	DiNUCindex_DNA function works based on physicochemical properties. Users, select the properties by their ids or indexes in DI_DNA index file. The default value of this parameter is a vector with ("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist") entries.
threshold	is a number between (0 , 1]. In selectedAAidx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Details

There are 148 physicochemical indexes in the dinucleotide database.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length-1)*(number of selected di-nucleotide indexes) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
fileLNC<-system.file("extdata/Athaliana1.fa",package="ftrCOOL")
vect<-DiNUCindex_DNA(seqs = fileLNC,outFormat="mat")
```

 DiNUCindex_RNA

Di riboNucleotide Index (DiNUCindex_RNA)

Description

This function replaces di ribonucleotides in a sequence with their physicochemical properties in the dinucleotide index file.

Usage

```
DiNUCindex_RNA(
  seqs,
  selectedIdx = c("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)",
    "Tilt (RNA)", "Twist (RNA)"),
  threshold = 1,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.

selectedIdx	DiNucIndex function works based on physicochemical properties. Users, select the properties by their ids or indexes in DI_RNA file. The default value of this parameter is a vector with ("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)", "Tilt (RNA)", "Twist (RNA)") entries.
threshold	is a number between (0 , 1]. In selectedAAidx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Details

There are 22 physicochemical indexes in the dinucleotide database.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length-1)*(number of selected di-nucleotide indexes) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
vect<-DiNUCindex_RNA(seqs = fileLNC,outFormat="mat")
```

DisorderB

disorder Binary (DisorderB)

Description

This function extracts the ordered and disordered amino acids in protein or peptide sequences. The input to the function is provided by VSL2 software. Also, the function converts order amino acids to '10' and disorder amino acids to '01'.

Usage

```
DisorderB(
  dirPath,
  binaryType = "strBin",
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

<code>dirPath</code>	Path of the directory which contains all output files of VSL2. Each file belongs to a sequence.
<code>binaryType</code>	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin' (String binary): each dinucleotide is represented by a string containing 2 characters(0-1). <code>order = "10" disorder="01"</code> . 'logicBin' (logical value): Each amino acid is represented by a vector containing 2 logical entries. <code>order = c(TRUE,FALSE) disorder=c(FALSE,TRUE)</code> . 'numBin' (numeric bin): Each amino acid is represented by a numeric (i.e., integer) vector containing 2 numeric entries. <code>order = c(1,0) disorder=c(0,1)</code> .
<code>outFormat</code>	It can take two values: 'mat' (which stands for matrix) and 'txt'. The default value is 'mat'.
<code>outputFileDist</code>	It shows the path and name of the 'txt' output file.

Value

The output is different depending on the `outFormat` parameter ('mat' or 'txt'). If `outFormat` is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if `binaryType` is 'strBin', the number of columns is the length of the sequences. Otherwise, it is equal to (length of the sequences)*2. If `outFormat` is 'txt', all binary values will be written to a tab-delimited file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in `outFormat` for sequences with different lengths. Warning: If `outFormat` is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()

PredDisdir<-system.file("testForder",package="ftrCOOL")
PredDisdir<-paste0(PredDisdir,"/Disdir/")
ad1<-paste0(dir,"/disorderB.txt")
```

```
DisorderB(PredDisdir,binaryType="strBin",outFormat="txt",outputFileDist=ad1)

unlink("dir", recursive = TRUE)
```

DisorderC

disorder Content (DisorderC)

Description

This function extracts ordered and disordered amino acids in protein or peptide sequences. The input to the function is provided by VSL2 software. Also, the function returns number of order and disorder amino acids in the sequence.

Usage

```
DisorderC(dirPath)
```

Arguments

dirPath	Path of the directory which contains all output files of VSL2. Each file belongs to a sequence.
---------	---

Value

The output is a feature matrix with 2 columns. The number of rows is equal to the number of sequences.

Examples

```
dir = tempdir()
PredDisdir<-system.file("testForder",package="ftrCOOL")
PredDisdir<-paste0(PredDisdir,"/Disdir/")

mat<-DisorderC(PredDisdir)
```

DisorderS

disorder Simple (DisorderS)

Description

This function extracts ordered and disordered amino acids in protein or peptide sequences. The input to the function is provided by VSL2 software. The function represent order amino acids by 'O' and disorder amino acids by 'D'.

Usage

```
DisorderS(dirPath, outFormat = "mat", outputFileDist = "")
```

Arguments

dirPath	Path of the directory which contains all output files of VSL2. Each file belongs to a sequence.
outFormat	It can take two values: 'mat' (which stands for matrix) and 'txt'. The default value is 'mat'.
outputFileDist	It shows the path and name of the 'txt' output file.

Value

The output depends on the outFormat which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same lengths such that the number of columns is equal to the length of the sequences and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()

PredDisdir<-system.file("testForder",package="ftrCOOL")
PredDisdir<-paste0(PredDisdir,"/Disdir/")
ad1<-paste0(dir,"/disorderS.txt")

DisorderS(PredDisdir, outFormat="txt",outputFileDist=ad1)

unlink("dir", recursive = TRUE)
```

EAAComposition	<i>Enhanced Amino Acid Composition (EAAComposition)</i>
----------------	---

Description

This function slides a window over the input sequence(s). Also, it computes the composition of amino acids that appears within the limits of the window.

Usage

```
EAAComposition(
  seqs,
  winSize = 50,
  overLap = TRUE,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
winSize	is a number which shows the size of the window.
overLap	This parameter shows how the window moves over the sequence. If overlap is set to FALSE, the window slides over the sequence in such a way that every time the window moves, it covers a unique portion of the sequence. Otherwise, portions of the sequence which appear within the window limits have "winSize-1" amino acids in common.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Details

Column names in the output matrix are $W_i(aa)$, where aa shows an amino acid type ("A", "C", "D",..., "Y") and i indicates the number of times that the window has moved over the sequence(s).

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (20 * number of partitions displayed by the window) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

When overlap is FALSE, the last partition represented by the window may have a different length with other parts.

References

Chen, Zhen, et al. "iFeature: a python package and web server for features extraction and selection from protein and peptide sequences." *Bioinformatics* 34.14 (2018): 2499-2502.

Examples

```
dir = tempdir()
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
mat<-EAAComposition(seqs = ptmSeqsVect,winSize=50, overLap=FALSE,outFormat='mat')

ad<-paste0(dir,"/EaaCompos.txt")
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
EAAComposition(seqs = filePrs,winSize=50, overLap=FALSE,outFormat="txt"
,outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

EffectiveNumberCodon *Effective Number of Codon (EffectiveNumberCodon)*

Description

This function calculates the effective number of codon for each sequence.

Usage

```
EffectiveNumberCodon(seqs, ORF = FALSE, reverseORF = TRUE, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).

reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature vector. The length of the vector is equal to the number of sequences. Each entry in the vector contains the effective number of codon.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
vect<-EffectiveNumberCodon(seqs=fileLNC,ORF=TRUE,reverseORF=FALSE)
```

EGAAComposition

Enhanced Grouped Amino Acid Composition (EGAAComposition)

Description

In this function, amino acids are first grouped into user-defined categories. Then, enhanced grouped amino acid composition is computed. For details about the enhanced feature, please refer to function [EAAComposition](#). Please note that this function differs from function [EAAComposition](#) which works on individual amino acids.

Usage

```
EGAAComposition(
  seqs,
  winSize = 50,
  overLap = TRUE,
  Grp = "locFus",
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
winSize	shows the size of sliding window. It is a numeric value.

overLap	This parameter shows how the window moves on the sequence. If the overlap is set to TRUE, the next window would have distance 1 with the previous window. Otherwise, the next window will start from the next amino acid after the previous window. There is no overlap between the next and previous windows.
Grp	is a list of vectors containig amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is ((number of categorizes) * (number of windows)) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
mat1<-EGAAComposition(seqs = ptmSeqsVect,winSize=20,overLap=FALSE,Grp="locFus")

mat2<-EGAAComposition(seqs = ptmSeqsVect,winSize=30,overLap=FALSE,Grp=
list(Grp1=c("G","A","V","L","M","I","F","Y","W"),Grp2=c("K","R","H","D","E")
,Grp3=c("S","T","C","P","N","Q")),outFormat="mat")

ad<-paste0(dir,"EGrpaaCompos.txt")
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
EGAAComposition(seqs = filePrs,winSize=20,Grp="cTriad",outFormat="txt"
,outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

Description

This function replaces each nucleotide in the input sequence with its electron-ion interaction value. The resulting sequence is represented by a feature vector whose length is equal to the length of the sequence. Please check the references for more information.

Usage

```
EIIP(seqs, outFormat = "mat", outputFileDist = "", label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is equal to the length of the sequences and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat parameter for sequences with different lengths. **Warning:** If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

References

Chen, Zhen, et al. "iLearn: an integrated platform and meta-learner for feature engineering, machine-learning analysis and modeling of DNA, RNA and protein sequence data." *Briefings in bioinformatics* 21.3 (2020): 1047-1057.

Examples

```
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-EIIP(seqs = LNC50Nuc,outFormat="mat")
```

ENUComposition_DNA *Enhanced Nucleotide Composition (ENUComposition_DNA)*

Description

This function slides a window over the input sequence(s). Also, it computes the composition of nucleotides that appears within the limits of the window.

Usage

```
ENUComposition_DNA(
  seqs,
  winSize = 50,
  overLap = TRUE,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
winSize	is a number which shows the size of the window.
overLap	This parameter shows how the window moves on the sequence. If the overlap is set to TRUE, the next window would have distance 1 with the previous window. Otherwise, the next window will start from the next amino acid after the previous window. There is no overlap between the next and previous windows.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (4 * number of partitions displayed by the window) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-ENUComposition_DNA(seqs = LNC50Nuc, winSize=20,outFormat="mat")

ad<-paste0(dir,"/ENUCcompos.txt")
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
ENUComposition_DNA(seqs = fileLNC,outFormat="txt",winSize=20
,outputFileDist=ad,overLap=FALSE)

unlink("dir", recursive = TRUE)
```

ENUComposition_RNA *Enhanced riboNucleotide Composition (ENUComposition_RNA)*

Description

This function slides a window over the input sequence(s). Also, it computes the composition of ribonucleotides that appears within the limits of the window.

Usage

```
ENUComposition_RNA(
  seqs,
  winSize = 50,
  overLap = TRUE,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
winSize	is a number which shows the size of the window.

overLap	This parameter shows how the window moves on the sequence. If the overlap is set to TRUE, the next window would have distance 1 with the previous window. Otherwise, the next window will start from the next amino acid after the previous window. There is no overlap between the next and previous windows.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (4 * number of partitions displayed by the window) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-ENUComposition_RNA(seqs = fileLNC, winSize=20,outFormat="mat")

ad<-paste0(dir,"/ENUCcompos.txt")
ENUComposition_RNA(seqs = fileLNC,outFormat="txt",winSize=20
,outputFileDist=ad,overLap=FALSE)

unlink("dir", recursive = TRUE)
```

ExpectedValKmerNUC_DNA

Expected Value for K-mer Nucleotide (ExpectedValKmerNUC_DNA)

Description

This function is introduced by this package for the first time. It computes the expected value for each k-mer in a sequence. $ExpectedValue(k\text{-mer}) = \text{freq}(k\text{-mer}) / (\text{freq}(\text{nucleotide1}) * \text{freq}(\text{nucleotide2}) * \dots * \text{freq}(\text{nucleotidek}))$

Usage

```
ExpectedValKmerNUC_DNA(
  seqs,
  k = 4,
  ORF = FALSE,
  reverseORF = TRUE,
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
k	is an integer value. The default is four.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is (4^k) .

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-ExpectedValKmerNUC_DNA(seqs=fileLNC,k=4,ORF=TRUE,reverseORF=FALSE)
```

ExpectedValKmerNUC_RNA

Expected Value for K-mer riboNucleotide (ExpectedValKmer-NUC_RNA)

Description

This function is introduced by this package for the first time. It computes the expected value for each k-mer in a sequence. $\text{ExpectedValue}(k\text{-mer}) = \text{freq}(k\text{-mer}) / (\text{freq}(\text{ribonucleotide1}) * \text{freq}(\text{ribonucleotide2}) * \dots * \text{freq}(\text{ribonucleotidek}))$

Usage

```
ExpectedValKmerNUC_RNA(
  seqs,
  k = 4,
  ORF = FALSE,
  reverseORF = TRUE,
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
k	is an integer value. The default is four.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is (4^k) .

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-ExpectedValKmerNUC_RNA(seqs=fileLNC,k=4,ORF=TRUE,reverseORF=FALSE)
```

ExpectedValueAA *Expected Value for each Amino Acid (ExpectedValueAA)*

Description

This function is introduced by this package for the first time. It computes the expected value for each k-mer in a sequence. $\text{ExpectedValue}(k\text{-mer}) = \text{freq}(k\text{-mer}) / (c_1 * c_2 * \dots * c_k)$, where c_i is the number of codons that encrypt the i 'th amino acid in the k-mer.

Usage

```
ExpectedValueAA(seqs, k = 2, normalized = TRUE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
k	is an integer value. The default is two.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is 20^k .

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-ExpectedValueAA(seqs=filePrs,k=2,normalized=FALSE)
```

ExpectedValueGAA *Expected Value for Grouped Amino Acid (ExpectedValueGAA)*

Description

This function is introduced by this package for the first time. In this function, amino acids are first grouped into user-defined categories. Later, the expected value of grouped amino acids is computed. Please note that this function differs from Function [ExpectedValueAA](#) which works on individual amino acids.

Usage

```
ExpectedValueGAA(seqs, k = 3, Grp = "locFus", normalized = TRUE, label = c())
```

Arguments

seqs is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.

k is an integer value. The default is three.

Grp is a list of vectors containing amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.

normalized is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.

label is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

for more information about ExpectedValueGAA, please refer to function ExpectedValueKmer.

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is (number of categories)^k.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-ExpectedValueGAA(seqs=filePrs,k=2,Grp="locFus")

mat2<-ExpectedValueGAA(seqs=filePrs,k=1,Grp=
list(Grp1=c("G","A","V","L","M","I","F","Y","W"),Grp2=c("K","R","H","D","E")
,Grp3=c("S","T","C","P","N","Q")))
```

ExpectedValueGKmerAA	<i>Expected Value for Grouped K-mer Amino Acid(ExpectedValueGKmerAA)</i>
----------------------	--

Description

This function is introduced by this package for the first time. In this function, amino acids are first grouped into user-defined categories. Later, the expected value of grouped k-mer is computed. Please note that this function differs from Function [ExpectedValueKmerAA](#) which works on individual amino acids.

Usage

```
ExpectedValueGKmerAA(
  seqs,
  k = 2,
  Grp = "locFus",
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
k	is an integer. The default value is two.
Grp	is a list of vectors containig amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is (number of categorizes)^k.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-ExpectedValueGKmerAA(seqs=filePrs,k=2,Grp="locFus")

mat2<-ExpectedValueGKmerAA(seqs=filePrs,k=1,Grp=
list(Grp1=c("G","A","V","L","M","I","F","Y","W"),Grp2=c("K","R","H","D","E")
,Grp3=c("S","T","C","P","N","Q")))
```

ExpectedValueKmerAA *Expected Value for K-mer Amino Acid (ExpectedValueKmerAA)*

Description

This function computes the expected value of each k-mer by dividing the frequency of the kmer to multiplying frequency of each amino acid of the k-mer in the sequence.

Usage

```
ExpectedValueKmerAA(seqs, k = 2, normalized = TRUE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
k	is an integer value and it shows the size of kmer in the kmer composition. The default value is 2.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

$$\text{ExpectedValue(k-mer)} = \text{freq(k-mer)} / (\text{freq(aminoacid1)} * \text{freq(aminoacid2)} * \dots * \text{freq(aminoacidk)})$$

Value

This function returns a feature matrix. The number of rows equals the number of sequences and the number of columns if upto set false, is 20^k .

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-ExpectedValueKmerAA(filePrs,k=2,normalized=FALSE)
```

fa.read	<i>Fasta File Reader (fa.read)</i>
---------	------------------------------------

Description

This function reads a FASTA file. Each sequence starts with '>' in the file. This is a general function which can be applied to all types of sequences (i.e., protein/peptide, dna, and rna).

Usage

```
fa.read(file, legacy.mode = TRUE, seqonly = FALSE, alphabet = "aa")
```

Arguments

file	The address of the FASTA file.
legacy.mode	comments all lines which start with ";".
seqonly	if it is set to true, the function will return sequences with no description.
alphabet	is a vector which contains amino acid, RNA, or DNA alphabets.

Value

a string vector such that each element is a sequence.

References

<https://cran.r-project.org/web/packages/rDNAse/index.html>

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
sequenceVectLNC<-fa.read(file=fileLNC,alphabet="dna")
```

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
sequenceVectPRO<-fa.read(file=filePrs,alphabet="aa")
```

fickettScore	<i>Fickett Score (fickettScore)</i>
--------------	-------------------------------------

Description

This function calculates the fickett score of each sequence.

Usage

```
fickettScore(seqs, ORF = FALSE, reverseORF = TRUE, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature vector. The length of the vector is equal to the number of sequences. Each entry in the vector contains the value of the fickett score.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
vect<-fickettScore(seqs=fileLNC,ORF=TRUE,reverseORF=FALSE)
```

GAAKpartComposition	<i>Grouped Amino Acid K Part Composition (GAAKpartComposition)</i>
---------------------	--

Description

In this function, amino acids are first grouped into user-defined categories. Later, the composition of the grouped amino acid k part is computed. Please note that this function differs from [AAKpart-Composition](#) which works on individual amino acids.

Usage

```
GAAKpartComposition(
  seqs,
  k = 5,
  normalized = TRUE,
  Grp = "locFus",
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
k	is an integer. Each sequence should be divided to k partition(s).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
Grp	is a list of vectors containig amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

a feature matrix with $k \times (\text{number of categorizes})$ number of columns. The number of rows is equal to the number of sequences.

Note

Warning: The length of all sequences should be greater than k.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-GAAKpartComposition(seqs=filePrs,k=5,Grp="aromatic")

mat2<-GAAKpartComposition(seqs=filePrs,k=3,normalized=FALSE,Grp=
list(Grp1=c("G","A","V","L","M","I","F","Y","W"),Grp2=c("K","R","H","D","E"),
,Grp3=c("S","T","C","P","N","Q")))
```

GrpDDE

Group Dipeptide Deviation from Expected Mean (GrpDDE)

Description

This function is introduced by this package for the first time. In this function, amino acids are first grouped into user-defined categories. Later, [DDE](#) is applied to grouped amino acids. Please note that this function differs from [DDE](#) which works on individual amino acids.

Usage

```
GrpDDE(seqs, Grp = "locFus", label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
Grp	is a list of vectors containig amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A feature matrix with (number of categorizes)² number of columns. The number of rows is equal to the number of sequences.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-GrpDDE(seqs=filePrs,Grp="aromatic")

mat2<-GrpDDE(seqs=filePrs,Grp=
list(Grp1=c("G","A","V","L","M","I","F","Y","W"),Grp2=c("K","R","H","D","E")
,Grp3=c("S","T","C","P","N","Q")))
```

G_Ccontent_DNA *G_C content in DNA (G_Ccontent_DNA)*

Description

This function calculates G-C content of each sequence.

Usage

```
G_Ccontent_DNA(
  seqs,
  ORF = FALSE,
  reverseORF = TRUE,
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature vector. The length of the vector is equal to the number of sequences. Each entry in the vector contains G-C content of a sequence.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
vect<-G_Ccontent_DNA(seqs=fileLNC,ORF=TRUE,reverseORF=FALSE)
```

G_Ccontent_RNA	<i>G_C content in RNA (G_Ccontent_RNA)</i>
----------------	--

Description

This function calculates G-C content of each sequence.

Usage

```
G_Ccontent_RNA(  
  seqs,  
  ORF = FALSE,  
  reverseORF = TRUE,  
  normalized = TRUE,  
  label = c()  
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The function returns a feature vector. The length of the vector is equal to the number of sequences. Each entry in the vector contains G-C content of a sequence.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")  
vect<-G_Ccontent_RNA(seqs=fileLNC,ORF=TRUE,reverseORF=FALSE)
```

kAAComposition	<i>k Amino Acid Composition (kAAComposition)</i>
----------------	--

Description

This function calculates the frequency of all k-mers in the sequence(s).

Usage

```
kAAComposition(seqs, rng = 3, upto = FALSE, normalized = TRUE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
rng	This parameter can be a number or a vector. Each entry of the vector holds the value of k in the k-mer composition.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from 1 to rng.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns depends on rng vector. For each value k in the vector, $(20)^k$ columns are created in the matrix.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")  
  
mat1<-kAAComposition(seqs=filePrs,rng=3,upto=TRUE)  
mat2<-kAAComposition(seqs=filePrs,rng=c(1,3),upto=TRUE)
```

kGAAComposition	<i>k Grouped Amino Acid Composition (kGAAComposition)</i>
-----------------	---

Description

In this function, amino acids are first grouped into user-defined categories. Later, the composition of the k grouped amino acids is computed. Please note that this function differs from [kAAComposition](#) which works on individual amino acids.

Usage

```
kGAAComposition(
  seqs,
  rng = 3,
  upto = FALSE,
  normalized = TRUE,
  Grp = "locFus",
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
rng	This parameter can be a number or a vector. Each entry of the vector holds the value of k in the k -mer composition. For each k in the rng vector, a new vector (whose size is 20^k) is created which contains the frequency of k -mers.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from 1 to rng.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
Grp	is a list of vectors containig amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

for more details, please refer to [kAAComposition](#)

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $((\text{number of categorizes})^k) * (\text{length of rng vector})$.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-CkSGAApair(seqs=filePrs,rng=2,upto=TRUE,Grp="aromatic")

mat2<-CkSGAApair(seqs=filePrs,rng=c(1,3,5),Grp=
list(Grp1=c("G","A","V","L","M","I","F","Y","W"),Grp2=c("K","R","H","D","E")
,Grp3=c("S","T","C","P","N","Q")))

```

KNNPeptide

*K-Nearest Neighbor for Peptides (KNNPeptide)***Description**

This function needs an extra training data set and a label. We compute the similarity score of each input sequence with all sequences in the training data set. We use the BLOSUM62 matrix to compute the similarity score. The label shows the class of each sequence in the training data set. KNNPeptide finds the label of 1 It reports the frequency of each class for each k

Usage

```
KNNPeptide(seqs, trainSeq, percent = 30, label = c(), labeltr = c())
```

Arguments

seqs	is a fasta file with amino acids sequences. Each sequence starts with a '>' character or it is a string vector such that each element is a peptide or protein sequence.
trainSeq	is a fasta file with amino acids sequences. Each sequence starts with a '>' character. Also it could be a string vector such that each element is a protein sequence. Each sequence in the training set is associated with a label. The label is found in the parameter labeltr.
percent	determines the threshold which is used to identify sequences (in the training set) which are similar to the input sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
labeltr	This parameter is a vector whose length is equivalent to the number of sequences in the training set. It shows class of each sequence in the training set.

Value

This function returns a feature matrix such that number of columns is number of classes multiplied by percent and number of rows is equal to the number of the sequences.

Note

This function is usable for amino acid sequences with the same length in both training data set and the set of sequences.

References

Chen, Zhen, et al. "iFeature: a python package and web server for features extraction and selection from protein and peptide sequences." *Bioinformatics* 34.14 (2018): 2499-2502.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])

posSeqs<-as.vector(read.csv(paste0(ptmSeqsADR,"/poSeqPTM101.csv"))[,2])
negSeqs<-as.vector(read.csv(paste0(ptmSeqsADR,"/negSeqPTM101.csv"))[,2])

posSeqs<-posSeqs[1:10]
negSeqs<-negSeqs[1:10]

trainSeq<-c(posSeqs,negSeqs)

labelPos<-rep(1,length(posSeqs))
labelNeg<-rep(0,length(negSeqs))

labeltr<-c(labelPos,labelNeg)

KNNPeptide(seqs=ptmSeqsVect,trainSeq=trainSeq,percent=10,labeltr=labeltr)
```

KNNProtein

K-Nearest Neighbor for Protein (KNNProtein)

Description

This function is like [KNNPeptide](#) with the difference that similarity score is computed by Needleman-Wunsch algorithm.

Usage

```
KNNProtein(seqs, trainSeq, percent = 30, labeltr = c(), label = c())
```

Arguments

seqs	is a fasta file with amino acids sequences. Each sequence starts with a '>' character. Also it could be a string vector such that each element is a protein sequence.
trainSeq	is a fasta file with amino acids sequences. Each sequence starts with a '>' character. Also it could be a string vector such that each element is a protein sequence. Each sequence in the training set is associated with a label. The label is found in the parameter labeltr.
percent	determines the threshold which is used to identify sequences (in the training set) which are similar to the input sequence.
labeltr	This parameter is a vector whose length is equivalent to the number of sequences in the training set. It shows class of each sequence in the training set.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix such that number of columns is number of classes multiplied by percent and number of rows is equal to the number of the sequences.

References

Chen, Zhen, et al. "iFeature: a python package and web server for features extraction and selection from protein and peptide sequences." *Bioinformatics* 34.14 (2018): 2499-2502.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
ptmSeqsVect<-ptmSeqsVect[1:2]

posSeqs<-as.vector(read.csv(paste0(ptmSeqsADR,"/poSeqPTM101.csv"))[,2])
negSeqs<-as.vector(read.csv(paste0(ptmSeqsADR,"/negSeqPTM101.csv"))[,2])

posSeqs<-posSeqs[1:3]
negSeqs<-negSeqs[1:3]

trainSeq<-c(posSeqs,negSeqs)

labelPos<-rep(1,length(posSeqs))
labelNeg<-rep(0,length(negSeqs))

labeltr<-c(labelPos,labelNeg)

KNNProtein(seqs=ptmSeqsVect,trainSeq=trainSeq,percent=10,labeltr=labeltr)
```

kNUComposition_DNA *k Nucleotide Composition (kNUComposition_DNA)*

Description

This function calculates the frequency of all k-mers in the sequence.

Usage

```
kNUComposition_DNA(
  seqs,
  rng = 3,
  reverse = FALSE,
  upto = FALSE,
  normalized = TRUE,
  ORF = FALSE,
  reverseORF = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
rng	This parameter can be a number or a vector. Each entry of the vector holds the value of k in the k-mer composition. For each k in the rng vector, a new vector (whose size is 20 ^k) is created which contains the frequency of kmers.
reverse	It is a logical parameter which assumes the reverse complement of the sequence.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from 1 to rng.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns depends on the rng vector. For each value k in the vector, (4)^k columns are created in the matrix.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-kNUComposition_DNA(seqs=fileLNC, rng=c(1,3))
```

kNUComposition_RNA *k riboNucleotide Composition (kNUComposition_RNA)*

Description

This function calculates the frequency of all k-mers in the sequence.

Usage

```
kNUComposition_RNA(
  seqs,
  rng = 3,
  reverse = FALSE,
  upto = FALSE,
  normalized = TRUE,
  ORF = FALSE,
  reverseORF = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
rng	This parameter can be a number or a vector. Each entry of the vector holds the value of k in the k-mer composition. For each k in the rng vector, a new vector (whose size is 20 ^k) is created which contains the frequency of kmers.
reverse	It is a logical parameter which assumes the reverse complement of the sequence.
upto	It is a logical parameter. The default value is FALSE. If rng is a number and upto is set to TRUE, rng is converted to a vector with values from 1 to rng.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns depends on the `rng` vector. For each value `k` in the vector, $(4)^k$ columns are created in the matrix.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-kNUComposition_RNA(seqs=fileLNC,rng=c(1,3))
```

 LocalPoSpKAAF

Local Position Specific k Amino Acids Frequency (LocalPoSpKAAF)

Description

For each sequence, this function creates a feature vector denoted as $(f_1, f_2, f_3, \dots, f_N)$, where $f_i = \text{freq}(i\text{'th } k\text{-mer of the sequence}) / i$. It should be applied to sequences with the same length.

Usage

```
LocalPoSpKAAF(seqs, k = 2, label = c(), outFormat = "mat", outputFileDist = "")
```

Arguments

<code>seqs</code>	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, <code>seqs</code> could be a string vector. Each element of the vector is a peptide/protein sequence.
<code>k</code>	is a numeric value which holds the value of <code>k</code> in the <code>k</code> -mers.
<code>label</code>	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
<code>outFormat</code>	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
<code>outputFileDist</code>	shows the path and name of the 'txt' output file.

Value

The output depends on the `outFormat` parameter which can be either 'mat' or 'txt'. If `outFormat` is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is $(\text{sequence length} - k + 1)$ and the number of rows is equal to the number of sequences. If the `outFormat` is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
mat<-LocalPoSpKAAF(seqs = ptmSeqsVect, k=2,outFormat="mat")

ad<-paste0(dir,"/LocalPoSpKaaF.txt")
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
LocalPoSpKAAF(seqs = filePrs, k=1,outFormat="txt"
,outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

LocalPoSpKNUCF_DNA *Local Position Specific k Nucleotide Frequency (LocalPoSp-KNUCF_DNA)*

Description

For each sequence, this function creates a feature vector denoted as $(f_1, f_2, f_3, \dots, f_N)$, where $f_i = \text{freq}(i\text{'th } k\text{-mer of the sequence}) / i$. It should be applied to sequences with the same length.

Usage

```
LocalPoSpKNUCF_DNA(
  seqs,
  k = 2,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.

k is a numeric value which holds the value of k in the k-mers.

`label` is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

`outFormat` (output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.

`outputFileDist` shows the path and name of the 'txt' output file.

Value

The output depends on the `outFormat` parameter which can be either 'mat' or 'txt'. If `outFormat` is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length-k+1) and the number of rows is equal to the number of sequences. If the `outFormat` is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in `outFormat` for sequences with different lengths. Warning: If `outFormat` is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-LocalPoSpKNUCF_DNA(seqs = LNC50Nuc, k=2,outFormat="mat")

ad<-paste0(dir,"/LocalPoSpKnuCF.txt")
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
LocalPoSpKNUCF_DNA(seqs = fileLNC,k=1,outFormat="txt"
,outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

LocalPoSpKNUCF_RNA *Local Position Specific k riboNucleotide Frequency (LocalPoSp-KNUCF_RNA)*

Description

For each sequence, this function creates a feature vector denoted as $(f_1, f_2, f_3, \dots, f_N)$, where $f_i = \text{freq}(i\text{'th } k\text{-mer of the sequence}) / i$. It should be applied to sequences with the same length.

Usage

```
LocalPoSpKNUCF_RNA(
  seqs,
  k = 2,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

<code>seqs</code>	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, <code>seqs</code> could be a string vector. Each element of the vector is a ribonucleotide sequence.
<code>k</code>	is a numeric value which holds the value of <code>k</code> in the <code>k</code> -mers.
<code>label</code>	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
<code>outFormat</code>	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
<code>outputFileDist</code>	shows the path and name of the 'txt' output file.

Value

The output depends on the `outFormat` parameter which can be either 'mat' or 'txt'. If `outFormat` is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length-`k`+1) and the number of rows is equal to the number of sequences. If the `outFormat` is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in `outFormat` for sequences with different lengths. Warning: If `outFormat` is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-LocalPoSpKNUCF_RNA(seqs = fileLNC, k=2,outFormat="mat")

ad<-paste0(dir,"/LocalPoSpKnucF.txt")
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
LocalPoSpKNUCF_RNA(seqs = fileLNC,k=1,outFormat="txt"
,outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

maxORF	<i>Maximum Open Reading Frame in DNA (maxORF)</i>
--------	---

Description

This function gets a sequence as the input. If reverse is true, the function extracts the max Open Reading Frame in the sequence and its reverse complement (hint: Six frames). Otherwise, only the sequence is searched (hint: Three frames).

Usage

```
maxORF(seqs, reverse = TRUE, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
reverse	It is a logical parameter which assumes the reverse complement of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A vector containing a subsequence for each given sequences. The subsequence is the maximum ORF of the sequence.

Note

If a sequence does not contain ORF, the function deletes the sequence.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
ORF<-maxORF(seqs=fileLNC,reverse=FALSE)
```

maxORFlength_DNA	<i>Maximum Open Reading Frame length in DNA (maxORFlength_DNA)</i>
------------------	--

Description

This function returns the length of the maximum Open Reading Frame for each sequence. If reverse is FALSE, ORF region will be searched in a sequence. Otherwise, it will be searched both in the sequence and its reverse complement.

Usage

```
maxORFlength_DNA(seqs, reverse = TRUE, normalized = FALSE, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
reverse	It is a logical parameter which assumes the reverse complement of the sequence.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A vector containing the lengths of maximum ORFs for each sequence.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")  
vect<-maxORFlength_DNA(seqs=fileLNC,reverse=TRUE,normalized=TRUE)
```

maxORFlength_RNA	<i>Maximum Open Reading Frame length in RNA (maxORFlength_RNA)</i>
------------------	--

Description

This function returns the length of the maximum Open Reading Frame for each sequence. If reverse is FALSE, ORF region will be searched in a sequence. Otherwise, it will be searched both in the sequence and its reverse complement.

Usage

```
maxORFlength_RNA(seqs, reverse = TRUE, normalized = FALSE, label = c())
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
reverse	It is a logical parameter which assumes the reverse complement of the sequence.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A vector containing the lengths of maximum ORFs for each sequence.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
vect<-maxORFlength_RNA(seqs=fileLNC,reverse=TRUE,normalized=TRUE)
```

maxORF_RNA	<i>Maximum Open Reading Frame in RNA (maxORF_RNA)</i>
------------	---

Description

This function gets a sequence as the input. If reverse is true, the function extracts the max Open Reading Frame in the sequence and its reverse complement (hint: Six frames). Otherwise, only the sequence is searched (hint: Three frames).

Usage

```
maxORF_RNA(seqs, reverse = TRUE, label = c())
```

Arguments

`seqs` is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, `seqs` could be a string vector. Each element of the vector is a ribonucleotide sequence.

`reverse` It is a logical parameter which assumes the reverse complement of the sequence.

`label` is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A vector containing a subsequence for each given sequences. The subsequence is the maximum ORF of the sequence.

Note

If a sequence does not contain ORF, the function deletes the sequence.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
ORF<-maxORF_RNA(seqs=fileLNC,reverse=FALSE)
```

nameKmer

naming Kmer (nameKmer)

Description

This function creates all possible k-combinations of the given alphabets.

Usage

```
nameKmer(k = 3, type = "aa", num = 0)
```

Arguments

`k` is a numeric value.

`type` can be one of "aa", "rna", "dna", or "num".

`num` When type is set to "num", it shows the numeric alphabet(1,...,num).

Value

a string vector of length (20^k for 'aa' type), (4^k for 'dna' type), (4^k for 'rna' type), and (num^k for 'num' type).

Examples

```
all_kmersAA<-nameKmer(k=2, type="aa")
all_kmersDNA<-nameKmer(k=3, type="dna")
all_kmersNUM<-nameKmer(k=3, type="num", num=2)
```

NCP_DNA

Nucleotide Chemical Property (NCP_DNA)

Description

This function replaces nucleotides with a three-length vector. The vector represent the nucleotides such that 'A' will be replaced with c(1, 1, 1), 'C' with c(0, 1, 0), 'G' with c(1, 0, 0), and 'T' with c(0, 0, 1).

Usage

```
NCP_DNA(
  seqs,
  binaryType = "strBin",
  outFormat = "mat",
  outputFileDist = "",
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
binaryType	It can take any of the following values: ('strBin', 'logicBin', 'numBin'). 'strBin' (String binary): each nucleotide is represented by a string containing 4 characters(0-1). A = "0001" , C = "0010" , G = "0100" , T = "1000" 'logicBin' (logical value): Each nucleotide is represented by a vector containing 4 logical entries. A = c(F,F,F,T) , ... , T = c(T,F,F,F) 'numBin' (numeric bin): Each nucleotide is represented by a numeric (i.e., integer) vector containing 4 numerals. A = c(0,0,0,1) , ... , T = c(1,0,0,0)
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The output is different depending on the `outFormat` parameter ('mat' or 'txt'). If `outFormat` is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if `binaryType` is 'strBin', the number of columns is the length of the sequences. Otherwise, it is equal to (length of the sequences)*3. If `outFormat` is 'txt', all binary values will be written to a tab-delimited file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in `outFormat` for sequences with different lengths. Warning: If `outFormat` is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

References

Chen, Zhen, et al. "iLearn: an integrated platform and meta-learner for feature engineering, machine-learning analysis and modeling of DNA, RNA and protein sequence data." *Briefings in bioinformatics* 21.3 (2020): 1047-1057.

Examples

```
dir = tempdir()
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-NCP_DNA(seqs = LNC50Nuc,binaryType="strBin",outFormat="mat")

ad<-paste0(dir,"/NCP.txt")
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
NCP_DNA(seqs = fileLNC,binaryType="strBin",outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

NCP_RNA

riboNucleotide Chemical Property (NCP_RNA)

Description

This function replaces ribonucleotides with a three-length vector. The vector represent the ribonucleotides such that 'A' will be replaced with c(1, 1, 1), 'C' with c(0, 1, 0), 'G' with c(1, 0, 0), and 'U' with c(0, 0, 1).

Usage

```
NCP_RNA(
  seqs,
  binaryType = "strBin",
  outFormat = "mat",
  outputFileDist = "",
  label = c()
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
binaryType	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin'(String binary): each nucleotide is represented by a string containing 4 characters(0-1). A = "0001" , C = "0010" , G = "0100" , T = "1000" 'logicBin'(logical value): Each nucleotide is represented by a vector containing 4 logical entries. A = c(F,F,F,T) , ... , T = c(T,F,F,F) 'numBin' (numeric bin): Each nucleotide is represented by a numeric (i.e., integer) vector containing 4 numerals. A = c(0,0,0,1) , ... , T = c(1,0,0,0)
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if binaryType is 'strBin', the number of columns is the length of the sequences. Otherwise, it is equal to (length of the sequences)*3. If outFormat is 'txt', all binary values will be written to a tab-delimited file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

References

Chen, Zhen, et al. "iLearn: an integrated platform and meta-learner for feature engineering, machine-learning analysis and modeling of DNA, RNA and protein sequence data." *Briefings in bioinformatics* 21.3 (2020): 1047-1057.

Examples

```
dir = tempdir()
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-NCP_RNA(seqs = fileLNC,binaryType="strBin",outFormat="mat")

ad<-paste0(dir,"/NCP.txt")
NCP_RNA(seqs = fileLNC,binaryType="strBin",outFormat="txt",outputFileDist=ad)
unlink("dir", recursive = TRUE)
```

needleman

Needleman-Wunsch (needleman)

Description

This function works based on Needleman-Wunsch algorithm which computes similarity score of two sequences.

Usage

```
needleman(seq1, seq2, gap = -1, mismatch = -1, match = 1)
```

Arguments

seq1	(sequence1) is a string.
seq2	(sequence2) is a string.
gap	The penalty for gaps in sequence alignment. Usually, it is a negative value.
mismatch	The penalty for the mismatch in the sequence alignment. Usually, it is a negative value.
match	A score for the match in sequence alignment. Usually, it is a positive value.

Value

The function returns a number which indicates the similarity between sequence1 and sequence2.

References

<https://gist.github.com/juliuskittler/ed53696ac1e590b413aac2dddf0457f6>

Examples

```
simScore<-needleman(seq1="Hello",seq2="Hello",gap=-1,mismatch=-2,match=1)
```

nonStandardSeq	<i>nonStandard sequence (nonStandardSeq)</i>
----------------	--

Description

This function returns sequences which contain at least one non-standard alphabet.

Usage

```
nonStandardSeq(file, legacy.mode = TRUE, seqonly = FALSE, alphabet = "aa")
```

Arguments

file	The address of fasta file which contains all the sequences.
legacy.mode	It comments all lines starting with ";"
seqonly	If it is set to true, the function returns sequences with no description.
alphabet	It is a vector which contains the amino acid, RNA, or DNA alphabets.

Value

This function returns a string vector. Each element of the vector is a sequence which contains at least one non-standard alphabet.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
nonStandardPrSeq<-nonStandardSeq(file = filePrs,alphabet="aa")

fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
nonStandardNUCSeq<-nonStandardSeq(file = filePrs, alphabet="dna")
```

NUC2Binary_DNA	<i>Nucleotide To Binary (NUC2Binary_DNA)</i>
----------------	--

Description

This function transforms a nucleotide to a binary format. The type of the binary format is determined by the binaryType parameter. For details about each format, please refer to the description of the binaryType parameter.

Usage

```

NUC2Binary_DNA(
  seqs,
  binaryType = "strBin",
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)

```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
binaryType	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin'(String binary): each nucleotide is represented by a string containing 4 characters(0-1). A = "0001" , C = "0010" , G = "0100" , T = "1000" 'logicBin'(logical value): Each nucleotide is represented by a vector containing 4 logical entries. A = c(F,F,F,T) , ... , T = c(T,F,F,F) 'numBin' (numeric bin): Each nucleotide is represented by a numeric (i.e., integer) vector containing 4 numerals. A = c(0,0,0,1) , ... , T = c(1,0,0,0)
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if binaryType is 'strBin', the number of columns is the length of the sequences. Otherwise, it is equal to (length of the sequences)*4. If outFormat is 'txt', all binary values will be written to a 'txt' file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat parameter for sequences with different lengths. **Warning:** If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes.

Examples

```

dir = tempdir()
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")

```



```

LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-NUC2Binary_DNA(seqs = LNC50Nuc,outFormat="mat")

ad<-paste0(dir,"/NUC2Binary.txt")
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
NUC2Binary_DNA(seqs = fileLNC,binaryType="strBin",outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)

```

NUC2Binary_RNA *riboNucleotide To Binary (NUC2Binary_RNA)*

Description

This function transforms a ribonucleotide to a binary format. The type of the binary format is determined by the `binaryType` parameter. For details about each format, please refer to the description of the `binaryType` parameter.

Usage

```

NUC2Binary_RNA(
  seqs,
  binaryType = "strBin",
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)

```

Arguments

<code>seqs</code>	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, <code>seqs</code> could be a string vector. Each element of the vector is a ribonucleotide sequence.
<code>binaryType</code>	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin'(String binary): each ribonucleotide is represented by a string containing 4 characters(0-1). A = "0001" , C = "0010" , G = "0100" , U = "1000" 'logicBin'(logical value): Each ribonucleotide is represented by a vector containing 4 logical entries. A = c(F,F,F,T) , ... , U = c(T,F,F,F) 'numBin' (numeric bin): Each ribonucleotide is represented by a numeric (i.e., integer) vector containing 4 numerals. A = c(0,0,0,1) , ... , U = c(1,0,0,0)
<code>label</code>	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
<code>outFormat</code>	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
<code>outputFileDist</code>	shows the path and name of the 'txt' output file.

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if binaryType is 'strBin', the number of columns is the length of the sequences. Otherwise, it is equal to (length of the sequences)*4. If outFormat is 'txt', all binary values will be written to a 'txt' file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat parameter for sequences with different lengths. Warning: If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes.

Examples

```
dir = tempdir()
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-NUC2Binary_RNA(seqs = fileLNC,outFormat="mat")

ad<-paste0(dir,"/NUC2Binary.txt")
NUC2Binary_RNA(seqs = fileLNC,binaryType="strBin",outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

NUCKpartComposition_DNA

Nucleotide to K Part Composition (NUCKpartComposition_DNA)

Description

In this function, each sequence is divided into k equal partitions. The length of each part is equal to $\text{ceiling}(l(\text{length of the sequence})/k)$. The last part can have a different length containing the residual nucleotides. The nucleotide composition is calculated for each part.

Usage

```
NUCKpartComposition_DNA(
  seqs,
  k = 5,
  ORF = FALSE,
  reverseORF = TRUE,
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
k	is an integer value. Each sequence should be divided to k partition(s).
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

a feature matrix with $k \times 4$ number of columns. The number of rows is equal to the number of sequences.

Note

Warning: The length of all sequences should be greater than k.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-NUCKpartComposition_DNA(seqs=fileLNC,k=5,ORF=TRUE,reverseORF=FALSE,normalized=FALSE)
```

NUCKpartComposition_RNA

riboNucleotide to K Part Composition (NUCKpartComposition_RNA)

Description

In this function, each sequence is divided into k equal partitions. The length of each part is equal to $\text{ceiling}(\text{length of the sequence}/k)$. The last part can have a different length containing the residual ribonucleotides. The ribonucleotide composition is calculated for each part.

Usage

```
NUCKpartComposition_RNA(  
  seqs,  
  k = 5,  
  ORF = FALSE,  
  reverseORF = TRUE,  
  normalized = TRUE,  
  label = c()  
)
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
k	is an integer value. Each sequence should be divided to k partition(s).
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

a feature matrix with $k*4$ number of columns. The number of rows is equal to the number of sequences.

Note

Warning: The length of all sequences should be greater than k.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")  
mat<-NUCKpartComposition_RNA(seqs=fileLNC,k=5,ORF=TRUE,reverseORF=FALSE,normalized=FALSE)
```

PCPseDNC

*Parallel Correlation Pseudo Dinucleotide Composition (PCPseDNC)***Description**

This function works like [PSEkNUCdi_DNA](#) except that the default value of selectedIdx parameter is different.

Usage

```
PCPseDNC(
  seqs,
  selectedIdx = c("Base stacking", "Protein induced deformability", "B-DNA twist",
    "A-philicity", "Propeller twist", "Duplex stability:(freeenergy)",
    "DNA denaturation", "Bending stiffness", "Protein DNA twist", "Aida_BA_transition",
    "Breslauer_dG", "Breslauer_dH", "Electron_interaction", "Hartman_trans_free_energy",
    "Helix-Coil_transition", "Lisser_BZ_transition", "Polar_interaction",
    "SantaLucia_dG", "SantaLucia_dS", "Sarai_flexibility", "Stability", "Sugimoto_dG",
    "Sugimoto_dH", "Sugimoto_dS", "Duplex tability(disruptenergy)",
    "Stabilising energy of Z-DNA", "Breslauer_dS", "Ivanov_BA_transition",
    "SantaLucia_dH", "Stacking_energy", "Watson-Crick_interaction",
    "Dinucleotide GC Content", "Rise", "Roll", "Shift", "Slide", "Tilt", "Twist"),
  lambda = 3,
  w = 0.05,
  l = 2,
  ORF = FALSE,
  reverseORF = TRUE,
  threshold = 1,
  label = c()
)
```

Arguments

seqs is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.

selectedIdx is a vector of Ids or indices of the desired physicochemical properties of dinucleotides. Users can choose the desired indices by their ids or their names in the DI_DNA index file. Default value of this parameter is a vector with ("Base stacking","Protein induced deformability","B-DNA twist","A-philicity", "Propeller twist","Duplex stability:(freeenergy)","DNA denaturation","Bending stiffness", "Protein DNA twist", "Aida_BA_transition", "Breslauer_dG", "Breslauer_dH", "Electron_interac", "Hartman_trans_free_energy", "Helix-Coil_transition", "Lisser_BZ_transition", "Polar_interaction", "SantaLucia_dG", "SantaLucia_dS", "Sarai_flexibility", "Stability", "Sugimoto_dG", "Sugimoto_dH", "Sugimoto_dS", "Duplex tability(disruptenergy)", "Stabilising energy of Z-DNA", "Breslauer_dS", "Ivanov_BA_transition", "SantaLucia_dH", "Stacking_energy", "Watson-

	Crick_interaction", "Dinucleotide GC Content", "Rise", "Roll", "Shift", "Slide", "Tilt", "Twist") entries.
lambda	is a tuning parameter. This integer value shows the maximum limit of spaces between dinucleotide pairs. The Number of spaces changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in the range of 0 to 1. The default value is 0.05.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 4^l elements of the APkNCdi descriptor.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
threshold	is a number between (0 , 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo nucleotide composition for each physicochemical property of di-nucleotides. We have provided users with the ability to choose among the 148 properties in the di-nucleotide index database.

Value

a feature matrix such that the number of columns is $4^l + \text{lambda}$ and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-PSEKNUCdi_DNA(seqs=fileLNC,l=2,ORF=TRUE,threshold=0.8)
```

PSEAAC

Pseudo-Amino Acid Composition (Parallel) (PSEAAC)

Description

This function calculates the pseudo amino acid composition (parallel) for each sequence.

Usage

```
PSEAAC(
  seqs,
  aaIDX = c("ARGP820101", "HOPT810101", "Mass"),
  lambda = 30,
  w = 0.05,
  l = 1,
  threshold = 1,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
aaIDX	is a vector of Ids or indexes of the user-selected physicochemical properties in the aaIndex2 database. The default values of the vector are the hydrophobicity ids and hydrophilicity ids and Mass of residual in the amino acid index file.
lambda	is a tuning parameter. Its value indicates the maximum number of spaces between di-nucleotide pairs. The number changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in from 0 to 1. The default value is 0.05.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 20^l elements of the APAAC descriptor.
threshold	is a number between (0, 1]. It deletes aaIndexes which have a correlation bigger than the threshold. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

A feature matrix such that the number of columns is $20^{l+lambda}$ and the number of rows is equal to the number of sequences.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-PSEAAC(seqs=filePrs,l=2)
```

PseEIIP	<i>Pseudo Electron-Ion Interaction Pseudopotentials of Trinucleotide (PseEIIP)</i>
---------	--

Description

This function calculates the pseudo electron-ion interaction for each sequence. It creates a feature vector for each sequence. The vector contains a value for each for each tri-nucleotide. The value is computed by multiplying the aggregate value of electron-ion interaction of each nucleotide

Usage

```
PseEIIP(seqs, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

This function returns a feature matrix which the number of rows is equal to the number of sequences and the number of columns is $4^3=64$.

References

Chen, Zhen, et al. "iLearn: an integrated platform and meta-learner for feature engineering, machine-learning analysis and modeling of DNA, RNA and protein sequence data." *Briefings in bioinformatics* 21.3 (2020): 1047-1057.

Examples

```
LNCSeqsADR<-system.file("extdata/",package="ftrCOOL")
LNC50Nuc<-as.vector(read.csv(paste0(LNCSeqsADR,"/LNC50Nuc.csv"))[,2])
mat<-PseEIIP(seqs = LNC50Nuc)
```

PSEkNUCdi_DNA *Pseudo k Nucleotide Composition-Di(Parallel) (PSEkNUCdi_DNA)*

Description

This function calculates the pseudo-k nucleotide composition(Di) (Parallel) for each sequence.

Usage

```
PSEkNUCdi_DNA(
  seqs,
  selectedIdx = c("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist"),
  lambda = 3,
  w = 0.05,
  l = 2,
  ORF = FALSE,
  reverseORF = TRUE,
  threshold = 1,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
selectedIdx	is a vector of Ids or indices of the desired physicochemical properties of dinucleotides. Users can choose the desired indices by their ids or their names in the DI_DNA file. The default values of the parameter is a vector with ("Rise", "Roll", "Shift", "Slide", "Tilt", "Twist") ids.
lambda	is a tuning parameter. This integer value shows the maximum limit of spaces between dinucleotide pairs. The Number of spaces changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in the range of 0 to 1. The default value is 0.05.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 4^l elements of the APkNCdi descriptor.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
threshold	is a number between (0 , 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo nucleotide composition for each physicochemical property of di-nucleotides. We have provided users with the ability to choose among the 148 properties in the di-nucleotide index database.

Value

a feature matrix such that the number of columns is $4^{\lambda+1}$ and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-PSEkNUCdi_DNA(seqs=fileLNC,l=2,ORF=TRUE,threshold=0.8)
```

PSEkNUCdi_RNA	<i>Pseudo</i>	<i>k</i>	<i>riboNucleotide</i>	<i>Composition-Di(Parallel)</i>
	<i>(PSEkNUCdi_RNA)</i>			

Description

This function calculates the pseudo-k ribonucleotide composition(Di) (Parallel) for each sequence.

Usage

```
PSEkNUCdi_RNA(
  seqs,
  selectedIdx = c("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)",
    "Tilt (RNA)", "Twist (RNA)"),
  lambda = 3,
  w = 0.05,
  l = 2,
  ORF = FALSE,
  reverseORF = TRUE,
  threshold = 1,
  label = c()
)
```

Arguments

`seqs` is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, `seqs` could be a string vector. Each element of the vector is a ribonucleotide sequence.

selectedIdx	is a vector of Ids or indices of the desired physicochemical properties of di-ribonucleotides. Users can choose the desired indices by their ids or their names in the DI_RNA peoperties file. The default value of this parameter is a vector with ("Rise (RNA)", "Roll (RNA)", "Shift (RNA)", "Slide (RNA)", "Tilt (RNA)", "Twist (RNA)") ids.
lambda	is a tuning parameter. This integer value shows the maximum limit of spaces between di-ribonucleotide pairs. The Number of spaces changes from 1 to lambda.
w	(weight) is a tuning parameter. It changes in the range of 0 to 1. The default value is 0.5.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 4^l elements of the APkNCdi descriptor.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
threshold	is a number between (0 , 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo ribonucleotide composition for each physicochemical property of di-ribonucleotides. We have provided users with the ability to choose among the 22 properties in the di-ribonucleotide index database.

Value

a feature matrix such that the number of columns is $4^l + \lambda$ and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Carica_papaya101RNA.txt",package="ftrCOOL")
mat<-PSEkNUCdi_RNA(seqs=fileLNC,l=2,ORF=TRUE,threshold=0.8)
```

PSEkNUCTri_DNA

Pseudo k Nucleotide Composition-Tri(Parallel) (PSEkNUCTri_RNA)

Description

This function calculates pseudo-k nucleotide composition(Tri) (Parallel) for each sequence.

Usage

```
PSEkNUCTri_DNA(
  seqs,
  selectedIdx = c("Dnase I", "Bendability (DNase)"),
  lambda = 3,
  w = 0.05,
  l = 3,
  ORF = FALSE,
  reverseORF = TRUE,
  threshold = 1,
  label = c()
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
selectedIdx	is a vector of Ids or indices of the desired physicochemical properties of trinucleotides. Users can choose the desired indices by their ids or their names in the TRI_DNA index file. The default value of this parameter is a vector with ("Dnase I", "Bendability (DNase)") ids.
lambda	is a tuning parameter. This integer value shows the maximum limit of spaces between di-nucleotide pairs. The Number of spaces changes from 1 to lambda.
w	(weight) is a tuning parameter. It can take a value in the range 0 to 1. The default value is 0.05.
l	This parameter keeps the value of l in lmer composition. The lmers form the first 4^l elements of the APkNCTri descriptor.
ORF	(Open Reading Frame) is a logical parameter. If it is set to true, ORF region of each sequence is considered instead of the original sequence (i.e., 3-frame).
reverseORF	is a logical parameter. It is enabled only if ORF is true. If reverseORF is true, ORF region will be searched in the sequence and also in the reverse complement of the sequence (i.e., 6-frame).
threshold	is a number between (0 , 1]. In selectedIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

This function computes the pseudo nucleotide composition for each physicochemical property of trinucleotides. We have provided users with the ability to choose among the 12 properties in the tri-nucleotide index database.

Value

a feature matrix such that the number of columns is $4^l + \text{lambda}$ and the number of rows is equal to the number of sequences.

Examples

```
fileLNC<-system.file("extdata/Athaliana_LNCRNA.fa",package="ftrCOOL")
mat<-PSEkNUCTri_DNA(seqs=fileLNC, l=2,ORF=TRUE,threshold=0.8)
```

PseKRAAC_T1	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-1 (PseKRAAC_T1)</i>
-------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type1(PseKRAAC_T1) contains Grp 2 to 20.

Usage

```
PseKRAAC_T1(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 2,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 2=c("CMFILVWY", "AGTSNQDEHRKP"), 3=c("CMFILVWY", "AGTSP", "NQDEHRK"), 4=c("CMFWY", "ILV", "AGTS", "NQDEHRKP"), 5=c("WIFYH", "MILV", "CATSP", "G", "NQDERK"), 6=c("WIFYH", "MILV", "CATS", "P", "G", "NQDERK"), 7=c("WIFYH", "MILV", "CATS", "P", "G", "NQDE", "RK"), 8=c("WIFYH", "MILV", "CA", "NTS", "P", "G", "DE", "QRK"), 9=c("WIFYH", "MI", "LV", "CA", "NTS", "P", "G", "DE", "QRK"), 10=c("WIFY", "ML", "IV", "CA", "TS", "NH", "P", "G", "DE", "QRK"), 11=c("WIFY", "ML", "IV", "CA", "TS", "NH", "P", "G", "D", "QE", "RK"), 12=c("WIFY", "ML", "IV", "C", "A", "TS", "NH", "P", "G", "D", "QE", "RK"), 13=c("WIFY", "ML", "IV", "C", "A", "T", "S", "NH", "P", "G", "D", "QE", "RK"), 14=c("WIFY", "ML", "IV", "C", "A", "T", "S", "NH", "P", "G", "D", "QE", "R", "K"), 15=c("WIFY", "ML", "IV", "C", "A", "T", "S", "N", "H", "P", "G", "D", "QE", "R", "K"), 16=c("W", "FY", "ML", "IV", "C", "A", "T", "S", "N", "H", "P", "G", "D", "QE", "R", "K"), 17=c("W", "FY", "ML", "IV", "C", "A", "T", "S", "N", "H", "P", "G", "D", "Q", "E", "R", "K"), 18=c("W", "FY", "M", "L", "IV", "C", "A", "T", "S", "N", "H", "P", "G", "D", "Q", "E", "R", "K"), 19=c("W", "F", "Y", "M", "L", "IV", "C", "A", "T", "S", "N", "H", "P", "G", "D", "Q", "E", "R", "K"), 20=c("W", "F", "Y", "M", "L", "I", "V", "C", "A", "T", "S", "N", "H", "P", "G", "D", "Q", "E", "R", "K")

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(\text{Grp})^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T1(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T1(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T10	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-10 (PseKRAAC_T10)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type10(PseKRAAC_T10) contains Grp 2-20.

Usage

```
PseKRAAC_T10(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 2=c('CMFILVWY', 'AGTSNQDEHRKP'), 3=c('CMFILVWY', 'AGTSP', 'NQDEHRK'), 4=c('CMFWY', 'ILV', 'AGTS', 'NQDEHRKP'), 5=c('FWYH', 'MILV', 'CATSP', 'G', 'NQDERK'), 6=c('FWYH', 'MILV', 'CATS', 'P', 'G', 'NQDERK'), 7=c('FWYH', 'MILV', 'CATS', 'P', 'G', 'NQDE', 'RK'), 8=c('FWYH', 'MILV', 'CA', 'NTS', 'P', 'G', 'DE', 'QRK'), 9=c('FWYH', 'ML', 'IV', 'CA', 'NTS', 'P', 'G', 'DE', 'QRK'), 10=c('FWY', 'ML', 'IV', 'CA', 'TS', 'NH', 'P', 'G', 'DE', 'QRK'), 11=c('FWY', 'ML', 'IV', 'CA', 'TS', 'NH', 'P', 'G', 'D', 'QE', 'RK'), 12=c('FWY', 'ML', 'IV', 'C', 'A', 'TS', 'NH', 'P', 'G', 'D', 'QE', 'RK'), 13=c('FWY', 'ML', 'IV', 'C', 'A', 'T', 'S', 'NH', 'P', 'G', 'D', 'QE', 'R', 'K'), 14=c('FWY', 'ML', 'IV', 'C', 'A', 'T', 'S', 'N', 'H', 'P', 'G', 'D', 'QE', 'R', 'K'), 15=c('FWY', 'ML', 'IV', 'C', 'A', 'T', 'S', 'N', 'H', 'P', 'G', 'D', 'QE', 'R', 'K'), 16=c('W', 'FY', 'ML', 'IV', 'C', 'A', 'T', 'S', 'N', 'H', 'P', 'G', 'D', 'QE', 'R', 'K'), 17=c('W', 'FY', 'ML', 'IV', 'C', 'A', 'T', 'S', 'N', 'H', 'P', 'G', 'D', 'Q', 'E', 'R', 'K'), 18=c('W', 'FY', 'M', 'L', 'IV', 'C', 'A', 'T', 'S', 'N', 'H', 'P', 'G', 'D', 'Q', 'E', 'R', 'K'), 19=c('W', 'F', 'Y', 'M', 'L', 'IV', 'C', 'A', 'T', 'S', 'N', 'H', 'P', 'G', 'D', 'Q', 'E', 'R', 'K'), 20=c('W', 'F', 'Y', 'M', 'L', 'I', 'V', 'C', 'A', 'T', 'S', 'N', 'H', 'P', 'G', 'D', 'Q', 'E', 'R', 'K')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")

mat1<-PseKRAAC_T10(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)

mat2<-PseKRAAC_T10(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T11	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-11 (PseKRAAC_T11)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type11(PseKRAAC_T11) contains Grp 2-20.

Usage

```
PseKRAAC_T11(  
  seqs,  
  type = "gap",  
  Grp = 5,  
  GapOrLambdaValue = 2,  
  k = 4,  
  label = c()  
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.

GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 2=c('CFYWMLIV', 'GPATSNHQEDRK'), 3=c('CFYWMLIV', 'GPATS', 'NHQEDRK'), 4=c('CFYW', 'MLIV', 'GPATS', 'NHQEDRK'), 5=c('CFYW', 'MLIV', 'G', 'PATS', 'NHQEDRK'), 6=c('CFYW', 'MLIV', 'G', 'P', 'ATS', 'NHQEDRK'), 7=c('CFYW', 'MLIV', 'G', 'P', 'ATS', 'NHQED', 'RK'), 8=c('CFYW', 'MLIV', 'G', 'P', 'ATS', 'NH', 'QED', 'RK'), 9=c('CFYW', 'ML', 'IV', 'G', 'P', 'ATS', 'NH', 'QED', 'RK'), 10=c('C', 'FYW', 'ML', 'IV', 'G', 'P', 'ATS', 'NH', 'QED', 'RK'), 11=c('C', 'FYW', 'ML', 'IV', 'G', 'P', 'A', 'TS', 'NH', 'QED', 'RK'), 12=c('C', 'FYW', 'ML', 'IV', 'G', 'P', 'A', 'TS', 'NH', 'QE', 'D', 'RK'), 13=c('C', 'FYW', 'ML', 'IV', 'G', 'P', 'A', 'T', 'S', 'NH', 'QE', 'D', 'RK'), 14=c('C', 'FYW', 'ML', 'IV', 'G', 'P', 'A', 'T', 'S', 'N', 'H', 'QE', 'D', 'RK'), 15=c('C', 'FYW', 'ML', 'IV', 'G', 'P', 'A', 'T', 'S', 'N', 'H', 'QE', 'D', 'R', 'K'), 16=c('C', 'FY', 'W', 'ML', 'IV', 'G', 'P', 'A', 'T', 'S', 'N', 'H', 'QE', 'D', 'R', 'K'), 17=c('C', 'FY', 'W', 'ML', 'IV', 'G', 'P', 'A', 'T', 'S', 'N', 'H', 'Q', 'E', 'D', 'R', 'K'), 18=c('C', 'FY', 'W', 'M', 'L', 'IV', 'G', 'P', 'A', 'T', 'S', 'N', 'H', 'Q', 'E', 'D', 'R', 'K'), 19=c('C', 'F', 'Y', 'W', 'M', 'L', 'IV', 'G', 'P', 'A', 'T', 'S', 'N', 'H', 'Q', 'E', 'D', 'R', 'K'), 20=c('C', 'F', 'Y', 'W', 'M', 'L', 'I', 'V', 'G', 'P', 'A', 'T', 'S', 'N', 'H', 'Q', 'E', 'D', 'R', 'K')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is (Grp)^k.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T11(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T11(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T12	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-12 (PseKRAAC_T12)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type12(PseKRAAC_T12) contains Grp 2-18,20.

Usage

```
PseKRAAC_T12(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 2=c('IVMLFWYC', 'ARNDQEGHKPST'), 3=c('IVLMFWC', 'YA', 'RNDQEGHKPST'), 4=c('IVLMFW', 'C', 'YA', 'RNDQEGHKPST'), 5=c('IVLMFW', 'C', 'YA', 'G', 'RNDQEGHKPST'), 6=c('IVLMF', 'WY', 'C', 'AH', 'G', 'RNDQEKPST'), 7=c('IVLMF', 'WY', 'C', 'AH', 'GP', 'R', 'NDQEKST'), 8=c('IVLMF', 'WY', 'C', 'A', 'G', 'R', 'Q', 'NDEHKPST'), 9=c('IVLMF', 'WY', 'C', 'A', 'G', 'P', 'H', 'K', 'RNDQEST'), 10=c('IVLM', 'F', 'W', 'Y', 'C', 'A', 'H',

```
'G', 'RN', 'DQEKPST'), 11=c('IVLMF', 'W', 'Y', 'C', 'A', 'H', 'G', 'R', 'N', 'Q', 'DEKPST'),
12=c('IVLM', 'F', 'W', 'Y', 'C', 'A', 'H', 'G', 'N', 'Q', 'T', 'RDEKPS'), 13=c('IVLM', 'F', 'W',
'Y', 'C', 'A', 'H', 'G', 'N', 'Q', 'P', 'R', 'DEKST'), 14=c('IVLM', 'F', 'W', 'Y', 'C', 'A', 'H',
'G', 'N', 'Q', 'P', 'R', 'K', 'DEST'), 15=c('IVLM', 'F', 'W', 'Y', 'C', 'A', 'H', 'G', 'N', 'Q',
'P', 'R', 'K', 'D', 'EST'), 16=c('IVLM', 'F', 'W', 'Y', 'C', 'A', 'H', 'G', 'N', 'Q', 'P', 'R', 'K',
'S', 'T', 'DE'), 17=c('IVL', 'M', 'F', 'W', 'Y', 'C', 'A', 'H', 'G', 'N', 'Q', 'P', 'R', 'K', 'S', 'T',
'DE'), 18=c('IVL', 'M', 'F', 'W', 'Y', 'C', 'A', 'H', 'G', 'N', 'Q', 'P', 'R', 'K', 'S', 'T', 'D', 'E'),
20=c('I', 'V', 'L', 'M', 'F', 'W', 'Y', 'C', 'A', 'H', 'G', 'N', 'Q', 'P', 'R', 'K', 'S', 'T', 'D', 'E')
```

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T12(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T12(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T13	<i>Pseudo K_tuple Reduced Amino Acid Composition Type_13 (PseKRAAC_T13)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type13(PseKRAAC_T13) contains Grp 4,12,17,20.

Usage

```
PseKRAAC_T13(
  seqs,
  type = "gap",
  Grp = 4,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 4=c('ADKERNTSQ', 'YFLIVMCWH', 'G', 'P'), 12=c('A', 'D', 'KER', 'N', 'TSQ', 'YF', 'LIVM', 'C', 'W', 'H', 'G', 'P'), 17=c('A', 'D', 'KE', 'R', 'N', 'T', 'S', 'Q', 'Y', 'F', 'LIV', 'M', 'C', 'W', 'H', 'G', 'P'), 20=c('A', 'D', 'K', 'E', 'R', 'N', 'T', 'S', 'Q', 'Y', 'F', 'L', 'I', 'V', 'M', 'C', 'W', 'H', 'G', 'P')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T13(seqs=filePrs,type="gap",Grp=17,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T13(seqs=filePrs,type="lambda",Grp=17,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T14	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-14 (PseKRAAC_T14)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type14(PseKRAAC_T14) contains Grp 2-20.

Usage

```
PseKRAAC_T14(
  seqs,
  type = "gap",
  Grp = 2,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 2=c('ARNDQEGHKPST', 'ILMFWYV'), 3=c('ARNDQEGHKPST', 'C', 'ILMFWYV'), 4=c('ARNDQEGHKPST', 'C', 'ILMFYV', 'W'), 5=c('AGPST', 'RNDQEHK', 'C', 'ILMFYV', 'W'), 6=c('AGPST', 'RNDQEK', 'C', 'H', 'ILMFYV', 'W'), 7=c('ANDGST', 'RQEK', 'C', 'H', 'ILMFYV', 'P', 'W'), 8=c('ANDGST', 'RQEK', 'C', 'H', 'ILMV', 'FY', 'P', 'W'), 9=c('AGST', 'RQEK', 'ND', 'C', 'H', 'ILMV', 'FY', 'P', 'W'), 10=c('AGST', 'RK', 'ND', 'C', 'QE', 'H',

```
'ILMV', 'FY', 'P', 'W'), 11=c('AST', 'RK', 'ND', 'C', 'QE', 'G', 'H', 'ILMV', 'FY', 'P', 'W'),
12=c('AST', 'RK', 'ND', 'C', 'QE', 'G', 'H', 'IV', 'LM', 'FY', 'P', 'W'), 13=c('AST', 'RK', 'N',
'D', 'C', 'QE', 'G', 'H', 'IV', 'LM', 'FY', 'P', 'W'), 14=c('AST', 'RK', 'N', 'D', 'C', 'Q', 'E',
'G', 'H', 'IV', 'LM', 'FY', 'P', 'W'), 15=c('A', 'RK', 'N', 'D', 'C', 'Q', 'E', 'G', 'H', 'IV', 'LM',
'FY', 'P', 'ST', 'W'), 16=c('A', 'RK', 'N', 'D', 'C', 'Q', 'E', 'G', 'H', 'IV', 'LM', 'F', 'P', 'ST',
'W', 'Y'), 17=c('A', 'R', 'N', 'D', 'C', 'Q', 'E', 'G', 'H', 'IV', 'LM', 'K', 'F', 'P', 'ST', 'W',
'Y'), 18=c('A', 'R', 'N', 'D', 'C', 'Q', 'E', 'G', 'H', 'IV', 'LM', 'K', 'F', 'P', 'S', 'T', 'W', 'Y'),
19=c('A', 'R', 'N', 'D', 'C', 'Q', 'E', 'G', 'H', 'IV', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y'),
20=c('A', 'R', 'N', 'D', 'C', 'Q', 'E', 'G', 'H', 'I', 'V', 'L', 'K', 'M', 'F', 'P', 'S', 'T', 'W', 'Y')
```

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T14(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T14(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T15	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-15 (PseKRAAC_T15)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type15(PseKRAAC_T15) contains Grp 2-16,20.

Usage

```
PseKRAAC_T15(
  seqs,
  type = "gap",
  Grp = 2,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups:

```
Grp2=c('MFILVAW', 'CYQHPGTSNRKDE'), Grp3=c('MFILVAW', 'CYQHPGTSNRK', 'DE'),
Grp4=c('MFILV', 'ACW', 'YQHPGTSNRK', 'DE'), Grp5=c('MFILV', 'ACW', 'YQHPGTSN',
'RK', 'DE'), Grp6=c('MFILV', 'A', 'C', 'WYQHPGTSN', 'RK', 'DE'), Grp7=c('MFILV', 'A',
'C', 'WYQHP', 'GTSN', 'RK', 'DE'), Grp8=c('MFILV', 'A', 'C', 'WYQHP', 'G', 'TSN', 'RK',
'DE'), Grp9=c('MF', 'ILV', 'A', 'C', 'WYQHP', 'G', 'TSN', 'RK', 'DE'), Grp10=c('MF', 'ILV',
'A', 'C', 'WYQHP', 'G', 'TSN', 'RK', 'D', 'E'), Grp11=c('MF', 'IL', 'V', 'A', 'C', 'WYQHP',
'G', 'TSN', 'RK', 'D', 'E'), Grp12=c('MF', 'IL', 'V', 'A', 'C', 'WYQHP', 'G', 'TS', 'N', 'RK',
'D', 'E'), Grp13=c('MF', 'IL', 'V', 'A', 'C', 'WYQHP', 'G', 'T', 'S', 'N', 'RK', 'D', 'E'), Grp14=c('MF',
'I', 'L', 'V', 'A', 'C', 'WYQHP', 'G', 'T', 'S', 'N', 'RK', 'D', 'E'), Grp15=c('MF', 'IL', 'V', 'A',
'C', 'WYQ', 'H', 'P', 'G', 'T', 'S', 'N', 'RK', 'D', 'E'), Grp16=c('MF', 'I', 'L', 'V', 'A', 'C',
'WYQ', 'H', 'P', 'G', 'T', 'S', 'N', 'RK', 'D', 'E'), Grp20=c('M', 'F', 'I', 'L', 'V', 'A', 'C', 'W',
'Y', 'Q', 'H', 'P', 'G', 'T', 'S', 'N', 'R', 'K', 'D', 'E')
```

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
```

```
mat1<-PseKRAAC_T15(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T15(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T16	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-16</i> (PseKRAAC_T16)
--------------	--

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type16(PseKRAAC_T16) contains Grp 2-16,20.

Usage

```
PseKRAAC_T16(
  seqs,
  type = "gap",
  Grp = 2,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups:

2=c('IMVLFWY', 'GPCASTNHQEDRK'), 3=c('IMVLFWY', 'GPCAST', 'NHQEDRK'), 4=c('IMVLFWY', 'G', 'PCAST', 'NHQEDRK'), 5=c('IMVL', 'FWY', 'G', 'PCAST', 'NHQEDRK'), 6=c('IMVL', 'FWY', 'G', 'P', 'CAST', 'NHQEDRK'), 7=c('IMVL', 'FWY', 'G', 'P', 'CAST', 'NHQED', 'RK'), 8=c('IMV', 'L', 'FWY', 'G', 'P', 'CAST', 'NHQED', 'RK'), 9=c('IMV', 'L', 'FWY', 'G', 'P', 'C', 'AST', 'NHQED', 'RK'), 10=c('IMV', 'L', 'FWY', 'G', 'P', 'C', 'A', 'STNH', 'RKQE', 'D'), 11=c('IMV', 'L', 'FWY', 'G', 'P', 'C', 'A', 'STNH', 'RKQ', 'E', 'D'), 12=c('IMV', 'L', 'FWY', 'G', 'P', 'C', 'A', 'ST', 'N', 'HRKQ', 'E', 'D'), 13=c('IMV', 'L', 'F', 'WY', 'G', 'P', 'C', 'A', 'ST', 'N', 'HRKQ', 'E', 'D'), 14=c('IMV', 'L', 'F', 'WY', 'G', 'P', 'C', 'A', 'S', 'T', 'N', 'HRKQ', 'E', 'D'), 15=c('IMV', 'L', 'F', 'WY', 'G', 'P', 'C', 'A', 'S', 'T', 'N', 'H', 'RKQ', 'E', 'D'), 16=c('IMV', 'L', 'F', 'W', 'Y', 'G', 'P', 'C', 'A', 'S', 'T', 'N', 'H', 'RKQ', 'E', 'D'), 20=c('I', 'M', 'V', 'L', 'F', 'W', 'Y', 'G', 'P', 'C', 'A', 'S', 'T', 'N', 'H', 'R', 'K', 'Q', 'E', 'D')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T16(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T16(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T2

*Pseudo K_tuple Reduced Amino Acid Composition Type-2
(PseKRAAC_T2)*

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type2(PseKRAAC_T2) contains Grp 2-6,8,15,20.

Usage

```
PseKRAAC_T2(
  seqs,
  type = "gap",
  Grp = 2,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups:

```
2=c('LVIMCAGSTPFYW', 'EDNQKRH'), 3=c('LVIMCAGSTP', 'FYW', 'EDNQKRH'), 4=c('LVIMC',
'AGSTP', 'FYW', 'EDNQKRH'), 5=c('LVIMC', 'AGSTP', 'FYW', 'EDNQ', 'KRH'), 6=c('LVIM',
'AGST', 'PHC', 'FYW', 'EDNQ', 'KR'), 8=c('LVIMC', 'AG', 'ST', 'P', 'FYW', 'EDNQ', 'KR',
'H'), 15=c('LVIM', 'C', 'A', 'G', 'S', 'T', 'P', 'FY', 'W', 'E', 'D', 'N', 'Q', 'KR', 'H'), 20=c('L',
'V', 'I', 'M', 'C', 'A', 'G', 'S', 'T', 'P', 'F', 'Y', 'W', 'E', 'D', 'N', 'Q', 'K', 'R', 'H')
```

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T2(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T2(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T3A	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-3A (PseKRAAC_T3A)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type3 contain two type: type3A and type3B. 'PseKRAAC_T3A' contains Grp 2-20.

Usage

```
PseKRAAC_T3A(
  seqs,
  type = "gap",
  Grp = 2,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: Grp2=c('AGSPDEQNHTKRMILFYVC', 'W'), Grp3=c('AGSPDEQNHTKRMILFYV', 'W', 'C'), Grp4=c('AGSPDEQNHTKRMIV', 'W', 'YFL', 'C'), Grp5=c('AGSPDEQNHTKR', 'W', 'YF', 'MIVL', 'C'), Grp6=c('AGSP', 'DEQNHTKR', 'W', 'YF', 'MIL', 'VC'), Grp7=c('AGP', 'DEQNH', 'TKRMIV', 'W', 'YF', 'L', 'CS'), Grp8=c('AG', 'DEQN', 'TKRMIV', 'HY', 'W', 'L', 'FP', 'CS'), Grp9=c('AG', 'P', 'DEQN', 'TKRMI', 'HY', 'W', 'F', 'L', 'VCS'), Grp10=c('AG', 'P', 'DEQN', 'TKRM', 'HY', 'W', 'F', 'I', 'L', 'VCS'), Grp11=c('AG', 'P', 'DEQN', 'TK', 'RI', 'H', 'Y', 'W', 'F', 'ML', 'VCS'), Grp12=c('FAS', 'P', 'G', 'DEQ', 'NL', 'TK', 'R', 'H', 'W', 'Y', 'IM', 'VC'), Grp13=c('FAS', 'P', 'G', 'DEQ', 'NL', 'T', 'K', 'R', 'H', 'W', 'Y', 'IM', 'VC'), Grp14=c('FA', 'P', 'G', 'T', 'DE', 'QM', 'NL', 'K', 'R', 'H', 'W', 'Y', 'IV', 'CS'), Grp15=c('FAS', 'P', 'G', 'T', 'DE', 'Q', 'NL', 'K', 'R', 'H', 'W', 'Y', 'M', 'I', 'VC'), Grp16=c('FA', 'P', 'G', 'ST', 'DE', 'Q', 'N', 'K', 'R', 'H', 'W', 'Y', 'M', 'L', 'I', 'VC'), Grp17=c('FA', 'P', 'G', 'S', 'T', 'DE', 'Q', 'N', 'K', 'R', 'H', 'W', 'Y', 'M', 'L', 'I', 'VC'), Grp18=c('FA', 'P', 'G', 'S', 'T', 'DE', 'Q', 'N', 'K', 'R', 'H', 'W', 'Y', 'M', 'L', 'I', 'V', 'C'), Grp19=c('FA', 'P', 'G', 'S', 'T', 'D', 'E', 'Q', 'N', 'K', 'R', 'H', 'W', 'Y', 'M', 'L', 'I', 'V', 'C'), Grp20=c('F', 'A', 'P', 'G', 'S', 'T', 'D', 'E', 'Q', 'N', 'K', 'R', 'H', 'W', 'Y', 'M', 'L', 'I', 'V', 'C')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta", package="ftrCOOL")
mat1<-PseKRAAC_T3A(seqs=filePrs, type="gap", Grp=4, GapOrLambdaValue=3, k=2)
mat2<-PseKRAAC_T3A(seqs=filePrs, type="lambda", Grp=4, GapOrLambdaValue=3, k=2)
```

PseKRAAC_T3B

*Pseudo K_tuple Reduced Amino Acid Composition Type_3B
(PseKRAAC_T3B)*

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type3 contain two type: type3A and type3B. 'PseKRAAC_T3B' contains Grp 2-20.

Usage

```
PseKRAAC_T3B(
  seqs,
  type = "gap",
  Grp = 2,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 2=c('HRKQNEDSTGPACVIM', 'LFYW'), 3=c('HRKQNEDSTGPACVIM', 'LFY', 'W'), 4=c('HRKQNEDSTGPA', 'CIV', 'MLFY', 'W'), 5=c('HRKQNEDSTGPA', 'CV', 'IML', 'FY', 'W'), 6=c('HRKQNEDSTPA', 'G', 'CV', 'IML', 'FY', 'W'), 7=c('HRKQNEDSTA', 'G', 'P', 'CV', 'IML', 'FY', 'W'), 8=c('HRKQNEDSTA', 'NED', 'G', 'P', 'CV', 'IML', 'FY', 'W'), 9=c('HRKQNEDSTA', 'ASTG', 'P', 'C', 'IV', 'MLF', 'Y', 'W'), 10=c('RKHSA', 'Q', 'NED', 'G', 'P', 'C', 'TIV', 'MLF', 'Y', 'W'), 11=c('RKQNEDSTA', 'NG', 'ED', 'AST', 'P', 'C', 'IV', 'HML', 'F', 'Y', 'W'), 12=c('RKQNEDSTA', 'ED', 'NAST', 'G', 'P', 'C', 'IV', 'H', 'ML', 'F', 'Y', 'W'), 13=c('RKQNEDSTA', 'NG', 'HA', 'ST', 'P', 'C', 'IV', 'ML', 'F', 'Y', 'W'), 14=c('R', 'K', 'QE', 'D', 'NG', 'HA', 'ST', 'P', 'C', 'IV', 'ML', 'F', 'Y', 'W'), 15=c('R', 'K', 'QE', 'D', 'NG', 'HA', 'ST', 'P', 'C', 'IV', 'M', 'L', 'F', 'Y', 'W'), 16=c('R', 'K', 'Q', 'E', 'D', 'NG', 'HA', 'ST', 'P', 'C', 'IV', 'M', 'L', 'F', 'Y', 'W'), 17=c('R', 'K', 'Q', 'E', 'D', 'NG', 'HA', 'S', 'T', 'P', 'C', 'IV', 'M', 'L', 'F', 'Y', 'W'), 18=c('R', 'K', 'Q', 'E', 'D', 'NG', 'HA', 'S', 'T', 'P', 'C', 'I', 'V', 'M', 'L', 'F', 'Y', 'W'), 19=c('R', 'K', 'Q', 'E', 'D', 'NG', 'H', 'A', 'S', 'T', 'P', 'C', 'I', 'V', 'M', 'L', 'F', 'Y', 'W'), 20=c('R', 'K', 'Q', 'E', 'D', 'N', 'G', 'H', 'A', 'S', 'T', 'P', 'C', 'I', 'V', 'M', 'L', 'F', 'Y', 'W')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T3B(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T3B(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T4	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-4 (PseKRAAC_T4)</i>
-------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type4(PseKRAAC_T4) contains Grp 5,8,9,11,13,20.

Usage

```
PseKRAAC_T4(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.

GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 5=c('G', 'IVFYW', 'ALMEQRK', 'P', 'NDHSTC'), 8=c('G', 'IV', 'FYW', 'ALM', 'EQRK', 'P', 'ND', 'HSTC'), 9=c('G', 'IV', 'FYW', 'ALM', 'EQRK', 'P', 'ND', 'HS', 'TC'), 11=c('G', 'IV', 'FYW', 'A', 'LM', 'EQRK', 'P', 'ND', 'HS', 'T', 'C'), 13=c('G', 'IV', 'FYW', 'A', 'L', 'M', 'E', 'QRK', 'P', 'ND', 'HS', 'T', 'C'), 20=c('G', 'I', 'V', 'F', 'Y', 'W', 'A', 'L', 'M', 'E', 'Q', 'R', 'K', 'P', 'N', 'D', 'H', 'S', 'T', 'C')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta", package="ftrCOOL")
mat1<-PseKRAAC_T4(seqs=filePrs, type="gap", Grp=8, GapOrLambdaValue=3, k=2)
mat2<-PseKRAAC_T4(seqs=filePrs, type="lambda", Grp=8, GapOrLambdaValue=3, k=2)
```

PseKRAAC_T5	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-5 (PseKRAAC_T5)</i>
-------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type5(PseKRAAC_T5) contains Grp 3,4,8,10,15,20.

Usage

```
PseKRAAC_T5(
  seqs,
  type = "gap",
  Grp = 4,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 3=c('FWYCILMVAGSTPHNQ', 'DE', 'KR'), 4=c('FWY', 'CILMV', 'AGSTP', 'EQNDHKR'), 8=c('FWY', 'CILMV', 'GA', 'ST', 'P', 'EQND', 'H', 'KR'), 10=c('G', 'FYW', 'A', 'ILMV', 'RK', 'P', 'EQND', 'H', 'ST', 'C'), 15=c('G', 'FY', 'W', 'A', 'ILMV', 'E', 'Q', 'RK', 'P', 'N', 'D', 'H', 'S', 'T', 'C'), 20=c('G', 'I', 'V', 'F', 'Y', 'W', 'A', 'L', 'M', 'E', 'Q', 'R', 'K', 'P', 'N', 'D', 'H', 'S', 'T', 'C')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T5(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T5(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T6A	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-6A</i> (PseKRAAC_T6A)
--------------	--

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type6 contain two type: type6A and type6B. 'PseKRAAC_T6A' contains Grp 4,5,20.

Usage

```
PseKRAAC_T6A(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 4=c('AGPST', 'CILMV', 'DEHKNQR', 'FYW'), 5=c('AHT', 'CFILMVWY', 'DE', 'GP', 'KNQRS'), 20=c('A', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'V', 'W', 'Y')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta", package="ftrCOOL")
mat1<-PseKRAAC_T6A(seqs=filePrs, type="gap", Grp=4, GapOrLambdaValue=3, k=2)
mat2<-PseKRAAC_T6A(seqs=filePrs, type="lambda", Grp=4, GapOrLambdaValue=3, k=2)
```

PseKRAAC_T6B	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-6B (PseKRAAC_T6B)</i>
--------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type6 contain two type: type6A and type6B. 'PseKRAAC_T6B' contains Grp 5.

Usage

```
PseKRAAC_T6B(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: 5=c('AEHKQRST', 'CFILMVWY', 'DN', 'G', 'P')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T6B(seqs=filePrs,type="gap",Grp=5,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T6B(seqs=filePrs,type="lambda",Grp=5,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T7	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-7 (PseKRAAC_T7)</i>
-------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type7(PseKRAAC_T7) contains Grp 2-20.

Usage

```
PseKRAAC_T7(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: Grp2=c('C', 'MFILVWYAGTSNQDEHRKP'), Grp3=c('C', 'MFILVWYAKR', 'GTSNQDEHP'), Grp4=c('C', 'KR', 'MFILVWYA', 'GTSNQDEHP'), Grp5=c('C', 'KR', 'MFILVWYA', 'DE', 'GTSNQHP'), Grp6=c('C', 'KR', 'WYA', 'MFILV', 'DE', 'GTSNQHP'), Grp7=c('C', 'KR', 'WYA', 'MFILV', 'DE', 'QH', 'GTSNP'), Grp8=c('C', 'KR', 'WYA', 'MFILV', 'D', 'E', 'QH', 'GTSNP'), Grp9=c('C', 'KR', 'WYA', 'MFILV', 'D', 'E', 'QH', 'TP', 'GSN'), Grp10=c('C', 'KR', 'WY',

```
'A', 'MFILV', 'D', 'E', 'QH', 'TP', 'GSN'), Grp11=c('C', 'K', 'R', 'WY', 'A', 'MFILV', 'D', 'E',
'QH', 'TP', 'GSN'), Grp12=c('C', 'K', 'R', 'WY', 'A', 'MFILV', 'D', 'E', 'QH', 'TP', 'GS', 'N'),
Grp13=c('C', 'K', 'R', 'W', 'Y', 'A', 'MFILV', 'D', 'E', 'QH', 'TP', 'GS', 'N'), Grp14=c('C', 'K',
'R', 'W', 'Y', 'A', 'FILV', 'M', 'D', 'E', 'QH', 'TP', 'GS', 'N'), Grp15=c('C', 'K', 'R', 'W', 'Y',
'A', 'FILV', 'M', 'D', 'E', 'Q', 'H', 'TP', 'GS', 'N'), Grp16=c('C', 'K', 'R', 'W', 'Y', 'A', 'FILV',
'M', 'D', 'E', 'Q', 'H', 'TP', 'G', 'S', 'N'), Grp17=c('C', 'K', 'R', 'W', 'Y', 'A', 'FI', 'LV', 'M',
'D', 'E', 'Q', 'H', 'TP', 'G', 'S', 'N'), Grp18=c('C', 'K', 'R', 'W', 'Y', 'A', 'FI', 'LV', 'M', 'D',
'E', 'Q', 'H', 'T', 'P', 'G', 'S', 'N'), Grp19=c('C', 'K', 'R', 'W', 'Y', 'A', 'F', 'I', 'LV', 'M', 'D',
'E', 'Q', 'H', 'T', 'P', 'G', 'S', 'N'), Grp20=c('C', 'K', 'R', 'W', 'Y', 'A', 'F', 'I', 'L', 'V', 'M',
'D', 'E', 'Q', 'H', 'T', 'P', 'G', 'S', 'N')
```

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(Grp)^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T7(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T7(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T8	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-8</i> (PseKRAAC_T8)
-------------	--

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type8(PseKRAAC_T8) contains Grp 2-20.

Usage

```
PseKRAAC_T8(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
```

```

    k = 4,
    label = c()
)

```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: Grp2=c('ADEGKNPQRST', 'CFHILMVWY'), Grp3=c('ADEGNPST', 'CHKQRW', 'FILMVY'), Grp4=c('AGNPST', 'CHWY', 'DEKQR', 'FILMV'), Grp5=c('AGPST', 'CFWY', 'DEN', 'HKQR', 'ILMV'), Grp6=c('APST', 'CW', 'DEGN', 'FHY', 'ILMV', 'KQR'), Grp7=c('AGST', 'CW', 'DEN', 'FY', 'HP', 'ILMV', 'KQR'), Grp8=c('AST', 'CG', 'DEN', 'FY', 'HP', 'ILV', 'KQR', 'MW'), Grp9=c('AST', 'CW', 'DE', 'FY', 'GN', 'HQ', 'ILV', 'KR', 'MP'), Grp10=c('AST', 'CW', 'DE', 'FY', 'GN', 'HQ', 'IV', 'KR', 'LM', 'P'), Grp11=c('AST', 'C', 'DE', 'FY', 'GN', 'HQ', 'IV', 'KR', 'LM', 'P', 'W'), Grp12=c('AST', 'C', 'DE', 'FY', 'G', 'HQ', 'IV', 'KR', 'LM', 'N', 'P', 'W'), Grp13=c('AST', 'C', 'DE', 'FY', 'G', 'H', 'IV', 'KR', 'LM', 'N', 'P', 'Q', 'W'), Grp14=c('AST', 'C', 'DE', 'FL', 'G', 'H', 'IV', 'KR', 'M', 'N', 'P', 'Q', 'W', 'Y'), Grp15=c('AST', 'C', 'DE', 'F', 'G', 'H', 'IV', 'KR', 'L', 'M', 'N', 'P', 'Q', 'W', 'Y'), Grp16=c('AT', 'C', 'DE', 'F', 'G', 'H', 'IV', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'W', 'Y'), Grp17=c('AT', 'C', 'DE', 'F', 'G', 'H', 'IV', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'W', 'Y'), Grp18=c('A', 'C', 'DE', 'F', 'G', 'H', 'IV', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'W', 'Y'), Grp19=c('A', 'C', 'D', 'E', 'F', 'G', 'H', 'IV', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'W', 'Y'), Grp20=c('A', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'V', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'W', 'Y')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is (Grp)^k.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T8(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T8(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PseKRAAC_T9	<i>Pseudo K_tuple Reduced Amino Acid Composition Type-9 (PseKRAAC_T9)</i>
-------------	---

Description

There are 16 types of PseKRAAC function. In the functions, a (user-selected) grouping of the amino acids might be used to reduce the amino acid alphabet. Also, the functions have a type parameter. The parameter determines the protein sequence analyses which can be either gap or lambda-correlation. PseKRAAC_type9(PseKRAAC_T9) contains Grp 2-20.

Usage

```
PseKRAAC_T9(
  seqs,
  type = "gap",
  Grp = 5,
  GapOrLambdaValue = 2,
  k = 4,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
type	This parameter has two valid value "lambda" and "gap". "lambda" calls lambda_model function and "gap" calls gap_model function.
Grp	is a numeric value. It shows the id of an amino acid group. Please find the available groups in the detail section.
GapOrLambdaValue	is an integer. If type is gap, this value shows number of gaps between two k-mers. If type is lambda, the value of GapOrLambdaValue shows the number of gaps between each two amino acids of k-mers.
k	This parameter keeps the value of k in k-mer.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Groups: Grp2=c('ADEGKNPQRST', 'CFHILMVWY'), Grp3=c('ADEGNPST', 'CHKQRW', 'FILMVY'), Grp4=c('AGNPST', 'CHWY', 'DEKQR', 'FILMV'), Grp5=c('AGPST', 'CFWY', 'DEN', 'HKQR', 'ILMV'), Grp6=c('APST', 'CW', 'DEGN', 'FHY', 'ILMV', 'KQR'), Grp7=c('AGST', 'CW', 'DEN', 'FY', 'HP', 'ILMV', 'KQR'), Grp8=c('AST', 'CG', 'DEN', 'FY', 'HP', 'ILV', 'KQR', 'MW'), Grp9=c('AST', 'CW', 'DE', 'FY', 'GN', 'HQ', 'ILV', 'KR', 'MP'), Grp10=c('AST', 'CW', 'DE', 'FY', 'GN', 'HQ', 'IV', 'KR', 'LM', 'P'), Grp11=c('AST', 'C', 'DE', 'FY', 'GN', 'HQ', 'IV', 'KR', 'LM', 'P', 'W'), Grp12=c('AST', 'C', 'DE', 'FY', 'G', 'HQ', 'IV', 'KR', 'LM', 'N', 'P', 'W'), Grp13=c('AST', 'C', 'DE', 'FY', 'G', 'H', 'IV', 'KR', 'LM', 'N', 'P', 'Q', 'W'), Grp14=c('AST', 'C', 'DE', 'FL', 'G', 'H', 'IV', 'KR', 'M', 'N', 'P', 'Q', 'W', 'Y'), Grp15=c('AST', 'C', 'DE', 'F', 'G', 'H', 'IV', 'KR', 'L', 'M', 'N', 'P', 'Q', 'W', 'Y'), Grp16=c('AT', 'C', 'DE', 'F', 'G', 'H', 'IV', 'KR', 'L', 'M', 'N', 'P', 'Q', 'S', 'W', 'Y'), Grp17=c('AT', 'C', 'DE', 'F', 'G', 'H', 'IV', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'W', 'Y'), Grp18=c('A', 'C', 'DE', 'F', 'G', 'H', 'IV', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'W', 'Y'), Grp19=c('A', 'C', 'D', 'E', 'F', 'G', 'H', 'IV', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'W', 'Y'), Grp20=c('A', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'V', 'K', 'L', 'M', 'N', 'P', 'Q', 'R', 'S', 'T', 'W', 'Y')

Value

This function returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(\text{Grp})^k$.

References

Zuo, Yongchun, et al. "PseKRAAC: a flexible web server for generating pseudo K-tuple reduced amino acids composition." *Bioinformatics* 33.1 (2017): 122-124.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat1<-PseKRAAC_T9(seqs=filePrs,type="gap",Grp=4,GapOrLambdaValue=3,k=2)
mat2<-PseKRAAC_T9(seqs=filePrs,type="lambda",Grp=4,GapOrLambdaValue=3,k=2)
```

PSSM

*Position-Specific Scoring Matrix (PSSM)***Description**

This functions receives as input PSSM matrices (which are created by PSI-BLAST software) and converts them into feature vectors.

Usage

```
PSSM(dirPath, outFormat = "mat", outputFileDist = "")
```


Arguments

- `dirPath` Path of the directory which contains all output files of PSI-BLAST. Each file belongs to a sequence.
- `outFormat` It can take two values: 'mat' (which stands for matrix) and 'txt'. The default value is 'mat'.
- `outputFileDist` It shows the path and name of the 'txt' output file.

Value

The output depends on the `outFormat` parameter which can be either 'mat' or 'txt'. If `outFormat` is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length)*(20) and the number of rows is equal to the number of sequences. If the `outFormat` is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in `outFormat` for sequences with different lengths. Warning: If `outFormat` is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes if sequences have different sizes. Otherwise 'txt' format is also usable for machine learning purposes.

Examples

```
dir = tempdir()
ad<-paste0(dir, "/pssm.txt")

PSSMdir<-system.file("testFolder", package="ftrCOOL")
PSSMdir<-paste0(PSSMdir, "/PSSMdir/")
mat<-PSSM(PSSMdir, outFormat="txt", outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

PSTNPs	<i>Position-Specific Trinucleotide Propensity based on double-strand (PSTNPs)</i>
--------	---

Description

This function works like [PSTNPss_DNA](#) except that it considers T as A and G as C. So it converts Ts in the sequence to A and Gs to C. Then, it works with 2 alphabets A and C. For more details refer to [PSTNPss_DNA](#).

Usage

```
PSTNPs(seqs, pos, neg, label = c())
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
pos	is a fasta file containing amino acid sequences. Each sequence starts with '>'. Also, the value of this parameter can be a string vector. Each element of the vector is a peptide/protein sequence. The sequences are positive sequences in the training model
neg	is a fasta file containing amino acid sequences. Each sequence starts with '>'. Also, the value of this parameter can be a string vector. Each element of the vector is a peptide/protein sequence.
label	is an optional parameter. It is a vector whose length is equal to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

It returns a feature matrix. The number of columns is equal to the length of sequences minus two and the number of rows is equal to the number of sequences.

Note

The length of the sequences in positive and negative data sets and the input sets should be equal.

References

Chen, Zhen, et al. "iLearn: an integrated platform and meta-learner for feature engineering, machine-learning analysis and modeling of DNA, RNA and protein sequence data." *Briefings in bioinformatics* 21.3 (2020): 1047-1057.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")

posSeqs<-fa.read(file=paste0(ptmSeqsADR,"/posData.txt"),alphabet="dna")
negSeqs<-fa.read(file=paste0(ptmSeqsADR,"/negData.txt"),alphabet="dna")
seqs<-fa.read(file=paste0(ptmSeqsADR,"/testData.txt"),alphabet="dna")

PSTNPDs(seqs=seqs,pos=posSeqs[1],neg=negSeqs[1])
```

PSTNPss_DNA	<i>Position-Specific Trinucleotide Propensity based on single-strand DNA (PSTNPss_DNA)</i>
-------------	--

Description

The inputs to this function are positive and negative data sets and a set of sequences. The output of the function is a matrix of feature vectors. The number of rows of the output matrix is equal to the number of sequences. The feature vector for an input sequence with length L is $[u(1), u(2), \dots, u(L-2)]$. For each input sequence, $u(1)$ is calculated by subtracting the frequency of sequences (which start with the same trinucleotides as the input sequence) in the positive set with those starting with the same trinucleotide in the negative set. We compute $u(i)$ like $u(1)$ with the exception that instead of the first trinucleotide, the i th trinucleotide is considered.

Usage

```
PSTNPss_DNA(seqs, pos, neg, label = c())
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
pos	is a fasta file containing amino acid sequences. Each sequence starts with '>'. Also, the value of this parameter can be a string vector. Each element of the vector is a peptide/protein sequence. The sequences are positive sequences in the training model
neg	is a fasta file containing amino acid sequences. Each sequence starts with '>'. Also, the value of this parameter can be a string vector. Each element of the vector is a peptide/protein sequence.
label	is an optional parameter. It is a vector whose length is equal to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

It returns a feature matrix. The number of columns is equal to the length of sequences minus two and the number of rows is equal to the number of sequences.

Note

The length of the sequences in positive and negative data sets and the input sets should be equal.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")

posSeqs<-fa.read(file=paste0(ptmSeqsADR,"/posDNA.txt"),alphabet="dna")
negSeqs<-fa.read(file=paste0(ptmSeqsADR,"/negDNA.txt"),alphabet="dna")
seqs<-fa.read(file=paste0(ptmSeqsADR,"/DNA_testing.txt"),alphabet="dna")

mat=PSTNPss_DNA(seqs=seqs,pos=posSeqs,neg=negSeqs)
```

PSTNPss_RNA	<i>Position-Specific Tri-ribonucleotide Propensity based on single-strand RNA (PSTNPss_RNA)</i>
-------------	---

Description

The inputs to this function are positive and negative data sets and a set of sequences. The output of the function is a matrix of feature vectors. The number of rows of the output matrix is equal to the number of sequences. The feature vector for an input sequence with length L is $[u(1), u(2), \dots, u(L-2)]$. For each input sequence, $u(1)$ is calculated by subtracting the frequency of sequences (which start with the same tri-ribonucleotides as the input sequence) in the positive set with those starting with the same tri-ribonucleotide in the negative set. We compute $u(i)$ like $u(1)$ with the exception that instead of the first tri-ribonucleotide, the i th tri-ribonucleotide is considered.

Usage

```
PSTNPss_RNA(seqs, pos, neg, label = c())
```

Arguments

seqs	is a FASTA file containing ribonucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a ribonucleotide sequence.
pos	is a fasta file containing amino acid sequences. Each sequence starts with '>'. Also, the value of this parameter can be a string vector. Each element of the vector is a peptide/protein sequence. The sequences are positive sequences in the training model
neg	is a fasta file containing amino acid sequences. Each sequence starts with '>'. Also, the value of this parameter can be a string vector. Each element of the vector is a peptide/protein sequence.
label	is an optional parameter. It is a vector whose length is equal to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

It returns a feature matrix. The number of columns is equal to the length of sequences minus two and the number of rows is equal to the number of sequences.

Note

The length of the sequences in positive and negative data sets and the input sets should be equal.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")

posSeqs<-fa.read(file=paste0(ptmSeqsADR,"/pos2RNA.txt"),alphabet="rna")
negSeqs<-fa.read(file=paste0(ptmSeqsADR,"/neg2RNA.txt"),alphabet="rna")
seqs<-fa.read(file=paste0(ptmSeqsADR,"/testSeq2RNA.txt"),alphabet="rna")

PSTNPss_RNA(seqs=seqs,pos=posSeqs,neg=negSeqs)
```

QSOrder

Quasi Sequence Order (QSOrder)

Description

This function computes the quasi-sequence-order for sequences. It is for amino acid pairs with d distances (d can be any number between 1 and 20). First, it calculates the frequencies of each amino acid ("A", "C", ..., "Y"). Then, it normalizes the frequencies by dividing the frequency of an amino acid to the frequency of all amino acids plus the sum of tau values which is multiplied by W . tau values are given by function [SOCNumber](#). For d bigger than 20, it computes tau for d in the range "1 to $(nlag-20) * W$ " and normalizes them like before.

Usage

```
QSOrder(seqs, nlag = 25, W = 0.1, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
nlag	is a numeric value which shows the maximum distance between two amino acids. Distances can be 1, 2, ..., or nlag.

W (weight) is a tuning parameter.
 label is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Details

Please find details about tau in function [SOCNumber](#).

Value

It returns a feature matrix which the number of rows equals to the number of sequences and the number of columns is (nlag*2). For each distance d, there are two values. One value for Granthman and another one for Schneider distance.

Note

For d between 21 to nlag, the function calculates tau values for (d-20) to (nlag-20).

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-QSOrder(seqs=filePrs,nlag=25)
```

readASAdir	<i>Read Directory of Accessible Solvent accessibility predicted files (readASAdir)</i>
------------	--

Description

This function reads a directory that contains the output files of SPINE-X. It gets the directory path as the input and returns a list of vectors. Each vector includes the ASA predicted value for amino acids of the sequence.

Usage

```
readASAdir(dirPath)
```

Arguments

dirPath path of the directory which contains all the output files of SPINE-X. Each file belongs to a sequence.

Value

a list of vectors with all the predicted ASA value for each amino acid. The length of the list is the number of files(sequences) and the length of each vector is (length of sequence(i))

Examples

```
PredASAdir<-system.file("testForder",package="ftrCOOL")
PredASAdir<-paste0(PredASAdir,"/ASAdir/")
PredVectASA<-readASAdir(PredASAdir)
```

readDisDir	<i>Read disorder predicted Directory (readDisDir)</i>
------------	---

Description

This function reads a directory that contains the output VSL2 files. It gets the directory path as the input and returns a list of vectors. Each vector includes the disorder/order type for the amino acids of the sequence.

Usage

```
readDisDir(dirPath)
```

Arguments

dirPath the path of a directory which contains all the VSL2 output files.

Value

a list of vectors with all the predicted disorder/order type for each amino acid. The length of the list is equal to the number of files(sequences) and the length of each vector is the length of the sequence(i).

Examples

```
PredDisdir<-system.file("testForder",package="ftrCOOL")
PredDisdir<-paste0(PredDisdir,"/Disdir/")
listPredVect<-readDisDir(PredDisdir)
```

readPSSMdir	<i>Read PSSM Directory (readPSSMdir)</i>
-------------	--

Description

This function reads a directory that contains the output psi-blast. It gets the directory path as the input and returns a list of vectors. Each vector includes the type for the amino acids of the sequence.

Usage

```
readPSSMdir(dirPath)
```

Arguments

dirPath the path of a directory which contains all the VSL2 output files.

Value

a list of vectors with all the predicted disorder/order type for each amino acid. The length of the list is equal to the number of files(sequences) and the length of each vector is the length of the sequence(i).

Examples

```
pssmDir<-system.file("testForder",package="ftrCOOL")
pssmDir<-paste0(pssmDir,"/PSSMdir/")
listPredVect<-readPSSMdir(pssmDir)
```

readss2Dir	<i>Read ss2 predicted Directory (readss2Dir)</i>
------------	--

Description

This function reads a directory that contains the output files of PSIPRED It gets the directory path as the input and returns a list of vectors. Each vector contains the secondary structure of the amino acids in a peptide/protein sequence.

Usage

```
readss2Dir(dirPath)
```

Arguments

dirPath The path of the directory which contains all predss2 files. Each file belongs to a sequence.

Value

returns a list of vectors with all the predicted secondary structure for each amino acid. The length of the list is the number of files(sequences) and the length of each vector is (length sequence(i))

Examples

```
PredSS2dir<-system.file("testForder",package="ftrCOOL")
PredSS2dir<-paste0(PredSS2dir,"/ss2Dir/")
listPredVect<-readss2Dir(PredSS2dir)
```

readTorsionDir	<i>Read Directory of Torsion predicted files (readTorsionDir)</i>
----------------	---

Description

This function reads a directory that contains the output files of SPINE-X. It gets the directory path as the input and returns a list of vectors. Each vector includes the phi and psi angle of the amino acids of the sequence.

Usage

```
readTorsionDir(dirPath)
```

Arguments

dirPath	The path of the directory which contains all output files of SPINE-X. Each file belongs to a sequence.
---------	--

Value

returns a list of vectors with all the predicted phi and psi angles for each amino acid. The length of the list is the number of files(sequences) and the length of each vector is (2(phi-psi)*length sequence(i)).

Examples

```
PredTorsioNdir<-system.file("testForder",package="ftrCOOL")
PredTorsioNdir<-paste0(PredTorsioNdir,"/TorsioNdir/")
PredVectASA<-readTorsionDir(PredTorsioNdir)
```

revComp	<i>reverseCompelement (revComp)</i>
---------	-------------------------------------

Description

This function returns the reverse complemant of a dna sequence.

Usage

```
revComp(seq, outputType = "str")
```

Arguments

seq	is a dna sequence.
outputType	this parameter can take two values: 'char' or 'str'. If outputType is 'str', the reverse complement sequence of the input sequence is returned as a string. Otherwise, a vector of characters which represent the reverse complement is returned. Default value is 'str'.

Value

The reverse complement of the input sequence.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
Seq<-ptmSeqsVect[1]
revCompSeq<-revComp(seq=Seq,outputType="char")
```

SAAC	<i>Splitted Amino Acid Composition (SAAC)</i>
------	---

Description

This function splits the input sequence into three parts. The first part is N-terminal and the third part is C-terminal and middle part contains all amino acids between these two part. N-terminal will be determined by the first numNterm amino acid in the sequences and C-terminal is determined by numCterm of the last amino acids in the sequence. Users should enter numNterm and numCterm parameters. Their default value is 25. The function calculates [kAAComposition](#) for each of the three parts.

Usage

```
SAAC(seqs, k = 1, numNterm = 5, numCterm = 5, normalized = TRUE, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
k	shows which type of amino acid composition applies to the parts. For example, the amino acid composition is applied when k=1 and when k=2, the dipeptide Composition is applied.
numNterm	shows how many amino acids should be considered for N-terminal.
numCterm	shows how many amino acids should be considered for C-terminal.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

It returns a feature matrix. The number of rows is equal to the number of sequences. The number of columns is $(3 \cdot (20^k))$.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-SAAC(seqs=filePrs,k=1,numNterm=15,numCterm=15)
```

SGAAC

Splitted Group Amino Acid Composition (SGAAC)

Description

In this function, amino acids are first grouped into a user-defined category. Later, the splitted amino Acid composition is computed. Please note that this function differs from [SAAC](#) which works on individual amino acids.

Usage

```
SGAAC(
  seqs,
  k = 1,
  numNterm = 25,
  numCterm = 25,
  Grp = "locFus",
  normalized = TRUE,
  label = c()
)
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
k	shows which type of amino acid composition applies to the parts. For example, the amino acid composition is applied when k=1 and when k=2, the dipeptide Composition is applied.
numNterm	shows how many amino acids should be considered for N-terminal.
numCterm	shows how many amino acids should be considered for C-terminal.
Grp	is a list of vectors containig amino acids. Each vector represents a category. Users can define a customized amino acid grouping, provided that the sum of all amino acids is 20 and there is no repeated amino acid in the groups. Also, users can choose 'cTriad'(conjointTriad), 'locFus', or 'aromatic'. Each option provides specific information about the type of an amino acid grouping.
normalized	is a logical parameter. When it is FALSE, the return value of the function does not change. Otherwise, the return value is normalized using the length of the sequence.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

It returns a feature matrix. The number of rows is equal to the number of sequences. The number of columns is $3*((\text{number of groups})^k)$.

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-SGAAC(seqs=filePrs,k=1,numNterm=15,numCterm=15,Grp="aromatic")
```

SOCNumber

Sequence Order Coupling Number (SOCNumber)

Description

This function uses dissimilarity matrices Grantham and Schneider to compute the dissimilarity between amino acid pairs. The distance between amino acid pairs is determined by d which varies between 1 to nlag. For each d, it computes the sum of the dissimilarities of all amino acid pairs. The sum shows the value of tau for a value d. The feature vector contains the values of taus for both matrices. Thus, the length of the feature vector is equal to nlag*2.

Usage

```
SOCNumber(seqs, nlag = 30, label = c())
```

Arguments

seqs	is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.
nlag	is a numeric value which shows the maximum distance between two amino acids. Distances can be 1, 2, ..., or nlag. Default is 30.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

Value

It returns a feature matrix. The number of rows is equal to the number of sequences and the number of columns is $(nlag*2)$. For each distance d , there are two values. One value for Granthman and another one for Schneider distance.

Note

When $d=1$, the pairs of amino acids have no gap and when $d=2$, there is one gap between the amino acid pairs in the sequence. It will repeat likewise for other values of d .

Examples

```
filePrs<-system.file("extdata/proteins.fasta",package="ftrCOOL")
mat<-SOCNumber(seqs=filePrs,nlag=25)
```

SSEB

Secondary Structure Elements Binary (SSEB)

Description

This function works based on the output of PSIPRED which predicts the secondary structure of the amino acids in a sequence. The output of the PSIPRED is a tab-delimited file which contains the secondary structure in the third column. SSEB gives a binary number (i.e., '001'='H', '010'='E', '100'='C') for each amino acid.

Usage

```
SSEB(dirPath, binaryType = "strBin", outFormat = "mat", outputFileDist = "")
```

Arguments

dirPath	Path of the directory which contains all output files of PSIPRED. Each file belongs to a sequence.
binaryType	It can take any of the following values: ('strBin','logicBin','numBin'). 'strBin'(String binary): each structure is represented by a string containing 3 characters(0-1). Helix = "001" , Extended = "010" , coil = "100". 'logicBin'(logical value): Each structure is represented by a vector containing 3 logical entries. Helix = c(FALSE,FALSE,TRUE) , Extended = c(FALSE,TRUE,FALSE) , Coil = c(TRUE,FALSE,FALSE). 'numBin' (numeric bin): Each structure is represented by a numeric (i.e., integer) vector containing 3 numerals. Helix = c(0,0,1) , Extended = c(0,1,0) , coil = c(1,0,0).
outFormat	It can take two values: 'mat' (which stands for matrix) and 'txt'. The default value is 'mat'.
outputFileDist	It shows the path and name of the 'txt' output file.

Details

This function converts each amino acid to a 3-bit value, such that 2 bits are 0 and 1 bit is 1. The position of 1 shows the type of the secondary structure of the amino acids in the protein/peptide. In this function, '001' is used to show Helix structure, '010' to show Extended structure and '100' to show coil structure.

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and if binaryType is 'strBin', the number of columns is the length of the sequences. Otherwise, it is equal to (length of the sequences)*3. If outFormat is 'txt', all binary values will be written to a tab-delimited file. Each line in the file shows the binary format of a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in the outFormat parameter for sequences with different lengths. Warning: If the outFormat is set to 'mat' for sequences with different lengths, it returns an error. It is noteworthy that 'txt' format is not usable for machine learning purposes.

Examples

```
dir = tempdir()
ad<-paste0(dir,"/SSEB.txt")

Predss2dir<-system.file("testForder",package="ftrCOOL")
Predss2dir<-paste0(Predss2dir,"/ss2Dir/")
mat<-SSEB(Predss2dir,binaryType="strBin",outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

SSEC*Secondary Structure Elements Composition (SSEC)*

Description

This function works based on the output of PSIPRED which predicts the secondary structure of the amino acids in a sequence. The output of the PSIPRED is a tab-delimited file which contains the secondary structure in the third column. SSEC returns the frequency of the secondary structures (i.e., Helix, Extended, Coil) of the sequences.

Usage

```
SSEC(dirPath)
```

Arguments

`dirPath` Path of the directory which contains all output files of PSIPRED. Each file belongs to a sequence.

Value

It returns a feature matrix which the number of rows is the number of sequences and the number of columns is 3. The first column shows the number of amino acids which participate in the coil structure. The second column shows the number of amino acids in the extended structure and the last column shows the number of amino acids in the helix structure.

Examples

```
Predss2dir<-system.file("testFolder", package="ftrCOOL")
Predss2dir<-paste0(Predss2dir, "/ss2Dir/")
mat<-SSEC(Predss2dir)
```

SSES*Secondary Structure Elements Simple (SSES)*

Description

This function works based on the output of PSIPRED which predicts the secondary structure of the amino acids in a sequence. The output of the PSIPRED is a tab-delimited file which contains the secondary structure in the third column. The function represent amino acids in the helix structure by 'H', amino acids in the extended structure by 'E', and amino acids in the coil structure by 'C'.

Usage

```
SSES(dirPath, outFormat = "mat", outputFileDist = "")
```

Arguments

dirPath	Path of the directory which contains all output files of PSIPRED. Each file belongs to a sequence.
outFormat	It can take two values: 'mat' (which stands for matrix) and 'txt'. The default value is 'mat'.
outputFileDist	It shows the path and name of the 'txt' output file.

Value

The output depends on the outFormat which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same lengths such that the number of columns is equal to the length of the sequences and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for the sequences with the same lengths. However, the users can use 'txt' option in the outFormat parameter for sequences with different lengths. Warning: If the outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when the output format is 'txt', the label information is not displayed in the text file. It is noteworthy that, 'txt' format is not usable for machine learning purposes.

Examples

```
dir = tempdir()
ad<-paste0(dir,"/simpleSSE.txt")

Predss2dir<-system.file("testForder",package="ftrCOOL")
Predss2dir<-paste0(Predss2dir,"/ss2Dir/")
mat<-SSES(Predss2dir,outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

TorsionAngle

Torsion Angle (TorsionAngle)

Description

The inputs to this function are phi and psi angles of each amino acid in the sequence. We use the output of SPINE-X software to obtain the angles. Further, the TA function replaces each amino acid of the sequence with a vector. The vector contain two elements: The phi and psi angles.

Usage

```
TorsionAngle(dirPath, outFormat = "mat", outputFileDist = "")
```

Arguments

dirPath Path of the directory which contains all output files of SPINE-X. Each file belongs to a sequence.

outFormat It can take two values: 'mat' (which stands for matrix) and 'txt'. The default value is 'mat'.

outputFileDist It shows the path and name of the 'txt' output file.

Value

The output is different depending on the outFormat parameter ('mat' or 'txt'). If the outFormat is set to 'mat', it returns a feature matrix for sequences with the same lengths. The number of rows is equal to the number of sequences and the number of columns is (length of the sequence)*2. If the outFormat is set to 'txt', all binary values will be written in a 'txt' file. Each row belongs to a sequence.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat parameter for sequences with different lengths. Warning: If the outFormat is set to 'mat' for sequences with different lengths, it returns an error. It is noteworthy that 'txt' format is not usable for machine learning purposes.

Examples

```
dir = tempdir()
ad<-paste0(dir,"/ta.txt")

PredTorsioNdir<-system.file("testFolder",package="ftrCOOL")
PredTorsioNdir<-paste0(PredTorsioNdir,"/TorsioNdir/")
mat<-TorsionAngle(PredTorsioNdir,outFormat="txt",outputFileDist=ad)

unlink("dir", recursive = TRUE)
```

TriNUCindex_DNA

Tri Nucleotide Index (TriNucIndex)

Description

This function replaces trinucleotides in a sequence with their physicochemical properties in the trinucleotide index file.

Usage

```
TriNUCindex_DNA(
  seqs,
  selectedNucIdx = c("Dnase I", "Bendability (DNase)"),
  threshold = 1,
  label = c(),
  outFormat = "mat",
  outputFileDist = ""
)
```

Arguments

seqs	is a FASTA file containing nucleotide sequences. The sequences start with '>'. Also, seqs could be a string vector. Each element of the vector is a nucleotide sequence.
selectedNucIdx	TriNucIndex function works based on physicochemical properties. Users, select the properties by their ids or indexes in TRI_DNA index file. The default values of the vector are the ids in "Dnase I", "Bendability (DNase)".
threshold	is a number between 0 to 1. In selectedNucIdx, indices with a correlation higher than the threshold will be deleted. The default value is 1.
label	is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).
outFormat	(output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.
outputFileDist	shows the path and name of the 'txt' output file.

Details

There are 12 physicochemical indexes in the trinucleotide database.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length)*(number of selected trinucleotide properties) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat parameter for sequences with different lengths. **Warning:** If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes.

Examples

```
fileLNC<-system.file("extdata/Athaliana1.fa",package="ftrCOOL")
vect<-TriNUCindex_DNA(seqs = fileLNC,threshold=1,outFormat="mat")
```

zSCALE

*Z-SCALE (zSCALE)***Description**

This function converts the amino acids of a sequence to five physicochemical descriptor variables which were developed by Sandberg et al. in 1998. The Z-SCALE function can be applied to encode peptides of equal length.

Usage

```
zSCALE(seqs, label = c(), outFormat = "mat", outputFileDist = "")
```

Arguments

seqs is a FASTA file with amino acid sequences. Each sequence starts with a '>' character. Also, seqs could be a string vector. Each element of the vector is a peptide/protein sequence.

label is an optional parameter. It is a vector whose length is equivalent to the number of sequences. It shows the class of each entry (i.e., sequence).

outFormat (output format) can take two values: 'mat'(matrix) and 'txt'. The default value is 'mat'.

outputFileDist shows the path and name of the 'txt' output file.

Value

The output depends on the outFormat parameter which can be either 'mat' or 'txt'. If outFormat is 'mat', the function returns a feature matrix for sequences with the same length such that the number of columns is (sequence length)*(5) and the number of rows is equal to the number of sequences. If the outFormat is 'txt', the output is written to a tab-delimited file.

Note

This function is provided for sequences with the same lengths. Users can use 'txt' option in outFormat parameter for sequences with different lengths. **Warning:** If outFormat is set to 'mat' for sequences with different lengths, it returns an error. Also, when output format is 'txt', label information is not shown in the text file. It is noteworthy that 'txt' format is not usable for machine learning purposes.

Examples

```
ptmSeqsADR<-system.file("extdata/",package="ftrCOOL")
ptmSeqsVect<-as.vector(read.csv(paste0(ptmSeqsADR,"/ptmVect101AA.csv"))[,2])
mat<-zSCALE(seqs = ptmSeqsVect,outFormat="mat")
```

Index

AA2Binary, 4
AAindex, 6
AAKpartComposition, 7, 63
AAutoCor, 8
alphabetCheck, 10
ANF_DNA, 11
ANF_RNA, 12
APAAC, 13
APkNUCdi_DNA, 14
APkNUCdi_RNA, 15
APkNUCTri_DNA, 17
ASA, 18
AutoCorDiNUC_DNA, 19
AutoCorDiNUC_RNA, 21
AutoCorTriNUC_DNA, 22

BLOSUM62, 24

CkSAApair, 25, 26
CkSGAAspair, 26
CkSNUCpair_DNA, 27
CkSNUCpair_RNA, 28
codonAdaptionIndex, 30
CodonFraction, 31
CodonUsage_DNA, 31
CodonUsage_RNA, 32
conjointTriad, 33
conjointTriadKS, 34
CTD, 35, 36, 37
CTDC, 35, 36
CTDD, 35, 37
CTDT, 35, 37

DDE, 38, 65
DiNUC2Binary_DNA, 39
DiNUC2Binary_RNA, 40
DiNUCindex_DNA, 42
DiNUCindex_RNA, 43
DisorderB, 44
DisorderC, 46

DisorderS, 47

EAAComposition, 48, 50
EffectiveNumberCodon, 49
EGAAComposition, 50
EIIP, 52
ENUComposition_DNA, 53
ENUComposition_RNA, 54
ExpectedValKmerNUC_DNA, 55
ExpectedValKmerNUC_RNA, 56
ExpectedValueAA, 58, 58
ExpectedValueGAA, 58
ExpectedValueGKmerAA, 59
ExpectedValueKmerAA, 60, 61

fa.read, 62
fickettScore, 63

G_Ccontent_DNA, 66
G_Ccontent_RNA, 67
GAAKpartComposition, 63
GrpDDE, 65

kAAComposition, 68, 69, 138
kGAAComposition, 69
KNNPeptide, 70, 71
KNNProtein, 71
kNUComposition_DNA, 73
kNUComposition_RNA, 74

LocalPoSpKAAF, 75
LocalPoSpKNUCF_DNA, 76
LocalPoSpKNUCF_RNA, 77

maxORF, 79
maxORF_RNA, 81
maxORFlength_DNA, 80
maxORFlength_RNA, 81

nameKmer, 82
NCP_DNA, 83

NCP_RNA, [84](#)
needleman, [86](#)
nonStandardSeq, [87](#)
NUC2Binary_DNA, [87](#)
NUC2Binary_RNA, [89](#)
NUCKpartComposition_DNA, [90](#)
NUCKpartComposition_RNA, [91](#)

PCPseDNC, [93](#)
PSEAAC, [94](#)
PseEIIP, [96](#)
PSEkNUCdi_DNA, [93](#), [97](#)
PSEkNUCdi_RNA, [98](#)
PSEkNUCTri_DNA, [99](#)
PseKRAAC_T1, [101](#)
PseKRAAC_T10, [102](#)
PseKRAAC_T11, [104](#)
PseKRAAC_T12, [106](#)
PseKRAAC_T13, [107](#)
PseKRAAC_T14, [109](#)
PseKRAAC_T15, [110](#)
PseKRAAC_T16, [112](#)
PseKRAAC_T2, [113](#)
PseKRAAC_T3A, [115](#)
PseKRAAC_T3B, [116](#)
PseKRAAC_T4, [118](#)
PseKRAAC_T5, [119](#)
PseKRAAC_T6A, [121](#)
PseKRAAC_T6B, [122](#)
PseKRAAC_T7, [124](#)
PseKRAAC_T8, [125](#)
PseKRAAC_T9, [127](#)
PSSM, [128](#)
PSTNPds, [129](#)
PSTNPss_DNA, [129](#), [131](#)
PSTNPss_RNA, [132](#)

QSOrder, [133](#)

readASAdir, [134](#)
readDisDir, [135](#)
readPSSMdir, [136](#)
readss2Dir, [136](#)
readTorsionDir, [137](#)
revComp, [138](#)

SAAC, [138](#), [139](#)
SGAAC, [139](#)
SOCNumber, [133](#), [134](#), [140](#)

SSEB, [141](#)
SSEC, [143](#)
SSES, [143](#)

TorsionAngle, [144](#)
TriNUCindex_DNA, [145](#)

zSCALE, [147](#)