

Package ‘giscoR’

October 13, 2020

Type Package

Title Download Geospatial Data from GISCO API - Eurostat

Version 0.1.0

Description Tools to download data from the GISCO
(Geographic Information System of the Commission) Eurostat database
<<https://ec.europa.eu/eurostat/web/gisco>>.
This package is in no way officially related to or endorsed by Eurostat.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

BugReports <https://github.com/dieghernan/giscoR/issues>

URL <https://dieghernan.github.io/giscoR/>,
<https://github.com/dieghernan/giscoR>

Depends R (>= 3.3.0)

Imports sf (>= 0.9), countrycode (>= 1.2.0), geojsonsf (>= 2.0)

Suggests cartography (>= 2.0.0), colorspace, eurostat, lwgeom,
tinytest, knitr, rmarkdown

Date 2020-10-05

VignetteBuilder knitr

SystemRequirements GDAL (>= 2.0.1), GEOS (>= 3.4.0), PROJ.4 (>= 4.8.0)

NeedsCompilation no

Author Diego Hernangómez [aut, cre] (<<https://orcid.org/0000-0001-8457-4658>>)

Maintainer Diego Hernangómez <diego.hernangomezherrero@gmail.com>

Repository CRAN

Date/Publication 2020-10-13 14:30:02 UTC

R topics documented:

giscoR-package	2
gisco_attributions	3
gisco_coastallines	4
gisco_countries	5
gisco_countrycode	6
gisco_get_coastallines	7
gisco_get_communes	8
gisco_get_countries	10
gisco_get_lau	12
gisco_get_nuts	14
gisco_get_urban_audit	16
gisco_nuts	18
Index	19

giscoR-package	<i>Download geospatial data from GISCO API - Eurostat</i>
----------------	---

Description

giscoR is a API package that helps to retrieve data from Eurostat - GISCO (the Geographic Information System of the COMmission)

Details

giscoR package

Package:	giscoR
Type:	Package
Version:	See sessionInfo() or DESCRIPTION file
Date:	2020
License:	GPL-3
LazyLoad:	yes

Note

COPYRIGHT NOTICE

When data downloaded from [this page](#) is used in any printed or electronic publication, in addition to any other provisions applicable to the whole Eurostat website, data source will have to be acknowledged in the legend of the map and in the introductory page of the publication with the following copyright notice:

- EN: (C) EuroGeographics for the administrative boundaries
- FR: (C) EuroGeographics pour les limites administratives
- DE: (C) EuroGeographics bezüglich der Verwaltungsgrenzen

For publications in languages other than English, French or German, the translation of the copyright notice in the language of the publication shall be used.

If you intend to use the data commercially, please contact EuroGeographics for information regarding their licence agreements.

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

[GISCO webpage](#)

References

See citation("giscoR")

See Also

Useful links:

- <https://dieghernan.github.io/giscoR/>
- <https://github.com/dieghernan/giscoR>
- Report bugs at <https://github.com/dieghernan/giscoR/issues>

gisco_attributions

Attribution when publishing GISCO data

Description

Get the legal text to be used along with the data downloaded with this package

Usage

```
gisco_attributions(lang = "en", copyright = FALSE)
```

Arguments

lang	Language (two-letter ISO_639-1 code). See details.
copyright	Boolean. Whether to display the copyright notice or not on the console.

Details

Current languages supported are "en" (English), "da" (Danish), "de" (German), "es" (Spanish), "fi" (Finnish), "fr" (French), "no" (Norwegian) and "sv" (Swedish).

Consider contributing if you spot any mistake or want to add a new language.

Value

A string with the attribution to be used.

Note**COPYRIGHT NOTICE**

When data downloaded from [this page](#) is used in any printed or electronic publication, in addition to any other provisions applicable to the whole Eurostat website, data source will have to be acknowledged in the legend of the map and in the introductory page of the publication with the following copyright notice:

- EN: (C) EuroGeographics for the administrative boundaries
- FR: (C) EuroGeographics pour les limites administratives
- DE: (C) EuroGeographics bezüglich der Verwaltungsgrenzen

For publications in languages other than English, French or German, the translation of the copyright notice in the language of the publication shall be used.

If you intend to use the data commercially, please contact EuroGeographics for information regarding their licence agreements.

Examples

```
en <- gisco_attributions()
gisco_attributions(lang = "es", copyright = TRUE )
gisco_attributions(lang = "XXX")
```

gisco_coastallines	<i>World coastal lines POLYGON object</i>
--------------------	---

Description

A sf object as provided by GISCO (2016 version).

Format

A POLYGON data frame (resolution: 1:20million, EPSG:4326) object with 8 variables:

FID FID

COAS_ID COAS_ID

geometry geometry field

Source

[GISCO .geojson source](#)

See Also[gisco_get_coastallines](#)**Examples**

```
library(sf)

coasts <- gisco_coastallines

plot(
  st_geometry(coasts),
  xlim = c(100, 120),
  ylim = c(-24, 24),
  col = "grey90",
  border = "deepskyblue4",
  lwd = 2
)
box()
title(
  main = "Coasts on Southeastern Asia",
  sub = gisco_attributions(),
  cex.sub = 0.7,
  line = 1
)
```

gisco_countries

*World countries POLYGON object***Description**

A sf object including all countries as provided by GISCO (2016 version).

Format

A MULTIPOLYGON data frame (resolution: 1:20million, EPSG:4326) object with 257 rows and 7 variables:

id row ID

CNTR_NAME Official country name on local language

ISO3_CODE **ISO 3166-1 alpha-3 code** of each country, as provided by GISCO

CNTR_ID Country ID

NAME_ENGL Country name in English

FID FID

geometry geometry field

Source

GISCO **.geojson source**

See Also

[gisco_get_countries](#)

Examples

```
library(sf)

cntry <- gisco_countries
GBR <- subset(cntry, ISO3_CODE == "GBR")

plot(st_geometry(GBR), col = "red3", border = "blue4")
title(sub = gisco_attributions(), line = 1)
```

gisco_countrycode	<i>Dataframe including Eurostat and ISO2 and ISO3 codes for countries and world regions</i>
-------------------	---

Description

A dataframe containing conversions between different country codification systems (Eurostat/ISO2 and 3) as well as geographic regions as provided by the World Bank and the UN (M49).

Format

- A data frame object with 249 rows and 12 variables:
- CNTR_CODE** Eurostat code of each country
 - iso2c** ISO 3166-1 alpha-2 code of each country
 - ISO3_CODE** ISO 3166-1 alpha-3 code of each country
 - iso.name.en** ISO English short name
 - cldr.short.en** English short name as provided by the [Unicode Common Locale Data Repository](#)
 - continent** As provided by the World Bank
 - un.region.code** Numeric region code UN (M49)
 - un.region.name** Region name UN (M49)
 - un.regionintermediate.code** Numeric intermediate Region code UN (M49)
 - un.regionintermediate.name** Intermediate Region name UN (M49)
 - un.regionsub.code** Numeric sub-region code UN (M49)
 - un.regionsub.name** Sub-Region name UN (M49)

Source

codelist dataset from the countrycode v1.2.0 package.

See Also

[codelist](#)

`gisco_get_coastallines`*Download Coastal Lines from GISCO*

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_coastallines(  
  resolution = "20",  
  year = "2016",  
  epsg = "4326",  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL  
)
```

Arguments

resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none">"60" (1:60million),"20" (1:20million)"10" (1:10million)"03" (1:3million) or"01" (1:1million).
year	Release year. One of "2006", "2010", "2013" or "2016"
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none">"4326" - WGS84"3035" - ETRS89 / ETRS-LAEA"3857" - Pseudo-Mercator
cache	a logical whether to do caching. Default is TRUE.
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with <code>options(gisco_cache_dir = <path>)</code> .

Value

a POLYGON object on sf format.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Coastal Lines

Examples

```
library(sf)

coastlines <- gisco_get_coastallines()
plot(st_geometry(coastlines), col = "palegreen", border = "lightblue3")
title(main = "Coastal Lines",
      sub = gisco_attributions(copyright = FALSE),
      line = 1)
```

gisco_get_communes *Download Geospatial Communes Data from GISCO*

Description

Downloads a simple feature (sf) object.

Usage

```
gisco_get_communes(
  year = "2016",
  epsg = "4326",
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  country = NULL
)
```

Arguments

year	Release year. One of "2001", "2004", "2006", "2008", "2010", "2013" or 2016
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4326" - WGS84 • "3035" - ETRS89 / ETRS-LAEA • "3857" - Pseudo-Mercator
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with options(gisco_cache_dir = <path>).

<code>spatialtype</code>	Type of geometry to be returned: <ul style="list-style-type: none"> • RG: Regions - Multipolygon • LB: Labels - Point • BN: Boundaries - Multilines • COASTL: coastlines - Multilines • INLAND: inland boundaries - Multilines
<code>country</code>	Optional. A character vector of country codes. See Details.

Details

`country` only available on specific datasets. Some `spatialtype` datasets (as Multilines data-types) may not have country-level identifies.

`country` could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

If you experience any problem on download, try to download the file by any other method and set `cache_dir = <folder>`.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Communes

See Also

[gisco_get_lau](#)

Examples

```
library(sf)

communes <- gisco_get_communes(country = "Belgique")
plot(
  st_geometry(communes),
  col = c("black", "gold", "brown2"),
  border = "grey90"
)

title(
```

```

main = "Communes on Belgium (2016)",
sub = gisco_attributions(copyright = FALSE),
line = 1,
cex.sub = 0.8
)

```

`gisco_get_countries` *Download Geospatial Country Data from GISCO*

Description

Downloads a simple feature (sf) object.

Usage

```

gisco_get_countries(
  resolution = "20",
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  country = NULL,
  region = NULL
)

```

Arguments

<code>resolution</code>	Resolution of the geospatial data. One of <ul style="list-style-type: none"> "60" (1:60million), "20" (1:20million) "10" (1:10million) "03" (1:3million) or "01" (1:1million).
<code>year</code>	Release year. One of "2001", "2006", "2010", "2013", "2016" or "2020"
<code>epsg</code>	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> "4326" - WGS84 "3035" - ETRS89 / ETRS-LAEA "3857" - Pseudo-Mercator
<code>cache</code>	a logical whether to do caching. Default is TRUE.
<code>update_cache</code>	a logical whether to update cache.
<code>cache_dir</code>	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from <code>tempdir</code> . The directory can also be set with <code>options(gisco_cache_dir = <path>)</code> .

spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • RG: Regions - Multipolygon • LB: Labels - Point • BN: Boundaries - Multilines • COASTL: coastlines - Multilines • INLAND: inland boundaries - Multilines
country	Optional. A character vector of countries. See Details
region	Optional. A character vector of UN M49 region codes. Possible values are "Africa", "Americas", "Asia", "Europe", "Oceania". See Details and gisco_countrycode

Details

country and region only available when applicable.

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Countries

See Also

[gisco_countrycode](#)

Examples

```
library(sf)

sf_world <- gisco_get_countries()
plot(st_geometry(sf_world), col = "seagreen2")
title(sub = gisco_attributions(), line = 1)

sf_africa <- gisco_get_countries(region = 'Africa')
plot(st_geometry(sf_africa),
     col = c("springgreen4", "darkgoldenrod1", "red2"))
```

```

title(sub = gisco_attributions(), line = 1)

sf_benelux <-
  gisco_get_countries(country = c('Belgium', 'Netherlands', 'Luxembourg'))
plot(st_geometry(sf_benelux),
     col = c("grey10", "orange", "deepskyblue2"))
title(sub = gisco_attributions(), line = 1)

```

gisco_get_lau

Download Geospatial Local Administrative Units Data from GISCO

Description

Downloads a simple feature (sf) object.

Usage

```

gisco_get_lau(
  year = "2016",
  epsg = "4326",
  update_cache = FALSE,
  cache_dir = NULL,
  country = NULL,
  gisco_id = NULL
)

```

Arguments

year	Release year. One of "2016", "2017", "2018" or "2019"
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4326" - WGS84 • "3035" - ETRS89 / ETRS-LAEA • "3857" - Pseudo-Mercator
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with options(gisco_cache_dir = <path>).
country	Optional. A character vector of country codes. See details
gisco_id	Optional. A character vector of GISCO_ID LAU values.

Details

See <https://ec.europa.eu/eurostat/web/nuts/local-administrative-units> for more detail about LAUs.

If you experience any problem on download, try to download the file by any other method and set `cache_dir = <folder>`.

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a POLYGON object on sf format.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Local Administrative Units

See Also

[gisco_get_communes](#)

Examples

```
library(sf)

lau <- gisco_get_lau(country = "Belgique")

plot(
  st_geometry(lau),
  col = c("black", "gold", "brown2"),
  border = "grey90"
)

title(
  main = "Local Administrative Units on Belgium (2016)",
  sub = gisco_attributions(copyright = FALSE),
  line = 1,
  cex.sub = 0.8
)
```

gisco_get_nuts

*Download Geospatial NUTS Data from GISCO***Description**

Downloads a simple feature (sf) object.

Usage

```
gisco_get_nuts(
  resolution = "20",
  year = "2016",
  epsg = "4326",
  nuts_level = "all",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  country = NULL,
  nuts_id = NULL
)
```

Arguments

resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> • "60" (1:60million), • "20" (1:20million) • "10" (1:10million) • "03" (1:3million) or • "01" (1:1million).
year	Release year. One of "2003", "2006", "2010", "2013", "2016" or "2021".
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4326" - WGS84 • "3035" - ETRS89 / ETRS-LAEA • "3857" - Pseudo-Mercator
nuts_level	NUTS level. One of "0" (Country-level), "1", "2" or "3". See https://ec.europa.eu/eurostat/web/nuts/background .
cache	a logical whether to do caching. Default is TRUE.
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from <code>tempdir</code> . The directory can also be set with <code>options(gisco_cache_dir = <path>)</code> .
spatialtype	Type of geometry to be returned:

	<ul style="list-style-type: none"> • RG: Regions - Multipolygon • LB: Labels - Point • BN: Boundaries - Multilines
country	Optional. A character vector of country codes. See Details
nuts_id	Optional. A character vector of NUTS IDs.

Details

country only available when applicable. Some spatialtype datasets (as Multilines data-types) may not have country-level identifies.

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO NUTS

See Also

[gisco_countrycode](#), [gisco_nuts](#)

Examples

```
library(sf)

nuts2 <- gisco_get_nuts(nuts_level = "2", country = "ITA")
nuts3 <- gisco_get_nuts(nuts_level = "3", country = "ITA")

plot(
  st_geometry(nuts3),
  lwd = 1,
  border = "grey40"
)
plot(st_geometry(nuts2),
     add = TRUE)
title(
  main = "NUTS2 and 3 Levels on Italy",
  sub = gisco_attributions(),
```

```

    cex.sub = 0.7,
    line = 1
  )

```

gisco_get_urban_audit *Download Geospatial Urban Audit Data from GISCO*

Description

Downloads a simple feature (sf) object.

Usage

```

gisco_get_urban_audit(
  year = "2020",
  epsg = "4326",
  update_cache = FALSE,
  cache_dir = NULL,
  spatialtype = "RG",
  level = NULL,
  country = NULL
)

```

Arguments

year	Release year. One of "2014", "2018" or "2020"
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> "4326" - WGS84 "3035" - ETRS89 / ETRS-LAEA "3857" - Pseudo-Mercator
update_cache	a logical whether to update cache.
cache_dir	a path to a cache directory. The directory have to exist. The NULL (default) uses and creates /gisco directory in the temporary directory from tempdir . The directory can also be set with options(gisco_cache_dir = <path>).
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> RG: Regions - Multipolygon LB: Labels - Point
level	Level of Urban Audit. Possible values are 'CITIES', 'FUA', 'GREATER_CITIES' or NULL. See Details.
country	Optional. A character vector of country codes. See details.

Details

level = NULL would download the whole dataset including all levels

country could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes.

Value

a sf object.

Note

Please check the download and usage provisions on [gisco_attributions](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

GISCO Urban Audit

Examples

```
library(sf)

GreatCities <-
  gisco_get_urban_audit(level = "GREATER_CITIES")

unique(GreatCities$CNTR_CODE)

countries <- gisco_get_countries()

plot(
  st_geometry(countries) ,
  col = "grey10",
  xlim = c(-15, 25),
  ylim = c(35, 60)
)
plot(st_geometry(GreatCities),
  add = TRUE,
  col = "darkgoldenrod3")
box()
title(
  main = "Greater Cities on Europe (2020)",
  sub = gisco_attributions(copyright = FALSE),
  cex.main = 0.8,
  cex.sub = 0.7,
  line = 1
)
```

gisco_nuts	<i>All NUTS POLYGON object</i>
------------	--------------------------------

Description

A sf object including all NUTS levels as provided by GISCO (2016 version).

Format

A POLYGON data frame (resolution: 1:20million, EPSG:4326) object with 11 variables:

id row ID
COAST_TYPE COAST_TYPE
MOUNT_TYPE MOUNT_TYPE
NAME_LATN Name on Latin characters
CNTR_CODE Eurostat Country code
FID FID
NUTS_ID NUTS identifier
NUTS_NAME NUTS name on local alphabet
LEVL_CODE NUTS level code (0,1,2,3)
URBN_TYPE URBN_TYPE
geometry geometry field

Source

[GISCO .geojson source](#)

See Also

[gisco_get_nuts](#)

Examples

```
library(sf)

nuts <- gisco_nuts

italy <- subset(nuts, CNTR_CODE == "IT" & LEVL_CODE == 3)

plot(st_geometry(italy), col = c("springgreen4", "ivory", "red2"))
title(
  sub = gisco_attributions(copyright = FALSE),
  cex.sub = 0.7,
  font.sub = 3
)
```

Index

* package

giscoR-package, [2](#)

codelist, [6](#)

gisco_attributions, [3](#), [7](#), [9](#), [11](#), [13](#), [15](#), [17](#)

gisco_coastallines, [4](#)

gisco_countries, [5](#)

gisco_countrycode, [6](#), [11](#), [15](#)

gisco_get_coastallines, [5](#), [7](#)

gisco_get_communes, [8](#), [13](#)

gisco_get_countries, [6](#), [10](#)

gisco_get_lau, [9](#), [12](#)

gisco_get_nuts, [14](#), [18](#)

gisco_get_urban_audit, [16](#)

gisco_nuts, [15](#), [18](#)

giscoR (giscoR-package), [2](#)

giscoR-package, [2](#)

tempdir, [7](#), [8](#), [10](#), [12](#), [14](#), [16](#)