

Package ‘heatmap3’

August 29, 2016

Type Package

Title An Improved Heatmap Package

Version 1.1.1

Date 2015-04-06

Author Shilin Zhao, Yan Guo, Quanhu Sheng, Yu Shyr

Maintainer Shilin Zhao <shilin.zhao@vanderbilt.edu>

VignetteBuilder knitr

Description An improved heatmap package. Completely compatible with the original R function 'heatmap', and provides more powerful and convenient features.

License GPL (>= 2)

Imports fastcluster

Suggests knitr

LazyLoad yes

NeedsCompilation no

Repository CRAN

Date/Publication 2015-04-12 21:23:12

R topics documented:

colByValue	2
heatmap3	3
showAnn	6
showLegend	7

Index	8
--------------	----------

 colByValue

colByValue

Description

The function colByValue convert the values in matrix into colors

Usage

```
colByValue(x, col, range = NA, breaks = NA, cex.axis = 2, las = 1, ...)
```

Arguments

x	matrix with values.
col	a list of colors such as that generated by rainbow , heat.colors , topo.colors , terrain.colors or similar functions.
range	the range of x. values out of the range will be changed to the max or min value of the range.
breaks	either a numeric vector of two or more unique cut points or a single number (greater than or equal to 2) giving the number of intervals into which x is to be cut.
cex.axis	The magnification to be used for axis annotation relative to the current setting of cex.
las	numeric in 0,1,2,3; the style of axis labels.
...	additional arguments passed on to image function to generate the color bar.

Value

A matrix with colors.

Examples

```
temp<-rnorm(1000)
col<-colByValue(temp,col=colorRampPalette(c('chartreuse4','white','firebrick'))(1024),range=c(-2,2))
col<-colByValue(temp,col=colorRampPalette(c('chartreuse4',
'white','firebrick'))(5),breaks=c(-5,-1,-0.1,0.1,1,5),cex.axis=0.8)
```

heatmap3

*heatmap3***Description**

The function heatmap3 is completely compatible with the original R function heatmap, and provides more new features.

Usage

```
heatmap3(x, Rowv = NULL, Colv = if (symm) "Rowv" else NULL,
  distfun = function(x) as.dist(1 - cor(t(x), use = "pa")),
  balanceColor = F, ColSideLabs, RowSideLabs, showColDendro = T,
  showRowDendro = T, col = colorRampPalette(c("navy", "white",
  "firebrick3"))(1024), legendfun, method = "complete", ColAxisColors = 0,
  RowAxisColors = 0, hclustfun = hclust, reorderfun = function(d, w)
  reorder(d, w), add.expr, symm = FALSE, revC = identical(Colv, "Rowv"),
  scale = c("row", "column", "none"), na.rm = TRUE, ColSideFun, ColSideAnn,
  ColSideWidth = 0.4, ColSideCut, colorCell, highlightCell,
  file = "heatmap3.pdf", topN = NA, filterFun = sd, margins = c(5, 5),
  ColSideColors, RowSideColors, cexRow = 0.2 + 1/log10(nrow(x)),
  cexCol = 0.2 + 1/log10(ncol(x)), lasRow = 2, lasCol = 2,
  labRow = NULL, labCol = NULL, main = NULL, xlab = NULL, ylab = NULL,
  keep.dendro = FALSE, verbose = getOption("verbose"), useRaster = if
  (ncol(x) * nrow(x) >= 50000) TRUE else FALSE, ...)
```

Arguments

x	numeric matrix of the values to be plotted.
Rowv	determines if and how the <i>row</i> dendrogram should be computed and reordered. Either a dendrogram or a vector of values used to reorder the row dendrogram or <code>NA</code> to suppress any row dendrogram (and reordering) or by default, <code>NULL</code> , see 'Details' below.
Colv	determines if and how the <i>column</i> dendrogram should be reordered. Has the same options as the Rowv argument above and <i>additionally</i> when x is a square matrix, Colv = "Rowv" means that columns should be treated identically to the rows (and so if there is to be no row dendrogram there will not be a column one either).
distfun	function used to compute the distance (dissimilarity) between both rows and columns. Defaults to dist .
balanceColor	logical indicating if the colors need to be balanced so that the median color will represent the 0 value. The default value is F.
ColSideLabs	label for ColSideColors
RowSideLabs	label for RowSideColors

showColDendro	logical indicating if the coloum dendrogram should be plotted (when Colv isn't NA).
showRowDendro	logical indicating if the row dendrogram should be plotted (when Rowv isn't NA).
col	specifying the colors, used in image function.
legendfun	function used to generate legend in top left of the figure. If not specified, the color bar will be plotted. The users can use any plot functions to generate their own legend. Or a function showLegend is also provided as a example.
method	the agglomeration method to be used by hclust function. This should be (an unambiguous abbreviation of) one of "ward", "single", "complete", "average", "mcquitty", "median" or "centroid".
ColAxisColors	integer indicating which coloum of ColSideColors will be used as colors for labels in coloum axis. The default value is 0, which means all coloum labels will be in black color.
RowAxisColors	integer indicating which coloum of RowSideColors will be used as colors for labels in row axis. The default value is 0, which means all row labels will be in black color.
hclustfun	function used to compute the hierarchical clustering when Rowv or Colv are not dendrograms. Defaults to hclust . Should take as argument a result of distfun and return an object to which as.dendrogram can be applied.
reorderfun	function(d, w) of dendrogram and weights for reordering the row and column dendrograms. The default uses reorder.dendrogram .
add.expr	expression that will be evaluated after the call to image . Can be used to add components to the plot.
symm	logical indicating if x should be treated symmetrically ; can only be true when x is a square matrix.
revC	logical indicating if the column order should be reversed for plotting, such that e.g., for the symmetric case, the symmetry axis is as usual.
scale	character indicating if the values should be centered and scaled in either the row direction or the column direction, or none. The default is "row" if <code>symm</code> false, and "none" otherwise.
na.rm	logical indicating whether NA's should be removed.
ColSideFun	function used to generate annotation and labeling figure in column side. The users can use any plot functions to generate their own figure. And a function showAnn is also provided as a example.
ColSideAnn	data frame with continuous and factor variables as annotation information. This parameter will be sorted by coloum dendrogram and then passed to ColSideFun.
ColSideWidth	numeric the height of column side area, which can be used by ColSideFun function.
ColSideCut	numeric the value to be used in cutting coloum dendrogram. The dendrogram and annotation will be divided into different parts and labeled respectively.
colorCell	A data.frame with 3 columns, indicating which cells will be colored by specific colors. The first column is row index, second column is column index, and the third column is color.

highlightCell	A data.frame with 3 or 4 columns, indicating which cells will be highlighted by rectangles with specific colors. The first column is row index, second column is column index, the third column is color for rectangle border, and the optional fourth column is width for rectangle border.
file	pdf file name, only works when topN was used.
topN	vector a list of numbers. topN genes will be used to generate the heatmaps.
filterFun	function used to filter genes, such as sd, mean, sum. It will be used in a apply function to calculate for each row.
margins	numeric vector of length 2 containing the margins (see <code>par(mar = *)</code>) for column and row names, respectively.
ColSideColors	(optional) character vector of length <code>ncol(x)</code> containing the color names for a horizontal side bar that may be used to annotate the columns of <code>x</code> .
RowSideColors	(optional) character vector of length <code>nrow(x)</code> containing the color names for a vertical side bar that may be used to annotate the rows of <code>x</code> .
cexRow, cexCol	positive numbers, used as <code>cex.axis</code> in for the row or column axis labeling. The defaults currently only use number of rows or columns, respectively.
lasRow, lasCol	the style of row or column axis labels.
labRow, labCol	character vectors with row and column labels to use; these default to <code>rownames(x)</code> or <code>colnames(x)</code> , respectively.
main, xlab, ylab	main, x- and y-axis titles; defaults to none.
keep.dendro	logical indicating if the dendrogram(s) should be kept as part of the result (when <code>Rowv</code> and/or <code>Colv</code> are not NA).
verbose	logical indicating if information should be printed.
useRaster	logical; if TRUE a bitmap raster is used to plot the image instead of polygons. The grid must be regular in that case, otherwise an error is raised.
...	additional arguments passed on to <code>image</code> .

Value

The same return value as `hclust` function.

Examples

```
#generate data
set.seed(123456789)
rnormData<-matrix(rnorm(1000), 40, 25)
rnormData[1:15, seq(6, 25, 2)] = rnormData[1:15, seq(6, 25, 2)] + 2
rnormData[16:40, seq(7, 25, 2)] = rnormData[16:40, seq(7, 25, 2)] + 4
colnames(rnormData)<-c(paste("Control", 1:5, sep = ""), paste(c("TrtA", "TrtB"),
rep(1:10,each=2), sep = ""))
rownames(rnormData)<-paste("Probe", 1:40, sep = "")
ColSideColors<-cbind(Group1=c(rep("steelblue2",5), rep(c("brown1", "mediumpurple2"),10)),
  Group2=sample(c("steelblue2","brown1", "mediumpurple2"),25,replace=TRUE))
colorCell<-data.frame(row=c(1,3,5),col=c(2,4,6),color=c("green4","black","orange2"),
  stringsAsFactors=FALSE)
highlightCell<-data.frame(row=c(2,4,6),col=c(1,3,5),color=c("black","green4","orange2"),
```

```

    lwd=1:3,stringsAsFactors=FALSE)
#A simple example
heatmap3(rnormData,ColSideColors=ColSideColors,showRowDendro=FALSE,colorCell=colorCell,
  highlightCell=highlightCell)
#A more detail example
ColSideAnn<-data.frame(Information=rnorm(25),Group=c(rep("Control",5), rep(c("TrtA", "TrtB"),10)))
row.names(ColSideAnn)<-colnames(rnormData)
RowSideColors<-colorRampPalette(c("chartreuse4", "white", "firebrick"))(40)
result<-heatmap3(rnormData,ColSideCut=1.2,ColSideAnn=ColSideAnn,ColSideFun=function(x)
showAnn(x),ColSideWidth=0.8,RowSideColors=RowSideColors,col=colorRampPalette(c("green",
"black", "red"))(1024),RowAxisColors=1,legendfun=function() showLegend(legend=c("Low",
"High"),col=c("chartreuse4","firebrick")),verbose=TRUE)
#annotations distribution in different clusters and the result of statistic tests
result$cutTable

```

showAnn

showAnn

Description

The function `showAnn` is an example for generating annotation figure in the result of `heatmap3` function. You can use your any plot functions to generate your own annotation figure.

Usage

```
showAnn(annData)
```

Arguments

`annData` a data frame contains the annotation information for samples. It can only contain factor or numeric variables, and each row represent a sample with the same order of the columns in expression matrix.

Examples

```

annData<-data.frame(mtcars[,c("mpg", "am", "wt", "gear")])
annData[,2]<-as.factor(annData[,2])
annData[,4]<-as.factor(annData[,4])
#Display annotation
## Not run:
showAnn(annData)

## End(Not run)
#Heatmap with annotation
heatmap3(t(mtcars),ColSideAnn=annData,ColSideFun=function(x)
showAnn(x),ColSideWidth=1.2,balanceColor=TRUE)

```

showLegend	<i>showLegend</i>
------------	-------------------

Description

The function `showLegend` is an example for generating legend in the figure of `heatmap3` function. You can use your any plot functions to generate your own legend.

Usage

```
showLegend(legend = c("Group A", "Group B"), lwd = 3, cex = 1.1,  
           col = c("red", "blue"), ...)
```

Arguments

<code>legend</code>	a character or expression vector of length ≥ 1 to appear in the legend. Other objects will be coerced by as.graphicsAnnot .
<code>lwd</code>	the line widths for lines appearing in the legend.
<code>cex</code>	character expansion factor relative to current <code>par("cex")</code> . Used for text, and provides the default for <code>pt.cex</code> and <code>title.cex</code> .
<code>col</code>	the color of points or lines appearing in the legend.
<code>...</code>	additional arguments passed on to legend

Examples

```
RowSideColors<-rep("steelblue2",nrow(mtcars))  
RowSideColors[c(4:6,15:17,22:26,29)]<-"lightgoldenrod"  
RowSideColors[c(1:3,19:21)]<-"brown1"  
heatmap3(mtcars,scale="col",margins=c(2,10),RowSideColors=RowSideColors,legendfun=function()  
showLegend(legend=c("European","American","Japanese"),col=c("steelblue2","lightgoldenrod",  
"brown1"),cex=1.5))
```

Index

as.dendrogram, [4](#)
as.graphicsAnnot, [7](#)

colByValue, [2](#)

dendrogram, [3](#)
dist, [3](#)

expression, [7](#)

hclust, [4, 5](#)
heat.colors, [2](#)
heatmap3, [3](#)

image, [2, 4, 5](#)

legend, [7](#)

NA, [3](#)
NULL, [3](#)

par, [5](#)

rainbow, [2](#)
reorder.dendrogram, [4](#)
rev, [4](#)

showAnn, [4, 6](#)
showLegend, [4, 7](#)

terrain.colors, [2](#)
topo.colors, [2](#)