

Package ‘insiderTrades’

October 4, 2021

Title Tools to Download Insider Transactions and Holdings

Version 0.0.1

Description Download insider trading transactions and insider holdings from a public NoSQL SEC database (<https://www.sec.gov/Archives/edgar/full-index/>) using keyword criteria and generate a relational dataframe.

License CC0

URL <https://github.com/US-Department-of-the-Treasury/insiderTrades>

BugReports <https://github.com/US-Department-of-the-Treasury/insiderTrades/issues>

Encoding UTF-8

RoxygenNote 7.1.1

Imports stringr (>= 1.4.0), magrittr (>= 2.0.1), RCurl (>= 1.98-1.3)

Suggests knitr, rmarkdown, devtools

VignetteBuilder knitr

NeedsCompilation no

Author Joseph Hancuch [aut, cre]

Maintainer Joseph Hancuch <joseph.hancuch@treasury.gov>

Repository CRAN

Date/Publication 2021-10-04 20:20:05 UTC

R topics documented:

derivativeHoldingsPullAndScrape	2
derivativeHoldingsScrape	3
derivativeTransactionsPullAndScrape	4
derivativeTransactionsScrape	6
formFilters	7
nonderivativeHoldingsPullAndScrape	9
nonderivativeHoldingsScrape	11
nonderivativeTransactionsPullAndScrape	12

nondervativeTransactionsScrape	13
secUrlDownload	15
transactionFilters	16

Index	19
--------------	-----------

derivativeHoldingsPullAndScrape
derivativeTransactionsPullAndScrape

Description

The function takes the specified quarter (1-4), year (2004- 2021), and form type (4 or 5) and returns a dataframe of all the derivative holdings that meet the keyword criteria from the specified financial quarter. If no criteria is set, all holdings from the financial quarter are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a holding has only one of the footnoteKeywords and none of the issuerKeywords, the holding will still be scraped.

Usage

```
derivativeHoldingsPullAndScrape(  
  quarter,  
  year,  
  form,  
  name,  
  email,  
  footnoteKeywords = NA,  
  issuerKeywords = NA,  
  issuerTradingSymbol = NA,  
  rptOwnerKeywords = NA  
)
```

Arguments

quarter	Specify the financial reporting quarter. Options are 1, 2, 3, and 4.
year	Specify the calendar year. Options range from 2004 to present.
form	Specify the form type. Options are 4 or 5.
name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.
footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.

issuerTradingSymbol

The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.

rptOwnerKeywords

The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing the scraped information where each row represents a derivative holding. The holding observations can be grouped by form through the URL variable within the dataframe.

Examples

```
dat <- derivativeHoldingsPullAndScrape(quarter = 3, year = 2012, form = 4,
name = "Your Name", email = "yourEmail@yourEmail.com",
footnoteKeywords = c("gift", "charity"))
```

derivativeHoldingsScrape

derivativeHoldingsScrape

Description

The function takes the dataframe returned by [secUrlDownload](#) and scrapes and compiles a dataframe of all the derivative holdings that meet the keyword criteria. If no criteria is set, all holdings from the dataframe returned by [secUrlDownload](#) are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a holding has only one of the footnoteKeywords and none of the issuerKeywords, the holding will still be scraped.

Usage

```
derivativeHoldingsScrape(
  index,
  form,
  name,
  email,
  footnoteKeywords = NA,
  issuerKeywords = NA,
  issuerTradingSymbol = NA,
  rptOwnerKeywords = NA
)
```

Arguments

index	A local object that was returned by utilizing the secUrlDownload . It contains the URLs necessary to grab each text version of the filed Form 4 or 5.
form	Define if the form is a Form 4 or Form 5. Must match the type used in secUrlDownload .
name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.
footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing containing the scraped information where each row represents a derivative holding. The holding observations can be grouped by form through the URL variable within the dataframe.

Examples

```
dat <- derivativeHoldingsScrape(index = tempIndex, form = 4,
name = "Your Name", email = "yourEmail@yourEmail.com",
issuerKeywords = c("AMAZON", "MICROSOFT"))
```

derivativeTransactionsPullAndScrape

derivativeTransactionsPullAndScrape

Description

The function takes the specified quarter (1-4), year (2004- 2021), and form type (4 or 5) and returns a dataframe of all the derivative transactions that meet the keyword criteria from the specified financial quarter. If no criteria is set, all transactions from the financial quarter are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a transaction has only one of the footnoteKeywords and none of the issuerKeywords, the transaction will still be scraped.

Usage

```

derivativeTransactionsPullAndScrape(
  quarter,
  year,
  form,
  name,
  email,
  transactionType = NA,
  footnoteKeywords = NA,
  issuerKeywords = NA,
  issuerTradingSymbol = NA,
  rptOwnerKeywords = NA
)

```

Arguments

quarter	Specify the financial reporting quarter. Options are 1, 2, 3, and 4.
year	Specify the calendar year. Options range from 2004 to present.
form	Specify the form type. Options are 4 or 5.
name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.
transactionType	The character vector containing any specified transaction codes. Values must be capitalized to match against SEC values. Detailed information about the transaction type can be found here: https://www.sec.gov/files/forms-3-4-5.pdf . Default value is NA.
footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing containing the scraped information where each row represents a derivative transaction. The transaction observations can be grouped by form through the URL variable within the dataframe.

Examples

```
dat <- derivativeTransactionsPullAndScrape(quarter = 3, year = 2012,
form = 4, name = "Your Name", email = "yourEmail@yourEmail.com",
issuerKeywords = c("AMAZON", "MICROSOFT"))
```

```
derivativeTransactionsScrape
      derivativeTransactionsScrape
```

Description

The function takes the dataframe returned by [secUrlDownload](#) and scrapes and compiles a dataframe of all the derivative transactions that meet the keyword criteria. If no criteria is set, all transactions from the dataframe returned by [secUrlDownload](#) are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a transaction has only one of the footnoteKeywords and none of the issuerKeywords, the transaction will still be scraped.

Usage

```
derivativeTransactionsScrape(
  index,
  form,
  name,
  email,
  transactionType = NA,
  footnoteKeywords = NA,
  issuerKeywords = NA,
  issuerTradingSymbol = NA,
  rptOwnerKeywords = NA
)
```

Arguments

index	A local object that was returned by utilizing the secUrlDownload . It contains the URLs necessary to grab each text version of the filed Form 4 or 5.
form	Define if the form is a Form 4 or Form 5. Must match the type used in secUrlDownload .
name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.
transactionType	The character vector containing any specified transaction codes. Values must be capitalized to match against SEC values. Detailed information about the transaction type can be found here: https://www.sec.gov/files/forms-3-4-5.pdf . Default value is NA.

footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing the scraped information where each row represents a derivative transaction. The transaction observations can be grouped by form through the URL variable within the dataframe.

Examples

```
dat <- derivativeTransactionsScrape(index = tempIndex, form = 4,
  name = "Your Name", email = "yourEmail@yourEmail.com",
  issuerKeywords = c("AMAZON", "MICROSOFT"))
```

formFilters

formFilters

Description

formFilters

Usage

```
formFilterNonderivativeTransactions(
  filing,
  footnoteKeywords,
  issuerKeywords,
  issuerTradingSymbol,
  rptOwnerKeywords,
  transactionType
)
```

```

formFilterDerivativeTransactions(
  filing,
  footnoteKeywords,
  issuerKeywords,
  issuerTradingSymbol,
  rptOwnerKeywords,
  transactionType
)

formFilterNonderivativeHoldings(
  filing,
  footnoteKeywords,
  issuerKeywords,
  issuerTradingSymbol,
  rptOwnerKeywords
)

formFilterDerivativeHoldings(
  filing,
  footnoteKeywords,
  issuerKeywords,
  issuerTradingSymbol,
  rptOwnerKeywords
)

```

Arguments

filing	The object containing the Form 4 text
footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Default is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Default is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Default is NA.
transactionType	The character vector containing any specified transaction codes. Default is NA.

Value

An integer value that if greater than 0, reflects that at the one of the criteria parameters listed above has been met. The form will then be parsed further. Otherwise, if the integer value is 0, the function pulls in the next Form 4 to evaluate.

Note

formFilterNonderivativeTransactions parses the form and returns an integer value greater than 0 if one of the key word criteras is met. This function is specifically for the [nonderivativeTransactionsScrape](#) and [nonderivativeTransactionsPullAndScrape](#) functions.

formFilterDerivativeTransactions parses the form and returns an integer value greater than 0 if one of the key word criteras is met. This function is specifically for the [derivativeTransactionsScrape](#) and [derivativeTransactionsPullAndScrape](#) functions. The function shares the same paramters as [formFilterNonderivativeTransactions](#) (filing, footnoteKeywords, issuerKeywords, issuerTradingSymbol, rptOwnerKeywords, transactionType). The only difference is within the parsing commands which use the key word derivative rather than nonderivative.

formFilterNonderivativeHoldings parses the form and returns an integer value greater than 0 if one of the key word criteras is met. This function is specifically for the [nonderivativeHoldingsScrape](#) and [nonderivativeHoldingsPullAndScrape](#) functions. The function shares the same paramters as [formFilterNonderivativeTransactions](#) (filing, footnoteKeywords, issuerKeywords, issuerTradingSymbol, rptOwnerKeywords) except for transactionType since that isn't a criteria for a non-derivative holdings. Additionally, parsing criteria is different due to targeting holding information rather than transaction information.

formFilterDerivativeHoldings parses the form and returns an integer value greater than 0 if one of the key word criteras is met. This function is specifically for the [derivativeHoldingsScrape](#) and [derivativeHoldingsPullAndScrape](#) functions. The function shares the same paramters as [formFilterNonderivativeHoldings](#) (filing, footnoteKeywords, issuerKeywords, issuerTradingSymbol, rptOwnerKeywords) except for transactionType since that isn't a criteria for a derivative holdings. The only difference is within the parsing commands which use the key word derivative rather than nonderivative.

nonderivativeHoldingsPullAndScrape

nonderivativeHoldingsPullAndScrape

Description

The function takes the specifield quarter (1-4), year (2004- 2021), and form type (4 or 5) and returns a dataframe of all the nonderivative holdings that meet the keyword crtieras from the specified financial quarter. If no criteria is set, all holdings from the financial quarter are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a holding has only one of the footnoteKeywords and none of the issuerKeywords, the holding will still be scraped.

Usage

```
nonderivativeHoldingsPullAndScrape(
  quarter,
  year,
  form,
  name,
```

```

    email,
    footnoteKeywords = NA,
    issuerKeywords = NA,
    issuerTradingSymbol = NA,
    rptOwnerKeywords = NA
  )

```

Arguments

<code>quarter</code>	Specify the financial reporting quarter. Options are 1, 2, 3, and 4.
<code>year</code>	Specify the calendar year. Options range from 2004 to present.
<code>form</code>	Specify the form type. Options are 4 or 5.
<code>name</code>	Specify your name. This is required by the SEC.
<code>email</code>	Specify your email. This is required by the SEC.
<code>footnoteKeywords</code>	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
<code>issuerKeywords</code>	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.
<code>issuerTradingSymbol</code>	The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.
<code>rptOwnerKeywords</code>	The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing the scraped information where each row represents a nonderivative holding. The holding observations can be grouped by form through the URL variable within the dataframe.

Examples

```

dat <- nonderivativeHoldingsPullAndScrape(quarter = 1, year = 2018,
form = 4, name = "Your Name", email = "yourEmail@yourEmail.com",
issuerKeywords = c("AMAZON", "MICROSOFT"))

```

```
nonderivativeHoldingsScrape
      nonderivativeHoldingsScrape
```

Description

The function takes the dataframe returned by [secUrlDownload](#) and scrapes and compiles a dataframe of all the nonderivative holdings that meet the keyword criteria. If no criteria is set, all holdings from the dataframe returned by [secUrlDownload](#) are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a holding has only one of the footnoteKeywords and none of the issuerKeywords, the holding will still be scraped.

Usage

```
nonderivativeHoldingsScrape(
  index,
  form,
  name,
  email,
  footnoteKeywords = NA,
  issuerKeywords = NA,
  issuerTradingSymbol = NA,
  rptOwnerKeywords = NA
)
```

Arguments

index	A local object that was returned by utilizing the secUrlDownload . It contains the URLs necessary to grab each text version of the filed Form 4 or 5.
form	Define if the form is a Form 4 or Form 5. Must match the type used in secUrlDownload .
name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.
footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing containing the scraped information where each row represents a nonderivative holding. The holding observations can be grouped by form through the URL variable within the dataframe.

Examples

```
dat <- nonderivativeHoldingsScrape(index = tempIndex, form = 4,  
name = "Your Name", email = "yourEmail@yourEmail.com",  
rptOwnerKeywords = c("SMITH JOHN"))
```

```
nonderivativeTransactionsPullAndScrape  
      nonderivativeTransactionsPullAndScrape
```

Description

The function takes the specificied quarter (1-4), year (2004- 2021), and form type (4 or 5) and returns a dataframe of all the nonderivative transactions that meet the keyword criteria from the specified financial quarter. If no criteria is set, all transactions from the financial quarter are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a transaction has only one of the footnoteKeywords and none of the issuerKeywords, the transaction will still be scraped.

Usage

```
nonderivativeTransactionsPullAndScrape(  
  quarter,  
  year,  
  form,  
  name,  
  email,  
  transactionType = NA,  
  footnoteKeywords = NA,  
  issuerKeywords = NA,  
  issuerTradingSymbol = NA,  
  rptOwnerKeywords = NA  
)
```

Arguments

quarter	Specify the financial reporting quarter. Options are 1, 2, 3, and 4.
year	Specify the calendar year. Options range from 2004 to present.
form	Specify the form type. Options are 4 or 5.

name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.
transactionType	The character vector containing any specified transaction codes. Values must be capitalized to match against SEC values. Detailed information about the transaction type can be found here: https://www.sec.gov/files/forms-3-4-5.pdf . Default value is NA.
footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing the scraped information where each row represents a nonderivative transaction. The transaction observations can be grouped by form through the URL variable within the dataframe.

Examples

```
dat <- nonderivativeHoldingsPullAndScrape(quarter = 1, year = 2018,
form = 4, name = "Your Name", email = "yourEmail@yourEmail.com",
rptOwnerKeywords = c("10165", "10166"))
```

nonderivativeTransactionsScrape
nonderivativeTransactionsScrape

Description

The function takes the dataframe returned by [secUrlDownload](#) and scrapes and compiles a dataframe of all the nonderivative transactions that meet the keyword criteria. If no criteria is set, all transactions from the dataframe returned by [secUrlDownload](#) are scraped. Note that the logic for the keywords is "OR." Thus if a user sets multiple footnoteKeywords and a keyword for issuerKeywords, if a transaction has only one of the footnoteKeywords and none of the issuerKeywords, the transaction will still be scraped.

Usage

```

nonderivativeTransactionsScrape(
  index,
  form,
  name,
  email,
  transactionType = NA,
  footnoteKeywords = NA,
  issuerKeywords = NA,
  issuerTradingSymbol = NA,
  rptOwnerKeywords = NA
)

```

Arguments

index	A local object that was returned by utilizing the secUrlDownload . It contains the URLs necessary to grab each text version of the filed Form 4 or 5.
form	Define if the form is a Form 4 or Form 5. Must match the type used in secUrlDownload .
name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.
transactionType	The character vector containing any specified transaction codes. Values must be capitalized to match against SEC values. Detailed information about the transaction type can be found here: https://www.sec.gov/files/forms-3-4-5.pdf . Default value is NA.
footnoteKeywords	The character vector containing any specified key words to be searched in the form's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Criteria can include the firms CIK or name. Values must be capitalized to match against SEC values. Default value is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Values must be capitalized to match against SEC values. Default value is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Values must be capitalized to match against SEC values. Additionally, the format is LAST NAME, FIRST NAME. The criteria can include the individuals CIK, address, or name. Default value is NA.

Value

A dataframe containing the scraped information where each row represents a nonderivative transaction. The transaction observations can be grouped by form through the URL variable within the dataframe.

Examples

```
dat <- nonderivativeTransactionsScrape(index = tempIndex, form = 4,  
name = "Your Name", email = "yourEmail@yourEmail.com",  
rptOwnerKeywords = c("SMITH JOHN"))
```

secUrlDownload	<i>secUrlDownload</i>
----------------	-----------------------

Description

The function takes the specified quarter (1-4), year (2004- 2021), and form type (4 or 5) and returns a dataframe of URLs to each form filed during the specified quarter.

Usage

```
secUrlDownload(quarter, year, form, name, email)
```

Arguments

quarter	Specify the financial reporting quarter. Options are 1, 2, 3, and 4.
year	Specify the calendar year. Options range from 2004 to present.
form	Specify the form type. Options are 4 or 5.
name	Specify your name. This is required by the SEC.
email	Specify your email. This is required by the SEC.

Value

A dataframe consisting of the URLs to the Form 4 or 5 text filings for the specified quarter and year.

Examples

```
tempIndex <- secUrlDownload(quarter = 1, year = 2018, form = 4,  
form = 4, name = "Your Name", email = "yourEmail@yourEmail.com")
```

transactionFilters *transactionFilters*

Description

transactionFilters

Usage

```
transactionFilterNonderivative(  
    filing,  
    footnoteKeywords,  
    issuerKeywords,  
    issuerTradingSymbol,  
    rptOwnerKeywords,  
    transactionType  
)  
  
transactionFilterDerivative(  
    filing,  
    footnoteKeywords,  
    issuerKeywords,  
    issuerTradingSymbol,  
    rptOwnerKeywords,  
    transactionType  
)  
  
transactionFilterNonderivativeHoldings(  
    filing,  
    footnoteKeywords,  
    issuerKeywords,  
    issuerTradingSymbol,  
    rptOwnerKeywords  
)  
  
transactionFilterDerivativeHoldings(  
    filing,  
    footnoteKeywords,  
    issuerKeywords,  
    issuerTradingSymbol,  
    rptOwnerKeywords  
)
```

Arguments

filing The object containing a single transaction from a Form 4 filing in text format

footnoteKeywords	The character vector containing any specified key words to be searched in the transaction's footnotes. Default is NA.
issuerKeywords	The character vector containing any specified key words to be searched within the issuer block. Default is NA.
issuerTradingSymbol	The character vector containing any specified stock tickers. Default is NA.
rptOwnerKeywords	The character vector containing any specified key words to be searched within the rptOwner block. Default is NA.
transactionType	The character vector containing any specified transaction codes. Default is NA.

Value

An integer value that if greater than 0, reflects that at the one of the criteria parameters listed above has been met. The form will then be parsed further. Otherwise, if the integer value is 0, the function pulls in the next Form 4 to evaluate.

Note

`transactionFilterNonderivative` parses a transaction contained in the filing and returns an integer value greater than 0 if one of the transaction specific key word criteras or form specific key word criteras is met. This function is specifically for the [nonderivativeTransactionsScrape](#) and [nonderivativeTransactionsPullAndScrape](#) functions.

`transactionFilterDerivative` parses a transaction contained in the filing and returns an integer value greater than 0 if the transaction contains one of the specific key word criteras or if the key word criteria cannot be applied at the transaction level (`rptOwnerKeywords` or `issuerKeywords` for example), but the form contains form specific key word criteria. This function is specifically for the [derivativeTransactionsScrape](#) and [derivativeTransactionsPullAndScrape](#) functions. The function shares the same paramters as `formFilterNonderivativeTransactions` (filing, footnoteKeywords, issuerKeywords, issuerTradingSymbol, rptOwnerKeywords, transactionType). The only difference is within the parsing commands which use the key word derivative rather than non-derivative.

`transactionFilterNonderivativeHoldings` parses a transaction contained in the filing and returns an integer value greater than 0 if the transaction contains one of the specific key word criteras or if the key word criteria cannot be applied at the transaction level (`rptOwnerKeywords` or `issuerKeywords` for example), but the form contains form specific key word criteria. This function is specifically for the [nonderivativeHoldingsScrape](#) and [nonderivativeHoldingsPullAndScrape](#) functions. The function shares the same paramters as `transactionFilterNonderivative` (filing, footnoteKeywords, issuerKeywords, issuerTradingSymbol, rptOwnerKeywords) except for transactionType since that isn't a criteria for a nonderivative holdings. Additionally, parsing criteria is different due to targeting holding information rather than transaction information.

`transactionFilterDerivativeHoldings` parses a transaction contained in the filing and returns an integer value greater than 0 if the transaction contains one of the specific key word criteras or if the key word criteria cannot be applied at the transaction level (`rptOwnerKeywords` or `issuerKeywords` for example), but the form contains form specific key word criteria. This function is

specifically for the `derivativeHoldingsScrape` and `derivativeHoldingsPullAndScrape` functions. The function shares the same parameters as `transactionFilterNonDerivative` (filing, footnoteKeywords, issuerKeywords, issuerTradingSymbol, rptOwnerKeywords) except for transactionType since that isn't a criteria for a derivative holdings. The only difference is within the parsing commands which use the key word derivative rather than nonderivative.

Index

derivativeHoldingsPullAndScrape, [2](#), [9](#),
[18](#)
derivativeHoldingsScrape, [3](#), [9](#), [18](#)
derivativeTransactionsPullAndScrape, [4](#),
[9](#), [17](#)
derivativeTransactionsScrape, [6](#), [9](#), [17](#)

formFilterDerivativeHoldings
(formFilters), [7](#)
formFilterDerivativeTransactions
(formFilters), [7](#)
formFilterNonderivativeHoldings, [9](#)
formFilterNonderivativeHoldings
(formFilters), [7](#)
formFilterNonderivativeTransactions, [9](#),
[17](#)
formFilterNonderivativeTransactions
(formFilters), [7](#)
formFilters, [7](#)

nonderivativeHoldingsPullAndScrape, [9](#),
[9](#), [17](#)
nonderivativeHoldingsScrape, [9](#), [11](#), [17](#)
nonderivativeTransactionsPullAndScrape,
[9](#), [12](#), [17](#)
nonderivativeTransactionsScrape, [9](#), [13](#),
[17](#)

secUrlDownload, [3](#), [4](#), [6](#), [11](#), [13](#), [14](#), [15](#)

transactionFilterDerivative
(transactionFilters), [16](#)
transactionFilterDerivativeHoldings
(transactionFilters), [16](#)
transactionFilterNonderivative, [17](#), [18](#)
transactionFilterNonderivative
(transactionFilters), [16](#)
transactionFilterNonderivativeHoldings
(transactionFilters), [16](#)
transactionFilters, [16](#)