

Package ‘mcmcsae’

January 20, 2021

Version 0.6.0

License GPL-3

Title Markov Chain Monte Carlo Small Area Estimation

Type Package

LazyLoad yes

Encoding UTF-8

Description Fit multi-level models with possibly correlated random effects using Markov Chain Monte Carlo simulation. Such models allow smoothing over space and time and are useful in, for example, small area estimation.

Date 2021-01-15

Depends R (>= 3.2.0)

Imports Matrix (>= 1.2.0), Rcpp (>= 0.11.0), methods, GIGrvg, loo (>= 2.0.0), matrixStats

Suggests BayesLogit, lintools, splines, spdep, maptools, bayesplot, coda, parallel, testthat, roxygen2, knitr, rmarkdown, survey

LinkingTo Rcpp, RcppEigen, Matrix, GIGrvg

VignetteBuilder knitr

RoxygenNote 7.1.1

Collate 'MCMCsim.R' 'MH.R' 'tabMatrix.R' 'MatrixUtils.R' 'RcppExports.R' 'TMVN_sampler.R' 'aux_closures.R' 'cholesky.R' 'family.R' 'formulas.R' 'kronprod.R' 'mc_block.R' 'mc_gen.R' 'mc_gl.R' 'mc_mec.R' 'mc_reg.R' 'mc_vfac.R' 'mc_vreg.R' 'mcmcsae.R' 'model_eval.R' 'modelmatrix.R' 'models.R' 'opts.R' 'parallel.R' 'plots.R' 'prediction.R' 'priors.R' 'random.R' 'samplers.R' 'sparse_template.R' 'utils.R'

NeedsCompilation yes

Author Harm Jan Boonstra [aut, cre],
Grzegorz Baltissen [ctb]

Maintainer Harm Jan Boonstra <hjboonstra@gmail.com>

Repository CRAN

Date/Publication 2021-01-20 08:40:02 UTC

R topics documented:

mcmcsae-package	3
acceptance_rates	3
aggrMatrix	4
combine_chains	5
combine_iters	5
computeDesignMatrix	6
compute_GMRF_matrices	6
correlation	8
create_sampler	8
create_TMVN_sampler	12
gen	14
generate_data	18
get_draw	20
glreg	20
labels	21
matrix-vector	22
maximize_llh	23
MCMC-diagnostics	24
MCMC-object-conversion	25
mcmcsae-family	26
mcmcsae_example	27
MCMCsim	28
mec	31
model-information-criteria	33
model_matrix	35
nchains-ndraws-nvars	36
par_names	37
plot.dc	38
plot.draws	38
plot_coef	39
posterior-moments	41
predict.draws	42
print.dc_summary	44
print.draws_summary	45
pr_exp	45
pr_fixed	46
pr_gig	47
pr_invchisq	47
pr_invwishart	48
read_draws	49
reg	50
residuals-fitted-values	52
setup_cluster	54
set_opts	54
stop_cluster	56
subset.dc	56

summary.dc	57
summary.draws	58
transform_dc	59
vfac	60
vreg	61
weights.draws	62

Index	64
--------------	-----------

mcmcsae-package	<i>MCMC Small Area Estimation</i>
-----------------	-----------------------------------

Description

Fit multi-level models with possibly correlated random effects using MCMC.

Details

Functions to fit multi-level models with Gaussian and binomial or negative binomial likelihoods using MCMC. Models with a linear predictor consisting of various possibly correlated random effects are supported, allowing flexible modeling of temporal, spatial or other kinds of dependence structures. For Gaussian models the variance can be modeled too. By modeling unit-level variances it is possible to account for outliers. The package has been developed with applications to small area estimation in official statistics in mind. The posterior samples for the model parameters can be passed to a prediction function to generate samples from the posterior predictive distribution for user-defined quantities such as finite population domain means. For model assessment, posterior predictive checks and DIC/WAIC criteria are supported.

acceptance_rates	<i>Return Metropolis-Hastings acceptance rates</i>
------------------	--

Description

Return Metropolis-Hastings acceptance rates

Usage

```
acceptance_rates(object, aggregate.chains = FALSE)
```

Arguments

object	a draws object, i.e. the output of function MCMCsim.
aggregate.chains	whether to return averages over chains or results per chain.

Value

A list of acceptance rates.

Examples

```
ex <- mcmcsae_example()
# specify a model that requires MH sampling (in this case for a modeled
# degrees of freedom parameter in the variance part of the model)
sampler <- create_sampler(ex$model, data=ex$dat, formula.V=~vfac(factor="fA",
  prior=pr_invchisq(df="modeled")))
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, n.chain=4, store.all=TRUE)
(summary(sim))
acceptance_rates(sim)
```

aggrMatrix

Utility function to construct a sparse aggregation matrix from a factor

Description

Utility function to construct a sparse aggregation matrix from a factor

Usage

```
aggrMatrix(fac, w = 1, mean = FALSE, facnames = FALSE)
```

Arguments

fac	factor variable.
w	vector of weights associated with the levels of fac.
mean	if TRUE, aggregation will produce (weighted) means instead of sums.
facnames	whether the factor levels should be used as column names for the aggregation matrix.

Value

sparse aggregation matrix of class `tabMatrix`.

Examples

```
n <- 1000
f <- sample(1:100, n, replace=TRUE)
x <- runif(n)
M <- aggrMatrix(f)
all.equal(crossprod_mv(M, x), as.vector(tapply(x, f, sum)))
```

combine_chains	<i>Combine multiple draws objects to a single one by combining their chains</i>
----------------	---

Description

This function can be used to combine the results of parallel simulations.

Usage

```
combine_chains(...)
```

Arguments

... objects of class draws.

Value

A combined object of class draws where the number of stored chains equals the sum of the numbers of chains in the input objects.

combine_iters	<i>Combine multiple draws objects to a single one by combining their draws</i>
---------------	--

Description

This function is used to combine the results of parallel posterior predictive simulations.

Usage

```
combine_iters(...)
```

Arguments

... objects of class draws

Value

A combined object of class draws where the number of stored draws equals the sum of the numbers of draws in the input objects.

`computeDesignMatrix` *Compute list of design matrices for all terms in a model formula*

Description

The output is a list of dense or sparse design matrices for the specified model components with respect to data. The design matrices contain appropriate column names.

Usage

```
computeDesignMatrix(formula, data)
```

Arguments

<code>formula</code>	model formula.
<code>data</code>	data frame to be used in deriving the design matrices.

Value

A list of design matrices.

Examples

```
n <- 1000
dat <- data.frame(
  x = rnorm(n),
  f = factor(sample(1:50, n, replace=TRUE))
)
str(X <- computeDesignMatrix(~ x, dat)[[1]])
X <- computeDesignMatrix(
  ~ reg(~x, name="beta") + gen(~x, factor=~f, name="v"), dat
)
str(X)
```

`compute_GMRF_matrices` *Compute (I)GMRF incidence, precision and restriction matrices corresponding to a generic model component*

Description

This function computes incidence, precision and restriction matrices, or a subset thereof, for a Gaussian Markov Random Field (GMRF). A GMRF is specified by a formula passed to the `factor` argument, in the same way as for the `factor` argument of [gen](#).

Usage

```
compute_GMRF_matrices(
  factor,
  data,
  D = TRUE,
  Q = TRUE,
  R = TRUE,
  cols2remove = NULL,
  remove.redundant.R.cols = TRUE,
  ...
)
```

Arguments

factor	factor formula of a generic model component, see gen .
data	data frame to be used in deriving the matrices.
D	if TRUE compute the incidence matrix.
Q	if TRUE compute the precision matrix.
R	if TRUE compute the restriction matrix.
cols2remove	if an integer vector is passed, the dimensions (columns of D, rows and columns of Q and rows of R) that are removed. This can be useful in the case of empty domains.
remove.redundant.R.cols	whether to test for and remove redundant restrictions from restriction matrix R
...	further arguments passed to <code>economizeMatrix</code> .

Value

A list containing some or all of the components D (incidence matrix), Q (precision matrix) and R (restriction matrix).

Examples

```
n <- 1000
dat <- data.frame(
  x = rnorm(n),
  f1 = factor(sample(1:50, n, replace=TRUE)),
  f2 = factor(sample(1:10, n, replace=TRUE))
)
mats <- compute_GMRF_matrices(~ f1 * RW1(f2), dat)
str(mats)
```

correlation *Correlation structures*

Description

Element 'factor' of a model component is a formula composed of several possible terms described below. It is used to derive a (sparse) precision matrix for a set of coefficient, and possibly a matrix representing a set of linear constraints to be imposed on the coefficient vector.

iid(f) Independent effects corresponding to the levels of factor f.

RW1(f, circular=FALSE) First-order random walk.

RW2(f) Second-order random walk.

AR1(f, phi) First-order autoregressive correlation structure among the levels of f. Required argument phi (fixed number for now).

season(f, period) Dummy seasonal with period period.

spatial(f, poly.df, snap, queen, derive.constraints=FALSE) CAR spatial correlation. Argument poly.df should be an object of class SpatialPolygonsDataFrame obtained e.g. from reading in a shape file with [readShapeSpatial](#) from package **maptools**. Arguments snap and queen are passed to [poly2nb](#). If derive.constraints=TRUE the constraint matrix for an IGMRF model component is formed by computing the singular vectors of the precision matrix.

custom(f, QD) A custom precision or incidence matrix associated with factor f can be passed to argument QD.

create_sampler *Create a sampler object*

Description

This sets up a sampler object, based on the specification of a model. The object contains functions to draw a set of model parameters from their prior and conditional posterior distributions, and to generate starting values for the MCMC simulation. The functions share a common environment containing precomputed quantities such as design matrices based on the model and the data. The sampler object is the main input for the MCMC simulation function [MCMCsim](#).

Usage

```
create_sampler(
  formula,
  data = NULL,
  family = "gaussian",
  ny = NULL,
  ry,
  r.mod,
  sigma.fixed = NULL,
```



```

sigma.mod = NULL,
Q0 = NULL,
formula.V = NULL,
logJacobian = NULL,
linpred = NULL,
compute.weights = FALSE,
block = compute.weights,
prior.only = FALSE,
control = NULL
)

```

Arguments

formula	formula to specify the response variable and additive model components. The model components form the linear predictor part of the model. A model component on the right hand side can currently be either a regression term specified with <code>reg(...)</code> or a generic random effect term specified with <code>gen(...)</code> . See for details the help pages for these model component creation functions. Other terms in the formula are interpreted as ordinary regression effects (treated in the same way as <code>reg(...)</code> terms, but without the option to change e.g. the prior). An offset can be specified as <code>offset(...)</code> .
data	data frame with n rows in which the variables specified in model components (if any) can be found.
family	character string describing the data distribution. The default is 'gaussian'. Other options are 'binomial' for the binomial distribution and 'negbinomial' for the negative binomial distribution. For the binomial and negative binomial distributions logistic and log link functions are used by default, respectively. In the case of binary data a probit link function is also supported for the binomial/Bernoulli distribution.
ny	in case family="binomial" the (vector of) numbers of trials. It can be either a numeric vector or the name of a variable in data. Defaults to a vector of 1s.
ry	in case family="negbinomial" the dispersion parameter or vector of dispersion parameters. Use <code>r.mod</code> instead if the (scalar) dispersion parameter should be inferred from the data. If neither <code>ry</code> nor <code>r.mod</code> is specified a default chi-squared prior with 1 degree of freedom is assumed.
r.mod	prior specification for a scalar (reciprocal) dispersion parameter of the negative binomial distribution, in case the dispersion parameter is to be inferred. The prior can be specified by a call to a prior specification function. Currently <code>pr_invchisq</code> , <code>pr_gig</code> and <code>pr_fixed</code> are supported.
sigma.fixed	for Gaussian models, if TRUE the residual standard deviation parameter 'sigma_' is fixed at 1. In that case argument <code>sigma.mod</code> is ignored. This is convenient for Fay-Herriot type models with (sampling) variances assumed to be known. Default is FALSE.
sigma.mod	prior for the variance parameter of a gaussian sampling distribution. This can be specified by a call to one of the prior specification functions <code>pr_invchisq</code> , <code>pr_exp</code> , <code>pr_gig</code> or <code>pr_fixed</code> for inverse chi-squared, exponential, generalized inverse gaussian or degenerate prior distribution, respectively. The default is an

improper prior `pr_invchisq(df=0, scale=1)`. A half-t prior on the standard deviation can be specified using `pr_invchisq` with a chi-squared distributed scale parameter.

<code>Q0</code>	<code>n x n</code> data-level precision matrix for a Gaussian model. It defaults to the unit matrix. If an <code>n</code> -vector is provided it will be expanded to a (sparse) diagonal matrix with <code>Q0</code> on its diagonal. If a name is supplied it will be looked up in <code>data</code> and subsequently expanded to a diagonal matrix.
<code>formula.v</code>	a formula specifying the terms of a variance model in the case of a Gaussian likelihood. Currently two types of terms are supported: a regression term for the log-variance specified with <code>vreg(...)</code> , and a term <code>vfac(...)</code> for multiplicative modeled factors at a certain level specified by a factor variable. By using unit-level inverse-chi-squared factors the marginal sampling distribution becomes a Student-t distribution, and by using unit-level exponential factors it becomes a Laplace or double exponential distribution.
<code>logJacobian</code>	if the data are transformed the logarithm of the Jacobian can be supplied so that it is incorporated in all log-likelihood computations. This can be useful for comparing information criteria for different transformations. It should be supplied as a vector of the same size as the response variable, and is currently only supported if <code>family="gaussian"</code> . For example, when a log-transformation is used on response vector <code>y</code> , the vector <code>-log(y)</code> should be supplied.
<code>linpred</code>	a list of matrices defining (possibly out-of-sample) linear predictors to be simulated. This allows inference on e.g. (sub)population totals or means. The list must be of the form <code>list(name_1=X_1, ...)</code> where the names refer to the model component names and predictions are computed by summing <code>X_i %*% p[[name_i]]</code> . Alternatively, <code>linpred="fitted"</code> can be used for simulations of the full in-sample linear predictor.
<code>compute.weights</code>	if TRUE weights are computed for each element of <code>linpred</code> . Note that for a large dataset in combination with vector-valued linear predictors the weights can take up a lot of memory. By default only means are stored in the simulation carried out using <code>MCMCsim</code> .
<code>block</code>	if TRUE all coefficients are sampled in a single block. Alternatively, a list of character vectors indicating which coefficients should be sampled together in blocks.
<code>prior.only</code>	whether a sampler is set up only for sampling from the prior or for sampling from both prior and posterior distributions. Default FALSE. If TRUE there is no need to specify a response in <code>formula</code> . This is used by <code>generate_data</code> , which samples from the prior predictive distribution.
<code>control</code>	a list with further computational options, see details section.

Details

The right hand side of the `formula` argument to `create_sampler` can be used to specify additive model components. Currently two specialized model components are supported, `reg(...)` and `gen(...)` for regression and generic random effects components, respectively.

For gaussian models, `formula.V` can be used to specify the variance structure of the model. Currently two specialized variance model components are supported, `vreg(...)` for regression effects predicting the log-variance and `vfac(...)` for modeled variance factors.

Further computational options can be set using the `control` parameter, which should be passed as a list with possible elements

add.outer.R whether to add the outer product of the constraint matrix for a better conditioned solve system for blocks. This is done by default when using blocked Gibbs sampling for blocks with constraints.

recompute.e when FALSE residuals or linear predictors are only computed at the start of the simulation. This may give a modest speedup but in some cases may be less accurate due to roundoff error accumulation. Default is TRUE.

Value

A sampler object, which is the main input for the MCMC simulation function `MCMCsim`. The sampler object is an environment with precomputed quantities and functions. The main functions are `rprior`, which returns a sample from the prior distributions, `draw`, which returns a sample from the full conditional posterior distributions, and `start`, which returns a list with starting values for the Gibbs sampler. If `prior.only` is TRUE, functions `draw` and `start` are not created.

References

- J.H. Albert and S. Chib (1993). Bayesian analysis of binary and polychotomous response data. *Journal of the American statistical Association* 88(422), 669-679.
- D. Bates, M. Maechler, B. Bolker and S.C. Walker (2015). Fitting Linear Mixed-Effects Models Using lme4. *Journal of Statistical Software* 67(1), 1-48.
- N. Polson, J.G. Scott and J. Windle (2013). Bayesian Inference for Logistic Models Using Polya-Gamma Latent Variables. *Journal of the American Statistical Association* 108(504), 1339-1349.
- H. Rue and L. Held (2005). *Gaussian Markov Random Fields*. Chapman & Hall/CRC.
- M. Zhou and L. Carin (2015). Negative Binomial Process Count and Mixture Modeling. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 37(2), 307-320.

Examples

```
# first generate some data
n <- 200
x <- rnorm(n)
y <- 0.5 + 2*x + 0.3*rnorm(n)
# create a sampler for a simple linear regression model
sampler <- create_sampler(y ~ x)
sim <- MCMCsim(sampler)
(summary(sim))

y <- rbinom(n, 1, 1 / (1 + exp(-(0.5 + 2*x))))
# create a sampler for a binary logistic regression model
sampler <- create_sampler(y ~ x, family="binomial")
sim <- MCMCsim(sampler)
(summary(sim))
```

`create_TMVN_sampler` *Set up a sampler object for sampling from a possibly truncated and degenerate multivariate normal distribution*

Description

This function sets up an object for multivariate normal sampling based on a specified precision matrix or cholesky decomposition thereof. Linear equality and inequality restrictions are supported. For sampling under inequality restrictions three algorithms are available. The default in that case is an exact Hamiltonian Monte Carlo algorithm (Pakman and Paninski, 2014). Alternatively, a Gibbs sampling algorithm can be used (Rodriguez-Yam et al., 2004). The third option is a data augmentation method to sample from a smooth approximation to the truncated multivariate normal distribution (Souris et al., 2018).

Usage

```
create_TMVN_sampler(
  Q,
  perm = NULL,
  mu = NULL,
  Xy = NULL,
  update.Q = FALSE,
  update.mu = update.Q,
  name = "x",
  coef.names = NULL,
  R = NULL,
  r = NULL,
  S = NULL,
  s = NULL,
  lower = NULL,
  upper = NULL,
  method = NULL,
  reduce = (method == "Gibbs" && !is.null(R)),
  T.HMC = pi/2,
  print.info = FALSE,
  sharpness = 100,
  useV = FALSE
)
```

Arguments

<code>Q</code>	precision matrix (unconstrained) (n x n); used in case <code>cholQ</code> is not supplied.
<code>perm</code>	whether permutation/pivoting should be used to build a Cholesky object.
<code>mu</code>	mean of the (unconstrained) multivariate normal distribution.

Xy	alternative to specifying mu; in this case mu is computed as $Q^{-1} Xy$.
update.Q	whether Q is updated for each draw.
update.mu	whether mu is updated for each draw. By default equal to update.Q.
name	name of the TMVN vector parameter.
coef.names	optional labels for the components of the vector parameter.
R	equality restriction matrix.
r	rhs vector for equality constraints $R^T x = r$.
S	inequality restriction matrix.
s	rhs vector for inequality constraints $S^T x \geq s$.
lower	alternative to s for two-sided inequality restrictions $lower \leq S^T x \leq upper$.
upper	alternative to s for two-sided inequality restrictions $lower \leq S^T x \leq upper$.
method	sampling method. The options are "direct" for direct sampling from the unconstrained or equality constrained multivariate normal (MVN). For inequality constrained MVN sampling three methods are supported: "HMC" for (exact) Hamiltonian Monte Carlo, "Gibbs" for a component-wise Gibbs sampling approach, and "softTMVN" for a data augmentation method that samples from a smooth approximation to the truncated MVN.
reduce	whether to a priori restrict the simulation to the subspace defined by the equality constraints.
T.HMC	the duration of a Hamiltonian Monte Carlo simulated particle trajectory. If a vector of length 2 is supplied it is interpreted as an interval from which the duration is drawn uniformly, independently in each HMC iteration.
print.info	whether information about violations of inequalities and bounces off inequality walls is printed to the screen. This sometimes provides useful diagnostic information.
sharpness	for method 'softTMVN', the sharpness of the soft inequalities; the larger the better the approximation of exact inequalities. It must be either a scalar value or a vector of length equal to the number of inequality restrictions.
useV	for method 'softTMVN' whether to base computations on variance instead of precision matrices.

Details

The componentwise Gibbs sampler uses univariate truncated normal samplers as described in Botev and L'Ecuyer (2016). These samplers are implemented in R package **TruncatedNormal**, but here translated to C++ for an additional speed-up.

Value

An environment for sampling from a possibly degenerate and truncated multivariate normal distribution.

Author(s)

Harm Jan Boonstra, with help from Grzegorz Baltissen

References

- Z.I. Botev and P. L'Ecuyer (2016). Simulation from the Normal Distribution Truncated to an Interval in the Tail. in VALUETOOLS.
- Y. Cong, B. Chen and M. Zhou (2017). Fast simulation of hyperplane-truncated multivariate normal distributions. Bayesian Analysis 12(4), 1017-1037.
- A. Pakman and L. Paninski (2014). Exact Hamiltonian Monte Carlo for truncated multivariate gaussians. Journal of Computational and Graphical Statistics 23(2), 518-542.
- G. Rodriguez-Yam, R.A. Davis and L.L. Scharf (2004). Efficient Gibbs sampling of truncated multivariate normal with application to constrained linear regression. Unpublished manuscript.
- H. Rue and L. Held (2005). Gaussian Markov Random Fields. Chapman & Hall/CRC.
- A. Souris, A. Bhattacharya and P. Debdeep (2018). The Soft Multivariate Truncated Normal Distribution. arXiv:1807.09155.

Examples

```
S <- cbind(diag(2), c(-1, 1), c(1.1, -1)) # inequality matrix
# S'x >= 0 represents the wedge x1 <= x2 <= 1.1 x1
# example taken from Pakman and Paninski (2014)
# 1. exact Hamiltonian Monte Carlo (Pakman and Paninski, 2014)
sampler <- create_TMVN_sampler(Q=diag(2), mu=c(4, 4), S=S, method="HMC")
sim <- MCMCsim(sampler)
summary(sim)
plot(as.matrix(sim$x), pch=".")
# 2. Gibbs sampling approach (Rodriguez-Yam et al., 2004)
sampler <- create_TMVN_sampler(Q=diag(2), mu=c(4, 4), S=S, method="Gibbs")
sim <- MCMCsim(sampler)
summary(sim)
plot(as.matrix(sim$x), pch=".")
# 3. soft TMVN approximation (Souris et al., 2018)
sampler <- create_TMVN_sampler(Q=diag(2), mu=c(4, 4), S=S, method="softTMVN")
sim <- MCMCsim(sampler)
summary(sim)
plot(as.matrix(sim$x), pch=".")
```

gen

Create a model component object for a generic random effects component in the linear predictor

Description

This function is intended to be used on the right hand side of the formula argument to [create_sampler](#) or [generate_data](#).

Usage

```

gen(
  formula = ~1,
  factor = NULL,
  remove.redundant = FALSE,
  drop.empty.levels = FALSE,
  X = NULL,
  var = NULL,
  prior = NULL,
  Q0 = NULL,
  PX = TRUE,
  GMRFmats = NULL,
  priorA = NULL,
  Leroux = FALSE,
  R0 = NULL,
  RA = NULL,
  constr = NULL,
  S0 = NULL,
  SA = NULL,
  formula.gl = NULL,
  name = "",
  sparse = NULL,
  perm = NULL,
  debug = FALSE,
  e = parent.frame()
)

```

Arguments

- | | |
|---------|---|
| formula | a model formula specifying the effects that vary over the levels of the factor variable(s) specified by argument factor. Defaults to ~1, corresponding to random intercepts. If X is specified formula is ignored. Variable names are looked up in the data frame passed as data argument to create_sampler or generate_data , or in environment(formula). |
| factor | a formula with factors by which the effects specified in the formula argument vary. Often only one such factor is needed but multiple factors are allowed so that interaction terms can be modeled conveniently. The formula must take the form ~ f1(fac1, ...) * f2(fac2, ...) ..., where fac1, fac2 are factor variables and f1, f2 determine the correlation structure assumed between levels of each factor, and the ... indicate that for some correlation types further arguments can be passed. Correlation structures currently supported include iid for independent identically distributed effects, RW1 and RW2 for random walks of first or second order over the factor levels, AR1 for first-order autoregressive effects, season for seasonal effects, spatial for spatial (CAR) effects and custom for supplying a custom precision matrix corresponding to the levels of the factor. For further details about the correlation structures, and further arguments that can be passed, see correlation . Argument factor is ignored if X is specified. The factor variables are looked up in the data frame passed as data argument to |

	create_sampler or generate_data , or in <code>environment(formula)</code> .
<code>remove.redundant</code>	whether redundant columns should be removed from the model matrix associated with <code>formula</code> . Default is <code>FALSE</code> .
<code>drop.empty.levels</code>	whether to remove factor levels without observations.
<code>X</code>	A (possibly sparse) design matrix. This can be used instead of <code>formula</code> and <code>factor</code> .
<code>var</code>	the (co)variance structure among the varying effects defined by <code>formula</code> over the levels of the factors defined by <code>factor</code> . The default is "unstructured", meaning that a full covariance matrix parameterization is used. For uncorrelated effects with different variances use <code>var="diagonal"</code> . For uncorrelated and equal variances use <code>var="scalar"</code> . In the case of a single varying effect there is no difference between these choices.
<code>prior</code>	the prior specification for the variance parameters of the random effects. These can currently be specified by a call to pr_invwishart in case <code>var="unstructured"</code> or by a call to pr_invchisq otherwise. See the documentation of those prior specification functions for more details.
<code>Q0</code>	precision matrix associated with <code>formula</code> . This can only be used in combination with <code>var="scalar"</code> .
<code>PX</code>	whether parameter expansion should be used. Default is <code>TRUE</code> , which applies parameter expansion with default options. Alternative options can be specified by supplying a list with one or more of the following components: <ul style="list-style-type: none"> vector whether a redundant multiplicative expansion parameter is used for each varying effect specified by <code>formula</code>. The default is <code>TRUE</code> except when <code>var="scalar"</code>. If <code>FALSE</code> a single redundant multiplicative parameter is used. data.scale whether the data level scale is used as a variance factor for the expansion parameters. Default is <code>TRUE</code>. mu0 location (vector) parameter for parameter expansion. By default \emptyset. Q0 precision (matrix) parameter for parameter expansion. Default is the identity matrix.
<code>GMRFmats</code>	list of incidence/precision/constraint matrices. This can be specified as an alternative to <code>factor</code> . It should be a list such as is usually returned by compute_GMRF_matrices . Can be used together with argument <code>X</code> as a flexible alternative to <code>formula</code> and <code>factor</code> .
<code>priorA</code>	prior distribution for scale factors at the variance scale associated with <code>QA</code> . In case of IGMRF models the scale factors correspond to the innovations. The default <code>NULL</code> means not to use any local scale factors. A prior can currently be specified using pr_invchisq or pr_exp .
<code>Leroux</code>	this option alters the precision matrix determined by <code>factor</code> by taking a weighted average of it with the identity matrix. If <code>TRUE</code> the model gains an additional parameter, the 'Leroux' parameter, being the weight of the original, structured, precision matrix in the weighted average. By default a uniform prior for the weight and a uniform Metropolis-Hastings proposal density are employed. This

default can be changed by supplying a list with elements `a`, `b`, and `a.star`, `b.star`, implying a $\text{beta}(a, b)$ prior and a $\text{beta}(a.\text{star}, b.\text{star})$ independence proposal density. A third option is to supply a single number between 0 and 1, which is then used as a fixed value for the Leroux parameter.

<code>R0</code>	an optional equality restriction matrix acting on the coefficients defined by <code>formula</code> , for each level defined by <code>factor</code> . If <code>c</code> is the number of restrictions, <code>R0</code> is a $q0 \times c$ matrix where <code>q0</code> is the number of columns of the design matrix derived from <code>formula</code> . Together with <code>RA</code> it defines the set of equality constraints to be imposed on the vector of coefficients. Only allowed in combination with <code>var="scalar"</code> .
<code>RA</code>	an optional equality restriction matrix acting on the coefficients defined by <code>factor</code> , for each effect defined by <code>formula</code> . If <code>c</code> is the number of restrictions, <code>RA</code> is a $l \times c$ matrix where <code>l</code> is the number of levels defined by <code>factor</code> . Together with <code>R0</code> this defines the set of equality constraints to be imposed on the vector of coefficients. If <code>constr=TRUE</code> , additional constraints are imposed, corresponding to the null-vectors of the singular precision matrix in case of an intrinsic Gaussian Markov Random Field.
<code>constr</code>	whether constraints corresponding to the null-vectors of the precision matrix are to be imposed on the vector of coefficients. By default this is <code>TRUE</code> for improper or intrinsic GMRF model components, i.e. components with a singular precision matrix such as random walks or CAR spatial components.
<code>S0</code>	an optional inequality restriction matrix acting on the coefficients defined by <code>formula</code> , for each level defined by <code>factor</code> . If <code>c</code> is the number of restrictions, <code>S0</code> is a $q0 \times c$ matrix where <code>q0</code> is the number of columns of the design matrix derived from <code>formula</code> . Together with <code>SA</code> it defines the set of inequality constraints to be imposed on the vector of coefficients.
<code>SA</code>	an optional inequality restriction matrix acting on the coefficients defined by <code>factor</code> , for each effect defined by <code>formula</code> . If <code>c</code> is the number of restrictions, <code>SA</code> is a $l \times c$ matrix where <code>l</code> is the number of levels defined by <code>factor</code> . Together with <code>S0</code> this defines the set of constraints to be imposed on the vector of coefficients.
<code>formula.gl</code>	a formula of the form <code>~ glreg(...)</code> for group-level predictors around which the random effect component is hierarchically centered. See <code>glreg</code> for details.
<code>name</code>	the name of the model component. This name is used in the output of the MCMC simulation function <code>MCMCsim</code> . By default the name will be <code>'gen'</code> with the number of the model term attached.
<code>sparse</code>	whether the model matrix associated with <code>formula</code> should be sparse. The default is based on a simple heuristic based on storage size.
<code>perm</code>	whether permutation should be used in the Cholesky decomposition used for updating the model component's coefficient vector. Default is based on a simple heuristic.
<code>debug</code>	if <code>TRUE</code> a breakpoint is set at the beginning of the posterior draw function associated with this model component. Mainly intended for developers.
<code>e</code>	for internal use only.

Value

An object with precomputed quantities and functions for sampling from prior or conditional posterior distributions for this model component. Only intended for internal use by other package functions.

References

- J. Besag and C. Kooperberg (1995). On Conditional and Intrinsic Autoregression. *Biometrika* 82(4), 733-746.
- C.M. Carvalho, N.G. Polson and J.G. Scott (2010). The horseshoe estimator for sparse signals. *Biometrika* 97(2), 465-480.
- L. Fahrmeir, T. Kneib and S. Lang (2004). Penalized Structured Additive Regression for Space-Time Data: a Bayesian Perspective. *Statistica Sinica* 14, 731-761.
- A. Gelman (2006). Prior distributions for variance parameters in hierarchical models. *Bayesian Analysis* 1(3), 515-533.
- A. Gelman, D.A. Van Dyk, Z. Huang and W.J. Boscardin (2008). Using Redundant Parameterizations to Fit Hierarchical Models. *Journal of Computational and Graphical Statistics* 17(1), 95-122.
- B. Leroux, X. Lei and N. Breslow (1999). Estimation of Disease Rates in Small Areas: A New Mixed Model for Spatial Dependence. In M. Halloran and D. Berry (Eds.), *Statistical Models in Epidemiology, the Environment and Clinical Trials*, 135-178.
- T. Park and G. Casella (2008). The Bayesian Lasso. *Journal of the American Statistical Association* 103(482), 681-686.
- H. Rue and L. Held (2005). *Gaussian Markov Random Fields*. Chapman & Hall/CRC.

generate_data

Generate a data vector according to a model

Description

This function generates draws from the prior predictive distribution. Parameter values are drawn from their priors, and consequently data is generated from the sampling distribution given these parameter values.

Usage

```
generate_data(  
  formula,  
  data = NULL,  
  family = "gaussian",  
  ny = NULL,  
  ry,  
  r.mod,  
  sigma.fixed = (family != "gaussian"),  
  sigma.mod = NULL,  
)
```

```

  Q0 = NULL,
  formula.V = NULL,
  linpred = NULL
)

```

Arguments

formula	A model formula, see create_sampler. Any left-hand-side of the formula is ignored.
data	see create_sampler.
family	see create_sampler.
ny	see create_sampler.
ry	see create_sampler.
r.mod	see create_sampler.
sigma.fixed	see create_sampler.
sigma.mod	see create_sampler.
Q0	see create_sampler.
formula.V	see create_sampler.
linpred	see create_sampler.

Value

A list with a generated data vector and a list of prior means of the parameters. The parameters are drawn from their priors.

Examples

```

n <- 250
dat <- data.frame(
  x = rnorm(n),
  g = factor(sample(1:10, n, replace=TRUE)),
  ny = 10
)
gd <- generate_data(
  ~ reg(~ 1 + x, Q0=10, b0=c(0, 1), name="beta") + gen(factor = ~ g, name="v"),
  family="binomial", ny="ny", data=dat
)
gd
plot(dat$x, gd$y)

```

`get_draw`*Extract a list of parameter values for a single draw*

Description

Extract a list of parameter values for a single draw

Usage

```
get_draw(object, iter, chain)
```

Arguments

<code>object</code>	an object of class <code>draws</code> .
<code>iter</code>	iteration number.
<code>chain</code>	chain number.

Value

A list with all parameter values of draw `iter` from chain `chain`.

Examples

```
ex <- mcmcsae_example(n=50)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, n.chain=4, store.all=TRUE)
get_draw(sim, iter=20, chain=3)
```

`glreg`*Create a model object for group-level regression effects within a generic random effects component.*

Description

This function is intended to be used to specify the `formula.gl` argument to the `gen` model component specification function. Group-level predictors and hierarchical centering are not used by default, and they currently cannot be used in a model component that is sampled together with another model component in the same Gibbs block.

Usage

```
glreg(
  formula = NULL,
  remove.redundant = FALSE,
  Q0 = NULL,
  data = NULL,
  name = "",
  e = parent.frame()
)
```

Arguments

<code>formula</code>	a formula specifying the group-level predictors to be used within a model component. If no data is supplied the group-level predictors are derived as group-level means from the unit-level data passed as <code>data</code> argument to create_sampler or generate_data .
<code>remove.redundant</code>	whether redundant columns should be removed from the design matrix. Default is FALSE.
<code>Q0</code>	prior precision matrix for the group-level effects. The default is a zero matrix corresponding to a noninformative improper prior.
<code>data</code>	group-level data frame in which the group-level variables specified in <code>formula</code> are looked up.
<code>name</code>	the name of the model component. This name is used in the output of the MCMC simulation function MCMCsim . By default this name will be the name of the corresponding generic random effects component appended by <code>'_gl'</code> .
<code>e</code>	for internal use only.

Value

An object with precomputed quantities for sampling from prior or conditional posterior distributions for this model component. Only intended for internal use by other package functions.

<code>labels</code>	<i>Get and set the variable labels of a draws component for a vector-valued parameter</i>
---------------------	---

Description

Get and set the variable labels of a draws component for a vector-valued parameter

Usage

```
## S3 method for class 'dc'
labels(object, ...)

labels(object) <- value
```

Arguments

object	a component of a draws object.
...	currently not used.
value	a vector of labels.

Value

The extractor function returns the variable labels.

Examples

```
ex <- mcmcsae_example()
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=50, n.iter=100, n.chain=1, store.all=TRUE)
labels(sim$beta)
labels(sim$v)
labels(sim$beta) <- c("a", "b")
labels(sim$beta)
```

matrix-vector

Fast matrix-vector multiplications

Description

Functions for matrix-vector multiplies like `%*%` and `crossprod`, but often faster for the matrix types supported. The return value is always a numeric vector.

Usage

`M %m*v% v`

`crossprod_mv(M, v)`

Arguments

M	a matrix of class 'matrix', 'dgCMatrix', 'dsCMatrix', 'tabMatrix', or 'ddiMatrix'.
v	a numeric vector.

Value

For `%m*v%` the vector Mv and for `crossprod_mv` the vector $M'v$ where M' denotes the transpose of M .

Examples

```

M <- matrix(rnorm(10*10), 10, 10)
x <- rnorm(10)
M %m*v% x
crossprod_mv(M, x)
M <- Matrix::rsparsematrix(100, 100, nnz=100)
x <- rnorm(100)
M %m*v% x
crossprod_mv(M, x)

```

maximize_llh

Maximize log-likelihood defined inside a sampler function

Description

Maximize log-likelihood defined inside a sampler function

Usage

```
maximize_llh(sampler, method = "BFGS", control = list(fnscale = -1), ...)
```

Arguments

sampler	sampler function.
method	optimization method, passed to <code>optim</code> .
control	control parameters, passed to <code>optim</code> .
...	other parameters passed to <code>optim</code> .

Value

A list of parameter values that, provided the optimization was successful, maximize the likelihood.

Examples

```

n <- 1000
dat <- data.frame(
  x = rnorm(n),
  f = factor(sample(1:50, n, replace=TRUE))
)
df <- generate_data(
  ~ reg(~x, name="beta", Q0=1) + gen(~x, factor=~f, name="v"),
  sigma.fixed=TRUE, data=dat
)
dat$y <- df$y
sampler <- create_sampler(y ~ x + gen(~x, factor=~f, name="v"), data=dat)
opt <- maximize_llh(sampler)

```

```
str(opt)
plot(df$par$v, opt$par$v); abline(0, 1, col="red")
```

MCMC-diagnostics

Compute MCMC diagnostic measures

Description

R_hat computes Gelman-Rubin convergence diagnostics based on the MCMC output in a model component, and n_eff computes the effective sample sizes, .i.e. estimates for the number of independent samples from the posterior distribution.

Usage

```
R_hat(dc)
```

```
n_eff(dc, useFFT = TRUE, lag.max, cl = NULL)
```

Arguments

dc	a component of a draws object corresponding to a model parameter.
useFFT	whether to use the Fast Fourier Transform algorithm. Default is TRUE as this is typically faster.
lag.max	the lag up to which autocorrelations are computed in case useFFT=FALSE.
cl	a cluster for parallel computation.

Value

In case of R_hat the split-Rhat convergence diagnostic for each component of the vector parameter, and in case of n_eff the effective number of independent samples for each component of the vector parameter.

References

A. Gelman and D. B. Rubin (1992). Inference from Iterative Simulation Using Multiple Sequences. *Statistical Science* 7, 457-511.

A. Gelman, J.B. Carlin, H.S. Stern, D.B. Dunson, A. Vehtari and D.B. Rubin (2013). *Bayesian Data Analysis*, 3rd edition. Chapman & Hall/CRC.

Examples

```
ex <- mcmcsae_example()
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, n.chain=4, store.all=TRUE)
n_eff(sim$beta)
n_eff(sim$v_sigma)
n_eff(sim$v_rho)
R_hat(sim$beta)
R_hat(sim$llh_)
R_hat(sim$v_sigma)
```

MCMC-object-conversion

Convert a draws component object to another format

Description

Use `to_mcmc` to convert a draws component to class `mcmc.list`, allowing one to use MCMC diagnostic functions provided by package `cod`. Use `as.array` to convert to an array of dimension (draws, chains, parameters). The array format is supported by some packages for analysis or visualisation of MCMC simulation results, e.g. `bayesplot`. Use `as.matrix` to convert to a matrix, concatenating the chains.

Usage

```
to_mcmc(x)

## S3 method for class 'dc'
as.array(x, ...)

## S3 method for class 'dc'
as.matrix(x, colnames = TRUE, ...)
```

Arguments

<code>x</code>	a component of a draws object corresponding to a scalar or vector model parameter.
<code>...</code>	currently ignored.
<code>colnames</code>	whether column names should be set.

Value

The draws component coerced to a `mcmc.list`, an array, or a matrix.

Examples

```

data(iris)
sampler <- create_sampler(Sepal.Length ~ reg(~ Petal.Length + Species, name="beta"), data=iris)
sim <- MCMCsim(sampler, burnin=100, n.chain=2, n.iter=400)
summary(sim)
if (require("coda", quietly=TRUE)) {
  mcbeta <- to_mcmc(sim$beta)
  geweke.diag(mcbeta)
}
str(as.array(sim$beta))
str(as.matrix(sim$beta))

# generate some example data
n <- 250
dat <- data.frame(x=runif(n), f=as.factor(sample(1:5, n, replace=TRUE)))
gd <- generate_data(~ reg(~ x + f, Q0=1, name="beta"), data=dat)
dat$y <- gd$y
sampler <- create_sampler(y ~ reg(~ x + f, name="beta"), data=dat)
sim <- MCMCsim(sampler, n.chain=2, n.iter=400)
str(sim$beta)
str(as.array(sim$beta))
bayesplot::mcmc_hist(as.array(sim$beta))
bayesplot::mcmc_dens_overlay(as.array(sim$beta))
# fake data simulation check:
bayesplot::mcmc_recover_intervals(as.array(sim$beta), gd$pars$beta)
bayesplot::mcmc_recover_hist(as.array(sim$beta), gd$pars$beta)

ex <- mcmc-sae-example()
plot(ex$dat$fT, ex$dat$y)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, n.chain=2, n.iter=400, store.all=TRUE)
str(sim$beta)
str(as.matrix(sim$beta))
# fake data simulation check:
bayesplot::mcmc_recover_intervals(as.matrix(sim$beta), ex$pars$beta)
bayesplot::mcmc_recover_intervals(as.matrix(sim$u), ex$pars$u)

```

Description

These functions are intended for use in the family argument of `create_sampler`. In future versions these functions may gain additional arguments, but currently the corresponding functions `gaussian` and `binomial` can be used as well.

Usage

```
f_gaussian(link = "identity")  
  
f_binomial(link = c("logit", "probit"))  
  
f_negbinomial(link = "logit")
```

Arguments

link the name of a link function. Currently the only allowed link functions are: "identity" for (log-)Gaussian sampling distributions, "logit" (default) and "probit" for binomial distributions and "log" for negative binomial sampling distributions.

Value

A family object.

mcmcsae_example	<i>Generate artificial data according to an additive spatio-temporal model</i>
-----------------	--

Description

This function is used to generate data for several examples.

Usage

```
mcmcsae_example(n = 100L)
```

Arguments

n the size of the generated dataset.

Value

A list containing the generated dataset, the values of the model parameters, and the model specification as a formula.

Examples

```
ex <- mcmcsae_example()  
str(ex)
```

Description

Given a sampler object this function runs a MCMC simulation and stores the posterior draws. A sampler object for a wide class of multilevel models can be created using `create_sampler`, but users can also define their own sampler functions, see below. `MCMCsim` allows to choose the parameters for which simulation results must be stored. It is possible to define derived quantities that will also be stored. To save memory, it is also possible to only store Monte Carlo means/standard errors for some large vector parameters, say. Another way to use less memory is to save the simulation results of large vector parameters to file. For parameters specified in `plot.trace` traceplots or pair plots of multiple parameters are displayed during the simulation.

Usage

```
MCMCsim(
  sampler,
  from.prior = FALSE,
  n.iter = 1000L,
  n.chain = 3L,
  thin = 1L,
  burnin = if (from.prior) 0L else 250L,
  start = NULL,
  store,
  store.all = FALSE,
  pred = NULL,
  store.mean,
  store.sds = FALSE,
  to.file = NULL,
  filename = "MCMCdraws_",
  write.single.prec = FALSE,
  verbose = TRUE,
  n.progress = n.iter%%10L,
  trace.convergence = NULL,
  stop.on.convergence = FALSE,
  convergence.bound = 1.05,
  plot.trace = NULL,
  add.to.plot = TRUE,
  plot.type = "1",
  n.cores = 1L,
  cl = NULL,
  seed = NULL,
  export = NULL
)
```

Arguments

sampler	sampler object created by <code>create_sampler</code> .
from.prior	whether to sample from the prior. By default <code>from.prior=FALSE</code> and samples are taken from the posterior.
n.iter	number of draws after burnin.
n.chain	number of independent chains.
thin	only every thin'th draw is kept.
burnin	number of draws to discard at the beginning of each chain.
start	an optional function to generate starting values or a list containing for each chain a named list of starting values. It may be used to provide starting values for some or all parameters. The sampler object's own start function, if it exists, is called to generate any starting values not provided by the user.
store	vector of names of parameters to store MCMC draws for. By default, simulations are stored for all parameters returned by <code>sampler\$store_default</code> .
store.all	if TRUE simulation vectors of all parameters returned by the sampling function of <code>sampler</code> will be stored. The default is FALSE, and in that case only simulations for the parameters named in <code>store</code> are stored.
pred	list of character strings defining derived quantities to be computed (and stored) for each draw.
store.mean	vector of names of parameters for which only the mean (per chain) is to be stored. This may be useful for large vector parameters (e.g. regression residuals) for which storing complete MCMC output would use too much memory. The function <code>sampler\$store_mean_default</code> exists it provides the default.
store.sds	if TRUE store for all parameters in <code>store.mean</code> , besides the mean, also the standard deviation. Default is FALSE.
to.file	vector of names of parameters to write to file.
filename	name of file to write parameter draws to. Each named parameter is written to a separate file, named <code>filename_parametername</code> .
write.single.prec	Whether to write to file in single precision. Default is FALSE.
verbose	if FALSE no output is sent to the screen during the simulation. TRUE by default.
n.progress	print iteration number and diagnostics and update plots after so many iterations.
trace.convergence	vector of names of parameters for which Gelman-Rubin R-hat diagnostics are printed to the screen every <code>n.progress</code> iterations.
stop.on.convergence	if TRUE stop the simulation if the R-hat diagnostics for all parameters in <code>trace.convergence</code> are less than <code>convergence.bound</code> .
convergence.bound	threshold used with <code>stop.on.convergence</code> .
plot.trace	character vector of parameter names for which to plot draws during the simulation. For one or two parameters traceplots will be shown, and if more parameters are specified the results will be displayed in a pairs plot. For vector parameters a specific component can be selected using brackets, e.g. "beta[2]".

<code>add.to.plot</code>	if TRUE traceplot is added to every <code>n.progress</code> iterations, otherwise a new plot (with new scales etc) is made after each <code>n.progress</code> iterations.
<code>plot.type</code>	default is "l" (lines).
<code>n.cores</code>	the number of cpu cores to use. Default is one, i.e. no parallel computation. If an existing cluster <code>cl</code> is provided, <code>n.cores</code> will be set to the number of workers in that cluster.
<code>cl</code>	an existing cluster can be passed for parallel computation. If NULL and <code>n.cores > 1</code> , a new cluster is created.
<code>seed</code>	a random seed (integer). For parallel computation it is used to independently seed RNG streams for all workers.
<code>export</code>	a character vector with names of objects to export to the workers. This may be needed for parallel execution if expressions in <code>pred</code> depend on global variables.

Details

A sampler object is an environment containing data and functions to use for sampling. The following elements of the sampler object are used by MCMCsim:

start function to generate starting values.

draw function to draw samples, typically from a full conditional posterior distribution.

rprior function to draw from a prior distribution.

coef.names list of vectors of parameter coefficient names, for vector parameters.

MHpars vector of names of parameters that are sampled using a Metropolis-Hastings (MH) sampler; acceptance rates are kept for these parameters.

adapt function of acceptance rates of MHpars to adapt MH-kernel, called every 100 iterations during the burn-in period.

Value

An object of class `draws` containing posterior draws as well as some meta information.

Examples

```
# 1. create a sampler function
sampler <- new.env()
sampler$draw <- function(p) list(x=rnorm(1L), y=runif(1L))
# 2. do the simulation
sim <- MCMCsim(sampler, store=c("x", "y"))
str(sim)
summary(sim)

# example that requires start values or a start function
sampler$draw <- function(p) list(x=rnorm(1L), y=p$x * runif(1L))
sampler$start <- function(p) list(x=rnorm(1L), y=runif(1L))
sim <- MCMCsim(sampler, store=c("x", "y"))
summary(sim)
plot(sim, c("x", "y"))
```

```
# example using create_sampler; first generate some data
n <- 100
dat <- data.frame(x=runif(n), f=as.factor(sample(1:4, n, replace=TRUE)))
gd <- generate_data(~ reg(~ x + f, Q0=1, name="beta"), data=dat)
dat$y <- gd$y
sampler <- create_sampler(y ~ x + f, data=dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=400, n.chain=2)
(summary(sim))
gd$pars
```

mec

Create a model component object for a regression (fixed effects) component in the linear predictor with measurement errors in quantitative covariates

Description

This function is intended to be used on the right hand side of the formula argument to [create_sampler](#) or [generate_data](#). It creates an additive regression term in the model's linear predictor. By default, the prior for the regression coefficients is improper uniform. If b_0 or Q_0 are specified the prior becomes normal with mean b_0 (default 0) and variance (matrix) $\sigma^2 Q_0^{-1}$ where σ^2 is the overall scale parameter of the model, if any. Covariates are assumed to be measured subject to normally distributed errors with zero mean and variance specified using the formula or V arguments. Note that this means that formula should only contain quantitative variables, and no intercept.

Usage

```
mec(
  formula = ~1,
  sparse = NULL,
  X = NULL,
  V = NULL,
  Q0 = NULL,
  b0 = NULL,
  R = NULL,
  r = NULL,
  S = NULL,
  s = NULL,
  lower = NULL,
  upper = NULL,
  name = "",
  perm = NULL,
  debug = FALSE,
  e = parent.frame()
)
```

Arguments

formula	a formula specifying the predictors subject to measurement error and possibly their variances as well. In the latter case the formula syntax $\sim (x1 V.x1) + (x2 V.x2) + \dots$ should be used where $x1, x2, \dots$ are the names of (quantitative) predictors and $V.x1, V.x2, \dots$ are the names of the variables holding the corresponding measurement error variances. If only the predictors are specified the formula has the usual form $\sim x1 + x2 + \dots$. In that case variances should be specified using argument <code>V</code> . All variable names are looked up in the data frame passed as <code>data</code> argument to <code>create_sampler</code> or <code>generate_data</code> , or in <code>environment(formula)</code> .
sparse	whether the model matrix associated with <code>formula</code> should be sparse. The default is to base this on a simple heuristic.
X	a (possibly sparse) design matrix can be specified directly, as an alternative to the creation of one based on <code>formula</code> . If <code>X</code> is specified <code>formula</code> is ignored.
V	measurement error variance; can contain zeros
Q0	prior precision matrix for the regression effects. The default is a zero matrix corresponding to a noninformative improper prior. It can be specified as a scalar value, as a numeric vector of appropriate length, or as a matrix object.
b0	prior mean for the regression effect. Defaults to a zero vector. It can be specified as a scalar value or as a numeric vector of appropriate length.
R	optional constraint matrix for equality restrictions $R'x = r$ where x is the vector of regression effects.
r	right hand side for the equality constraints.
S	optional constraint matrix for inequality constraints $S'x \geq s$ where x is the vector of regression effects.
s	right hand side for the inequality constraints.
lower	as an alternative to <code>s</code> , <code>lower</code> and <code>upper</code> may be specified for two-sided constraints $lower \leq S'x \leq upper$.
upper	as an alternative to <code>s</code> , <code>lower</code> and <code>upper</code> may be specified for two-sided constraints $lower \leq S'x \leq upper$.
name	the name of the model component. This name is used in the output of the MCMC simulation function <code>MCMCsim</code> . By default the name will be 'reg' with the number of the model term attached.
perm	whether permutation should be used in the Cholesky decomposition used for updating the model component's coefficient. Default is based on a simple heuristic.
debug	if TRUE a breakpoint is set at the beginning of the posterior draw function associated with this model component. Mainly intended for developers.
e	for internal use only.

Value

an object with precomputed quantities and functions for sampling from prior or conditional posterior distributions for this model component. Only intended for internal use by other package functions.

References

L.M. Ybarra and S.L. Lohr (2008). Small area estimation when auxiliary information is measured with error. *Biometrika* 95(4), 919-931.

S. Arima, G.S. Datta and B. Liseo (2015). Bayesian estimators for small area models when auxiliary information is measured with error. *Scandinavian Journal of Statistics* 42(2), 518-529.

Examples

```
# example of Ybarra and Lohr (2008)
m <- 50
X <- rnorm(m, mean=5, sd=3) # true covariate values
v <- rnorm(m, sd=2)
theta <- 1 + 3*X + v # true values
psi <- rgamma(m, shape=4.5, scale=2)
e <- rnorm(m, sd=sqrt(psi)) # sampling error
y <- theta + e # direct estimates
C <- c(rep(3, 10), rep(0, 40)) # measurement error for first 10 values
W <- X + rnorm(m, sd=sqrt(C)) # covariate subject to measurement error

# fit Ybarra-Lohr model
sampler <- create_sampler(
  y ~ 1 + mec(~ 0 + W, V=C) + gen(factor=~local_),
  Q0=1/psi, sigma.fixed=TRUE, linpred="fitted"
)
sim <- MCMCsim(sampler, n.iter=800, n.chain=2, store.all=TRUE, verbose=FALSE)
(summ <- summary(sim))
plot(X, W, xlab="true X", ylab="inferred X")
points(X, summ$mec2_X[, "Mean"], col="green")
abline(0, 1, col="red")
legend("topleft", legend=c("prior mean", "posterior mean"), col=c("black", "green"), pch=c(1,1))
```

model-information-criteria

Compute DIC, WAIC and leave-one-out cross-validation model measures

Description

Compute the Deviance Information Criterion (DIC) or Watanabe-Akaike Information Criterion (WAIC) from an object of class `draws` output by `MCMCsim`. Method `waic.draws` computes WAIC using package `loo`. Method `loo.draws` also depends on package `loo` to compute a Pareto-smoothed importance sampling (PSIS) approximation to leave-one-out cross-validation.

Usage

```

compute_DIC(x, use.pV = FALSE)

compute_WAIC(x, diagnostic = FALSE, batch.size = NULL, show.progress = TRUE)

## S3 method for class 'draws'
waic(x, by.unit = FALSE, ...)

## S3 method for class 'draws'
loo(x, r_eff = FALSE, n.cores = 1L, ...)

```

Arguments

<code>x</code>	an object of class <code>draws</code> .
<code>use.pV</code>	whether half the posterior variance of the deviance should be used as an alternative estimate of the effective number of model parameters for DIC.
<code>diagnostic</code>	whether vectors of log-pointwise-predictive-densities and pointwise contributions to the WAIC effective number of model parameters should be returned.
<code>batch.size</code>	number of data units to process per batch.
<code>show.progress</code>	whether to show a progress bar.
<code>by.unit</code>	if TRUE the computation is carried out unit-by-unit, which is slower but uses much less memory.
<code>...</code>	Other arguments, passed to <code>loo</code> . Not currently used by <code>waic.draws</code> .
<code>r_eff</code>	whether to compute relative effective sample size estimates for the likelihood of each observation. This takes more time, but should result in a better PSIS approximation. See <code>loo</code> .
<code>n.cores</code>	how many cores to use.

Value

For `compute_DIC` a vector with the deviance information criterion and effective number of model parameters. For `compute_WAIC` a vector with the WAIC model selection criterion and WAIC effective number of model parameters. Method `waic` returns an object of class `waic_loo`, see the documentation for `waic` in package `loo`. Method `loo` returns an object of class `psis_loo`, see `loo`.

References

- D. Spiegelhalter, N. Best, B. Carlin and A. van der Linde (2002). Bayesian Measures of Model Complexity and Fit. *Journal of the Royal Statistical Society B* 64 (4), 583-639.
- S. Watanabe (2010). Asymptotic equivalence of Bayes cross validation and widely applicable information criterion in singular learning theory. *Journal of Machine Learning* 11, 3571-3594.
- A. Gelman, J. Hwang and A. Vehtari (2014). Understanding predictive information criteria for Bayesian models. *Statistics and Computing* 24, 997-1016.
- A. Vehtari, A. Gelman and J. Gabry (2015). Pareto smoothed importance sampling. arXiv preprint arXiv:1507.02646.

A. Vehtari, A. Gelman and J. Gabry (2017). Practical Bayesian model evaluation using leave-one-out cross-validation and WAIC. *Statistics and Computing* 27, 1413-1432.

P.-C. Buerkner, J. Gabry and A. Vehtari (2019). Bayesian leave-one-out cross-validation for non-factorizable normal models. [arXiv:1810.10559v3](https://arxiv.org/abs/1810.10559v3).

Examples

```
ex <- mcmcsae_example(n=100)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=300, n.chain=4, store.all=TRUE)
compute_DIC(sim)
compute_WAIC(sim)
if (require(loo)) {
  waic(sim)
  loo(sim, r_eff=TRUE)
}
```

model_matrix

Compute possibly sparse model matrix

Description

Compute possibly sparse model matrix

Usage

```
model_matrix(
  formula,
  data = environment(formula),
  contrasts.arg = NULL,
  drop.unused.levels = FALSE,
  sparse = NULL,
  drop0 = TRUE,
  catsep = "",
  by = NULL,
  tabM = FALSE
)
```

Arguments

formula	model formula.
data	data frame containing all variables used in formula. These variables should not contain missing values. An error is raised in case any of them does.

<code>contrasts.arg</code>	specification of contrasts for factor variables. Currently supported are "contr.none" (no contrasts applied), "contr.treatment" (first level removed) and "contr.SAS" (last level removed). Alternatively, a named list specifying a single level per factor variable can be passed.
<code>drop.unused.levels</code>	whether empty levels of individual factor variables should be removed.
<code>sparse</code>	if TRUE a sparse matrix of class <code>dgMatrix</code> is returned. This can be efficient for large datasets and a model containing categorical variables with many categories. If <code>sparse=NULL</code> , the default, whether a sparse or dense model matrix is returned is based on a simple heuristic.
<code>drop0</code>	whether to drop any remaining explicit zeros in resulting sparse matrix.
<code>catsep</code>	separator for concatenating factor variable names and level names. By default it is the empty string, reproducing the labels of <code>model.matrix</code> .
<code>by</code>	a vector by which to aggregate the result.
<code>tabM</code>	if TRUE return a list of <code>tabMatrix</code> objects.

Value

Design matrix X , either an ordinary matrix or a sparse `dgMatrix`.

`nchains-ndraws-nvars` *Get the number of chains, samples per chain or the number of variables in a simulation object*

Description

Get the number of chains, samples per chain or the number of variables in a simulation object

Usage

`nchains(object)`

`ndraws(object)`

`nvars(dc)`

Arguments

`object` a draws object or component of a draws object.

`dc` a component of a draws object.

Value

The number of chains or retained samples per chain or the number of variables.

Examples

```
ex <- mcmc_sae_example(n=50)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, n.chain=5, store.all=TRUE)
nchains(sim); nchains(sim$beta)
ndraws(sim); ndraws(sim$beta)
nvars(sim$beta); nvars(sim$sigma_); nvars(sim$llh_); nvars(sim$v)
plot(sim, "beta")
nchains(subset(sim$beta, chains=1:2))
ndraws(subset(sim$beta, draws=sample(1:ndraws(sim), 100)))
nvars(subset(sim$, vars=1:2))
```

par_names

Get the parameter names from a draws object

Description

Get the parameter names from a draws object

Usage

```
par_names(draws)
```

Arguments

draws a draws object.

Value

The names of the parameters whose MCMC simulations are stored in draws.

Examples

```
data(iris)
sampler <- create_sampler(Sepal.Length ~
  reg(~ Petal.Length + Species, name="beta"), data=iris)
sim <- MCMCsim(sampler, burnin=100, n.iter=400)
(summary(sim))
par_names(sim)
```

plot.dc	<i>Trace, density and autocorrelation plots for (parameters of a) draws component object</i>
---------	--

Description

Trace, density and autocorrelation plots for (parameters of a) draws component object

Usage

```
## S3 method for class 'dc'
plot(x, nrows, ncols, ask = FALSE, ...)
```

Arguments

x	a draws component object.
nrows	number of rows in plot layout.
ncols	number of columns in plot layout.
ask	ask before plotting the next page; default is FALSE.
...	arguments passed to density .

Examples

```
ex <- mcmc_sae_example(n=50)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, store.all=TRUE)
plot(sim$u)
```

plot.draws	<i>Trace, density and autocorrelation plots</i>
------------	---

Description

Trace, density and autocorrelation plots for selected components of a draws object.

Usage

```
## S3 method for class 'draws'
plot(x, vnames, nrows, ncols, ask = FALSE, ...)
```

Arguments

x	an object of class draws.
vnames	optional character vector to select a subset of parameters.
nrows	number of rows in plot layout.
ncols	number of columns in plot layout.
ask	ask before plotting the next page; default is FALSE.
...	arguments passed to density .

Examples

```
ex <- mcmcsae_example(n=50)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, store.all=TRUE)
plot(sim, c("beta", "u", "u_sigma", "v_sigma"), ask=TRUE)
```

plot_coef

Plot a set of model coefficients or predictions with uncertainty intervals based on summaries of simulation results or other objects.

Description

This function plots estimates with error bars. Multiple sets of estimates can be compared. The error bars can either be based on standard errors or on explicitly specified lower and upper bounds. The function is adapted from function `plot.sae` in package **hbsae**, which in turn was adapted from function `coefplot.default` from package **arm**.

Usage

```
plot_coef(
  ...,
  n.se = 1,
  est.names,
  sort.by = NULL,
  decreasing = FALSE,
  index = NULL,
  maxrows = 50L,
  maxcols = 6L,
  offset = 0.1,
  cex.var = 0.8,
  mar = c(0.1, 2.1, 5.1, 0.1)
)
```

Arguments

...	dc_summary objects (output by the summary method for simulation objects of class dc), sae objects (output by the functions of package hbsae), or lists. In case of a list the components used are those with name est for point estimates, se for standard error based intervals or lower and upper for custom intervals. Instead of dc_summary objects matrix objects are also supported as long as they contain columns named "Mean" and "SD" as do dc_summary objects. Named parameters of other types that do not match any other argument names are passed to lower-level plot functions.
n.se	number of standard errors below and above the point estimates to use for error bars. By default equal to 1. This only refers to the objects of class dc_summary and sae.
est.names	labels to use in the legend for the components of the ... argument
sort.by	vector by which to sort the coefficients, referring to the first object passed.
decreasing	if TRUE, sort in decreasing order (default).
index	vector of names or indices of the selected areas to be plotted.
maxrows	maximum number of rows in a column.
maxcols	maximum number of columns of estimates on a page.
offset	space used between plots of multiple estimates for the same area.
cex.var	the fontsize of the variable names, default=0.8.
mar	a numerical vector of the form c(bottom, left, top, right) which gives the number of lines of margin to be specified on the four sides of the plot. The default is c(0,1,5,0).

Examples

```
# create artificial data
set.seed(21)
n <- 100
dat <- data.frame(
  x=runif(n),
  f=factor(sample(1:20, n, replace=TRUE))
)
model <- ~ reg(~ x, Q0=1, name="beta") + gen(factor=~f, name="v")
gd <- generate_data(model, data=dat)
dat$y <- gd$y
# fit a base model
model0 <- y ~ reg(~ 1, name="beta") + gen(factor=~f, name="v")
sampler <- create_sampler(model0, data=dat, block=TRUE)
sim <- MCMCsim(sampler, store.all=TRUE)
(summ0 <- summary(sim))
# fit 'true' model
model <- y ~ reg(~ x, name="beta") + gen(factor=~f, name="v")
sampler <- create_sampler(model, data=dat, block=TRUE)
sim <- MCMCsim(sampler, store.all=TRUE)
(summ <- summary(sim))
```



```
# compare random effect estimates against true parameter values
plot_coef(summ0$v, summ$v, list(est=gd$pars$v), n.se=2, offset=0.2,
  maxrows=10, est.names=c("base model", "true model", "true"))
```

posterior-moments	<i>Get means or standard deviations of parameters from the MCMC output in a draws object</i>
-------------------	--

Description

Get means or standard deviations of parameters from the MCMC output in a draws object

Usage

```
get_means(draws, vnames = NULL)
```

```
get_sds(draws, vnames = NULL)
```

Arguments

draws	an object of class draws.
vnames	optional character vector to select a subset of parameters.

Value

A list with simulation means or standard deviations.

Examples

```
ex <- mcmcsae_example(n=50)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, n.chain=4)
get_means(sim)
get_means(sim, "e_")
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, n.chain=4,
  store.mean=c("beta", "u"), store.sds=TRUE)
summary(sim, "beta")
get_means(sim, "beta")
get_sds(sim, "beta")
get_means(sim, "u")
get_sds(sim, "u")
```

predict.draws *Generate draws from the predictive distribution*

Description

Generate draws from the predictive distribution

Usage

```
## S3 method for class 'draws'
predict(
  object,
  newdata = NULL,
  X. = if (is.null(newdata)) "in-sample" else NULL,
  type = c("data", "link", "response"),
  var = NULL,
  ny = NULL,
  fun. = identity,
  labels = NULL,
  ppcheck = FALSE,
  iters = NULL,
  to.file = FALSE,
  filename,
  write.single.prec = FALSE,
  show.progress = TRUE,
  n.cores = 1L,
  cl = NULL,
  seed = NULL,
  export = NULL,
  ...
)
```

Arguments

object	draws object.
newdata	data frame with auxiliary information to be used for prediction.
X.	a list of design matrices; alternatively, X. equals 'in-sample' or 'linpred'. If 'in-sample' (the default if newdata is not supplied), the design matrices for in-sample prediction are used. If 'linpred' the 'linpred_' component of object is used.
type	the type of predictions. The default is "data", meaning that new data is generated according to the predictive distribution. If type="link" only the linear predictor for the mean is generated, and in case type="response" the linear predictor is transformed to the response scale. For Gaussian models type="link" and type="response" are equivalent. For binomial and negative binomial models type="response" returns the simulations of the latent probabilities.

var	variance(s) used for out-of-sample prediction. By default 1.
ny	number of trials for used for out-of-sample prediction in case of a binomial model. By default 1.
fun.	function applied to the vector of posterior predictions to compute one or multiple summaries or test statistics. The function can have one or two arguments. The first argument is always the vector of posterior predictions. The optional second argument represents a list of model parameters, needed only when a test statistic depends on them.
labels	optional names for the output object. Must be a vector of the same length as the result of fun..
ppcheck	if TRUE, function fun. is also applied to the observed data and an MCMC approximation is computed of the posterior predictive probability that the test statistic for predicted data is greater than the test statistic for the observed data.
iters	iterations in object to use for prediction. Default NULL means that all draws from object are used.
to.file	if TRUE the predictions are streamed to file.
filename	name of the file to write predictions to in case to.file=TRUE.
write.single.prec	Whether to write to file in single precision. Default is FALSE.
show.progress	whether to show a progress bar.
n.cores	the number of cpu cores to use. Default is one, i.e. no parallel computation. If an existing cluster cl is provided, n.cores will be set to the number of workers in that cluster.
cl	an existing cluster can be passed for parallel computation. If NULL and n.cores > 1, a new cluster is created.
seed	a random seed (integer). For parallel computation it is used to independently seed RNG streams for all workers.
export	a character vector with names of objects to export to the workers. This may be needed for parallel execution if expressions in fun. depend on global variables.
...	currently not used.

Value

An object of class `dc`, containing draws from the posterior (or prior) predictive distribution. If `ppcheck=TRUE` posterior predictive p-values are returned as an additional attribute. In case `to.file=TRUE` the file name used is returned.

Examples

```
n <- 250
dat <- data.frame(x=runif(n))
dat$y <- 1 + dat$x + rnorm(n)
sampler <- create_sampler(y ~ x, data=dat)
sim <- MCMCsim(sampler)
```

```
summary(sim)
# in-sample prediction
pred <- predict(sim, ppcheck=TRUE)
hist(attr(pred, "ppp"))
# out-of-sample prediction
pred <- predict(sim, newdata=data.frame(x=seq(0, 1, by=0.1)))
summary(pred)
```

print.dc_summary *Display a summary of a dc object*

Description

Display a summary of a dc object

Usage

```
## S3 method for class 'dc_summary'
print(x, digits = 3L, max.lines = 1000L, tail = FALSE, sort = NULL, ...)
```

Arguments

x	an object of class dc_summary.
digits	number of digits to use, defaults to 3.
max.lines	maximum number of lines to display. If NULL, all elements are displayed.
tail	if TRUE the last instead of first at most max.lines are displayed.
sort	column name on which to sort the output.
...	passed on to print.default.

Examples

```
ex <- mcmc_sae_example()
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, store.all=TRUE)
print(summary(sim$u), sort="n_eff")
```

```
print.draws_summary
```

Print a summary of MCMC simulation results

Description

Display a summary of a draws object, output by `MCMCsim`.

Usage

```
## S3 method for class 'draws_summary'
print(x, digits = 3L, max.lines = 10L, tail = FALSE, sort = NULL, ...)
```

Arguments

<code>x</code>	an object of class <code>draws_summary</code> as output by <code>summary.draws</code> .
<code>digits</code>	number of digits to use, defaults to 3.
<code>max.lines</code>	maximum number of elements per vector parameter to display. If <code>NULL</code> , all elements are displayed.
<code>tail</code>	if <code>TRUE</code> the last instead of first <code>max.lines</code> of each component are displayed.
<code>sort</code>	column name on which to sort the output.
<code>...</code>	passed on to <code>print.default</code> .

Examples

```
ex <- mcmc_sae_example()
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, store.all=TRUE)
print(summary(sim), sort="n_eff")
```

```
pr_exp
```

Create an object containing information about exponential prior distributions

Description

Create an object containing information about exponential prior distributions

Usage

```
pr_exp(scale = 1, n = NULL, post = FALSE)
```

Arguments

scale	scale parameter of length 1 or n.
n	dimension, if known. For internal use only.
post	whether conditional posterior sampling function should be created. For internal use only.

Value

An environment with information about the prior and possibly conditional posterior distribution(s), to be used by other package functions.

pr_fixed	<i>Create an object containing information about a degenerate prior fixing a parameter to a fixed value</i>
----------	---

Description

Create an object containing information about a degenerate prior fixing a parameter to a fixed value

Usage

```
pr_fixed(value = 1, n = NULL, post = FALSE)
```

Arguments

value	value parameter of length 1 or n.
n	dimension, if known. For internal use only.
post	whether conditional posterior sampling function should be created. For internal use only.

Value

An environment with information about the prior and possibly conditional posterior distribution(s), to be used by other package functions.

pr_gig	<i>Create an object containing information about Generalized Inverse Gaussian (GIG) prior distributions</i>
--------	---

Description

Create an object containing information about Generalized Inverse Gaussian (GIG) prior distributions

Usage

```
pr_gig(a, b, p, n = NULL, post = FALSE)
```

Arguments

a	parameter of length 1 or n.
b	parameter of length 1 or n.
p	parameter of length 1 or n.
n	dimension, if known. For internal use only.
post	whether conditional posterior sampling function should be created. For internal use only.

Value

An environment with information about the prior and possibly conditional posterior distribution(s), to be used by other package functions.

pr_invchisq	<i>Create an object containing information about inverse chi-squared priors with possibly modeled degrees of freedom and scale parameters</i>
-------------	---

Description

Create an object containing information about inverse chi-squared priors with possibly modeled degrees of freedom and scale parameters

Usage

```
pr_invchisq(df = 1, scale = 1, n = NULL, post = FALSE)
```

Arguments

df	degrees of freedom parameter. This can be a numeric scalar or vector of length n , the dimension of the parameter vector. Alternatively, for a scalar degrees of freedom parameter, <code>df="modeled"</code> or <code>df="modelled"</code> assign a default (gamma) prior to the degrees of freedom parameter. For more control of this gamma prior a list can be passed with some of the following components: alpha0 shape parameter of the gamma distribution beta0 rate parameter of the gamma distribution proposal "RW" for random walk Metropolis-Hastings or "mala" for Metropolis-adjusted Langevin tau (starting) scale of Metropolis-Hastings update adapt whether to adapt the scale of the proposal distribution during burnin to achieve better acceptance rates.
scale	scalar or vector scale parameter. Alternatively, <code>scale="modeled"</code> or <code>scale="modelled"</code> puts a default chi-squared prior on the scale parameter. For more control on this chi-squared prior a list can be passed with some of the following components: df degrees of freedom (scalar or vector) scale scale (scalar or vector) common whether the modeled scale parameter of the inverse chi-squared distribution is (a scalar parameter) common to all n parameters.
n	dimension, if known. For internal use only.
post	whether conditional posterior sampling function should be created. For internal use only.

Value

An environment with information about the prior and possibly conditional posterior distribution(s), to be used by other package functions.

pr_invwishart	<i>Create an object containing information about an inverse Wishart prior, possibly with modeled scale matrix</i>
---------------	---

Description

Create an object containing information about an inverse Wishart prior, possibly with modeled scale matrix

Usage

```
pr_invwishart(df = NULL, scale = NULL, n = NULL)
```


Arguments

df	Degrees of freedom parameter. This should be a scalar numeric value. The default value is the dimension (n) plus one.
scale	Either a (known) scale matrix, or scale="modeled" or scale="modelled", which puts default chi-squared priors on the diagonal elements of the inverse Wishart scale matrix. For more control on these chi-squared priors a list can be passed with some of the following components: df degrees of freedom (scalar or vector) of the chi-squared distribution(s) scale scale parameter(s) of the chi-squared distribution(s) common whether the modeled scale parameter of the inverse chi-squared distribution is (a scalar parameter) common to all n diagonal elements.
n	dimension, if known. For internal use only.

Value

An environment with information about the prior distribution used, to be used by other package functions.

References

A. Huang and M.P. Wand (2013). Simple marginally noninformative prior distributions for covariance matrices. *Bayesian Analysis* 8, 439-452.

read_draws	<i>Read MCMC draws from a file</i>
------------	------------------------------------

Description

Read draws written to file by `MCMCsim` used with argument `to.file`.

Usage

```
read_draws(name, filename = paste0("MCMCdraws_", name, ".dat"))
```

Arguments

name	name of the parameter to load the corresponding file with posterior draws for.
filename	name of the file in which the draws are stored.

Value

An object of class `dc` containing MCMC draws for a (vector) parameter.

Examples

```
## Not run:
# NB this example creates a file "MCMCdraws_e_.RData" in the working directory
n <- 100
dat <- data.frame(x=runif(n), f=as.factor(sample(1:5, n, replace=TRUE)))
gd <- generate_data(~ reg(~ x + f, Q0=1, name="beta"), data=dat)
dat$y <- gd$y
sampler <- create_sampler(y ~ reg(~ x + f, name="beta"), data=dat)
# run the MCMC simulation and write draws of residuals to file:
sim <- MCMCsim(sampler, n.iter=500, to.file="e_")
summary(sim)
mcrec <- read_draws("e_")
summary(mcrec)

## End(Not run)
```

reg

Create a model component object for a regression (fixed effects) component in the linear predictor

Description

This function is intended to be used on the right hand side of the formula argument to `create_sampler` or `generate_data`. It creates an additive regression term in the model's linear predictor. By default, the prior for the regression coefficients is improper uniform. If b_0 or Q_0 are specified the prior becomes normal with mean b_0 (default 0) and variance (matrix) $\sigma^2 Q_0^{-1}$ where σ^2 is the overall scale parameter of the model, if any.

Usage

```
reg(
  formula = ~1,
  remove.redundant = FALSE,
  sparse = NULL,
  X = NULL,
  Q0 = NULL,
  b0 = NULL,
  R = NULL,
  r = NULL,
  S = NULL,
  s = NULL,
  lower = NULL,
  upper = NULL,
  name = "",
  perm = NULL,
  debug = FALSE,
  e = parent.frame()
)
```

Arguments

formula	a formula specifying the predictors to be used in the model, in the same way as the right hand side of the formula argument of R's <code>lm</code> function. Variable names are looked up in the data frame passed as data argument to <code>create_sampler</code> or <code>generate_data</code> , or in <code>environment(formula)</code> .
remove.redundant	whether redundant columns should be removed from the design matrix. Default is FALSE. But note that treatment contrasts are automatically applied to all factor variables in formula.
sparse	whether the model matrix associated with formula should be sparse. The default is to base this on a simple heuristic.
X	a (possibly sparse) design matrix can be specified directly, as an alternative to the creation of one based on formula. If X is specified formula is ignored.
Q0	prior precision matrix for the regression effects. The default is a zero matrix corresponding to a noninformative improper prior. It can be specified as a scalar value, as a numeric vector of appropriate length, or as a matrix object.
b0	prior mean for the regression effect. Defaults to a zero vector. It can be specified as a scalar value or as a numeric vector of appropriate length.
R	optional constraint matrix for equality restrictions $R'x = r$ where x is the vector of regression effects.
r	right hand side for the equality constraints.
S	optional constraint matrix for inequality constraints $S'x \geq s$ where x is the vector of regression effects.
s	right hand side for the inequality constraints.
lower	as an alternative to s, lower and upper may be specified for two-sided constraints $lower \leq S'x \leq upper$.
upper	as an alternative to s, lower and upper may be specified for two-sided constraints $lower \leq S'x \leq upper$.
name	the name of the model component. This name is used in the output of the MCMC simulation function <code>MCMCsim</code> . By default the name will be 'reg' with the number of the model term attached.
perm	whether permutation should be used in the Cholesky decomposition used for updating the model component's coefficient. Default is based on a simple heuristic.
debug	if TRUE a breakpoint is set at the beginning of the posterior draw function associated with this model component. Mainly intended for developers.
e	for internal use only.

Value

an object with precomputed quantities and functions for sampling from prior or conditional posterior distributions for this model component. Only intended for internal use by other package functions.

Examples

```

data(iris)
# default: flat priors on regression coefficients
sampler <- create_sampler(Sepal.Length ~
  reg(~ Petal.Length + Species, name="beta"),
  data=iris
)
sim <- MCMCsim(sampler, burnin=100, n.iter=400)
summary(sim)
# (weakly) informative normal priors on regression coefficients
sampler <- create_sampler(Sepal.Length ~
  reg(~ Petal.Length + Species, Q0=1e-2, name="beta"),
  data=iris
)
sim <- MCMCsim(sampler, burnin=100, n.iter=400)
summary(sim)
# binary regression
sampler <- create_sampler(Species == "setosa" ~
  reg(~ Sepal.Length, Q=0.1, name="beta"),
  family="binomial", data=iris)
sim <- MCMCsim(sampler, burnin=100, n.iter=400)
summary(sim)
pred <- predict(sim)
str(pred)
# example with equality constrained regression effects
n <- 500
df <- data.frame(x=runif(n))
df$y <- rnorm(n, 1 + 2*df$x)
R <- matrix(1, 2, 1)
r <- 3
sampler <- create_sampler(y ~ reg(~ 1 + x, R=R, r=r, name="beta"), data=df)
sim <- MCMCsim(sampler)
summary(sim)
plot(sim, "beta")
summary(transform_dc(sim$beta, fun=function(x) crossprod_mv(R, x) - r))

```

residuals-fitted-values

Extract draws of fitted values or residuals from a draws object

Description

For a model created with `create_sampler` and estimated using `MCMCsim`, these functions return the posterior draws of fitted values or residuals. In the current implementation the fitted values correspond to the linear predictor and the residuals are computed as the data vector minus the fitted values, regardless of the model's distribution family. For large datasets the returned object can

become very large. One may therefore select a subset of draws or chains or use `mean.only=TRUE` to return a vector of posterior means only.

Usage

```
## S3 method for class 'draws'
fitted(
  object,
  mean.only = FALSE,
  units = NULL,
  chains = seq_len(nchains(object)),
  draws = seq_len(ndraws(object)),
  matrix = FALSE,
  type = c("link", "response"),
  ...
)

## S3 method for class 'draws'
residuals(
  object,
  mean.only = FALSE,
  units = NULL,
  chains = seq_len(nchains(object)),
  draws = seq_len(ndraws(object)),
  matrix = FALSE,
  ...
)
```

Arguments

<code>object</code>	a draws object.
<code>mean.only</code>	if TRUE only the vector of posterior means is returned. In that case the subsequent arguments are ignored. Default is FALSE.
<code>units</code>	the data units (by default all) for which fitted values or residuals should be computed.
<code>chains</code>	optionally, a selection of chains.
<code>draws</code>	optionally, a selection of draws per chain.
<code>matrix</code>	whether a matrix should be returned instead of a dc object.
<code>type</code>	the type of fitted values: "link" for fitted values on the linear predictor scale (the default), and "response" for fitted values on the response scale. Returned residuals are always on the response scale.
<code>...</code>	currently not used.

Value

Either a draws component object or a matrix with draws of fitted values or residuals. The residuals are always on the response scale, whereas fitted values can be on the scale of the linear predictor or the response depending on `type`. If `mean.only=TRUE`, a vector of posterior means.

Examples

```

ex <- mcmcsae_example(n=50)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, store.all=TRUE)
fitted(sim, mean.only=TRUE)
summary(fitted(sim))
residuals(sim, mean.only=TRUE)
summary(residuals(sim))
bayesplot::mcmc_intervals(as.matrix(subset(residuals(sim), vars=1:20)))

```

setup_cluster	<i>Set up a cluster for parallel computing</i>
---------------	--

Description

The cluster is set up for a number of workers by loading the **mcmcsae** package and setting up independent RNG streams.

Usage

```
setup_cluster(n.cores = NULL, seed = NULL, export = NULL)
```

Arguments

n.cores	the number of cpu cores to use.
seed	optional random seed for reproducibility.
export	a character vector with names of objects to export to the workers.

Value

an object representing the cluster.

set_opts	<i>Set global options relating to computational details</i>
----------	---

Description

Set global options relating to computational details

Usage

```

set_opts(
  auto.order.block = TRUE,
  chol.inplace = TRUE,
  chol.ordering = 0L,
  PG.approx = TRUE,
  PG.approx.m = -2L,
  CRT.approx.m = 20L
)

```

Arguments

<code>auto.order.block</code>	whether Gibbs blocks should be ordered automatically in such a way that those with the most sparse design matrices come first. This way of ordering can make Cholesky updates more efficient.
<code>chol.inplace</code>	whether sparse Cholesky updates should re-use the same memory location.
<code>chol.ordering</code>	an integer passed to CHOLMOD routines determining which reordering schemes are tried to limit sparse Cholesky fill-in.
<code>PG.approx</code>	whether Polya-Gamma draws for logistic binomial models are approximated by a hybrid gamma convolution approach. If not, <code>BayesLogit:rpg</code> is used, which is exact for some values of the shape parameter.
<code>PG.approx.m</code>	if <code>PG.approx=TRUE</code> , the number of explicit gamma draws in the sum-of-gammas representation of the Polya-Gamma distribution. The remainder (infinite) convolution is approximated by a single moment-matching gamma draw. Special values are: <code>-2L</code> for a default choice depending on the value of the shape parameter and balancing performance and accuracy, <code>-1L</code> for a moment-matching normal approximation, and <code>0L</code> for a moment-matching gamma approximation.
<code>CRT.approx.m</code>	scalar integer specifying the degree of approximation to sampling from a Chinese Restaurant Table distribution. The approximation is based on Le Cam's theorem. Larger values yield a slower but more accurate sampler.

Value

This function sets or resets options in the option environment `.opts`.

References

- D. Bates, M. Maechler, B. Bolker and S.C. Walker (2015). Fitting Linear Mixed-Effects Models Using lme4. *Journal of Statistical Software* 67(1), 1-48.
- Y. Chen, T.A. Davis, W.W. Hager and S. Rajamanickam (2008). Algorithm 887: CHOLMOD, supernodal sparse Cholesky factorization and update/downdate. *ACM Transactions on Mathematical Software* 35(3), 1-14.

stop_cluster	<i>Stop a cluster</i>
--------------	-----------------------

Description

Stop a cluster set up by `setup_cluster`.

Usage

```
stop_cluster(c1)
```

Arguments

c1	the cluster object.
----	---------------------

Value

NULL.

subset.dc	<i>Select a subset of chains, samples and parameters from a draws component</i>
-----------	---

Description

Select a subset of chains, samples and parameters from a draws component

Usage

```
## S3 method for class 'dc'
subset(
  x,
  chains = seq_len(nchains(x)),
  draws = seq_len(ndraws(x)),
  vars = seq_len(nvars(x)),
  ...
)
```

Arguments

x	a draws component object.
chains	an integer vector indicating which chains to select.
draws	an integer vector indicating which samples to select.
vars	an integer vector indicating which parameters to select.
...	not used.

Value

The selected part of the draws component as an object of class dc.

Examples

```
n <- 300
dat <- data.frame(x=runif(n), f=as.factor(sample(1:7, n, replace=TRUE)))
gd <- generate_data(~ reg(~ x + f, Q0=1, name="beta"), data=dat)
dat$y <- gd$y
sampler <- create_sampler(y ~ reg(~ x + f, name="beta"), data=dat)
sim <- MCMCsim(sampler)
(summary(sim$beta))
(summary(subset(sim$beta, chains=1)))
(summary(subset(sim$beta, chains=1, draws=sample(1:ndraws(sim), 100))))
(summary(subset(sim$beta, vars=1:2)))
```

summary.dc

Summarize a draws component object

Description

Summarize a draws component object

Usage

```
## S3 method for class 'dc'
summary(
  object,
  probs = c(0.05, 0.5, 0.95),
  na.rm = FALSE,
  time = NULL,
  abbr = FALSE,
  batch.size = 100L,
  ...
)
```

Arguments

object	an object of class dc.
probs	vector of probabilities at which to evaluate quantiles.
na.rm	whether to remove NA/NaN draws in computing the summaries.
time	MCMC computation time; if specified the effective sample size per unit of time is returned in an extra column labeled 'efficiency'.
abbr	if TRUE abbreviate the labels in the output.

batch.size number of parameter columns to process simultaneously. A larger batch size may speed things up a little, but if an out of memory error occurs it may be a good idea to use a smaller number and try again. The default is 100.

... arguments passed to `n_eff`.

Value

A matrix with summaries of class `dc_summary`.

Examples

```
ex <- mcmc_sae_example()
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, store.all=TRUE)
summary(sim$u)
```

summary.draws	<i>Summarize a draws object</i>
---------------	---------------------------------

Description

Summarize a draws object

Usage

```
## S3 method for class 'draws'
summary(
  object,
  vnames = NULL,
  probs = c(0.05, 0.5, 0.95),
  na.rm = FALSE,
  efficiency = FALSE,
  abbr = FALSE,
  batch.size = 100L,
  ...
)
```

Arguments

object an object of class `draws`.

vnames optional character vector to select a subset of parameters.

probs vector of probabilities at which to evaluate quantiles.

na.rm whether to remove NA/NaN draws in computing the summaries.

efficiency	if TRUE the effective sample size per second of computation time is returned as well.
abbr	if TRUE abbreviate the labels in the output.
batch.size	number of parameter columns to process simultaneously for vector parameters. A larger batch size may speed things up a little, but if an out of memory error occurs it may be a good idea to use a smaller number and try again. The default is 100.
...	arguments passed to <code>n_eff</code> .

Value

A list of class `draws_summary` summarizing object.

Examples

```
ex <- mcmcsae_example()
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, store.all=TRUE)
summary(sim)
par_names(sim)
summary(sim, c("beta", "v_sigma", "u_sigma"))
```

transform_dc	<i>Transform one or more draws components into a new one by applying a function</i>
--------------	---

Description

Transform one or more draws components into a new one by applying a function

Usage

```
transform_dc(..., fun, to.matrix = FALSE, labels = NULL)
```

Arguments

...	draws component object(s).
fun	a function to apply. This function should take as many arguments as there are input objects. The arguments can be arbitrarily named, but they are assumed to be in the same order as the input objects. The function should return a vector.
to.matrix	if TRUE the output is in matrix format; otherwise it is a draws component object.
labels	optional labels for the output object.

Value

Either a matrix or a draws component.

Examples

```
ex <- mcmc_sae_example(n=50)
sampler <- create_sampler(ex$model, data=ex$dat)
sim <- MCMCsim(sampler, burnin=100, n.iter=300, thin=2, n.chain=4, store.all=TRUE)
summary(sim$v_sigma)
summary(transform_dc(sim$v_sigma, fun=function(x) x^2))
summary(transform_dc(sim$u, sim$u_sigma, fun=function(x1, x2) abs(x1)/x2))
```

vfac	<i>Create a model component object for a variance factor component in the variance function of a gaussian sampling distribution</i>
------	---

Description

This function is intended to be used on the right hand side of the formula.V argument to [create_sampler](#) or [generate_data](#).

Usage

```
vfac(
  factor = "local_",
  prior = pr_invchisq(df = 1, scale = 1),
  name = "",
  debug = FALSE,
  e = parent.frame()
)
```

Arguments

factor	The name of a factor variable. The name "local_" has a special meaning, and assigns a different variance scale parameter to each data unit. In case of inverse chi-squared priors this implies that the marginal sampling distribution is a t distribution. In case of exponential priors the marginal sampling distribution is a Laplace or double exponential distribution.
prior	the prior assigned to the variance factors. Currently the prior can be inverse chi-squared or exponential, specified by a call to pr_invchisq or pr_exp , respectively. The default priors are inverse chi-squared with 1 degree of freedom. See the help pages of the prior specification functions for details on how to set non-default priors.

name	The name of the variance model component. This name is used in the output of the MCMC simulation function <code>MCMCsim</code> . By default the name will be 'vfac' with the number of the variance model term attached.
debug	If TRUE a breakpoint is set at the beginning of the posterior draw function associated with this model component. Mainly intended for developers.
e	For internal use only.

Value

An object with precomputed quantities and functions for sampling from prior or conditional posterior distributions for this model component. Only intended for internal use by other package functions.

vreg	<i>Create a model component object for a regression component in the variance function of a gaussian sampling distribution</i>
------	--

Description

This function is intended to be used on the right hand side of the `formula.V` argument to `create_sampler` or `generate_data`.

Usage

```
vreg(
  formula = NULL,
  remove.redundant = FALSE,
  sparse = NULL,
  X = NULL,
  Q0 = NULL,
  b0 = NULL,
  name = "",
  e = parent.frame()
)
```

Arguments

formula	a formula for the regression effects explaining the log-variance. Variable names are looked up in the data frame passed as <code>data</code> argument to <code>create_sampler</code> or <code>generate_data</code> , or in <code>environment(formula)</code> .
remove.redundant	whether redundant columns should be removed from the design matrix. Default is FALSE.
sparse	whether the model matrix associated with <code>formula</code> should be sparse. The default is determined by a simple heuristic based on storage size.

X	a (possibly sparse) design matrix can be specified directly, as an alternative to the creation of one based on formula. If X is specified formula is ignored.
Q0	prior precision matrix for the regression effects. The default is a zero matrix corresponding to a noninformative improper prior.
b0	prior mean for the regression effect. Defaults to a zero vector.
name	the name of the model component. This name is used in the output of the MCMC simulation function <code>MCMCsim</code> . By default the name will be 'vreg' with the number of the variance model term attached.
e	for internal use only.

Value

An object with precomputed quantities and functions for sampling from prior or conditional posterior distributions for this model component. Only intended for internal use by other package functions.

References

E. Cepeda and D. Gamerman (2000). Bayesian modeling of variance heterogeneity in normal regression models. *Brazilian Journal of Probability and Statistics*, 207-221.

T.I. Lin and W.L. Wang (2011). Bayesian inference in joint modelling of location and scale parameters of the t distribution for longitudinal data. *Journal of Statistical Planning and Inference* 141(4), 1543-1553.

weights.draws	<i>Extract weights from a draws object</i>
---------------	--

Description

Extract weights from a draws object

Usage

```
## S3 method for class 'draws'
weights(object, ...)
```

Arguments

object	an object of class draws.
...	currently not used.

Value

A vector with (simulation means of) weights.

Examples

```

# first create a population data frame
N <- 1000 # population size
pop <- data.frame(x=rnorm(N), area=factor(sample(1:10, N, replace=TRUE)))
pop$y <- 1 + 2*pop$x + seq(-1, to=1, length.out=10)[pop$area] + 0.5*rnorm(N)
pop$sample <- FALSE
pop$sample[sample(seq_len(N), 100)] <- TRUE
# a simple linear regression model:
sampler <- create_sampler(
  y ~ reg(~ x, name="beta"),
  linpred=list(beta=rowsum(model.matrix(~ x, pop), pop$area)), compute.weights=TRUE,
  data=pop[pop$sample, ]
)
sim <- MCMCsim(sampler)
(summary(sim))
str(weights(sim))
crossprod_mv(weights(sim), pop$y[pop$sample])
summary(sim$linpred_)
# a multilevel model:
sampler <- create_sampler(
  y ~ reg(~ x, name="beta") + gen(factor = ~ area, name="v"),
  linpred=list(beta=rowsum(model.matrix(~ x, pop), pop$area), v=diag(10)), compute.weights=TRUE,
  data=pop[pop$sample, ]
)
sim <- MCMCsim(sampler)
(summary(sim))
str(weights(sim))
crossprod_mv(weights(sim), pop$y[pop$sample])
summary(sim$linpred_)

```

Index

- `%m*v%` (matrix-vector), 22
- acceptance_rates, 3
- aggrMatrix, 4
- as.array.dc (MCMC-object-conversion), 25
- as.matrix.dc (MCMC-object-conversion), 25

- combine_chains, 5
- combine_iters, 5
- compute_DIC
 - (model-information-criteria), 33
- compute_GMRF_matrices, 6, 16
- compute_WAIC
 - (model-information-criteria), 33
- computeDesignMatrix, 6
- correlation, 8, 15
- create_sampler, 8, 14–16, 21, 26, 28, 29, 31, 32, 50–52, 60, 61
- create_TMVN_sampler, 12
- crossprod_mv (matrix-vector), 22

- density, 38, 39

- f_binomial (mcmc_sae-family), 26
- f_gaussian (mcmc_sae-family), 26
- f_negbinomial (mcmc_sae-family), 26
- fitted.draws (residuals-fitted-values), 52

- gen, 6, 7, 9, 10, 14, 20
- generate_data, 10, 14–16, 18, 21, 31, 32, 50, 51, 60, 61
- get_draw, 20
- get_means (posterior-moments), 41
- get_sds (posterior-moments), 41
- glreg, 17, 20

- labels, 21

- labels<- (labels), 21
- loo, 34
- loo.draws (model-information-criteria), 33

- matrix-vector, 22
- maximize_llh, 23
- MCMC-diagnostics, 24
- MCMC-object-conversion, 25
- mcmc.list, 25
- mcmc_sae (mcmc_sae-package), 3
- mcmc_sae-family, 26
- mcmc_sae-package, 3
- mcmc_sae_example, 27
- MCMCsim, 8, 10, 11, 17, 21, 28, 32, 33, 45, 49, 51, 52, 61, 62
- mec, 31
- model-information-criteria, 33
- model_matrix, 35

- n_eff, 58, 59
- n_eff (MCMC-diagnostics), 24
- nchains (nchains-ndraws-nvars), 36
- nchains-ndraws-nvars, 36
- ndraws (nchains-ndraws-nvars), 36
- nvars (nchains-ndraws-nvars), 36

- optim, 23

- par_names, 37
- plot.dc, 38
- plot.draws, 38
- plot_coef, 39
- poly2nb, 8
- posterior-moments, 41
- pr_exp, 9, 16, 45, 60
- pr_fixed, 9, 46
- pr_gig, 9, 47
- pr_invchisq, 9, 10, 16, 47, 60
- pr_invwishart, 16, 48

predict.draws, 42
print.dc_summary, 44
print.draws_summary, 45

R_hat (MCMC-diagnostics), 24
read_draws, 49
readShapeSpatial, 8
reg, 9, 10, 50
residuals-fitted-values, 52
residuals.draws
 (residuals-fitted-values), 52

set_opts, 54
setup_cluster, 54, 56
stop_cluster, 56
subset.dc, 56
summary.dc, 57
summary.draws, 58

to_mcmc (MCMC-object-conversion), 25
transform_dc, 59

vfac, 10, 11, 60
vreg, 10, 11, 61

waic, 34
waic.draws
 (model-information-criteria),
 33
weights.draws, 62