

Package ‘options’

January 9, 2023

Title Simple, Consistent Package Options

Version 0.0.1

Description Simple mechanisms for defining and interpreting package options. Provides helpers for interpreting environment variables, global options, defining default values and more.

License MIT + file LICENSE

URL <https://dgkf.github.io/options/>, <https://github.com/dgkf/options>

BugReports <https://github.com/dgkf/options/issues>

Imports utils

Suggests crayon, knitr, rmarkdown, roxygen2, testthat (>= 3.0.0)

Config/Needs/website pkgdown

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.2.3

Config/testthat/edition 3

NeedsCompilation no

Author Doug Kelkhoff [aut, cre]

Maintainer Doug Kelkhoff <doug.kelkhoff@gmail.com>

Repository CRAN

Date/Publication 2023-01-09 10:10:01 UTC

R topics documented:

as_params	2
as_roxygen_docs	3
defining_options	3
envvar_fns	5
naming	7
naming_formats	8
opt	9
option_spec	10

`as_params`*Produce @param roxygen sections for options*

Description

Generate parameter documentation based on option behaviors. Especially useful for ubiquitous function parameters that default to option values.

Usage

```
as_params(...)
```

Arguments

... Character values of options to use. If named arguments are provided, the option description provided as the value is mapped to a parameter of the argument's name.

Value

A character vector of roxygen2 @param tags

See Also

Other options_roxygen2: [as_roxygen_docs\(\)](#)

Examples

```
options::define_options(  
  "whether messages should be written softly, or in all-caps",  
  quiet = TRUE  
)  
  
#' Hello, World  
#'  
#' @eval options::as_params("softly" = "quiet")  
#'  
hello <- function(who, softly = opt("quiet")) {  
  say_what <- paste0("Hello, ", who, "!" )  
  if (quiet) say_what else toupper(say_what)  
}
```

as_roxygen_docs	<i>Generate Standalone ?options Documentation</i>
-----------------	---

Description

Produce a comprehensive documentation page outlining all your defined options' behaviors.

Usage

```
as_roxygen_docs(
  title = paste(pkgname(env), "Options"),
  desc = default_options_rd_desc(),
  env = parent.frame()
)
```

Arguments

title	An optional, customized title (defaults to "Options")
desc	An optional, customized description of behaviors
env	An environemnt in which to find the associated options object

Value

A character vector of roxygen2 tag segments

See Also

Other options_roxygen2: [as_params\(\)](#)

Examples

```
#' @eval options::as_roxygen_docs()
NULL
```

defining_options	<i>Defining Options</i>
------------------	-------------------------

Description

Define options which can be used throughout your package.

Usage

```
define_option(option, ...)

define_options(...)
```

Arguments

option	An option name to use
...	Additional arguments passed to <code>option_spec()</code>

Details

At their simplest, defining options lets you refer to a global option using a shorthand option name throughout your package, with the added benefit of looking for configurations in global options and environment variables.

Value

the package options environment

Functions

- `define_option()`: Define an option. Unlike `define_options()`, this function allows detailed customization of all option behaviors. Accepts either an `option_spec()` object, or an option named followed by arguments to provide to `option_spec()`.
- `define_options()`: Define multiple options. This function provides a shorthand syntax for succinctly defining many options. Arguments are defined in groups, each starting with an unnamed description argument. For more details see Section *Non-Standard Evaluation*.

Non-Standard Evaluation

`define_options()` accepts arguments in a *non-standard* way, as groups of arguments which each are used to specify an option (See `options_spec()`). Groups of arguments must start with an unnamed argument, which provides the description for the argument, followed immediately by a named argument providing the name of option and default value, followed by any additional arguments to provide to `options_spec()`.

The environment in which options are defined is always assumed to be the parent environment. If you'd prefer to specify options in a different environment, this is best done using `define_option()` or `with(<env>, define_options(...))`.

Although `define_options()` provides all the functionality of `define_option()` in a succinct shorthand, it is only recommended in cases where the overwhelming majority of your options leverage default behaviors. It is encouraged to use `define_option()` if you repeatedly need more involved definitions to minimize non-standard evaluation bugs.

Examples

```
define_options(
  "Whether execution should emit console output",
  quiet = FALSE,

  "Whether to use detailed console output (showcasing additional
  configuration parameters)",
  verbose = TRUE,
  envvar_fn = envvar_is_true()
)
```

```
define_option(  
  "deprecations",  
  desc = "Whether deprecation warnings should be suppressed automatically",  
  default = FALSE,  
  option_name = "MypackageDeprecations",  
  envvar_name = "MYPACKAGE_ENVVARS_DEPRECATIONS"  
)
```

envvar_fns

Generator functions for environment variable processors

Description

These functions return environment variable processor functions. Arguments to them are used to specify behaviors.

Usage

```
envvar_is(value, ...)  
  
## S3 method for class 'NULL'  
envvar_is(value, case_sensitive = FALSE, ...)  
  
## S3 method for class 'character'  
envvar_is(value, case_sensitive = FALSE, ...)  
  
## S3 method for class 'numeric'  
envvar_is(value, ...)  
  
## S3 method for class 'logical'  
envvar_is(value, case_sensitive = FALSE, ...)  
  
envvar_eval(...)  
  
envvar_eval_or_raw(...)  
  
envvar_is_one_of(values, ...)  
  
envvar_choice_of(values, default = NULL, ...)  
  
envvar_is_true(...)  
  
envvar_is_false(...)  
  
envvar_is_set(...)  
  
envvar_str_split(delim = ";", ...)
```

Arguments

value	A value to test against
...	Other arguments unused
case_sensitive	A logical value indicating whether string comparisons should be case-sensitive.
values	A list or vector of values to match
default	A default value used when a value cannot be coerced from the environment variable value
delim	A character value to use as a delimiter to use when splitting the environment variable value

Value

A function to be used for processing an environment variable value

Functions

- `envvar_is()`: Test for equality with handlers for most atomic R types, performing sensible interpretation of environment variable values.
- `envvar_is("NULL")`: environment variable has value "null"
- `envvar_is(character)`: environment variable is equal to string value
- `envvar_is(numeric)`: environment variable is equal to string representation of numeric value
- `envvar_is(logical)`: environment variable is equal to string representation of logical value
- `envvar_eval()`: Parse the environment variable value as R code and evaluate it to produce a return value, emitting an error if the expression fails to parse or evaluate. This option is a sensible default for most R-specific environment variables, but may fail for string literals, and meaningful values that don't conform to R's syntax like "true" (see `envvar_is_true()`), "false" (see `envvar_is_false()`) or "null".
- `envvar_eval_or_raw()`: Parse the environment variable value as R code and evaluate it to produce a return value, or falling back to the raw value as a string if an error occurs.
- `envvar_is_one_of()`: For meaningful string comparisons, check whether the environment variable is equal to some meaningful string. Optionally with case-sensitivity.
- `envvar_choice_of()`: Check whether environment variable can be coerced to match one of values, returning the value if it matches or default otherwise.
- `envvar_is_true()`: Test whether the environment variable is "truthy", that is whether it is case-insensitive "true" or 1
- `envvar_is_false()`: Test whether the environment variable is "falsy", that is whether it is case-insensitive "false" or 0
- `envvar_is_set()`: Test whether the environment variable is set. This is somewhat operating-system dependent, as not all operating systems can distinguish between an empty string as a value and an unset environment variable. For details see `Sys.getenv()`'s Details about its unset parameter.
- `envvar_str_split()`: Interpret the environment variable as a delimited list of strings, such as PATH variables.

Description

Option naming conventions use sensible defaults so that you can get started quickly with minimal configuration.

Usage

```
set_envvar_name_fn(fn, env = parent.frame())
```

```
set_option_name_fn(fn, env = parent.frame())
```

Arguments

`fn` A callback function which expects two arguments, the package name and option name, and returns a single character value to use as an environment variable name.

`env` An environment in which to search for options settings

Value

The callback function `fn`

Functions

- `set_envvar_name_fn()`: Set a callback function to use to format environment variable names.
- `set_option_name_fn()`: Set a callback function to use to format option names.

Defaults

Given a package `mypackage` and option `myoption`, the default settings will generate options and environment variables using the convention:

option:

```
mypackage.myoption
```

environment variable:

```
R_MYPACKAGE_MYOPTION
```

This convention is intended to track closely with how options and environment variables are handled frequently in the wild. Perhaps in contrast to the community conventions, an `R_` prefix is tacked on to the default environment variables. This prefix helps to differentiate environment variables when similarly named tools exist outside of the R ecosystem.

Setting Alternative Conventions

If you choose to use alternative naming conventions, you must set the callback function *before* defining options. This is best achieved by altering these settings in the file where you define your options.

If you choose to break up your options across multiple files, then it is best to define the collate order for your R scripts to ensure that the options are consistently configured across operating systems.

See Also

naming_formats

Examples

```
set_envvar_name_fn(envvar_name_generic)

set_envvar_name_fn(function(package, name) {
  toupper(paste("ENV", package, name, sep = "_"))
})
```

naming_formats

Naming Convention Formatters

Description

This family of functions is used internally to generate global option and environment variable names from the package name and internal option name.

Usage

```
option_name_default(package, option) # "package.option"

envvar_name_default(package, option) # "R_PACKAGE_OPTION"

envvar_name_generic(package, option) # "PACKAGE_OPTION"
```

Arguments

package, option

The package name and internal option name used for generating a global R option and environment variable name. As these functions are often provided as values, their arguments rarely need to be provided by package authors directly.

Value

A character value to use as the global option name or environment variable name

Functions

- `option_name_default()`: A default naming convention, producing a global R option name from the package name and internal option name (`mypackage.myoption`)
- `envvar_name_default()`: A default naming convention, producing an environment variable name from the package name and internal option name (`R_MYPACKAGE_MYOPTION`)
- `envvar_name_generic()`: A generic naming convention, producing an environment variable name from the package name and internal option name. Useful when a generic convention might be used to share environment variables with other tools of the same name, or when you're confident that your R package will not conflict with other tools. (`MYPACKAGE_MYOPTION`)

See Also

naming

opt

Inspecting Option Values

Description

Inspecting Option Values

Usage

```
opt(x, default, env = parent.frame())
```

```
opt_source(x, env = parent.frame())
```

```
opts(xs, env = parent.frame())
```

Arguments

<code>x</code> , <code>xs</code>	An option name or vector of option names
<code>default</code>	A default value if the option is not set
<code>env</code>	An environment, namespace or package name to pull options from

Value

For `opt()` and `opts()`; the result of the option (or a list of results), either the value from a global option, the result of processing the environment variable or the default value, depending on which of the alternative sources are defined.

For `opt_source()`; the source that is used for a specific option, one of "option", "envir" or "default".

Functions

- `opt()`: Retrieve an option
- `opt_source()`: Determine source of option value. Primarily used for diagnosing options behaviors.
- `opts()`: Retrieve multiple options

Examples

```
define_options("Whether execution should emit console output", quiet = FALSE)
opt("quiet")
```

```
define_options("Whether execution should emit console output", quiet = FALSE)
opt_source("quiet")
```

```
Sys.setenv(R_GLOBALENV_QUIET = TRUE)
opt_source("quiet")
```

```
options(globalenv.quiet = FALSE)
opt_source("quiet")
```

option_spec

Specify Option

Description

An option specification outlines the various behaviors of an option. It's default value, related global R option, and related environment variable name, as well as a description. This information defines the operating behavior of the option.

Usage

```
option_spec(
  name,
  default = bquote(),
  desc = NULL,
  option_name = get_option_name_fn(envir),
  envvar_name = get_envvar_name_fn(envir),
  envvar_fn = envvar_eval_or_raw(),
  quoted = FALSE,
  eager = FALSE,
  envir = parent.frame()
)
```

Arguments

name	A string representing the internal name for the option. This is the short form <code><option></code> used within a namespace and relates to, for example, <code><package>.<option></code> global R option.
default	Either a quoted expression (if parameter <code>quote == TRUE</code>) or default value for the option. Defaults to an empty expression, indicating that it is unset. The default value is lazily evaluated, evaluated only when the option is first requested unless parameter <code>eager == TRUE</code> .
desc	A written description of the option's effects
option_name, envvar_name	A character value or function. If a character value is provided it is used as the corresponding global option name or environment variable name. If a function is provided it is provided with the package name and internal option name to derive the global option name. For example, provided with package "mypkg" and option "myoption", the function might return global option name "mypkg.myoption" or environment variable name "R_MYPKG_MYOPTION". Defaults to configured default functions which fall back to <code>option_name_default</code> and <code>envvar_name_default</code> , and can be configured using <code>set_option_name_fn</code> and <code>set_envvar_name_fn</code> .
envvar_fn	A function to use for parsing environment variable values. Defaults to <code>envvar_eval_or_raw()</code> .
quoted	A logical value indicating whether the default argument should be treated as a quoted expression or as a value.
eager	A logical value indicating whether the default argument should be eagerly evaluated (upon call), or lazily evaluated (upon first use). This distinction will only affect default values that rely on evaluation of an expression, which may produce a different result depending on the context in which it is evaluated.
envir	An environment in which to search for an options <code>envir</code> object. It is rarely necessary to use anything but the default.

Value

An `option_spec` object, which is a simple S3 class wrapping a list containing these arguments.

Index

- * **envvar_parsers**
 - envvar_fns, 5
- * **naming_formats**
 - naming_formats, 8
- * **naming**
 - naming, 7
- * **options_roxygen2**
 - as_params, 2
 - as_roxygen_docs, 3
- * **roxygen2**
 - as_params, 2
 - as_roxygen_docs, 3

as_params, 2, 3
as_roxygen_docs, 2, 3

define_option (defining_options), 3
define_options (defining_options), 3
define_options(), 4
defining_options, 3

envvar_choice_of (envvar_fns), 5
envvar_eval (envvar_fns), 5
envvar_eval_or_raw (envvar_fns), 5
envvar_fns, 5
envvar_is (envvar_fns), 5
envvar_is_false (envvar_fns), 5
envvar_is_false(), 6
envvar_is_one_of (envvar_fns), 5
envvar_is_set (envvar_fns), 5
envvar_is_true (envvar_fns), 5
envvar_is_true(), 6
envvar_name_default (naming_formats), 8
envvar_name_generic (naming_formats), 8
envvar_str_split (envvar_fns), 5

naming, 7
naming_formats, 8

opt, 9
opt_source (opt), 9

option_name_default (naming_formats), 8
option_spec, 10
option_spec(), 4
opts (opt), 9

set_envvar_name_fn (naming), 7
set_option_name_fn (naming), 7
Sys.getenv(), 6