

Package ‘parseRPDR’

September 10, 2021

Type Package

Title Parse and Manipulate Research Patient Data Registry ('RPDR')
Text Queries

Version 0.2.1

Date 2021-09-10

Maintainer Marton Kolossvary <mkolossvary@mgh.harvard.edu>

Description Functions to load Research Patient Data Registry ('RPDR') text queries from Partners Healthcare institutions into R.

The package also provides helper functions to manipulate data and execute common procedures such as finding the closest radiological exams considering a given timepoint, or creating a DICOM header database

from the downloaded images. 'parseRPDR' currently supports

txt sources: ``mrn``, ``con``, ``dem``, ``enc``, ``rdt``, ``lab``,

``med``, ``dia``, ``rfv``, ``prc``, ``phy``, ``lno``, ``car``, ``dis``, ``end``, ``hnp``, ``opn``, ``pat``, ``prg``, ``pul``, ``rad`` and ``vis``.

All functionalities are parallelized for fast and efficient analyses.

License AGPL (>= 3)

Depends R (>= 4.0)

Imports data.table (>= 1.13.2), stringr (>= 1.4.0), readr (>= 1.4.0),
doParallel (>= 1.0.16), foreach (>= 1.5.1), bigmemory (>= 4.5.36), reticulate (>= 1.20)

LazyData TRUE

RoxygenNote 7.1.1

NeedsCompilation no

Suggests testthat (>= 3.0.0), knitr, rmarkdown

Encoding UTF-8

Config/testthat/edition 3

Author Marton Kolossvary [aut, cre]

Repository CRAN

Date/Publication 2021-09-10 12:10:02 UTC

R topics documented:

| | |
|-------------------------|----|
| all_ids_mi2b2 | 3 |
| convert_dia | 3 |
| convert_enc | 5 |
| convert_lab | 6 |
| convert_med | 7 |
| convert_notes | 9 |
| convert_phy | 11 |
| convert_prc | 12 |
| convert_rfv | 14 |
| create_img_db | 15 |
| data_con | 17 |
| data_con_raw | 18 |
| data_dem | 20 |
| data_dem_raw | 21 |
| data_dia | 22 |
| data_dia_raw | 23 |
| data_enc | 24 |
| data_enc_raw | 26 |
| data_lab | 28 |
| data_lab_raw | 30 |
| data_med | 31 |
| data_med_raw | 32 |
| data_mrn | 34 |
| data_mrn_raw | 35 |
| data_rad | 36 |
| data_rad_raw | 37 |
| data_rdt | 38 |
| data_rdt_raw | 39 |
| find_exam | 40 |
| load_all | 42 |
| load_con | 44 |
| load_dem | 46 |
| load_dia | 48 |
| load_enc | 50 |
| load_lab | 53 |
| load_lno | 56 |
| load_med | 58 |
| load_mrn | 60 |
| load_notes | 62 |
| load_phy | 64 |
| load_prc | 66 |
| load_rdt | 68 |
| load_rfv | 70 |
| pretty_mrn | 72 |

| | |
|---------------|---|
| all_ids_mi2b2 | <i>Creates a vector of all possible IDs for mi2b2 workbench</i> |
|---------------|---|

Description

Gathers all possible IDs from different input sources to provide a vector of all possible MGH or BWH IDs to be used as a data request for mi2b2 workbench. mi2b2 workbench only works with MGH or BWH IDs, therefore curated IDs, such as PMRN cannot be used. However, as MGH and BWH IDs may change over time, to access all possible images for given patients, a full list of all IDs over time for each patient is needed. For this all possible IDs need to gathered and returned.

Usage

```
all_ids_mi2b2(type = "MGH", d_mrn, d_con)
```

Arguments

| | |
|-------|--|
| type | string, either "MGH" or "BWH" specifying which IDs to use. |
| d_mrn | data.table, parsed mrn dataset using the <i>load_mrn</i> function. |
| d_con | data.table, parsed con dataset using the <i>load_con</i> function. |

Value

vector, with all MGH or BWH IDs that occur in the con and mrn datasources for all patients. This is required to request mi2b2 workbench allowing access to all possible images of the patients, even if the MGH or BWH changed over time.

Examples

```
## Not run:  
all_MGH_mrn <- all_ids_mi2b2(type = "MGH", d_mrn = data_mrn, d_con = data_con)  
  
## End(Not run)
```

| | |
|-------------|---|
| convert_dia | <i>Searches diagnosis columns for given diseases.</i> |
|-------------|---|

Description

Analyzes diagnosis data loaded using *load_dia*. Searches diagnosis columns for a specified set of diseases. By default, the data.table is returned with new columns corresponding to boolean values, whether given group of diagnoses are present in the given diagnosis. If *collapse* is given, then the information is aggregated based-on the *collapse* column and the earliest of latest time of the given diagnosis is provided.

Usage

```

convert_dia(
  d,
  code = "dia_code",
  code_type = "dia_code_type",
  codes_to_find = NULL,
  collapse = NULL,
  code_time = "time_dia",
  time_type = "earliest",
  nThread = 4
)

```

Arguments

| | |
|---------------|---|
| d | data.table, database containing diagnosis information data loaded using the <i>load_dia</i> function. |
| code | string, column name of the diagnosis code column. Defaults to <i>dia_code</i> . |
| code_type | string, column name of the code_type column. Defaults to <i>dia_code_type</i> . |
| codes_to_find | list, a list of string arrays corresponding to sets of code types and codes separated by :, i.e.: "ICD9:250.00". The function searches for the given disease code type and code pair and adds new boolean columns with the name of each list element. These columns are indicators whether any of the disease code type and code pair occurs in the set of codes. |
| collapse | string, a column name on which to collapse the data.table. Used in case we wish to assess whether given disease codes are present within all the same instances of <i>collapse</i> . See vignette for details. |
| code_time | string, column name of the time column. Defaults to <i>time_dia</i> . Used in case collapse is present to provide the earliest or latest instance of diagnosing the given disease. |
| time_type | string, if multiple diagnoses are present within the same case of <i>collapse</i> , which timepoint to return. Supported are: "earliest" or "latest". Defaults to <i>earliest</i> . |
| nThread | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |

Value

data.table, with indicator columns whether the any of the given diagnoses are reported. If *collapse* is present, then only unique ID and the summary columns are returned.

Examples

```

## Not run:
#Search for Hypertension and Stroke ICD codes
diseases <- list(HT = c("ICD10:I10"), Stroke = c("ICD9:434.91", "ICD9:I63.50"))
data_dia_parse <- convert_dia(d = data_dia, codes_to_find = diseases, nThread = 2)

```

```
#Search for Hypertension and Stroke ICD codes and summarize per patient providing earliest time
diseases <- list(HT = c("ICD10:I10"), Stroke = c("ICD9:434.91", "ICD9:I63.50"))
data_dia_disease <- convert_dia(d = data_dia, codes_to_find = diseases, nThread = 2,
collapse = "ID_MERGE", time_type = "earliest")

## End(Not run)
```

convert_enc

Searches columns for given diseases defined by ICD codes.

Description

Analyzes encounter data loaded using *load_enc*. Converts columns with ICD codes and text to simple ICD codes. If requested, the *data.table* is returned with new columns corresponding to boolean values, whether given group of diagnoses are present in the given columns. If *collapse* is given, then the information is aggregated based-on the *collapse* column and the earliest of latest time of the given diagnosis is provided.

Usage

```
convert_enc(
  d,
  code = c("enc_diag_admit", "enc_diag_princ", paste0("enc_diag_", 1:10)),
  keep = FALSE,
  codes_to_find = NULL,
  collapse = NULL,
  code_time = "time_enc_admit",
  time_type = "earliest",
  nThread = 4
)
```

Arguments

| | |
|---------------|--|
| d | data.table, database containing encounter information data loaded using the <i>load_enc</i> function. |
| code | string vector, an array of column names to convert to simple ICD codes. The new column names will be the old one with <i>ICD_</i> added to the beginning of it. |
| keep | boolean, whether to keep original columns that were converted. Defaults to <i>FALSE</i> . |
| codes_to_find | list, a list of arrays corresponding to sets of ICD codes. The function searches the columns in code and new boolean columns with the name of each list element will be created. These columns are indicators whether the given disease is present in the set of ICD codes or not. |
| collapse | string, a column name on which to collapse the data.table. Used in case we wish to assess whether given diagnoses are present within all the same instances of <i>collapse</i> . See vignette for details. |

| | |
|-----------|---|
| code_time | string, column name of the time column. Defaults to <i>time_enc_admit</i> . Used in case collapse is present to provide the earliest or latest instance of diagnosing the given disease. |
| time_type | string, if multiple diagnoses are present within the same case of <i>collapse</i> , which timepoint to return. Supported are: "earliest" or "latest". Defaults to <i>earliest</i> . |
| nThread | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |

Value

data.table, with formatted ICD code columns and possibly indicator columns if provided. If *collapse* is present, then only unique ID and the summary columns are returned.

Examples

```
## Not run:
#Parse encounter ICD columns and keep original ones as well
data_enc_parse <- convert_enc(d = data_enc, keep = TRUE, nThread = 2)

#Parse encounter ICD columns and discard original ones,
#and create indicator variable for the following diseases
diseases <- list(HT = c("I10"), Stroke = c("434.91", "I63.50"))
data_enc_disease <- convert_enc(d = data_enc, keep = FALSE,
codes_to_find = diseases, nThread = 2)

#Parse encounter ICD columns and discard original ones
#and create indicator variables for the following diseases and summarize per patient,
#whether there are any encounters where the given diseases were registered
diseases <- list(HT = c("I10"), Stroke = c("434.91", "I63.50"))
data_enc_disease <- convert_enc(d = data_enc, keep = FALSE,
codes_to_find = diseases, nThread = 2, collapse = "ID_MERGE")

## End(Not run)
```

convert_lab

Converts lab results to normal/abnormal based-on reference values.

Description

Analyzes laboratory data loaded using *load_lab*. Converts laboratory results to values without ">" or "<" by creating a column where these characters are removed. Furthermore, adds two indicator columns where based-on the reference ranges or the Abnormal_Flag column in RPDR (lab_result_abn using load_lab), the value is considered normal or abnormal.

Usage

```
convert_lab(
  d,
  code_results = "lab_result",
  code_reference = "lab_result_range",
  code_flag = "lab_result_abn"
)
```

Arguments

d data.table, database containing laboratory results data loaded using the *load_lab* function.

code_results string vector, column name containing the results. Defaults to: *"lab_result"*.

code_reference string vector, column name containing the reference ranges. Defaults to: *"lab_result_range"*.

code_flag, string vector, column name containing the abnormal flags. Defaults to: *"lab_result_abn"*.

Value

data.table, with three additional columns: *"lab_result_pretty"* containing numerical results. In case of ">" or "<" notation, the numeric value is returned, as we only have information that it is at least as much or not larger than a given value. The other column: *"lab_result_abn_pretty"* can take values: NORMAL/ABNORMAL, depending on whether the value is within the reference range. Please be aware that there can be very different representations of values, and in some cases this will result in misclassification of values. The third column: *"lab_result_abn_flag_pretty"* gives abnormal if the original Abnormal_Flag column contains any information. Borderline values are considered NORMAL.

Examples

```
## Not run:
#Convert loaded lab results
data_lab_pretty <- convert_lab(d = data_lab)
data_lab_pretty[, c("lab_result", "lab_result_pretty", "lab_result_range",
"lab_result_abn_pretty", "lab_result_abn_flag_pretty")]

## End(Not run)
```

| | |
|-------------|---|
| convert_med | <i>Adds boolean columns corresponding to a group of medications whether it is present in the given row.</i> |
|-------------|---|

Description

Analyzes medication data loaded using *load_med*. By default, the data.table is returned with new columns corresponding to boolean values, whether given group of diagnoses are present in the given diagnosis. If *collapse* is given, then the information is aggregated based-on the *collapse* column and the earliest of latest time of the given diagnosis is provided.

Usage

```
convert_med(
  d,
  code = "med",
  codes_to_find = NULL,
  collapse = NULL,
  code_time = "time_med",
  time_type = "earliest",
  nThread = 4
)
```

Arguments

| | |
|----------------------------|---|
| <code>d</code> | data.table, database containing medication data loaded using the <i>load_med</i> function. |
| <code>code</code> | string, column name of the medication column. Defaults to <i>med</i> . |
| <code>codes_to_find</code> | list, a list of arrays corresponding to sets of medication names. New boolean columns with the name of each list element will be created. These columns are indicators whether the given medication is present in the set of medication names or not. |
| <code>collapse</code> | string, a column name on which to collapse the data.table. Used in case we wish to assess whether given medications are present within all the same instances of <i>collapse</i> . See vignette for details. |
| <code>code_time</code> | string, column name of the time column. Defaults to <i>time_med</i> . Used in case collapse is present to provide the earliest or latest instance of diagnosing the given disease. |
| <code>time_type</code> | string, if multiple diagnoses are present within the same case of <i>collapse</i> , which timepoint to return. Supported are: "earliest" or "latest". Defaults to <i>earliest</i> . |
| <code>nThread</code> | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |

Value

data.table, with indicator columns whether given group of `codes_to_find` is present or not. If *collapse* is present, then only unique ID and the summary columns are returned.

Examples

```
## Not run:
#Define medication group and add an indicator column whether
#the given medication group was administered
meds <- list(statin = c("Simvastatin", "Atorvastatin"),
            NSAID = c("Acetaminophen", "Paracetamol"))

data_med_indic <- convert_med(d = data_med, codes_to_find = meds, nThread = 1)
```



```
#Summarize per patient if they ever had the given medication groups registered
data_med_indic_any <- convert_med(d = data_med,
codes_to_find = meds, collapse = "ID_MERGE", nThread = 2)

## End(Not run)
```

convert_notes

Extracts information from notes free text.

Description

Analyzes notes loaded using *load_notes* or *load_Ino*. Extracts information from the free text present in *abc_rep_txt*, where *abc* stands for the three letter abbreviation of the given type of note. An array of string is provided using the *anchors* argument. The function will return as many columns as there are anchor points. Each column will contain the text between the given anchor point and the next following anchor point. This way the free text report is split into corresponding smaller texts. By default, these are the common standard elements of given note types. Here are provided potential anchor points for the given types of notes:

- Cardiology: c("Report Number:", "Report Status:", "Type:", "Date:", "Ordering Provider:", "SYSTOLIC BLOOD PRESSURE", "DIASTOLIC BLOOD PRESSURE", "VENTRICULAR RATE EKG/MIN", "ATRIAL RATE", "PR INTERVAL", "QRS DURATION", "QT INTERVAL", "QTC INTERVAL", "P AXIS", "R AXIS", "T WAVE AXIS", "LOC", "DX:", "REF:", "Electronically Signed", "report_end")
- Discharge: c("***This text report", "Patient Information", "Physician Discharge Summary", "Surgeries this Admission", "Items for Post-Hospitalization Follow-Up:", "Pending Results", "Hospital Course", "ED Course:", "Diagnosis", "Prescriptions prior to admission", "Family History:", "Physical Exam on Admission:", "Discharge Exam", "report_end")
- Endoscopy: c("NAME:", "DATE:", "Patient Information", "report_end")
- History & Physical: c("***This text report", "Patient Information", "H&P by", "Author:", "Service:", "Author Type:", "Filed:", "Note Time:", "Status:", "Editor:", "report_end")
- Operative: c("NAME:", "UNIT NO:", "DATE:", "SURGEON:", "ASST:", "PREOPERATIVE DIAGNOSIS:", "POSTOPERATIVE DIAGNOSIS:", "NAME OF OPERATION:", "ANESTHESIA:", "INDICATIONS", "OPERATIVE FINDINGS:", "DESCRIPTION OF PROCEDURE:", "Electronically Signed", "report_end")
- Pathology: c("Accession Number:", "Report Status:", "Type:", "Report:", "CASE:", "PATIENT:", "Date", "Source Care Unit:", "Path Subspecialty Service:", "Results To:", "Signed Out by:", "CLINICAL DATA:", "FINAL DIAGNOSIS:", "GROSS DESCRIPTION:", "report_end")
- Progress: c("***This text report", "Patient Information", "History", "Overview", "Progress Notes", "Medications", "Relevant Orders", "Level of Service", "report_end")
- Pulmonary: c("The Pulmonary document", "Name:", "Unit #:", "Date:", "Location:", "Smoking Status:", "Pack Years:", "SPIROMETRY:", "LUNG VOLUMES:", "DIFFUSION:", "PLETHYSMOGRAPHY:" "Pulmonary Function Test Interpretation", "Spirometry", "report_end")

- Radiology: c("Exam Code", "Ordering Provider", "HISTORY", "Associated Reports", "Report Below", "REASON", "REPORT", "TECHNIQUE", "COMPARISON", "FINDINGS", "IMPRESSION", "RECOMMENDATION", "SIGNATURES", "report_end")
- Visit: c("***This text report", "Reason for Visit", "Reason for Visit", "Vital Signs", "Chief Complaint", "History", "Overview", "Medications", "Relevant Orders", "Level of Service", "report_end")
- LMR: c("Subject", "Patient Name:", "Reason for visit", "report_end")

However, these may be modified and extended to include sections of interest, i.e. if a given score is reported standardly, then adding this phrase (i.e. "CAD-RADS") would create a column where the text following this statement is returned. After this the resulting columns can be easily cleaned up if needed. Be aware to always include *"report_end"* in the anchors array, to provide the function of the last occurring statement in the report.

Usage

```
convert_notes(d, code = NULL, anchors = NULL, nThread = 4)
```

Arguments

| | |
|---------|---|
| d | data.table, database containing notes loaded using the <i>load_notes</i> function. |
| code | string vector, column name containing the results, which should be <i>"abc_rep_txt"</i> , where <i>abc</i> stands for the three letter abbreviation of the given type of note. |
| anchors | string array, elements to search for in the text report. |
| nThread | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |

Value

data.table, with new columns corresponding to elements in *anchors*.

Examples

```
## Not run:
#Create columns with specific parts of the radiological report defined by anchors
data_rad_parsed <- convert_notes(d = data_rad, code = "rad_rep_txt",
anchors = c("Exam Code", "Ordering Provider", "HISTORY", "Associated Reports",
"Report Below", "REASON", "REPORT", "TECHNIQUE", "COMPARISON", "FINDINGS",
"IMPRESSION", "RECOMMENDATION", "SIGNATURES", "report_end"), nThread = 2)

## End(Not run)
```

 convert_phy

Searches health history data for given codes

Description

Analyzes health history data loaded using *load_phy*. Searches health history columns for a specified set of codes. By default, the `data.table` is returned with new columns corresponding to boolean values, whether given group of diagnoses are present in the given diagnosis. If *collapse* is given, then the information is aggregated based-on the *collapse* column and the earliest of latest time of the given diagnosis is provided.

Usage

```
convert_phy(
  d,
  code = "phy_code",
  code_type = "phy_code_type",
  codes_to_find = NULL,
  collapse = NULL,
  code_time = "time_phy",
  time_type = "earliest",
  nThread = 4
)
```

Arguments

| | |
|----------------------------|--|
| <code>d</code> | <code>data.table</code> , database containing health history information data loaded using the <i>load_phy</i> function. |
| <code>code</code> | string, column name of the diagnosis code column. Defaults to <i>phy_code</i> . |
| <code>code_type</code> | string, column name of the <code>code_type</code> column. Defaults to <i>phy_code_type</i> . |
| <code>codes_to_find</code> | list, a list of string arrays corresponding to sets of code types and codes separated by <code>:</code> , i.e.: "LMR:3688". The function searches for the given health history code type and code pair and adds new boolean columns with the name of each list element. These columns are indicators whether any of the health history code type and code pair occurs in the set of codes. |
| <code>collapse</code> | string, a column name on which to collapse the <code>data.table</code> . Used in case we wish to assess whether given health history codes are present within all the same instances of <i>collapse</i> . See vignette for details. |
| <code>code_time</code> | string, column name of the time column. Defaults to <i>time_phy</i> . Used in case <i>collapse</i> is present to provide the earliest or latest instance of health history information. |
| <code>time_type</code> | string, if multiple health histories are present within the same case of <i>collapse</i> , which timepoint to return. Supported are: "earliest" or "latest". Defaults to <i>earliest</i> . |

`nThread` integer, number of threads to use by *dopar* for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used.

Value

data.table, with indicator columns whether the any of the given health histories are reported. If *collapse* is present, then only unique ID and the summary columns are returned.

Examples

```
## Not run:
#Search for Height and Weight codes
anthropometrics <- list(Weight = c("LMR:3688", "EPIC:WGT"), Height = c("LMR:3771", "EPIC:HGT"))
data_phy_parse <- convert_phy(d = data_phy, codes_to_find = anthropometrics, nThread = 2)

#Search for for Height and Weight codes and summarize per patient providing earliest time
anthropometrics <- list(Weight = c("LMR:3688", "EPIC:WGT"), Height = c("LMR:3771", "EPIC:HGT"))
data_phy_parse <- convert_phy(d = data_phy, codes_to_find = anthropometrics, nThread = 2,
collapse = "ID_MERGE", time_type = "earliest")

## End(Not run)
```

convert_prc

Searches procedures columns for given procedures

Description

Analyzes procedure data loaded using *load_prc*. Searches procedures columns for a specified set of procedures. By default, the data.table is returned with new columns corresponding to boolean values, whether given group of procedures are present in the given procedure. If *collapse* is given, then the information is aggregated based-on the *collapse* column and the earliest of latest time of the given procedure is provided.

Usage

```
convert_prc(
  d,
  code = "prc_code",
  code_type = "prc_code_type",
  codes_to_find = NULL,
  collapse = NULL,
  code_time = "time_prc",
  time_type = "earliest",
  nThread = 4
)
```

Arguments

| | |
|---------------|---|
| d | data.table, database containing procedure information data loaded using the <i>load_prc</i> function. |
| code | string, column name of the procedure code column. Defaults to <i>prc_code</i> . |
| code_type | string, column name of the code_type column. Defaults to <i>prc_code_type</i> . |
| codes_to_find | list, a list of string arrays corresponding to sets of code types and codes separated by :, i.e.: "CPT:00104". The function searches for the given procedure code type and code pair and adds new boolean columns with the name of each list element. These columns are indicators whether any of the procedure code type and code pair occurs in the set of codes. |
| collapse | string, a column name on which to collapse the data.table. Used in case we wish to assess whether given disease codes are present within all the same instances of <i>collapse</i> . See vignette for details. |
| code_time | string, column name of the time column. Defaults to <i>time_prc</i> . Used in case collapse is present to provide the earliest or latest instance of diagnosing the given disease. |
| time_type | string, if multiple diagnoses are present within the same case of <i>collapse</i> , which timepoint to return. Supported are: "earliest" or "latest". Defaults to <i>earliest</i> . |
| nThread | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |

Value

data.table, with indicator columns whether the any of the given procedures are reported. If *collapse* is present, then only unique ID and the summary columns are returned.

Examples

```
## Not run:
#Search for Anesthesia CPT codes
procedures <- list(Anesthesia = c("CTP:00410", "CPT:00104"))
data_prc_parse <- convert_prc(d = data_prc, codes_to_find = procedures, nThread = 2)

#Search for Anesthesia CPT codes
procedures <- list(Anesthesia = c("CTP:00410", "CPT:00104"))
data_prc_procedures <- convert_prc(d = data_prc, codes_to_find = procedures,
nThread = 2, collapse = "ID_MERGE", time_type = "earliest")

## End(Not run)
```

 convert_rfv

Searches columns for given reason for visit defined by ERFV codes.

Description

Analyzes reason for visit data loaded using *load_rfv*. If requested, the `data.table` is returned with new columns corresponding to boolean values, whether given group of ERFV are present in the given columns. If *collapse* is given, then the information is aggregated based-on the *collapse* column and the earliest of latest time of the given diagnosis is provided.

Usage

```
convert_rfv(
  d,
  code = "rfv_concept_id",
  codes_to_find = NULL,
  collapse = NULL,
  code_time = "time_rfv_start",
  time_type = "earliest",
  nThread = 4
)
```

Arguments

| | |
|---------------|---|
| d | data.table, database containing reason for visit information data loaded using the <i>load_rfv</i> function. |
| code | string vector, an array of column names to search. |
| codes_to_find | list, a list of arrays corresponding to sets of ERFV codes. The function searches the columns in code and the name of each list element will be created. These columns are indicators whether the given disease is present in the set of ERFV codes or not. |
| collapse | string, a column name on which to collapse the <code>data.table</code> . Used in case we wish to assess whether given ERFV are present within all the same instances of <i>collapse</i> . See vignette for details. |
| code_time | string, column name of the time column. Defaults to <i>time_rfv_start</i> . Used in case collapse is present to provide the earliest or latest instance of diagnosing the given disease. |
| time_type | string, if multiple diagnoses are present within the same case of <i>collapse</i> , which timepoint to return. Supported are: "earliest" or "latest". Defaults to <i>earliest</i> . |
| nThread | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |

Value

data.table, with indicator columns if provided. If *collapse* is present, then only unique ID and the summary columns are returned.

Examples

```
## Not run:
#Parse reason for visit columns
#and create indicator variables for the following reasons and summarize per patient,
#whether there are any encounters where the given reasons were registered
reasons <- list(Pain = c("ERFV:160357", "ERFV:140012"), Visit = c("ERFV:501"))
data_rfv_disease <- convert_rfv(d = data_rfv, keep = FALSE,
codes_to_find = reasons, nThread = 2, collapse = "ID_MERGE")

## End(Not run)
```

create_img_db

Create a database of DICOM headers.

Description

The function creates a database of DICOM headers present in a folder structure. Each series should be in its own folder, but they can be in a nested folder structure. Files where there are also folder present next to them at the same level will not be parsed. That is the folder structure needs to comply with the DICOM standard. Be aware that the function requires **python** and **pydicom** to be installed! The function cycles through all folders present in the provided path and recursively goes through them, every subfolder, and extracts the DICOM header information from the files using the **dcmread** function of the **pydicom** package. The extension of the files can be provided by the *ext* argument, as DICOM files may have different extensions than that of .dcm. Also, using the *all* boolean argument, you can specify whether the function provides output for each file, or only for the first file, which is beneficial if you are analyzing multi-slice series, as all instances have almost all the same header information. Furthermore, using the *keywords* argument you can manually specify which DICOM keywords you wish to extract. These need to be a valid keyword specified in the **DICOM standard**.

Usage

```
create_img_db(
  path,
  ext = "dcm",
  all = TRUE,
  keywords = c("StudyDate", "StudyTime", "SeriesDate", "SeriesTime", "AcquisitionDate",
    "AcquisitionTime", "ConversionType", "Manufacturer", "InstitutionName",
    "InstitutionalDepartmentName", "ReferringPhysicianName", "Modality",
    "ManufacturerModelName", "StudyDescription", "SeriesDescription", "StudyComments",
    "ProtocolName", "RequestedProcedureID", "ViewPosition", "StudyInstanceUID",
    "SeriesInstanceUID", "SOPInstanceUID", "AccessionNumber", "PatientName", "PatientID",
    "IssuerOfPatientID", "PatientBirthDate", "PatientSex", "PatientAge",
```

```

    "PatientSize", "PatientWeight", "StudyID", "SeriesNumber", "AcquisitionNumber",
    "InstanceNumber", "BodyPartExamined", "SliceThickness", "SpacingBetweenSlices",
    "PixelSpacing", "PixelAspectRatio", "Rows", "Columns", "FieldOfViewDimensions",
    "RescaleIntercept", "RescaleSlope", "WindowCenter", "WindowWidth", "BitsAllocated",
    "BitsStored", "PhotometricInterpretation", "KVP", "ExposureTime", "XRayTubeCurrent",
    "ExposureInuAs", "ImageAndFluoroscopyAreaDoseProduct", "FilterType",
    "ConvolutionKernel", "CTDIvol", "ReconstructionFieldOfView"),
  nThread = 4,
  na = TRUE,
  identical = TRUE
)

```

Arguments

| | |
|-----------|---|
| path | string vector, full folder path to folder that contains the images. |
| ext | string array, possible file extensions to parse. |
| all | boolean, whether all files in a series should be parsed, or only the first one. |
| keywords | string array, of valid DICOM keywords. |
| nThread | integer, number of threads to use for parsing data. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |

Value

data.table, with DICOM header information return unchanged. However, the function also provides additional new columns which help further data manipulations, these are:

time_study POSIXct, StudyDate and StudyTime concatenated together to POSIXct.
time_series POSIXct, SeriesDate and SeriesTime concatenated together to POSIXct.
time_acquisition POSIXct, AcquisitionDate and AcquisitionTime concatenated together to POSIXct.
name_img string, PatientName with special characters removed.
time_date_of_birth_img POSIXct, PatientBirthDate as POSIXct.
img_pixel_spacing numeric, PixelSpacing value of the first element in the array returned as numerical value.

Examples

```

## Not run:
#Create a database with DICOM header information
all_dicom_headers <- create_img_db(path = "/Users/Test/Data/DICOM/")
all_dicom_headers <- create_img_db(path = "/Users/Test/Data/DICOM/", ext = c("dcm", "DICOM"))
#Create a database with DICOM header information for only IDs and accession numbers
all_dicom_headers <- create_img_db(path = "/Users/Test/Data/DICOM/",
keywords = c("PatientID", "AccessionNumber"))

## End(Not run)

```

| | |
|----------|---|
| data_con | <i>Example of processed con.txt output from RPDR using the load_con() function.</i> |
|----------|---|

Description

Result of a con.txt output from RPDR loaded into a data table in R using `load_con()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_con
```

Format

```
data.table
```

Value

data table, with contact information data.

ID_MERGE numeric, defined IDs by `merge_id`, used for merging later.

ID_con_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from `con` datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_con_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from `condatasource`, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_con_loc string, if `mrn_type == TRUE`, then the data in `MRN_Type` and `MRN` are parsed into IDs corresponding to locations. Data is formatted using `pretty_mrn()`.

ID_con_loc_list string, if prevalence of IDs in `Patient_ID_List > perc`, then they are included in the output. Data is formatted using `pretty_mrn()`.

name_last string, Patient's last name, corresponds to `Last_Name` in RPDR.

name_first string, Patient's first name, corresponds to `First_Name` in RPDR.

name_middle string, Patient's middle name or initial, corresponds to `Middle_Name` in RPDR.

name_previous string, Any alternate names on record for this patient, corresponds to `Previous_Name` in RPDR.

SSN string, Social Security Number, corresponds to `SSN` in RPDR.

VIP character, Special patient statuses as defined by the EMPI group, corresponds to `VIP` in RPDR.

address1 string, Patient's current address, corresponds to `address1` in RPDR.

address2 string, Additional address information, corresponds to `address2` in RPDR.

city string, City of residence, corresponds to `City` in RPDR.

- state** string, State of residence, corresponds to State in RPDR.
- country_con** string, Country of residence from con datasource, corresponds to Country in RPDR. Punctuation marks are removed.
- zip_con** numeric, Mailing zip code of primary residence from con datasource, corresponds to Zip in RPDR. Formatted to 5 character zip codes.
- direct_contact_consent** boolean, Indicates whether the patient has given permission to contact them directly through the RODY program, corresponds to Direct_Contact_Consent in RPDR.
- phone_home** number, Patient's home phone number, corresponds to Home_Phone in RPDR. Formatted to 10 digit phone numbers.
- phone_day** number, Phone number where the patient can be reached during the day, corresponds to Day_Phone in RPDR. Formatted to 10 digit phone numbers.
- insurance1** string, Patient's primary health insurance carrier and subscriber ID information, corresponds to Insurance_1 in RPDR. Punctuation marks are removed.
- insurance2** string, Patient's secondary health insurance carrier and subscriber ID information, if any, corresponds to Insurance_2 in RPDR. Punctuation marks are removed.
- insurance3** string, Patient's tertiary health insurance carrier and subscriber ID information, if any, corresponds to Insurance_3 in RPDR. Punctuation marks are removed.
- primary_care_physician** string, Comma-delimited list of all primary care providers on record for this patient per institution, along with contact information (if available), corresponds to Primary_Care_Physician in RPDR. Punctuation marks are removed.
- primary_care_physician_resident** string, Comma-delimited list of any Resident primary care providers on record for this patient per institution, along with contact information (if available), corresponds to Resident_Primary_Care_Physician in RPDR. Punctuation marks are removed.

data_con_raw

Example of con.txt output from RPDR.

Description

A con.txt output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_con_raw
```

Format

```
data.table
```

Value

data table, imported from con.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Last_Name string, Patient's last name.

First_Name string, Patient's first name.

Middle_Name string, Patient's middle name or initial.

Direct_Contact_Consent boolean, Indicates whether the patient has given permission to contact them directly through the RODY program.

Address1 string, Patient's current address.

Address2 string, Additional address information.

City string, City of residence.

State string, State of residence.

Zip numeric, Mailing zip code of primary residence from con datasource.

Country string, Country of residence from con datasource.

Home_Phone number, Patient's home phone number.

Day_Phone number, Phone number where the patient can be reached during the day.

SSN string, Social Security Number.

VIP character, Special patient statuses as defined by the EMPI group.

Previous_Name string, Any alternate names on record for this patient.

Patient_ID_List string, Comma-delimited list of all hospital-specific identifiers on record for this patient.

Insurance_1 string, Patient's primary health insurance carrier and subscriber ID information.

Insurance_2 string, Patient's secondary health insurance carrier and subscriber ID information.

Insurance_3 string, Patient's tertiary health insurance carrier and subscriber ID information.

Primary_Care_Physician string, Comma-delimited list of all primary care providers on record for this patient per institution, along with contact information (if available).

Resident_Primary_Care_Physician string, Comma-delimited list of any Resident primary care providers on record for this patient per institution, along with contact information (if available).

| | |
|----------|---|
| data_dem | <i>Example of processed dem.txt output from RPDR using the load_dem() function.</i> |
|----------|---|

Description

Result of a dem.txt output from RPDR loaded into a data table in R using `load_dem()`.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_dem
```

Format

```
data.table
```

Value

data table, with demographic information data.

ID_MERGE numeric, defined IDs by `merge_id`, used for merging later.

ID_dem_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information. from `dem` datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_dem_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network. from `dem` datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_dem_loc string, if `mrn_type == TRUE`, then the data in `MRN_Type` and `MRN` are parsed into IDs corresponding to locations. Data is formatted using `pretty_mrn()`.

gender string, Patient's legal sex, corresponds to Gender in RPDR. Punctuation marks and white spaces are removed.

time_date_of_birth POSIXct, Patient's date of birth, corresponds to Date_of_Birth in RPDR. Converted to POSIXct format.

age string, Patient's current age (or age at death), corresponds to Age in RPDR.

language string, Patient's preferred spoken language, corresponds to Language in RPDR. Punctuation marks and white spaces are removed.

race string, Patient's primary race, corresponds to Race in RPDR. Punctuation marks and white spaces are removed.

marital string, Patient's current marital status, corresponds to Marital_Status in RPDR. Punctuation marks and white spaces are removed.

religion string, Patient-identified religious preference, corresponds to Religion in RPDR. Punctuation marks and white spaces are removed.

veteran string, Patient's current military veteran status, corresponds to Is_a_veteran in RPDR. Punctuation marks and white spaces are removed.

country_dem string, Patient's current country of residence from dem datasource, corresponds to Country in RPDR. Punctuation marks and white spaces are removed.

zip_dem string, Mailing zip code of patient's primary residence from dem datasource, corresponds to Zip_code in RPDR. Formatted to 5 character zip codes.

vital_status string, Identifies if the patient is living or deceased. This data is updated monthly from the Partners registration system and the Social Security Death Master Index, corresponds to Vital_Status in RPDR. Punctuation marks are removed.

time_date_of_death POSIXct, Recorded date of death from source in 'Vital_Status'. Date of death information obtained solely from the Social Security Death Index will not be reported until 3 years after death due to privacy concerns. If the value is independently documented by a Partners entity within the 3 year window then the date will be displayed. corresponds to Date_of_Death in RPDR. Converted to POSIXct format.

data_dem_raw

Example of dem.txt output from RPDR.

Description

A dem.txt output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

data_dem_raw

Format

data.table

Value

data table, imported from dem.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Gender string, Patient's legal sex.

Date_of_Birth string, Patient's date of birth.

Age string, Patient's current age (or age at death).

Language string, Patient's preferred spoken language.

Race string, Patient's primary race.

Marital_status string, Patient's current marital status.

Religion string, Patient-identified religious preference.

Is_a_veteran string, Patient's current military veteran status.

Zip_code string, Mailing zip code of patient's primary residence from dem datasource.

Country string, Patient's current country of residence from dem datasource.

Vital_status string, Identifies if the patient is living or deceased. This data is updated monthly from the Partners registration system and the Social Security Death Master Index.

Date_Of_Death string, Recorded date of death from source in 'Vital_Status'. Date of death information obtained solely from the Social Security Death Index will not be reported until 3 years after death due to privacy concerns. If the value is independently documented by a Partners entity within the 3 year window then the date will be displayed.

| | |
|----------|---|
| data_dia | <i>Example of processed dia.txt output from RPDR using the load_dia() function.</i> |
|----------|---|

Description

Result of a dia.txt output from RPDR loaded into a data table in R using `load_dia()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_dia
```

Format

```
data.table
```

Value

data table, with diagnoses information.

ID_MERGE numeric, defined IDs by `merge_id`, used for merging later.

ID_dia_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from `dia` datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

- ID_dia_PMRN** string, Epic medical record number. This value is unique across Epic instances within the Partners network from *dia* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.
- ID_dia_loc** string, if `mrn_type == TRUE`, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.
- time_dia** POSIXct, Date when the diagnosis was noted, corresponds to Date in RPDR. Converted to POSIXct format.
- dia_name** string, Name of the diagnosis, diagnosis-related group, or phenotype. For more information on available Phenotypes visit https://phenotypes.partners.org/phenotype_list.html, corresponds to *Diagnosis_Name* in RPDR.
- dia_code** string, Diagnosis, diagnosis-related group, or phenotype code, corresponds to *Code* in RPDR.
- dia_code_type** string, Standardized classification system or custom grouping associated with the diagnosis code, corresponds to *Code_type* in RPDR.
- dia_flag** string, Qualifier for the diagnosis, if any, corresponds to *Diagnosis_flag* in RPDR.
- dia_enc_num** string, Unique identifier of the record/visit. This values includes the source system, hospital, and a unique identifier within the source system, corresponds to *Encounter_number* in RPDR.
- dia_provider** string, Provider of record for the encounter where the diagnosis was entered, corresponds to *Provider* in RPDR. Punctuation marks are removed.
- dia_clinic** string, Specific department/location where the patient encounter took place, corresponds to *Clinic* in RPDR. Punctuation marks are removed.
- dia_hosp** string, Facility where the encounter occurred, corresponds to *Hospital* in RPDR.
- dia_inpatient** string, Identifies whether the diagnosis was noted during an inpatient or outpatient encounter, Punctuation marks are removed.

 data_dia_raw

Example of dia.txt output from RPDR.

Description

A *dia.txt* output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the PPartners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_dia_raw
```

Format

```
data.table
```

Value

data table, imported from dia.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Date string, Date when the diagnosis was noted.

Diagnosis_Name string, Name of the diagnosis, diagnosis-related group, or phenotype. For more information on available Phenotypes visit https://phenotypes.partners.org/phenotype_list.html.

Code_type string, Standardized classification system or custom grouping associated with the diagnosis code.

Code string, IDiagnosis, diagnosis-related group, or phenotype code.

Diagnosis_flag string, Qualifier for the diagnosis, if any.

Provider string, Provider of record for the encounter where the diagnosis was entered.

Clinic string, Specific department/location where the patient encounter took place.

Hospital numeric, Facility where the encounter occurred.

Inpatient_Outpatient string, Identifies whether the diagnosis was noted during an inpatient or outpatient encounter.

Encounter_number string, Unique identifier of the record/visit. This values includes the source system, hospital, and a unique identifier within the source system.

data_enc

Example of processed enc.txt output from RPDR using the load_enc() function.

Description

Result of a enc.txt output from RPDR loaded into a data table in R using *load_enc()*.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under **parserpdr-sample-data**.

Usage

data_enc

Format

data.table

Value

data table, with encounter information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_enc_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *enc* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

ID_enc_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *enc* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_enc_loc string, if *mrn_type* == TRUE, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations. Data is formatted using *pretty_mrn()*.

enc_num string, Unique identifier of the record/visit. This values includes the source system, hospital, and a unique identifier within the source system, corresponds to *Encounter_number* in RPDR.

time_enc_admit POSIXct, Date when the patient was admitted or entered the facility, corresponds to *Admit_Date* in RPDR. Converted to POSIXct format.

time_enc_disch POSIXct, Date when the patient was discharged or left the facility, corresponds to *Discharge_Date* in RPDR. Converted to POSIXct format.

enc_status string, Billing account-related notes about the encounter. This will not be populated for all encounters, corresponds to *Encounter_Status* in RPDR. Punctuation marks are removed.

enc_hosp string, Facility where the encounter occurred, corresponds to *Hospital* in RPDR. Punctuation marks and white spaces are removed.

enc_inpatient string, Classifies the type of encounter as either Inpatient or Outpatient. ED visits are currently classified under the 'Outpatient' label, corresponds to *Inpatient_or_Outpatient* in RPDR. Punctuation marks are removed.

enc_service string, Hospital service line assigned to the encounter, corresponds to *Service_Line* in RPDR. Punctuation marks are removed.

enc_attending string, The attending provider associated with the encounter. For Epic professional billing, this is the billing provider, corresponds to *Attending_MD* in RPDR. Punctuation marks are removed.

enc_length numeric, Length of stay for the encounter, corresponds to *LOS_days* in RPDR.

enc_clinic string, Specific department/location where the encounter occurred, corresponds to *Clinic_Name* in RPDR. Punctuation marks are removed.

enc_admit_src string, Location where the patient was admitted when entering the hospital/clinic, corresponds to *Admit_Source* in RPDR. Punctuation marks are removed.

enc_pat_type string, Provides information regarding the specific patient classifications and status of the patient visit. This field is only populated for McLean Hospital encounters, corresponds to *Patient_Type* in RPDR. Punctuation marks are removed.

enc_ref_disp string, Location where the patient has been directed for treatment or follow-up by a staff member. This field is only populated for McLean Hospital encounters, corresponds to *Referrer_Discipline* in RPDR. Punctuation marks are removed.

enc_disch_disp string, Patient's anticipated location or status following the encounter, corresponds to *Discharge_Disposition* in RPDR. Punctuation marks are removed.

- enc_pay** string, Payors responsible for the hospital account. Multiple payors (primary, secondary, etc.) may be listed, corresponds to Payor in RPDR. Punctuation marks are removed.
- enc_diag_admit** string, Initial working diagnosis documented by the admitting or attending physician, corresponds to Admitting_Diagnosis in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_princ** string, Condition established, after study, to be chiefly responsible for occasioning the admission of the patient to the hospital for care, corresponds to Principle_Diagnosis in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_1** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_1 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_2** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_2 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_3** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_3 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_4** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_4 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_5** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_5 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_6** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_6 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_7** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_7 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_8** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_8 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_9** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_9 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_10** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_10 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_group** string, Diagnosis-Related Group for the encounter, in the following format: SYSTEM:CODE - Description, corresponds to DRG in RPDR. Punctuation marks and white spaces are removed.

 data_enc_raw

 Example of enc.txt output from RPDR.

Description

A enc.txt output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_enc_raw
```

Format

data.table

Value

data table, imported from enc.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Encounter_number string, Unique identifier of the record/visit. This values includes the source system, hospital, and a unique identifier within the source system.

Encounter_Status string, Billing account-related notes about the encounter. This will not be populated for all encounters.

Hospital string, Facility where the encounter occurred.

Inpatient_Outpatient string, Classifies the type of encounter as either Inpatient or Outpatient. ED visits are currently classified under the 'Outpatient' label.

Service_Line string, Hospital service line assigned to the encounter.

Attending_MD string, The attending provider associated with the encounter. For Epic professional billing, this is the billing provider.

Admit_Date string, Date when the patient was admitted or entered the facility.

Discharge_Date string, Date when the patient was discharged or left the facility.

LOS_Days numeric, Length of stay for the encounter.

Clinic_Name string, Specific department/location where the encounter occurred.

Admit_Source string, Location where the patient was admitted when entering the hospital/clinic.

Discharge_Disposition string, Patient's anticipated location or status following the encounter.

Payor string, Payors responsible for the hospital account. Multiple payors (primary, secondary, etc.) may be listed.

Admitting_Diagnosis string, Initial working diagnosis documented by the admitting or attending physician.

Principal_Diagnosis string, Condition established, after study, to be chiefly responsible for occasioning the admission of the patient to the hospital for care.

Diagnosis_1 string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_1 in RPDR.

Diagnosis_2 string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_2 in RPDR.

- Diagnosis_3** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_3 in RPDR.
- Diagnosis_4** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_4 in RPDR.
- Diagnosis_5** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_5 in RPDR.
- Diagnosis_6** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_6 in RPDR.
- Diagnosis_7** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_7 in RPDR.
- Diagnosis_8** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_8 in RPDR.
- Diagnosis_9** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_9 in RPDR.
- Diagnosis_10** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_10 in RPDR.
- DRG** string, Diagnosis-Related Group for the encounter, in the following format: SYSTEM:CODE - Description.
- Patient_Type** string, Provides information regarding the specific patient classifications and status of the patient visit. This field is only populated for McLean Hospital encounters.
- Referrer_Discipline** string, Location where the patient has been directed for treatment or follow-up by a staff member. This field is only populated for McLean Hospital encounters.

| | |
|----------|---|
| data_lab | <i>Example of processed lab.txt output from RPDR using the load_lab() function.</i> |
|----------|---|

Description

Result of a lab.txt output from RPDR loaded into a data table in R using *load_lab()*.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under **parserpdr-sample-data**.

Usage

```
data_lab
```

Format

```
data.table
```

Value

data table, with laboratory exam information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_lab_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *lab* datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_lab_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *lab* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_lab_loc string, if `mrn_type == TRUE`, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations. Data is formatted using `pretty_mrn()`.

time_lab_result POSIXct, Date when the specimen was collected, corresponds to *Seq_Date_Time* in RPDR. Converted to POSIXct format.

lab_group string, Higher-level grouping concept used to consolidate similar tests across hospitals, corresponds to *Group_ID* in RPDR.

lab_loinc string, Standardized LOINC code for the laboratory test, corresponds to *Loinc_Code* in RPDR.

lab_testID string, Internal identifier for the test used by the source system, corresponds to *Test_ID* in RPDR.

lab_descript string, Name of the lab test, corresponds to *Test_Description* in RPDR.

lab_result string, Result value for the test, corresponds to *Result* in RPDR. Punctuation marks and white spaces are removed.

lab_result_txt string, Additional information included with the result. This can include instructions for interpretation or comments from the laboratory, corresponds to *Result_Text* in RPDR. Punctuation marks and white spaces are removed.

lab_result_abn string, Flag for identifying if values are outside of normal ranges or represent a significant deviation from previous values, corresponds to *Abnormal_Flag* in RPDR. Punctuation marks and white spaces are removed.

lab_result_unit string, Units associated with the result value, corresponds to *Reference_Unit* in RPDR. Punctuation marks and white spaces are removed.

lab_result_range string, Normal or therapeutic range for this value, corresponds to *Reference_Range* in RPDR. Punctuation marks and white spaces are removed.

lab_result_toxic string, Reference range of values defined as being toxic to the patient, corresponds to *Toxic_Range* in RPDR. Punctuation marks and white spaces are removed.

lab_spec string, Type of specimen collected to perform the test, corresponds to *Specimen_Type* in RPDR. Punctuation marks and white spaces are removed.

lab_spec_txt string, Free-text information about the specimen, its collection or its integrity, corresponds to *Specimen_Text* in RPDR. Punctuation marks and white spaces are removed.

lab_correction string, Free-text information about any changes made to the results, corresponds to *Correction_Flag* in RPDR. Punctuation marks and white spaces are removed.

lab_status string, Flag which indicates whether the procedure is pending or complete, corresponds to *Test_Status* in RPDR. Punctuation marks and white spaces are removed.

lab_ord_pys string, Name of the ordering physician, corresponds to Ordering_Doc in RPDR. Punctuation marks are removed.

lab_accession string, Internal tracking number assigned to the specimen for identification in the lab, corresponds to Accession in RPDR.

lab_source string, Database source, either CDR (Clinical Data Repository) or RPDR (internal RPDR database), corresponds to Source in RPDR. Punctuation marks and white spaces are removed.

data_lab_raw

Example of lab.txt output from RPDR.

Description

A lab.txt output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

data_lab_raw

Format

data.table

Value

data table, imported from lab.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Seq_Date_Time string, Date when the specimen was collected.

Group_Id string, Higher-level grouping concept used to consolidate similar tests across hospitals.

Loinc_Code string, Standardized LOINC code for the laboratory test.

Test_Id string, Internal identifier for the test used by the source system.

Test_Description string, Name of the lab test.

Result string, Result value for the test.

Result_Text string, Additional information included with the result. This can include instructions for interpretation or comments from the laboratory.

Abnormal_Flag string, Flag for identifying if values are outside of normal ranges or represent a significant deviation from previous values.

Reference_Units numeric, Units associated with the result value.

Reference_Range string, Normal or therapeutic range for this value.

Toxic_Range string, Reference range of values defined as being toxic to the patient.

Specimen_Type string, Type of specimen collected to perform the test.

Specimen_Text string, Free-text information about the specimen, its collection or its integrity.

Correction_Flag string, Free-text information about any changes made to the results.

Test_Status string, Flag which indicates whether the procedure is pending or complete.

Ordering_Doc_Name string, Name of the ordering physician.

Accession string, Internal tracking number assigned to the specimen for identification in the lab.

Source string, Database source, either CDR (Clinical Data Repository) or RPDR (internal RPDR database).

| | |
|----------|---|
| data_med | <i>Example of processed med.txt output from RPDR using the load_med() function.</i> |
|----------|---|

Description

Result of a med.txt output from RPDR loaded into a data table in R using *load_med()*.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under **parserpdr-sample-data**.

Usage

```
data_med
```

Format

```
data.table
```

Value

data table, with encounter information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_med_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *enc* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

- ID_med_PMRN** string, Epic medical record number. This value is unique across Epic instances within the Partners network from *enc* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.
- ID_med_loc** string, if `mrn_type == TRUE`, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.
- med_enc_num** string, Unique identifier of the record/visit, displayed in the following format: Source System - Institution Number, corresponds to `Encounter_number` in RPDR.
- time_med** POSIXct, Completion status of the requested test/transfusion. Converted to POSIXct format, corresponds to `Medication_Date` in RPDR.
- time_med_detail** string, To clarify when patients may have stopped taking a medication, this column provides the statuses of 'Listed' or 'Removed'. This is provided on pre-Epic (LMR) medication dates (1997-2017). The 'Listed' value denotes that a medication was on the patient's medication list on the date indicated. The 'Removed' value denotes that a medication was removed from a patient's medication list on the date indicated. Corresponds to `Medication_Date_Detail` in RPDR.
- med** string, Name of the medication. This may be appended with the source system in the case of OnCall and LMR medications, corresponds to `Medication` in RPDR.
- med_code** string, Medication code associated with the "Code_type" value, corresponds to `Code` in RPDR.
- med_code_type** string, Standardized classification system or custom source value used to identify the medication, corresponds to `Code_Type` in RPDR.
- med_quant** string, Number of units of the medication ordered, corresponds to `Quantity` in RPDR.
- med_prov** string, Ordering provider for the medication, corresponds to `Provider` in RPDR. Punctuation marks are removed.
- med_clinic** string, Specific department/location where the medication was ordered or administered, corresponds to `Clinic` in RPDR. Punctuation marks are removed.
- med_hosp** string, Facility where the medication was ordered or administered, corresponds to `Hospital` in RPDR.
- med_inpatient** string, Identifies whether the medication was ordered with an Inpatient or Outpatient indication, corresponds to `Inpatient_Outpatient` in RPDR. Punctuation marks are removed.
- med_add_info** string, Additional administration information about the medication, corresponds to `Additional_Info` in RPDR.

data_med_raw

Example of med.txt output from RPDR.

Description

A `med.txt` output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

data_med_raw

Format

data.table

Value

data table, imported from med.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Medication_Date string, Completion status of the requested test/transfusion.

Medication_Date_Detail string, To clarify when patients may have stopped taking a medication, this column provides the statuses of 'Listed' or 'Removed'. This is provided on pre-Epic (LMR) medication dates (1997-2017). The 'Listed' value denotes that a medication was on the patient's medication list on the date indicated. The 'Removed' value denotes that a medication was removed from a patient's medication list on the date indicated.

Medication string, Name of the medication. This may be appended with the source system in the case of OnCall and LMR medications.

Code_Type boolean, Standardized classification system or custom source value used to identify the medication.

Code string, Medication code associated with the "Code_type" value.

Quantity string, Number of units of the medication ordered.

Provider string, Ordering provider for the medication.

Clinic string, Specific department/location where the medication was ordered or administered.

Hospital numeric, Facility where the medication was ordered or administered.

Inpatient_Outpatient string, Identifies whether the medication was ordered with an Inpatient or Outpatient indication.

Encounter_number number, Unique identifier of the record/visit, displayed in the following format: Source System - Institution Number.

Additional_Info number, Additional administration information about the medication.

| | |
|----------|---|
| data_mrn | <i>Example of processed mrn.txt output from RPDR using the load_mrn() function.</i> |
|----------|---|

Description

Result of a mrn.txt output from RPDR loaded into a data table in R using `load_mrn()`.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_mrn
```

Format

```
data.table
```

Value

data table, with MRN data.

ID_MERGE numeric, defined IDs by `merge_id`, used for merging later.

ID_mrn_INCOMING string, Patient identifier, usually the EMPI, corresponds to `IncomingId` in RPDR. Data is formatted using `pretty_mrn()`.

ID_mrn_INCOMING_SITE string, Source of identifier, e.g. EMP for Enterprise Master Patient Index, MGH for Mass General Hospital, corresponds to `IncomingSite` in RPDR.

ID_mrn_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network, corresponds to `EPIC_PMRN` in RPDR. Data is formatted using `pretty_mrn()`.

ID_mrn_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information, corresponds to `Enterprise_Master_Patient_Index` in RPDR. Data is formatted using `pretty_mrn()`.

ID_mrn_MGH string, Unique Medical Record Number for Mass General Hospital, corresponds to `MGH_MRN` in RPDR. Data is formatted using `pretty_mrn()`.

ID_mrn_BWH string, Unique Medical Record Number for Brigham and Women's Hospital, corresponds to `BWH_MRN` in RPDR. Data is formatted using `pretty_mrn()`.

ID_mrn_FH string, Unique Medical Record Number for Faulkner Hospital, corresponds to `FH_MRN` in RPDR. Data is formatted using `pretty_mrn()`.

ID_mrn_SRH string, Unique Medical Record Number for Spaulding Rehabilitation Hospital, corresponds to `SRH_MRN` in RPDR. Data is formatted using `pretty_mrn()`.

ID_mrn_NWH string, Unique Medical Record Number for Newton-Wellesley Hospital, corresponds to `NWH_MRN` in RPDR. Data is formatted using `pretty_mrn()`.

- ID_mrn_NSMC** string, Unique Medical Record Number for North Shore Medical Center, corresponds to NSMC_MRN in RPDR. Data is formatted using `pretty_mrn()`.
- ID_mrn_MCL** string, Unique Medical Record Number for McLean Hospital, corresponds to MCL_MRN in RPDR. Data is formatted using `pretty_mrn()`.
- ID_mrn_MEE** string, Unique Medical Record Number for Mass Eye and Ear, corresponds to MEE_MRN in RPDR. Data is formatted using `pretty_mrn()`.
- ID_mrn_DFC** string, Unique Medical Record Number for Dana Farber Cancer center, corresponds to DFC_MRN in RPDR. Data is formatted using `pretty_mrn()`.
- ID_mrn_WDH** string, Unique Medical Record Number for Wentworth-Douglass Hospital, corresponds to WDH_MRN in RPDR. Data is formatted using `pretty_mrn()`.
- ID_mrn_STATUS** string, Status of the record, corresponds to Status in RPDR.

 data_mrn_raw

Example of mrn.txt output from RPDR.

Description

A `mrn.txt` output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_mrn_raw
```

Format

```
data.table
```

Value

data table, imported from `mrn.txt`

IncomingId numeric, Patient identifier, usually the EMPI.

IncomingSite string, Source of identifier, e.g. EMP for Enterprise Master Patient Index, MGH for Mass General Hospital.

Status string, Status of the record.

Enterprise_Master_Patient_Index numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MGH_MRN numeric, Unique Medical Record Number for Mass General Hospital.

BWH_MRN numeric, Unique Medical Record Number for Brigham and Women's Hospital.

FH_MRN numeric, Unique Medical Record Number for Faulkner Hospital.

SRH_MRN numeric, Unique Medical Record Number for Spaulding Rehabilitation Hospital.
NWH_MRN numeric, Unique Medical Record Number for Newton-Wellesley Hospital.
NSMC_MRN numeric, Unique Medical Record Number for North Shore Medical Center.
MCL_MRN numeric, Unique Medical Record Number for McLean Hospital.
MEE_MRN numeric, Unique Medical Record Number for Mass Eye and Ear.
DFC_MRN numeric, Unique Medical Record Number for Dana Farber Cancer center.
WDH_MRN numeric, Unique Medical Record Number for Wentworth-Douglass Hospital.

data_rad *Example of processed rad.txt output from RPDR using the load_rad() function.*

Description

Result of a rad.txt output from RPDR loaded into a data table in R using `load_rad()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

data_rad

Format

data.table

Value

data table, with radiological notes information.

ID_MERGE numeric, defined IDs by `merge_id`, used for merging later.

ID_rad_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from `rad` datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_rad_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from `rad` datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_rad_loc string, if `mrn_type == TRUE`, then the data in `MRN_Type` and `MRN` are parsed into IDs corresponding to locations (`loc`). Data is formatted using `pretty_mrn()`.

time_rad_exam POSIXct, Date when the report was filed, corresponds to Report_Date_Time in RPDR. Converted to POSIXct format.

rad_rep_num string, Source-specific identifier used to reference the report, corresponds to Report_Number in RPDR.

rad_rep_desc string, Type of procedure detailed in the report, corresponds to Report_Description in RPDR.

rad_rep_status string, Completion status of the note/report, corresponds to Report_Status in RPDR.

rad_rep_type string, This will always default to RAD, corresponds to Report_Type in RPDR.

rad_rep_txt string, Full narrative text contained in the note/report, corresponds to Report_Text in RPDR.

data_rad_raw

Example of rad.txt output from RPDR.

Description

A rad.txt output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

data_rad_raw

Format

data.table

Value

data table, imported from rad.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Report_Number string, Source-specific identifier used to reference the report.

Report_Date_Time string, Date when the report was filed.

Report_Description string, Type of procedure detailed in the report.

Report_Status string, Completion status of the note/report..

Report_Type string, This will always default to RAD.

Report_Text string, Full narrative text contained in the note/report.

| | |
|----------|---|
| data_rdt | <i>Example of processed rdt.txt output from RPDR using the load_rdt() function.</i> |
|----------|---|

Description

Result of a rdt.txt output from RPDR loaded into a data table in R using `load_rdt()`.

****NOTE**:** Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

```
data_rdt
```

Format

```
data.table
```

Value

data table, with radiological exam information.

ID_MERGE numeric, defined IDs by `merge_id`, used for merging later.

ID_rdt_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from `rdt` datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_rdt_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from `rdt` datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_con_loc string, if `mrn_type == TRUE`, then the data in `MRN_Type` and `MRN` are parsed into IDs corresponding to locations. Data is formatted using `pretty_mrn()`.

time_rad_exam POSIXct, Date of the radiology exam, corresponds to Date in RPDR. Converted to POSIXct format.

rad_mode string, Modality of the exam, corresponds to Mode in RPDR. Punctuation marks and white spaces are removed.

rad_group string, Higher-level grouping concept used to consolidate similar procedures across hospitals, corresponds to Group in RPDR. Punctuation marks and white spaces are removed.

rad_test_code string, Internal identifier for the procedure used by the source system, corresponds to Test_Code in RPDR.

rad_test_desc string, Full name of the exam/study performed, corresponds to Test_Description in RPDR.

rad_accession string, Identifier assigned to the report or procedure for Radiology tracking purposes, corresponds to Accession_Number in RPDR.

rad_provider string, Ordering or authorizing provider for the study, corresponds to Provider in RPDR. Punctuation marks are removed.

rad_clinic string, Specific department/location where the procedure was ordered or performed, corresponds to Clinic in RPDR. Punctuation marks are removed.

rad_hosp string, Facility where the order was entered, corresponds to Hospital in RPDR. Punctuation marks and white spaces are removed.

rad_inpatient string, Classifies the type of encounter where the procedure was performed, corresponds to Inpatient_Outpatient in RPDR. Punctuation marks are removed.

data_rdt_raw

Example of rdt.txt output from RPDR.

Description

A rdt.txt output from RPDR loaded into a data table in R using `data.table::fread()`.

****NOTE****: Due to potential issues with PHI and PPI, the example datasets can be downloaded from the Partners Gitlab repository under `*parserpdr-sample-data*`.

Usage

data_rdt_raw

Format

data.table

Value

data table, imported from rdt.txt

EMPI numeric, Unique Partners-wide identifier assigned to the patient used to consolidate patient information.

EPIC_PMRN numeric, Epic medical record number. This value is unique across Epic instances within the Partners network.

MRN_Type string, Indicates the institution associated with a specific MRN. This can appear as a comma-delimited list if MRNs from multiple Partners Health System institutions are available.

MRN string, Unique Medical Record Number for the site identified in the 'MRN_Type' field. This can appear as a comma-delimited list if multiple MRNs from Partners hospitals are available.

Date string, Date of the radiology exam.

Mode string, Modality of the exam.

Group string, Higher-level grouping concept used to consolidate similar procedures across hospitals.

Test_Code string, Internal identifier for the procedure used by the source system.

Test_Description string, Full name of the exam/study performed.

Accession_Number string, Identifier assigned to the report or procedure for Radiology tracking purposes.

Provider string, Ordering or authorizing provider for the study.

Clinic string, Specific department/location where the procedure was ordered or performed.

Hospital numeric, Facility where the order was entered.

Inpatient_Outpatient string, Classifies the type of encounter where the procedure was performed.

| | |
|-----------|---|
| find_exam | <i>Find exam data within a given timeframe using parallel CPU computing and possibly shared RAM management.</i> |
|-----------|---|

Description

Finds all, earliest or closest examination to a given timepoints using parallel computing

Usage

```
find_exam(
  d_from,
  d_to,
  d_from_ID = "ID_MERGE",
  d_to_ID = "ID_MERGE",
  d_from_time = "time_rad_exam",
  d_to_time = "time_enc_admit",
  time_diff_name = "timediff_exam_to_db",
  before = TRUE,
  after = TRUE,
  time = 1,
  time_unit = "days",
  multiple = "closest",
  add_column = NULL,
  keep_data = FALSE,
  nThread = 4,
  shared_RAM = FALSE
)
```

Arguments

| | |
|-------------|---|
| d_from | data table, the database which is searched to find examinations within the time-frame. |
| d_to | data table, the database to which we wish to find examinations within the time-frame. |
| d_from_ID | string, column name of the patient ID column in d_from. Defaults to <i>ID_MERGE</i> . |
| d_to_ID | string, column name of the patient ID column in d_to. Defaults to <i>ID_MERGE</i> . |
| d_from_time | string, column name of the time variable column in d_from. Defaults to <i>time_rad_exam</i> . |

| | |
|----------------|---|
| d_to_time | string, column name of the time variable column in d_to. Defaults to <i>time_enc_admit</i> . |
| time_diff_name | string, column name of the new column created which holds the time difference between the exam and the time provided by d_to. Defaults to <i>timediff_exam_to_db</i> . |
| before | boolean, should times before the given time be considered. Defaults to <i>TRUE</i> . |
| after | boolean, should times after the given time be considered. Defaults to <i>TRUE</i> . |
| time | integer, the timeframe considered between the exam and the d_to timepoints. Defaults to <i>1</i> . |
| time_unit | string, the unit of time used. Time variables are in d_to and d_from are truncated to the supplied time unit. For example: "2005-09-18 08:15:01 PDT" would be truncated to "2005-09-18 PDT" if <i>time_unit</i> is set to days. Then the time differences is calculated using <i>difftime</i> passing the argument to <i>units</i> . The following time units are supported: "secs", "mins", "hours", "days", "months" and "years" are supported. Defaults to <i>days</i> . |
| multiple | string, which exams to give back. <i>closest</i> gives back the exam closest to the time provided by d_to. <i>all</i> gives back all occurrences within the timeframe. <i>earliest</i> the earliest exam within the timeframe. In case of ties for <i>closest</i> or <i>earliest</i> , all are returned. Defaults to <i>closest</i> . |
| add_column | string, a column name in d_to to add to the output. Defaults to <i>NULL</i> . |
| keep_data | boolean, whether to include empty rows with only the <i>d_from_ID</i> column filed out for cases that have data in the <i>d_from</i> , but not within the time range. Defaults to <i>FALSE</i> . |
| nThread | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |
| shared_RAM | boolean, whether to use shared memory during parallelization using the <i>big-memory</i> package. This allows to process <i>d_from</i> and/or <i>d_to</i> datasets with >1M rows. Be aware that shared RAM usually results in slower run times, therefore by default it is set to <i>FALSE</i> , but it allows to run more threads when the datasets are large providing overall faster run times. Be aware that the optimal number of clusters might be different setting it to <i>TRUE</i> or <i>FALSE</i> , and this has to be determined empirically per machine. |

Value

data table, with *d_from* filtered to ones only within the timeframe. The columns of *d_from* are returned with the corresponding time column in *data_to* where the rows are instances which comply with the time constraints specified by the function. An additional column specified in *time_diff_name* is also returned, which shows the time difference between the time column in *d_from* and *d_to* for that given case. Also the time column from *d_to* specified by *d_to_time* is returned under the name of *time_to_db*. An additional column specified in *add_column* may be added from *data_to* to the data table.

Examples

```
## Not run:
#Filter encounters for first emergency visits at one of MGH's ED departments
data_enc_ED <- data_enc[enc_clinic == "MGH EMERGENCY 10020010608"]
data_enc_ED <- data_enc_ED[!duplicated(data_enc_ED$ID_MERGE)]

#Find all radiological examinations within 3 day of the ED registration
rdt_ED <- find_exam(d_from = data_rdt, d_to = data_enc_ED,
  d_from_ID = "ID_MERGE", d_to_ID = "ID_MERGE",
  d_from_time = "time_rdt_exam", d_to_time = "time_enc_admit", time_diff_name = "time_diff_ED_rdt",
  before = TRUE, after = TRUE, time = 3, time_unit = "days", multiple = "all",
  nThread = 2, shared_RAM = FALSE)

#Find earliest radiological examinations within 3 day of the ED registration
rdt_ED <- find_exam(d_from = data_rdt, d_to = data_enc_ED,
  d_from_ID = "ID_MERGE", d_to_ID = "ID_MERGE",
  d_from_time = "time_rdt_exam", d_to_time = "time_enc_admit", time_diff_name = "time_diff_ED_rdt",
  before = TRUE, after = TRUE, time = 3, time_unit = "days", multiple = "earliest",
  nThread = 2, shared_RAM = FALSE)

#Find closest radiological examinations on or after 1 day of the ED registration
#and add primary diagnosis column from encounters
rdt_ED <- find_exam(d_from = data_rdt, d_to = data_enc_ED,
  d_from_ID = "ID_MERGE", d_to_ID = "ID_MERGE",
  d_from_time = "time_rdt_exam", d_to_time = "time_enc_admit", time_diff_name = "time_diff_ED_rdt",
  before = FALSE, after = TRUE, time = 1, time_unit = "days", multiple = "earliest",
  add_column = "enc_diag_princ", nThread = 2, shared_RAM = FALSE)

#Find closest radiological examinations on or after 1 day of the ED registration
#but also provide empty rows for patients with exam data but not within the timeframe
rdt_ED <- find_exam(d_from = data_rdt, d_to = data_enc_ED,
  d_from_ID = "ID_MERGE", d_to_ID = "ID_MERGE",
  d_from_time = "time_rdt_exam", d_to_time = "time_enc_admit", time_diff_name = "time_diff_ED_rdt",
  before = FALSE, after = TRUE, time = 1, time_unit = "days", multiple = "earliest",
  add_column = "enc_diag_princ", keep_data = TRUE nThread = 2, shared_RAM = FALSE)

## End(Not run)
```

load_all

Loads all RPDR text outputs into R.

Description

Loads all RPDR text outputs into R and returns a list of data tables processed. Currently supported outputs are: *Mrn.txt*, *Con.txt*, *Dem.txt*, *Enc.txt*, *Rdt.txt*, *Lab.txt*, *Med.txt*, *Dia.txt*, *Rfv.txt*, *Prc.txt*, *Car.txt*, *Dis.txt*, *End.txt*, *Hnp.txt*, *Opn.txt*, *Pat.txt*, *Prg.txt*, *Pul.txt*, *Rad.txt* and *Vis.txt*. If multiple text files of the same type are available (if the query is larger than 25000 patients), then add a "_" and a number to merge the same data sources into a single output in the order of the provided number.

Usage

```
load_all(
  folder,
  which_data = c("mrn", "con", "dem", "enc", "rdt", "lab", "med", "dia", "rfv", "prc",
    "lno", "car", "dis", "end", "hnp", "opn", "pat", "prg", "pul", "rad", "vis"),
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  many_sources = TRUE
)
```

Arguments

| | |
|--------------|--|
| folder | string, full folder path to RPDR text files. |
| which_data | string vector, an array of abbreviation corresponding to the datasources wished to load. Currently supported values and the default is: <code>c("mrn", "con", "dem", "enc", "rdt", "lab", "med", "dia", "rfv", "prc", "car", "dis", "end", "hnp", "opn", "pat", "prg", "pul", "rad" and "vis")</code> |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EMPI</i> , as it is the preferred MRN in the RPDR system. In case of <i>mrn</i> dataset, leave at <i>EMPI</i> , as it is automatically converted to: "Enterprise_Master_Patient_Index". |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length</i> = <i>standard</i> , or to keep lengths as is <i>id_length</i> = <i>asis</i> . If <i>id_length</i> = <i>standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc</i> x 100% of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use for parallelization. |
| many_sources | boolean, if <i>TRUE</i> , then parallelization is done on the level of the datasources. If <i>FALSE</i> , then parallelization is done within the datasources. If there are many datasources, then it is advised to set this <i>TRUE</i> , as then each different datasource will be processed in parallel. However, if there are only a few datasources selected to load, but many files per datasource (result of large queries), then it may be faster to parallelize within each datasource and therefore should be set to <i>FALSE</i> . If there are only a few sources each with one file then set to <i>TRUE</i> . |

Value

list of parsed data tables containing the information.

Examples

```
## Not run:
#Load all Con, Dem and Mrn datasets processing all files within given datasource in parallel
load_all(folder = folder_rpdr, which_data = c("con", "dem", "mrn"),
nThread = 2, many_sources = FALSE)

#Load all supported file types parallelizing on the level of datasources
load_all(folder = folder_rpdr, nThread = 2, many_sources = TRUE)

## End(Not run)
```

| | |
|----------|--|
| load_con | <i>Loads contact information into R.</i> |
|----------|--|

Description

Loads patient contact, insurance, and PCP information into the R environment.

Usage

```
load_con(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = TRUE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Con.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <i>:</i> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |

| | |
|-----------|---|
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>TURE</i> only for Con.txt, as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with contact information data.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_con_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *con* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

ID_con_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *con*datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_con_loc string, if *mrn_type* == *TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using *pretty_mrn()*.

ID_con_loc_list string, if prevalence of IDs in *Patient_ID_List* > *perc*, then they are included in the output. Data is formatted using *pretty_mrn()*.

name_last string, Patient's last name, corresponds to Last_Name in RPDR.

name_first string, Patient's first name, corresponds to First_Name in RPDR.

name_middle string, Patient's middle name or initial, corresponds to Middle_Name in RPDR.

name_previous string, Any alternate names on record for this patient, corresponds to Previous_Name in RPDR.

SSN string, Social Security Number, corresponds to SSN in RPDR.

VIP character, Special patient statuses as defined by the EMPI group, corresponds to VIP in RPDR.

address1 string, Patient's current address, corresponds to address1 in RPDR.

address2 string, Additional address information, corresponds to address2 in RPDR.

city string, City of residence, corresponds to City in RPDR.

state string, State of residence, corresponds to State in RPDR.

country_con string, Country of residence from *con* datasource, corresponds to Country in RPDR. Punctuation marks are removed.

zip_con numeric, Mailing zip code of primary residence from *con* datasource, corresponds to Zip in RPDR. Formatted to 5 character zip codes using *pretty_numbers()*.

direct_contact_consent boolean, Indicates whether the patient has given permission to contact them directly through the RODY program, corresponds to Direct_Contact_Consent in RPDR.

phone_home number, Patient's home phone number, corresponds to Home_Phone in RPDR. Formatted to 10 digit phone numbers using *pretty_numbers()*.

phone_day number, Phone number where the patient can be reached during the day, corresponds to Day_Phone in RPDR. Formatted to 10 digit phone numbers using *pretty_numbers()*.

insurance1 string, Patient's primary health insurance carrier and subscriber ID information, corresponds to Insurance_1 in RPDR. Punctuation marks are removed.

insurance2 string, Patient's secondary health insurance carrier and subscriber ID information, if any, corresponds to Insurance_2 in RPDR. Punctuation marks are removed.

insurance3 string, Patient's tertiary health insurance carrier and subscriber ID information, if any, corresponds to Insurance_3 in RPDR. Punctuation marks are removed.

primary_care_physician string, Comma-delimited list of all primary care providers on record for this patient per institution, along with contact information (if available), corresponds to Primary_Care_Physician in RPDR. Punctuation marks are removed.

primary_care_physician_resident string, Comma-delimited list of any Resident primary care providers on record for this patient per institution, along with contact information (if available), corresponds to Resident_Primary_Care_Physician in RPDR. Punctuation marks are removed.

Examples

```
## Not run:
#Using defaults
d_con <- load_con(file = "test_Con.txt")

#Use sequential processing
d_con <- load_con(file = "test_Con.txt", nThread = 1)

#Use parallel processing and parse data in
#MRN_Type and MRN columns (default in load_con) and keep all IDs
d_con <- load_con(file = "test_Con.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_dem

Loads demographic information into R.

Description

Loads patient demographic and vital status information into the R environment.

Usage

```
load_dem(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
```

```

    identical = TRUE,
    nThread = 4,
    mrn_type = FALSE
)

```

Arguments

| | |
|-----------|--|
| file | string, full file path to Dem.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH, BWH, MCL, EMPI and PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with demographic information data.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_dem_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information. from *dem* datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_dem_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network. from *dem* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_dem_loc string, if *mrn_type == TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.

gender string, Patient's legal sex, corresponds to Gender in RPDR. Punctuation marks and white spaces are removed.

time_date_of_birth POSIXct, Patient's date of birth, corresponds to Date_of_Birth in RPDR. Converted to POSIXct format.

age string, Patient's current age (or age at death), corresponds to Age in RPDR.

language string, Patient's preferred spoken language, corresponds to Language in RPDR. Punctuation marks and white spaces are removed.

race string, Patient's primary race, corresponds to Race in RPDR. Punctuation marks and white spaces are removed.

marital string, Patient's current marital status, corresponds to Marital_Status in RPDR. Punctuation marks and white spaces are removed.

religion string, Patient-identified religious preference, corresponds to Religion in RPDR. Punctuation marks and white spaces are removed.

veteran string, Patient's current military veteran status, corresponds to Is_a_veteran in RPDR. Punctuation marks and white spaces are removed.

country_dem string, Patient's current country of residence from dem datasource, corresponds to Country in RPDR. Punctuation marks and white spaces are removed.

zip_dem string, Mailing zip code of patient's primary residence from dem datasource, corresponds to Zip_code in RPDR. Formatted to 5 character zip codes.

vital_status string, Identifies if the patient is living or deceased. This data is updated monthly from the Partners registration system and the Social Security Death Master Index, corresponds to Vital_Status in RPDR. Punctuation marks are removed.

time_date_of_death POSIXct, Recorded date of death from source in 'Vital_Status'. Date of death information obtained solely from the Social Security Death Index will not be reported until 3 years after death due to privacy concerns. If the value is independently documented by a Partners entity within the 3 year window then the date will be displayed. corresponds to Date_of_Death in RPDR. Converted to POSIXct format.

Examples

```
## Not run:
#Using defaults
d_dem <- load_dem(file = "test_Dem.txt")

#Use sequential processing
d_dem <- load_dem(file = "test_Dem.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_dem <- load_dem(file = "test_Dem.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_dia

Loads diagnoses into R.

Description

Loads diagnoses information into the R environment.

Usage

```
load_dia(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Dia.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with diagnoses information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_dia_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *dia* datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_dia_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *dia* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_dia_loc string, if `mrn_type == TRUE`, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.

time_dia POSIXct, Date when the diagnosis was noted, corresponds to Date in RPDR. Converted to POSIXct format.

dia_name string, Name of the diagnosis, diagnosis-related group, or phenotype. For more information on available Phenotypes visit https://phenotypes.partners.org/phenotype_list.html, corresponds to Diagnosis_Name in RPDR.

dia_code string, Diagnosis, diagnosis-related group, or phenotype code, corresponds to Code in RPDR.

dia_code_type string, Standardized classification system or custom grouping associated with the diagnosis code, corresponds to Code_type in RPDR.

dia_flag string, Qualifier for the diagnosis, if any, corresponds to Diagnosis_flag in RPDR.

dia_enc_num string, Unique identifier of the record/visit. This values includes the source system, hospital, and a unique identifier within the source system, corresponds to Encounter_number in RPDR.

dia_provider string, Provider of record for the encounter where the diagnosis was entered, corresponds to Provider in RPDR. Punctuation marks are removed.

dia_clinic string, Specific department/location where the patient encounter took place, corresponds to Clinic in RPDR.

dia_hosp string, Facility where the encounter occurred, corresponds to Hospital in RPDR.

dia_inpatient string, Identifies whether the diagnosis was noted during an inpatient or outpatient encounter, corresponds to Inpatient_Outpatient in RPDR. Punctuation marks removed.

Examples

```
## Not run:
#Using defaults
d_dia <- load_dia(file = "test_Dia.txt")

#Use sequential processing
d_dia <- load_dia(file = "test_Dia.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_dia <- load_dia(file = "test_Dia.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_enc

Loads encounter information into R.

Description

Loads encounter-level detail information into the R environment.

Usage

```
load_enc(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Enc.txt or Exc.txt |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with encounter information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_enc_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *enc* datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_enc_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *enc* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_enc_loc string, if *mrn_type == TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.

- enc_numb** string, Unique identifier of the record/visit. This values includes the source system, hospital, and a unique identifier within the source system, corresponds to Encounter_number in RPDR.
- time_enc_admit** POSIXct, Date when the patient was admitted or entered the facility, corresponds to Admit_Date in RPDR. Converted to POSIXct format.
- time_enc_disch** POSIXct, Date when the patient was discharged or left the facility, corresponds to Discharge_Date in RPDR. Converted to POSIXct format.
- enc_status** string, Billing account-related notes about the encounter. This will not be populated for all encounters, corresponds to Encounter_Status in RPDR. Punctuation marks are removed.
- enc_hosp** string, Facility where the encounter occurred, corresponds to Hospital in RPDR.
- enc_inpatient** string, Classifies the type of encounter as either Inpatient or Outpatient. ED visits are currently classified under the 'Outpatient' label, corresponds to Inpatient_or_Outpatient in RPDR. Punctuation marks are removed.
- enc_service** string, Hospital service line assigned to the encounter, corresponds to Service_Line in RPDR. Punctuation marks are removed.
- enc_attending** string, The attending provider associated with the encounter. For Epic professional billing, this is the billing provider, corresponds to Attending_MD in RPDR. Punctuation marks are removed.
- enc_length** numeric, Length of stay for the encounter, corresponds to LOS_days in RPDR.
- enc_clinic** string, Specific department/location where the encounter occurred, corresponds to Clinic_Name in RPDR.
- enc_admit_src** string, Location where the patient was admitted when entering the hospital/clinic, corresponds to Admit_Source in RPDR. Punctuation marks are removed.
- enc_pat_type** string, Provides information regarding the specific patient classifications and status of the patient visit. This field is only populated for McLean Hospital encounters, corresponds to Patient_Type in RPDR. Punctuation marks are removed.
- enc_ref_disp** string, Location where the patient has been directed for treatment or follow-up by a staff member. This field is only populated for McLean Hospital encounters, corresponds to Referrer_Discipline in RPDR. Punctuation marks are removed.
- enc_disch_disp** string, Patient's anticipated location or status following the encounter, corresponds to Discharge_Disposition in RPDR. Punctuation marks are removed.
- enc_pay** string, Payors responsible for the hospital account. Multiple payors (primary, secondary, etc.) may be listed, corresponds to Payor in RPDR. Punctuation marks are removed.
- enc_diag_admit** string, Initial working diagnosis documented by the admitting or attending physician, corresponds to Admitting_Diagnosis in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_princ** string, Condition established, after study, to be chiefly responsible for occasioning the admission of the patient to the hospital for care, corresponds to Principle_Diagnosis in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_1** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_1 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_2** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_2 in RPDR. Punctuation marks and white spaces are removed.

- enc_diag_3** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_3 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_4** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_4 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_5** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_5 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_6** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_6 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_7** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_7 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_8** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_8 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_9** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_9 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_10** string, Additional diagnoses associated with this encounter or visit, corresponds to Diagnosis_10 in RPDR. Punctuation marks and white spaces are removed.
- enc_diag_group** string, Diagnosis-Related Group for the encounter, in the following format: SYSTEM:CODE - Description, corresponds to DRG in RPDR. Punctuation marks and white spaces are removed.

Examples

```
## Not run:
#Using defaults
d_enc <- load_enc(file = "test_Enc.txt")

#Use sequential processing
d_enc <- load_enc(file = "test_Enc.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_enc <- load_enc(file = "test_Enc.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_lab

Loads laboratory results into R.

Description

Loads laboratory results into the R environment.

Usage

```
load_lab(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Enc.txt or Exc.txt |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <i>:</i> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with laboratory exam information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_lab_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *lab* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

ID_lab_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *lab* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_lab_loc string, if *mrn_type == TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using *pretty_mrn()*.

- time_lab_result** POSIXct, Date when the specimen was collected, corresponds to Seq_Date_Time in RPDR. Converted to POSIXct format.
- lab_group** string, Higher-level grouping concept used to consolidate similar tests across hospitals, corresponds to Group_ID in RPDR.
- lab_loinc** string, Standardized LOINC code for the laboratory test, corresponds to Loinc_Code in RPDR.
- lab_testID** string, Internal identifier for the test used by the source system, corresponds to Test_ID in RPDR.
- lab_descript** string, Name of the lab test, corresponds to Test_Description in RPDR.
- lab_result** string, Result value for the test, corresponds to Result in RPDR.
- lab_result_txt** string, Additional information included with the result. This can include instructions for interpretation or comments from the laboratory, corresponds to Result_Text in RPDR.
- lab_result_abn** string, Flag for identifying if values are outside of normal ranges or represent a significant deviation from previous values, corresponds to Abnormal_Flag in RPDR.
- lab_result_unit** string, Units associated with the result value, corresponds to Reference_Unit in RPDR.
- lab_result_range** string, Normal or therapeutic range for this value, corresponds to Reference_Range in RPDR.
- lab_result_toxic** string, Reference range of values defined as being toxic to the patient, corresponds to Toxic_Range in RPDR.
- lab_spec** string, Type of specimen collected to perform the test, corresponds to Specimen_Type in RPDR.
- lab_spec_txt** string, Free-text information about the specimen, its collection or its integrity, corresponds to Specimen_Text in RPDR.
- lab_correction** string, Free-text information about any changes made to the results, corresponds to Correction_Flag in RPDR.
- lab_status** string, Flag which indicates whether the procedure is pending or complete, corresponds to Test_Status in RPDR.
- lab_ord_pys** string, Name of the ordering physician, corresponds to Ordering_Doc in RPDR. Punctuation marks are removed.
- lab_accession** string, Internal tracking number assigned to the specimen for identification in the lab, corresponds to Accession in RPDR.
- lab_source** string, Database source, either CDR (Clinical Data Repository) or RPDR (internal RPDR database), corresponds to Source in RPDR.

Examples

```
## Not run:
#Using defaults
d_lab <- load_lab(file = "test_Lab.txt")

#Use sequential processing
d_lab <- load_lab(file = "test_Lab.txt", nThread = 1)
```

```
#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_lab <- load_lab(file = "test_Lab.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

| | |
|----------|---|
| load_lno | <i>Loads LMR note documents into R.</i> |
|----------|---|

Description

Loads notes from the LMR legacy EHR system.

Usage

```
load_lno(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Lno.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <i>:</i> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with LMR notes information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_lno_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *lno* datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_lno_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *lno* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_lno_loc string, if `mrn_type == TRUE`, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.

time_lno POSIXct, Date when the report was filed, corresponds to LMRNote_Date in RPDR. Converted to POSIXct format.

lno_rec_id string, Internal identifier for this report within the LMR system, corresponds to Record_Id in RPDR.

lno_status string, Completion status of the note, corresponds to Status in RPDR.

lno_author string, Name of user who created the note, corresponds to Author in RPDR.

lno_author_mrn string, Author's user identifier within the LMR system, corresponds to Author_MRN in RPDR.

lno_COD string, Hospital-specific user code of the note author. The first character is a hospital-specific prefix, corresponds to COD in RPDR. Punctuation marks are removed.

lno_hosp string, Facility where the encounter occurred, corresponds to Institution in RPDR.

lno_subject string, Type of note. This value is derived from the "Subject" line of the narrative text, corresponds to Subject in RPDR.

lno_rep_txt string, Full narrative text of the note, corresponds to Comments in RPDR.

Examples

```
## Not run:
#Using defaults
d_lno <- load_lno(file = "test_Lno.txt")

#Use sequential processing
d_lno <- load_lno(file = "test_Lno.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_lno <- load_lno(file = "test_Lno.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

| | |
|----------|--|
| load_med | <i>Loads medication order detail into R.</i> |
|----------|--|

Description

Loads medication order detail information into the R environment.

Usage

```
load_med(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|--|
| file | string, full file path to Enc.txt or Exc.txt |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length</i> = <i>standard</i> , or to keep lengths as is <i>id_length</i> = <i>asis</i> . If <i>id_length</i> = <i>standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc</i> x 100% of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with medication order information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_med_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *enc* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

ID_med_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *enc* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_med_loc string, if *mrn_type* == TRUE, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using *pretty_mrn()*.

med_enc_num string, Unique identifier of the record/visit, displayed in the following format: Source System - Institution Number, corresponds to *Encounter_number* in RPDR.

time_med POSIXct, Completion status of the requested test/transfusion. Converted to POSIXct format, corresponds to *Medication_Date* in RPDR.

time_med_detail string, To clarify when patients may have stopped taking a medication, this column provides the statuses of 'Listed' or 'Removed'. This is provided on pre-Epic (LMR) medication dates (1997-2017). The 'Listed' value denotes that a medication was on the patient's medication list on the date indicated. The 'Removed' value denotes that a medication was removed from a patient's medication list on the date indicated. Corresponds to *Medication_Date_Detail* in RPDR.

med string, Name of the medication. This may be appended with the source system in the case of OnCall and LMR medications, corresponds to *Medication* in RPDR.

med_code string, Medication code associated with the "Code_type" value, corresponds to *Code* in RPDR.

med_code_type string, Standardized classification system or custom source value used to identify the medication, corresponds to *Code_Type* in RPDR.

med_quant string, Number of units of the medication ordered, corresponds to *Quantity* in RPDR.

med_prov string, Ordering provider for the medication, corresponds to *Provider* in RPDR. Punctuation marks are removed.

med_clinic string, Specific department/location where the medication was ordered or administered, corresponds to *Clinic* in RPDR.

med_hosp string, Facility where the medication was ordered or administered, corresponds to *Hospital* in RPDR.

med_inpatient string, Identifies whether the medication was ordered with an Inpatient or Outpatient indication, corresponds to *Inpatient_Outpatient* in RPDR. Punctuation marks are removed.

med_add_info string, Additional administration information about the medication, corresponds to *Additional_Info* in RPDR.

Examples

```
## Not run:
#Using defaults
d_med <- load_med(file = "test_Med.txt")

#Use sequential processing
d_med <- load_med(file = "test_Med.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_med <- load_med(file = "test_Med.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

| | |
|----------|-------------------------------|
| load_mrn | <i>Loads MRN data into R.</i> |
|----------|-------------------------------|

Description

Loads patient identifiers for Partners institutions, including hospital-specific MRNs into the R environment.

Usage

```
load_mrn(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Mrn.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |

| | |
|-----------|--|
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. Not used for loading mrn data. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with MRN data.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_mrn_INCOMING string, Patient identifier, usually the EMPI, corresponds to IncomingId in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_INCOMING_SITE string, Source of identifier, e.g. EMP for Enterprise Master Patient Index, MGH for Mass General Hospital, corresponds to IncomingSite in RPDR.

ID_mrn_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information, corresponds to Enterprise_Master_Patient_Index in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_MGH string, Unique Medical Record Number for Mass General Hospital, corresponds to MGH_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_BWH string, Unique Medical Record Number for Brigham and Women's Hospital, corresponds to BWH_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_FH string, Unique Medical Record Number for Faulkner Hospital, corresponds to FH_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_SRH string, Unique Medical Record Number for Spaulding Rehabilitation Hospital, corresponds to SRH_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_NWH string, Unique Medical Record Number for Newton-Wellesley Hospital, corresponds to NWH_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_NSMC string, Unique Medical Record Number for North Shore Medical Center, corresponds to NSMC_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_MCL string, Unique Medical Record Number for McLean Hospital, corresponds to MCL_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_MEE string, Unique Medical Record Number for Mass Eye and Ear, corresponds to MEE_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_DFC string, Unique Medical Record Number for Dana Farber Cancer center, corresponds to DFC_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_WDH string, Unique Medical Record Number for Wentworth-Douglass Hospital, corresponds to WDH_MRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_mrn_STATUS string, Status of the record, corresponds to Status in RPDR.

Examples

```
## Not run:
#Using defaults
d_mrn <- load_mrn(file = "test_Mrn.txt")

#Use sequential processing
d_mrn <- load_mrn(file = "test_Mrn.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_mrn <- load_mrn(file = "test_Mrn.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_notes

Loads note documents into R.

Description

Loads documents information into the R environment, which are:

- Cardiology: "car"
- Discharge: "dis"
- Endoscopy: "end"
- History & Physical: "hnp"
- Operative: "opn"
- Pathology: "pat"
- Progress: "prg"
- Pulmonary: "pul"
- Radiology: "rad"
- Visit: "vis"

Usage

```
load_notes(
  file,
  type,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|--|
| file | string, full file path to given type of note i.e. Hnp.txt. |
| type | string, the type of note to be loaded. May be on of: "car", "dis", "end", "hnp", "opn", "pat", "prg", "pul", "rad" or "vis". |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>.</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length</i> = <i>standard</i> , or to keep lengths as is <i>id_length</i> = <i>asis</i> . If <i>id_length</i> = <i>standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc</i> x 100% of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with notes information. *abc* stands for the three letter abbreviation of the given type of note.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_abc_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *abc* datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_abc_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *abc* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_abc_loc string, if *mrn_type* == *TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.

abc_rep_num string, Source-specific identifier used to reference the report, corresponds to Report_Number in RPDR.

time_abc POSIXct, Date when the report was filed, corresponds to Report_Date_Time in RPDR. Converted to POSIXct format.

abc_rep_desc string, Type of report or procedure documented in the report, corresponds to Report_Description in RPDR.

abc_rep_status string, Completion status of the note/report, corresponds to Report_Status in RPDR.

abc_rep_type string, See specification in RPDR data dictionary, corresponds to Report_Type in RPDR.

abc_rep_txt string, Full narrative text contained in the note/report, corresponds to Report_Text in RPDR. Not provided for progress notes.

Examples

```
## Not run:
#Using defaults
d_hnp <- load_notes(file = "test_Hnp.txt", type = "hnp")

#Use sequential processing
d_hnp <- load_notes(file = "test_Hnp.txt", type = "hnp", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_hnp <- load_notes(file = "test_Hnp.txt", type = "hnp", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_phy

Loads helath history information into R.

Description

Loads vital signs, social history, immunizations, and various other health history details into the R environment.

Usage

```
load_phy(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Phy.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <i>:</i> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |

| | |
|-----------|--|
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with health history information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_phy_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *phy* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

ID_phy_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *phy* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_phy_loc string, if *mrn_type == TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using *pretty_mrn()*.

time_phy POSIXct, Date when the diagnosis was noted, corresponds to Date in RPDR. Converted to POSIXct format.

phy_name string, Type of clinical value/observation recorded, corresponds to Concept_Name in RPDR.

phy_code string, Source-specific identifier for the specific type of clinical observation, corresponds to Code in RPDR.

phy_code_type string, Source system for the value, corresponds to Code_type in RPDR.

phy_result string, Value associated with the clinical observation. Note: BMI results are calculated internally in the RPDR, corresponds to Results in RPDR. Punctuation marks and white spaces are removed.

phy_unit string, Units associated with the clinical observation, corresponds to Units in RPDR. Punctuation marks and white spaces are removed.

phy_provider string, Provider of record for the encounter where the observation was recorded, corresponds to Providers in RPDR. Punctuation marks are removed.

phy_clinic string, Specific department/location where the patient observation was recorded, corresponds to Clinic in RPDR.

phy_hosp string, Facility where the observation was recorded, corresponds to Hospital in RPDR.

phy_inpatient string, Classifies the type of encounter where the observation was entered, corresponds to Inpatient_Outpatient in RPDR. Punctuation marks are removed.

phy_enc_num string, Unique identifier of the record/visit. This values includes the source system and a unique identifier within the source system, corresponds to Encounter_number in RPDR.

Examples

```
## Not run:
#Using defaults
d_phy <- load_phy(file = "test_Phy.txt")

#Use sequential processing
d_phy <- load_phy(file = "test_Phy.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_phy <- load_phy(file = "test_Phy.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

| | |
|----------|---------------------------------|
| load_prc | <i>Loads procedures into R.</i> |
|----------|---------------------------------|

Description

Loads Clinical procedure information into the R environment.

Usage

```
load_prc(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|--|
| file | string, full file path to Prc.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length</i> = <i>standard</i> , or to keep lengths as is <i>id_length</i> = <i>asis</i> . If <i>id_length</i> = <i>standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |

| | |
|------------------------|--|
| <code>perc</code> | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| <code>na</code> | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| <code>identical</code> | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| <code>nThread</code> | integer, number of threads to use to load data. |
| <code>mrn_type</code> | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with procedural information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_prc_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *prc* datasource, corresponds to EMPI in RPDR. Data is formatted using `pretty_mrn()`.

ID_prc_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *prc* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using `pretty_mrn()`.

ID_prc_loc string, if `mrn_type == TRUE`, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using `pretty_mrn()`.

time_prc POSIXct, Date when the procedure was performed, corresponds to Date in RPDR. Converted to POSIXct format.

prc_name string, Name of the procedure or operation performed, corresponds to Procedure_Name in RPDR.

prc_code string, Procedure code associated with the "Code_type" value, corresponds to Code in RPDR.

prc_code_type string, Standardized classification system or custom source value associated with the procedure code, corresponds to Code_type in RPDR.

prc_flag string, Qualifier for the diagnosis, corresponds to Procedure_Flag in RPDR.

prc_quantity string, Number of the procedures that were ordered for this record, corresponds to Quantity in RPDR.

prc_provider string, Provider identifies the health care clinician performing the procedure, corresponds to Provider in RPDR. Punctuation marks are removed.

prc_clinic string, Specific department/location where the procedure was ordered or performed, corresponds to Clinic in RPDR.

prc_hosp string, Facility where the procedure was ordered or performed, corresponds to Hospital in RPDR.

prc_inpatient string, classifies the type of encounter where the procedure was performed or ordered, Punctuation marks are removed.

prc_enc_num string, Unique identifier of the record/visit, displayed in the following format: Source System - Institution Number, corresponds to Encounter_number in RPDR.

Examples

```
## Not run:
#Using defaults
d_prc <- load_prc(file = "test_Prc.txt")

#Use sequential processing
d_prc <- load_prc(file = "test_Prc.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_prc <- load_prc(file = "test_Prc.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_rdt

Loads radiology procedures data into R.

Description

Loads radiology procedures information into the R environment.

Usage

```
load_rdt(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|--|
| file | string, full file path to Rdt.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length</i> = <i>standard</i> , or to keep lengths as is <i>id_length</i> = <i>asis</i> . If <i>id_length</i> = <i>standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |

| | |
|-----------|--|
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with radiological exam information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_rdt_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *rdt* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

ID_rdt_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *rdt* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_rdt_loc string, if *mrn_type* == *TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using *pretty_mrn()*.

time_rdt_exam POSIXct, Date of the radiology exam, corresponds to Date in RPDR. Converted to POSIXct format.

rdt_mode string, Modality of the exam, corresponds to Mode in RPDR.

rdt_group string, Higher-level grouping concept used to consolidate similar procedures across hospitals, corresponds to Group in RPDR.

rdt_test_code string, Internal identifier for the procedure used by the source system, corresponds to Test_Code in RPDR.

rdt_test_desc string, Full name of the exam/study performed, corresponds to Test_Description in RPDR.

rdt_accession string, Identifier assigned to the report or procedure for Radiology tracking purposes, corresponds to Accession_Number in RPDR.

rdt_provider string, Ordering or authorizing provider for the study, corresponds to Provider in RPDR. Punctuation marks are removed.

rdt_clinic string, Specific department/location where the procedure was ordered or performed, corresponds to Clinic in RPDR.

rdt_hosp string, Facility where the order was entered, corresponds to Hospital in RPDR.

rdt_inpatient string, Classifies the type of encounter where the procedure was performed, corresponds to Inpatient_Outpatient in RPDR. Punctuation marks are removed.

Examples

```
## Not run:
#Using defaults
d_rdt <- load_rdt(file = "test_Rdt.txt")

#Use sequential processing
d_rdt <- load_rdt(file = "test_Rdt.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_rdt <- load_rdt(file = "test_Rdt.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

load_rfv

Loads reason for visit data into R.

Description

Loads reason for visit information into the R environment.

Usage

```
load_rfv(
  file,
  merge_id = "EMPI",
  sep = ":",
  id_length = "standard",
  perc = 0.6,
  na = TRUE,
  identical = TRUE,
  nThread = 4,
  mrn_type = FALSE
)
```

Arguments

| | |
|-----------|---|
| file | string, full file path to Rfv.txt. |
| merge_id | string, column name to use to create <i>ID_MERGE</i> column used to merge different datasets. Defaults to <i>EPIC_PMRN</i> , as it is the preferred MRN in the RPDR system. |
| sep | string, divider between hospital ID and MRN. Defaults to <i>:</i> . |
| id_length | string, indicating whether to modify MRN length based-on required values <i>id_length = standard</i> , or to keep lengths as is <i>id_length = asis</i> . If <i>id_length = standard</i> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |

| | |
|-----------|--|
| perc | numeric, a number between 0-1 indicating which parsed ID columns to keep. Data present in <i>perc x 100%</i> of patients are kept. |
| na | boolean, whether to remove columns with only NA values. Defaults to <i>TRUE</i> . |
| identical | boolean, whether to remove columns with identical values. Defaults to <i>TRUE</i> . |
| nThread | integer, number of threads to use to load data. |
| mrn_type | boolean, should data in <i>MRN_Type</i> and <i>MRN</i> be parsed. Defaults to <i>FALSE</i> , as it is not advised to parse these for all data sources as it takes considerable time. |

Value

data table, with reason for visit information.

ID_MERGE numeric, defined IDs by *merge_id*, used for merging later.

ID_rfv_EMPI string, Unique Partners-wide identifier assigned to the patient used to consolidate patient information from *dia* datasource, corresponds to EMPI in RPDR. Data is formatted using *pretty_mrn()*.

ID_rfv_PMRN string, Epic medical record number. This value is unique across Epic instances within the Partners network from *rfv* datasource, corresponds to EPIC_PMRN in RPDR. Data is formatted using *pretty_mrn()*.

ID_rfv_loc string, if *mrn_type == TRUE*, then the data in *MRN_Type* and *MRN* are parsed into IDs corresponding to locations (*loc*). Data is formatted using *pretty_mrn()*.

time_rfv_start POSIXct, Start date of the encounter, corresponds to *Start_Date* in RPDR. Converted to POSIXct format.

time_rfv_end POSIXct, End date of the encounter, corresponds to *End_Date* in RPDR. Converted to POSIXct format.

rfv_provider string, Primary provider for the encounter, corresponds to *Provider* in RPDR. Punctuation marks are removed.

rfv_hosp string, Facility where the encounter occurred, corresponds to *Hospital* in RPDR.

rfv_clinic string, Specific department/location where the patient encounter took place, corresponds to *Clinic* in RPDR.

rfv_chief_complaint string, Description of the chief complaint/reason for visit, corresponds to *Chief_Complaint* in RPDR.

rfv_concept_id string, Epic identifier for the chief complaint/reason for visit, corresponds to *Concept_id* in RPDR.

rfv_comment string, Free-text comments regarding the chief complain/reason for visit, corresponds to *Comments* in RPDR.

rfv_enc_num string, Unique identifier of the record/visit. This values includes the source system, hospital, and a unique identifier within the source system, corresponds to *Encounter_number* in RPDR.

Examples

```
## Not run:
#Using defaults
d_rfv <- load_rfv(file = "test_Rfv.txt")

#Use sequential processing
d_rfv <- load_rfv(file = "test_Rfv.txt", nThread = 1)

#Use parallel processing and parse data in MRN_Type and MRN columns and keep all IDs
d_rfv <- load_rfv(file = "test_Rfv.txt", nThread = 20, mrn_type = TRUE, perc = 1)

## End(Not run)
```

```
pretty_mrn
```

Converts MRN integer to string compatible with RPDR.

Description

Adds or removes zeros from integers to comply with MRN code standards for given institution and adds institution prefix.

Usage

```
pretty_mrn(v, prefix = "MGH", sep = ":", id_length = "standard", nThread = 1)
```

Arguments

| | |
|------------------------|---|
| <code>v</code> | vector, integer or sting vector with MRNs. |
| <code>prefix</code> | string or vector, hospital ID from where the MRNs are from. Defaults to <i>MGH</i> . If a vector is provided then it must be the same length as <code>v</code> . This allows to potentially use different prefixes for different IDs using the same vector of values. |
| <code>sep</code> | string, divider between hospital ID and MRN. Defaults to <code>:</code> . |
| <code>id_length</code> | string, indicating whether to modify MRN length based-on required values <code>id_length = standard</code> , or to keep lengths as is <code>id_length = asis</code> . If <code>id_length = standard</code> then in case of <i>MGH</i> , <i>BWH</i> , <i>MCL</i> , <i>EMPI</i> and <i>PMRN</i> the length of the MRNs are corrected accordingly by adding zeros, or removing numeral from the beginning. In other cases the lengths are unchanged. Defaults to <i>standard</i> . |
| <code>nThread</code> | integer, number of threads to use by <i>dopar</i> for parallelization. If it is set to 1, then no parallel backends are created and the function is executed sequentially. On windows machines sockets are used, while on other operating systems fork parallelization is used. |

Value

vector, with characters formatted to specified lengths. If length of the ID does not match the required length, then leading zeros are added to the ID. If the ID is longer then the required length, then numerals from the beginning of the ID are cut off until it is the required length.

Examples

```
## Not run:
mrns <- sample(1e4:1e7, size = 10) #Simulate MRNs

#MGH format
pretty_mrn(v = mrns, prefix = "MGH")

#BWH format
pretty_mrn(v = mrns, prefix = "BWH")

#Multiple sources using space as a separator
pretty_mrn(v = mrns[1:3], prefix = c("MGH", "BWH", "EMPI"), sep = " ")

#Keeping the length of the IDs despite not adhering to the requirements
pretty_mrn(v = mrns, prefix = "EMPI", id_length = "asis")

## End(Not run)
```

Index

[all_ids_mi2b2](#), 3

[convert_dia](#), 3

[convert_enc](#), 5

[convert_lab](#), 6

[convert_med](#), 7

[convert_notes](#), 9

[convert_phy](#), 11

[convert_prc](#), 12

[convert_rfv](#), 14

[create_img_db](#), 15

[data_con](#), 17

[data_con_raw](#), 18

[data_dem](#), 20

[data_dem_raw](#), 21

[data_dia](#), 22

[data_dia_raw](#), 23

[data_enc](#), 24

[data_enc_raw](#), 26

[data_lab](#), 28

[data_lab_raw](#), 30

[data_med](#), 31

[data_med_raw](#), 32

[data_mrn](#), 34

[data_mrn_raw](#), 35

[data_rad](#), 36

[data_rad_raw](#), 37

[data_rdt](#), 38

[data_rdt_raw](#), 39

[find_exam](#), 40

[load_all](#), 42

[load_con](#), 44

[load_dem](#), 46

[load_dia](#), 48

[load_enc](#), 50

[load_lab](#), 53

[load_lno](#), 56

[load_med](#), 58

[load_mrn](#), 60

[load_notes](#), 62

[load_phy](#), 64

[load_prc](#), 66

[load_rdt](#), 68

[load_rfv](#), 70

[pretty_mrn](#), 72