

Package ‘pheatmap’

December 11, 2015

Type Package

Title Pretty Heatmaps

Version 1.0.8

Date 2015-07-02

Author Raivo Kolde

Maintainer Raivo Kolde <rkolde@gmail.com>

Depends R (>= 2.0)

Description Implementation of heatmaps that offers more control over dimensions and appearance.

Imports grid, RColorBrewer, scales, gtable, stats, grDevices, graphics

License GPL-2

LazyLoad yes

NeedsCompilation no

Repository CRAN

Date/Publication 2015-12-11 16:50:10

R topics documented:

pheatmap-package	1
pheatmap	2
Index	7

pheatmap-package *Pretty heatmaps*

Description

Implementation of heatmaps that offers more control over dimensions and appearance.

pheatmap

A function to draw clustered heatmaps.

Description

A function to draw clustered heatmaps where one has better control over some graphical parameters such as cell size, etc.

Usage

```
pheatmap(mat, color = colorRampPalette(rev(brewer.pal(n = 7, name =
  "RdYlBu")))(100), kmeans_k = NA, breaks = NA, border_color = "grey60",
  cellwidth = NA, cellheight = NA, scale = "none", cluster_rows = TRUE,
  cluster_cols = TRUE, clustering_distance_rows = "euclidean",
  clustering_distance_cols = "euclidean", clustering_method = "complete",
  clustering_callback = identity2, cutree_rows = NA, cutree_cols = NA,
  treeheight_row = ifelse((class(cluster_rows) == "hclust") || cluster_rows,
  50, 0), treeheight_col = ifelse((class(cluster_cols) == "hclust") ||
  cluster_cols, 50, 0), legend = TRUE, legend_breaks = NA,
  legend_labels = NA, annotation_row = NA, annotation_col = NA,
  annotation = NA, annotation_colors = NA, annotation_legend = TRUE,
  annotation_names_row = TRUE, annotation_names_col = TRUE,
  drop_levels = TRUE, show_rownames = T, show_colnames = T, main = NA,
  fontsize = 10, fontsize_row = fontsize, fontsize_col = fontsize,
  display_numbers = F, number_format = "%.2f", number_color = "grey30",
  fontsize_number = 0.8 * fontsize, gaps_row = NULL, gaps_col = NULL,
  labels_row = NULL, labels_col = NULL, filename = NA, width = NA,
  height = NA, silent = FALSE, ...)
```

Arguments

mat	numeric matrix of the values to be plotted.
color	vector of colors used in heatmap.
kmeans_k	the number of kmeans clusters to make, if we want to aggregate the rows before drawing heatmap. If NA then the rows are not aggregated.
breaks	a sequence of numbers that covers the range of values in mat and is one element longer than color vector. Used for mapping values to colors. Useful, if needed to map certain values to certain colors, to certain values. If value is NA then the breaks are calculated automatically.
border_color	color of cell borders on heatmap, use NA if no border should be drawn.
cellwidth	individual cell width in points. If left as NA, then the values depend on the size of plotting window.
cellheight	individual cell height in points. If left as NA, then the values depend on the size of plotting window.

scale	character indicating if the values should be centered and scaled in either the row direction or the column direction, or none. Corresponding values are "row", "column" and "none"
cluster_rows	boolean values determining if rows should be clustered or hclust object,
cluster_cols	boolean values determining if columns should be clustered or hclust object.
clustering_distance_rows	distance measure used in clustering rows. Possible values are "correlation" for Pearson correlation and all the distances supported by dist , such as "euclidean", etc. If the value is none of the above it is assumed that a distance matrix is provided.
clustering_distance_cols	distance measure used in clustering columns. Possible values the same as for clustering_distance_rows.
clustering_method	clustering method used. Accepts the same values as hclust .
clustering_callback	callback function to modify the clustering. Is called with two parameters: original hclust object and the matrix used for clustering. Must return a hclust object.
cutree_rows	number of clusters the rows are divided into, based on the hierarchical clustering (using cutree), if rows are not clustered, the argument is ignored
cutree_cols	similar to cutree_rows, but for columns
treeheight_row	the height of a tree for rows, if these are clustered. Default value 50 points.
treeheight_col	the height of a tree for columns, if these are clustered. Default value 50 points.
legend	logical to determine if legend should be drawn or not.
legend_breaks	vector of breakpoints for the legend.
legend_labels	vector of labels for the legend_breaks.
annotation_row	data frame that specifies the annotations shown on left side of the heatmap. Each row defines the features for a specific row. The rows in the data and in the annotation are matched using corresponding row names. Note that color schemes takes into account if variable is continuous or discrete.
annotation_col	similar to annotation_row, but for columns.
annotation	deprecated parameter that currently sets the annotation_col if it is missing
annotation_colors	list for specifying annotation_row and annotation_col track colors manually. It is possible to define the colors for only some of the features. Check examples for details.
annotation_legend	boolean value showing if the legend for annotation tracks should be drawn.
annotation_names_row	boolean value showing if the names for row annotation tracks should be drawn.
annotation_names_col	boolean value showing if the names for column annotation tracks should be drawn.

<code>drop_levels</code>	logical to determine if unused levels are also shown in the legend
<code>show_rownames</code>	boolean specifying if column names are to be shown.
<code>show_colnames</code>	boolean specifying if column names are to be shown.
<code>main</code>	the title of the plot
<code>fontsize</code>	base fontsize for the plot
<code>fontsize_row</code>	fontsize for rownames (Default: <code>fontsize</code>)
<code>fontsize_col</code>	fontsize for colnames (Default: <code>fontsize</code>)
<code>display_numbers</code>	logical determining if the numeric values are also printed to the cells. If this is a matrix (with same dimensions as original matrix), the contents of the matrix are shown instead of original values.
<code>number_format</code>	format strings (C printf style) of the numbers shown in cells. For example <code>"%.2f"</code> shows 2 decimal places and <code>"%.1e"</code> shows exponential notation (see more in sprintf).
<code>number_color</code>	color of the text
<code>fontsize_number</code>	fontsize of the numbers displayed in cells
<code>gaps_row</code>	vector of row indices that show where to put gaps into heatmap. Used only if the rows are not clustered. See <code>cutree_row</code> to see how to introduce gaps to clustered rows.
<code>gaps_col</code>	similar to <code>gaps_row</code> , but for columns.
<code>labels_row</code>	custom labels for rows that are used instead of rownames.
<code>labels_col</code>	similar to <code>labels_row</code> , but for columns.
<code>filename</code>	file path where to save the picture. Filetype is decided by the extension in the path. Currently following formats are supported: png, pdf, tiff, bmp, jpeg. Even if the plot does not fit into the plotting window, the file size is calculated so that the plot would fit there, unless specified otherwise.
<code>width</code>	manual option for determining the output file width in inches.
<code>height</code>	manual option for determining the output file height in inches.
<code>silent</code>	do not draw the plot (useful when using the gtable output)
<code>...</code>	graphical parameters for the text used in plot. Parameters passed to grid.text , see gpar .

Details

The function also allows to aggregate the rows using kmeans clustering. This is advisable if number of rows is so big that R cannot handle their hierarchical clustering anymore, roughly more than 1000. Instead of showing all the rows separately one can cluster the rows in advance and show only the cluster centers. The number of clusters can be tuned with parameter `kmeans_k`.

Value

Invisibly a list of components

- `tree_row` the clustering of rows as `hclust` object
- `tree_col` the clustering of columns as `hclust` object
- `kmeans` the kmeans clustering of rows if parameter `kmeans_k` was specified

Author(s)

Raivo Kolde <rkolde@gmail.com>

Examples

```
# Create test matrix
test = matrix(rnorm(200), 20, 10)
test[1:10, seq(1, 10, 2)] = test[1:10, seq(1, 10, 2)] + 3
test[11:20, seq(2, 10, 2)] = test[11:20, seq(2, 10, 2)] + 2
test[15:20, seq(2, 10, 2)] = test[15:20, seq(2, 10, 2)] + 4
colnames(test) = paste("Test", 1:10, sep = "")
rownames(test) = paste("Gene", 1:20, sep = "")

# Draw heatmaps
pheatmap(test)
pheatmap(test, kmeans_k = 2)
pheatmap(test, scale = "row", clustering_distance_rows = "correlation")
pheatmap(test, color = colorRampPalette(c("navy", "white", "firebrick3"))(50))
pheatmap(test, cluster_row = FALSE)
pheatmap(test, legend = FALSE)

# Show text within cells
pheatmap(test, display_numbers = TRUE)
pheatmap(test, display_numbers = TRUE, number_format = "%.1e")
pheatmap(test, display_numbers = matrix(ifelse(test > 5, "*", ""), nrow(test)))
pheatmap(test, cluster_row = FALSE, legend_breaks = -1:4, legend_labels = c("0",
"1e-4", "1e-3", "1e-2", "1e-1", "1"))

# Fix cell sizes and save to file with correct size
pheatmap(test, cellwidth = 15, cellheight = 12, main = "Example heatmap")
pheatmap(test, cellwidth = 15, cellheight = 12, fontsize = 8, filename = "test.pdf")

# Generate annotations for rows and columns
annotation_col = data.frame(
  CellType = factor(rep(c("CT1", "CT2"), 5)),
  Time = 1:5
)
rownames(annotation_col) = paste("Test", 1:10, sep = "")

annotation_row = data.frame(
  GeneClass = factor(rep(c("Path1", "Path2", "Path3"), c(10, 4, 6)))
)
rownames(annotation_row) = paste("Gene", 1:20, sep = "")
```

```

# Display row and color annotations
pheatmap(test, annotation_col = annotation_col)
pheatmap(test, annotation_col = annotation_col, annotation_legend = FALSE)
pheatmap(test, annotation_col = annotation_col, annotation_row = annotation_row)

# Specify colors
ann_colors = list(
  Time = c("white", "firebrick"),
  CellType = c(CT1 = "#1B9E77", CT2 = "#D95F02"),
  GeneClass = c(Path1 = "#7570B3", Path2 = "#E7298A", Path3 = "#66A61E")
)

pheatmap(test, annotation_col = annotation_col, annotation_colors = ann_colors, main = "Title")
pheatmap(test, annotation_col = annotation_col, annotation_row = annotation_row,
  annotation_colors = ann_colors)
pheatmap(test, annotation_col = annotation_col, annotation_colors = ann_colors[2])

# Gaps in heatmaps
pheatmap(test, annotation_col = annotation_col, cluster_rows = FALSE, gaps_row = c(10, 14))
pheatmap(test, annotation_col = annotation_col, cluster_rows = FALSE, gaps_row = c(10, 14),
  cutree_col = 2)

# Show custom strings as row/col names
labels_row = c("", "", "", "", "", "", "", "", "", "", "", "", "", "", "", "",
  "", "", "I110", "I115", "I11b")

pheatmap(test, annotation_col = annotation_col, labels_row = labels_row)

# Specifying clustering from distance matrix
drows = dist(test, method = "minkowski")
dcols = dist(t(test), method = "minkowski")
pheatmap(test, clustering_distance_rows = drows, clustering_distance_cols = dcols)

# Modify ordering of the clusters using clustering callback option
callback = function(hc, mat){
  sv = svd(t(mat))$v[,1]
  dend = reorder(as.dendrogram(hc), wts = sv)
  as.hclust(dend)
}

pheatmap(test, clustering_callback = callback)

## Not run:
# Same using dendsort package
library(dendsort)

callback = function(hc, ...){dendsort(hc)}
pheatmap(test, clustering_callback = callback)

## End(Not run)

```

Index

`dist`, [3](#)

`gpar`, [4](#)

`grid.text`, [4](#)

`hclust`, [3](#), [5](#)

`pheatmap`, [2](#)

`pheatmap-package`, [1](#)

`sprintf`, [4](#)