

# Package ‘prediction’

December 4, 2018

**Type** Package

**Title** Tidy, Type-Safe 'prediction()' Methods

**Description** A one-function package containing 'prediction()', a type-safe alternative to 'predict()' that always returns a data frame. The package currently supports common model types (e.g., ``lm``, ``glm``) from the 'stats' package, as well as numerous other model classes from other add-on packages. See the README or main package documentation page for a complete listing.

**License** MIT + file LICENSE

**Version** 0.3.6.1

**Date** 2018-05-22

**URL** <https://github.com/leeper/prediction>

**BugReports** <https://github.com/leeper/prediction/issues>

**Imports** utils, stats, data.table

**Suggests** datasets, methods, testthat

**Enhances** AER, aod, betareg, biglm, brglm, caret, crch, e1071, earth, ff, ffbase, gam (>= 1.15), gee, glmnet, glmx, kernlab, lme4, MASS, mclogit, mda, mlogit, mnlogit, MNP, nlme, nnet, ordinal, plm, pscl, quantreg, rpart, sampleSelection, speedglm, survey (>= 3.31-5), survival, truncreg, VGAM

**ByteCompile** true

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Author** Thomas J. Leeper [aut, cre] (<<https://orcid.org/0000-0003-4097-6326>>),  
Carl Ganz [ctb]

**Maintainer** Thomas J. Leeper <[thosjleeper@gmail.com](mailto:thosjleeper@gmail.com)>

**Repository** CRAN

**Date/Publication** 2018-12-04 08:48:44 UTC

## R topics documented:

prediction-package	2
build_datalist	10
find_data	11
mean_or_mode	13
seq_range	14

<b>Index</b>	<b>15</b>
--------------	-----------

---

prediction-package      *Extract Predictions from a Model Object*

---

### Description

Extract predicted values via `predict` from a model object, conditional on data, and return a data frame.

### Usage

```
prediction(model, ...)

## Default S3 method:
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = "response", calculate_se = TRUE, ...)

## S3 method for class 'Arima'
prediction(model, calculate_se = TRUE, ...)

## S3 method for class 'Gam'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link", "terms"), calculate_se = TRUE,
  ...)

## S3 method for class 'ar'
prediction(model, data, at = NULL, calculate_se = TRUE, ...)

## S3 method for class 'arima0'
prediction(model, data, at = NULL, calculate_se = TRUE,
  ...)

## S3 method for class 'betareg'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link", "precision", "variance",
  "quantile"), calculate_se = FALSE, ...)

## S3 method for class 'bigLm'
prediction(model, data = NULL, calculate_se = FALSE, ...)
```

```
## S3 method for class 'biglm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = "response", calculate_se = TRUE, ...)

## S3 method for class 'bruto'
prediction(model, data = NULL, at = NULL, type = "fitted",
  calculate_se = FALSE, ...)

## S3 method for class 'clm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = TRUE, category, ...)

## S3 method for class 'coxph'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("risk", "expected", "lp"), calculate_se = TRUE, ...)

## S3 method for class 'crch'
prediction(model, data = find_data(model), at = NULL,
  type = c("response", "location", "scale", "quantile"),
  calculate_se = FALSE, ...)

## S3 method for class 'earth'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link"), calculate_se = TRUE, category,
  ...)

## S3 method for class 'fda'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'gausspr'
prediction(model, data, at = NULL, type = NULL,
  calculate_se = TRUE, category, ...)

## S3 method for class 'gee'
prediction(model, calculate_se = FALSE, ...)

## S3 method for class 'glimML'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link"), calculate_se = TRUE, ...)

## S3 method for class 'glimQL'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link"), calculate_se = TRUE, ...)

## S3 method for class 'glm'
prediction(model, data = find_data(model, parent.frame()),
```

```
    at = NULL, type = c("response", "link"), calculate_se = TRUE, ...)  
  
## S3 method for class 'glmnet'  
prediction(model, data, lambda = model[["lambda"]][1L],  
  at = NULL, type = c("response", "link"), calculate_se = FALSE, ...)  
  
## S3 method for class 'glmX'  
prediction(model, data = find_data(model, parent.frame()),  
  at = NULL, type = c("response", "link"), calculate_se = FALSE, ...)  
  
## S3 method for class 'gls'  
prediction(model, data = find_data(model), at = NULL,  
  calculate_se = FALSE, ...)  
  
## S3 method for class 'hetglm'  
prediction(model, data = find_data(model, parent.frame()),  
  at = NULL, type = c("response", "link", "scale"), calculate_se = FALSE,  
  ...)  
  
## S3 method for class 'hurdle'  
prediction(model, data = find_data(model, parent.frame()),  
  at = NULL, type = c("response", "count", "prob", "zero"),  
  calculate_se = FALSE, ...)  
  
## S3 method for class 'hxlR'  
prediction(model, data = find_data(model), at = NULL,  
  type = c("class", "probability", "cumprob", "location", "scale"),  
  calculate_se = FALSE, ...)  
  
## S3 method for class 'ivreg'  
prediction(model, data = find_data(model, parent.frame()),  
  at = NULL, calculate_se = FALSE, ...)  
  
## S3 method for class 'knnreg'  
prediction(model, data, at = NULL, calculate_se = FALSE,  
  ...)  
  
## S3 method for class 'kqr'  
prediction(model, data, at = NULL, calculate_se = FALSE, ...)  
  
## S3 method for class 'ksvm'  
prediction(model, data, at = NULL, type = NULL,  
  calculate_se = TRUE, category, ...)  
  
## S3 method for class 'lm'  
prediction(model, data = find_data(model, parent.frame()),  
  at = NULL, type = "response", calculate_se = TRUE, ...)
```

```
## S3 method for class 'lme'
prediction(model, data = find_data(model), at = NULL,
  calculate_se = FALSE, ...)

## S3 method for class 'loess'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = "response", calculate_se = TRUE, ...)

## S3 method for class 'lqs'
prediction(model, data = find_data(model), at = NULL,
  calculate_se = FALSE, ...)

## S3 method for class 'mars'
prediction(model, data = NULL, at = NULL, type = "fitted",
  calculate_se = FALSE, ...)

## S3 method for class 'mca'
prediction(model, data = find_data(model), at = NULL,
  calculate_se = FALSE, ...)

## S3 method for class 'mclogit'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link"), calculate_se = TRUE, ...)

## S3 method for class 'merMod'
prediction(model, data = find_data(model), at = NULL,
  type = c("response", "link"), re.form = NULL, calculate_se = FALSE, ...)

## S3 method for class 'mnlogit'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'mnp'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'multinom'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'nls'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'nnet'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)
```

```
## S3 method for class 'plm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'polr'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'polyreg'
prediction(model, data = NULL, at = NULL,
  type = "fitted", calculate_se = FALSE, ...)

## S3 method for class 'ppr'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'princomp'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'rlm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = "response", calculate_se = TRUE, ...)

## S3 method for class 'rpart'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = NULL, calculate_se = FALSE, category, ...)

## S3 method for class 'rq'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = TRUE, ...)

## S3 method for class 'selection'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = "response", calculate_se = FALSE, ...)

## S3 method for class 'speedglm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link"), calculate_se = FALSE, ...)

## S3 method for class 'speedlm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, calculate_se = FALSE, ...)

## S3 method for class 'survreg'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "lp", "quantile", "uquantile"),
  calculate_se = TRUE, ...)
```

```

## S3 method for class 'svm'
prediction(model, data = NULL, at = NULL,
  calculate_se = TRUE, category, ...)

## S3 method for class 'svyglm'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "link"), calculate_se = TRUE, ...)

## S3 method for class 'train'
prediction(model, data = find_data(model), at = NULL,
  type = c("raw", "prob"), ...)

## S3 method for class 'truncreg'
prediction(model, data, at = NULL, calculate_se = FALSE,
  ...)

## S3 method for class 'zeroinfl'
prediction(model, data = find_data(model, parent.frame()),
  at = NULL, type = c("response", "count", "prob", "zero"),
  calculate_se = FALSE, ...)

```

## Arguments

model	A model object, perhaps returned by <code>lm</code> or <code>glm</code> .
...	Additional arguments passed to <code>predict</code> methods.
data	A <code>data.frame</code> over which to calculate marginal effects. If missing, <code>find_data</code> is used to specify the data frame.
at	A list of one or more named vectors, specifically values at which to calculate the predictions. These are used to modify the value of <code>data</code> (see <code>build_datalist</code> for details on use).
type	A character string indicating the type of marginal effects to estimate. Mostly relevant for non-linear models, where the reasonable options are “response” (the default) or “link” (i.e., on the scale of the linear predictor in a GLM). For models of class “polr” (from <code>polr</code> ), possible values are “class” or “probs”; both are returned.
calculate_se	A logical indicating whether to calculate standard errors (if possible). The output will always contain a “calculate_se” column regardless of this value; this only controls the calculation of standard errors. Setting it to <code>FALSE</code> may improve speed.
category	For multi-level or multi-category outcome models (e.g., ordered probit, multinomial logit, etc.), a value specifying which of the outcome levels should be used for the “fitted” column. If missing, some default is chosen automatically.
lambda	For models of class “glmnet”, a value of the penalty parameter at which predictions are required.
re.form	An argument passed forward to <code>predict.merMod</code> .

## Details

This function is simply a wrapper around `predict` that returns a data frame containing the value of data and the predicted values with respect to all variables specified in data.

Methods are currently implemented for the following object classes:

- “lm”, see `lm`
- “glm”, see `glm`, `glm.nb`, `glmX`, `hetglm`, `brglm`
- “ar”, see `ar`
- “Arima”, see `arima`
- “arima0”, see `arima0`
- “bigglm”, see `bigglm` (including “ffdf”-backed models provided by `bigglm.ffdf`)
- “betareg”, see `betareg`
- “bruto”, see `bruto`
- “clm”, see `clm`
- “coxph”, see `coxph`
- “crch”, see `crch`
- “earth”, see `earth`
- “fda”, see `fda`
- “Gam”, see `gam`
- “gausspr”, see `gausspr`
- “gee”, see `gee`
- “glmnet”, see `glmnet`
- “gls”, see `gls`
- “glimML”, see `betabin`, `negbin`
- “glimQL”, see `quasibin`, `quasipois`
- “hurdle”, see `hurdle`
- “hxl”, see `hxl`
- “ivreg”, see `ivreg`
- “knnreg”, see `knnreg`
- “kqr”, see `kqr`
- “ksvm”, see `ksvm`
- “lda”, see `lda`
- “lme”, see `lme`
- “loess”, see `loess`
- “lqs”, see `lqs`
- “mars”, see `mars`
- “mca”, see `mca`
- “mclogit”, see `mclogit`



- “mda”, see [mda](#)
- “merMod”, see [lmer](#), [glmer](#)
- “mnlogit”, see [mnlogit](#)
- “mnp”, see [mnp](#)
- “naiveBayes”, see [naiveBayes](#)
- “nlme”, see [nlme](#)
- “nls”, see [nls](#)
- “nnet”, see [nnet](#)
- “plm”, see [plm](#)
- “polr”, see [polr](#)
- “polyreg”, see [polyreg](#)
- “ppr”, see [ppr](#)
- “princomp”, see [princomp](#)
- “qda”, see [qda](#)
- “rlm”, see [rlm](#)
- “rpart”, see [rpart](#)
- “rq”, see [rq](#)
- “selection”, see [selection](#)
- “speedglm”, see [speedglm](#)
- “speedlm”, see [speedlm](#)
- “survreg”, see [survreg](#)
- “svm”, see [svm](#)
- “svyglm”, see [svyglm](#)
- “tobit”, see [tobit](#)
- “train”, see [train](#)
- “truncreg”, see [truncreg](#)
- “zeroinfl”, see [zeroinfl](#)

### Value

A data frame with class “prediction” that has a number of rows equal to number of rows in data, or a multiple thereof, if `!is.null(at)`. The return value contains data (possibly modified by `at` using [build\\_datalist](#)), plus a column containing fitted/predicted values (“fitted”) and a column containing the standard errors thereof (“calculate\_se”). Additional columns may be reported depending on the object class.

### See Also

[find\\_data](#), [build\\_datalist](#), [mean\\_or\\_mode](#), [seq\\_range](#)

**Examples**

```

require("datasets")
x <- lm(Petal.Width ~ Sepal.Length * Sepal.Width * Species, data = iris)
# prediction for every case
prediction(x)

# prediction for first case
prediction(x, iris[1,])

# basic use of 'at' argument
prediction(x, at = list(Species = c("setosa", "virginica")))

# prediction at means/modes of input variables
prediction(x, at = lapply(iris, mean_or_mode))

# prediction with multi-category outcome
## Not run:
library("mlogit")
data("Fishing", package = "mlogit")
Fish <- mlogit.data(Fishing, varying = c(2:9), shape = "wide", choice = "mode")
mod <- mlogit(mode ~ price + catch, data = Fish)
prediction(mod)
prediction(mod, category = 3)

## End(Not run)

```

---

build\_datalist

*Build list of data.frames*


---

**Description**

Construct a list of data.frames based upon an input data.frame and a list of one or more at values

**Usage**

```
build_datalist(data, at = NULL, as.data.frame = FALSE, ...)
```

**Arguments**

data	A data.frame containing the original data.
at	A list of one or more named vectors of values, which will be used to specify values of variables in data. All possible combinations are generated. Alternatively, this can be a data frame of combination levels if only a subset of combinations are desired. See examples.
as.data.frame	A logical indicating whether to return a single stacked data frame rather than a list of data frames
...	Ignored.

**Value**

A list of data.frames, unless `as.data.frame = TRUE` in which case a single, stacked data frame is returned.

**Author(s)**

Thomas J. Leeper

**See Also**

[find\\_data](#), [mean\\_or\\_mode](#), [seq\\_range](#)

**Examples**

```
# basic examples
require("datasets")
build_datalist(head(mtcars), at = list(cyl = c(4, 6)))

str(build_datalist(head(mtcars), at = list(cyl = c(4,6), wt = c(2.75,3,3.25))), 1)

str(build_datalist(head(mtcars), at = data.frame(cyl = c(4,4), wt = c(2.75,3))))
```

---

find\_data

*Extract data from a model object*

---

**Description**

Attempt to reconstruct the data used to create a model object

**Usage**

```
find_data(model, ...)

## Default S3 method:
find_data(model, env = parent.frame(), ...)

## S3 method for class 'data.frame'
find_data(model, ...)

## S3 method for class 'crch'
find_data(model, env = parent.frame(), ...)

## S3 method for class 'glmML'
find_data(model, ...)

## S3 method for class 'glm'
find_data(model, env = parent.frame(), ...)
```

```
## S3 method for class 'hxr'  
find_data(model, env = parent.frame(), ...)  
  
## S3 method for class 'lm'  
find_data(model, env = parent.frame(), ...)  
  
## S3 method for class 'mca'  
find_data(model, env = parent.frame(), ...)  
  
## S3 method for class 'merMod'  
find_data(model, env = parent.frame(), ...)  
  
## S3 method for class 'svyglm'  
find_data(model, ...)  
  
## S3 method for class 'train'  
find_data(model, ...)  
  
## S3 method for class 'vgam'  
find_data(model, env = parent.frame(), ...)  
  
## S3 method for class 'vglm'  
find_data(model, env = parent.frame(), ...)
```

### Arguments

model	The model object.
...	Additional arguments passed to methods.
env	An environment in which to look for the data argument to the modelling call.

### Details

This is a convenience function and, as such, carries no guarantees. To behave well, it typically requires that a model object be specified using a formula interface and an explicit data argument. Models that can be specified using variables from the `.GlobalEnv` or with a non-formula interface (e.g., a matrix of data) will tend to generate errors. `find_data` is an S3 generic so it is possible to expand it with new methods.

### Value

A data frame containing the original data used in a modelling call, modified according to the original model's 'subset' and 'na.action' arguments, if appropriate.

### See Also

[prediction](#), [build\\_datalist](#), [mean\\_or\\_mode](#), [seq\\_range](#)

**Examples**

```
require("datasets")
x <- lm(mpg ~ cyl * hp + wt, data = head(mtcars))
find_data(x)
```

---

mean\_or\_mode

*Class-dependent variable aggregation*

---

**Description**

Summarize a vector/variable into a single number, either a mean (median) for numeric vectors or the mode for categorical (character, factor, ordered, or logical) vectors. Useful for aggregation.

**Usage**

```
mean_or_mode(x)

## Default S3 method:
mean_or_mode(x)

## S3 method for class 'numeric'
mean_or_mode(x)

## S3 method for class 'data.frame'
mean_or_mode(x)

median_or_mode(x)

## Default S3 method:
median_or_mode(x)

## S3 method for class 'numeric'
median_or_mode(x)

## S3 method for class 'data.frame'
median_or_mode(x)
```

**Arguments**

x                    A vector.

**Value**

A numeric or factor vector of length 1.

**See Also**

[prediction](#), [build\\_datalist](#), [seq\\_range](#)

**Examples**

```
require("datasets")
# mean for numerics
mean_or_mode(iris)
mean_or_mode(iris[["Sepal.Length"]])
mean_or_mode(iris[["Species"]])

# median for numerics
median_or_mode(iris)
```

---

seq\_range

*Create a sequence over the range of a vector*

---

**Description**

Define a sequence of evenly spaced values from the minimum to the maximum of a vector

**Usage**

```
seq_range(x, n = 2)
```

**Arguments**

x	A numeric vector
n	An integer specifying the length of sequence (i.e., number of points across the range of x)

**Value**

A vector of length n.

**See Also**

[mean\\_or\\_mode](#), [build\\_datalist](#)

**Examples**

```
identical(range(1:5), seq_range(1:5, n = 2))
seq_range(1:5, n = 3)
```

# Index

- \*Topic **data**
  - build\_datalist, 10
- \*Topic **manip**
  - build\_datalist, 10
- \*Topic **models**
  - prediction-package, 2
- ar, 8
- arima, 8
- arima0, 8
  
- betabin, 8
- betareg, 8
- bigglm, 8
- bigglm.ffdf, 8
- brglm, 8
- bruto, 8
- build\_datalist, 7, 9, 10, 12, 14
  
- clm, 8
- coxph, 8
- crch, 8
  
- earth, 8
  
- fda, 8
- find\_data, 7, 9, 11, 11
  
- gam, 8
- gausspr, 8
- gee, 8
- glm, 7, 8
- glm.nb, 8
- glmer, 9
- glmnet, 8
- glmx, 8
- gls, 8
  
- hetglm, 8
- hurdle, 8
- hxlr, 8
  
- ivreg, 8
  
- knnreg, 8
- kqr, 8
- ksvm, 8
  
- lda, 8
- lm, 7, 8
- lme, 8
- lmer, 9
- loess, 8
- lqs, 8
  
- mars, 8
- mca, 8
- mclogit, 8
- mda, 9
- mean\_or\_mode, 9, 11, 12, 13, 14
- median\_or\_mode (mean\_or\_mode), 13
- mnlogit, 9
- mnp, 9
  
- naiveBayes, 9
- negbin, 8
- nlme, 9
- nls, 9
- nnet, 9
  
- plm, 9
- polr, 7, 9
- polyreg, 9
- ppr, 9
- predict, 2, 7, 8
- predict.merMod, 7
- prediction, 12, 14
- prediction (prediction-package), 2
- prediction-package, 2
- prediction.ar (prediction-package), 2
- prediction.Arima (prediction-package), 2
- prediction.arima0 (prediction-package), 2

- prediction.betareg
  - (prediction-package), 2
- prediction.bigLm (prediction-package), 2
- prediction.biglm (prediction-package), 2
- prediction.bruto (prediction-package), 2
- prediction.clm (prediction-package), 2
- prediction.coxph (prediction-package), 2
- prediction.crch (prediction-package), 2
- prediction.default
  - (prediction-package), 2
- prediction.earth (prediction-package), 2
- prediction.fda (prediction-package), 2
- prediction.Gam (prediction-package), 2
- prediction.gausspr
  - (prediction-package), 2
- prediction.gee (prediction-package), 2
- prediction.glimML (prediction-package), 2
- prediction.glimQL (prediction-package), 2
- prediction.glm (prediction-package), 2
- prediction.glmnet (prediction-package), 2
- prediction.glmx (prediction-package), 2
- prediction.gls (prediction-package), 2
- prediction.hetglm (prediction-package), 2
- prediction.hurdle (prediction-package), 2
- prediction.hxlr (prediction-package), 2
- prediction.ivreg (prediction-package), 2
- prediction.knnreg (prediction-package), 2
- prediction.kqr (prediction-package), 2
- prediction.ksvm (prediction-package), 2
- prediction.lm (prediction-package), 2
- prediction.lme (prediction-package), 2
- prediction.loess (prediction-package), 2
- prediction.lqs (prediction-package), 2
- prediction.mars (prediction-package), 2
- prediction.mca (prediction-package), 2
- prediction.mclogit
  - (prediction-package), 2
- prediction.merMod (prediction-package), 2
- prediction.mnlogit
  - (prediction-package), 2
- prediction.mnp (prediction-package), 2
- prediction.multinom
  - (prediction-package), 2
- prediction.nls (prediction-package), 2
- prediction.nnet (prediction-package), 2
- prediction.plm (prediction-package), 2
- prediction.polr (prediction-package), 2
- prediction.polyreg
  - (prediction-package), 2
- prediction.ppr (prediction-package), 2
- prediction.princomp
  - (prediction-package), 2
- prediction.rlm (prediction-package), 2
- prediction.rpart (prediction-package), 2
- prediction.rq (prediction-package), 2
- prediction.selection
  - (prediction-package), 2
- prediction.speedglm
  - (prediction-package), 2
- prediction.speedlm
  - (prediction-package), 2
- prediction.survreg
  - (prediction-package), 2
- prediction.svm (prediction-package), 2
- prediction.svyglm (prediction-package), 2
- prediction.train (prediction-package), 2
- prediction.truncreg
  - (prediction-package), 2
- prediction.zeroinfl
  - (prediction-package), 2
- princomp, 9
- qda, 9
- quasibin, 8
- quasipois, 8
- rlm, 9
- rpart, 9
- rq, 9
- selection, 9
- seq\_range, 9, 11, 12, 14, 14
- speedglm, 9
- speedlm, 9
- survreg, 9
- svm, 9
- svyglm, 9
- tobit, 9



train, 9  
truncreg, 9  
zeroinfl, 9