

# Package ‘quantmod’

April 19, 2017

**Type** Package

**Title** Quantitative Financial Modelling Framework

**Version** 0.4-8

**Date** 2017-04-18

**Depends** xts(>= 0.9-0), zoo, TTR(>= 0.2), methods

**Suggests** DBI,RMySQL,RSQLite,timeSeries,XML,downloader,jsonlite(>= 1.1)

**Description** Specify, build, trade, and analyse quantitative financial trading strategies.

**LazyLoad** yes

**License** GPL-3

**URL** <http://www.quantmod.com> <https://github.com/joshualrich/quantmod>

**BugReports** <https://github.com/joshualrich/quantmod/issues>

**NeedsCompilation** yes

**Author** Jeffrey A. Ryan [aut, cph],  
Joshua M. Ulrich [cre, ctb],  
Wouter Thielen [ctb]

**Maintainer** Joshua M. Ulrich <josh.m.ulrich@gmail.com>

**Repository** CRAN

**Date/Publication** 2017-04-19 04:21:46 UTC

## R topics documented:

|                            |    |
|----------------------------|----|
| quantmod-package . . . . . | 3  |
| addADX . . . . .           | 4  |
| addBBands . . . . .        | 5  |
| addCCI . . . . .           | 6  |
| addExpiry . . . . .        | 7  |
| addMA . . . . .            | 8  |
| addMACD . . . . .          | 9  |
| addROC . . . . .           | 10 |
| addRSI . . . . .           | 11 |

|                      |    |
|----------------------|----|
| addSAR               | 12 |
| addSMI               | 13 |
| addVo                | 14 |
| addWPR               | 15 |
| adjustOHLC           | 16 |
| attachSymbols        | 17 |
| buildData            | 19 |
| buildModel           | 21 |
| chartSeries          | 22 |
| chartTheme           | 25 |
| chart_Series         | 27 |
| chob-class           | 28 |
| chobTA-class         | 29 |
| create.binding       | 30 |
| Defaults             | 31 |
| Delt                 | 33 |
| findPeaks            | 34 |
| fittedModel          | 35 |
| getDividends         | 37 |
| getFinancials        | 39 |
| getFX                | 40 |
| getMetals            | 42 |
| getModelData         | 43 |
| getOptionChain       | 44 |
| getQuote             | 45 |
| getSplits            | 47 |
| getSymbols           | 48 |
| getSymbols.csv       | 52 |
| getSymbols.FRED      | 53 |
| getSymbols.google    | 55 |
| getSymbols.MySQL     | 57 |
| getSymbols.oanda     | 59 |
| getSymbols.rda       | 61 |
| getSymbols.SQLite    | 62 |
| getSymbols.yahoo     | 64 |
| getSymbols.yahooj    | 66 |
| has.OHLC             | 67 |
| internal-quantmod    | 69 |
| is.quantmod          | 69 |
| Lag                  | 70 |
| modelData            | 71 |
| modelSignal          | 72 |
| newTA                | 73 |
| Next                 | 76 |
| OHLC.Transformations | 78 |
| options.expiry       | 80 |
| periodReturn         | 81 |
| quantmod-class       | 83 |

|                           |    |
|---------------------------|----|
| quantmod.OHLC . . . . .   | 84 |
| saveChart . . . . .       | 85 |
| setSymbolLookup . . . . . | 86 |
| setTA . . . . .           | 88 |
| specifyModel . . . . .    | 89 |
| TA . . . . .              | 91 |
| tradeModel . . . . .      | 93 |
| zoomChart . . . . .       | 94 |

**Index 96**

---

quantmod-package            *Quantitative Financial Modelling Framework*

---

**Description**

Quantitative Financial Modelling and Trading Framework for R

**Details**

Package:     quantmod  
Type:        Package  
Version:     0.4-8  
Date:        2017-04-18  
Depends:     xts(>= 0.9-0),zoo,TTR(>= 0.2),methods  
Suggests:    DBI,RMySQL,RSQLite,timeSeries,XML,downloader,jsonlite(>= 1.1)  
LazyLoad:    yes  
License:     GPL-3  
URL:         http://www.quantmod.com  
URL:         https://github.com/joshuaulrich/quantmod

The quantmod package for R is designed to assist the quantitative trader in the development, testing, and deployment of statistically based trading models.

*What quantmod IS*

A rapid prototyping environment, with comprehensive tools for data management and visualization. where quant traders can quickly and cleanly explore and build trading models.

*What quantmod is NOT*

A replacement for anything statistical. It has no 'new' modelling routines or analysis tool to speak of. It does now offer charting not currently available elsewhere in R, but most everything else is more of a wrapper to what you already know and love about the language and packages you currently use.

quantmod makes modelling easier by removing the repetitive workflow issues surrounding data management, modelling interfaces, and performance analysis.

**Author(s)**

Jeffrey A. Ryan  
Maintainer: Joshua M. Ulrich <josh.m.ulrich@gmail.com>

---

addADX                      *Add Directional Movement Index*

---

**Description**

Add Directional Movement Index

**Usage**

```
addADX(n = 14, maType="EMA", wilder=TRUE)
```

**Arguments**

|        |                                   |
|--------|-----------------------------------|
| n      | periods to use for DX calculation |
| maType | moving average type               |
| wilder | should Welles Wilder EMA be used? |

**Details**

See 'ADX' in **TTR** for specific details and references.

**Value**

An ADX indicator will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see ADX in **TTR** written by Josh Ulrich

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addADX()  
  
## End(Not run)
```

---

addBBands                      *Add Bollinger Bands to Chart*

---

### Description

Add Bollinger Bands to current chart.

### Usage

```
addBBands(n = 20, sd = 2, maType = "SMA", draw = 'bands', on = -1)
```

### Arguments

|        |   |
|--------|---|
| n      | number of moving average periods            |
| maType | type of moving average to be used           |
| sd     | number of standard deviations               |
| draw   | indicator to draw: bands, percent, or width |
| on     | which figure area of chart to apply to      |

### Details

The primary addition to this function call over the **TTR** version is in the draw argument. 'bands' will draw standard Bollinger Bands, 'percent' will draw Bollinger %b and 'width' will draw Bolinger Bands Width. The last two will be drawn in new figure regions.

See bollingerBands in **TTR** for specific details as to implementation and references.

### Value

Bollinger Bands will be drawn, or scheduled to be drawn, on the current chart. If draw is either percent or width a new figure will be added to the current TA figures charted.

A chobTA object will be returned silently.

### Author(s)

Jeffrey A. Ryan

### References

See bollingerBands in **TTR** written by Josh Ulrich

### See Also

[addTA](#)

**Examples**

```
## Not run:  
addBBands()  
  
## End(Not run)
```

---

|        |                                    |
|--------|------------------------------------|
| addCCI | <i>Add Commodity Channel Index</i> |
|--------|------------------------------------|

---

**Description**

Add Commodity Channel Index

**Usage**

```
addCCI(n = 20, maType="SMA", c=0.015)
```

**Arguments**

|        |  |
|--------|--|
| n      | periods to use for DX calculation        |
| maType | moving average type                      |
| c      | Constant to apply to the mean deviation. |

**Details**

See 'CCI' in **TTR** for specific details and references.

**Value**

An CCI indicator will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see CCI in **TTR** written by Josh Ulrich

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addCCI()  
  
## End(Not run)
```

---

|           |  |
|-----------|--|
| addExpiry | <i>Add Contract Expiration Bars to Chart</i> |
|-----------|--|

---

**Description**

Apply options or futures expiration vertical bars to current chart.

**Usage**

```
addExpiry(type = "options", lty = "dotted")
```

**Arguments**

|      |                               |
|------|-------------------------------|
| type | options or futures expiration |
| lty  | type of lines to draw         |

**Details**

See options.expiry and futures.expiry in **quantmod** for details and limitations.

**Value**

Expiration lines will be drawn at appropriate dates. A chibTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addExpiry()  
  
## End(Not run)
```

---

 addMA

---

*Add Moving Average to Chart*


---

### Description

Add one or more moving averages to a chart.

### Usage

```
addSMA(n = 10, on = 1, with.col = C1, overlay = TRUE, col = "brown")
```

```
addEMA(n = 10, wilder = FALSE, ratio=NULL, on = 1,
       with.col = C1, overlay = TRUE, col = "blue")
```

```
addWMA(n = 10, wts=1:n, on = 1, with.col = C1, overlay = TRUE, col = "green")
```

```
addDEMA(n = 10, on = 1, with.col = C1, overlay = TRUE, col = "pink")
```

```
addEVWMA(n = 10, on = 1, with.col = C1, overlay = TRUE, col = "yellow")
```

```
addZLEMA(n = 10, ratio=NULL, on = 1, with.col = C1, overlay = TRUE, col = "red")
```

### Arguments

|          |  |
|----------|--|
| n        | periods to average over                |
| wilder   | logical; use wilder?                   |
| wts      | a vector of weights                    |
| ratio    | a smoothing/decay ratio                |
| on       | apply to which figure (see below)      |
| with.col | using which column of data (see below) |
| overlay  | draw as overlay                        |
| col      | color of MA                            |

### Details

see the appropriate base MA functions in **TTR** for more details and references.

### Value

A moving average indicator will be draw on the current chart. A chobTA object will be returned silently.

### Author(s)

Jeffrey A. Ryan



**References**

see MovingAverages in **TTR** written by Josh Ulrich

**See Also**

[addTA](#)

**Examples**

```
## Not run:
addSMA()
addEMA()
addWMA()
addDEMA()
addEVWMA()
addZLEMA()

## End(Not run)
```

---

addMACD

*Add Moving Average Convergence Divergence to Chart*

---

**Description**

Add Moving Average Convergence Divergence indicator to chart.

**Usage**

```
addMACD(fast = 12, slow = 26, signal = 9, type = "EMA", histogram = TRUE, col)
```

**Arguments**

|           |   |
|-----------|---|
| fast      | fast period   |
| slow      | slow period   |
| signal    | signal period                                       |
| type      | type of MA to use. Single values will be replicated |
| histogram | include histogram                                   |
| col       | colors to use for lines (optional)                  |

**Details**

See and 'MACD' in **TTR** for specific details and implementation references.

**Value**

A MACD indicator will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see MACD in **TTR** written by Josh Ulrich

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addMACD()  
  
## End(Not run)
```

---

addROC

*Add Rate Of Change to Chart*

---

**Description**

Add Rate Of Change indicator to chart.

**Usage**

```
addROC(n = 1, type = c("discrete", "continuous"), col = "red")
```

**Arguments**

|      |                       |
|------|-----------------------|
| n    | periods               |
| type | compounding type      |
| col  | line color (optional) |

**Details**

See 'ROC' in **TTR** for specific details and references.

**Value**

A ROC indicator will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see ROC in **TTR** written by Josh Ulrich

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addROC()  
  
## End(Not run)
```

---

addRSI

*Add Relative Strength Index to Chart*

---

**Description**

Add a Relative Strength Index indicator to chart.

**Usage**

```
addRSI(n = 14, maType = "EMA", wilder = TRUE)
```

**Arguments**

|        |                      |
|--------|----------------------|
| n      | periods              |
| maType | type of MA to use    |
| wilder | use wilder (see EMA) |

**Details**

see 'RSI' in **TTR** for specific details and references.

**Value**

An RSI indicator will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see RSI in **TTR** written by Josh Ulrich

**See Also**[addTA](#)**Examples**

```
## Not run:  
addRSI()  
  
## End(Not run)
```

---

|        |   |
|--------|---|
| addSAR | <i>Add Parabolic Stop and Reversal to Chart</i> |
|--------|---|

---

**Description**

Add Parabolic Stop and Reversal indicator overlay to chart.

**Usage**

```
addSAR(accel = c(0.02, 0.2), col = "blue")
```

**Arguments**

|       |                                |
|-------|--------------------------------|
| accel | Acceleration factors - see SAR |
| col   | color of points (optional)     |

**Details**

see 'SAR' in **TTR** for specific details and references.

**Value**

A SAR overlay will be drawn on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see SAR in **TTR** written by Josh Ulrich

**See Also**[addTA](#)

**Examples**

```
## Not run:  
addSAR()  
  
## End(Not run)
```

---

`addSMI`*Add Stochastic Momentum Indicator to Chart*

---

**Description**

Add Stochastic Momentum Indicator to chart.

**Usage**

```
addSMI(n=13,slow=25,fast=2,signal=9,ma.type="EMA")
```

**Arguments**

|         |                                       |
|---------|---------------------------------------|
| n       | periods                               |
| slow    | slow                                  |
| fast    | fast                                  |
| signal  | signal                                |
| ma.type | MA type to use, recycled as necessary |

**Details**

see 'SMI in **TTR** for specifics and references.

**Value**

An SMI indicator will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see SMI in **TTR** written by Josh Ulrich

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addSMI()  
  
## End(Not run)
```

---

|       |                            |
|-------|----------------------------|
| addVo | <i>Add Volume to Chart</i> |
|-------|----------------------------|

---

**Description**

Add Volume of a series, if available, to the current chart. This is the default TA argument for all charting functions.

**Usage**

```
addVo(log.scale=FALSE)
```

**Arguments**

log.scale      use log-scale for volume

**Details**

Add volume bars to current chart if data object contains appropriate volume column.  
log.scale will transform the series via standard R graphics mechanisms.

**Value**

Volume will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addVo()  
  
## End(Not run)
```

---

`addWPR`*Add William's Percent R to Chart*

---

**Description**

Add William's percent R indicator to the current chart.

**Usage**

```
addWPR(n = 14)
```

**Arguments**

n                    periods

**Details**

see 'WPR' in **TTR** for details and references.

**Value**

A William's percent R indicator will be draw in a new window on the current chart. A chobTA object will be returned silently.

**Author(s)**

Jeffrey A. Ryan

**References**

see 'WPR' in **TTR** written by Josh Ulrich

**See Also**

[addTA](#)

**Examples**

```
## Not run:  
addWPR()  
  
## End(Not run)
```

---

 adjustOHLC

*Adjust Open,High,Low,Close Prices For Splits and Dividends*


---

**Description**

Adjust all columns of an OHLC object for split and dividend.

**Usage**

```
adjustOHLC(x,
           adjust = c("split", "dividend"),
           use.Adjusted = FALSE,
           ratio = NULL,
           symbol.name=deparse(substitute(x)))
```

**Arguments**

|                           |  |
|---------------------------|--|
| <code>x</code>            | An OHLC object   |
| <code>adjust</code>       | adjust by split, dividend, or both (default)                         |
| <code>use.Adjusted</code> | use the 'Adjusted' column in Yahoo! data to adjust                   |
| <code>ratio</code>        | ratio to adjust with, bypassing internal calculations                |
| <code>symbol.name</code>  | used if <code>x</code> is not named the same as the symbol adjusting |

**Details**

This function calculates the adjusted Open, High, Low, and Close prices according to split and dividend information.

There are three methods available to calculate the new OHLC object prices.

By default, `getSplits` and `getDividends` are called to retrieve the respective information. These may dispatch to custom methods following the “.” methodology used by `quantmod` dispatch. See `getSymbols` for information related to extending `quantmod`. This information is passed to `adjRatios` from the **TTR** package, and the resulting ratio calculations are used to adjust to observed historical prices. This is the most precise way to adjust a series.

The second method works only on standard Yahoo! data containing an explicit Adjusted column.

A final method allows for one to pass a `ratio` into the function directly.

All methods proceed as follows:

New columns are derived by taking the ratio of adjusted value to original Close, and multiplying by the difference of the respective column and the original Close. This is then added to the modified Close column to arrive at the remaining 'adjusted' Open, High, Low column values.

If no adjustment is needed, the function returns the original data unaltered.

**Value**

An object of the original class, with prices adjusted for splits and dividends.



**Warning**

Using `use.Adjusted = TRUE` will be less precise than the method that employs actual split and dividend information. This is due to loss of precision from Yahoo! using Adjusted columns of only two decimal places. The advantage is that this can be run offline, and for short series or those with few adjustments the loss of precision will be small.

The resulting precision loss will be from row observation to row observation, as the calculation will be exact for intraday values.

**Author(s)**

Jeffrey A. Ryan

**References**

Yahoo Finance <http://finance.yahoo.com>

**See Also**

[getSymbols.yahoo](#) [getSplits](#) [getDividends](#)

**Examples**

```
## Not run:
getSymbols("AAPL", from="1990-01-01", src="yahoo")
head(AAPL)
head(AAPL.a <- adjustOHLC(AAPL))
head(AAPL.uA <- adjustOHLC(AAPL, use.Adjusted=TRUE))

# intrada adjustments are precise across all methods
# an example with Open to Close (OpCl)
head(cbind(OpCl(AAPL), OpCl(AAPL.a), OpCl(AAPL.uA)))

# Close to Close changes ma lose precision
head(cbind(ClCl(AAPL), ClCl(AAPL.a), ClCl(AAPL.uA)))

## End(Not run)
```

---

attachSymbols

*Attach and Flush DDB*

---

**Description**

Attach a demand database (lazy load) as a new environment.

**Usage**

```
attachSymbols(DB = DDB_Yahoo(),
             pos = 2,
             prefix = NULL,
             postfix = NULL,
             mem.cache = TRUE,
             file.cache = !mem.cache,
             cache.dir = tempdir())

flushSymbols(DB = DDB_Yahoo())
```

**Arguments**

|            |                                       |
|------------|---------------------------------------|
| DB         | A DDB data base object                |
| pos        | position in search path to attach DB  |
| prefix     | character to prefix all symbols with  |
| postfix    | character to postfix all symbols with |
| mem.cache  | should objects be cached in memory    |
| file.cache | should objects be cached in on disk   |
| cache.dir  | directory to use for file.cache=TRUE  |

**Details**

An experimental function to allow access to remote objects without requiring explicit calls to a loading function.

`attachSymbols` requires a DDB object to define where the data is to come from, as well as what symbols are loaded on-demand.

`attachSymbols` calls the method referred to by the DDB object. In the default case this is `DDB_Yahoo`. See this function for specific details about the Yahoo implementation.

The individual methods make use of `getSymbols` to load the data. This requires a corresponding `getSymbols` method.

Internally, `attachSymbols` makes use of `quantmod`'s unexported `create.bindings` to dynamically create active bindings to each symbol listed in the DDB object.

In turn, `create.bindings` uses one of two R methods to create the binding to the names required. This depends on the cache method requested.

Immediately after a call to `attachSymbols`, a new environment is attached that contains the names of objects yet to be loaded. This is similar to the lazy-load mechanism in R, though extended to be both more general and easier to use.

It is important to note that no data is loaded at this stage. What occurs instead is that these symbols now have active bindings using either `delayedAssign` (`mem.cache`) or `makeActiveBinding` (`file.cache`).

During all future requests for the object(s) in question, the binding will be used to determine how this data is loaded into R. `mem.cache` will simply load the data from its corresponding source (as defined by the DDB object) and leave it in the environment specified in the original call. The effect

of this is to allow lazy-loading of data from a variety of external sources (Yahoo in the default case). Once loaded, these are cached in R's memory. Nothing further differentiates these from standard variables. This also means that the environment will grow as more symbols are loaded.

If the `file.cache` option is set, the data is loaded from its source the first time the symbol is referenced. The difference is that the data is then written to a temporary file and maintained there. Data is loaded and subsequently removed upon each request for the object. See `makeActiveBinding` for details of how this occurs at the R level.

A primary advantage of using the `file.cache` option is the ability to maintain hundreds or thousands of objects in your current session without using memory, or explicitly loading and removing. The main downside of this approach is that data must be loaded from disk each time, with the corresponding (if generally negligible) overhead of file access.

### Note

This function is new, and all aspects may change in the near future.

### Author(s)

Jeffrey A. Ryan

### References

Luke's stuff and Mark Brevington and Roger Peng

### See Also

`delayedAssign`, `makeActiveBinding`

### Examples

```
## Not run:  
attachSymbols()  
SBUX  
QQQQ  
ls()  
  
## End(Not run)
```

---

buildData

*Create Data Object for Modelling*

---

### Description

Create one data object from multiple sources, applying transformations via standard R formula mechanism.

### Usage

```
buildData(formula, na.rm = TRUE, return.class = "zoo")
```

**Arguments**

|              |  |
|--------------|--|
| formula      | an object of class formula (or one that can be coerced to that class): a symbolic description of the desired output data object, with the dependent side corresponding to first column, and the independent parameters of the formula assigned to the remaining columns. |
| na.rm        | drop rows with missing values?   |
| return.class | one of "zoo", "data.frame", "ts", "timeSeries"   |

**Details**

Makes available for use *outside* the **quantmod** workflow a dataset of appropriately transformed variables, using the same mechanism underlying `specifyModel`. Offers the ability to apply transformations to raw data using a common formula mechanism, without having to explicitly merge different data objects.

Internally calls `specifyModel` followed by `modelData`, with the returned object being coerced to the desired 'return.class' if possible, otherwise returns a zoo object.

See `getSymbols` and `specifyModel` for more information regarding proper usage.

**Value**

An object of class `return.class`.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[getSymbols](#), [specifyModel](#), [modelData](#)

**Examples**

```
## Not run:
buildData(Next(OpCl(DIA)) ~ Lag(TBILL) + I(Lag(OpHi(DIA))^2))
buildData(Next(OpCl(DIA)) ~ Lag(TBILL), na.rm=FALSE)
buildData(Next(OpCl(DIA)) ~ Lag(TBILL), na.rm=FALSE, return.class="ts")

## End(Not run)
```

---

|            |  |
|------------|--|
| buildModel | <i>Build quantmod model given specified fitting method</i> |
|------------|--|

---

**Description**

Construct and attach a fitted model of type method to quantmod object.

**Usage**

```
buildModel(x, method, training.per, ...)
```

**Arguments**

|              |   |
|--------------|---|
| x            | An object of class quantmod created with <code>specifyModel</code> or an R formula                                      |
| training.per | character vector representing dates in ISO 8601 format “CCYY-MM-DD” or “CCYY-MM-DD HH:MM:SS” of length 2                |
| method       | A character string naming the fitting method. See details section for available methods, and how to create new methods. |
| ...          | Additional arguments to method call   |

**Details**

Currently available methods include:

lm, glm, loess, step, ppr, rpart[rpart], tree[tree], randomForest[randomForest], mars[mda], poly-mars[pol spline], lars[lars], rq[quantreg], lqs[MASS], rlm[MASS], svm[e1071], and nnet[nnet].

The `training.per` *should* match the underlying date format of the time-series data used in modelling. Any other style may not return what you expect.

Additional methods wrappers can be created to allow for modelling using custom functions. The only requirements are for a wrapper function to be constructed taking parameters `quantmod`, `training.data`, and `...`. The function must return the fitted model object and have a `predict` method available. It is possible to add `predict` methods if non exist by adding an S3 method for `predictModel`. The `buildModel.skeleton` function can be used for new methods.

**Value**

An object of class quantmod with fitted model attached

**Note**

See `buildModel.skeleton` for information on adding additional methods

**Author(s)**

Jeffrey Ryan

**See Also**

[specifyModel](#) [tradeModel](#)

**Examples**

```
## Not run:
getSymbols('QQQQ',src='yahoo')
q.model = specifyModel(Next(OpCl(QQQQ)) ~ Lag(OpHi(QQQQ),0:3))
buildModel(q.model,method='lm',training.per=c('2006-08-01','2006-09-30'))

## End(Not run)
```

---

chartSeries

*Create Financial Charts*

---

**Description**

Charting tool to create standard financial charts given a time series like object. Serves as the base function for future technical analysis additions. Possible chart styles include candles, matches (1 pixel candles), bars, and lines. Chart may have white or black background.

reChart allows for dynamic changes to the chart without having to respecify the full chart parameters.

**Usage**

```
chartSeries(x,
            type = c("auto", "candlesticks", "matchsticks", "bars", "line"),
            subset = NULL,
            show.grid = TRUE,
            name = NULL,
            time.scale = NULL,
            log.scale = FALSE,
            TA = 'addVo()',
            TAsep=';',
            line.type = "l",
            bar.type = "ohlc",
            theme = chartTheme("black"),
            layout = NA,
            major.ticks='auto', minor.ticks=TRUE,
            yrange=NULL,
            plot=TRUE,
            up.col,dn.col,color.vol = TRUE, multi.col = FALSE,
            ...)

reChart(type = c("auto", "candlesticks", "matchsticks", "bars", "line"),
        subset = NULL,
        show.grid = TRUE,
```

```

name = NULL,
time.scale = NULL,
line.type = "l",
bar.type = "ohlc",
theme = chartTheme("black"),
major.ticks='auto', minor.ticks=TRUE,
yrange=NULL,
up.col,dn.col,color.vol = TRUE, multi.col = FALSE,
...)
```

### Arguments

|             |   |
|-------------|---|
| x           | an OHLC object - see details                                      |
| type        | style of chart to draw  |
| subset      | xts style date subsetting argument                                |
| show.grid   | display price grid lines?   |
| name        | name of chart   |
| time.scale  | what is the timescale? automatically deduced (broken)             |
| log.scale   | should the y-axis be log-scaled?                                  |
| TA          | a vector of technical indicators and params, or character strings |
| TAsep       | TA delimiter for TA strings                                       |
| line.type   | type of line in line chart  |
| bar.type    | type of barchart - ohlc or hlc                                    |
| theme       | a chart.theme object  |
| layout      | if NULL bypass internal layout                                    |
| major.ticks | where should major ticks be drawn                                 |
| minor.ticks | should minor ticks be draw?                                       |
| yrange      | override y-scale  |
| plot        | should plot be drawn  |
| up.col      | up bar/candle color   |
| dn.col      | down bar/candle color   |
| color.vol   | color code volume?  |
| multi.col   | 4 color candle pattern  |
| ...         | additional parameters   |

### Details

Currently displays standard style OHLC charts familiar in financial applications, or line charts when not passes OHLC data. Works with objects having explicit time-series properties.

Line charts are created with close data, or from single column time series.

The subset argument can be used to specify a particular area of the series to view. The underlying series is left intact to allow for TA functions to use the full data set. Additionally, it is possible to use syntax borrowed from the `first` and `last` functions, e.g. 'last 4 months'.

TA allows for the inclusion of a variety of chart overlays and technical indicators. A full list is available from `addTA`. The default TA argument is `addVo()` - which adds volume, if available, to the chart being drawn.

`theme` requires an object of class `chart.theme`, created by a call to `chartTheme`. This function can be used to modify the look of the resulting chart. See `chart.theme` for details.

`line.type` and `bar.type` allow further fine tuning of chart styles to user tastes.

`multi.col` implements a color coding scheme used in some charting applications, and follows the following rules:

- grey =>  $Op[t] < Cl[t]$  and  $Op[t] < Cl[t-1]$
- white =>  $Op[t] < Cl[t]$  and  $Op[t] > Cl[t-1]$
- red =>  $Op[t] > Cl[t]$  and  $Op[t] < Cl[t-1]$
- black =>  $Op[t] > Cl[t]$  and  $Op[t] > Cl[t-1]$

`reChart` takes any number of arguments from the original chart call — and redraws the chart with the updated parameters. One item of note: if multiple color bars/candles are desired, it is necessary to respecify the `theme` argument. Additionally it is not possible to change TA parameters at present. This must be done with `addTA/dropTA/swapTA/moveTA` commands.

### Value

Returns a standard chart plus volume, if available, suitably scaled.

If `plot=FALSE` a `chob` object will be returned.

### Note

Most details can be fine-tuned within the function, though the code does a reasonable job of scaling and labelling axes for the user.

The current implementation maintains a record of actions carried out for any particular chart. This is used to recreate the original when adding new indicator. A list of applied TA actions is available with a call to `listTA`. This list can be assigned to a variable and used in new chart calls to recreate a set of technical indicators. It is also possible to force all future charts to use the same indicators by calling `setTA`.

Additional motivation to add outlined candles to allow for scaling and advanced color coding is owed to Josh Ulrich, as are the base functions (from **TTR**) for the yet to be released technical analysis charting code.

Many improvements in the current version were the result of conversations with Gabor Grothendieck. Many thanks to him.

### Author(s)

Jeffrey A. Ryan

### References

Josh Ulrich - **TTR** package and `multi.col` coding



**See Also**

[getSymbols](#), [addTA](#), [setTA](#), [chartTheme](#)

**Examples**

```
## Not run:
getSymbols("YH00")
chartSeries(YH00)
chartSeries(YH00, subset='last 4 months')
chartSeries(YH00, subset='2007::2008-01')
chartSeries(YH00, theme=chartTheme('white'))
chartSeries(YH00, TA=NULL) #no volume
chartSeries(YH00, TA=c(addVo(), addBBands())) #add volume and Bollinger Bands from TTR

addMACD() # add MACD indicator to current chart

setTA()
chartSeries(YH00) #draws chart again, this time will all indicators present

## End(Not run)
```

---

chartTheme

*Create A Chart Theme*


---

**Description**

Create a chart.theme object for use within chartSeries to manage desired chart colors.

**Usage**

```
chartTheme(theme = "black", ...)
```

**Arguments**

|       |                            |
|-------|----------------------------|
| theme | name of base theme         |
| ...   | name=value pairs to modify |

**Details**

Used as an argument to the chartSeries family of functions, chartTheme allows for on-the-fly modification of pre-specified chart ‘themes’. Users can modify a pre-built theme in-place, or copy the theme to a new variable for use in subsequent charting calls.

Internally a chart.theme object is nothing more than a list of values organized by chart components. The primary purpose of this is to facilitate minor modification on the fly, as well as provide a template for larger changes.

Setting style arguments for TA calls via chartTheme requires the user to pass the styles as name=value pairs with a name containing the TA call in question. See examples for assistance.

Current components that may be modified with appropriate values:

- fg.colforeground color
- bg.colbackground color
- grid.colgrid color
- borderborder color
- minor.tickminor tickmark color
- major.tickmajor tickmark color
- up.colup bar/candle color
- dn.coldown bar/candle color
- up.up.colup after up bar/candle color
- up.dn.colup after down bar/candle color
- dn.dn.coldown after down bar/candle color
- dn.up.coldown after up bar/candle color
- up.borderup bar/candle border color
- dn.borderdown bar/candle border color
- up.up.borderup after up bar/candle border color
- up.dn.borderup after down bar/candle border color
- dn.dn.borderdown after down bar/candle border color
- dn.up.borderdown after up bar/candle border color

**Value**

A chart.theme object

**Author(s)**

Jeffrey A. Ryan

**See Also**

[chartSeries](#)

**Examples**

```
chartTheme()  
chartTheme('white')  
chartTheme('white', up.col='blue', dn.col='red')  
  
# A TA example  
chartTheme(addRSI.col='red')  
  
str(chartTheme())
```

---

chart\_Series                      *Experimental Charting Version 2*

---

### Description

These are experimental functions for a new version of chartSeries in quantmod. Interface, behavior, and functionality will change.

### Usage

```
chart_Series(x,  
             name = deparse(substitute(x)),  
             type = "candlesticks",  
             subset = "",  
             TA = "",  
             pars = chart_pars(),  
             theme = chart_theme(),  
             clev = 0,  
             ...)
```

### Arguments

|        |  |
|--------|--|
| x      | time series object   |
| name   | name for chart   |
| type   | one of:  |
| subset | an ISO8601 style character string indicating date range                            |
| TA     | a character string of semi-colon seperated TA calls.                               |
| pars   | chart parameters   |
| theme  | chart theme  |
| clev   | color level (experimental). Indicates the degree of brightness 0 is darkest color. |
| ...    | additional parameters  |

### Details

These functions, when complete, will revert back to the original chartSeries naming convention.

### Value

Called for graphical side effects.

### Note

Highly experimental (read: alpha) use with caution.

### Author(s)

Jeffrey A. Ryan

---

 chob-class

*A Chart Object Class*


---

## Description

Internal Objects for Tracking and Plotting Chart Changes

## Objects from the Class

Objects are created internally through the charting functions `chartSeries`, `barChart`, `lineChart`, and `candleChart`.

## Slots

`device`: Object of class "ANY" ~~  
`call`: Object of class "call" ~~  
`xdata`: Object of class "ANY" ~~  
`xsubset`: Object of class "ANY" ~~  
`name`: Object of class "character" ~~  
`type`: Object of class "character" ~~  
`passed.args`: Object of class "ANY" ~~  
`windows`: Object of class "numeric" ~~  
`xrange`: Object of class "numeric" ~~  
`yrange`: Object of class "numeric" ~~  
`log.scale`: Object of class "logical" ~~  
`length`: Object of class "numeric" ~~  
`color.vol`: Object of class "logical" ~~  
`multi.col`: Object of class "logical" ~~  
`show.vol`: Object of class "logical" ~~  
`show.grid`: Object of class "logical" ~~  
`line.type`: Object of class "character" ~~  
`bar.type`: Object of class "character" ~~  
`xlab`: Object of class "character" ~~  
`ylab`: Object of class "character" ~~  
`spacing`: Object of class "numeric" ~~  
`width`: Object of class "numeric" ~~  
`bp`: Object of class "numeric" ~~  
`x.labels`: Object of class "character" ~~  
`colors`: Object of class "ANY" ~~  
`layout`: Object of class "ANY" ~~  
`time.scale`: Object of class "ANY" ~~  
`major.ticks`: Object of class "ANY" ~~  
`minor.ticks`: Object of class "logical" ~~

**Methods**

No methods defined with class "chob" in the signature.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[chartSeries](#), or [chobTA](#) for links to other classes

**Examples**

```
showClass("chob")
```

---

chobTA-class

*A Technical Analysis Chart Object*


---

**Description**

Internal storage class for handling arbitrary TA objects

**Objects from the Class**

Objects of class chobTA are created and returned invisibly through calls to addTA-style functions.

**Slots**

```
call: Object of class "call" ~~
on: Object of class "ANY" ~~
new: Object of class "logical" ~~
TA.values: Object of class "ANY" ~~
name: Object of class "character" ~~
params: Object of class "ANY" ~~
```

**Methods**

```
show signature(object = "chobTA"): ...
```

**Note**

It is of no external vaule to handle chobTA objects directly

**Author(s)**

Jeffrey A. Ryan

**See Also**

[addTA](#), [~~~](#) or [chob](#) for links to other classes

**Examples**

```
showClass("chobTA")
```

---

|                |                            |
|----------------|----------------------------|
| create.binding | <i>Create DDB Bindings</i> |
|----------------|----------------------------|

---

**Description**

Internal function used in `attachSymbols` to create active bindings for symbols defined in a DDB object.

**Usage**

```
create.binding(s,
              lsym,
              rsym,
              gsrc,
              mem.cache = TRUE,
              file.cache = !mem.cache,
              cache.dir = tempdir(),
              envir,...)
```

**Arguments**

|            |  |
|------------|--|
| s          | symbol name  |
| lsym       | function to convert to local name (legal R name)         |
| rsym       | function to convert to remote name (source name)         |
| gsrc       | corresponds to 'src' arg in <code>getSymbols</code> call |
| mem.cache  | cache to memory  |
| file.cache | cache to disk  |
| cache.dir  | directory to cache to/from                               |
| envir      | environment name (character)                             |
| ...        | arguments to pass to <code>getSymbols</code> call        |

**Details**

Low level function to create bindings during initial demand-database construction.

**Value**

Called for its side effect of creating active bindings to symbols.

**Note**

This is code used internally by `attachSymbols`. User's may modify this to accomodate different systems. The upstream functions needn't maintain consistency with this interface.

Use as a guide or template.

**Author(s)**

Jeffrey A. Ryan

**References**

Mark, Roger, ?

---

 Defaults

---

*Manage Default Argument Values for `quantmod` Functions*


---

**Description**

Use globally specified defaults, if set, in place of formally specified default argument values. Allows user to specify function defaults different than formally supplied values, e.g. to change poorly performing defaults, or satisfy a different preference.

**Usage**

```
setDefaultts(name, ...)
unsetDefaultts(name, confirm = TRUE)
getDefaultts(name = NULL, arg = NULL)
importDefaultts(calling.fun)
```

**Arguments**

|                          |                                      |
|--------------------------|--------------------------------------|
| <code>name</code>        | name of function, quoted or unquoted |
| <code>...</code>         | name=value default pairs             |
| <code>confirm</code>     | prompt before unsetting defaults     |
| <code>arg</code>         | values to retrieve                   |
| <code>calling.fun</code> | name of function to act upon         |

**Details**

**setDefaultts** Provides a wrapper to R options that allows the user to specify any name=value pair for a function's formal arguments. Only formal name=value pairs specified will be updated.

Values do not have to be respecified in subsequent calls to `setDefaultts`, so it is possible to add new defaults for each function one at a time, without having to retype all previous values.

Assigning NULL to any argument will remove the argument from the defaults list.

**unsetDefaultts** Removes name=value pairs from the defaults list.

**getDefaults** Provides access to the stored user defaults. Single arguments need not be quoted, multiple arguments must be in a character vector.

**importDefaults** A call to `importDefaults` should be placed on the first line in the body of the function. It checks the user's environment for globally specified default values for the called function. These defaults can be specified by the user with a call to `setDefault`s, and will override any default formal parameters, in effect replacing the original defaults with user supplied values instead. Any user-specified values in the parent function (that is, the function containing `importDefaults`) will override the values set in the global default environment.

### Value

|                             |  |
|-----------------------------|--|
| <code>setDefault</code> s   | None. Used for its side effect of setting a list of default arguments by function.   |
| <code>unsetDefault</code> s | None. Used for its side effect of unsetting default arguments by function.   |
| <code>getDefaults</code>    | A named list of defaults and associated values, similar to <code>formals</code> , but only returning values set by <code>setDefault</code> s for the name function. Calling <code>getDefaults()</code> (without arguments) returns in a character vector of all functions currently having defaults set (by <code>setDefault</code> s).<br>This <i>does not</i> imply that the returned function names are able to accept defaults (via <code>importDefaults</code> ), rather that they have been set to store user defaults. All values can also be viewed with a call to <code>getOption(name_of_function, Default)</code> . |
| <code>importDefaults</code> | None. Used for its side-effect of loading all non-NULL user-specified default values into the current function's environment, effectively changing the default values passed in the parent function call. Like formally defined defaults in the function definition, default values set by <code>importDefaults</code> take lower precedence than arguments specified by the user in the function call.  |

### Note

**setDefault**s At present it is not possible to specify NULL as a replacement for a non-NULL default, as the process interprets NULL values as being not set, and will simply use the value specified formally in the function. If NULL is what is desired, it is necessary to include this in the function call itself.

Any arguments included in the actual function call will take precedence over `setDefault`s values, as well as the standard formal function values. This conforms to the current user experience in R.

Like options, default settings are *not* kept across sessions. Currently, it is *not* possible to pass values for ... arguments, only formally specified arguments in the original function definition.

**unsetDefault**s `unsetDefault`s removes the *all* entries from the options lists for the specified function. To remove single function default values simply set the name of the argument to NULL in `setDefault`s.

**importDefaults** When a function implements `importDefaults`, non-named arguments *may* be ignored if a global default has been set (i.e. not NULL). If this is the case, simply name the arguments in the calling function.

This *should* also work for functions retrieving formal parameter values from options, as it assigns a value to the parameter in a way that looks like it was passed in the function call. So any check on options would presumably disregard `importDefaults` values if an argument was passed to the function.



**Author(s)**

Jeffrey A. Ryan

**See Also**[options](#)**Examples**

```
my.fun <- function(x=3)
{
  importDefaults('my.fun')
  x^2
}

my.fun()          # returns 9

setDefault(my.fun, x=10)
my.fun()          # returns 100
my.fun(x=4)       # returns 16

getDefault(my.fun)
formals(my.fun)
unsetDefaults(my.fun, confirm=FALSE)
getDefault(my.fun)

my.fun()          # returns 9
```

---

**Delt***Calculate Percent Change*

---

**Description**

Calculate the k-period percent difference within one series, or between two series. Primarily used to calculate the percent change from one period to another of a given series, or to calculate the percent difference between two series over the full series.

**Usage**

```
Delt(x1, x2 = NULL, k = 0, type = c("arithmetic", "log"))
```

**Arguments**

|      |   |
|------|---|
| x1   | <i>m x 1</i> vector                                 |
| x2   | <i>m x 1</i> vector                                 |
| k    | change over k-periods. default k=1 when x2 is NULL. |
| type | type of difference. log or arithmetic (default).    |

**Details**

When called with only x1, the one period percent change of the series is returned by default. Internally this happens by copying x1 to x2. A two period difference would be specified with k=2.

If called with both x1 and x2, the difference between the two is returned. That is, k=0. A one period difference would be specified by k=1. k may also be a vector to calculate more than one period at a time. The results will then be an m x length(k)

Arithmetic differences are used by default:  $\text{Lag} = (x2(t) - x1(t-k))/x1(t-k)$

Log differences are calculated:  $\text{Lag} = \log(x2(t)/x1(t-k))$

**Value**

An matrix of length(x1) rows and length(k) columns.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[OpOp](#) [OpCl](#)

**Examples**

```
Stock.Open <- c(102.25,102.87,102.25,100.87,103.44,103.87,103.00)
Stock.Close <- c(102.12,102.62,100.12,103.00,103.87,103.12,105.12)

Delt(Stock.Open)                #one period pct. price change
Delt(Stock.Open,k=1)            #same
Delt(Stock.Open,type='arithmetic') #using arithmetic differences (default)
Delt(Stock.Open,type='log')      #using log differences

Delt(Stock.Open,Stock.Close)    #Open to Close pct. change
Delt(Stock.Open,Stock.Close,k=0:2) #...for 0,1, and 2 periods
```

---

findPeaks

*Find Peaks and Valleys In A Series*

---

**Description**

Functions to find the peaks (tops) and valleys (bottoms) of a given series.

**Usage**

```
findPeaks(x, thresh=0)
findValleys(x, thresh=0)
```

**Arguments**

x                    a time series or vector  
 thresh              minimum peak/valley threshold

**Value**

A vector of integers corresponding to peaks/valleys.

As a peak[valley] is defined as the highest[lowest] value in a series, the function can only define it after a change in direction has occurred. This means that the function will always return the first period *after* the peak/valley of the data, so as not to accidentally induce a look-ahead bias.

**Author(s)**

Jeffrey A. Ryan

**Examples**

```
findPeaks(sin(1:10))

p <- findPeaks(sin(seq(1,10,.1)))
sin(seq(1,10,.1))[p]

plot(sin(seq(1,10,.1))[p])
plot(sin(seq(1,10,.1)),type='l')
points(p,sin(seq(1,10,.1))[p])
```

---

fittedModel                    *quantmod Fitted Objects*

---

**Description**

Extract and replace fitted models from quantmod objects built with buildModel. All objects fitted through methods specified in buildModel calls can be extracted for further analysis.

**Usage**

```
fittedModel(object)

## S3 method for class 'quantmod'
formula(x, ...)

## S3 method for class 'quantmod'
plot(x, ...)

## S3 method for class 'quantmod'
coefficients(object, ...)
```

```

## S3 method for class 'quantmod'
coef(object, ...)

## S3 method for class 'quantmod'
residuals(object, ...)

## S3 method for class 'quantmod'
resid(object, ...)

## S3 method for class 'quantmod'
fitted.values(object, ...)

## S3 method for class 'quantmod'
fitted(object, ...)

## S3 method for class 'quantmod'
anova(object, ...)

## S3 method for class 'quantmod'
logLik(object, ...)

## S3 method for class 'quantmod'
vcov(object, ...)

```

### Arguments

|        |                      |
|--------|----------------------|
| object | a quantmod object    |
| x      | a suitable object    |
| ...    | additional arguments |

### Details

Most often used to extract the final fitted object of the modelling process, usually for further analysis with tools outside the **quantmod** package.

Most common methods to apply to fitted objects are available to the parent quantmod object. At present, one can call directly the following S3 methods on a built model as if calling directly on the fitted object. See *\*Usage\** section.

It is also *possible* to add a fitted model to an object. This may be of value when applying heuristic rule sets for trading approaches, or when fine tuning already fit models by hand.

### Value

Returns an object matching that returned by a call to the method specified in buildModel.

### Note

The replacement function fittedModel<- is highly experimental, and may or may not continue into further releases.

The fitted model added *must* use the same names as appear in the quantmod object's dataset.

### Author(s)

Jeffrey A. Ryan

### See Also

[quantmod](#), [buildModel](#)

### Examples

```
## Not run:
x <- specifyModel(Next(OpCl(DIA)) ~ OpCl(VIX))
x.lm <- buildModel(x,method='lm',training.per=c('2001-01-01','2001-04-01'))

fittedModel(x.lm)

coef(fittedModel(x.lm))
coef(x.lm)           # same

vcov(fittedModel(x.lm))
vcov(x.lm)           # same

## End(Not run)
```

---

getDividends

*Load Financial Dividend Data*

---

### Description

Download, or download and append stock dividend data from Yahoo! Finance.

### Usage

```
getDividends(Symbol,
              from = "1970-01-01",
              to = Sys.Date(),
              env = parent.frame(),
              src = "yahoo",
              auto.assign = FALSE,
              auto.update = FALSE,
              verbose = FALSE,
              split.adjust = TRUE, ...)
```

**Arguments**

|              |   |
|--------------|---|
| Symbol       | The Yahoo! stock symbol   |
| from         | date from in CCYY-MM-DD format  |
| to           | date to in CCYY-MM-DD format  |
| env          | where to create object  |
| src          | data source (only yahoo is valid at present)                                    |
| auto.assign  | should results be loaded to env   |
| auto.update  | automatically add dividend to data object                                       |
| verbose      | display status of retrieval   |
| split.adjust | adjust dividends for splits (TRUE by default because that's what Yahoo returns) |
| ...          | currently unused  |

**Details**

Eventually destined to be a wrapper function along the lines of `getSymbols` to different sources - this currently only support Yahoo data.

**Value**

If `auto.assign` is TRUE, the symbol will be written to the environment specified in `env` with a `.div` appended to the name.

If `auto.update` is TRUE and the object is of class `xts`, the dividends will be included as an attribute of the original object and be reassigned to the environment specified by `env`.

All other cases will return the dividend data as an `xts` object.

**Note**

This function is very preliminary - and will most likely change significantly in the future.

**Author(s)**

Jeffrey A. Ryan

**References**

Yahoo! Finance: <http://finance.yahoo.com>

**See Also**

[getSymbols](#)

**Examples**

```
## Not run:
getSymbols("MSFT")
getDividends("MSFT")

getDividends(MSFT)

## End(Not run)
```

---

getFinancials

*Download and View Financial Statements*


---

**Description**

Download Income Statement, Balance Sheet, and Cash Flow Statements from Google Finance.

**Usage**

```
getFinancials(Symbol, env = parent.frame(), src = "google",
              auto.assign = TRUE,
              ...)

viewFinancials(x, type=c('BS','IS','CF'), period=c('A','Q'),
              subset = NULL)
```

**Arguments**

|             |   |
|-------------|---|
| Symbol      | one or more valid google symbol, as a character vector or semi-colon delimited string |
| env         | where to create the object  |
| src         | currently unused  |
| auto.assign | should results be loaded to the environment   |
| ...         | currently unused  |
| x           | an object of class financials   |
| type        | type of statement to view   |
| period      | period of statement to view   |
| subset      | 'xts' style subset string   |

**Details**

A utility to download financial statements for publically traded companies. The data is directly from Google finance. All use of the data is under there Terms of Service, available at <http://www.google.com/accounts/TOS>.

Individual statements can be accessed using standard R list extraction tools, or by using viewFinancials.

viewFinancials allows for the use of date subsetting as available in the **xts** package, as well as the specification of the type of statement to view. BS for balance sheet, IS for income statement, and CF for cash flow statement. The period argument is used to identify which statements to view - (A) for annual and (Q) for quarterly.

### Value

Six individual matrices organized in a list of class 'financials':

|    |   |
|----|---|
| IS | a list containing (Q)uarterly and (A)nnual Income Statements    |
| BS | a list containing (Q)uarterly and (A)nnual Balance Sheets       |
| CF | a list containing (Q)uarterly and (A)nnual Cash Flow Statements |

### Note

As with all free data, you may be getting exactly what you pay for.

### Author(s)

Jeffrey A. Ryan

### References

Google Finance BETA: <http://finance.google.com/finance>

### Examples

```
## Not run:
getFinancials('JAVA') # returns JAVA.f to "env"
getFin('AAPL') # returns AAPL.f to "env"

viewFin(JAVA.f, "IS", "Q") # Quarterly Income Statement
viewFin(AAPL.f, "CF", "A") # Annual Cash Flows

str(AAPL.f)

## End(Not run)
```

---

getFX

*Download Exchange Rates*

---

### Description

Download exchange rates or metals prices from oanda.



**Usage**

```
getFX(Currencies,  
      from = Sys.Date() - 179,  
      to = Sys.Date(),  
      env = parent.frame(),  
      verbose = FALSE,  
      warning = TRUE,  
      auto.assign = TRUE, ...)
```

**Arguments**

|             |   |
|-------------|---|
| Currencies  | Currency pairs expressed as 'CUR/CUR'                         |
| from        | start date expressed in ISO CCYY-MM-DD format                 |
| to          | end date expressed in ISO CCYY-MM-DD format                   |
| env         | which environment should they be loaded into                  |
| verbose     | be verbose  |
| warning     | show warnings   |
| auto.assign | use auto.assign   |
| ...         | additional parameters to be passed to getSymbols.oanda method |

**Details**

A convenience wrapper to `getSymbols(x, src='oanda')`. See `getSymbols` and `getSymbols.oanda` for more detail.

**Value**

The results of the call will be the data will be assigned automatically to the environment specified (parent by default). Additionally a vector of downloaded symbol names will be returned.

See `getSymbols` and `getSymbols.oanda` for more detail.

**Author(s)**

Jeffrey A. Ryan

**References**

Oanda.com <http://www.oanda.com>

**See Also**

[getSymbols](#), [getSymbols.oanda](#)

**Examples**

```
## Not run:

getFX("USD/JPY")

getFX("EUR/USD", from="2005-01-01")

## End(Not run)
```

---

getMetals

*Download Daily Metals Prices*


---

**Description**

Download daily metals prices from oanda.

**Usage**

```
getMetals(Metals,
          from = Sys.Date() - 179,
          to = Sys.Date(),
          base.currency="USD",
          env = parent.frame(),
          verbose = FALSE,
          warning = TRUE,
          auto.assign = TRUE, ...)
```

**Arguments**

|               |   |
|---------------|---|
| Metals        | metals expressed in common name or symbol form                |
| from          | start date expressed in ISO CCYY-MM-DD format                 |
| to            | end date expressed in ISO CCYY-MM-DD format                   |
| base.currency | which currency should the price be in                         |
| env           | which environment should they be loaded into                  |
| verbose       | be verbose  |
| warning       | show warnings   |
| auto.assign   | use auto.assign   |
| ...           | additional parameters to be passed to getSymbols.oanda method |

**Details**

A convenience wrapper to `getSymbols(x, src='oanda')`.

The most useful aspect of `getMetals` is the ability to specify the Metals in terms of underlying 3 character symbol or by name (e.g. XAU (gold), XAG (silver), XPD (palladium), or XPT (platinum)).

There are unique aspects of any continuously traded commodity, and it is recommended that the user visit <http://www.oanda.com> for details on specific pricing issues.

See `getSymbols` and `getSymbols.oanda` for more detail.

**Value**

Data will be assigned automatically to the environment specified (parent by default). If `auto.assign` is set to `FALSE`, the data from a single metal request will simply be returned from the function call.

If `auto.assign` is used (the default) a vector of downloaded symbol names will be returned.

See `getSymbols` and `getSymbols.oanda` for more detail.

**Author(s)**

Jeffrey A. Ryan

**References**

Oanda.com <http://www.oanda.com>

**See Also**

[getSymbols](#), [getSymbols.oanda](#)

**Examples**

```
## Not run:  
  
getFX(c("gold", "XPD"))  
  
getFX("plat", from="2005-01-01")  
  
## End(Not run)
```

---

getModelData

*Update model's dataset*

---

**Description**

Update currently specified or built model with most recent data.

**Usage**

```
getModelData(x, na.rm = TRUE)
```

**Arguments**

|                    |  |
|--------------------|--|
| <code>x</code>     | An object of class <code>quantmod</code>                 |
| <code>na.rm</code> | Boolean. Remove NA values. Defaults to <code>TRUE</code> |

**Details**

Primarily used within specify model calls, getModelData is used to retrieve the appropriate underlying variables, and apply model specified transformations automatically. It can be used to also update a current model in memory with the most recent data.

**Value**

Returns object of class quantmod.OHLC

**Author(s)**

Jeffrey Ryan

**See Also**

[getSymbols](#) load data [specifyModel](#) create model structure [buildModel](#) construct model [modelData](#) extract model dataset

**Examples**

```
## Not run:
my.model <- specifyModel(Next(OpCl(QQQQ)) ~ Lag(Cl(NDX),0:5))
getModelData(my.model)

## End(Not run)
```

---

getOptionChain      *Download Option Chains*

---

**Description**

Function to download option chain data from data providers.

**Usage**

```
getOptionChain(Symbols, Exp = NULL, src="yahoo", ...)
```

**Arguments**

|         |   |
|---------|---|
| Symbols | The name of the underlying symbol.  |
| Exp     | One or more expiration dates, NULL, or an ISO-8601 style string. If Exp is missing, only the front month contract will be returned. |
| src     | Source of data. Currently only 'yahoo' is provided.   |
| ...     | Additional parameters.  |

**Details**

This function is a wrapper to data-provider specific APIs. By default the data is sourced from yahoo.

**Value**

A named list containing two data.frames, one for calls and one for puts. If more than one expiration was requested, this two-element list will be contained within list of length length(Exp). Each element of this list will be named with the expiration month, day, and year (for Yahoo sourced data).

If Exp is set to NULL, all expirations will be returned. Not explicitly setting will only return the front month.

**Author(s)**

Jeffrey A. Ryan, Joshua M. Ulrich

**References**

<http://finance.yahoo.com>

**Examples**

```
## Not run:  
# Only the front-month expiry  
AAPL.OPT <- getOptionChain("AAPL")  
# All expiries  
AAPL.OPTS <- getOptionChain("AAPL", NULL)  
# All 2015 and 2016 expiries  
AAPL.2015 <- getOptionChain("AAPL", "2015/2016")  
  
## End(Not run)
```

---

getQuote

*Download Current Stock Quote*

---

**Description**

Fetch current stock quote(s) from specified source. At present this only handles sourcing quotes from Yahoo Finance, but it will be extended to additional sources over time.

**Usage**

```
getQuote(Symbols, src = "yahoo", what, ...)  
  
standardQuote(src="yahoo")  
yahooQF(names)  
yahooQuote.EOD
```

**Arguments**

|         |  |
|---------|--|
| Symbols | character string of symbols, seperated by semi-colons          |
| src     | source of data (only yahoo is implemented in <b>quantmod</b> ) |
| what    | what should be retrieved                                       |
| names   | which data should be retrieved                                 |
| ...     | currently unused   |

**Value**

A maximum of 200 symbols may be requested per call to Yahoo!, and all requested will be returned in one data.frame object. If more that 200 symbols are requested, multiple 200 symbol calls will be made and the results will be returned as one data object.

getQuote returns a data frame with rows matching the number of Symbols requested, and the columns matching the requested columns.

The what argument allows for specific data to be requested. For getQuote.yahoo, the value of what should be a quoteFormat object like that returned by standardQuote which contains Yahoo!'s formatting string. If not provided, the A list and interactive selection tool can be seen with yahooQF.

standardQuote currently only applied to Yahoo! data, and returns an object of class quoteFormat, for use within the getQuote function.

yahooQuote.EOD is a constant quoteFormat object for OHLCV data.

**Author(s)**

Jeffrey A. Ryan

**References**

Yahoo! Finance [finance.yahoo.com](http://finance.yahoo.com) [gummy-stuff.org](http://gummy-stuff.org) [www.gummy-stuff.org/Yahoo-data.htm](http://www.gummy-stuff.org/Yahoo-data.htm)

**See Also**

[getSymbols](#)

**Examples**

```
yahooQuote.EOD
## Not run:
getQuote("AAPL")
getQuote("QQQQ;SPY;^VXN", what=yahooQF(c("Bid", "Ask")))
standardQuote()
yahooQF()

## End(Not run)
```

---

`getSplits`*Load Financial Split Data*

---

**Description**

Download, or download and append stock split data from Yahoo! Finance.

**Usage**

```
getSplits(Symbol,  
          from = "1970-01-01",  
          to = Sys.Date(),  
          env = parent.frame(),  
          src = "yahoo",  
          auto.assign = FALSE,  
          auto.update = FALSE,  
          verbose = FALSE, ...)
```

**Arguments**

|                          |  |
|--------------------------|--|
| <code>Symbol</code>      | The Yahoo! stock symbol                      |
| <code>from</code>        | date from in CCYY-MM-DD format               |
| <code>to</code>          | date to in CCYY-MM-DD format                 |
| <code>env</code>         | where to create object                       |
| <code>src</code>         | data source (only yahoo is valid at present) |
| <code>auto.assign</code> | should results be loaded to env              |
| <code>auto.update</code> | automatically add split to data object       |
| <code>verbose</code>     | display status of retrieval                  |
| <code>...</code>         | currently unused                             |

**Details**

Eventually destined to be a wrapper function along the lines of `getSymbols` to different sources - this currently only support Yahoo data.

**Value**

If `auto.assign` is TRUE, the symbol will be written to the environment specified in `env` with a `.div` appended to the name.

If `auto.update` is TRUE and the object is of class `xts`, the dividends will be included as an attribute of the original object and be reassigned to the environment specified by `env`.

All other cases will return the split data as an `xts` object. NA is returned if there is no split data.

**Note**

This function is very preliminary - and will most likely change significantly in the future.

**Author(s)**

Josh Ulrich

**References**

Yahoo! Finance: <http://finance.yahoo.com>

**See Also**

[getSymbols](#), [getDividends](#)

**Examples**

```
## Not run:  
getSymbols("MSFT")  
getSplits("MSFT")  
  
getSplits(MSFT)  
  
## End(Not run)
```

---

getSymbols

*Load and Manage Data from Multiple Sources*

---

**Description**

Functions to load and manage Symbols in specified environment. Used by [specifyModel](#) to retrieve symbols specified in first step of modelling procedure. Not a true S3 method, but methods for different data sources follow an S3-like naming convention. Additional methods can be added by simply adhering to the convention.

Current src methods available are: yahoo, google, MySQL, FRED, csv, RData, and oanda.

Data is loaded silently *without* user assignment by default.

**Usage**

```
getSymbols(Symbols = NULL,  
           env = parent.frame(),  
           reload.Symbols = FALSE,  
           verbose = FALSE,  
           warnings = TRUE,  
           src = "yahoo",  
           symbol.lookup = TRUE,  
           auto.assign = getOption('getSymbols.auto.assign', TRUE),
```



```

...))

loadSymbols(Symbols = NULL,
            env = parent.frame(),
            reload.Symbols = FALSE,
            verbose = FALSE,
            warnings = TRUE,
            src = "yahoo",
            symbol.lookup = TRUE,
            auto.assign = getOption('loadSymbols.auto.assign', TRUE),
            ...)

showSymbols(env=parent.frame())
removeSymbols(Symbols=NULL,env=parent.frame())
saveSymbols(Symbols = NULL,
            file.path=stop("must specify 'file.path'"),
            env = parent.frame())

```

### Arguments

|                |   |
|----------------|---|
| Symbols        | a character vector specifying the names of each symbol to be loaded   |
| env            | where to create objects. Setting env=NULL is equal to auto.assign=FALSE   |
| reload.Symbols | boolean to reload current symbols in specified environment. (FALSE)   |
| verbose        | boolean to turn on status of retrieval. (FALSE)   |
| warnings       | boolean to turn on warnings. (TRUE)   |
| src            | character string specifying sourcing method. (yahoo)  |
| symbol.lookup  | retrieve symbol's sourcing method from external lookup (TRUE)   |
| auto.assign    | should results be loaded to env If FALSE, return results instead. As of 0.4-0, this is the same as setting env=NULL. Defaults to TRUE |
| file.path      | character string of file location   |
| ...            | additional parameters   |

### Details

getSymbols is a wrapper to load data from various sources, local or remote. Data is fetched via one of the available getSymbols methods and either saved in the env specified - the parent.frame() by default – or returned to the caller. The functionality derives from base::load behavior and semantics, i.e. is assigned automatically to a variable in the specified environment *without* the user explicitly assigning the returned data to a variable. The assigned variable name is that of the respective Symbols value.

The previous sentence's point warrants repeating - getSymbols is called for its side effects, and by default *does not* return the data object loaded. The data is 'loaded' silently by the function into the environment specified.

If automatic assignment is not desired, env may be set to NULL, or auto.assign set to FALSE.

The early versions of getSymbols assigned each object into the user's .GlobalEnv by name (pre 2009 up to versions less than 0.4-0). This behavior is now supported by manually setting env=.GlobalEnv.

As of version 0.4-0, the environment is set to `parent.frame()`, which preserved the user workspace when called within another scope.

*This behavior is expect to change for `getSymbols` as of 0.5-0, and all results will instead be explicitly returned to the caller unless a `auto.assign` is set to `TRUE`. Many thanks to Kurt Hornik and Achim Zeileis for suggesting this change, and further thanks to Dirk Eddelbuettel for encouraging the move to a more functional default by 0.5-0.*

Using `auto.assign=TRUE`, the variable chosen is an R-legal name derived from the symbol being loaded. It is possible, using `setSymbolLookup` to specify an alternate name if the default is not desired. See that function for details.

If `auto.assign=FALSE` or `env=NULL` (as of 0.4-0) the data will be returned from the call, and will require the user to assign the results himself. Note that only *one* symbol at a time may be requested when auto assignment is disabled.

Most, if not all, documentation and functionality related to model construction and testing in **quantmod** assumes that `auto.assign` remains set to `TRUE` and `env` is a valid environment object for the calls related to those functions.

Upon completion a list of loaded symbols is stored in the specified environment under the name `.getSymbols`.

Objects loaded by `getSymbols` with `auto.assign=TRUE` can be viewed with `showSymbols` and removed by a call to `removeSymbols`. Additional data loading “methods” can be created simply by following the S3-like naming convention where `getSymbols.NAME` is used for your function NAME. See `getSymbols` source code.

`setDefault(getSymbols)` can be used to specify defaults for `getSymbols` arguments. `setDefault(getSymbols.MySQL)` may be used for arguments specific to `getSymbols.MySQL`, etc.

The “sourcing” of data is managed internally through a complex lookup procedure. If `symbol.lookup` is `TRUE` (the default), a check is made if any symbol has had its source specified by `setSymbolLookup`.

If not set, the process continues by checking to see if `src` has been specified by the user in the function call. If not, any `src` defined with `setDefault(getSymbols, src=)` is used.

Finally, if none of the other source rules apply the default `getSymbols` `src` method is used (`‘yahoo’`).

## Value

Called for its side-effect with `env` set to a valid environment and `auto.assign=TRUE`, `getSymbols` will load into the specified `env` one object for each `Symbol` specified, with class defined by `return.class`. Presently this may be `ts`, `zoo`, `xts`, or `timeSeries`.

If `env=NULL` or `auto.assign=FALSE` an object of type `return.class` will be returned.

## Note

As of version 0.4-0, the default `env` value is now `parent.frame()`. In interactive use this should provide the same functionality as the previous version.

While it is possible to load symbols as classes other than `zoo`, **quantmod** requires most, if not all, data to be of class `zoo` or inherited from `zoo` - e.g. `xts`. The additional methods are meant mainly to be of use for those using the functionality outside of the **quantmod** workflow.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[getModelData](#), [specifyModel](#), [setSymbolLookup](#), [getSymbols.csv](#), [getSymbols.RData](#), [getSymbols.oanda](#), [getSymbols.yahoo](#), [getSymbols.google](#), [getSymbols.FRED](#), [getFX](#), [getMetals](#),

**Examples**

```
## Not run:
setSymbolLookup(QQQ='yahoo',SPY='google')

# loads QQQQ from yahoo (set with setSymbolLookup)
# loads SPY from MySQL (set with setSymbolLookup)
getSymbols(c('QQQ','SPY'))

# loads Ford market data from yahoo (the formal default)
getSymbols('F')

# loads symbol from MySQL database (set with setDefaults)
getSymbols('DIA', verbose=TRUE, src='MySQL')

# loads Ford as time series class ts
getSymbols('F',src='yahoo',return.class='ts')

# load into a new environment
data.env <- new.env()
getSymbols("YH00", env=data.env)
ls.str(data.env)

# constrain to local scope
try(local( {
  getSymbols("AAPL") # or getSymbols("AAPL", env=environment())
  str(AAPL)
}))

exists("AAPL") # FALSE

# assign into an attached environment
attach(NULL, name="DATA.ENV")
getSymbols("AAPL", env=as.environment("DATA.ENV"))
ls("DATA.ENV")
detach("DATA.ENV")

# directly return to caller
str( getSymbols("AAPL", env=NULL) )
str( getSymbols("AAPL", auto.assign=FALSE) ) # same

## End(Not run)
```

---

|                |                                |
|----------------|--------------------------------|
| getSymbols.csv | <i>Load Data from csv File</i> |
|----------------|--------------------------------|

---

### Description

Downloads Symbols to specified env from local comma seperated file. This method is not to be called directly, instead a call to `getSymbols(Symbols, src='csv')` will in turn call this method. It is documented for the sole purpose of highlighting the arguments accepted, and to serve as a guide to creating additional `getSymbols` 'methods'.

### Usage

```
getSymbols.csv(Symbols,
               env,
               dir="",
               return.class = "xts",
               extension="csv",
               col.names=c("Open", "High", "Low", "Close", "Volume", "Adjusted"),
               ...)
```

### Arguments

|              |   |
|--------------|---|
| Symbols      | a character vector specifying the names of each symbol to be loaded |
| env          | where to create objects. (.GlobalEnv)                               |
| dir          | directory of csv file   |
| return.class | class of returned object  |
| extension    | extension of csv file   |
| col.names    | data column names   |
| ...          | additional parameters   |

### Details

Meant to be called internally by `getSymbols` (see also).

One of a few currently defined methods for loading data for use with **quantmod**. Essentially a simple wrapper to the underlying R `read.csv`.

### Value

A call to `getSymbols.csv` will load into the specified environment one object for each Symbol specified, with class defined by `return.class`. Presently this may be `ts`, `zoo`, `xts`, or `timeSeries`.

### Note

This has yet to be tested on a windows platform. It *should* work though file seperators may be an issue.

**Author(s)**

Jeffrey A. Ryan

**See Also**[getSymbols](#), [read.csv](#), [setSymbolLookup](#)**Examples**

```
## Not run:
# All 3 getSymbols calls return the same
# MSFT to the global environment
# The last example is what NOT to do!

## Method #1
getSymbols('MSFT',src='csv')

## Method #2
setDefaults(getSymbols,src='csv')
# OR
setSymbolLookup(MSFT='csv')

getSymbols('MSFT')

#####
## NOT RECOMMENDED!!!
#####
## Method #3
getSymbols.csv('MSFT',verbose=TRUE,env=globalenv())

## End(Not run)
```

---

getSymbols.FRED

*Download Federal Reserve Economic Data - FRED(R)*


---

**Description**

R access to over 11,000 data series accessible via the St. Louis Federal Reserve Bank's FRED system.

Downloads Symbols to specified env from 'research.stlouisfed.org'. This method is not to be called directly, instead a call to `getSymbols(Symbols,src='FRED')` will in turn call this method. It is documented for the sole purpose of highlighting the arguments accepted, and to serve as a guide to creating additional `getSymbols` 'methods'.

**Usage**

```
getSymbols.FRED(Symbols,  
                env,  
                return.class = "xts",  
                ...)
```

**Arguments**

|              |   |
|--------------|---|
| Symbols      | a character vector specifying the names of each symbol to be loaded |
| env          | where to create objects. (.GlobalEnv)                               |
| return.class | class of returned object  |
| ...          | additional parameters   |

**Details**

Meant to be called internally by `getSymbols` (see also).

One of many methods for loading data for use with **quantmod**. Essentially a simple wrapper to the underlying FRED data download site.

Naming conventions must follow those as seen on the Federal Reserve Bank of St Louis's website for FRED. A lookup facility will hopefully be incorporated into **quantmod** in the near future.

**Value**

A call to `getSymbols.FRED` will load into the specified environment one object for each Symbol specified, with class defined by `return.class`. Presently this may be `ts`, `zoo`, `xts`, or `timeSeries`.

**Note**

FRED changed its URL scheme for the downloads from `http://` to `https://`. If `getSymbols.FRED` fails for this reason, try one of the following solutions:

1. Explicitly pass method via the `getSymbols` call (or via `setDefault`s).
2. Install **downloader**, which may be able to automatically determine a suitable method.
3. Set the `download.file.method` global option.

**Author(s)**

Jeffrey A. Ryan

**References**

St. Louis Fed: Economic Data - FRED <http://research.stlouisfed.org/fred2/>

**See Also**

[getSymbols](#), [setSymbolLookup](#)

**Examples**

```
## Not run:
# All 3 getSymbols calls return the same
# CPI data to the global environment
# The last example is what NOT to do!

## Method #1
getSymbols('CPIAUCNS',src='FRED')

## Method #2
setDefaults(getSymbols,src='FRED')
# OR
setSymbolLookup(CPIAUCNS='FRED')

getSymbols('CPIAUCNS')

#####
## NOT RECOMMENDED!!
#####
## Method #3
getSymbols.FRED('CPIAUCNS',env=globalenv())

## End(Not run)
```

---

getSymbols.google

*Download OHLC Data From Google Finance*


---

**Description**

Downloads Symbols to specified env from 'finance.google.com'. This method is not to be called directly, instead a call to `getSymbols(Symbols,src='google')` will in turn call this method. It is documented for the sole purpose of highlighting the arguments accepted, and to serve as a guide to creating additional `getSymbols` 'methods'.

**Usage**

```
getSymbols.google(Symbols,
                  env,
                  return.class = 'xts',
                  from = "2007-01-01",
                  to = Sys.Date(),
                  ...)
```

**Arguments**

|         |   |
|---------|---|
| Symbols | a character vector specifying the names of each symbol to be loaded |
| env     | where to create objects. (.GlobalEnv)                               |

|              |                                    |
|--------------|------------------------------------|
| return.class | class of returned object           |
| from         | Retrieve no earlier than this date |
| to           | Retrieve though this date          |
| ...          | additional parameters              |

### Details

Meant to be called internally by getSymbols (see also).

One of a few currently defined methods for loading data for use with **quantmod**. Essentially a simple wrapper to the underlying Google Finance site for historical data.

A word of warning. Google is the home of *BETA*, and historic data is no exception. There is a *BUG* in practically all series that include the dates Dec 29,30, and 31 of 2003. The data will show the wrong date and corresponding prices. This essentially makes it useless, but if they ever apply a fix the data is nice(r) than Yahoo, in so much as it is all split adjusted and there is forty years worth to be had. As long as you skip the holiday week of 2003. : )

### Value

A call to getSymbols.google will load into the specified environment one object for each Symbol specified, with class defined by return.class. Presently this may be ts, zoo, xts, or timeSeries.

### Note

As mentioned in the details section, a serious flaw exists within the google database/SQL. A caution is issued when retrieving data via this method if this particular error is encountered, but one can only wonder what else may be wrong. Caveat emptor.

### Author(s)

Jeffrey A. Ryan

### References

Google Finance: <http://finance.google.com>

### See Also

[getSymbols](#), [setSymbolLookup](#)

### Examples

```
## Not run:
# All 3 getSymbols calls return the same
# MSFT to the global environment
# The last example is what NOT to do!

## Method #1
getSymbols('MSFT',src='google')
```



```

## Method #2
setDefault(getSymbols,src='google')
# OR
setSymbolLookup(MSFT='google')

getSymbols('MSFT')

#####
## NOT RECOMMENDED!!!
#####
## Method #3
getSymbols.google('MSFT',verbose=TRUE,env=globalenv())

## End(Not run)

```

---

getSymbols.MySQL

*Retrieve Data from MySQL Database*


---

### Description

Fetch data from MySQL database. As with other methods extending the `getSymbols` function, this should *NOT* be called directly. Its documentation is meant to highlight the formal arguments, as well as provide a reference for further user contributed data tools.

### Usage

```

getSymbols.MySQL(Symbols,
                 env,
                 return.class = 'xts',
                 db.fields = c("date", "o", "h", "l", "c", "v", "a"),
                 field.names = NULL,
                 user = NULL,
                 password = NULL,
                 dbname = NULL,
                 host = "localhost",
                 port = 3306,
                 ...)

```

### Arguments

|                           |  |
|---------------------------|--|
| <code>Symbols</code>      | a character vector specifying the names of each symbol to be loaded  |
| <code>env</code>          | where to create objects. ( <code>.GlobalEnv</code> )   |
| <code>return.class</code> | desired class of returned object. Can be <code>xts</code> , <code>zoo</code> , <code>data.frame</code> , or <code>ts</code> . ( <code>zoo</code> ) |
| <code>db.fields</code>    | character vector indicating names of fields to retrieve  |
| <code>field.names</code>  | names to assign to returned columns  |
| <code>user</code>         | username to access database  |

|          |                             |
|----------|-----------------------------|
| password | password to access database |
| dbname   | database name               |
| host     | database host               |
| port     | database port               |
| ...      | currently not used          |

### Details

Meant to be called internally by `getSymbols` (see also)

One of a few currently defined methods for loading data for use with **quantmod**. Its use requires the packages **DBI** and **MySQL**, along with a running MySQL database with tables corresponding to the Symbol name.

The purpose of this abstraction is to make transparent the ‘source’ of the data, allowing instead the user to concentrate on the data itself.

### Value

A call to `getSymbols.MySQL` will load into the specified environment one object for each Symbol specified, with class defined by `return.class`.

### Note

The default configuration needs a table named for the Symbol specified (e.g. MSFT), with column names date,o,h,l,c,v,a. For table layout changes it is best to use `setDefaultts(getSymbols.MySQL, ...)` with the new `db.fields` values specified.

### Author(s)

Jeffrey A. Ryan

### References

MySQL AB <http://www.mysql.com>

David A. James and Saikat DebRoy (2006). *R Interface to the MySQL database*. [www.omegahat.net](http://www.omegahat.net)

*R-SIG-DB. DBI: R Database Interface*

### See Also

[getSymbols](#), [setSymbolLookup](#)

### Examples

```
## Not run:
# All 3 getSymbols calls return the same
# MSFT to the global environment
# The last example is what NOT to do!
```

```

setDefaults(getSymbols.MySQL,user='jdoe',password='secret',
            dbname='tradedata')

## Method #1
getSymbols('MSFT',src='MySQL')

## Method #2
setDefaults(getSymbols,src='MySQL')
# OR
setSymbolLookup(MSFT='MySQL')

getSymbols('MSFT')

#####
## NOT RECOMMENDED!!!
#####
## Method #3
getSymbols.MySQL('MSFT',env=globalenv())

## End(Not run)

```

---

getSymbols.oanda

*Download Currency and Metals Data from Oanda.com*


---

## Description

Access to 191 currency and metal prices, downloadable as more than 36000 currency pairs from Oanda.com.

Downloads Symbols to specified env from [www.oanda.com](http://www.oanda.com) historical currency database. This method is not meant to be called directly, instead a call to `getSymbols("x",src="oanda")` will in turn call this method. It is documented for the sole purpose of highlighting the arguments accepted, and to serve as a guide to creating additional `getSymbols` 'methods'.

## Usage

```

getSymbols.oanda(Symbols,
                env,
                return.class = "xts",
                from = Sys.Date() - 179,
                to = Sys.Date(),
                ...)

```

## Arguments

**Symbols** a character vector specifying the names of each symbol to be loaded - expressed as a currency pair. (e.g. U.S. Dollar to Euro rate would be expressed as a string "USD/EUR". The naming convention follows from Oanda.com, and a table of possible values is available by calling `oanda.currencies`

|              |   |
|--------------|---|
| env          | where to create objects.                  |
| return.class | class of returned object                  |
| from         | Start of series expressed as "CCYY-MM-DD" |
| to           | Start of series expressed as "CCYY-MM-DD" |
| ...          | additional parameters                     |

### Details

Meant to be called internally by getSymbols only.

Oanda data is 7 day daily average price data, that is Monday through Sunday. Oanda only provides historical data for the past 180 days. getSymbols will return as much data as possible, and warn when the from date is more than 180 days ago.

### Value

A call to getSymbols(Symbols,src="oanda") will load into the specified environment one object for each 'Symbol' specified, with class defined by 'return.class'. Presently this may be 'ts', 'zoo', 'xts', or 'timeSeries'.

### Note

Oanda rates are quoted as one unit of base currency to the equivalent amount of foreign currency.

### Author(s)

Jeffrey A. Ryan

### References

Oanda.com <http://www.oanda.com>

### See Also

Currencies: [getSymbols.FRED](#), [getSymbols](#)

### Examples

```
## Not run:  
getSymbols("USD/EUR", src="oanda")  
getSymbols("USD/EUR", src="oanda", from="2005-01-01")  
  
## End(Not run)
```

---

|                |                                     |
|----------------|-------------------------------------|
| getSymbols.rda | <i>Load Data from R Binary File</i> |
|----------------|-------------------------------------|

---

### Description

Downloads Symbols to specified env from local R data file. This method is not to be called directly, instead a call to `getSymbols(Symbols, src='rda')` will in turn call this method. It is documented for the sole purpose of highlighting the arguments accepted, and to serve as a guide to creating additional `getSymbols` 'methods'.

### Usage

```
getSymbols.rda(Symbols,
               env,
               dir="",
               return.class = "xts",
               extension="rda",
               col.names=c("Open", "High", "Low", "Close", "Volume", "Adjusted"),
               ...)
```

### Arguments

|              |   |
|--------------|---|
| Symbols      | a character vector specifying the names of each symbol to be loaded |
| env          | where to create objects. (.GlobalEnv)                               |
| dir          | directory of rda/RData file   |
| return.class | class of returned object  |
| extension    | extension of R data file  |
| col.names    | data column names   |
| ...          | additional parameters   |

### Details

Meant to be called internally by `getSymbols` (see also).

One of a few currently defined methods for loading data for use with **quantmod**. Essentially a simple wrapper to the underlying R load.

### Value

A call to `getSymbols.csv` will load into the specified environment one object for each Symbol specified, with class defined by `return.class`. Presently this may be `ts`, `zoo`, `xts`, `data.frame`, or `timeSeries`.

### Author(s)

Jeffrey A. Ryan

**See Also**

[getSymbols](#), [load](#), [setSymbolLookup](#)

**Examples**

```
## Not run:
# All 3 getSymbols calls return the same
# MSFT to the global environment
# The last example is what NOT to do!

## Method #1
getSymbols('MSFT',src='rda')
getSymbols('MSFT',src='RData')

## Method #2
setDefaults(getSymbols,src='rda')
# OR
setSymbolLookup(MSFT='rda')
# OR
setSymbolLookup(MSFT=list(src='rda'))

getSymbols('MSFT')

#####
## NOT RECOMMENDED!!!
#####
## Method #3
getSymbols.rda('MSFT',verbose=TRUE,env=globalenv())

## End(Not run)
```

---

getSymbols.SQLite

*Retrieve Data from SQLite Database*

---

**Description**

Fetch data from SQLite database. As with other methods extending `getSymbols` this function should *NOT* be called directly.

**Usage**

```
getSymbols.SQLite(Symbols,
                  env,
                  return.class = 'xts',
                  db.fields = c("row_names",
                                "Open",
                                "High",
                                "Low",
```

```

        "Close",
        "Volume",
        "Adjusted"),
    field.names = NULL,
    dbname = NULL,
    POSIX = TRUE,
    ...)
```

### Arguments

|                           |   |
|---------------------------|---|
| <code>Symbols</code>      | a character vector specifying the names of each symbol to be loaded |
| <code>env</code>          | where to create the objects   |
| <code>return.class</code> | desired class of returned object                                    |
| <code>db.fields</code>    | character vector naming fields to retrieve                          |
| <code>field.names</code>  | names to assign to returned columns                                 |
| <code>dbname</code>       | database name   |
| <code>POSIX</code>        | are rownames numeric  |
| <code>...</code>          | additional arguments  |

### Details

Meant to be called internally by `getSymbols` (see also)

One of a few currently defined methods for loading data for use with 'quantmod'. Its use requires the packages 'DBI' and 'RSQLite', along with a SQLite database.

The purpose of this abstraction is to make transparent the 'source' of the data, allowing instead the user to concentrate on the data itself.

### Value

A call to `getSymbols.SQLite` will load into the specified environment one object for each 'Symbol' specified, with class defined by 'return.class'.

### Note

This function is experimental at best, and has not been thoroughly tested. Use with caution, and please report any bugs to the maintainer of `quantmod`.

### Author(s)

Jeffrey A. Ryan

### References

SQLite <http://www.sqlite.org>  
 David A. James *RSQLite: SQLite interface for R*  
*R-SIG-DB. DBI: R Database Interface*

**See Also**[getSymbols](#)**Examples**

```
## Not run:
getSymbols("QQQQ",src="SQLite")

## End(Not run)
```

---

getSymbols.yahoo      *Download OHLC Data From Yahoo Finance*

---

**Description**

Downloads Symbols to specified env from 'finance.yahoo.com'. This method is not to be called directly, instead a call to `getSymbols(Symbols,src='yahoo')` will in turn call this method. It is documented for the sole purpose of highlighting the arguments accepted, and to serve as a guide to creating additional `getSymbols` 'methods'.

**Usage**

```
getSymbols.yahoo(Symbols,
                 env,
                 return.class = 'xts',
                 index.class = 'Date',
                 from = "2007-01-01",
                 to = Sys.Date(),
                 ...)
```

**Arguments**

|              |   |
|--------------|---|
| Symbols      | a character vector specifying the names of each symbol to be loaded |
| env          | where to create objects. (.GlobalEnv)                               |
| return.class | class of returned object  |
| index.class  | class of returned object index (xts only)                           |
| from         | Retrieve data no earlier than this date. (2007-01-01)               |
| to           | Retrieve data through this date (Sys.Date())                        |
| ...          | additional parameters   |

**Details**

Meant to be called internally by `getSymbols` (see also).

One of a few currently defined methods for loading data for use with **quantmod**. Essentially a simple wrapper to the underlying Yahoo! finance site's historical data download.



**Value**

A call to `getSymbols.yahoo` will load into the specified environment one object for each `Symbol` specified, with class defined by `return.class`. Presently this may be `ts`, `zoo`, `xts`, or `timeSeries`.

In the case of `xts` objects, the indexing will be by `Date`. This can be altered with the `index.class` argument. See `indexClass` for more information on changing index classes.

**Author(s)**

Jeffrey A. Ryan

**References**

Yahoo Finance: <http://finance.yahoo.com>

**See Also**

[getSymbols](#), [setSymbolLookup](#)

**Examples**

```
## Not run:
# All 3 getSymbols calls return the same
# MSFT to the global environment
# The last example is what NOT to do!

## Method #1
getSymbols('MSFT',src='yahoo')

## Method #2
setDefaults(getSymbols,src='yahoo')
# OR
setSymbolLookup(MSFT='yahoo')

getSymbols('MSFT')

#####
## NOT RECOMMENDED!!!
#####
## Method #3
getSymbols.yahoo('MSFT',env=globalenv())

## End(Not run)
```

---

getSymbols.yahooj      *Download OHLC Data From Yahoo! Japan Finance*

---

### Description

Downloads Symbols to specified env from 'finance.yahoo.co.jp'. This method is not to be called directly, instead a call to `getSymbols(Symbols, src='yahooj')` will in turn call this method. It is documented for the sole purpose of highlighting the arguments accepted, and to serve as a guide to creating additional `getSymbols` 'methods'.

### Usage

```
getSymbols.yahooj(Symbols,
                  env,
                  return.class = 'xts',
                  index.class = 'Date',
                  from = "2007-01-01",
                  to = Sys.Date(),
                  ...)
```

### Arguments

|                           |   |
|---------------------------|---|
| <code>Symbols</code>      | a character vector specifying the names of each symbol to be loaded |
| <code>env</code>          | where to create objects. (.GlobalEnv)                               |
| <code>return.class</code> | class of returned object  |
| <code>index.class</code>  | class of returned object index (xts only)                           |
| <code>from</code>         | Retrieve data no earlier than this date. (2007-01-01)               |
| <code>to</code>           | Retrieve data through this date (Sys.Date())                        |
| <code>...</code>          | additional parameters   |

### Details

Meant to be called internally by `getSymbols` (see also).

One of the few currently defined methods for loading data for use with **quantmod**. Essentially a simple wrapper to the underlying Yahoo! Japan finance site's historical data download.

The string 'YJ' will be prepended to the `Symbols` because Japanese ticker symbols usually start with a number and it is cumbersome to use variable names that start with a number in the R environment.

It is recommended to prepend the ticker symbols with 'YJ' yourself if you use `setSymbolLookup`. That will make it possible for the main `getSymbols` function to find the symbols in the lookup table.

### Value

A call to `getSymbols.yahooj` will load into the specified environment one object for each `Symbol` specified, with class defined by `return.class`. Presently this may be `ts`, `zoo`, `xts`, or `timeSeries`.

In the case of `xts` objects, the indexing will be by `Date`. This can be altered with the `index.class` argument. See `indexClass` for more information on changing index classes.

**Author(s)**

Wouter Thielen

**References**Yahoo! Japan Finance: <http://finance.yahoo.co.jp>**See Also**[getSymbols](#), [setSymbolLookup](#)**Examples**

```
## Not run:
# All 4 getSymbols calls return the same
# Sony (6758.T) OHLC to the global environment
# The last example is what NOT to do!

## Method #1
getSymbols('6758.T',src='yahooj')

## Method #2
getSymbols('YJ6758.T',src='yahooj')

## Method #3
setDefault(getSymbols,src='yahooj')
# OR
setSymbolLookup(YJ6758.T='yahooj')

getSymbols('YJ6758.T')

#####
## NOT RECOMMENDED!!!
#####
## Method #4
getSymbols.yahooj('6758.T',env=globalenv())

## End(Not run)
```

has.OHLC

*Check For OHLC Data***Description**

A set of functions to check for appropriate OHLC and HLC column names within a data object, as well as the availability and position of those columns.

**Usage**

```

is.OHLC(x)
has.OHLC(x, which = FALSE)

is.OHLCV(x)
has.OHLCV(x, which = FALSE)

is.HLC(x)
has.HLC(x, which = FALSE)

has.Op(x, which = FALSE)
has.Hi(x, which = FALSE)
has.Lo(x, which = FALSE)
has.Cl(x, which = FALSE)
has.Vo(x, which = FALSE)
has.Ad(x, which = FALSE)

is.BBO(x)
is.TBBO(x)

has.Ask(x, which = FALSE)
has.Bid(x, which = FALSE)
has.Price(x, which = FALSE)
has.Qty(x, which = FALSE)
has.Trade(x, which = FALSE)

```

**Arguments**

|       |                           |
|-------|---------------------------|
| x     | data object               |
| which | display position of match |

**Details**

Mostly used internally by **quantmod**, they can be useful for checking whether an object can be used in OHLC requiring functions like `Op`, `OpCl`, etc.

Column names must contain the full description of data, that is, `Open`, `High`, `Low`, `Close`, `Volume` or `Adjusted`. Abbreviations will return `FALSE` (or `NA` when `which=TRUE`). See [quantmod.OHLC](#) for details of **quantmod** naming conventions.

`is.OHLC` (and `is.HLC`, similarly) will only return `TRUE` if there are columns for `Open`, `High`, `Low` and `Close`. Additional columns will not affect the value.

**Value**

A logical value indicating success or failure by default.

If `which=TRUE`, a numeric value representing the column position will be returned.

`is.OHLC` and `is.HLC` return a single value of `TRUE` or `FALSE`.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[quantmod.OHLC,OHLC.Transformations](#)

**Examples**

```
## Not run:  
getSymbols("YH00")  
  
is.OHLC(YH00)  
has.OHLC(YH00)  
  
has.Ad(YH00)  
  
## End(Not run)
```

---

internal-quantmod      *Internal quantmod Objects*

---

**Description**

To be documented...

---

is.quantmod      *Test If Object of Type quantmod*

---

**Description**

Test if object is of type quantmod or quantmodResults.

**Usage**

```
is.quantmod(x)  
is.quantmodResults(x)
```

**Arguments**

x                      object to test

**Value**

Boolean TRUE or FALSE

**Author(s)**

Jeffrey A. Ryan

**See Also**[specifyModel](#), [tradeModel](#)

---

**Lag***Lag a Time Series*

---

**Description**

Create a lagged series from data, with NA used to fill.

**Usage**

```
Lag(x, k = 1)

## S3 method for class 'quantmod.OHLC'
Lag(x, k = 1)

## S3 method for class 'zoo'
Lag(x, k = 1)

## S3 method for class 'data.frame'
Lag(x, k = 1)

## S3 method for class 'numeric'
Lag(x, k = 1)
```

**Arguments**

|   |                               |
|---|-------------------------------|
| x | vector or series to be lagged |
| k | periods to lag.               |

**Details**

Shift series k-periods down, prepending NAs to front of series.  
Specifically designed to handle quantmod.OHLC and zoo series within the quantmod workflow.  
If no S3 method is found, a call to `lag` in **base** is made.

**Value**

The original x prepended with k NAs and missing the trailing k values.  
The returned series maintains the number of obs. of the original.

**Note**

This function differs from `lag` by returning the original series modified, as opposed to simply changing the time series properties. It differs from the like named `Lag` in the **Hmisc** as it deals primarily with time-series like objects.

It is important to realize that if there is no applicable method for `Lag`, the value returned will be from `lag` in **base**. That is, coerced to 'ts' if necessary, and subsequently shifted.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[lag](#)

**Examples**

```
Stock.Close <- c(102.12,102.62,100.12,103.00,103.87,103.12,105.12)
Close.Dates <- as.Date(c(10660,10661,10662,10665,10666,10667,10668),origin="1970-01-01")
Stock.Close <- zoo(Stock.Close,Close.Dates)

Lag(Stock.Close)          #lag by 1 period
Lag(Stock.Close,k=1)     #same
Lag(Stock.Close,k=1:3)  #lag 1,2 and 3 periods
```

---

modelData

*Extract Dataset Created by specifyModel*

---

**Description**

Extract from a `quantmod` object the dataset created for use in modelling.

`specifyModel` creates a `zoo` object for use in subsequent workflow stages (`buildModel`,`tradeModel`) that combines all model inputs, from a variety of sources, into one model frame.

`modelData` returns this object.

**Usage**

```
modelData(x, data.window = NULL, exclude.training = FALSE)
```

**Arguments**

`x` a `quantmod` object

`data.window` a character vector of subset start and end dates to return

`exclude.training` remove training period

**Details**

When a model is created by `specifyModel`, it is attached to the returned object. One of the slots of this S4 class is `model.data`.

**Value**

an object of class `zoo` containing all transformations to data specified in `specifyModel`.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[specifyModel,getModelData](#)

**Examples**

```
## Not run:
m <- specifyModel(Next(OpCl(SPY)) ~ Cl(SPY) + OpHi(SPY) + Lag(Cl(SPY)))
modelData(m)

## End(Not run)
```

---

modelSignal

*Extract Model Signal Object*

---

**Description**

Extract model signal object from `quantmodResults` object as an object of class `zoo`.

**Usage**

```
modelSignal(x)
```

**Arguments**

x                    object of class `quantmodResults`

**Details**

For use after a call to `tradeModel` to extract the generated signal of a given `quantmod` model. Normally this would not need to be called by the end user unless he was manually post processing the trade results.

**Value**

A `zoo` object indexed by signal dates.



**Author(s)**

Jeffrey A. Ryan

**See Also**[tradeModel](#)

newTA

*Create A New TA Indicator For chartSeries***Description**

Functions to assist in the creation of indicators or content to be drawn on plots produced by chartSeries.

**Usage**

```
addTA(ta,
      order = NULL,
      on = NA,
      legend = "auto",
      yrange = NULL,
      ...)

newTA(FUN,
      preFUN,
      postFUN,
      on = NA,
      yrange = NULL,
      legend.name,
      fdots = TRUE,
      cdots = TRUE,
      data.at = 1,
      ...)
```

**Arguments**

|         |   |
|---------|---|
| ta      | data to be plotted                                    |
| order   | which should the columns (if > 1) be plotted          |
| legend  | what custom legend text should be added to the chart. |
| FUN     | Main filter function name - as a symbol               |
| preFUN  | Pre-filter transformation or extraction function      |
| postFUN | Post-filter transformation or extraction function     |
| on      | where to draw   |
| yrange  | length 2 vector of y-axis range                       |

|             |   |
|-------------|---|
| legend.name | optional legend heading, automatically derived otherwise  |
| fdots       | should any ... be included in the main filter call  |
| cdots       | should any ... be included in the resultant function object. fdots=TRUE will override this to TRUE. |
| data.at     | which argument to the main filter function is for data.   |
| ...         | any additional graphical parameters/default to be included.   |

## Details

Both addTA and newTA can be used to dynamically add custom content to a displayed chart.

addTA takes a series of values, either in a form coercible to xts or of the same length as the charted series has rows, and displays the results in either a new TA sub-window, or over/underlaid on the main price chart. If the object can be coerced to xts, the time values present must only be within the original series time-range. Internally a merge of dates occurs and will allow for the plotting of discontinuous series.

The order argument allows for multiple column data to be plotted in an order that makes the most visual sense.

Specifying a legend will override the standard parsing of the addTA call to attempt a guess at a suitable title for the sub-chart. Specifying this will cause the standard last value to *not* be printed.

The ... arg to addTA is used to set graphical parameters interpretable by lines.

newTA acts as more of a skeleton function, taking functions as arguments, as well as charting parameters, and returns a function that can be called in the same manner as the built-in TA tools, such as addRSI and addMACD. Essentially a dynamic code generator that allows for highly customizable chart tools with minimal (possibly zero) coding. It is also possible to modify the resultant code to further change behavior.

To create a new TA function with newTA certain arguments must be specified.

The FUN argument is a function symbol (or coercible to such) that is the primary filter to be used on the core-data of a chartSeries chart. This can be like most of the functions within the **TTR** package — e.g. RSI or EMA. The resultant object of the function call will be equal to calling the function on the original data passed into the chartSeries function that created the chart. It should be coercible to a matrix object, of one or more columns of output. By default all columns of output will be added to the chart, unless suppressed by passing the appropriately positioned type='n' as the ... arg. Note that this will not suppress the labels added to the chart.

The preFUN argument will be called on the main chart's data prior to passing it to FUN. This must be a function symbol or a character string of the name function to be called.

The postFUN argument will be called on the resultant data returned from the FUN filter. This is useful for extracting the relevant data from the returned filter data. Like preFUN it must be a function symbol or a character string of the name of the function to be called.

The yrange argument is used to provide a custom scale to the y-axis. If NULL the min and max of the data to be plotted will be used for the y-axis range.

The on is used to identify which subchart to add the graphic to. By default, on=NA will draw the series in a new subchart below the last indicator. Setting this to either a positive or negative value will allow for the series to be super-imposed on, or under, the (sub)chart specified, respectively. A value of 1 refers to the main chart, and at present is the only location supported.

`legend.name` will change the main label for a new plot.

`fdots` and `cdots` enable inclusion or suppression of the ... within the resulting TA code's call to FUN, or the argument list of the new TA function, respectively. In order to facilitate user-specified graphical parameters it is usually desirable to not impose artificial limits on the end-user with constraints on types of parameters available. By default the new TA function will include the dots argument, and the internal FUN call will keep all arguments, including the dots. This may pose issues if the internal function then passes those ... arguments to a function that can't handle them.

The final argument is `data.at` which is the position in the FUN argument list which expects the data to be passed in at. This default to the sensible first position, though can be changed at the time of creation by setting this argument to the required value.

While the above functions are usually sufficient to construct very pleasing graphical additions to a chart, it may be necessary to modify by-hand the code produced. This can be accomplished by dumping the function to a file, or using `fix` on it during an interactive session.

Another item of note, with respect to `newTA` is the naming of the main legend label. Following `addTA` convention, the first 'add' is stripped from the function name, and the rest of the call's name is used as the label. This can be overridden by specifying `legend.name` in the construction of the new TA call, or by passing `legend` into the new TA function. Subtle differences exist, with the former being the preferred solution.

While both functions can be used to build new indicators without any understanding of the internal `chartSeries` process, it may be beneficial in more complex cases to have a knowledge of the multi-step process involved in creating a chart via `chartSeries`.

to be added...

## Value

`addTA` will invisibly return an S4 object of class `chobTA`. If this function is called interactively, the `chobTA` object will be evaluated and added to the current chart.

`newTA` will return a function object that can either be assigned or evaluated. Evaluating this function will follow the logic of any standard `addTA`-style call, returning invisibly a `chobTA` object, or adding to the chart.

## Note

Both interfaces are meant to facilitate custom chart additions. `addTA` is for adding any arbitrary series to a chart, where-as `newTA` works with the underlying series with the main chart object. The latter also acts as a dynamic TA skeleton generation tool to help develop reusable TA generation code for use on any chart.

## Author(s)

Jeffrey A. Ryan

## See Also

[chartSeries](#), [TA](#), [chob](#), [chobTA](#)

## Examples

```
## Not run:
getSymbols('SBUX')
barChart(SBUX)
addTA(EMA(C1(SBUX)), on=1, col=6)
addTA(OpC1(SBUX), col=4, type='b', lwd=2)
# create new EMA TA function
newEMA <- newTA(EMA, C1, on=1, col=7)
newEMA()
newEMA(on=NA, col=5)

## End(Not run)
```

---

Next

*Advance a Time Series*

---

## Description

Create a new series with all values advanced forward one period. The value of period 1, becomes the value at period 2, value at 2 becomes the original value at 3, etc. The opposite of Lag. NA is used to fill.

## Usage

```
Next(x, k = 1)

## S3 method for class 'quantmod.OHLC'
Next(x,k=1)

## S3 method for class 'zoo'
Next(x,k=1)

## S3 method for class 'data.frame'
Next(x,k=1)

## S3 method for class 'numeric'
Next(x,k=1)
```

## Arguments

|   |                                 |
|---|---------------------------------|
| x | vector or series to be advanced |
| k | periods to advance              |

**Details**

Shift series k-periods up, appending NAs to end of series.

Specifically designed to handle `quantmod.OHLC` and `zoo` series within the **quantmod** workflow.

If no S3 method is found, a call to `lag` in **base** is made, with the indexing reversed to shift the time series forward.

**Value**

The original `x` appended with `k` NAs and missing the leading `k` values.

The returned series maintains the number of obs. of the original.

Unlike `Lag`, only one value for `k` is allowed.

**Note**

This function's purpose is to get the "next" value of the data you hope to forecast, e.g. a stock's closing value at `t+1`. Specifically to be used within the **quantmod** framework of `specifyModel`, as a functional wrapper to the LHS of the model equation.

It is not magic - and thus will not get tomorrow's values...

**Author(s)**

Jeffrey A. Ryan

**See Also**

[specifyModel](#), [Lag](#)

**Examples**

```
Stock.Close <- c(102.12,102.62,100.12,103.00,103.87,103.12,105.12)
Close.Dates <- as.Date(c(10660,10661,10662,10665,10666,10667,10668),origin="1970-01-01")
Stock.Close <- zoo(Stock.Close,Close.Dates)

Next(Stock.Close)      #one period ahead
Next(Stock.Close,k=1)  #same

merge(Next(Stock.Close),Stock.Close)

## Not run:
# a simple way to build a model of next days
# IBM close, given todays. Technically both
# methods are equal, though the former is seen
# as more intuitive..ymmv
specifyModel(Next(Cl(IBM)) ~ Cl(IBM))
specifyModel(Cl(IBM) ~ Lag(Cl(IBM)))

## End(Not run)
```

---

 OHLC.Transformations    *Extract and Transform OHLC Time-Series Columns*


---

**Description**

Extract (transformed) data from a suitable OHLC object. Column names must contain the complete description - either “Open”, “High”, “Low”, “Close”, “Volume”, or “Adjusted” - though may also contain additional characters. This is the default for objects returned from most `getSymbols` calls.

In the case of functions consisting of combined Op, Hi, Lo, Cl (e.g. `ClCl(x)`) the one period transformation will be applied.

For example, to return the Open to Close of a object it is possible to call `OpCl(x)`. If multiple periods are desired a call to the function `Delt` is necessary.

`seriesLo` and `seriesHi` will return the low and high, respectively, of a given series.

`seriesAccel`, `seriesDecel`, `seriesIncr`, and `seriesDecr`, return a vector of logicals indicating if the series is accelerating, decelerating, increasing, or decreasing. This is managed by `diff`, which provides NA fill and suitable re-indexing. These are here to make trade rules easier to read.

HLC extracts the High, Low, and Close columns. OHLC extracts the Open, High, Low, and Close columns.

These functions are merely to speed the model specification process. All columns may also be extracted through standard R methods.

Assignment will not work at present.

`getPrice` will attempt to extract price column(s) from a time series, using sensible defaults. Additionally, the user may provide by symbol and price preference.

**Usage**

`Op(x)`

`Hi(x)`

`Lo(x)`

`Cl(x)`

`Vo(x)`

`Ad(x)`

`seriesHi(x)`

`seriesLo(x)`

`seriesIncr(x, thresh=0, diff.=1L)`

`seriesDecr(x, thresh=0, diff.=1L)`

`OpCl(x)`

`ClCl(x)`

`HiCl(x)`

`LoCl(x)`

`LoHi(x)`

`OpHi(x)`

OpLo(x)  
OpOp(x)

HLC(x)  
OHLC(x)  
OHLCV(x)

getPrice(x, symbol=NULL, prefer=NULL, ...)

### Arguments

|        |   |
|--------|---|
| x      | A data object with columns containing data to be extracted. |
| thresh | noise threshold (seriesIncr/seriesDecr)                     |
| diff.  | differencing (seriesIncr/seriesDecr)                        |
| symbol | text string containing the symbol to extract                |
| prefer | price type preference (see Details)                         |
| ...    | not currently used  |

### Details

Internally, the code uses `grep` to locate the appropriate columns. Therefore it is necessary to use inputs with column names matching the requirements in the description section, though the exact naming convention is not as important.

`prefer` can be used with `getPrice` to extract many commonly used financial time series prices descriptions (e.g. open, high, low, close, bid, ask/offer, midpoint, trade, price). If the value of `prefer` does not match one of the currently supported types, it will be matched against the object column names using `grep`.

### Value

Returns an object of the same class as the original series, with the appropriately column names if applicable and/or possible. The only exceptions are for `quantmod.OHLC` objects which will be returned as `zoo` objects, and calls to `seriesLo` and `seriesHi` which *may* return a numeric value instead of the original object type.

### Author(s)

Jeffrey A. Ryan

### See Also

[specifyModel](#)

**Examples**

```
## Not run:
getSymbols('IBM',src='yahoo')
Ad(IBM)
Cl(IBM)
ClCl(IBM)

seriesHi(IBM)
seriesHi(Lo(IBM))

removeSymbols('IBM')

## End(Not run)
```

---

options.expiry

*Calculate Contract Expirations*

---

**Description**

Return the index of the contract expiration date. The third Friday of the month for options, the last third Friday of the quarter for futures.

**Usage**

```
options.expiry(x)
futures.expiry(x)
```

**Arguments**

x                    a time-indexed zoo object

**Details**

Designed to be used within a charting context via addExpiry, the values returned are based on the description above. Exceptions, though rare, are not accounted for.

**Value**

A numeric vector of values to index on.

**Note**

There is currently no accounting for holidays that may interfere with the general rule. Additionally all efforts have been focused on US equity and futures markets.

**Author(s)**

Jeffrey A. Ryan



**References**

~put references to the literature/web site here ~

**See Also**

[addExpiry](#)

**Examples**

```
## Not run:
getSymbols("AAPL")

options.expiry(AAPL)
futures.expiry(AAPL)

AAPL[options.expiry(AAPL)]

## End(Not run)
```

---

periodReturn

*Calculate Periodic Returns*

---

**Description**

Given a set of prices, return periodic returns.

**Usage**

```
periodReturn(x,
             period='monthly',
             subset=NULL,
             type='arithmetic',
             leading=TRUE,
             ...)

dailyReturn(x, subset=NULL, type='arithmetic',
            leading=TRUE, ...)
weeklyReturn(x, subset=NULL, type='arithmetic',
            leading=TRUE, ...)
monthlyReturn(x, subset=NULL, type='arithmetic',
            leading=TRUE, ...)
quarterlyReturn(x, subset=NULL, type='arithmetic',
            leading=TRUE, ...)
annualReturn(x, subset=NULL, type='arithmetic',
            leading=TRUE, ...)
yearlyReturn(x, subset=NULL, type='arithmetic',
            leading=TRUE, ...)
allReturns(x, subset=NULL, type='arithmetic',
            leading=TRUE)
```

**Arguments**

|         |  |
|---------|--|
| x       | object of state prices, or an OHLC type object   |
| period  | character string indicating time period. Valid entries are ‘daily’, ‘weekly’, ‘monthly’, ‘quarterly’, ‘yearly’. All are accessible from wrapper functions described below. Defaults to monthly returns (same as <code>monthlyReturn</code> ) |
| subset  | an xts/ISO8601 style subset string   |
| type    | type of returns: arithmetic (discrete) or log (continuous)   |
| leading | should incomplete leading period returns be returned   |
| ...     | passed along to <code>to.period</code>   |

**Details**

`periodReturn` is the underlying function for wrappers:

- `allReturns`: calculate all available return periods
- `dailyReturn`: calculate daily returns
- `weeklyReturn`: calculate weekly returns
- `monthlyReturn`: calculate monthly returns
- `quarterlyReturn`: calculate quarterly returns
- `annualReturn`: calculate annual returns

**Value**

Returns object of the class that was originally passed in, with the possible exception of monthly and quarterly return indices being changed to class `yearmon` and `yearqtr` where available. This can be overridden with the `indexAt` argument passed in the ... to the `to.period` function.

By default, if `subset` is NULL, the full dataset will be used.

**Note**

Attempts are made to re-convert the resultant series to its original class, if supported by the xts package. At present, objects inheriting from the ‘ts’ class are returned as xts objects. This is to make the results more visually appealing and informative. All xts objects can be converted to class `ts` with `as.ts` if that is desirable.

The first and final row of returned object will have the period return to last date, i.e. this week/month/quarter/year return to date even if the start/end is not the start/end of the period. Leading period calculations can be suppressed by setting `leading=FALSE`.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[getSymbols](#)

**Examples**

```
## Not run:
getSymbols('QQQQ',src='yahoo')
allReturns(QQQQ) # returns all periods

periodReturn(QQQQ,period='yearly',subset='2003::') # returns years 2003 to present
periodReturn(QQQQ,period='yearly',subset='2003') # returns year 2003

rm(QQQQ)

## End(Not run)
```

---

|                |                         |
|----------------|-------------------------|
| quantmod-class | <i>Class "quantmod"</i> |
|----------------|-------------------------|

---

**Description**

Objects of class `quantmod` help to manage the process of model building within the `quantmod` package. Created automatically by a call to `specifyModel` they carry information to be used by a variety of accessor functions and methods.

**Objects from the Class**

Objects can be created by calls of the form `new("quantmod", ...)`.  
 Normally objects are created as a result of a call to `specifyModel`.

**Slots**

```
model.id: Object of class "character" ~~
model.spec: Object of class "formula" ~~
model.formula: Object of class "formula" ~~
model.target: Object of class "character" ~~
model.inputs: Object of class "character" ~~
build.inputs: Object of class "character" ~~
symbols: Object of class "character" ~~
product: Object of class "character" ~~
price.levels: Object of class "zoo" ~~
training.data: Object of class "Date" ~~
build.date: Object of class "Date" ~~
fitted.model: Object of class "ANY" ~~
model.data: Object of class "zoo" ~~
quantmod.version: Object of class "numeric" ~~
```

**Methods**

No methods defined with class "quantmod" in the signature.

**Author(s)**

Jeffrey A. Ryan

**Examples**

```
showClass("quantmod")
```

---

|               |  |
|---------------|--|
| quantmod.OHLC | <i>Create Open High Low Close Object</i> |
|---------------|--|

---

**Description**

Coerce an object with the appropriate columns to class quantmod.OHLC, which extends zoo.

**Usage**

```
as.quantmod.OHLC(x,
                  col.names = c("Open", "High",
                               "Low", "Close",
                               "Volume", "Adjusted"),
                  name = NULL, ...)
```

**Arguments**

|           |   |
|-----------|---|
| x         | object of class zoo   |
| col.names | suffix for columns  |
| name      | name to attach unique column suffixes to, defaults to the object name |
| ...       | additional arguments (unused)   |

**Details**

quantmod.OHLC is actually just a renaming of an object of class zoo, with the convention of NAME.Open, NAME.High, ... for the column names.

Additionally methods may be written to handle or check for the above conditions within other functions - as is the case within the **quantmod** package.

**Value**

An object of class c('quantmod.OHLC','zoo')

**Author(s)**

Jeffrey A. Ryan

**See Also**

[OHLC.Transformations](#), [getSymbols](#)

---

|           |                                    |
|-----------|------------------------------------|
| saveChart | <i>Save Chart to External File</i> |
|-----------|------------------------------------|

---

**Description**

Save selected chart to an external file.

**Usage**

```
saveChart(.type = "pdf", ..., dev = dev.cur())
```

**Arguments**

|       |                                 |
|-------|---------------------------------|
| .type | type of export. See Details.    |
| ...   | arguments to pass to device     |
| dev   | which device should be exported |

**Details**

This function wraps the base R function pdf, postscript, png, jpeg, and bitmap. The .type argument must specify which device driver is desired.

The currently active device is used if dev is missing. The result is an exact copy (within the device limits) of the chart specified.

The name of the resultant file is derived from the name of the chart, with the appropriate extension appended. (from .type). Specifying the appropriate device file/filename will override this name.

The caller may specify any parameters that are valid for the device called. Internally, effort is made to match the dimensions of the device being used to create the output file. User supplied dimensions will override this internal calculation.

**Value**

A file in the current directory (default) matching the type of the output requested.

**Note**

As this uses do.call internally to create the new output device, any device that makes use of R conventions should be acceptable as a value for .type

**Author(s)**

Jeffrey A. Ryan

**See Also**

[pdf](#) [png](#) [jpeg](#) [bitmap](#) [postscript](#)

**Examples**

```
## Not run:
getSymbols("AAPL")

chartSeries(AAPL)

require(TTR)
addBBands()

saveChart('pdf')
saveChart('pdf', width=13)

## End(Not run)
```

---

|                 |                                   |
|-----------------|-----------------------------------|
| setSymbolLookup | <i>Manage Symbol Lookup Table</i> |
|-----------------|-----------------------------------|

---

**Description**

Create and manage Symbol defaults lookup table within R session for use in `getSymbols` calls.

**Usage**

```
setSymbolLookup(...)
getSymbolLookup(Symbols=NULL)

saveSymbolLookup(file, dir="")
loadSymbolLookup(file, dir="")
```

**Arguments**

|         |                                      |
|---------|--------------------------------------|
| ...     | name=value pairs for symbol defaults |
| Symbols | name of symbol(s)                    |
| file    | filename                             |
| dir     | directory of filename                |

**Details**

Use of these functions allows the user to specify a set of default parameters for each Symbol to be loaded.

Different sources (e.g. yahoo, MySQL, csv), can be specified for each Symbol of interest. The sources must be *valid* `getSymbols` methods - see `getSymbols` for details on which methods are available, as well as how to add additional methods.

The argument list to `setSymbolLookup` is simply the unquoted name of the Symbol matched to the desired default source, or list of Symbol specific parameters.

For example, to signify that the stock data for Sun Microsystems (JAVA) should be downloaded from Yahoo! Finance, one would call `setSymbolLookup(JAVA='yahoo')` or `setSymbolLookup(JAVA=list(src='yahoo'))`

It is also possible to specify additional, possibly source specific, lookup details on a per symbol basis. These include an alternate naming convention (useful for sites like Yahoo! where certain non-traded symbols are prepended with a caret, or more correctly a circumflex accent. In that case one would specify `setSymbolLookup(DJI=list(name="^DJI",src="yahoo"))` as well as passed parameters like `dbname` and `password` for database sources. See the specific `getSymbols` function related to the source in question for more details of each implementation.

If a single named list is passed into the function without naming the list as a parameter, the names of this list will be presumed to be symbol names to be added to the current list of symbols.

All changes are made to the current list, and will persist *only* until the end of the session. To *always* use the same defaults it is necessary to call `setSymbolLookup` with the appropriate parameters from a startup file (e.g. `.Rprofile`) or to use `saveSymbolLookup` and `loadSymbolLookup` to save and restore lookup tables.

To unset a specific Symbol's defaults, simply assign NULL to the Symbol.

### Value

Called for its side effects, the function changes the options value for the specified Symbol through a call to `options(getSymbols.sources=...)`

### Note

Changes are *NOT* persistent across sessions, as the table is stored in the session options by default.

This *may* change to allow for an easier to manage process, as for now it is designed to minimize the clutter created during a typical session.

### Author(s)

Jeffrey A. Ryan

### See Also

[getSymbols](#), [options](#),

### Examples

```
setSymbolLookup(QQQQ='yahoo',DIA='MySQL')
getSymbolLookup('QQQQ')
getSymbolLookup(c('QQQQ','DIA'))

## Not run:
## Will download QQQQ from yahoo
## and load DIA from MySQL
getSymbols(c('QQQQ','DIA'))
```

```
## End(Not run)

## Use something like this to always retrieve
## from the same source

.First <- function() {
  require(quantmod,quietly=TRUE)
  quantmod::setSymbolLookup(JAVA="MySQL")
}

## OR

saveSymbolLookup()
loadSymbolLookup()
```

---

setTA

*Manage TA Argument Lists*


---

### Description

Used to manage the TA arguments used inside `chartSeries` calls.

### Usage

```
setTA(type = c("chartSeries", "barChart", "candleChart"))

listTA(dev)
```

### Arguments

|                   |  |
|-------------------|--|
| <code>type</code> | the function to apply defaults TAs to  |
| <code>dev</code>  | the device to display TA arguments for |

### Details

`setTA` and `unsetTA` provide a simple way to reuse the same TA arguments for multiple charts. By default all charting functions will be set to use the current chart's defaults.

It is important to note that the *current* device will be used to extract the list of TA arguments to apply. This is done with a call to `listTA` internally, and followed by calls to `setDefault`s of the appropriate functions.

An additional way to set default TA arguments for subsequent charts is via `setDefault`s. See the examples.

### Value

Called for its side-effect of setting the default TA arguments to `quantmod`'s charting functions.



**Note**

Using `setDefault`s directly will require the vector of default TA calls to be wrapped in a call to `substitute` to prevent unintended evaluations; *OR* a call to `listTA` to get the present TA arguments. This last approach is what `setTA` wraps.

**Author(s)**

Jeffrey A. Ryan

**See Also**

[chartSeries](#), [addTA](#)

**Examples**

```
## Not run:
listTA()
setTA()

# a longer way to accomplish the same
setDefault(chartSeries,TA=listTA())
setDefault(barCart,TA=listTA())
setDefault(candleChart,TA=listTA())

setDefault(chartSeries,TA=substitute(c(addVo(),addBBands())))

## End(Not run)
```

---

specifyModel

*Specify Model Formula For quantmod Process*

---

**Description**

Create a single reusable model specification for subsequent `buildModel` calls. An object of class `quantmod` is created that can be then be reused with different modelling methods and parameters. No data frame is specified, as data is retrieved from potentially multiple environments, and internal calls to `getSymbols`.

**Usage**

```
specifyModel(formula, na.rm=TRUE)
```

**Arguments**

|                      |   |
|----------------------|---|
| <code>formula</code> | an object of class <code>formula</code> (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under <code>Details</code> . |
| <code>na.rm</code>   | remove all incomplete rows.   |

**Details**

Models are specified through the standard formula mechanism.

As financial models may include a variety of financial and economic indicators, each differing in source, frequency, and/or class, a single mechanism to specify sources is included within a call to `specifyModel`. See `getModelData` for details of how this process works.

Currently, objects of class `quantmod.OHLC`, `zoo` and `ts` are supported within the model formula.

All symbols are first retrieved from the global environment, without inheritance. If an object is not found in the global environment, it is added to a list of objects to load through the `getSymbols` function. `getSymbols` retrieves each object specified by using information as to its location specified a priori via `setDefault`s or `setSymbolLookup`.

Internally all data is coerced to `zoo`, `data.frame`, or numeric classes.

**Value**

Returns an object of class `quantmod`. Use `modelData` to extract full data set as `zoo` object.

**Note**

It is possible to include any supported series in the formula by simply specifying the object's symbol. See *\*Details\** for a list of currently supported classes.

Use `getSymbols.skeleton` to create additional methods of data sourcing, e.g. from a proprietary data format or currently unimplemented source (Bloomberg, Oracle).

See `getSymbols.MySQL` and `getSymbols.yahoo` for examples of adding additional functionality

**Author(s)**

Jeffrey Ryan

**References**

quantmod.com <http://www.quantmod.com>

**See Also**

[getModelData](#), [getSymbols](#), [buildModel](#), [tradeModel](#), [formula](#) [setSymbolLookup](#)

**Examples**

```
## Not run:
# if QQQQ is not in the Global environment, an attempt will be made
# to retrieve it from the source specified with getSymbols.Default

specifyModel(Next(OpCl(QQQQ)) ~ Lag(OpHi(QQQQ),0:3) + Hi(DIA))

## End(Not run)
```

---

 TA *Add Technical Indicator to Chart*


---

**Description**

Functions to add technical indicators to a chart.

**Details**

The general mechanism to add technical analysis studies or overlays to a financial chart created with `chartSeries`.

Functionality marked with a '\*' is via the **TTR** package.

General TA charting tool functions:

- `addTA` add data as custom indicator
- `dropTA` remove technical indicator
- `moveTA` move a technical indicator
- `swapTA` swap two technical indicators

Current technical indicators include:

- `addADX` add Welles Wilder's Directional Movement Indicator\*
- `addATR` add Average True Range \*
- `addAroon` add Aroon Indicator \*
- `addAroonOsc` add Aroon Oscillator \*
- `addBBands`: add Bollinger Bands \*
- `addCCI` add Commodity Channel Index \*
- `addCMF` add Chaiken Money Flow \*
- `addChAD` add Chaiken Accumulation Distribution Line \*
- `addChVol` add Chaiken Volatility \*
- `addCMO` add Chande Momentum Oscillator \*
- `addDEMA` add Double Exponential Moving Average \*
- `addDPO` add Detrended Price Oscillator \*
- `addEMA` add Exponential Moving Average \*
- `addEMV` add Arm's Ease of Movement \*
- `addEnvelope` add Moving Average Envelope
- `addEVWMA` add Exponential Volume Weighted Moving Average \*
- `addExpiry` add options or futures expiration lines
- `addKST` add Know Sure Thing \*
- `addLines` add line(s)

- addMACD:add Moving Average Convergence Divergence \*
- addMFIadd Money Flow Index \*
- addMomentumadd Momentum \*
- addOBVadd On-Balance Volume \*
- addPointsadd point(s)
- addROC:add Rate of Change \*
- addRSIadd Relative Strength Indicator \*
- addSARadd Parabolic SAR \*
- addSMAadd Simple Moving Average \*
- addSMIadd Stochastic Momentum Index \*
- addTDIadd Trend Direction Index \*
- addTRIXadd Triple Smoothed Exponential Oscillator \*
- addVoadd Volume if available
- addVolatilityadd volatility \*
- addWMAadd Weighted Moving Average \*
- addWPRadd Williams Percent R \*
- addZigZagadd Zig Zag \*
- addZLEMAadd ZLEMA \*

See the individual functions for specific implementation and argument details. Details of the underlying TTR implementations can be found in **TTR**.

The primary changes between the add\*\*\* version of an indicator and the **TTR** base function is the absence of the data argument in the former.

Notable additions include `on, with.col`.

### Value

Called for its side effects, an object to class `chobTA` will be returned invisibly. If called from the R command line the method will draw the appropriate indicator on the current chart.

### Note

Calling any of the above methods from within a function or script will generally require them to be wrapped in a `plot` call as they rely on the context of the call to initiate the actual charting addition.

### Author(s)

Jeffrey A. Ryan

### References

Josh Ulrich - TTR package

---

|            |   |
|------------|---|
| tradeModel | <i>Simulate Trading of Fitted quantmod Object</i> |
|------------|---|

---

### Description

Simulated trading of fitted quantmod object. Given a fitted model, tradeModel calculates the signal generated over a given historical period, then applies specified trade.rule to calculate and return a tradeLog object. Additional methods can then be called to evaluate the performance of the model's strategy.

### Usage

```
tradeModel(x,
  signal.threshold = c(0, 0),
  leverage = 1,
  return.model = TRUE,
  plot.model = FALSE,
  trade.dates = NULL,
  exclude.training = TRUE,
  ret.type = c("weeks", "months", "quarters", "years"),
  ...)
```

### Arguments

|                  |   |
|------------------|---|
| x                | a quantmod object from buildModel   |
| signal.threshold | a numeric vector describing simple lower and upper thresholds before trade occurs |
| leverage         | amount of leverage to apply - currently a constant                                |
| return.model     | should the full model be returned?  |
| plot.model       | plot the model?   |
| trade.dates      | specific trade interval - defaults to full dataset                                |
| exclude.training | exclude the period trained on?  |
| ret.type         | a table of period returns   |
| ...              | additional parameters needed by the underlying modelling function, if any         |

### Details

Still highly experimental and changing. The purpose is to apply a newly constructed model from buildModel to a new dataset to investigate the model's trading potential.

At present all parameters are very basic. The near term changes include allowing for a trade.rule argument to allow for a dynamic trade rule given a set of signals. Additionally the application of variable leverage and costs will become part of the final structure.

Any suggestions as to inclusions or alterations are appreciated and should be directed to the maintainer of the package.

**Value**

A quantmodResults object

**Author(s)**

Jeffrey A. Ryan

**See Also**

[specifyModel](#) [buildModel](#)

**Examples**

```
## Not run:
m <- specifyModel(Next(OpCl(QQQQ)) ~ Lag(OpHi(QQQQ)))
m.built <- buildModel(m,method='rpart',training.per=c('2007-01-01','2007-04-01'))

tradeModel(m.built)
tradeModel(m.built,leverage=2)

## End(Not run)
```

---

zoomChart

*Change Zoom Level Of Current Chart*

---

**Description**

Using `xts` style date subsetting, zoom into or out of the current chart.

**Usage**

```
zoom(n=1, eps=2)
zoomChart(subset, yrange=NULL)
```

**Arguments**

|                     |   |
|---------------------|---|
| <code>n</code>      | the number of interactive view changes per call                     |
| <code>eps</code>    | the distance between clicks to be considered a valid subset request |
| <code>subset</code> | a valid subset string   |
| <code>yrange</code> | override y-scale  |

## Details

These function allow for viewing of specific areas of a chart produced by `chartSeries` by simply specifying the dates of interest

`zoom` is an interactive chart version of `zoomChart` which utilizes the standard R device interaction tool `locator` to estimate the subset desired. This estimate is then passed to `zoomChart` for actual redrawing. At present it is quite experimental in its interface and arguments. Its usage entails a call to `zoom()` followed by the selection of the leftmost and rightmost points desired in the newly zoomed chart. This selection is accomplished by the user left-clicking each extreme point. Two click are required to determine the level of zooming. Double clicking will reset the chart to the full data range. The arguments and internal working of this function are likely to change dramatically in future releases, though its use will likely remain.

Standard format for the subset argument is the same as the subsetting for `xts` objects, which is how the data is stored internally for rendering.

Calling `zoomChart` with no arguments (NULL) resets the chart to the original data.

Examples include `'2007'` for all of the year 2007, `'2007::2008'` for years 2007 through 2008, `'::2007'` for all data from the beginning of the set to the end of 2007, `'2007::'` all data from the beginning of 2007 through the end of the data. For specifics regarding the level of detail and internal interpretation please see `[.xts`

## Value

This function is called for its side effect - notably changing the perspective of the current chart, and changing its formal subset level. The underlying data attached to the chart is left unchanged.

## Author(s)

Jeffrey A. Ryan

## See Also

[chartSeries](#)

## Examples

```
## Not run:
data(sample_matrix)
chartSeries(sample_matrix)
zoomChart('2007-04::')
zoomChart()

zoom() # interactive example

## End(Not run)
```

# Index

- \*Topic **IO**
  - getQuote, [45](#)
- \*Topic **aplot**
  - newTA, [73](#)
  - saveChart, [85](#)
  - TA, [91](#)
- \*Topic **classes**
  - chob-class, [28](#)
  - chobTA-class, [29](#)
  - quantmod-class, [83](#)
- \*Topic **datagen**
  - buildData, [19](#)
  - Lag, [70](#)
  - Next, [76](#)
- \*Topic **datasets**
  - getModelData, [43](#)
  - getSymbols.oanda, [59](#)
- \*Topic **data**
  - getQuote, [45](#)
  - getSymbols, [48](#)
  - getSymbols.csv, [52](#)
  - getSymbols.FRED, [53](#)
  - getSymbols.google, [55](#)
  - getSymbols.MySQL, [57](#)
  - getSymbols.rda, [61](#)
  - getSymbols.yahoo, [64](#)
  - getSymbols.yahooj, [66](#)
  - modelData, [71](#)
  - quantmod.OHLC, [84](#)
- \*Topic **device**
  - saveChart, [85](#)
- \*Topic **dplot**
  - chart\_Series, [27](#)
  - newTA, [73](#)
  - saveChart, [85](#)
- \*Topic **hplot**
  - newTA, [73](#)
- \*Topic **misc**
  - adjustOHLC, [16](#)
  - attachSymbols, [17](#)
  - create.binding, [30](#)
  - findPeaks, [34](#)
  - Lag, [70](#)
  - Next, [76](#)
- \*Topic **models**
  - buildModel, [21](#)
  - fittedModel, [35](#)
  - specifyModel, [89](#)
  - tradeModel, [93](#)
- \*Topic **package**
  - quantmod-package, [3](#)
- \*Topic **ts**
  - Lag, [70](#)
- \*Topic **utilities**
  - addADX, [4](#)
  - addBBands, [5](#)
  - addCCI, [6](#)
  - addExpiry, [7](#)
  - addMA, [8](#)
  - addMACD, [9](#)
  - addROC, [10](#)
  - addRSI, [11](#)
  - addSAR, [12](#)
  - addSMI, [13](#)
  - addVo, [14](#)
  - addWPR, [15](#)
  - chartSeries, [22](#)
  - chartTheme, [25](#)
  - Defaults, [31](#)
  - Delt, [33](#)
  - getDividends, [37](#)
  - getFinancials, [39](#)
  - getFX, [40](#)
  - getMetals, [42](#)
  - getOptionChain, [44](#)
  - getSplits, [47](#)
  - getSymbols.SQLite, [62](#)
  - has.OHLC, [67](#)



- internal-quantmod, 69
- is.quantmod, 69
- modelData, 71
- modelSignal, 72
- OHLC.Transformations, 78
- options.expiry, 80
- periodReturn, 81
- setSymbolLookup, 86
- setTA, 88
- zoomChart, 94
- .quantmodEnv (internal-quantmod), 69
- Ad (OHLC.Transformations), 78
- add\_axis (chart\_Series), 27
- add\_BBands (chart\_Series), 27
- add\_DEMA (addMA), 8
- add\_EMA (addMA), 8
- add\_EVWMA (addMA), 8
- add\_GMMA (addMA), 8
- add\_MACD (chart\_Series), 27
- add\_RSI (chart\_Series), 27
- add\_Series (chart\_Series), 27
- add\_SMA (addMA), 8
- add\_SMI (chart\_Series), 27
- add\_TA (chart\_Series), 27
- add\_VMA (addMA), 8
- add\_Vo (chart\_Series), 27
- add\_VWAP (addMA), 8
- add\_WMA (addMA), 8
- addADX, 4
- addAroon (TA), 91
- addAroonOsc (TA), 91
- addATR (TA), 91
- addBBands, 5
- addCCI, 6
- addChAD (TA), 91
- addChVol (TA), 91
- addCLV (TA), 91
- addCMF (TA), 91
- addCMO (TA), 91
- addDEMA (addMA), 8
- addDPO (TA), 91
- addEMA (addMA), 8
- addEMV (TA), 91
- addEnvelope (TA), 91
- addEVWMA (addMA), 8
- addExpiry, 7, 81
- addKST (TA), 91
- addLines (TA), 91
- addMA, 8
- addMACD, 9
- addMFI (TA), 91
- addMomentum (TA), 91
- addOBV (TA), 91
- addPoints (TA), 91
- addROC, 10
- addRSI, 11
- addSAR, 12
- addShading (internal-quantmod), 69
- addSMA (addMA), 8
- addSMI, 13
- addTA, 4–7, 9–15, 25, 30, 89
- addTA (newTA), 73
- addTDI (TA), 91
- addTRIX (TA), 91
- addVo, 14
- addVolatility (TA), 91
- addWMA (addMA), 8
- addWPR, 15
- addZigZag (TA), 91
- addZLEMA (addMA), 8
- adjustOHLC, 16
- allReturns (periodReturn), 81
- annualReturn (periodReturn), 81
- anova.quantmod (fittedModel), 35
- as.quantmod.OHLC (quantmod.OHLC), 84
- attachSymbols, 17
- axTicksByTime2 (chart\_Series), 27
- axTicksByValue (chart\_Series), 27
- barChart (chartSeries), 22
- bitmap, 86
- buildData, 19
- buildModel, 21, 37, 44, 90, 94
- candleChart (chartSeries), 22
- chart\_pars (chart\_Series), 27
- chart\_Series, 27
- chart\_theme (chart\_Series), 27
- chartSeries, 22, 26, 29, 75, 89, 95
- chartShading (internal-quantmod), 69
- chartTA (newTA), 73
- chartTheme, 25, 25
- chob, 30, 75
- chob-class, 28
- chobTA, 29, 75
- chobTA-class, 29
- Cl (OHLC.Transformations), 78

- ClCl (OHLC.Transformations), 78
- coef.quantmod (fittedModel), 35
- coefficients.quantmod (fittedModel), 35
- create.binding, 30
- current.chob (chartSeries), 22
- dailyReturn (periodReturn), 81
- Defaults, 31
- Delt, 33
- dropTA (TA), 91
- findPeaks, 34
- findValleys (findPeaks), 34
- fitted.quantmod (fittedModel), 35
- fitted.values.quantmod (fittedModel), 35
- fittedModel, 35
- fittedModel<- (fittedModel), 35
- fittedModel<- , quantmod-method  
(quantmod-class), 83
- fittedModel<--methods (quantmod-class),  
83
- flushSymbols (attachSymbols), 17
- formula, 90
- formula.quantmod (fittedModel), 35
- futures.expiry (options.expiry), 80
- getDefault (Defaults), 31
- getDividends, 17, 37, 48
- getFin (getFinancials), 39
- getFinancials, 39
- getFX, 40, 51
- getMetals, 42, 51
- getModelData, 43, 51, 72, 90
- getOptionChain, 44
- getPrice (OHLC.Transformations), 78
- getQuote, 45
- getSplits, 17, 47
- getSymbolLookup (setSymbolLookup), 86
- getSymbols, 20, 25, 38, 41, 43, 44, 46, 48, 48,  
53, 54, 56, 58, 60, 62, 64, 65, 67, 82,  
85, 87, 90
- getSymbols.csv, 51, 52
- getSymbols.FRED, 51, 53, 60
- getSymbols.google, 51, 55
- getSymbols.MySQL, 57
- getSymbols.mysql (getSymbols.MySQL), 57
- getSymbols.oanda, 41, 43, 51, 59
- getSymbols.rda, 61
- getSymbols.RData, 51
- getSymbols.RData (getSymbols.rda), 61
- getSymbols.SQLite, 62
- getSymbols.yahoo, 17, 51, 64
- getSymbols.yahooj, 66
- has.Ad (has.OHLC), 67
- has.Ask (has.OHLC), 67
- has.Bid (has.OHLC), 67
- has.Cl (has.OHLC), 67
- has.Hi (has.OHLC), 67
- has.HLC (has.OHLC), 67
- has.Lo (has.OHLC), 67
- has.OHLC, 67
- has.OHLCV (has.OHLC), 67
- has.Op (has.OHLC), 67
- has.Price (has.OHLC), 67
- has.Qty (has.OHLC), 67
- has.Trade (has.OHLC), 67
- has.Vo (has.OHLC), 67
- Hi (OHLC.Transformations), 78
- HiCl (OHLC.Transformations), 78
- HLC (OHLC.Transformations), 78
- importDefaults (Defaults), 31
- internal-quantmod, 69
- is.BBO (has.OHLC), 67
- is.HLC (has.OHLC), 67
- is.OHLC (has.OHLC), 67
- is.OHLCV (has.OHLC), 67
- is.quantmod, 69
- is.quantmodResults (is.quantmod), 69
- is.TBBO (has.OHLC), 67
- jpeg, 86
- Lag, 70, 77
- lag, 71
- lineChart (chartSeries), 22
- listTA (setTA), 88
- Lo (OHLC.Transformations), 78
- load, 62
- loadSymbolLookup (setSymbolLookup), 86
- loadSymbols (getSymbols), 48
- LoCl (OHLC.Transformations), 78
- logLik.quantmod (fittedModel), 35
- LoHi (OHLC.Transformations), 78
- matchChart (chartSeries), 22
- modelData, 20, 44, 71

- modelSignal, 72
- monthlyReturn (periodReturn), 81
- moveTA (TA), 91
- new.replot (chart\_Series), 27
- newTA, 73
- Next, 76
- oanda.currencies (getSymbols.oanda), 59
- OHLC (OHLC.Transformations), 78
- OHLC.Transformations, 69, 78, 85
- OHLCV (OHLC.Transformations), 78
- Op (OHLC.Transformations), 78
- OpCl, 34
- OpCl (OHLC.Transformations), 78
- OpHi (OHLC.Transformations), 78
- OpLo (OHLC.Transformations), 78
- OpOp, 34
- OpOp (OHLC.Transformations), 78
- options, 33, 87
- options.expiry, 80
- pdf, 86
- peak (findPeaks), 34
- periodReturn, 81
- plot.quantmod (fittedModel), 35
- png, 86
- postscript, 86
- quantmod, 37
- quantmod (quantmod-package), 3
- quantmod-class, 83
- quantmod-package, 3
- quantmod.OHLC, 68, 69, 84
- quantmodenv (quantmod-package), 3
- quantmodResults-class (quantmod-class), 83
- quantmodReturn-class (quantmod-class), 83
- quarterlyReturn (periodReturn), 81
- read.csv, 53
- reChart (chartSeries), 22
- removeSymbols (getSymbols), 48
- resid.quantmod (fittedModel), 35
- residuals.quantmod (fittedModel), 35
- saveChart, 85
- saveSymbolLookup (setSymbolLookup), 86
- saveSymbols (getSymbols), 48
- seriesAccel (OHLC.Transformations), 78
- seriesDecel (OHLC.Transformations), 78
- seriesDecr (OHLC.Transformations), 78
- seriesHi (OHLC.Transformations), 78
- seriesIncr (OHLC.Transformations), 78
- seriesLo (OHLC.Transformations), 78
- setDefault (Defaults), 31
- setSymbolLookup, 51, 53, 54, 56, 58, 62, 65, 67, 86, 90
- setTA, 25, 88
- show, chobTA-method (chobTA-class), 29
- show, quantmod-method (quantmod-class), 83
- show, quantmodResults-method (quantmod-class), 83
- show, tradeLog-method (quantmod-class), 83
- showSymbols (getSymbols), 48
- specifyModel, 20–22, 44, 48, 51, 70, 72, 77, 79, 89, 94
- standardQuote (getQuote), 45
- summary, quantmod-method (quantmod-class), 83
- swapTA (TA), 91
- TA, 75, 91
- tradeLog-class (quantmod-class), 83
- tradeModel, 22, 70, 73, 90, 93
- unsetDefaults (Defaults), 31
- unsetTA (setTA), 88
- valley (findPeaks), 34
- vcov.quantmod (fittedModel), 35
- viewFin (getFinancials), 39
- viewFinancials (getFinancials), 39
- Vo (OHLC.Transformations), 78
- weeklyReturn (periodReturn), 81
- yahooQF (getQuote), 45
- yahooQuote.EOD (getQuote), 45
- yearlyReturn (periodReturn), 81
- zoom (zoomChart), 94
- zoom\_Chart (chart\_Series), 27
- zoomChart, 94
- zoom (zoomChart), 94