

Package ‘queueing’

May 29, 2017

Version 0.2.10

Date 2017-05-13

Title Analysis of Queueing Networks and Models

Author Pedro Canadilla

Maintainer Pedro Canadilla <pedro.canadilla@gmail.com>

Depends R (>= 2.11.1)

Suggests

Description

It provides versatile tools for analysis of birth and death based Markovian Queueing Models and Single and Multiclass Product-Form Queueing Networks.

It imple-

ments M/M/1, M/M/c, M/M/Infinite, M/M/1/K, M/M/c/K, M/M/c/c, M/M/1/K/K, M/M/c/K/K, M/M/c/K/m, M/M/Infinite/K, Multiple Channel Open Jackson Networks, Multiple Channel Closed Jackson Networks, Single Channel Multiple Class Open Networks, Single Channel Multiple Class Closed Networks and Single Channel Multiple Class Mixed Networks.

Also it provides a B-Erlang, C-Erlang and Engset calculators.

This work is dedicated to the memory of D. Sixto Rios Insua.

License GPL-2

Copyright Pedro Canadilla

URL <https://www.r-project.org>

NeedsCompilation no

Repository CRAN

Date/Publication 2017-05-29 06:58:57 UTC

R topics documented:

queueing-package	8
B_erlang	10
CheckInput	11
CheckInput.i_CJN	12
CheckInput.i_MCCN	13

CheckInput.i_MCMN	14
CheckInput.i_MCON	15
CheckInput.i_MM1	16
CheckInput.i_MM1K	17
CheckInput.i_MM1KK	18
CheckInput.i_MMC	19
CheckInput.i_MMCC	20
CheckInput.i_MMCK	21
CheckInput.i_MMCKK	22
CheckInput.i_MMCKM	23
CheckInput.i_MMInf	24
CheckInput.i_MMInfKK	25
CheckInput.i_OJN	26
CompareQueueingModels	27
C_erlang	28
Engset	29
Inputs	29
Inputs.o_CJN	30
Inputs.o_MCCN	32
Inputs.o_MCMN	33
Inputs.o_MCON	34
Inputs.o_MM1	35
Inputs.o_MM1K	36
Inputs.o_MM1KK	37
Inputs.o_MMC	38
Inputs.o_MMCC	39
Inputs.o_MMCK	40
Inputs.o_MMCKK	41
Inputs.o_MMCKM	42
Inputs.o_MMInf	43
Inputs.o_MMInfKK	44
Inputs.o_OJN	45
L	46
L.o_CJN	47
L.o_MCCN	48
L.o_MCMN	49
L.o_MCON	51
L.o_MM1	52
L.o_MM1K	53
L.o_MM1KK	54
L.o_MMC	55
L.o_MMCC	56
L.o_MMCK	57
L.o_MMCKK	58
L.o_MMCKM	59
L.o_MMInf	60
L.o_MMInfKK	61
L.o_OJN	62

Lc	63
Lc.o_MCCN	64
Lc.o_MCMN	65
Lc.o_MCON	66
Lck	67
Lck.o_MCCN	69
Lck.o_MCMN	70
Lck.o_MCON	71
Lk	72
Lk.o_CJN	73
Lk.o_MCCN	75
Lk.o_MCMN	76
Lk.o_MCON	77
Lk.o_OJN	78
Lq	79
Lq.o_MM1	80
Lq.o_MM1K	81
Lq.o_MM1KK	82
Lq.o_MMC	83
Lq.o_MMCC	84
Lq.o_MMCK	85
Lq.o_MMCKK	86
Lq.o_MMCKM	87
Lq.o_MMInf	88
Lq.o_MMInfKK	89
Lqq	90
Lqq.o_MM1	91
Lqq.o_MM1K	92
Lqq.o_MM1KK	93
Lqq.o_MMC	94
Lqq.o_MMCC	95
Lqq.o_MMCK	96
Lqq.o_MMCKK	97
Lqq.o_MMCKM	98
Lqq.o_MMInf	99
Lqq.o_MMInfKK	100
NewInput.CJN	101
NewInput.MCCN	103
NewInput.MCMN	104
NewInput.MCON	106
NewInput.MM1	107
NewInput.MM1K	108
NewInput.MM1KK	109
NewInput.MMC	110
NewInput.MMCC	111
NewInput.MMCK	112
NewInput.MMCKK	113
NewInput.MMCKM	114

NewInput.MMInf	115
NewInput.MMInfKK	116
NewInput.OJN	117
Pn	119
Pn.o_MM1	120
Pn.o_MM1K	121
Pn.o_MM1KK	122
Pn.o_MMC	123
Pn.o_MMCC	124
Pn.o_MMCK	125
Pn.o_MMCKK	126
Pn.o_MMCKM	127
Pn.o_MMInf	128
Pn.o_MMInfKK	129
Pn.o_OJN	130
print.summary.o_CJN	131
print.summary.o_MCCN	132
print.summary.o_MCMN	133
print.summary.o_MCON	135
print.summary.o_MM1	136
print.summary.o_MM1K	137
print.summary.o_MM1KK	138
print.summary.o_MMC	139
print.summary.o_MMCC	140
print.summary.o_MMCK	141
print.summary.o_MMCKK	142
print.summary.o_MMCKM	143
print.summary.o_MMInf	144
print.summary.o_MMInfKK	145
print.summary.o_OJN	146
QueueingModel	147
QueueingModel.i_CJN	148
QueueingModel.i_MCCN	149
QueueingModel.i_MCMN	150
QueueingModel.i_MCON	151
QueueingModel.i_MM1	152
QueueingModel.i_MM1K	153
QueueingModel.i_MM1KK	154
QueueingModel.i_MMC	155
QueueingModel.i_MMCC	156
QueueingModel.i_MMCK	157
QueueingModel.i_MMCKK	158
QueueingModel.i_MMCKM	159
QueueingModel.i_MMInf	160
QueueingModel.i_MMInfKK	161
QueueingModel.i_OJN	162
Report	163
Report.o_CJN	164

Report.o_MCCN	165
Report.o_MCMN	166
Report.o_MCON	167
Report.o_MM1	168
Report.o_MM1K	169
Report.o_MM1KK	170
Report.o_MMC	171
Report.o_MMCC	172
Report.o_MMCK	173
Report.o_MMCKK	174
Report.o_MMCKM	175
Report.o_MMInf	176
Report.o_MMInfKK	177
Report.o_OJN	178
RO	179
RO.o_MM1	180
RO.o_MM1K	181
RO.o_MM1KK	182
RO.o_MMC	183
RO.o_MMCC	184
RO.o_MMCK	185
RO.o_MMCKK	186
RO.o_MMCKM	187
RO.o_MMInf	188
RO.o_MMInfKK	189
ROck	190
ROck.o_MCCN	191
ROck.o_MCMN	192
ROck.o_MCON	193
ROk	194
ROk.o_CJN	196
ROk.o_MCCN	197
ROk.o_MCMN	198
ROk.o_MCON	199
ROk.o_OJN	200
SP	201
SP.o_MM1KK	202
summary.o_CJN	203
summary.o_MCCN	204
summary.o_MCMN	206
summary.o_MCON	207
summary.o_MM1	208
summary.o_MM1K	209
summary.o_MM1KK	210
summary.o_MMC	211
summary.o_MMCC	212
summary.o_MMCK	213
summary.o_MMCKK	214

summary.o_MMCKM	215
summary.o_MMInf	216
summary.o_MMInfKK	217
summary.o_OJN	218
Throughput	219
Throughput.o_CJN	220
Throughput.o_MCCN	221
Throughput.o_MCMN	222
Throughput.o_MCON	223
Throughput.o_MM1	224
Throughput.o_MM1K	225
Throughput.o_MM1KK	226
Throughput.o_MMC	227
Throughput.o_MMCC	228
Throughput.o_MMCK	229
Throughput.o_MMCKK	230
Throughput.o_MMCKM	231
Throughput.o_MMInf	232
Throughput.o_MMInfKK	233
Throughput.o_OJN	234
Throughputc	235
Throughputc.o_MCCN	236
Throughputc.o_MCMN	237
Throughputc.o_MCON	239
Throughputck	240
Throughputck.o_MCCN	241
Throughputck.o_MCMN	242
Throughputck.o_MCON	243
Throughputcn	245
Throughputcn.o_MCCN	246
Throughputk	247
Throughputk.o_CJN	248
Throughputk.o_MCCN	249
Throughputk.o_MCMN	251
Throughputk.o_MCON	252
Throughputk.o_OJN	253
Throughputn	254
Throughputn.o_CJN	255
VN	257
VN.o_MM1	258
VN.o_MM1K	259
VN.o_MM1KK	260
VN.o_MMC	261
VN.o_MMCC	262
VN.o_MMCK	263
VN.o_MMCKK	264
VN.o_MMCKM	265
VN.o_MMInf	266

VN.o_MMInfKK	267
VNq	268
VNq.o_MM1	269
VNq.o_MM1K	270
VNq.o_MM1KK	271
VNq.o_MMC	272
VNq.o_MMCC	273
VNq.o_MMCK	274
VNq.o_MMCKK	275
VNq.o_MMCKM	276
VNq.o_MMInf	277
VNq.o_MMInfKK	278
VT	279
VT.o_MM1	280
VT.o_MM1K	281
VT.o_MM1KK	282
VT.o_MMC	283
VT.o_MMCC	284
VT.o_MMInf	285
VT.o_MMInfKK	286
VTq	287
VTq.o_MM1	288
VTq.o_MM1K	289
VTq.o_MM1KK	290
VTq.o_MMC	291
VTq.o_MMCC	292
VTq.o_MMCK	293
VTq.o_MMCKK	294
VTq.o_MMInf	295
VTq.o_MMInfKK	296
W	297
W.o_CJN	298
W.o_MCCN	299
W.o_MCMN	300
W.o_MCON	301
W.o_MM1	302
W.o_MM1K	303
W.o_MM1KK	304
W.o_MMC	305
W.o_MMCC	306
W.o_MMCK	307
W.o_MMCKK	308
W.o_MMCKM	309
W.o_MMInf	310
W.o_MMInfKK	311
W.o_OJN	312
Wc	313
Wc.o_MCCN	314

Wc.o_MCMN	315
Wc.o_MCON	316
Wck	318
Wck.o_MCCN	319
Wck.o_MCMN	320
Wck.o_MCON	321
Wk	322
Wk.o_CJN	323
Wk.o_MCCN	325
Wk.o_MCMN	326
Wk.o_MCON	327
Wk.o_OJN	328
Wq	329
Wq.o_MM1	330
Wq.o_MM1K	331
Wq.o_MM1KK	332
Wq.o_MMC	333
Wq.o_MMCC	334
Wq.o_MMCK	335
Wq.o_MMCKK	336
Wq.o_MMCKM	337
Wq.o_MMInf	338
Wq.o_MMInfKK	339
Wqq	340
Wqq.o_MM1	341
Wqq.o_MM1K	342
Wqq.o_MM1KK	343
Wqq.o_MMC	344
Wqq.o_MMCC	345
Wqq.o_MMCK	346
Wqq.o_MMCKK	347
Wqq.o_MMCKM	348
Wqq.o_MMInf	349
Wqq.o_MMInfKK	350
Wws	351
Wws.o_MM1KK	352

Index**354**

Description

It provides a versatile tool for analysis of birth and death based Markovian Queueing Models and Single and Multiclass Product-Form Queueing Networks.

It implements the following basic markovian models:

M/M/1, M/M/c, M/M/Infinite,
 M/M/1/K, M/M/c/K, M/M/c/c,
 M/M/1/K/K, M/M/c/K/K, M/M/c/K/m, M/M/Infinite/K/K

It also solves the following types of networks:

- Multiple Channel Open Jackson Networks.
- Multiple Channel Closed Jackson Networks.
- Single Channel Multiple Class Open Networks.
- Single Channel Multiple Class Closed Networks
- Single Channel Multiple Class Mixed Networks

Also it provides B-Erlang, C-Erlang and Engset calculators.

This work is dedicated to the memory of D. Sixto Rios Insua.

Details

All models are used in the same way:

1. Create inputs calling the appropriate *NewInput.model*. For example, `x <- NewInput.MM1(lambda=0.25, mu=1, n=10)` for a M/M/1 model. To know the exact acronym model to use for *NewInput* function, you can search the html help or write `help.search("NewInput")` at the command line.
2. Optionally, as a help for creating the inputs, the `CheckInput(x)` function can be called
3. Solve the model calling `y <- QueueingModel(x)`. In this step, the `CheckInput(x)` will be called. That is the reason that the previous step is optional
4. Finally, you can get a performance value as `W(y)`, `Wq(y)` or a report of the principals performance values calling `summary(y)`

See the examples for more detailed information of the use.

Author(s)

Author, Maintainer and Copyright: Pedro Canadilla <pedro.canadilla@gmail.com>

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

Examples

```
## M/M/1 model
summary(QueueingModel(NewInput.MM1(lambda=1/4, mu=1/3, n=0)))

## M/M/1/K model
summary(QueueingModel(NewInput.MM1K(lambda=1/4, mu=1/3, k=3)))
```

B_erlang

Returns the probability that all servers are busy

Description

Returns the probability that all servers are busy

Usage

```
B_erlang(c=1, u=0)
```

Arguments

c	numbers of servers
u	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability that all servers are busy

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Jagerman1974] Jagerman, D. L. (1974).
Some properties of the Erlang loss function.
Bell System Tech. J. (53), 525-551

See Also[C_erlang](#)**Examples**

```
## two servers
B_erlang(2, 0.5/0.7)
```

CheckInput	<i>Generic S3 method to check the params of a queueing model (or network)</i>
------------	---

Description

Generic S3 method to check the params of a queueing model (or network)

Usage

```
CheckInput(x, ...)
```

Arguments

x	a object of class <code>i_MM1</code> , <code>i_MMC</code> , <code>i_MM1K</code> , <code>i_MMCK</code> , <code>i_MM1KK</code> , <code>i_MMCKK</code> , <code>i_MMCC</code> , <code>i_MMCKM</code> , <code>i_MMInfKK</code> , <code>i_MMInf</code> , <code>i_OJN</code>
...	additional arguments

Details

Generic S3 method to check the params of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

```
CheckInput.i_MM1  
CheckInput.i_MMC  
CheckInput.i_MM1K  
CheckInput.i_MMCK  
CheckInput.i_MM1KK  
CheckInput.i_MMCKK  
CheckInput.i_MMCC  
CheckInput.i_MMCKM  
CheckInput.i_MMInfKK  
CheckInput.i_MMInf  
CheckInput.i_OJN
```

Examples

```
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Check the inputs  
CheckInput(i_mm1)
```

CheckInput.i_CJN

Check the input params of a Closed Jackson Network

Description

Check the input params of a Closed Jackson Network

Usage

```
## S3 method for class 'i_CJN'  
CheckInput(x, ...)
```

Arguments

```
x          a object of class i_CJN  
...       additional arguments
```

Details

Check the input params of a Closed Jackson Network. The inputs params are created calling previously the [NewInput.CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

CheckInput(cjn1)
```

CheckInput.i_MCCN

Check the input params of a MultiClass Closed Network

Description

Check the input params of a MultiClass Closed Network

Usage

```
## S3 method for class 'i_MCCN'
CheckInput(x, ...)
```

Arguments

x a object of class i_MCCN
... additional arguments

Details

Check the input params of a MultiClass Closed Network. The inputs params are created calling previously the [NewInput.MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

CheckInput(i_MCCN1)
```

CheckInput.i_MCMN

Check the input params of a MultiClass Mixed Network

Description

Check the input params of a MultiClass Mixed Network

Usage

```
## S3 method for class 'i_MCMN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCMN
...	additional arguments

Details

Check the input params of a MultiClass Mixed Network. The inputs params are created calling previously the [NewInput.MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

CheckInput(i_mcmn1)
```

CheckInput.i_MCON

Check the input params of a MultiClass Open Network

Description

Check the input params of a MultiClass Open Network

Usage

```
## S3 method for class 'i_MCON'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCON
...	additional arguments

Details

Check the input params of a MultiClass Open Network. The inputs params are created calling previously the [NewInput.MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

CheckInput(i_mcon1)
```

CheckInput.i_MM1

Checks the input params of a M/M/1 queueing model

Description

Checks the input params of a M/M/1 queueing model

Usage

```
## S3 method for class 'i_MM1'
CheckInput(x, ...)
```

Arguments

x a object of class i_MM1
 ... additional arguments

Details

Checks the input params of a M/M/1 queueing model. The inputs params are created calling previously the [NewInput.MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Check the inputs  
CheckInput(i_mm1)
```

CheckInput.i_MM1K	<i>Checks the input params of a M/M/1/K queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/1/K queueing model

Usage

```
## S3 method for class 'i_MM1K'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MM1K
...	additional arguments

Details

Checks the input params of a M/M/1/K queueing model. The inputs params are created calling previously the [NewInput.MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## check the parameters  
CheckInput(i_mm1k)
```

CheckInput.i_MM1KK *Checks the input params of a M/M/1/K/K queueing model*

Description

Checks the input params of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'i_MM1KK'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MM1KK
...	additional arguments

Details

Checks the input params of a M/M/1/K/K queueing model. The inputs params are created calling previously the [NewInput.MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## check the parameters
CheckInput(i_mm1kk)
```

CheckInput.i_MMC	<i>Checks the input params of a M/M/c queueing model</i>
------------------	--

Description

Checks the input params of a M/M/c queueing model

Usage

```
## S3 method for class 'i_MMC'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMC
...	additional arguments

Details

Checks the input params of a M/M/c queueing model. The inputs params are created calling previously the [NewInput.MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## check the parameters
CheckInput(i_mmc)
```

CheckInput.i_MMCC	<i>Checks the input params of a M/M/c/c queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/c/c queueing model

Usage

```
## S3 method for class 'i_MMCC'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCC
...	aditional arguments

Details

Checks the input params of a M/M/c/c queueing model. The inputs params are created calling previously the [NewInput.MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## check the parameters
CheckInput(i_mmcc)
```

CheckInput.i_MMCK	<i>Checks the input params of a M/M/c/K queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/c/K queueing model

Usage

```
## S3 method for class 'i_MMCK'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCK
...	additional arguments

Details

Checks the input params of a M/M/c/K queueing model. The inputs params are created calling previously the [NewInput.MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Check the inputs
CheckInput(i_mmck)
```

CheckInput.i_MMCKK *Checks the input params of a M/M/c/K/K queueing model*

Description

Checks the input params of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'i_MMCKK'
CheckInput(x, ...)
```

Arguments

```
x                    a object of class i_MMCKK
...                  additional arguments
```

Details

Checks the input params of a M/M/c/K/K queueing model. The inputs params are created calling previously the [NewInput.MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## check the parameters
CheckInput(i_mmckk)
```

CheckInput.i_MMCKM *Checks the input params of a M/M/c/K/m queueing model*

Description

Checks the input params of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'i_MMCKM'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCKM
...	additional arguments

Details

Checks the input params of a M/M/c/K/m queueing model. The inputs params are created calling previously the [NewInput.MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## check the parameters  
CheckInput(i_mmckm)
```

CheckInput.i_MMInf *Checks the input params of a M/M/Infinite queueing model*

Description

Checks the input params of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'i_MMInf'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMInf
...	additional arguments

Details

Checks the input params of a M/M/Infinite queueing model. The inputs params are created calling previously the [NewInput.MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Check the parameters  
CheckInput(i_mminf)
```

CheckInput.i_MMInfKK *Checks the input params of a M/M/Infinite/K/K queueing model*

Description

Checks the input params of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'i_MMInfKK'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMInfKK
...	additional arguments

Details

Checks the input params of a M/M/Infinite/K/K queueing model. The inputs params are created calling previously the [NewInput.MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## check the parameters  
CheckInput(i_MMInfKK)
```

CheckInput.i_OJN	<i>Check the input params of an Open Jackson Network</i>
------------------	--

Description

Check the input params of an Open Jackson Network

Usage

```
## S3 method for class 'i_OJN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_OJN
...	additional arguments

Details

Check the input params of an Open Jackson Network. The inputs params are created calling previously the [NewInput.OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

CheckInput(ojn1)
```

CompareQueueingModels *Compare several queueing models in a tabulated format*

Description

Compare several queueing models in a tabulated format

Usage

```
CompareQueueingModels(model, ...)
CompareQueueingModels2(models)
```

Arguments

model	A Queueing Model obtained calling QueueingModel from classes described in the details section
...	a separated by comma list of queueing models obtained calling QueueingModel from classes described in the details section
models	A list of queueing models obtained calling QueueingModel from classes described in the details section

Details

Compare several queueing models in a tabulated format. By now, only o_MM1, o_MMC, o_MMInf, o_MM1K, o_MMCK, o_MMCC, o_MM1KK, o_MMCKK, o_MMCKM, o_MMInfKK classes can be compared

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel](#)

Examples

```
q1 <- QueueingModel(NewInput.MM1(lambda=5, mu=7))
q2 <- QueueingModel(NewInput.MMC(lambda=5, mu=3, c=4))
q3 <- QueueingModel(NewInput.MMInf(lambda=3, mu=4))
q4 <- QueueingModel(NewInput.MMCC(lambda=5, mu=3, c=4))

CompareQueueingModels(q1, q2, q3)
CompareQueueingModels2(list(q1, q2, q3, q4))
```

C_erlang	Returns the probability to wait in queue because all servers are busy
----------	---

Description

Returns the probability to wait in queue because all servers are busy

Usage

```
C_erlang(c=1, r=0)
```

Arguments

c	numbers of servers
r	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability to wait in queue because all servers are busy

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[B_erlang](#)

Examples

```
## two servers  
C_erlang(2, 0.5/0.7)
```

Engset *Returns the probability that all servers are busy*

Description

Returns the probability that all servers are busy

Usage

```
Engset(k=1, c=0, r=0)
```

Arguments

k	numbers of users
c	numbers of servers
r	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability of blocking in a finite source model

See Also

[B_erlang](#)

Examples

```
## three users, two servers
Engset(3, 2, 0.5/0.7)
```

Inputs *Returns the input parameters of a queueing model (or network)*

Description

Returns the inputs parameters of a already built queueing model (or network)

Usage

```
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMCC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_MCON, o_MCCN, o_MCMN
...	aditional arguments

Details

Returns the input parameters of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[Inputs.o_MM1](#)
[Inputs.o_MMC](#)
[Inputs.o_MM1K](#)
[Inputs.o_MMCK](#)
[Inputs.o_MM1KK](#)
[Inputs.o_MMCKK](#)
[Inputs.o_MMCC](#)
[Inputs.o_MMCKM](#)
[Inputs.o_MMInfKK](#)
[Inputs.o_MMInf](#)
[Inputs.o_OJN](#)
[Inputs.o_CJN](#)
[Inputs.o_MCON](#)
[Inputs.o_MCCN](#)
[Inputs.o_MCMN](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Inputs
Inputs(o_mm1)
```

Inputs.o_CJN

Returns the input params of a Closed Jackson Network

Description

Returns the input params of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'  
Inputs(x, ...)
```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Returns the input params of a Closed Jackson Network. The inputs parameters are created calling previously the [NewInput.CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)  
  
# Define a new input  
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)  
  
# Check the inputs and build the model  
m_cjn1 <- QueueingModel(cjn1)  
  
Inputs(m_cjn1)
```

Inputs.o_MCCN	<i>Returns the input params of a MultiClass Closed Network</i>
---------------	--

Description

Returns the input params of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Inputs(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns the input params of a MultiClass Closed Network. The inputs parameters are created calling previously the [NewInput.MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)
```



```
Inputs(o_MCMN1)
```

Inputs.o_MCMN	<i>Returns the input params of a MultiClass Mixed Network</i>
---------------	---

Description

Returns the input params of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Inputs(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns the input params of a MultiClass Mixed Network. The inputs parameters are created calling previously the [NewInput.MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)
```

```
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Inputs(o_mcmn1)
```

Inputs.o_MCON *Returns the input params of a MultiClass Open Network*

Description

Returns the input params of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Inputs(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns the input params of a MultiClass Open Network. The inputs parameters are created calling previously the [NewInput.MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Inputs(o_mcon1)
```

Inputs.o_MM1

Returns the input parameters of a M/M/1 queueing model

Description

Returns the inputs parameters of a already built M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the input parameters of a M/M/1 queueing model. The inputs parameters are created calling previously the [NewInput.MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Inputs
Inputs(o_mm1)
```

Inputs.o_MM1K	<i>Returns the input parameters of a M/M/1/K queueing model</i>
---------------	---

Description

Returns the inputs parameters of a already built M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the input parameters of a M/M/1/K queueing model. The inputs parameters are created calling previously the [NewInput.MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Inputs
Inputs(o_mm1k)
```

Inputs.o_MM1KK	Returns the input parameters of a M/M/1/K/K queueing model
----------------	--

Description

Returns the inputs parameters of a already built M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the input parameters of a M/M/1/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Inputs
Inputs(o_mm1kk)
```

Inputs.o_MMC	Returns the input parameters of a M/M/c queueing model
--------------	--

Description

Returns the inputs parameters of a already built M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the input parameters of a M/M/c queueing model. The inputs parameters are created calling previously the [NewInput.MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMCC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Inputs
Inputs(o_mmc)
```

Inputs.o_MMCC	Returns the input parameters of a M/M/c/c queueing model
---------------	--

Description

Returns the inputs parameters of a already built M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the input parameters of a M/M/c/c queueing model. The inputs parameters are created calling previously the [NewInput.MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Inputs
Inputs(o_mmcc)
```

Inputs.o_MMCK	<i>Returns the input parameters of a M/M/c/K queueing model</i>
---------------	---

Description

Returns the inputs parameters of a already built M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the input parameters of a M/M/c/K queueing model. The inputs parameters are created calling previously the [NewInput.MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Inputs
Inputs(o_mmck)
```

Inputs.o_MMCKK	<i>Returns the input parameters of a M/M/c/K/K queueing model</i>
----------------	---

Description

Returns the inputs parameters of a already built M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the input parameters of a M/M/c/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Inputs
Inputs(o_mmckk)
```

Inputs.o_MMCKM	<i>Returns the input parameters of a M/M/c/K/m queueing model</i>
----------------	---

Description

Returns the inputs parameters of a already built M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the input parameters of a M/M/c/K/m queueing model. The inputs parameters are created calling previously the [NewInput.MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Inputs
Inputs(o_mmckm)
```

Inputs.o_MMInf	Returns the input parameters of a M/M/Infinite queueing model
----------------	---

Description

Returns the inputs parameters of a already built M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the input parameters of a M/M/Infinite queueing model. The inputs parameters are created calling previously the [NewInput.MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Inputs
Inputs(o_mminf)
```

Inputs.o_MMInfKK	Returns the input parameters of a M/M/Infinite/K/K queueing model
------------------	---

Description

Returns the inputs parameters of a already built M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the input parameters of a M/M/Infinite/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Inputs
Inputs(o_MMInfKK)
```

Inputs.o_OJN	<i>Returns the input params of an Open Jackson Network</i>
--------------	--

Description

Returns the input params of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Inputs(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Returns the input params of an Open Jackson Network. The inputs parameters are created calling previously the [NewInput.OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn1 <- QueueingModel(i_ojn1)

Inputs(o_ojn1)
```

L *Returns the mean number of customers in a queueing model (or network)*

Description

Returns the mean number of customers in a queueing model (or network)

Usage

`L(x, ...)`

Arguments

x a object of class `o_MM1`, `o_MMC`, `o_MM1K`, `o_MMCK`, `o_MM1KK`, `o_MMCKK`, `o_MMCC`, `o_MMCKM`, `o_MMInfKK`, `o_MMInf`, `o_OJN`, `o_MCON`, `o_MCCN`, `o_MCMN`

... additional arguments

Details

Returns the mean number of customers in a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[L.o_MM1](#)
[L.o_MMC](#)
[L.o_MM1K](#)
[L.o_MMCK](#)
[L.o_MM1KK](#)
[L.o_MMCKK](#)
[L.o_MMCC](#)
[L.o_MMCKM](#)
[L.o_MMInfKK](#)
[L.o_MMInf](#)
[L.o_OJN](#)
[L.o_CJN](#)
[L.o_MCON](#)
[L.o_MCCN](#)
[L.o_MCMN](#)

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the L
L(o_mm1)

```

L.o_CJN

Returns the mean number of customers of a Closed Jackson Network

Description

Returns the mean number of customers of a Closed Jackson Network

Usage

```

## S3 method for class 'o_CJN'
L(x, ...)

```

Arguments

x a object of class o_CJN
... additional arguments

Details

Returns the mean number of customers of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

L(m_cjn1)
```

L.o_MCCN

Returns the mean number of customers of a MultiClass Closed Network

Description

Returns the mean number of customers of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
L(x, ...)
```


Arguments

x a object of class o_MCCN
 ... additional arguments

Details

Returns the mean number of customers of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

L(o_MCCN1)
```

L.o_MCMN

Returns the mean number of customers of a MultiClass Mixed Network

Description

Returns the mean number of customers of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'  
L(x, ...)
```

Arguments

```
x          a object of class o_MCMN  
...       additional arguments
```

Details

Returns the mean number of customers of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.  
  
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=1, nrow=4, ncol=2)  
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)  
  
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcmn1 <- QueueingModel(i_mcmn1)  
  
L(o_mcmn1)
```

`L.o_MCON`*Returns the mean number of customers of a MultiClass Open Network*

Description

Returns the mean number of customers of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'  
L(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MCON</code>
<code>...</code>	additional arguments

Details

Returns the mean number of customers of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
L(o_mcon1)
```

`L.o_MMI`*Returns the mean number of customers in the M/M/1 queueing model*

Description

Returns the mean number of customers in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
L(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MM1</code>
<code>...</code>	aditional arguments

Details

Returns the mean number of customers in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the L  
L(o_mm1)
```

L.o_MM1K	<i>Returns the mean number of customers in the M/M/1/K queueing model</i>
----------	---

Description

Returns the mean number of customers in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
L(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the mean number of customers in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the L  
L(o_mm1k)
```

L.o_MM1KK	<i>Returns the mean number of customers in the M/M/1/K/K queueing model</i>
-----------	---

Description

Returns the mean number of customers in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
L(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the mean number of customers in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the L  
L(o_mm1kk)
```

L.o_MMC	Returns the mean number of customers in the M/M/c queueing model
---------	--

Description

Returns the mean number of customers in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
L(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the mean number of customers in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the L  
L(o_mmc)
```

`L.o_MMCC`*Returns the mean number of customers in the M/M/c/c queueing model*

Description

Returns the mean number of customers in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
L(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MMCC</code>
<code>...</code>	additional arguments

Details

Returns the mean number of customers in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the L  
L(o_mmcc)
```

L.o_MMCK	<i>Returns the mean number of customers in the M/M/c/K queueing model</i>
----------	---

Description

Returns the mean number of customers in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
L(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean number of customers in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the L  
L(o_mmck)
```

L.o_MMCKK	<i>Returns the mean number of customers in the M/M/c/K/K queueing model</i>
-----------	---

Description

Returns the mean number of customers in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
L(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the L  
L(o_mmckk)
```

L.o_MMCKM	Returns the mean number of customers in the M/M/c/K/m queueing model
-----------	--

Description

Returns the mean number of customers in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
L(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the L  
L(o_mmckm)
```

L.o_MMInf	<i>Returns the mean number of customers in the M/M/Infinite queueing model</i>
-----------	--

Description

Returns the mean number of customers in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
L(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the mean number of customers in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the L  
L(o_mminf)
```

L.o_MMInfKK	<i>Returns the mean number of customers in the M/M/Infinite/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
L(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the L  
L(o_MMInfKK)
```

L.o_OJN

Returns the mean number of customers of an Open Jackson Network

Description

Returns the mean number of customers of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
L(x, ...)
```

Arguments

```
x          a object of class o_OJN
...        additional arguments
```

Details

Returns the mean number of customers of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn <- QueueingModel(i_ojn)
```

L(o_ojn)

Lc *Returns the vector with the mean number of customers of each class in a multiclass queueing network*

Description

Returns the vector with the mean number of customers of each class in a multiclass queueing network

Usage

Lc(x, ...)

Arguments

x a object of class o_MCON, o_MCCN, o_MCMN
... additional arguments

Details

Returns the vector with the mean number of customers of each class in a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.

Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Lc.o_MCON](#)

[Lc.o_MCCN](#)

[Lc.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lc(o_mcon1)
```

Lc.o_MCCN

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

Description

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Lc(x, ...)
```

Arguments

x a object of class o_MCCN
... additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lc(o_MCCN1)
```

Lc.o_MCMN

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

Description

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lc(x, ...)
```

Arguments

x a object of class o_MCMN
... additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lc(o_mcmn1)
```

Lc.o_MCON

Returns the vector with the mean number of customers of each class in a MultiClass Open Network

Description

Returns the vector with the mean number of customers of each class in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lc(x, ...)
```

Arguments

x a object of class o_MCON
... additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON.](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lc(o_mcon1)
```

Lck

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

Usage

Lck(x, ...)

Arguments

x a object of class o_MCON, o_MCCN, o_MCMN
 ... additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Lck.o_MCON](#)
[Lck.o_MCCN](#)
[Lck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lck(o_mcon1)
```

Lck.o_MCCN	<i>Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network</i>
------------	---

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
Lck(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lck(o_MCCN1)
```

Lck.o_MCMN	<i>Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network</i>
------------	--

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lck(o_mcmn1)
```

Lck.o_MCON

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lck(x, ...)
```

Arguments

x a object of class o_MCON
 \dots additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lck(o_mcon1)
```

Lk	<i>Returns the vector with the mean number of customers in each node (server) of a queueing network</i>
----	---

Description

Returns the vector with the mean number of customers in each node (server) of a queueing network

Usage

```
Lk(x, ...)
```

Arguments

x	a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the vector with the mean number of customers in each node (server) of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.

Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Lk.o_OJN](#)

[Lk.o_CJN](#)

[Lk.o_MCON](#)

[Lk.o_MCCN](#)

[Lk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lk(o_mcon1)
```

Lk.o_CJN

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

Description

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Lk(x, ...)
```

Arguments

```
x          a object of class o_CJN
...        additional arguments
```

Details

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN.](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Lk(m_cjn1)
```

Lk.o_MCCN	Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network
-----------	---

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
Lk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lk(o_MCCN1)
```

Lk.o_MCMN	<i>Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network</i>
-----------	---

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lk(o_mcmn1)
```

Lk.o_MCON	<i>Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network</i>
-----------	--

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lk(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lk(o_mcon1)
```

Lk.o_OJN

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

Description

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Lk(x, ...)
```

Arguments

x a object of class o_OJN
 ... additional arguments

Details

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn <- QueueingModel(i_ojn)

Lk(o_ojn)
```

Lq	<i>Returns the mean number of customers in the queue in a queueing model</i>
----	--

Description

Returns the mean number of customers in the queue in a queueing model

Usage

Lq(x, ...)

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the mean number of customers in the queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[Lq.o_MM1](#)
[Lq.o_MMC](#)
[Lq.o_MM1K](#)
[Lq.o_MMCK](#)
[Lq.o_MM1KK](#)
[Lq.o_MMCKK](#)
[Lq.o_MMCC](#)
[Lq.o_MMCKM](#)
[Lq.o_MMInfKK](#)
[Lq.o_MMInf](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lq
Lq(o_mm1)
```

Lq.o_MM1

Returns the mean number of customers in the queue in the M/M/1 queueing model

Description

Returns the mean number of customers in the queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Lq(x, ...)
```


Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lq
Lq(o_mm1)
```

Lq.o_MM1K	<i>Returns the mean number of customers in the queue in the M/M/1/K queueing model</i>
-----------	--

Description

Returns the mean number of customers in the queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Lq(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Lq
Lq(o_mm1k)
```

Lq.o_MM1KK	<i>Returns the mean number of customers in the queue in the M/M/1/K/K queueing model</i>
------------	--

Description

Returns the mean number of customers in the queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Lq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Lq
Lq(o_mm1kk)
```

Lq.o_MMC	<i>Returns the mean number of customers in the queue in the M/M/c queueing model</i>
----------	--

Description

Returns the mean number of customers in the queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Lq(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Lq
Lq(o_mmc)
```

Lq.o_MMCC	<i>Returns the mean number of customers in the queue in the M/M/c/c queueing model</i>
-----------	--

Description

Returns the mean number of customers in the queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Lq
Lq(o_mmcc)
```

Lq.o_MMCK	<i>Returns the mean number of customers in the queue in the M/M/c/K queueing model</i>
-----------	--

Description

Returns the mean number of customers in the queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Lq
Lq(o_mmck)
```

Lq.o_MMCKK	<i>Returns the mean number of customers in the queue in the M/M/c/K/K queueing model</i>
------------	--

Description

Returns the mean number of customers in the queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Lq
Lq(o_mmckk)
```

Lq.o_MMCKM	<i>Returns the mean number of customers in the queue in the M/M/c/K/m queueing model</i>
------------	--

Description

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Lq
Lq(o_mmckm)
```

Lq.o_MMInf	<i>Returns the mean number of customers in the queue in the M/M/Infinite queueing model</i>
------------	---

Description

Returns the mean number of customers in the queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Lq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Lq
Lq(o_mminf)
```

Lq.o_MMInfKK	<i>Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model</i>
--------------	---

Description

Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Lq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Lq
Lq(o_MMInfKK)
```

Lqq	<i>Returns the mean number of customers in queue when there is queue in a queueing model</i>
-----	--

Description

Returns the mean number of customers in queue when there is queue in a queueing model

Usage

```
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Lqq.o_MM1](#)
[Lqq.o_MMC](#)
[Lqq.o_MM1K](#)
[Lqq.o_MMCK](#)
[Lqq.o_MM1KK](#)
[Lqq.o_MMCKK](#)
[Lqq.o_MMCC](#)

```
Lqq.o_MMCKM
Lqq.o_MMInfKK
Lqq.o_MMInf
```

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lqq
Lqq(o_mm1)
```

Lqq.o_MM1	<i>Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model</i>
-----------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lqq
Lqq(o_mm1)
```

Lqq.o_MM1K	<i>Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Lq
Lqq(o_mm1k)
```

Lqq.o_MM1KK	<i>Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Lqq
Lqq(o_mm1kk)
```

Lqq.o_MMC	<i>Returns the mean number of customers in queue when there is queue in the M/M/c queueing model</i>
-----------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Lqq
Lqq(o_mmc)
```

Lqq.o_MMCC	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Lqq
Lqq(o_mmcc)
```

Lqq.o_MMCK	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Lqq
Lqq(o_mmck)
```

Lqq.o_MMCKK	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Lqq
Lqq(o_mmckk)
```

Lqq.o_MMCKM	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K/m queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Lqq
Lqq(o_mmckm)
```

Lqq.o_MMInf	<i>Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model</i>
-------------	---

Description

Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Lqq
Lqq(o_mminf)
```

Lqq.o_MMInfKK	<i>Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model</i>
---------------	---

Description

Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Lqq
Lqq(o_MMInfKK)
```

NewInput.CJN

Define the inputs of a Closed Jackson Network

Description

Define the inputs of a Closed Jackson Network

Usage

```
NewInput.CJN(prob=NULL, n=0, z=0, operational=FALSE, method=0, tol=0.001, ...)
NewInput2.CJN(prob=NULL, n=0, z=0, operational=FALSE, method=0, tol=0.001, nodes)
NewInput3.CJN(n, z, numNodes, vType, vVisit, vService, vChannel, method=0, tol=0.001)
```

Arguments

prob	It is probability transition matrix or visit ratio vector. That is, the prob[i, j] is the transition probability of node i to node j, or prob[i] is the visit ratio (a probability, that is, a value between 0 and 1) to node i. Also, the visit ratio can express the number of times that a client visits the queueing center, in a more operational point of view. See the parameter operational
n	number of customers in the Network
z	think time of the client
operational	If prob is a vector with the visit ratios, operational equal to FALSE gives to the visit ratio a probability meaning, that is, as the stationary values of the imbedded markov chain. If operational is equal to TRUE, the operational point of view is used: it is the number of visits that the same client makes to a node.
method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used.
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm.
...	a separated by comma list of nodes of i_MM1, i_MMC or i_MMInf class
nodes	A list of nodes of i_MM1, i_MMC or i_MMInf class
numNodes	The number of nodes of the network
vType	A vector with the type of server: "Q" for a queueing node, "D" for a delay node
vVisit	A vector with the visit ratios. It represent visit counts to a center as if the parameter operational were TRUE

vService	A vector with the services time of each node
vChannel	A vector with the number of channels of the node. The type of the server has to be "Q" to be inspected

Details

Define the inputs of a Closed Jackson Network. For a operational use, NewInput3.CJN is recommended. For a more academic use, NewInput.CJN or NewInput2.CJN is recommended. Please, note that the different ways to create the inputs for a Closed Jackson Network are equivalent to each other, and no validation is done at this stage. The validation is done calling CheckInput function.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

## think time = 0
z <- 0

## operational value
operational <- FALSE

## definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

## Not run:
cjn1 <- NewInput2.CJN(prob, n, z, operational, 0, 0.001, list(n1, n2))

## End(Not run)
```

```

## using visit ratios and service demands. See [Lazowska84] pag 117.
## E[S] cpu = 0.005, Visit cpu = 121, D cpu = E[S] cpu * Visit cpu = 0.605
cpu <- NewInput.MM1(mu=1/0.005)

## E[S] disk1 = 0.030, Visit disk1 = 70, D disk1 = E[S] disk1 * Visit disk1 = 2.1
disk1 <- NewInput.MM1(mu=1/0.030)

## E[S] disk2 = 0.027, Visit disk2 = 50, D disk2 = E[S] disk2 * Visit disk2 = 1.35
disk2 <- NewInput.MM1(mu=1/0.027)

## The visit ratios.
vVisit <- c(121, 70, 50)

operational <- TRUE

net <- NewInput.CJN(prob=vVisit, n=3, z=15, operational, 0, 0.001, cpu, disk1, disk2)

## Using the operational creation function
n <- 3
think <- 15
numNodes <- 3
vType <- c("Q", "Q", "Q")
vService <- c(0.005, 0.030, 0.027)
vChannel <- c(1, 1, 1)

net2 <- NewInput3.CJN(n, think, numNodes, vType, vVisit, vService, vChannel, method=0, tol=0.001)

```

NewInput.MCCN

Define the inputs of a MultiClass Closed Network

Description

Define the inputs of a MultiClass Closed Network

Usage

```

NewInput.MCCN(
  classes, vNumber, vThink, nodes, vType, vVisit, vService, method=1, tol=0.01
)

```

Arguments

classes	The number of classes
vNumber	A vector with the number of customers of each class
vThink	A vector with the think time of each class
nodes	The number of nodes in the network

vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j
vService	A matrix[i, j]. The rows represents the different service time for each class i in each node j
method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm

Details

Define the inputs of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

NewInput.MCMN

Define the inputs of a MultiClass Mixed Network

Description

Define the inputs of a MultiClass Mixed Network

Usage

```
NewInput.MCMN(
  classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService, method=0, tol=0.01
)
```

Arguments

classes	The number of classes
vLambda	It is a vector with the rate of arrivals of each class
vNumber	A vector with the number of customers of each class
vThink	A vector with the think time of each class
nodes	The number of nodes in the network
vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j. Take caution about the orden: open classes are defined first and closed classes are defined second
vService	A matrix[i, j]. The rows represents the different service times for each class i in each node j. Take caution about the orden: open classes are defined first and closed classes are defined second.
method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm

Details

Define the inputs of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4 # A and B are open classes and C and D are closed classes.
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
```

```

vType <- c("Q", "Q")

# When the visit ratios and vService are set,
# be sure that the open classes are in the first positions
# and the closed classes after the open classes.
vVisit <- matrix(data=1, nrow=4, ncol=2)

# A and B are open classes:
# with demand service of 1/4 and 1/2 at the node 1 and 1/2 and 1 at the node 2
# C and D are open classes:
# with demand service of 1/4 and 1/2 at the node 1 and 1/2 and 1 at the node 2
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

```

NewInput.MCON

Define the inputs of a MultiClass Open Network

Description

Define the inputs of a MultiClass Open Network

Usage

```
NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

Arguments

classes	The number of classes
vLambda	It is a vector with the rate of arrivals of each class
nodes	The number of nodes in the network
vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j
vService	A matrix[i, j]. The rows represents the different service times for each class i in each node j

Details

Define the inputs of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

NewInput.MM1

Define the inputs of a new M/M/1 queueing model

Description

Define the inputs of a new M/M/1 queueing model

Usage

```
NewInput.MM1(lambda=0, mu=0, n=0)
```

Arguments

lambda	arrival rate
mu	server service rate
n	number of customers in the system from which you want to obtain its probabilities. Put n=0 for a idle probability (no customer present in the system or system idle). With n=-1, no probabilities are computed

Details

Define the inputs of a new M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)
```

NewInput.MM1K	<i>Define the inputs of a new M/M/1/K queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/1/K queueing model

Usage

```
NewInput.MM1K(lambda=0, mu=0, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity

Details

Define the inputs of a new M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1K](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)
```

NewInput.MM1KK *Define the inputs of a new M/M/1/K/K queueing model*

Description

Define the inputs of a new M/M/1/K/K queueing model

Usage

```
NewInput.MM1KK(lambda=0, mu=0, k=1, method=3)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms. With method=2, Jain's Method [Jain2007], pag. 26 is used. With method=3, the result that K-n customers up has a truncated poisson distribution is used [Kobayashi2012] pag. 709

Details

Define the inputs of a new M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Jain2007] Joti Lal Jain, Sri Gopal Mohanty, Walter Bohm (2007).
A course on Queueing Models.
Chapman-Hall.

[Kobayashi2012] Hisashi Kobayashi, Brian L. Mark, William Turin (2012).
Probability, Random Processes, and Statistical Analysis: Applications to Communications, Signal Processing, Queueing Theory and Mathematical Finance.
Cambridge University Press.

See Also

[CheckInput.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)
```

NewInput.MMC

Define the inputs of a new M/M/c queueing model

Description

Define the inputs of a new M/M/c queueing model

Usage

```
NewInput.MMC(lambda=0, mu=0, c=1, n=0, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
n	number of customers in the system from which you want to obtain its probabilities. Put n=0 for a idle probability (no customer present in the system or system idle). With n=-1, no probabilities are computed
method	method of computation of the probabilities of n number of customers in the system. With method=0, the exact results are calculated using the formal definition. With method=1, aproximate results are calculated using Stirling aproximation of factorials and logaritms.

Details

Define the inputs of a new M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)
```

NewInput.MMCC	<i>Define the inputs of a new M/M/c/c queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/c/c queueing model

Usage

```
NewInput.MMCC(lambda=0, mu=0, c=1, method=1)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
method	with method = 0, the state probabilities are calculated using the formal definition (with overflow problems with factorials; with method = 1 (default), the truncated poisson distribution is used (recomended for professional use)

Details

Define the inputs of a new M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Kobayashi2012] Hisashi Kobayashi, Brian L. Mark, William Turin (2012).
Probability, Random Processes, and Statistical Analysis: Applications to Communications, Signal Processing, Queueing Theory and Mathematical Finance.
Cambridge University Press.

See Also

[CheckInput.i_MMCC](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)
```

NewInput.MMCK	<i>Define the inputs of a new M/M/c/K queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/c/K queueing model

Usage

```
NewInput.MMCK(lambda=0, mu=0, c=1, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity

Details

Define the inputs of a new M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCK](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)
```

NewInput.MMCKK *Define the inputs of a new M/M/c/K/K queueing model*

Description

Define the inputs of a new M/M/c/K/K queueing model

Usage

```
NewInput.MMCKK(lambda=0, mu=0, c=1, k=1, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms. With method=2, Jain's Method [Jain2007], pag. 26 is used

Details

Define the inputs of a new M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Jain2007] Joti Lal Jain, Sri Gopal Mohanty, Walter Bohm (2007).

A course on Queueing Models.
Chapman-Hall.

See Also

[CheckInput.i_MMCKK](#)

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)
```

NewInput.MMCKM

Define the inputs of a new M/M/c/K/m queueing model

Description

Define the inputs of a new M/M/c/K/m queueing model

Usage

```
NewInput.MMCKM(lambda=0, mu=0, c=1, k=1, m=1, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity
m	population size. Please, observe that should be $m \geq k$
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms.

Details

Define the inputs of a new M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKM](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)
```

NewInput.MMInf *Define the inputs of a new M/M/Infinite queueing model*

Description

Define the inputs of a new M/M/Infinite queueing model

Usage

```
NewInput.MMInf(lambda=0, mu=0, n=0)
```

Arguments

lambda	arrival rate
mu	server service rate
n	number of customers in the system from which you want to obtain its probabilities. Put n=0 for a idle probability (no customer present in the system or system idle). With n=-1, no probabilities are computed

Details

Define the inputs of a new M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMInf](#)

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)
```

NewInput.MMInfKK	<i>Define the inputs of a new M/M/Infinite/K/K queueing model</i>
------------------	---

Description

Define the inputs of a new M/M/Infinite/K/K queueing model

Usage

```
NewInput.MMInfKK(lambda=0, mu=0, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity

Details

Define the inputs of a new M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MMInfKK](#)

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)
```

NewInput.OJN *Define the inputs of an Open Jackson Network*

Description

Define the inputs of an Open Jackson Network

Usage

```
NewInput.OJN(prob=NULL, ...)
NewInput2.OJN(prob=NULL, nodes)
NewInput3.OJN(vLambda, numNodes, vType, vVisit, vService, vChannel)
```

Arguments

prob	It is probability transition matrix or visit ratio vector. That is, the prob[i, j] is the transition probability of node i to node j, or prob[i] is the visit ratio to node i (the visit ratio values doesn't need to be probabilities, that is, a value greater than 1 can be used here. See the examples)
...	a separated by comma list of nodes of i_MM1, i_MMC or i_MMInf class
nodes	A list of nodes of i_MM1, i_MMC or i_MMInf class
vLambda	Vector with the arrivals rates to each node
numNodes	Number of nodes
vType	A vector with the type of server: "Q" for a queueing node, "D" for a delay node
vVisit	A vector with the visit ratios
vService	A vector with the services time of each node
vChannel	A vector with the number of channels of the node. The type of the server has to be "Q" to be inspected

Details

Define the inputs of an Open Jackson Network. For a operational use, NewInput3.OJN is recommended. For a more academic use, NewInput.OJN or NewInput2.OJN is recommended. Please, note that the different ways to create the inputs for a Open Jackson Network are equivalent to each other, and no validation is done at this stage. The validation is done calling CheckInput function.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

## Using function NewInput2
## Not run:
  ojn1 <- NewInput2.OJN(prob, list(n1, n2, n3, n4))

## End(Not run)

## Using visit ratios. Values taken from [Lazowska84], pag. 113.

## E[S] cpu = 0.005, Visit cpu = 121, D cpu = E[S] cpu * Visit cpu = 0.605
cpu <- NewInput.MM1(lambda=0.2, mu=1/0.005)

## E[S] disk1 = 0.030, Visit disk1 = 70, D disk1 = E[S] disk1 * Visit disk1 = 2.1
disk1 <- NewInput.MM1(lambda=0.2, mu=1/0.030)

## E[S] disk2 = 0.027, Visit disk2 = 50, D disk2 = E[S] disk2 * Visit disk2 = 1.35
disk2 <- NewInput.MM1(lambda=0.2, mu=1/0.027)

## In this example, to have the throughput per node, the visit ratios has to be given in this form.
## Please, don't use in the closed Jackson Network
visit <- c(121, 70, 50)
net <- NewInput.OJN(visit, cpu, disk1, disk2)

## Using NewInput3
vLambda <- c(0.2, 0.2, 0.2)
vService <- c(0.005, 0.030, 0.027)
numNodes <- 3
vType <- c("Q", "Q", "Q")
vChannel <- c(1, 1, 1)
net2 <- NewInput3.OJN(vLambda, numNodes, vType, visit, vService, vChannel)
```

Pn	<i>Returns the probabilities of a queueing model (or network)</i>
----	---

Description

Pn returns the probabilities that a queueing model (or network) has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it

Usage

Pn(x, ...)

Qn(x, ...)

Arguments

x	For Pn, an object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN. For Qn, an object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Pn returns the system probabilities of a queueing model (or network). Qn returns the probability that an effective arrival see n customers in the system

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[Pn.o_MM1](#)
[Qn.o_MM1](#)
[Pn.o_MMC](#)
[Qn.o_MMC](#)
[Pn.o_MM1K](#)
[Qn.o_MM1K](#)
[Pn.o_MMCK](#)
[Qn.o_MMCK](#)
[Pn.o_MM1KK](#)
[Qn.o_MM1KK](#)
[Pn.o_MMCKK](#)
[Qn.o_MMCKK](#)

```

Pn.o_MMCC
Qn.o_MMCC
Pn.o_MMCKM
Qn.o_MMCKM
Pn.o_MMInfKK
Qn.o_MMInfKK
Pn.o_MMInf
Qn.o_MMInf
Pn.o_OJN

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the probabilities
Pn(o_mm1)

```

Pn.o_MM1

Returns the probabilities of a M/M/1 queueing model

Description

Pn returns the probabilities that a M/M/1 queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```

## S3 method for class 'o_MM1'
Pn(x, ...)
## S3 method for class 'o_MM1'
Qn(x, ...)

```

Arguments

x a object of class o_MM1
 ... additional arguments

Details

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the probabilities
Pn(o_mm1)
Qn(o_mm1)
```

Pn.o_MM1K

Returns the probabilities of a M/M/1/K queueing model

Description

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MM1K'
Pn(x, ...)
## S3 method for class 'o_MM1K'
Qn(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the probabilities
Pn(o_mm1k)
Qn(o_mm1k)
```

Pn.o_MM1KK

Returns the probabilities of a M/M/1/K/K queueing model

Description

Pn returns the probabilities of a M/M/1/K/K queueing model Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MM1KK'
Pn(x, ...)
## S3 method for class 'o_MM1KK'
Qn(x, ...)
```

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

Pn returns the probabilities that a M/M/1/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the probabilities
Pn(o_mm1kk)
Qn(o_mm1kk)
```

Pn.o_MMC

Returns the probabilities of a M/M/c queueing model

Description

Pn returns the probabilities that a M/M/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMC'
Pn(x, ...)
## S3 method for class 'o_MMC'
Qn(x, ...)
```

Arguments

x a object of class o_MMC
 ... additional arguments

Details

Pn returns the probabilities that a M/M/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the probabilities
Pn(o_mmc)
Qn(o_mmc)
```

Pn.o_MMCC

Returns the probabilities of a M/M/c/c queueing model

Description

Pn returns the probabilities that a M/M/c/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCC'
Pn(x, ...)
## S3 method for class 'o_MMCC'
Qn(x, ...)
```

Arguments

x a object of class o_MMCC
 ... additional arguments

Details

Pn returns the probabilities that a M/M/c/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the probabilities
Pn(o_mmcc)
Qn(o_mmcc)
```

Pn.o_MMCK

Returns the probabilities of a M/M/c/K queueing model

Description

Pn returns the probabilities that a M/M/c/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCK'
Pn(x, ...)
## S3 method for class 'o_MMCK'
Qn(x, ...)
```

Arguments

x a object of class o_MMCK
... additional arguments

Details

Pn returns the probabilities that a M/M/c/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the probabilities
Pn(o_mmck)
Qn(o_mmck)
```

Pn.o_MMCKK

Returns the probabilities of a M/M/c/K/K queueing model

Description

Pn returns the probabilities that a M/M/c/K/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCKK'
Pn(x, ...)
## S3 method for class 'o_MMCKK'
Qn(x, ...)
```

Arguments

x a object of class o_MMCKK
 ... additional arguments

Details

Pn returns the probabilities that a M/M/c/K/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the parameters
Pn(o_mmckk)
Qn(o_mmckk)
```

Pn.o_MMCKM

Returns the probabilities of a M/M/c/K/m queueing model

Description

Pn returns the probabilities that a M/M/c/K/m queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCKM'
Pn(x, ...)
## S3 method for class 'o_MMCKM'
Qn(x, ...)
```

Arguments

x a object of class o_MMCKM
 ... additional arguments

Details

Pn returns the probabilities that a M/M/c/K/m queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the probabilities
Pn(o_mmckm)
Qn(o_mmckm)
```

Pn.o_MMInf

Returns the probabilities of a M/M/Infinite queueing model

Description

Pn returns the probabilities that a M/M/Infinite queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMInf'
Pn(x, ...)
## S3 method for class 'o_MMInf'
Qn(x, ...)
```

Arguments

x a object of class o_MMInf
 ... additional arguments

Details

Pn returns the probabilities that a M/M/Infinite queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf.](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the probabilities
Pn(o_mminf)
Qn(o_mminf)
```

Pn.o_MMInfKK

Returns the probabilities of a M/M/Infinite/K/K queueing model

Description

Pn returns the probabilities that a M/M/Infinite/K/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMInfKK'
Pn(x, ...)
## S3 method for class 'o_MMInfKK'
Qn(x, ...)
```

Arguments

x a object of class o_MMInfKK
... additional arguments

Details

Pn returns the probabilities that a M/M/Infinite/K/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the probabilities
Pn(o_MMInfKK)
Qn(o_MMInfKK)
```

Pn.o_OJN	<i>Returns vector of the probabilities of each node (server) of an Open Jackson Network</i>
----------	---

Description

Returns vector of the probabilities of each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Pn(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Returns vector of the probabilities of each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Pn(o_ojn)
```

```
print.summary.o_CJN   Summary of the results of a Closed Jackson Network
```

Description

Summary of the results of a Closed Jackson Network

Usage

```
## S3 method for class 'summary.o_CJN'
print(x, ...)
```

Arguments

x	a object of class summary.o_CJN
...	additional arguments

Details

Summaries a Closed Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

print(summary(m_cjn1))
```

print.summary.o_MCCN *Summary of the results of a MultiClass Closed Network*

Description

Summary of the results of a MultiClass Closed Network

Usage

```
## S3 method for class 'summary.o_MCCN'
print(x, ...)
```

Arguments

x a object of class summary.o_MCCN
 ... additional arguments

Details

Summaries a MultiClass Closed Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

print(summary(o_MCCN1))
```

```
print.summary.o_MCMN    Summary of the results of a MultiClass Mixed Network
```

Description

Summary of the results of a MultiClass Mixed Network

Usage

```
## S3 method for class 'summary.o_MCMN'  
print(x, ...)
```

Arguments

```
x          a object of class summary.o_MCMN  
...       additional arguments
```

Details

Summaries a MultiClass Mixed Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.  
  
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=1, nrow=4, ncol=2)  
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)  
  
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcmn1 <- QueueingModel(i_mcmn1)  
  
print(summary(o_mcmn1))
```

print.summary.o_MCON *Summary of the results of a MultiClass Open Network*

Description

Summary of the results of a MultiClass Open Network

Usage

```
## S3 method for class 'summary.o_MCON'  
print(x, ...)
```

Arguments

x a object of class summary.o_MCON
... additional arguments

Details

Summaries a MultiClass Open Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
print(summary(o_mcon1))
```

print.summary.o_MM1 *Summary of the results of a M/M/1 queueing model*

Description

Summary of the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'summary.o_MM1'  
print(x, ...)
```

Arguments

x a object of class summary.o_MM1
... additional arguments

Details

Summaries a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Report the results  
print(summary(o_mm1))
```

print.summary.o_MM1K *Summary of the results of a M/M/1/K queueing model*

Description

Summary of the results of a M/M/1/K queueing model.

Usage

```
## S3 method for class 'summary.o_MM1K'  
print(x, ...)
```

Arguments

x	a object of class summary.o_MM1K
...	additional arguments

Details

Summaries a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Report the results  
print(summary(o_mm1k))
```

print.summary.o_MM1KK *Summary of the results of a M/M/1/K/K queueing model*

Description

Summary of the results of a M/M/1/K/K queueing model.

Usage

```
## S3 method for class 'summary.o_MM1KK'  
print(x, ...)
```

Arguments

x a object of class summary.o_MM1KK
... additional arguments

Details

Summaries a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Report the results  
print(summary(o_mm1kk))
```

print.summary.o_MMC *Summary of the results of a M/M/c queueing model*

Description

Summary of the results of a M/M/c queueing model.

Usage

```
## S3 method for class 'summary.o_MMC'  
print(x, ...)
```

Arguments

x a object of class summary.o_MMC
... additional arguments

Details

Summaries a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Report the results  
print(summary(o_mmc))
```

print.summary.o_MMCC *Summary of the results of a M/M/c/c queueing model*

Description

Summary of the results of a M/M/c/c queueing model.

Usage

```
## S3 method for class 'summary.o_MMCC'  
print(x, ...)
```

Arguments

x a object of class summary.o_MMCC
... additional arguments

Details

Summaries a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Report the results  
print(summary(o_mmcc))
```

print.summary.o_MMCK *Summary of the results of a M/M/c/K queueing model*

Description

Summary of the results of a M/M/c/K queueing model.

Usage

```
## S3 method for class 'summary.o_MMCK'  
print(x, ...)
```

Arguments

x a object of class summary.o_MMCK
... additional arguments

Details

Summaries a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Report the results  
print(summary(o_mmck))
```

print.summary.o_MMCKK *Summary of the results of a M/M/c/K/K queueing model*

Description

Summary of the results of a M/M/c/K/K queueing model.

Usage

```
## S3 method for class 'summary.o_MMCKK'  
print(x, ...)
```

Arguments

x	a object of class summary.o_MMCKK
...	aditional arguments

Details

Summaries a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Report the results  
print(summary(o_mmckk))
```

print.summary.o_MMCKM *Summary of the results of a M/M/c/K/m queueing model*

Description

Summary of the results of a M/M/c/K/m queueing model.

Usage

```
## S3 method for class 'summary.o_MMCKM'  
print(x, ...)
```

Arguments

x	a object of class summary.o_MMCKM
...	additional arguments

Details

Summaries a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Report the results  
print(summary(o_mmckm))
```

print.summary.o_MMInf *Summary of the results of a M/M/Infinite queueing model*

Description

Summary of the results of a M/M/Infinite queueing model.

Usage

```
## S3 method for class 'summary.o_MMInf'  
print(x, ...)
```

Arguments

x a object of class summary.o_MMInf
... additional arguments

Details

Summaries a M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Report the results  
print(summary(o_mminf))
```

```
print.summary.o_MMInfKK
```

Reports the results of a M/M/Infinite/K/K queueing model

Description

Reports the results of a M/M/Infinite/K/K queueing model.

Usage

```
## S3 method for class 'summary.o_MMInfKK'  
print(x, ...)
```

Arguments

x	a object of class summary.o_MMInfKK
...	additional arguments

Details

Summaries a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Report the results  
print(summary(o_MMInfKK))
```

```
print.summary.o_OJN    Reports the results of an Open Jackson Network
```

Description

Reports the results of an Open Jackson Network

Usage

```
## S3 method for class 'summary.o_OJN'
print(x, ...)
```

Arguments

```
x          a object of class summary.o_OJN
...        additional arguments
```

Details

Summaries an Open Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

o_ojn <- QueueingModel(i_ojn)
```

```
print(summary(o_ojn))
```

QueueingModel

Generic S3 method to build a queueing model (or network)

Description

Generic S3 method to build a queueing model (or network)

Usage

```
QueueingModel(x, ...)
```

Arguments

x	a object of class <code>i_MM1</code> , <code>i_MMC</code> , <code>i_MM1K</code> , <code>i_MMCK</code> , <code>i_MM1KK</code> , <code>i_MMCKK</code> , <code>i_MMCC</code> , <code>i_MMCKM</code> , <code>i_MMInfKK</code> , <code>i_MMInf</code> , <code>i_OJN</code> , <code>i_MCON</code>
...	additional arguments

Details

Generic S3 method to build a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#)
[QueueingModel.i_MMC](#)
[QueueingModel.i_MM1K](#)
[QueueingModel.i_MMCK](#)
[QueueingModel.i_MM1KK](#)
[QueueingModel.i_MMCKK](#)
[QueueingModel.i_MMCC](#)
[QueueingModel.i_MMCKM](#)
[QueueingModel.i_MMInfKK](#)
[QueueingModel.i_MMInf](#)
[QueueingModel.i_OJN](#)
[QueueingModel.i_MCON](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
QueueingModel(i_mm1)
```

QueueingModel.i_CJN *Builds one Closed Jackson Network*

Description

Builds one Closed Jackson Network

Usage

```
## S3 method for class 'i_CJN'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_CJN
...	aditional arguments

Details

Build one Closed Jackson Network. It also checks the input params calling the [CheckInput.i_CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)
```

```
# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

m_cjn1
```

QueueingModel.i_MCCN *Builds one MultiClass Closed Network*

Description

Builds one MultiClass Closed Network

Usage

```
## S3 method for class 'i_MCCN'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MCCN
...	additional arguments

Details

Build one MultiClass Closed Network. It also checks the input params calling the [CheckInput.i_MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

o_MCCN1
```

QueueingModel.i_MCMN *Builds one MultiClass Mixed Network*

Description

Builds one MultiClass Mixed Network

Usage

```
## S3 method for class 'i_MCMN'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MCMN
...	additional arguments

Details

Build one MultiClass Mixed Network. It also checks the input params calling the [CheckInput.i_MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

o_mcmn1
```

QueueingModel.i_MCON *Builds one MultiClass Open Network*

Description

Builds one MultiClass Open Network

Usage

```
## S3 method for class 'i_MCON'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MCON
...	additional arguments

Details

Build one MultiClass Open Network. It also checks the input params calling the [CheckInput.i_MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

o_mcon1
```

QueueingModel.i_MM1 *Builds a M/M/1 queueing model*

Description

Builds a M/M/1 queueing model

Usage

```
## S3 method for class 'i_MM1'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1
...	aditional arguments

Details

Build a M/M/1 queueing model. It also checks the input params calling the [CheckInput.i_MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
QueueingModel(i_mm1)
```

QueueingModel.i_MM1K *Builds a M/M/1/K queueing model*

Description

Builds a M/M/1/K queueing model

Usage

```
## S3 method for class 'i_MM1K'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1K
...	additional arguments

Details

Build a M/M/1/K queueing model. It also checks the input params calling the [CheckInput.i_MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
QueueingModel(i_mm1k)
```

QueueingModel.i_MM1KK *Builds a M/M/1/K/K queueing model*

Description

Builds a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'i_MM1KK'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1KK
...	aditional arguments

Details

Build a M/M/1/K/K queueing model. It also checks the input params calling the [CheckInput.i_MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
QueueingModel(i_mm1kk)
```

QueueingModel.i_MMC *Builds a M/M/c queueing model*

Description

Builds a M/M/c queueing model

Usage

```
## S3 method for class 'i_MMC'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMC
...	aditional arguments

Details

Build a M/M/c/ queueing model. It also checks the input params calling the [CheckInput.i_MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
QueueingModel(i_mmc)
```

QueueingModel.i_MMCC *Builds a M/M/c/c queueing model*

Description

Builds a M/M/c/c queueing model

Usage

```
## S3 method for class 'i_MMCC'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCC
...	additional arguments

Details

Build a M/M/c/c queueing model. It also checks the input params calling the [CheckInput.i_MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
QueueingModel(i_mmcc)
```

QueueingModel.i_MMCK *Builds a M/M/c/K queueing model*

Description

Builds a M/M/c/K queueing model

Usage

```
## S3 method for class 'i_MMCK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCK
...	additional arguments

Details

Build a M/M/c/K queueing model. It also checks the input params calling the [CheckInput.i_MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
QueueingModel(i_mmck)
```

QueueingModel.i_MMCKK *Builds a M/M/c/K/K queueing model*

Description

Builds a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'i_MMCKK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCKK
...	additional arguments

Details

Build a M/M/c/K/K queueing model. It also checks the input params calling the [CheckInput.i_MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
QueueingModel(i_mmckk)
```

QueueingModel.i_MMCKM *Builds a M/M/c/K/m queueing model*

Description

Builds a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'i_MMCKM'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCKM
...	additional arguments

Details

Build a M/M/c/K/m queueing model. It also checks the input params calling the [CheckInput.i_MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKM](#)

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
QueueingModel(i_mmckm)
```

QueueingModel.i_MMInf *Builds a M/M/Infinite queue model*

Description

Builds a M/M/Infinite queue model

Usage

```
## S3 method for class 'i_MMInf'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMInf
...	additional arguments

Details

Build a M/M/Infinite model. It also checks the input params calling the [CheckInput.i_MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMInf](#)

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
QueueingModel(i_mminf)
```

`QueueingModel.i_MMInfKK`*Builds a M/M/Infinite/K/K queueing model*

Description

Builds a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'i_MMInfKK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMInfKK
...	additional arguments

Details

Build a M/M/Infinite/K/K queueing model. It also checks the input params calling the [CheckInput.i_MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MMInfKK](#)

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
QueueingModel(i_MMInfKK)
```

QueueingModel.i_OJN *Builds one Open Jackson Network*

Description

Builds one Open Jackson Network

Usage

```
## S3 method for class 'i_OJN'
QueueingModel(x, ...)
```

Arguments

x a object of class i_OJN
 ... additional arguments

Details

Build one Open Jackson Network. It also checks the input params calling the [CheckInput.i_OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

m_ojn1 <- QueueingModel(ojn1)
```

m_ojn1

Report

Reports the results of a queueing model

Description

Reports the results of a queueing model.

Usage

```
Report(x, ...)
```

Arguments

x	i_MM1, i_MMC, i_MM1K, i_MMCK, i_MM1KK, i_MMCKK, i_MMCC, i_MMCKM, i_MMInfKK, i_MMInf, i_OJN, i_MCON
...	additional arguments

Details

Generic S3 method to report a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Report the results  
Report(o_mm1)
```

`Report.o_CJN`*Reports the results of a Closed Jackson Network*

Description

Reports the results of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'  
Report(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_CJN</code>
<code>...</code>	additional arguments

Details

Generates a report of the queueing network received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)
```

```
# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Report(m_cjn1)
```

Report.o_MCCN

Reports the results of a MultiClass Closed Network

Description

Reports the results of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Report(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
```

```
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Report(o_MCCN1)
```

Report.o_MCMN

Reports the results of a MultiClass Mixed Network

Description

Reports the results of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Report(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Report(o_mcmn1)
```

Report.o_MCON

Reports the results of a MultiClass Open Network

Description

Reports the results of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Report(x, ...)
```

Arguments

x	a object of class o_MCON
...	aditional arguments

Details

Generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Report(o_mcon1)
```

Report.o_MM1

Reports the results of a M/M/1 queueing model

Description

Reports the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'o_MM1'
Report(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the results
Report(o_mm1)
```

Report.o_MM1K

Reports the results of a M/M/1/K queueing model

Description

Reports the results of a M/M/1/K queueing model.

Usage

```
## S3 method for class 'o_MM1K'
Report(x, ...)
```

Arguments

x a object of class o_MM1K
... additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Report the results
Report(o_mm1k)
```

Report.o_MM1KK	<i>Reports the results of a M/M/1/K/K queueing model</i>
----------------	--

Description

Reports the results of a M/M/1/K/K queueing model.

Usage

```
## S3 method for class 'o_MM1KK'
Report(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Report the results
Report(o_mm1kk)
```

Report.o_MMC

Reports the results of a M/M/c queueing model

Description

Reports the results of a M/M/c queueing model.

Usage

```
## S3 method for class 'o_MMC'
Report(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Report the results
Report(o_mmc)
```

Report.o_MMCC

Reports the results of a M/M/c/c queueing model

Description

Reports the results of a M/M/c/c queueing model.

Usage

```
## S3 method for class 'o_MMCC'
Report(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Report the results
Report(o_mmcc)
```

Report.o_MMCK	<i>Reports the results of a M/M/c/K queueing model</i>
---------------	--

Description

Reports the results of a M/M/c/K queueing model.

Usage

```
## S3 method for class 'o_MMCK'
Report(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Report the results
Report(o_mmck)
```

Report.o_MMCKK	<i>Reports the results of a M/M/c/K/K queueing model</i>
----------------	--

Description

Reports the results of a M/M/c/K/K queueing model.

Usage

```
## S3 method for class 'o_MMCKK'
Report(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Report the results
Report(o_mmckk)
```

Report.o_MMCKM	<i>Reports the results of a M/M/c/K/m queueing model</i>
----------------	--

Description

Reports the results of a M/M/c/K/m queueing model.

Usage

```
## S3 method for class 'o_MMCKM'
Report(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Report the results
Report(o_mmckm)
```

Report.o_MMInf	<i>Reports the results of a M/M/Infinite queueing model</i>
----------------	---

Description

Reports the results of a M/M/Infinite queueing model.

Usage

```
## S3 method for class 'o_MMInf'
Report(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Report the results
Report(o_mminf)
```

Report.o_MMInfKK	<i>Reports the results of a M/M/Infinite/K/K queueing model</i>
------------------	---

Description

Reports the results of a M/M/Infinite/K/K queueing model.

Usage

```
## S3 method for class 'o_MMInfKK'
Report(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Generates a report of the queueing model received as parameter

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Report the results
Report(o_MMInfKK)
```

Report.o_OJN

Reports the results of an Open Jackson Network

Description

Reports the results of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Report(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Generates a report of the queueing network received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

o_ojn <- QueueingModel(i_ojn)

Report(o_ojn)
```

RO

Reports the server use of a queueing model

Description

Reports the server use of a queueing model)

Usage

RO(x, ...)

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	aditional arguments

Details

Reports the server use of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[RO.o_MM1](#)
[RO.o_MM2](#)
[RO.o_MM1K](#)
[RO.o_MMCK](#)
[RO.o_MM1KK](#)
[RO.o_MMCKK](#)
[RO.o_MMCC](#)
[RO.o_MMCKM](#)
[RO.o_MMInfKK](#)
[RO.o_MMInf](#)

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the use of the server
RO(o_mm1)

```

RO.o_MM1

Reports the server use of a M/M/1 queueing model

Description

Reports the server use of a M/M/1 queueing model

Usage

```

## S3 method for class 'o_MM1'
RO(x, ...)

```

Arguments

x a object of class o_MM1
... additional arguments

Details

Reports the server use of a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the use of the server
RO(o_mm1)
```

 RO.o_MM1K

Reports the server use of a M/M/1/K queueing model

Description

Reports the server use of a M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
RO(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Reports the server use of a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Report the use of the server
RO(o_mm1k)
```

RO.o_MM1KK

Reports the server use of a M/M/1/K/K queueing model

Description

Reports the server use of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
RO(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Reports the server use of a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Report the use of the server
RO(o_mm1kk)
```

RO.o_MMC

Reports the server use of a M/M/c queueing model

Description

Reports the server use of a M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
RO(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Reports the server use of a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Report the use of the server
RO(o_mmc)
```

RO.o_MMCC

Reports the server use of a M/M/c/c queueing model

Description

Reports the server use of a M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
RO(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Reports the server use of a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Report the use of the server
RO(o_mmcc)
```

RO.o_MMCK

Reports the server use of a M/M/c/K queueing model

Description

Reports the server use of a M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
RO(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Reports the server use of a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Report the use of the server
RO(o_mmck)
```

RO.o_MMCKK

Reports the server use of a M/M/c/K/K queueing model

Description

Reports the server use of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
RO(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Reports the server use of a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Report the use of the server
RO(o_mmckk)
```

RO.o_MMCKM

Reports the server use of a M/M/c/K/m queueing model

Description

Reports the server use of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
RO(x, ...)
```

Arguments

x a object of class o_MMCKM
... additional arguments

Details

Reports the server use of a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Report the use of the server
RO(o_mmckm)
```

RO.o_MMInf

Reports the server use of a M/M/Infinite queueing model

Description

Reports the server use of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
RO(x, ...)
```

Arguments

x a object of class o_MMInf
... additional arguments

Details

Reports the server use of a M/M/Infinite queueing model. It should be noted that in this model, the RO parameter has a different meaning, its the traffic intensity and it coincides exactly with the average number of customers in the system (L)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#)
[L.o_MMInf](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Report the use of the server
RO(o_mminf)
```

RO.o_MMInfKK	<i>Reports the server use of a M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Reports the server use of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
RO(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Reports the server use of a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Report the use of the server
RO(o_MMInfKK)
```

ROck	<i>Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network</i>
------	--

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network

Usage

```
ROck(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	aditional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos CaballeROk, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial CentROk de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[ROck.o_MCON](#)
[ROck.o_MCCN](#)
[ROck.o_MCMN](#)

Examples

```

## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROck(o_MCCN1)

```

ROck.o_MCCN	<i>Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network</i>
-------------	--

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

Usage

```

## S3 method for class 'o_MCCN'
ROck(x, ...)

```

Arguments

x	a object of class o_MCCN
...	aditional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROck(o_MCCN1)
```

ROck.o_MCMN

Reports a matrix with the use of class i in each node (server) j in a MultiClass Mixed Network

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
ROck(x, ...)
```

Arguments

x a object of class o_MCMN
... additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

ROck(o_mcmn1)
```

ROck.o_MCON

Reports a matrix with the use of class i in each node (server) j in a MultiClass Open Network

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
ROck(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

ROk(o_mcon1)
```

 ROk

Reports a vector with each node (server) use of a queueing network

Description

Reports a vector with each node (server) use of a queueing network

Usage

```
ROk(x, ...)
```

Arguments

x a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
 . . . additional arguments

Details

Reports a vector with each node (server) use of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos CaballeROk, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial CentROk de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[ROk.o_OJN](#)
[ROk.o_CJN](#)
[ROk.o_MCON](#)
[ROk.o_MCCN](#)
[ROk.o_MCMN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROk(o_MCCN1)
```

ROk.o_CJN	<i>Reports a vector with each node (server) use of a Closed Jackson Network</i>
-----------	---

Description

Reports a vector with each node (server) use of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
ROk(x, ...)
```

Arguments

x	a object of class o_CJN
...	aditional arguments

Details

Reports a vector with each node (server) use of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN.](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)
```

```
# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

ROk(m_cjn1)
```

ROk.o_MCCN	<i>Reports a vector with each node (server) use of a MultiClass Closed Network</i>
------------	--

Description

Reports a vector with each node (server) use of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
ROk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a vector with each node (server) use of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROk(o_MCCN1)
```

ROk.o_MCMN	<i>Reports a vector with each node (server) use of a MultiClass Mixed Network</i>
------------	---

Description

Reports a vector with each node (server) use of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
ROk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Reports a vector with each node (server) use of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

ROk(o_mcmn1)
```

ROk.o_MCON	<i>Reports a vector with each node (server) use of a MultiClass Open Network</i>
------------	--

Description

Reports a vector with each node (server) use of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
ROk(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each node (server) use of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

ROk(o_mcon1)
```

ROk.o_OJN

Reports a vector with each node (server) use of an Open Jackson Network

Description

Reports a vector with each node (server) use of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
ROk(x, ...)
```

Arguments

x a object of class o_OJN
 ... additional arguments

Details

Reports a vector with each node (server) use of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Deinition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

R0k(o_ojn)
```

 SP

Returns the saturation point of a queueing model

Description

Returns the saturation point of a queueing model

Usage

SP(x, ...)

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

Returns the saturation point of a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[SP.o_MM1KK](#)

Examples

```
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=4, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the saturation point
SP(o_mm1kk)
```

SP.o_MM1KK

Returns the saturation point of a M/M/1/K/K queueing model

Description

Returns the saturation point, or the maximum number of customers that the M/M/1/K/K queueing model can support with no interference or synchronization between themselves

Usage

```
## S3 method for class 'o_MM1KK'
SP(x, ...)
```

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

The value returned is the optimal number of customers of a M/M/1/K/K queueing model. It coincides with the inverse of the serialization parameter of Amdahl's Law. That is, the value which converges the speedup $\text{func}(k) = k/(1 + \text{ser} * (k-1))$. It makes sense, because the saturation point is the maximum value in which no synchronization happens.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=4, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the saturation point
SP(o_mm1kk)
```

summary.o_CJN

Summary of the results of a Closed Jackson Network

Description

Summary of the results of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
summary(object, ...)
```

Arguments

```
object      a object of class o_CJN
...         additional arguments
```

Details

Summaries a Closed Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

summary(m_cjn1)
```

summary.o_MCCN

Summary of the results of a MultiClass Closed Network

Description

Summary of the results of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
summary(object, ...)
```

Arguments

```
object      a object of class o_MCCN  
...        additional arguments
```

Details

Summaries a queueing network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_MCCN1 <- QueueingModel(i_MCCN1)  
  
summary(o_MCCN1)
```

`summary.o_MCMN`*Summary of the results of a MultiClass Mixed Network*

Description

Summary of the results of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MCMN</code>
<code>...</code>	additional arguments

Details

Summaries a MultiClass Mixed Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.  
  
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=1, nrow=4, ncol=2)  
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)  
  
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcmn1 <- QueueingModel(i_mcmn1)
```

```
summary(o_mcmn1)
```

```
summary.o_MCON
```

Summary of the results of a MultiClass Open Network

Description

Summary of the results of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
summary(object, ...)
```

Arguments

```
object      a object of class o_MCON
...         additional arguments
```

Details

Summaries a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

```
# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

summary(o_mcon1)
```

summary.o_MM1

Summary of the results of a M/M/1 queueing model

Description

Summary of the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'o_MM1'
summary(object, ...)
```

Arguments

object	a object of class o_MM1
...	aditional arguments

Details

Summaries a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the results
summary(o_mm1)
```

`summary.o_MM1K`*Summary of the results of a M/M/1/K queueing model*

Description

Summary of the results of a M/M/1/K queueing model.

Usage

```
## S3 method for class 'o_MM1K'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MM1K</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Report the results  
summary(o_mm1k)
```

`summary.o_MM1KK`*Summary of the results of a M/M/1/K/K queueing model*

Description

Summary of the results of a M/M/1/K/K queueing model.

Usage

```
## S3 method for class 'o_MM1KK'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MM1KK</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Report the results  
summary(o_mm1kk)
```

`summary.o_MMC`*Summary of the results of a M/M/c queueing model*

Description

Summary of the results of a M/M/c queueing model.

Usage

```
## S3 method for class 'o_MMC'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMC</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Report the results  
summary(o_mmc)
```

`summary.o_MMCC`*Summary of the results of a M/M/c/c queueing model*

Description

Summary of the results of a M/M/c/c queueing model.

Usage

```
## S3 method for class 'o_MMCC'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCC</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Report the results  
summary(o_mmcc)
```

`summary.o_MMCK`*Summary of the results of a M/M/c/K queueing model*

Description

Summary of the results of a M/M/c/K queueing model.

Usage

```
## S3 method for class 'o_MMCK'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCK</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Report the results  
summary(o_mmck)
```

`summary.o_MMCKK`*Summary of the results of a M/M/c/K/K queueing model*

Description

Summary of the results of a M/M/c/K/K queueing model.

Usage

```
## S3 method for class 'o_MMCKK'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCKK</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Report the results  
summary(o_mmckk)
```

summary.o_MMCKM	<i>Summary of the results of a M/M/c/K/m queueing model</i>
-----------------	---

Description

Summary of the results of a M/M/c/K/m queueing model.

Usage

```
## S3 method for class 'o_MMCKM'  
summary(object, ...)
```

Arguments

object	a object of class o_MMCKM
...	additional arguments

Details

Summaries a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Report the results  
summary(o_mmckm)
```

`summary.o_MMInf`*Summary of the results of a M/M/Infinite queueing model*

Description

Summary of the results of a M/M/Infinite queueing model.

Usage

```
## S3 method for class 'o_MMInf'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMInf</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Report the results  
summary(o_mminf)
```

summary.o_MMInfKK	<i>Summary of the results of a M/M/Infinite/K/K queueing model</i>
-------------------	--

Description

Summary of the results of a M/M/Infinite/K/K queueing model.

Usage

```
## S3 method for class 'o_MMInfKK'  
summary(object, ...)
```

Arguments

object	a object of class o_MMInfKK
...	additional arguments

Details

Summaries a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Report the results  
summary(o_MMInfKK)
```

summary.o_OJN

Summary of the results of an Open Jackson Network

Description

Summary of the results of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
summary(object, ...)
```

Arguments

object	a object of class o_OJN
...	aditional arguments

Details

Summaries an Open Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

o_ojn <- QueueingModel(i_ojn)
```

summary(o_ojn)

Throughput *Throughput of a queueing model (or network)*

Description

Returns the throughput of a queueing model (or network)

Usage

Throughput(x, ...)

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the throughput of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughput.o_MM1](#)
[Throughput.o_MMC](#)
[Throughput.o_MM1K](#)
[Throughput.o_MMCK](#)
[Throughput.o_MM1KK](#)
[Throughput.o_MMCKK](#)
[Throughput.o_MMCC](#)
[Throughput.o_MMCKM](#)
[Throughput.o_MMInfKK](#)

```

Throughput.o_MMInf
Throughput.o_OJN
Throughput.o_CJN
Throughput.o_MCON
Throughput.o_MCCN
Throughput.o_MCMN

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Throughput
Throughput(o_mm1)

```

Throughput.o_CJN	<i>Reports the network throughput of a Closed Jackson Network</i>
------------------	---

Description

Reports the network throughput of a Closed Jackson Network

Usage

```

## S3 method for class 'o_CJN'
Throughput(x, ...)

```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Reports the network throughput of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughput(m_cjn1)
```

Throughput.o_MCCN *Reports the throughput of a MultiClass Closed Network*

Description

Reports the throughput of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughput(x, ...)
```

Arguments

x a object of class o_MCCN
 ... additional arguments

Details

Reports the throughput of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughput(o_MCCN1)
```

Throughput.o_MCMN *Reports the throughput of a MultiClass Mixed Network*

Description

Reports the throughput of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughput(x, ...)
```

Arguments

x a object of class o_MCMN
... additional arguments

Details

Reports the throughput of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughput(o_mcmn1)
```

Throughput.o_MCON *Reports the throughput of a MultiClass Open Network*

Description

Reports the throughput of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Throughput(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Reports the throughput of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughput(o_mcon1)
```

Throughput.o_MM1

Throughput of a M/M/1 queueing model

Description

Returns the throughput of a M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Throughput(x, ...)
```


Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the throughput of a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#), [CheckInput.i_MM1](#), [QueueingModel.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Throughput
Throughput(o_mm1)
```

Throughput.o_MM1K *Throughput of a M/M/1/K queueing model*

Description

Returns the throughput of a M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Throughput(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the throughput of a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#), [CheckInput.i_MM1K](#), [QueueingModel.i_MM1K](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mmck <- QueueingModel(i_mm1k)

## Throughput
Throughput(o_mmck)
```

Throughput.o_MM1KK *Throughput of a M/M/1/K/K queueing model*

Description

Returns the throughput of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Throughput(x, ...)
```

Arguments

x a object of class o_MM1KK
... additional arguments

Details

Returns the throughput of a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK](#), [CheckInput.i_MM1KK](#), [QueueingModel.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_MM1KKk <- QueueingModel(i_mm1kk)

## Throughput
Throughput(o_MM1KKk)
```

Throughput.o_MMC

Throughput of a M/M/c queueing model

Description

Returns the throughput of a M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Throughput(x, ...)
```

Arguments

x a object of class o_MMC
 ... additional arguments

Details

Returns the throughput of a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC](#), [CheckInput.i_MMC](#), [QueueingModel.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Throughput
Throughput(o_mmc)
```

Throughput.o_MMCC *Throughput of a M/M/c/c queueing model*

Description

Returns the throughput of a M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Throughput(x, ...)
```

Arguments

x a object of class o_MMCC
 ... additional arguments

Details

Returns the throughput of a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC](#), [CheckInput.i_MMCC](#), [QueueingModel.i_MMCC](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Throughput
Throughput(o_mmcc)
```

Throughput.o_MMCK	<i>Throughput of a M/M/c/K queueing model</i>
-------------------	---

Description

Returns the throughput of a M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the throughput of a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#), [CheckInput.i_MMCK](#), [QueueingModel.i_MMCK](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Throughput
Throughput(o_mmck)
```

Throughput.o_MMCKK *Throughput of a M/M/c/K/K queueing model*

Description

Returns the throughput of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Throughput(x, ...)
```

Arguments

x a object of class o_MMCKK
... additional arguments

Details

Returns the throughput of a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#), [CheckInput.i_MMCKK](#), [QueueingModel.i_MMCKK](#)

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## build the model
o_mmckk <- QueueingModel(i_mmckk)

## Throughput
Throughput(o_mmckk)
```

Throughput.o_MMCKM *Throughput of a M/M/c/K/m queueing model*

Description

Returns the throughput of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Throughput(x, ...)
```

Arguments

x a object of class o_MMCKM
 ... additional arguments

Details

Returns the throughput of a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#), [CheckInput.i_MMCKM](#), [QueueingModel.i_MMCKM](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Throughput
Throughput(o_mmckm)
```

Throughput.o_MMInf *Throughput of a M/M/Infinite queueing model*

Description

Returns the throughput of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Throughput(x, ...)
```

Arguments

x a object of class o_MMInf
... additional arguments

Details

Returns the throughput of a M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#), [CheckInput.i_MMInf](#), [QueueingModel.i_MMInf](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Throughput
Throughput(o_mminf)
```

Throughput.o_MMInfKK *Throughput of a M/M/Infinite/K/K queueing model*

Description

Returns the throughput of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the throughput of a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#), [CheckInput.i_MMInfKK](#), [QueueingModel.i_MMInfKK](#)

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Throughput
Throughput(o_MMInfKK)
```

Throughput.o_OJN	<i>Reports the throughput of an Open Jackson Network</i>
------------------	--

Description

Reports the throughput of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Throughput(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Reports the throughput of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_OJN](#), [QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Throughput(o_ojn)
```

Throughputc	<i>Reports a vector with each class throughput in a multiclass queueing network</i>
-------------	---

Description

Reports a vector with each class throughput in a multiclass queueing network

Usage

```
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Reports a vector with each class throughput in a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputc.o_MCON](#)
[Throughputc.o_MCCN](#)
[Throughputc.o_MCCN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputc(o_mcon1)
```

Throughputc.o_MCCN	<i>Reports a vector with each class throughput in a MultiClass Closed Network</i>
--------------------	---

Description

Reports a vector with each class throughput in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a vector with each class throughput in a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.

Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputc(o_MCCN1)
```

Throughputc.o_MCMN	<i>Reports a vector with each class throughput in a MultiClass Mixed Network</i>
--------------------	--

Description

Reports a vector with each class throughput in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughputc(x, ...)
```

Arguments

```
x          a object of class o_MCMN
...        additional arguments
```

Details

Reports a vector with each class throughput in a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputc(o_mcmn1)
```

Throughputc.o_MCON	<i>Reports a vector with each class throughput in a MultiClass Open Network</i>
--------------------	---

Description

Reports a vector with each class throughput in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'  
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each class throughput in a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)
```

```

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputc(o_mcon1)

```

Throughputck	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network</i>
--------------	--

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network

Usage

```
Throughputck(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN
...	additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputck.o_MCON](#)

[Throughputck.o_MCCN](#)

[Throughputck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputck(o_mcon1)
```

Throughputck.o_MCCN *Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network*

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputck(x, ...)
```

Arguments

x a object of class o_MCCN
 ... additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputck(o_MCCN1)
```

Throughputck.o_MCMN	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network</i>
---------------------	--

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughputck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.

Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputck(o_mcmn1)
```

Throughputck.o_MCON	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network</i>
---------------------	---

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Throughputck(x, ...)
```

Arguments

```
x          a object of class o_MCON
...        additional arguments
```

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputck(o_mcon1)
```

Throughputcn	<i>Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network</i>
--------------	--

Description

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

Usage

```
Throughputcn(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputcn.o_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputcn(o_MCCN1)
```

Throughputcn.o_MCCN *Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network*

Description

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputcn(x, ...)
```

Arguments

x a object of class o_MCCN
... additional arguments

Details

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputcn(o_MCCN1)
```

Throughputk	<i>Reports a vector with each node (server) throughput of a queueing network</i>
-------------	--

Description

Reports a vector with each node (server) throughput of a queueing network

Usage

```
Throughputk(x, ...)
```

Arguments

x	a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Reports a vector with each node (server) throughput of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik

(1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputk.o_OJN](#)
[Throughputk.o_CJN](#)
[Throughputk.o_MCON](#)
[Throughputk.o_MCCN](#)
[Throughputk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputk(o_mcon1)
```

Throughputk.o_CJN	<i>Reports a vector with each node (server) throughput of a Closed Jackson Network</i>
-------------------	--

Description

Reports a vector with each node (server) throughput of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Throughputk(x, ...)
```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Reports a vector with each node (server) throughput of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputk(m_cjn1)
```

Throughputk.o_MCCN	<i>Reports a vector with each node (server) throughput of a MultiClass Closed Network</i>
--------------------	---

Description

Reports a vector with each node (server) throughput of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputk(x, ...)
```

Arguments

```
x          a object of class o_MCCN
...        additional arguments
```

Details

Reports a vector with each node (server) throughput of a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputk(o_MCCN1)
```

Throughputk.o_MCMN	<i>Reports a vector with each node (server) throughput of a MultiClass Mixed Network</i>
--------------------	--

Description

Reports a vector with each node (server) throughput of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'  
Throughputk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a vector with each node (server) throughput of a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.
```

```
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")
```

```

vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputk(o_mcmn1)

```

Throughputk.o_MCON	<i>Reports a vector with each node (server) throughput of a MultiClass Open Network</i>
--------------------	---

Description

Reports a vector with each node (server) throughput of a MultiClass Open Network

Usage

```

## S3 method for class 'o_MCON'
Throughputk(x, ...)

```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each node (server) throughput of a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputk(o_mcon1)
```

Throughputk.o_OJN	<i>Reports a vector with each node (server) throughput of an Open Jackson Network</i>
-------------------	---

Description

Reports a vector with each node (server) throughput of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Throughputk(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Reports a vector with each node (server) throughput of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_OJN](#), [QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Throughputk(o_ojn)
```

Throughputn

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network

Description

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network

Usage

```
Throughputn(x, ...)
```

Arguments

x a object of class o_CJN
 ... additional arguments

Details

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Throughputn.o_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputn(m_cjn1)
```

Throughputn.o_CJN	<i>Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network</i>
-------------------	---

Description

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Throughputn(x, ...)
```

Arguments

x a object of class o_CJN
 ... additional arguments

Details

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputn(m_cjn1)
```

VN	Returns the variance of the number of customers in a queueing model (or network)
----	--

Description

Returns the variance of the number of customers in a queueing model (or network)

Usage

```
VN(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in a queueing model (or network)

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[VN.o_MM1](#)
[VN.o_MMC](#)
[VN.o_MMCC](#)
[VN.o_MMInf](#)
[VN.o_MMInfKK](#)
[VN.o_MM1K](#)
[VN.o_MMCK](#)
[VN.o_MM1KK](#)
[VN.o_MMCKK](#)
[VN.o_MMCKM](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)
```

```
## Returns the variance  
VN(o_mm1)
```

VN.o_MM1	<i>Returns the variance of the number of customers in the M/M/1 queueing model</i>
----------	--

Description

Returns the variance of the number of customers in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
VN(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the variance  
VN(o_mm1)
```

VN.o_MM1K	<i>Returns the variance of the number of customers in the M/M/1/K queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VN(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VN(o_mm1k)
```

VN.o_MM1KK	<i>Returns the variance of the number of customers in the M/M/1/K/K queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VN(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VN(o_mm1kk)
```

VN.o_MMC	<i>Returns the variance of the number of customers in the M/M/c queueing model</i>
----------	--

Description

Returns the variance of the number of customers in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VN(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance  
VN(o_mmc)
```

VN.o_MMCC	<i>Returns the variance of the number of customers in the M/M/c/c queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VN(o_mmcc)
```

VN.o_MMCK	<i>Returns the variance of the number of customers in the M/M/c/K queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VN(o_mmck)
```

VN.o_MMCKK	<i>Returns the variance of the number of customers in the M/M/c/K/K queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VN(o_mmckk)
```

VN.o_MMCKM	<i>Returns the variance of the number of customers in the M/M/c/K/m queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/c/K/m queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the variance  
VN(o_mmckm)
```

VN.o_MMInf	<i>Returns the variance of the number of customers in the M/M/Infinite queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VN(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VN(o_mminf)
```

VN.o_MMInfKK	<i>Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model</i>
--------------	---

Description

Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the variance  
VN(o_MMInfKK)
```

VNq	<i>Returns the variance of the number of customers in the queue in a queueing model</i>
-----	---

Description

Returns the variance of the number of customers in the queue in a queueing model

Usage

```
VNq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMCC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the queue in a queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[VNq.o_MM1](#)
[VNq.o_MM1](#)
[VNq.o_MMCC](#)
[VNq.o_MMInf](#)
[VNq.o_MMInfKK](#)
[VNq.o_MM1K](#)
[VNq.o_MMCK](#)
[VNq.o_MM1KK](#)
[VNq.o_MMCKK](#)
[VNq.o_MMCKM](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)
```

```
## Returns the variance
VNq(o_mm1)
```

VNq.o_MM1	<i>Returns the variance of the number of customers in the queue in the M/M/1 queueing model</i>
-----------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
VNq(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance
VNq(o_mm1)
```

VNq.o_MM1K	<i>Returns the variance of the number of customers in the queue in the M/M/1/K queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VNq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VNq(o_mm1k)
```

VNq.o_MM1KK	<i>Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VNq(o_mm1kk)
```

VNq.o_MMC	<i>Returns the variance of the number of customers in the queue in the M/M/c queueing model</i>
-----------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance  
VNq(o_mmc)
```

VNq.o_MMCC	<i>Returns the variance of the number of customers in the queue in the M/M/c/c queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VNq(o_mmcc)
```

VNq.o_MMCK	<i>Returns the variance of the number of customers in the queue in the M/M/c/K queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VNq(o_mmck)
```

VNq.o_MMCKK	<i>Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VNq(o_mmckk)
```

VNq.o_MMCKM	<i>Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the variance  
VNq(o_mmckm)
```

VNq.o_MMInf	<i>Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model</i>
-------------	--

Description

Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VNq(o_mminf)
```

VNq.o_MMInfKK	<i>Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model</i>
---------------	--

Description

Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the VNq  
VNq(o_MMInfKK)
```

VT	Returns the variance of the time spend in a queueing model (or network)
----	---

Description

Returns the variance of the time spend in a queueing model (or network)

Usage

```
VT(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the time spend in a queueing model (or network)

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[VT.o_MM1](#)
[VT.o_MMC](#)
[VT.o_MMCC](#)
[VT.o_MMInf](#)
[VT.o_MMInfKK](#)
[VT.o_MM1K](#)
[VT.o_MM1KK](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in the system
VT(o_mm1)
```

`VT.o_MM1`*Returns the variance of the time spend in the M/M/1 queueing model*

Description

Returns the variance of the time spend in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
VT(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MM1</code>
<code>...</code>	aditional arguments

Details

Returns the variance of the time spend in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the variance of the time spend in the system  
VT(o_mm1)
```

VT.o_MM1K *Returns the variance of the time spend in the M/M/1/K queueing model*

Description

Returns the variance of the time spend in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VT(x, ...)
```

Arguments

x a object of class o_MM1K
... additional arguments

Details

Returns the variance of the time spend in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VT(o_mm1k)
```

VT.o_MM1KK	<i>Returns the variance of the time spend in the M/M/1/K/K queueing model</i>
------------	---

Description

Returns the variance of the time spend in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VT(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the time spend in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VT(o_mm1kk)
```

VT.o_MMC *Returns the variance of the time spend in the M/M/c queueing model*

Description

Returns the variance of the time spend in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VT(x, ...)
```

Arguments

x a object of class o_MMC
... additional arguments

Details

Returns the variance of the time spend in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance of the time spend in the system  
VT(o_mmc)
```

`VT.o_MMCC`*Returns the variance of the time spend in the M/M/c/c queueing model*

Description

Returns the variance of the time spend in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VT(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MMCC</code>
<code>...</code>	additional arguments

Details

Returns the variance of the time spend in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VT(o_mmcc)
```

VT.o_MMInf	<i>Returns the variance of the time spend in the M/M/Infinite queueing model</i>
------------	--

Description

Returns the variance of the time spend in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VT(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the the variance of the time spend in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VT(o_mminf)
```

VT.o_MMInfKK	<i>Returns the variance of the time spend in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the variance of the time spend in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VT(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the variance of the time spend in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the variance  
VT(o_MMInfKK)
```

VTq	<i>Returns the variance of the time spend in queue in a queueing model</i>
-----	--

Description

Returns the variance of the time spend in queue in a queueing model

Usage

```
VTq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMIInfKK, o_MMIInf
...	additional arguments

Details

Returns the variance of the time spend in queue in a queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[VTq.o_MM1](#)
[VTq.o_MMC](#)
[VTq.o_MMCC](#)
[VTq.o_MMIInf](#)
[VTq.o_MMIInfKK](#)
[VTq.o_MM1K](#)
[VTq.o_MMCK](#)
[VTq.o_MM1KK](#)
[VTq.o_MMCKK](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in queue
VTq(o_mm1)
```

VTq.o_MM1	<i>Returns the variance of the time spend in queue in the M/M/1 queueing model</i>
-----------	--

Description

Returns the variance of the time spend in queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the variance of the time spend in queue  
VTq(o_mm1)
```

VTq.o_MM1K	<i>Returns the variance of the time spend in queue in the M/M/1/K queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VTq(o_mm1k)
```

VTq.o_MM1KK	<i>Returns the variance of the time spend in queue in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the variance of the time spend in queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the VTq  
VTq(o_mm1kk)
```

VTq.o_MMC	<i>Returns the variance of the time spend in queue in the M/M/c queueing model</i>
-----------	--

Description

Returns the variance of the time spend in queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance of the time spend in queue  
VTq(o_mmc)
```

VTq.o_MMCC	<i>Returns the variance of the time spend in queue in the M/M/c/c queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VTq(o_mmcc)
```

VTq.o_MMCK	<i>Returns the variance of the time spend in queue in the M/M/c/K queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VTq(o_mmck)
```

VTq.o_MMCKK	<i>Returns the variance of the time spend in queue in the M/M/c/K/K queueing model</i>
-------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VTq(o_mmckk)
```

VTq.o_MMInf	<i>Returns the variance of the time spend in queue in the M/M/Infinite queueing model</i>
-------------	---

Description

Returns the variance of the time spend in queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the time spend in queue in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VTq(o_mminf)
```

VTq.o_MMInfKK	<i>Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model</i>
---------------	---

Description

Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the variance  
VTq(o_MMInfKK)
```

W *Returns the mean time spend in a queueing model (or network)*

Description

Returns the mean time spend in a queueing model (or network)

Usage

$W(x, \dots)$

Arguments

x a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_MCON, o_MCCN, o_MCMN
... additional arguments

Details

Returns the mean time spend in a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[W.o_MM1](#)
[W.o_MMC](#)
[W.o_MM1K](#)
[W.o_MMCK](#)
[W.o_MM1KK](#)
[W.o_MMCKK](#)
[W.o_MMCC](#)
[W.o_MMCKM](#)
[W.o_MMInfKK](#)
[W.o_MMInf](#)
[W.o_OJN](#)
[W.o_MCON](#)
[W.o_MCCN](#)
[W.o_MCMN](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the W
W(o_mm1)
```

W.o_CJN

Returns the mean time spend in a Closed Jackson Network

Description

Returns the mean time spend in a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
W(x, ...)
```

Arguments

x a object of class o_CJN
... additional arguments

Details

Returns the mean time spend in a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```

## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

W(m_cjn1)

```

W.o_MCCN

Returns the mean time spend in a MultiClass Closed Network

Description

Returns the mean time spend in a MultiClass Closed Network

Usage

```

## S3 method for class 'o_MCCN'
W(x, ...)

```

Arguments

x	a object of class o_MCCN
...	aditional arguments

Details

Returns the mean time spend in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

W(o_MCCN1)
```

W.o_MCMN

Returns the mean time spend in a MultiClass Mixed Network

Description

Returns the mean time spend in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
W(x, ...)
```

Arguments

x a object of class o_MCMN
 ... additional arguments

Details

Returns the mean time spend in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

W(o_mcmn1)
```

W.o_MCON

Returns the mean time spend in a MultiClass Open Network

Description

Returns the mean time spend in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
W(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Returns the mean time spend in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON.](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

W(o_mcon1)
```

W.o_MMI

Returns the mean time spend in the M/M/1 queueing model

Description

Returns the mean time spend in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MMI'
W(x, ...)
```

Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the mean time spend in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the W
W(o_mm1)
```

W.o_MM1K

Returns the mean time spend in the M/M/1/K queueing model

Description

Returns the mean time spend in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
W(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean time spend in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the W
W(o_mm1k)
```

W.o_MM1KK

Returns the mean time spend in the M/M/1/K/K queueing model

Description

Returns the mean time spend in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
W(x, ...)
```

Arguments

x a object of class o_MM1KK
... additional arguments

Details

Returns the mean time spend in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the W
W(o_mm1kk)
```

W.o_MMC

Returns the mean time spend in the M/M/c queueing model

Description

Returns the mean time spend in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
W(x, ...)
```

Arguments

x a object of class o_MMC
 ... additional arguments

Details

Returns the mean time spend in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the W
W(o_mmc)
```

W.o_MMCC

Returns the mean time spend in the M/M/c/c queueing model

Description

Returns the mean time spend in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
W(x, ...)
```

Arguments

x a object of class o_MMCC
 ... additional arguments

Details

Returns the mean time spend in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the W
W(o_mmcc)
```

W.o_MMCK

Returns the mean time spend in the M/M/c/K queueing model

Description

Returns the mean time spend in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
W(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean time spend in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the W
W(o_mmck)
```

W.o_MMCKK

Returns the mean time spend in the M/M/c/K/K queueing model

Description

Returns the mean time spend in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
W(x, ...)
```

Arguments

x a object of class o_MMCKK
... additional arguments

Details

Returns the mean time spend in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the W
W(o_mmckk)
```

W.o_MMCKM

Returns the mean time spend in the M/M/c/K/m queueing model

Description

Returns the mean time spend in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
W(x, ...)
```

Arguments

x a object of class o_MMCKM
... additional arguments

Details

Returns the mean time spend in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the W
W(o_mmckm)
```

W.o_MMInf

Returns the time spend in the M/M/Infinite queueing model

Description

Returns the mean time spend in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
W(x, ...)
```

Arguments

x a object of class o_MMInf
... additional arguments

Details

Returns the mean time spend in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf.](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the W
W(o_mminf)
```

W.o_MMInfKK	Returns the mean time spend in the M/M/Infinite/K/K queueing model
-------------	--

Description

Returns the mean time spend in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
W(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the mean time spend in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the W
W(o_MMInfKK)
```

W.o_OJN

Returns the mean time spend in an Open Jackson Network

Description

Returns the mean time spend in an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
W(x, ...)
```

Arguments

x a object of class o_OJN
... additional arguments

Details

Returns the mean time spend in an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

W(o_ojn)
```

Wc	<i>Returns the vector with each class mean time spend on a multiclass queueing network</i>
----	--

Description

Returns the vector with each class mean time spend on a multiclass queueing network

Usage

```
Wc(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the vector with each class mean time spend on a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wc.o_MCON](#)
[Wc.o_MCCN](#)
[Wc.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wc(o_mcon1)
```

Wc.o_MCCN	<i>Returns the vector with each class mean time spend on a MultiClass Closed Network</i>
-----------	--

Description

Returns the vector with each class mean time spend on a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Wc(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns the vector with each class mean time spend on a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Wc(o_MCCN1)
```

Wc.o_MCMN

Returns the vector with each class mean time spend on a MultiClass Mixed Network

Description

Returns the vector with each class mean time spend on a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wc(x, ...)
```

Arguments

x a object of class o_MCMN
 ... additional arguments

Details

Returns the vector with each class mean time spend on a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN.](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wc(o_mcmn1)
```

Wc.o_MCON

Returns the vector with each class mean time spend on a MultiClass Open Network

Description

Returns the vector with each class mean time spend on a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'  
Wc(x, ...)
```

Arguments

```
x          a object of class o_MCON  
...        additional arguments
```

Details

Returns the vector with each class mean time spend on a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
Wc(o_mcon1)
```

Wck	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network</i>
-----	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network

Usage

```
Wck(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wck.o_MCON](#)
[Wck.o_MCCN](#)
[Wck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
```

```

vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wck(o_mcon1)

```

Wck.o_MCCN	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network</i>
------------	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network

Usage

```

## S3 method for class 'o_MCCN'
Wck(x, ...)

```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Wck(o_MCCN1)
```

Wck.o_MCMN	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network</i>
------------	---

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wck(o_mcmn1)
```

Wck.o_MCON

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Wck(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wck(o_mcon1)
```

Wk	<i>Generic S3 method to return the mean time spend in each node (or server) of a network</i>
----	--

Description

Generic S3 method to return the mean time spend in each node (or server) of a network

Usage

```
Wk(x, ...)
```

Arguments

x	a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Generic S3 method to return the mean time spend in each node (or server) of a network

References

- [Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.
- [Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wk.o_OJN](#)
[Wk.o_CJN](#)
[Wk.o_MCON](#)
[Wk.o_MCCN](#)
[Wk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wk(o_mcon1)
```

Wk.o_CJN	<i>Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network</i>
----------	--

Description

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Wk(x, ...)
```

Arguments

x a object of class o_CJN
... additional arguments

Details

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)  
  
# Define a new input  
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)  
  
# Check the inputs and build the model  
m_cjn1 <- QueueingModel(cjn1)  
  
Wk(m_cjn1)
```

Wk.o_MCCN	Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network
-----------	--

Description

Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
Wk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_MCCN1 <- QueueingModel(i_MCCN1)
```

```
Wk(o_MCMN1)
```

Wk.o_MCMN	<i>Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network</i>
-----------	--

Description

Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)
```

```
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wk(o_mcmn1)
```

Wk.o_MCON	<i>Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network</i>
-----------	---

Description

Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Wk(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wk(o_mcon1)
```

Wk.o_OJN

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

Description

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Wk(x, ...)
```

Arguments

x a object of class o_OJN
... additional arguments

Details

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

m_ojn1 <- QueueingModel(ojn1)

Wk(m_ojn1)
```

Wq

Returns the mean time spend in queue in a queueing model

Description

Returns the mean time spend in queue in a queueing model

Usage

Wq(x, ...)

Arguments

x a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK,
o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
... additional arguments

Details

Returns the mean time spend in queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[Wq.o_MM1](#)
[Wq.o_MMC](#)
[Wq.o_MM1K](#)
[Wq.o_MMCK](#)
[Wq.o_MM1KK](#)
[Wq.o_MMCKK](#)
[Wq.o_MMCC](#)
[Wq.o_MMCKM](#)
[Wq.o_MMInfKK](#)
[Wq.o_MMInf](#)

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wq
Wq(o_mm1)

```

Wq.o_MM1

Returns the mean time spend in queue in the M/M/1 queueing model

Description

Returns the mean time spend in queue in the M/M/1 queueing model

Usage

```

## S3 method for class 'o_MM1'
Wq(x, ...)

```

Arguments

x a object of class o_MM1
... additional arguments

Details

Returns the mean time spend in queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wq
Wq(o_mm1)
```

Wq.o_MM1K

Returns the mean time spend in queue in the M/M/1/K queueing model

Description

Returns the mean time spend in queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Wq(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean time spend in queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Wq
Wq(o_mm1k)
```

Wq.o_MM1KK	<i>Returns the mean time spend in queue in the M/M/1/K/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wq
Wq(o_mm1kk)
```

Wq.o_MMC	<i>Returns the mean time spend in queue in the M/M/c queueing model</i>
----------	---

Description

Returns the mean time spend in queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Wq(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Wq
Wq(o_mmc)
```

Wq.o_MMCC	<i>Returns the mean time spend in queue in the M/M/c/c queueing model</i>
-----------	---

Description

Returns the mean time spend in queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Wq
Wq(o_mmcc)
```

Wq.o_MMCK	<i>Returns the mean time spend in queue in the M/M/c/K queueing model</i>
-----------	---

Description

Returns the mean time spend in queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Wq
Wq(o_mmck)
```

Wq.o_MMCKK	<i>Returns the mean time spend in queue in the M/M/c/K/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Wq
Wq(o_mmckk)
```

Wq.o_MMCKM	<i>Returns the mean time spend in queue in the M/M/c/K/m queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Wq
Wq(o_mmckm)
```

Wq.o_MMInf	<i>Returns the mean time spend in queue in the M/M/Infinite queueing model</i>
------------	--

Description

Returns the mean time spend in queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Wq
Wq(o_mminf)
```

Wq.o_MMInfKK	<i>Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Wq
Wq(o_MMInfKK)
```

Wq _q	<i>Returns the mean time spend in queue when there is queue in a queueing model</i>
-----------------	---

Description

Returns the mean time spend in queue when there is queue in a queueing model

Usage

```
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMCC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Wq_q.o_MM1](#)
[Wq_q.o_MMCC](#)
[Wq_q.o_MM1K](#)
[Wq_q.o_MMCK](#)
[Wq_q.o_MM1KK](#)
[Wq_q.o_MMCKK](#)
[Wq_q.o_MMCC](#)

```

Wqq.o_MMCKM
Wqq.o_MMInfKK
Wqq.o_MMInf

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wqq
Wqq(o_mm1)

```

Wqq.o_MM1	<i>Returns the mean time spend in queue when there is queue in the M/M/1 queueing model</i>
-----------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1 queueing model

Usage

```

## S3 method for class 'o_MM1'
Wqq(x, ...)

```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wqq
Wqq(o_mm1)
```

Wqq.o_MM1K	<i>Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Wqq
Wqq(o_mm1k)
```

Wqq.o_MM1KK	<i>Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wqq
Wqq(o_mm1kk)
```

Wqq.o_MMC	<i>Returns the mean time spend in queue when there is queue in the M/M/c queueing model</i>
-----------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Wqq
Wqq(o_mmc)
```

Wqq.o_MMCC	<i>Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Wqq
Wqq(o_mmcc)
```

Wqq.o_MMCK	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Wqq
Wqq(o_mmck)
```

Wqq.o_MMCKK	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Wqq
Wqq(o_mmckk)
```

Wqq.o_MMCKM	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Wq
Wq(o_mmckm)
```

Wq.o_MMInf	<i>Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model</i>
------------	--

Description

Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Wq
Wq(o_mminf)
```

Wq.o_MMInfKK	<i>Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Wqq
Wqq(o_MMInfKK)
```

WwS

Returns the normalized mean response time in a queueing model

Description

Returns the normalized mean response time in a queueing model

Usage

```
WwS(x, ...)
```

Arguments

x a object of class o_MM1KK
... additional arguments

Details

Returns the normalized mean response time in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[WwS.o_MM1KK.](#)

Examples

```
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wws
Wws(o_mm1kk)
```

Wws.o_MM1KK	<i>Returns the normalized mean response time in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the normalized mean response time in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wws(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the normalized mean response time in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the WVs  
WVs(o_mm1kk)
```

Index

- *Topic **B_erlang**
 - B_erlang, [10](#)
- *Topic **C_erlang**
 - C_erlang, [28](#)
- *Topic **Closed Jackson Network**
 - CheckInput.i_CJN, [12](#)
 - Inputs.o_CJN, [30](#)
 - L.o_CJN, [47](#)
 - Lk.o_CJN, [73](#)
 - NewInput.CJN, [101](#)
 - print.summary.o_CJN, [131](#)
 - QueueingModel.i_CJN, [148](#)
 - Report.o_CJN, [164](#)
 - ROk.o_CJN, [196](#)
 - summary.o_CJN, [203](#)
 - Throughput.o_CJN, [220](#)
 - Throughputk.o_CJN, [248](#)
 - Throughputn.o_CJN, [255](#)
 - W.o_CJN, [298](#)
 - Wk.o_CJN, [323](#)
- *Topic **CompareQueueingModels**
 - CompareQueueingModels, [27](#)
- *Topic **Engset**
 - Engset, [29](#)
- *Topic **M/M/1/K/K**
 - CheckInput.i_MM1KK, [18](#)
 - Inputs.o_MM1KK, [37](#)
 - L.o_MM1KK, [54](#)
 - Lq.o_MM1KK, [82](#)
 - Lqq.o_MM1KK, [93](#)
 - NewInput.MM1KK, [109](#)
 - Pn.o_MM1KK, [122](#)
 - print.summary.o_MM1KK, [138](#)
 - QueueingModel.i_MM1KK, [154](#)
 - Report.o_MM1KK, [170](#)
 - RO.o_MM1KK, [182](#)
 - SP, [201](#)
 - SP.o_MM1KK, [202](#)
 - summary.o_MM1KK, [210](#)
 - Throughput.o_MM1KK, [226](#)
 - VN.o_MM1KK, [260](#)
 - VNq.o_MM1KK, [271](#)
 - VT.o_MM1KK, [282](#)
 - VTq.o_MM1KK, [290](#)
 - W.o_MM1KK, [304](#)
 - Wq.o_MM1KK, [332](#)
 - Wqq.o_MM1KK, [343](#)
 - Wws, [351](#)
 - Wws.o_MM1KK, [352](#)
- *Topic **M/M/1/K**
 - CheckInput.i_MM1K, [17](#)
 - Inputs.o_MM1K, [36](#)
 - L.o_MM1K, [53](#)
 - Lq.o_MM1K, [81](#)
 - Lqq.o_MM1K, [92](#)
 - NewInput.MM1K, [108](#)
 - Pn.o_MM1K, [121](#)
 - print.summary.o_MM1K, [137](#)
 - QueueingModel.i_MM1K, [153](#)
 - Report.o_MM1K, [169](#)
 - RO.o_MM1K, [181](#)
 - summary.o_MM1K, [209](#)
 - Throughput.o_MM1K, [225](#)
 - VN.o_MM1K, [259](#)
 - VNq.o_MM1K, [270](#)
 - VT.o_MM1K, [281](#)
 - VTq.o_MM1K, [289](#)
 - W.o_MM1K, [303](#)
 - Wq.o_MM1K, [331](#)
 - Wqq.o_MM1K, [342](#)
- *Topic **M/M/1**
 - CheckInput.i_MM1, [16](#)
 - Inputs.o_MM1, [35](#)
 - L.o_MM1, [52](#)
 - Lq, [79](#)
 - Lq.o_MM1, [80](#)
 - Lqq, [90](#)
 - Lqq.o_MM1, [91](#)

- NewInput.MM1, 107
- Pn.o_MM1, 120
- print.summary.o_MM1, 136
- QueueingModel.i_MM1, 152
- Report, 163
- Report.o_MM1, 168
- RO.o_MM1, 180
- summary.o_MM1, 208
- Throughput.o_MM1, 224
- VN.o_MM1, 258
- VNq, 268
- VNq.o_MM1, 269
- VT.o_MM1, 280
- VTq, 287
- VTq.o_MM1, 288
- W.o_MM1, 302
- Wq, 329
- Wq.o_MM1, 330
- Wqq, 340
- Wqq.o_MM1, 341
- *Topic M/M/Infinite/K/K**
 - CheckInput.i_MMInfFKK, 25
 - Inputs.o_MMInfFKK, 44
 - L.o_MMInfFKK, 61
 - Lq.o_MMInfFKK, 89
 - Lqq.o_MMInfFKK, 100
 - NewInput.MMInfFKK, 116
 - Pn.o_MMInfFKK, 129
 - print.summary.o_MMInfFKK, 145
 - QueueingModel.i_MMInfFKK, 161
 - Report.o_MMInfFKK, 177
 - RO.o_MMInfFKK, 189
 - summary.o_MMInfFKK, 217
 - Throughput.o_MMInfFKK, 233
 - VN.o_MMInfFKK, 267
 - VNq.o_MMInfFKK, 278
 - VT.o_MMInfFKK, 286
 - VTq.o_MMInfFKK, 296
 - W.o_MMInfFKK, 311
 - Wq.o_MMInfFKK, 339
 - Wqq.o_MMInfFKK, 350
- *Topic M/M/Infinite**
 - CheckInput.i_MMInf, 24
 - Inputs.o_MMInf, 43
 - L.o_MMInf, 60
 - Lq.o_MMInf, 88
 - Lqq.o_MMInf, 99
 - NewInput.MMInf, 115
 - Pn.o_MMInf, 128
 - print.summary.o_MMInf, 144
 - QueueingModel.i_MMInf, 160
 - Report.o_MMInf, 176
 - RO.o_MMInf, 188
 - summary.o_MMInf, 216
 - Throughput.o_MMInf, 232
 - VN.o_MMInf, 266
 - VNq.o_MMInf, 277
 - VT.o_MMInf, 285
 - VTq.o_MMInf, 295
 - W.o_MMInf, 310
 - Wq.o_MMInf, 338
 - Wqq.o_MMInf, 349
- *Topic M/M/c/K/K**
 - CheckInput.i_MMCKK, 22
 - Inputs.o_MMCKK, 41
 - L.o_MMCKK, 58
 - Lq.o_MMCKK, 86
 - Lqq.o_MMCKK, 97
 - NewInput.MMCKK, 113
 - Pn.o_MMCKK, 126
 - print.summary.o_MMCKK, 142
 - QueueingModel.i_MMCKK, 158
 - Report.o_MMCKK, 174
 - RO.o_MMCKK, 186
 - summary.o_MMCKK, 214
 - Throughput.o_MMCKK, 230
 - VN.o_MMCKK, 264
 - VNq.o_MMCKK, 275
 - VTq.o_MMCKK, 294
 - W.o_MMCKK, 308
 - Wq.o_MMCKK, 336
 - Wqq.o_MMCKK, 347
- *Topic M/M/c/K/m**
 - CheckInput.i_MMCKM, 23
 - Inputs.o_MMCKM, 42
 - L.o_MMCKM, 59
 - Lq.o_MMCKM, 87
 - Lqq.o_MMCKM, 98
 - NewInput.MMCKM, 114
 - Pn.o_MMCKM, 127
 - print.summary.o_MMCKM, 143
 - QueueingModel.i_MMCKM, 159
 - Report.o_MMCKM, 175
 - RO.o_MMCKM, 187
 - summary.o_MMCKM, 215
 - Throughput.o_MMCKM, 231

- VN.o_MMCKM, 265
- VNq.o_MMCKM, 276
- W.o_MMCKM, 309
- Wq.o_MMCKM, 337
- Wqq.o_MMCKM, 348
- *Topic **M/M/c/K**
 - CheckInput.i_MMCK, 21
 - Inputs.o_MMCK, 40
 - L.o_MMCK, 57
 - Lq.o_MMCK, 85
 - Lqq.o_MMCK, 96
 - NewInput.MMCK, 112
 - Pn.o_MMCK, 125
 - print.summary.o_MMCK, 141
 - QueueingModel.i_MMCK, 157
 - Report.o_MMCK, 173
 - RO.o_MMCK, 185
 - summary.o_MMCK, 213
 - Throughput.o_MMCK, 229
 - VN.o_MMCK, 263
 - VNq.o_MMCK, 274
 - VTq.o_MMCK, 293
 - W.o_MMCK, 307
 - Wq.o_MMCK, 335
 - Wqq.o_MMCK, 346
- *Topic **M/M/c/c**
 - CheckInput.i_MMCC, 20
 - Inputs.o_MMCC, 39
 - L.o_MMCC, 56
 - Lq.o_MMCC, 84
 - Lqq.o_MMCC, 95
 - NewInput.MMCC, 111
 - Pn.o_MMCC, 124
 - print.summary.o_MMCC, 140
 - QueueingModel.i_MMCC, 156
 - Report.o_MMCC, 172
 - RO.o_MMCC, 184
 - summary.o_MMCC, 212
 - Throughput.o_MMCC, 228
 - VN.o_MMCC, 262
 - VNq.o_MMCC, 273
 - VT.o_MMCC, 284
 - VTq.o_MMCC, 292
 - W.o_MMCC, 306
 - Wq.o_MMCC, 334
 - Wqq.o_MMCC, 345
- *Topic **M/M/c**
 - CheckInput.i_MMC, 19
 - Inputs.o_MMC, 38
 - L.o_MMC, 55
 - Lq.o_MMC, 83
 - Lqq.o_MMC, 94
 - NewInput.MMC, 110
 - Pn.o_MMC, 123
 - print.summary.o_MMC, 139
 - QueueingModel.i_MMC, 155
 - Report.o_MMC, 171
 - RO.o_MMC, 183
 - summary.o_MMC, 211
 - Throughput.o_MMC, 227
 - VN.o_MMC, 261
 - VNq.o_MMC, 272
 - VT.o_MMC, 283
 - VTq.o_MMC, 291
 - W.o_MMC, 305
 - Wq.o_MMC, 333
 - Wqq.o_MMC, 344
- *Topic **MultiClass Closed Network**
 - CheckInput.i_MCCN, 13
 - Inputs.o_MCCN, 32
 - L.o_MCCN, 48
 - Lc.o_MCCN, 64
 - Lck.o_MCCN, 69
 - Lk.o_MCCN, 75
 - NewInput.MCCN, 103
 - print.summary.o_MCCN, 132
 - QueueingModel.i_MCCN, 149
 - Report.o_MCCN, 165
 - ROck.o_MCCN, 191
 - ROk.o_MCCN, 197
 - summary.o_MCCN, 204
 - Throughput.o_MCCN, 221
 - Throughputc.o_MCCN, 236
 - Throughputck.o_MCCN, 241
 - Throughputcn, 245
 - Throughputcn.o_MCCN, 246
 - Throughputk.o_MCCN, 249
 - W.o_MCCN, 299
 - Wc.o_MCCN, 314
 - Wck.o_MCCN, 319
 - Wk.o_MCCN, 325
- *Topic **MultiClass Mixed Network**
 - CheckInput.i_MCMN, 14
 - Inputs.o_MCMN, 33
 - L.o_MCMN, 49
 - Lc.o_MCMN, 65

- Lck.o_MCMN, 70
- Lk.o_MCMN, 76
- NewInput.MCMN, 104
- print.summary.o_MCMN, 133
- QueueingModel.i_MCMN, 150
- Report.o_MCMN, 166
- ROck.o_MCMN, 192
- ROk.o_MCMN, 198
- summary.o_MCMN, 206
- Throughput.o_MCMN, 222
- Throughputc.o_MCMN, 237
- Throughputck.o_MCMN, 242
- Throughputk.o_MCMN, 251
- W.o_MCMN, 300
- Wc.o_MCMN, 315
- Wck.o_MCMN, 320
- Wk.o_MCMN, 326
- *Topic **MultiClass Open Network**
 - CheckInput.i_MCON, 15
 - Inputs.o_MCON, 34
 - L.o_MCON, 51
 - Lc.o_MCON, 66
 - Lck.o_MCON, 71
 - Lk.o_MCON, 77
 - NewInput.MCON, 106
 - print.summary.o_MCON, 135
 - QueueingModel.i_MCON, 151
 - Report.o_MCON, 167
 - ROck.o_MCON, 193
 - ROk.o_MCON, 199
 - summary.o_MCON, 207
 - Throughput.o_MCON, 223
 - Throughputc.o_MCON, 239
 - Throughputck.o_MCON, 243
 - Throughputk.o_MCON, 252
 - W.o_MCON, 301
 - Wc.o_MCON, 316
 - Wck.o_MCON, 321
 - Wk.o_MCON, 327
- *Topic **MultiClass Queueing Models**
 - Lck, 67
- *Topic **MultiClass Queueing Networks**
 - ROck, 190
- *Topic **MultiClass Queueing Network**
 - Lc, 63
 - Throughputc, 235
 - Throughputck, 240
- Wc, 313
- Wck, 318
- *Topic **Open Jackson Network**
 - CheckInput.i_OJN, 26
 - Inputs.o_OJN, 45
 - L.o_OJN, 62
 - Lk.o_OJN, 78
 - NewInput.OJN, 117
 - Pn.o_OJN, 130
 - print.summary.o_OJN, 146
 - QueueingModel.i_OJN, 162
 - Report.o_OJN, 178
 - ROk.o_OJN, 200
 - summary.o_OJN, 218
 - Throughput.o_OJN, 234
 - Throughputk.o_OJN, 253
 - W.o_OJN, 312
 - Wk.o_OJN, 328
- *Topic **Queueing Models**
 - CheckInput, 11
 - Inputs, 29
 - L, 46
 - Lk, 72
 - Pn, 119
 - QueueingModel, 147
 - RO, 179
 - Throughput, 219
 - VN, 257
 - VT, 279
 - W, 297
- *Topic **Queueing Networks**
 - ROk, 194
- *Topic **Queueing Network**
 - Throughputk, 247
 - Throughputn, 254
 - Wk, 322
- *Topic **queueing**
 - queueing-package, 8
- B_erlang, 10, 28, 29
- C_erlang, 11, 28
- CheckInput, 11
- CheckInput.i_CJN, 12, 148, 221, 249, 256
- CheckInput.i_MCCN, 13, 149, 222, 237, 242, 246, 250
- CheckInput.i_MCMN, 14, 150, 151, 223, 238, 243, 251

- CheckInput.i_MCON, [15](#), [151](#), [152](#), [224](#), [239](#), [244](#), [252](#)
- CheckInput.i_MM1, [12](#), [16](#), [108](#), [152](#), [153](#), [225](#)
- CheckInput.i_MM1K, [12](#), [17](#), [108](#), [153](#), [154](#), [226](#)
- CheckInput.i_MM1KK, [12](#), [18](#), [109](#), [154](#), [227](#)
- CheckInput.i_MMC, [12](#), [19](#), [110](#), [155](#), [228](#)
- CheckInput.i_MMCC, [12](#), [20](#), [111](#), [156](#), [229](#)
- CheckInput.i_MMCK, [12](#), [21](#), [112](#), [157](#), [230](#)
- CheckInput.i_MMCKK, [12](#), [22](#), [113](#), [158](#), [231](#)
- CheckInput.i_MMCKM, [12](#), [23](#), [114](#), [159](#), [232](#)
- CheckInput.i_MMInf, [12](#), [24](#), [115](#), [160](#), [232](#)
- CheckInput.i_MMInfKK, [12](#), [25](#), [116](#), [161](#), [233](#)
- CheckInput.i_OJN, [12](#), [26](#), [162](#), [234](#), [254](#)
- CompareQueueingModels, [27](#)
- CompareQueueingModels2
(CompareQueueingModels), [27](#)
- Engset, [29](#)
- Inputs, [29](#)
- Inputs.o_CJN, [30](#), [30](#)
- Inputs.o_MCCN, [30](#), [32](#)
- Inputs.o_MCMN, [30](#), [33](#)
- Inputs.o_MCON, [30](#), [34](#)
- Inputs.o_MM1, [30](#), [35](#)
- Inputs.o_MM1K, [30](#), [36](#)
- Inputs.o_MM1KK, [30](#), [37](#)
- Inputs.o_MMC, [30](#), [38](#)
- Inputs.o_MMCC, [30](#), [39](#)
- Inputs.o_MMCK, [30](#), [40](#)
- Inputs.o_MMCKK, [30](#), [41](#)
- Inputs.o_MMCKM, [30](#), [42](#)
- Inputs.o_MMInf, [30](#), [43](#)
- Inputs.o_MMInfKK, [30](#), [44](#)
- Inputs.o_OJN, [30](#), [45](#)
- L, [46](#)
- L.o_CJN, [47](#), [47](#)
- L.o_MCCN, [47](#), [48](#)
- L.o_MCMN, [47](#), [49](#)
- L.o_MCON, [47](#), [51](#)
- L.o_MM1, [47](#), [52](#)
- L.o_MM1K, [47](#), [53](#)
- L.o_MM1KK, [47](#), [54](#)
- L.o_MMC, [47](#), [55](#)
- L.o_MMCC, [47](#), [56](#)
- L.o_MMCK, [47](#), [57](#)
- L.o_MMCKK, [47](#), [58](#)
- L.o_MMCKM, [47](#), [59](#)
- L.o_MMInf, [47](#), [60](#), [188](#)
- L.o_MMInfKK, [47](#), [61](#)
- L.o_OJN, [47](#), [62](#)
- Lc, [63](#)
- Lc.o_MCCN, [63](#), [64](#)
- Lc.o_MCMN, [63](#), [65](#)
- Lc.o_MCON, [63](#), [66](#)
- Lck, [67](#)
- Lck.o_MCCN, [68](#), [69](#)
- Lck.o_MCMN, [68](#), [70](#)
- Lck.o_MCON, [68](#), [71](#)
- Lk, [72](#)
- Lk.o_CJN, [73](#), [73](#)
- Lk.o_MCCN, [73](#), [75](#)
- Lk.o_MCMN, [73](#), [76](#)
- Lk.o_MCON, [73](#), [77](#)
- Lk.o_OJN, [73](#), [78](#)
- Lq, [79](#)
- Lq.o_MM1, [80](#), [80](#)
- Lq.o_MM1K, [80](#), [81](#)
- Lq.o_MM1KK, [80](#), [82](#)
- Lq.o_MMC, [80](#), [83](#)
- Lq.o_MMCC, [80](#), [84](#)
- Lq.o_MMCK, [80](#), [85](#)
- Lq.o_MMCKK, [80](#), [86](#)
- Lq.o_MMCKM, [80](#), [87](#)
- Lq.o_MMInf, [80](#), [88](#)
- Lq.o_MMInfKK, [80](#), [89](#)
- Lqq, [90](#)
- Lqq.o_MM1, [90](#), [91](#)
- Lqq.o_MM1K, [90](#), [92](#)
- Lqq.o_MM1KK, [90](#), [93](#)
- Lqq.o_MMC, [90](#), [94](#)
- Lqq.o_MMCC, [90](#), [95](#)
- Lqq.o_MMCK, [90](#), [96](#)
- Lqq.o_MMCKK, [90](#), [97](#)
- Lqq.o_MMCKM, [91](#), [98](#)
- Lqq.o_MMInf, [91](#), [99](#)
- Lqq.o_MMInfKK, [91](#), [100](#)
- NewInput.CJN, [12](#), [13](#), [31](#), [101](#), [249](#), [256](#)
- NewInput.MCCN, [14](#), [32](#), [103](#), [222](#), [237](#), [242](#), [246](#), [250](#)
- NewInput.MCMN, [15](#), [33](#), [104](#), [223](#), [238](#), [243](#), [251](#)
- NewInput.MCON, [16](#), [34](#), [106](#), [224](#), [239](#), [244](#), [252](#)
- NewInput.MM1, [17](#), [35](#), [36](#), [107](#), [225](#)

- NewInput.MM1K, [17](#), [18](#), [36](#), [108](#), [226](#)
 NewInput.MM1KK, [18](#), [19](#), [37](#), [109](#), [227](#)
 NewInput.MMC, [19](#), [38](#), [110](#), [228](#)
 NewInput.MMCC, [20](#), [39](#), [111](#), [229](#)
 NewInput.MMCK, [21](#), [40](#), [112](#), [230](#)
 NewInput.MMCKK, [22](#), [41](#), [113](#), [231](#)
 NewInput.MMCKM, [23](#), [42](#), [114](#), [232](#)
 NewInput.MMInf, [24](#), [43](#), [115](#), [232](#)
 NewInput.MMInfFKK, [25](#), [44](#), [116](#), [233](#)
 NewInput.OJN, [26](#), [45](#), [117](#), [221](#), [234](#), [254](#)
 NewInput2.CJN (NewInput.CJN), [101](#)
 NewInput2.OJN (NewInput.OJN), [117](#)
 NewInput3.CJN (NewInput.CJN), [101](#)
 NewInput3.OJN (NewInput.OJN), [117](#)
- Pn, [119](#)
 Pn.o_MM1, [119](#), [120](#)
 Pn.o_MM1K, [119](#), [121](#)
 Pn.o_MM1KK, [119](#), [122](#)
 Pn.o_MMC, [119](#), [123](#)
 Pn.o_MMCC, [120](#), [124](#)
 Pn.o_MMCK, [119](#), [125](#)
 Pn.o_MMCKK, [119](#), [126](#)
 Pn.o_MMCKM, [120](#), [127](#)
 Pn.o_MMInf, [120](#), [128](#)
 Pn.o_MMInfFKK, [120](#), [129](#)
 Pn.o_OJN, [120](#), [130](#)
 print.summary.o_CJN, [131](#)
 print.summary.o_MCCN, [132](#)
 print.summary.o_MCMN, [133](#)
 print.summary.o_MCON, [135](#)
 print.summary.o_MM1, [136](#)
 print.summary.o_MM1K, [137](#)
 print.summary.o_MM1KK, [138](#)
 print.summary.o_MMC, [139](#)
 print.summary.o_MMCC, [140](#)
 print.summary.o_MMCK, [141](#)
 print.summary.o_MMCKK, [142](#)
 print.summary.o_MMCKM, [143](#)
 print.summary.o_MMInf, [144](#)
 print.summary.o_MMInfFKK, [145](#)
 print.summary.o_OJN, [146](#)
- Qn (Pn), [119](#)
 Qn.o_MM1, [119](#)
 Qn.o_MM1 (Pn.o_MM1), [120](#)
 Qn.o_MM1K, [119](#)
 Qn.o_MM1K (Pn.o_MM1K), [121](#)
 Qn.o_MM1KK, [119](#)
 Qn.o_MM1KK (Pn.o_MM1KK), [122](#)
 Qn.o_MMC, [119](#)
 Qn.o_MMC (Pn.o_MMC), [123](#)
 Qn.o_MMCC, [120](#)
 Qn.o_MMCC (Pn.o_MMCC), [124](#)
 Qn.o_MMCK, [119](#)
 Qn.o_MMCK (Pn.o_MMCK), [125](#)
 Qn.o_MMCKK, [119](#)
 Qn.o_MMCKK (Pn.o_MMCKK), [126](#)
 Qn.o_MMCKM, [120](#)
 Qn.o_MMCKM (Pn.o_MMCKM), [127](#)
 Qn.o_MMInf, [120](#)
 Qn.o_MMInf (Pn.o_MMInf), [128](#)
 Qn.o_MMInfFKK, [120](#)
 Qn.o_MMInfFKK (Pn.o_MMInfFKK), [129](#)
 queueing (queueing-package), [8](#)
 queueing-package, [8](#)
 QueueingModel, [27](#), [147](#), [163](#)
 QueueingModel.i_CJN, [48](#), [74](#), [102](#), [132](#), [148](#),
 [164](#), [196](#), [204](#), [221](#), [249](#), [256](#), [298](#),
 [324](#)
 QueueingModel.i_MCCN, [49](#), [65](#), [69](#), [75](#), [104](#),
 [133](#), [149](#), [165](#), [192](#), [197](#), [205](#), [222](#),
 [237](#), [242](#), [246](#), [250](#), [300](#), [315](#), [319](#),
 [325](#)
 QueueingModel.i_MCMN, [50](#), [66](#), [70](#), [76](#), [105](#),
 [134](#), [150](#), [166](#), [193](#), [199](#), [206](#), [223](#),
 [238](#), [243](#), [251](#), [301](#), [316](#), [321](#), [326](#)
 QueueingModel.i_MCON, [51](#), [67](#), [72](#), [78](#), [107](#),
 [135](#), [147](#), [151](#), [168](#), [194](#), [200](#), [207](#),
 [224](#), [239](#), [244](#), [252](#), [302](#), [317](#), [322](#),
 [327](#)
 QueueingModel.i_MM1, [52](#), [81](#), [91](#), [121](#), [136](#),
 [147](#), [152](#), [169](#), [181](#), [208](#), [225](#), [258](#),
 [269](#), [280](#), [288](#), [303](#), [331](#), [341](#)
 QueueingModel.i_MM1K, [53](#), [54](#), [82](#), [92](#), [122](#),
 [137](#), [147](#), [153](#), [169](#), [182](#), [209](#), [226](#),
 [259](#), [260](#), [270](#), [281](#), [289](#), [304](#), [332](#),
 [342](#)
 QueueingModel.i_MM1KK, [83](#), [93](#), [123](#), [138](#),
 [147](#), [154](#), [170](#), [182](#), [203](#), [210](#), [227](#),
 [271](#), [282](#), [290](#), [305](#), [332](#), [343](#), [352](#)
 QueueingModel.i_MMC, [55](#), [84](#), [94](#), [124](#), [139](#),
 [147](#), [155](#), [171](#), [183](#), [211](#), [228](#), [261](#),
 [272](#), [283](#), [291](#), [306](#), [333](#), [344](#)
 QueueingModel.i_MMCC, [56](#), [85](#), [95](#), [125](#), [140](#),
 [147](#), [156](#), [172](#), [184](#), [212](#), [229](#), [262](#),
 [273](#), [284](#), [292](#), [306](#), [334](#), [345](#)

- QueueingModel.i_MMCK, [57](#), [86](#), [96](#), [126](#), [141](#),
[147](#), [157](#), [173](#), [185](#), [213](#), [230](#), [263](#),
[274](#), [293](#), [307](#), [335](#), [346](#)
- QueueingModel.i_MMCKK, [58](#), [87](#), [97](#), [127](#),
[142](#), [147](#), [158](#), [174](#), [186](#), [214](#), [231](#),
[264](#), [275](#), [294](#), [308](#), [336](#), [347](#)
- QueueingModel.i_MMCKM, [59](#), [88](#), [98](#), [128](#),
[143](#), [147](#), [159](#), [175](#), [187](#), [215](#), [232](#),
[265](#), [276](#), [309](#), [337](#), [348](#)
- QueueingModel.i_MMInf, [60](#), [88](#), [99](#), [129](#),
[144](#), [147](#), [160](#), [176](#), [188](#), [216](#), [232](#),
[266](#), [277](#), [285](#), [295](#), [310](#), [338](#), [349](#)
- QueueingModel.i_MMInfFKK, [61](#), [89](#), [100](#), [130](#),
[145](#), [147](#), [161](#), [177](#), [189](#), [217](#), [233](#),
[267](#), [278](#), [286](#), [296](#), [311](#), [339](#), [350](#)
- QueueingModel.i_OJN, [62](#), [79](#), [118](#), [131](#), [146](#),
[147](#), [162](#), [178](#), [201](#), [218](#), [234](#), [254](#),
[312](#), [329](#)
- Report, [163](#)
- Report.o_CJN, [164](#)
- Report.o_MCCN, [165](#)
- Report.o_MCMN, [166](#)
- Report.o_MCON, [167](#)
- Report.o_MM1, [168](#)
- Report.o_MM1K, [169](#)
- Report.o_MM1KK, [170](#)
- Report.o_MMC, [171](#)
- Report.o_MMCC, [172](#)
- Report.o_MMCK, [173](#)
- Report.o_MMCKK, [174](#)
- Report.o_MMCKM, [175](#)
- Report.o_MMInf, [176](#)
- Report.o_MMInfFKK, [177](#)
- Report.o_OJN, [178](#)
- RO, [179](#)
- RO.o_MM1, [180](#), [180](#)
- RO.o_MM1K, [180](#), [181](#)
- RO.o_MM1KK, [180](#), [182](#)
- RO.o_MMC, [180](#), [183](#)
- RO.o_MMCC, [180](#), [184](#)
- RO.o_MMCK, [180](#), [185](#)
- RO.o_MMCKK, [180](#), [186](#)
- RO.o_MMCKM, [180](#), [187](#)
- RO.o_MMInf, [180](#), [188](#)
- RO.o_MMInfFKK, [180](#), [189](#)
- ROck, [190](#)
- ROck.o_MCCN, [191](#), [191](#)
- ROck.o_MCMN, [191](#), [192](#)
- ROck.o_MCON, [191](#), [193](#)
- ROk, [194](#)
- ROk.o_CJN, [195](#), [196](#)
- ROk.o_MCCN, [195](#), [197](#)
- ROk.o_MCMN, [195](#), [198](#)
- ROk.o_MCON, [195](#), [199](#)
- ROk.o_OJN, [195](#), [200](#)
- SP, [201](#)
- SP.o_MM1KK, [202](#), [202](#)
- summary.o_CJN, [203](#)
- summary.o_MCCN, [204](#)
- summary.o_MCMN, [206](#)
- summary.o_MCON, [207](#)
- summary.o_MM1, [208](#)
- summary.o_MM1K, [209](#)
- summary.o_MM1KK, [210](#)
- summary.o_MMC, [211](#)
- summary.o_MMCC, [212](#)
- summary.o_MMCK, [213](#)
- summary.o_MMCKK, [214](#)
- summary.o_MMCKM, [215](#)
- summary.o_MMInf, [216](#)
- summary.o_MMInfFKK, [217](#)
- summary.o_OJN, [218](#)
- Throughput, [219](#)
- Throughput.o_CJN, [220](#), [220](#)
- Throughput.o_MCCN, [220](#), [221](#)
- Throughput.o_MCMN, [220](#), [222](#)
- Throughput.o_MCON, [220](#), [223](#)
- Throughput.o_MM1, [219](#), [224](#)
- Throughput.o_MM1K, [219](#), [225](#)
- Throughput.o_MM1KK, [219](#), [226](#)
- Throughput.o_MMC, [219](#), [227](#)
- Throughput.o_MMCC, [219](#), [228](#)
- Throughput.o_MMCK, [219](#), [229](#)
- Throughput.o_MMCKK, [219](#), [230](#)
- Throughput.o_MMCKM, [219](#), [231](#)
- Throughput.o_MMInf, [220](#), [232](#)
- Throughput.o_MMInfFKK, [219](#), [233](#)
- Throughput.o_OJN, [220](#), [234](#)
- Throughputc, [235](#)
- Throughputc.o_MCCN, [236](#), [236](#)
- Throughputc.o_MCMN, [237](#)
- Throughputc.o_MCON, [236](#), [239](#)
- Throughputck, [240](#)
- Throughputck.o_MCCN, [240](#), [241](#)
- Throughputck.o_MCMN, [240](#), [242](#)

- Throughputck.o_MCON, 240, 243
 Throughputcn, 245
 Throughputcn.o_MCCN, 245, 246
 Throughputk, 247
 Throughputk.o_CJN, 248, 248
 Throughputk.o_MCCN, 248, 249
 Throughputk.o_MCMN, 248, 251
 Throughputk.o_MCON, 248, 252
 Throughputk.o_OJN, 248, 253
 Throughputn, 254
 Throughputn.o_CJN, 255, 255

 VN, 257
 VN.o_MM1, 257, 258
 VN.o_MM1K, 257, 259
 VN.o_MM1KK, 257, 260
 VN.o_MMC, 257, 261
 VN.o_MMCC, 257, 262
 VN.o_MMCK, 257, 263
 VN.o_MMCKK, 257, 264
 VN.o_MMCKM, 257, 265
 VN.o_MMInf, 257, 266
 VN.o_MMInfKK, 257, 267
 VNq, 268
 VNq.o_MM1, 268, 269
 VNq.o_MM1K, 268, 270
 VNq.o_MM1KK, 268, 271
 VNq.o_MMC, 272
 VNq.o_MMCC, 268, 273
 VNq.o_MMCK, 268, 274
 VNq.o_MMCKK, 268, 275
 VNq.o_MMCKM, 268, 276
 VNq.o_MMInf, 268, 277
 VNq.o_MMInfKK, 268, 278
 VT, 279
 VT.o_MM1, 279, 280
 VT.o_MM1K, 279, 281
 VT.o_MM1KK, 279, 282
 VT.o_MMC, 279, 283
 VT.o_MMCC, 279, 284
 VT.o_MMInf, 279, 285
 VT.o_MMInfKK, 279, 286
 VTq, 287
 VTq.o_MM1, 287, 288
 VTq.o_MM1K, 287, 289
 VTq.o_MM1KK, 287, 290
 VTq.o_MMC, 287, 291
 VTq.o_MMCC, 287, 292
 VTq.o_MMCK, 287, 293

 VTq.o_MMCKK, 287, 294
 VTq.o_MMInf, 287, 295
 VTq.o_MMInfKK, 287, 296

 W, 297
 W.o_CJN, 298
 W.o_MCCN, 297, 299
 W.o_MCMN, 297, 300
 W.o_MCON, 297, 301
 W.o_MM1, 297, 302
 W.o_MM1K, 297, 303
 W.o_MM1KK, 297, 304
 W.o_MMC, 297, 305
 W.o_MMCC, 297, 306
 W.o_MMCK, 297, 307
 W.o_MMCKK, 297, 308
 W.o_MMCKM, 297, 309
 W.o_MMInf, 297, 310
 W.o_MMInfKK, 297, 311
 W.o_OJN, 297, 312
 Wc, 313
 Wc.o_MCCN, 314, 314
 Wc.o_MCMN, 314, 315
 Wc.o_MCON, 314, 316
 Wck, 318
 Wck.o_MCCN, 318, 319
 Wck.o_MCMN, 318, 320
 Wck.o_MCON, 318, 321
 Wk, 322
 Wk.o_CJN, 323, 323
 Wk.o_MCCN, 323, 325
 Wk.o_MCMN, 323, 326
 Wk.o_MCON, 323, 327
 Wk.o_OJN, 323, 328
 Wq, 329
 Wq.o_MM1, 330, 330
 Wq.o_MM1K, 330, 331
 Wq.o_MM1KK, 330, 332
 Wq.o_MMC, 330, 333
 Wq.o_MMCC, 330, 334
 Wq.o_MMCK, 330, 335
 Wq.o_MMCKK, 330, 336
 Wq.o_MMCKM, 330, 337
 Wq.o_MMInf, 330, 338
 Wq.o_MMInfKK, 330, 339
 Wqq, 340
 Wqq.o_MM1, 340, 341
 Wqq.o_MM1K, 340, 342
 Wqq.o_MM1KK, 340, 343

Wqq.o_MMC, [340](#), [344](#)
Wqq.o_MMCC, [340](#), [345](#)
Wqq.o_MMCK, [340](#), [346](#)
Wqq.o_MMCKK, [340](#), [347](#)
Wqq.o_MMCKM, [341](#), [348](#)
Wqq.o_MMInf, [341](#), [349](#)
Wqq.o_MMInfKK, [341](#), [350](#)
Wws, [351](#)
Wws.o_MM1KK, [351](#), [352](#)