

Package ‘queueing’

December 8, 2019

Version 0.2.12

Date 2019-12-09

Title Analysis of Queueing Networks and Models

Author Pedro Canadilla

Maintainer Pedro Canadilla <pedro.canadilla@gmail.com>

Depends R (>= 2.11.1)

Description

It provides versatile tools for analysis of birth and death based Markovian Queueing Models and Single and Multiclass Product-Form Queueing Networks.

It imple-

ments M/M/1, M/M/c, M/M/Infinite, M/M/1/K, M/M/c/K, M/M/c/c, M/M/1/K/K, M/M/c/K/K, M/M/c/K/m, M/M/Infinite/K, Multiple Channel Open Jackson Networks, Multiple Channel Closed Jackson Networks, Single Channel Multiple Class Open Networks, Single Channel Multiple Class Closed Networks and Single Channel Multiple Class Mixed Networks.

Also it provides a B-Erlang, C-Erlang and Engset calculators.

This work is dedicated to the memory of D. Sixto Rios Insua.

License GPL-2

Copyright Pedro Canadilla

URL <https://www.r-project.org>

NeedsCompilation no

Repository CRAN

Date/Publication 2019-12-08 22:10:02 UTC

RoxygenNote 6.0.1

R topics documented:

queueing-package	9
B_erlang	10
CheckInput	11
CheckInput.i_BnD	12
CheckInput.i_CJN	13

CheckInput.i_MCCN	14
CheckInput.i_MCMN	15
CheckInput.i_MCON	16
CheckInput.i_MM1	17
CheckInput.i_MM1K	18
CheckInput.i_MM1KK	19
CheckInput.i_MMC	20
CheckInput.i_MMCC	21
CheckInput.i_MMCK	22
CheckInput.i_MMCKK	23
CheckInput.i_MMCKM	24
CheckInput.i_MMInf	25
CheckInput.i_MMInfKK	26
CheckInput.i_OJN	27
CompareQueueingModels	28
C_erlang	29
Engset	30
Inputs	30
Inputs.o_BnD	31
Inputs.o_CJN	32
Inputs.o_MCCN	34
Inputs.o_MCMN	35
Inputs.o_MCON	36
Inputs.o_MM1	37
Inputs.o_MM1K	38
Inputs.o_MM1KK	39
Inputs.o_MMC	40
Inputs.o_MMCC	41
Inputs.o_MMCK	42
Inputs.o_MMCKK	43
Inputs.o_MMCKM	44
Inputs.o_MMInf	45
Inputs.o_MMInfKK	46
Inputs.o_OJN	47
L	48
L.o_BnD	49
L.o_CJN	50
L.o_MCCN	51
L.o_MCMN	52
L.o_MCON	54
L.o_MM1	55
L.o_MM1K	56
L.o_MM1KK	57
L.o_MMC	58
L.o_MMCC	59
L.o_MMCK	60
L.o_MMCKK	61
L.o_MMCKM	62

L.o_MMInf	63
L.o_MMInfKK	64
L.o_OJN	65
Lc	66
Lc.o_MCCN	67
Lc.o_MCMN	68
Lc.o_MCON	69
Lck	70
Lck.o_MCCN	72
Lck.o_MCMN	73
Lck.o_MCON	74
Lk	75
Lk.o_CJN	76
Lk.o_MCCN	78
Lk.o_MCMN	79
Lk.o_MCON	80
Lk.o_OJN	81
Lq	82
Lq.o_MM1	83
Lq.o_MM1K	84
Lq.o_MM1KK	85
Lq.o_MMC	86
Lq.o_MMCC	87
Lq.o_MMCK	88
Lq.o_MMCKK	89
Lq.o_MMCKM	90
Lq.o_MMInf	91
Lq.o_MMInfKK	92
Lqq	93
Lqq.o_MM1	94
Lqq.o_MM1K	95
Lqq.o_MM1KK	96
Lqq.o_MMC	97
Lqq.o_MMCC	98
Lqq.o_MMCK	99
Lqq.o_MMCKK	100
Lqq.o_MMCKM	101
Lqq.o_MMInf	102
Lqq.o_MMInfKK	103
NewInput.BnD	104
NewInput.CJN	105
NewInput.MCCN	107
NewInput.MCMN	108
NewInput.MCON	110
NewInput.MM1	111
NewInput.MM1K	112
NewInput.MM1KK	113
NewInput.MMC	114

NewInput.MMCC	115
NewInput.MMCK	116
NewInput.MMCKK	117
NewInput.MMCKM	118
NewInput.MMInf	119
NewInput.MMInfKK	120
NewInput.OJN	121
Pn	123
Pn.o_BnD	124
Pn.o_MM1	125
Pn.o_MM1K	127
Pn.o_MM1KK	128
Pn.o_MMC	129
Pn.o_MMCC	130
Pn.o_MMCK	131
Pn.o_MMCKK	132
Pn.o_MMCKM	133
Pn.o_MMInf	134
Pn.o_MMInfKK	135
Pn.o_OJN	136
print.summary.o_BnD	137
print.summary.o_CJN	138
print.summary.o_MCCN	139
print.summary.o_MCMN	140
print.summary.o_MCON	141
print.summary.o_MM1	142
print.summary.o_MM1K	143
print.summary.o_MM1KK	144
print.summary.o_MMC	145
print.summary.o_MMCC	146
print.summary.o_MMCK	147
print.summary.o_MMCKK	148
print.summary.o_MMCKM	149
print.summary.o_MMInf	150
print.summary.o_MMInfKK	151
print.summary.o_OJN	152
QueueingModel	153
QueueingModel.i_BnD	154
QueueingModel.i_CJN	155
QueueingModel.i_MCCN	156
QueueingModel.i_MCMN	157
QueueingModel.i_MCON	159
QueueingModel.i_MM1	160
QueueingModel.i_MM1K	161
QueueingModel.i_MM1KK	162
QueueingModel.i_MMC	163
QueueingModel.i_MMCC	164
QueueingModel.i_MMCK	165

QueueingModel.i_MMCKK	166
QueueingModel.i_MMCKM	167
QueueingModel.i_MMInf	168
QueueingModel.i_MMInfKK	169
QueueingModel.i_OJN	170
Report	171
Report.o_BnD	172
Report.o_CJN	173
Report.o_MCCN	174
Report.o_MCMN	175
Report.o_MCON	176
Report.o_MM1	177
Report.o_MM1K	178
Report.o_MM1KK	179
Report.o_MMC	180
Report.o_MMCC	181
Report.o_MMCK	182
Report.o_MMCKK	183
Report.o_MMCKM	184
Report.o_MMInf	185
Report.o_MMInfKK	186
Report.o_OJN	187
RO	188
RO.o_MM1	189
RO.o_MM1K	190
RO.o_MM1KK	191
RO.o_MMC	192
RO.o_MMCC	193
RO.o_MMCK	194
RO.o_MMCKK	195
RO.o_MMCKM	196
RO.o_MMInf	197
RO.o_MMInfKK	198
ROck	199
ROck.o_MCCN	200
ROck.o_MCMN	201
ROck.o_MCON	202
ROk	203
ROk.o_CJN	205
ROk.o_MCCN	206
ROk.o_MCMN	207
ROk.o_MCON	208
ROk.o_OJN	209
SP	210
SP.o_MM1KK	211
summary.o_BnD	212
summary.o_CJN	213
summary.o_MCCN	214

summary.o_MCMN	215
summary.o_MCON	217
summary.o_MM1	218
summary.o_MM1K	219
summary.o_MM1KK	220
summary.o_MMC	221
summary.o_MMCC	222
summary.o_MMCK	223
summary.o_MMCKK	224
summary.o_MMCKM	225
summary.o_MMInf	226
summary.o_MMInfKK	227
summary.o_OJN	228
Throughput	229
Throughput.o_CJN	230
Throughput.o_MCCN	231
Throughput.o_MCMN	232
Throughput.o_MCON	233
Throughput.o_MM1	234
Throughput.o_MM1K	235
Throughput.o_MM1KK	236
Throughput.o_MMC	237
Throughput.o_MMCC	238
Throughput.o_MMCK	239
Throughput.o_MMCKK	240
Throughput.o_MMCKM	241
Throughput.o_MMInf	242
Throughput.o_MMInfKK	243
Throughput.o_OJN	244
Throughputc	245
Throughputc.o_MCCN	246
Throughputc.o_MCMN	247
Throughputc.o_MCON	249
Throughputck	250
Throughputck.o_MCCN	251
Throughputck.o_MCMN	252
Throughputck.o_MCON	253
Throughputcn	255
Throughputcn.o_MCCN	256
Throughputk	257
Throughputk.o_CJN	258
Throughputk.o_MCCN	259
Throughputk.o_MCMN	261
Throughputk.o_MCON	262
Throughputk.o_OJN	263
Throughputn	264
Throughputn.o_CJN	265
VN	267

VN.o_MM1	268
VN.o_MM1K	269
VN.o_MM1KK	270
VN.o_MMC	271
VN.o_MMCC	272
VN.o_MMCK	273
VN.o_MMCKK	274
VN.o_MMCKM	275
VN.o_MMInf	276
VN.o_MMInfKK	277
VNq	278
VNq.o_MM1	279
VNq.o_MM1K	280
VNq.o_MM1KK	281
VNq.o_MMC	282
VNq.o_MMCC	283
VNq.o_MMCK	284
VNq.o_MMCKK	285
VNq.o_MMCKM	286
VNq.o_MMInf	287
VNq.o_MMInfKK	288
VT	289
VT.o_MM1	290
VT.o_MM1K	291
VT.o_MM1KK	292
VT.o_MMC	293
VT.o_MMCC	294
VT.o_MMInf	295
VT.o_MMInfKK	296
VTq	297
VTq.o_MM1	298
VTq.o_MM1K	299
VTq.o_MM1KK	300
VTq.o_MMC	301
VTq.o_MMCC	302
VTq.o_MMCK	303
VTq.o_MMCKK	304
VTq.o_MMInf	305
VTq.o_MMInfKK	306
W	307
W.o_CJN	308
W.o_MCCN	309
W.o_MCMN	310
W.o_MCON	311
W.o_MM1	312
W.o_MM1K	313
W.o_MM1KK	314
W.o_MMC	315

W.o_MMCC	316
W.o_MMCK	317
W.o_MMCKK	318
W.o_MMCKM	319
W.o_MMInf	320
W.o_MMInfKK	321
W.o_OJN	322
Wc	323
Wc.o_MCCN	324
Wc.o_MCMN	325
Wc.o_MCON	326
Wck	328
Wck.o_MCCN	329
Wck.o_MCMN	330
Wck.o_MCON	331
Wk	332
Wk.o_CJN	333
Wk.o_MCCN	335
Wk.o_MCMN	336
Wk.o_MCON	337
Wk.o_OJN	338
Wq	339
Wq.o_MM1	340
Wq.o_MM1K	341
Wq.o_MM1KK	342
Wq.o_MMC	343
Wq.o_MMCC	344
Wq.o_MMCK	345
Wq.o_MMCKK	346
Wq.o_MMCKM	347
Wq.o_MMInf	348
Wq.o_MMInfKK	349
Wqq	350
Wqq.o_MM1	351
Wqq.o_MM1K	352
Wqq.o_MM1KK	353
Wqq.o_MMC	354
Wqq.o_MMCC	355
Wqq.o_MMCK	356
Wqq.o_MMCKK	357
Wqq.o_MMCKM	358
Wqq.o_MMInf	359
Wqq.o_MMInfKK	360
Wws	361
Wws.o_MM1KK	362

Description

It provides a versatile tool for analysis of birth and death based Markovian Queueing Models and Single and Multiclass Product-Form Queueing Networks.

It implements the following basic markovian models:

M/M/1,	M/M/c,	M/M/Infinite,
M/M/1/K,	M/M/c/K,	M/M/c/c,
M/M/1/K/K,	M/M/c/K/K,	M/M/c/K/m, M/M/Infinite/K/K

It also solves the following types of networks:

- Multiple Channel Open Jackson Networks.
- Multiple Channel Closed Jackson Networks.
- Single Channel Multiple Class Open Networks.
- Single Channel Multiple Class Closed Networks
- Single Channel Multiple Class Mixed Networks

Also it provides B-Erlang, C-Erlang and Engset calculators.

This work is dedicated to the memory of D. Sixto Rios Insua.

Details

All models are used in the same way:

1. Create inputs calling the appropriate *NewInput.model*. For example, `x <-NewInput.MM1(lambda=0.25, mu=1, n=10)` for a M/M/1 model. To know the exact acronymn model to use for *NewInput* function, you can search the html help or write `help.search("NewInput")` at the command line.
2. Optionally, as a help for creating the inputs, the `CheckInput(x)` function can be called
3. Solve the model calling `y <-QueueingModel(x)`. In this step, the `CheckInput(x)` will be called. That is the reason that the previous step is optional
4. Finally, you can get a performance value as `W(y)`, `Wq(y)` or a report of the principals performance values calling `summary(y)`

See the examples for more detailed information of the use.

Author(s)

Author, Maintainer and Copyright: Pedro Canadilla <pedro.canadilla@gmail.com>

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

Examples

```
## M/M/1 model
summary(QueueingModel(NewInput.MM1(lambda=1/4, mu=1/3, n=0)))

## M/M/1/K model
summary(QueueingModel(NewInput.MM1K(lambda=1/4, mu=1/3, k=3)))
```

B_erlang

Returns the probability that all servers are busy

Description

Returns the probability that all servers are busy

Usage

```
B_erlang(c=1, u=0)
```

Arguments

c	numbers of servers
u	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability that all servers are busy

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Jagerman1974] Jagerman, D. L. (1974).
Some properties of the Erlang loss function.
Bell System Tech. J. (53), 525-551

See Also[C_erlang](#)**Examples**

```
## two servers
B_erlang(2, 0.5/0.7)
```

CheckInput	<i>Generic S3 method to check the params of a queueing model (or network)</i>
------------	---

Description

Generic S3 method to check the params of a queueing model (or network)

Usage

```
CheckInput(x, ...)
```

Arguments

x	a object of class <code>i_MM1</code> , <code>i_MMC</code> , <code>i_MM1K</code> , <code>i_MMCK</code> , <code>i_MM1KK</code> , <code>i_MMCKK</code> , <code>i_MMCC</code> , <code>i_MMCKM</code> , <code>i_MMInfKK</code> , <code>i_MMInf</code> , <code>i_OJN</code>
...	aditional arguments

Details

Generic S3 method to check the params of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Kleinrock1975] Leonard Kleinrock (1975).

Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MM1](#)
[CheckInput.i_MMC](#)
[CheckInput.i_MM1K](#)
[CheckInput.i_MMCK](#)
[CheckInput.i_MM1KK](#)
[CheckInput.i_MMCKK](#)
[CheckInput.i_MMCC](#)
[CheckInput.i_MMCKM](#)
[CheckInput.i_MMInfKK](#)
[CheckInput.i_MMInf](#)
[CheckInput.i_OJN](#)

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Check the inputs
CheckInput(i_mm1)

```

CheckInput.i_BnD	<i>Checks the input params of a generic Birth and Death process model</i>
------------------	---

Description

Checks the input params of a generic Birth and Death process model

Usage

```

## S3 method for class 'i_BnD'
CheckInput(x, ...)

```

Arguments

x	a object of class i_BnD
...	additional arguments

Details

Checks the input params of a generic Birth and Death process model. The inputs params are created calling previously the [NewInput.BnD](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.BnD](#).

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)

## Check the inputs
CheckInput(i_BnD)
```

CheckInput.i_CJN *Check the input params of a Closed Jackson Network*

Description

Check the input params of a Closed Jackson Network

Usage

```
## S3 method for class 'i_CJN'
CheckInput(x, ...)
```

Arguments

x a object of class i_CJN
 ... additional arguments

Details

Check the input params of a Closed Jackson Network. The inputs params are created calling previously the [NewInput.CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

CheckInput(cjn1)
```

CheckInput.i_MCCN

Check the input params of a MultiClass Closed Network

Description

Check the input params of a MultiClass Closed Network

Usage

```
## S3 method for class 'i_MCCN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCCN
...	aditional arguments

Details

Check the input params of a MultiClass Closed Network. The inputs params are created calling previously the [NewInput.MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

CheckInput(i_MCCN1)
```

CheckInput.i_MCMN

Check the input params of a MultiClass Mixed Network

Description

Check the input params of a MultiClass Mixed Network

Usage

```
## S3 method for class 'i_MCMN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCMN
...	aditional arguments

Details

Check the input params of a MultiClass Mixed Network. The inputs params are created calling previously the [NewInput.MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

CheckInput(i_mcmn1)
```

CheckInput.i_MCON *Check the input params of a MultiClass Open Network*

Description

Check the input params of a MultiClass Open Network

Usage

```
## S3 method for class 'i_MCON'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCON
...	aditional arguments

Details

Check the input params of a MultiClass Open Network. The inputs params are created calling previously the [NewInput.MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

CheckInput(i_mcon1)
```

CheckInput.i_MM1

Checks the input params of a M/M/1 queueing model

Description

Checks the input params of a M/M/1 queueing model

Usage

```
## S3 method for class 'i_MM1'
CheckInput(x, ...)
```

Arguments

x a object of class i_MM1
 ... additional arguments

Details

Checks the input params of a M/M/1 queueing model. The inputs params are created calling previously the [NewInput.MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Check the inputs
CheckInput(i_mm1)
```

CheckInput.i_MM1K	<i>Checks the input params of a M/M/1/K queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/1/K queueing model

Usage

```
## S3 method for class 'i_MM1K'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MM1K
...	aditional arguments

Details

Checks the input params of a M/M/1/K queueing model. The inputs params are created calling previously the [NewInput.MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## check the parameters
CheckInput(i_mm1k)
```

CheckInput.i_MM1KK *Checks the input params of a M/M/1/K/K queueing model*

Description

Checks the input params of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'i_MM1KK'
CheckInput(x, ...)
```

Arguments

x a object of class i_MM1KK
 ... additional arguments

Details

Checks the input params of a M/M/1/K/K queueing model. The inputs params are created calling previously the [NewInput.MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## check the parameters
CheckInput(i_mm1kk)
```

CheckInput.i_MMC	<i>Checks the input params of a M/M/c queueing model</i>
------------------	--

Description

Checks the input params of a M/M/c queueing model

Usage

```
## S3 method for class 'i_MMC'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMC
...	aditional arguments

Details

Checks the input params of a M/M/c queueing model. The inputs params are created calling previously the [NewInput.MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## check the parameters
CheckInput(i_mmc)
```

CheckInput.i_MMCC	<i>Checks the input params of a M/M/c/c queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/c/c queueing model

Usage

```
## S3 method for class 'i_MMCC'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCC
...	aditional arguments

Details

Checks the input params of a M/M/c/c queueing model. The inputs params are created calling previously the [NewInput.MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## check the parameters
CheckInput(i_mmcc)
```

CheckInput.i_MMCK	<i>Checks the input params of a M/M/c/K queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/c/K queueing model

Usage

```
## S3 method for class 'i_MMCK'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCK
...	aditional arguments

Details

Checks the input params of a M/M/c/K queueing model. The inputs params are created calling previously the [NewInput.MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Check the inputs
CheckInput(i_mmck)
```

CheckInput.i_MMCKK *Checks the input params of a M/M/c/K/K queueing model*

Description

Checks the input params of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'i_MMCKK'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCKK
...	additional arguments

Details

Checks the input params of a M/M/c/K/K queueing model. The inputs params are created calling previously the [NewInput.MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## check the parameters
CheckInput(i_mmckk)
```

CheckInput.i_MMCKM *Checks the input params of a M/M/c/K/m queueing model*

Description

Checks the input params of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'i_MMCKM'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCKM
...	additional arguments

Details

Checks the input params of a M/M/c/K/m queueing model. The inputs params are created calling previously the [NewInput.MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## check the parameters  
CheckInput(i_mmckm)
```

CheckInput.i_MMInf *Checks the input params of a M/M/Infinite queueing model*

Description

Checks the input params of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'i_MMInf'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMInf
...	additional arguments

Details

Checks the input params of a M/M/Infinite queueing model. The inputs params are created calling previously the [NewInput.MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Check the parameters  
CheckInput(i_mminf)
```

CheckInput.i_MMInfKK *Checks the input params of a M/M/Infinite/K/K queueing model*

Description

Checks the input params of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'i_MMInfKK'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMInfKK
...	additional arguments

Details

Checks the input params of a M/M/Infinite/K/K queueing model. The inputs params are created calling previously the [NewInput.MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## check the parameters  
CheckInput(i_MMInfKK)
```

CheckInput.i_OJN	<i>Check the input params of an Open Jackson Network</i>
------------------	--

Description

Check the input params of an Open Jackson Network

Usage

```
## S3 method for class 'i_OJN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_OJN
...	additional arguments

Details

Check the input params of an Open Jackson Network. The inputs params are created calling previously the [NewInput.OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

CheckInput(ojn1)
```

CompareQueueingModels *Compare several queueing models in a tabulated format*

Description

Compare several queueing models in a tabulated format

Usage

```
CompareQueueingModels(model, ...)
CompareQueueingModels2(models)
```

Arguments

model	A Queueing Model obtained calling QueueingModel from classes described in the details section
...	a separated by comma list of queueing models obtained calling QueueingModel from classes described in the details section
models	A list of queueing models obtained calling QueueingModel from classes described in the details section

Details

Compare several queueing models in a tabulated format. By now, only o_MM1, o_MMC, o_MMInf, o_MM1K, o_MMCK, o_MMCC, o_MM1KK, o_MMCKK, o_MMCKM, o_MMInfKK classes can be compared

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel](#)

Examples

```
q1 <- QueueingModel(NewInput.MM1(lambda=5, mu=7))
q2 <- QueueingModel(NewInput.MMC(lambda=5, mu=3, c=4))
q3 <- QueueingModel(NewInput.MMInf(lambda=3, mu=4))
q4 <- QueueingModel(NewInput.MMCC(lambda=5, mu=3, c=4))

CompareQueueingModels(q1, q2, q3)
CompareQueueingModels2(list(q1, q2, q3, q4))
```

C_erlang	Returns the probability to wait in queue because all servers are busy
----------	---

Description

Returns the probability to wait in queue because all servers are busy

Usage

```
C_erlang(c=1, r=0)
```

Arguments

c	numbers of servers
r	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability to wait in queue because all servers are busy

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[B_erlang](#)

Examples

```
## two servers  
C_erlang(2, 0.5/0.7)
```

Engset	<i>Returns the probability that all servers are busy</i>
--------	--

Description

Returns the probability that all servers are busy

Usage

```
Engset(k=1, c=0, r=0)
```

Arguments

k	numbers of users
c	numbers of servers
r	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability of blocking in a finite source model

See Also

[B_erlang](#)

Examples

```
## three users, two servers
Engset(3, 2, 0.5/0.7)
```

Inputs	<i>Returns the input parameters of a queueing model (or network)</i>
--------	--

Description

Returns the inputs parameters of a already built queueing model (or network)

Usage

```
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_MCON, o_MCCN, o_MCMN
...	aditional arguments

Details

Returns the input parameters of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[Inputs.o_MM1](#)
[Inputs.o_MMC](#)
[Inputs.o_MM1K](#)
[Inputs.o_MMCK](#)
[Inputs.o_MM1KK](#)
[Inputs.o_MMCKK](#)
[Inputs.o_MMCC](#)
[Inputs.o_MMCKM](#)
[Inputs.o_MMInfKK](#)
[Inputs.o_MMInf](#)
[Inputs.o_OJN](#)
[Inputs.o_CJN](#)
[Inputs.o_MCON](#)
[Inputs.o_MCCN](#)
[Inputs.o_MCMN](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## It returns the Inputs
Inputs(o_mm1)
```

Inputs.o_BnD	<i>Returns the input parameters of a generic Birth and Death process model</i>
--------------	--

Description

Returns the inputs parameters of a already built Birth and Death process model

Usage

```
## S3 method for class 'o_BnD'
Inputs(x, ...)
```

Arguments

```
x          a object of class o_BnD
...        additional arguments
```

Details

Returns the input parameters of a generic Birth and Death process model. The inputs parameters are created calling previously the [NewInput.BnD](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.BnD](#).

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)

## Build the model
o_BnD <- QueueingModel(i_BnD)

## It returns the Inputs
Inputs(o_BnD)
```

Inputs.o_CJN

Returns the input params of a Closed Jackson Network

Description

Returns the input params of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Inputs(x, ...)
```

Arguments

```
x          a object of class o_CJN
...        additional arguments
```

Details

Returns the input params of a Closed Jackson Network. The inputs parameters are created calling previously the [NewInput.CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Inputs(m_cjn1)
```

Inputs.o_MCCN	Returns the input params of a MultiClass Closed Network
---------------	---

Description

Returns the input params of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
Inputs(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns the input params of a MultiClass Closed Network. The inputs parameters are created calling previously the [NewInput.MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_MCCN1 <- QueueingModel(i_MCCN1)
```

```
Inputs(o_MCMN1)
```

Inputs.o_MCMN	<i>Returns the input params of a MultiClass Mixed Network</i>
---------------	---

Description

Returns the input params of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Inputs(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns the input params of a MultiClass Mixed Network. The inputs parameters are created calling previously the [NewInput.MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)
```

```
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Inputs(o_mcmn1)
```

Inputs.o_MCON *Returns the input params of a MultiClass Open Network*

Description

Returns the input params of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Inputs(x, ...)
```

Arguments

x	a object of class o_MCON
...	aditional arguments

Details

Returns the input params of a MultiClass Open Network. The inputs parameters are created calling previously the [NewInput.MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Inputs(o_mcon1)
```

Inputs.o_MM1

Returns the input parameters of a M/M/1 queueing model

Description

Returns the inputs parameters of a already built M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Inputs(x, ...)
```

Arguments

x a object of class o_MM1
... additional arguments

Details

Returns the input parameters of a M/M/1 queueing model. The inputs parameters are created calling previously the [NewInput.MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## It returns the Inputs
Inputs(o_mm1)
```

Inputs.o_MM1K	<i>Returns the input parameters of a M/M/1/K queueing model</i>
---------------	---

Description

Returns the inputs parameters of a already built M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the input parameters of a M/M/1/K queueing model. The inputs parameters are created calling previously the [NewInput.MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## It returns the Inputs
Inputs(o_mm1k)
```

Inputs.o_MM1KK	<i>Returns the input parameters of a M/M/1/K/K queueing model</i>
----------------	---

Description

Returns the inputs parameters of a already built M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the input parameters of a M/M/1/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## It returns the Inputs
Inputs(o_mm1kk)
```

Inputs.o_MMC	Returns the input parameters of a M/M/c queueing model
--------------	--

Description

Returns the inputs parameters of a already built M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the input parameters of a M/M/c queueing model. The inputs parameters are created calling previously the [NewInput.MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## It returns the Inputs
Inputs(o_mmc)
```

Inputs.o_MMCC	Returns the input parameters of a M/M/c/c queueing model
---------------	--

Description

Returns the inputs parameters of a already built M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the input parameters of a M/M/c/c queueing model. The inputs parameters are created calling previously the [NewInput.MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## It returns the Inputs
Inputs(o_mmcc)
```

Inputs.o_MMCK	<i>Returns the input parameters of a M/M/c/K queueing model</i>
---------------	---

Description

Returns the inputs parameters of a already built M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the input parameters of a M/M/c/K queueing model. The inputs parameters are created calling previously the [NewInput.MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## It returns the Inputs
Inputs(o_mmck)
```

Inputs.o_MMCKK	Returns the input parameters of a M/M/c/K/K queueing model
----------------	--

Description

Returns the inputs parameters of a already built M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the input parameters of a M/M/c/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Inputs
Inputs(o_mmckk)
```

Inputs.o_MMCKM	Returns the input parameters of a M/M/c/K/m queueing model
----------------	--

Description

Returns the inputs parameters of a already built M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the input parameters of a M/M/c/K/m queueing model. The inputs parameters are created calling previously the [NewInput.MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## It returns the Inputs
Inputs(o_mmckm)
```

Inputs.o_MMInf	Returns the input parameters of a M/M/Infinite queueing model
----------------	---

Description

Returns the inputs parameters of a already built M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the input parameters of a M/M/Infinite queueing model. The inputs parameters are created calling previously the [NewInput.MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## It returns the Inputs
Inputs(o_mminf)
```

Inputs.o_MMInfKK	Returns the input parameters of a M/M/Infinite/K/K queueing model
------------------	---

Description

Returns the inputs parameters of a already built M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the input parameters of a M/M/Infinite/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## It returns the Inputs
Inputs(o_MMInfKK)
```

Inputs.o_OJN	Returns the input params of an Open Jackson Network
--------------	---

Description

Returns the input params of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Inputs(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Returns the input params of an Open Jackson Network. The inputs parameters are created calling previously the [NewInput.OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn1 <- QueueingModel(i_ojn1)

Inputs(o_ojn1)
```

L *Returns the mean number of customers in a queueing model (or network)*

Description

Returns the mean number of customers in a queueing model (or network)

Usage

`L(x, ...)`

Arguments

x a object of class `o_MM1`, `o_MMC`, `o_MM1K`, `o_MMCK`, `o_MM1KK`, `o_MMCKK`, `o_MMCC`, `o_MMCKM`, `o_MMInfKK`, `o_MMInf`, `o_OJN`, `o_MCON`, `o_MCCN`, `o_MCMN`

... additional arguments

Details

Returns the mean number of customers in a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

L.o_MM1
L.o_MMC
L.o_MM1K
L.o_MMCK
L.o_MM1KK
L.o_MMCKK
L.o_MMCC
L.o_MMCKM
L.o_MMInfKK
L.o_MMInf
L.o_OJN
L.o_CJN
L.o_MCON
L.o_MCCN
L.o_MCMN

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the L
L(o_mm1)
```

L.o_BnD	<i>Returns the mean number of customers in the generic Birth and Death process model</i>
---------	--

Description

Returns the mean number of customers in the generic Birth and Death process model

Usage

```
## S3 method for class 'o_BnD'
L(x, ...)
```

Arguments

x	a object of class o_BnD
...	additional arguments

Details

Returns the mean number of customers in the generic Birth and Death process model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_BnD](#).

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)

## Build the model
o_BnD <- QueueingModel(i_BnD)

## Returns the L
L(o_BnD)
```

L.o_CJN

Returns the mean number of customers of a Closed Jackson Network

Description

Returns the mean number of customers of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
L(x, ...)
```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Returns the mean number of customers of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

L(m_cjn1)
```

L.o_MCCN

Returns the mean number of customers of a MultiClass Closed Network

Description

Returns the mean number of customers of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
L(x, ...)
```

Arguments

x a object of class o_MCCN
 ... additional arguments

Details

Returns the mean number of customers of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

L(o_MCCN1)
```

L.o_MCMN

Returns the mean number of customers of a MultiClass Mixed Network

Description

Returns the mean number of customers of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'  
L(x, ...)
```

Arguments

```
x          a object of class o_MCMN  
...       additional arguments
```

Details

Returns the mean number of customers of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.  
  
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=1, nrow=4, ncol=2)  
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)  
  
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcmn1 <- QueueingModel(i_mcmn1)  
  
L(o_mcmn1)
```

`L.o_MCON`*Returns the mean number of customers of a MultiClass Open Network*

Description

Returns the mean number of customers of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'  
L(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MCON</code>
<code>...</code>	additional arguments

Details

Returns the mean number of customers of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
L(o_mcon1)
```

L.o_MM1	Returns the mean number of customers in the M/M/1 queueing model
---------	--

Description

Returns the mean number of customers in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
L(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the mean number of customers in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the L  
L(o_mm1)
```

L.o_MM1K	<i>Returns the mean number of customers in the M/M/1/K queueing model</i>
----------	---

Description

Returns the mean number of customers in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
L(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the mean number of customers in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the L  
L(o_mm1k)
```

L.o_MM1KK	<i>Returns the mean number of customers in the M/M/1/K/K queueing model</i>
-----------	---

Description

Returns the mean number of customers in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
L(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the mean number of customers in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the L  
L(o_mm1kk)
```

`L.o_MMC`*Returns the mean number of customers in the M/M/c queueing model*

Description

Returns the mean number of customers in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
L(x, ...)
```

Arguments

```
x          a object of class o_MMC  
...       additional arguments
```

Details

Returns the mean number of customers in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the L  
L(o_mmc)
```

L.o_MMCC	Returns the mean number of customers in the M/M/c/c queueing model
----------	--

Description

Returns the mean number of customers in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
L(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the mean number of customers in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the L  
L(o_mmcc)
```

L.o_MMCK	<i>Returns the mean number of customers in the M/M/c/K queueing model</i>
----------	---

Description

Returns the mean number of customers in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
L(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean number of customers in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the L  
L(o_mmck)
```

L.o_MMCKK	<i>Returns the mean number of customers in the M/M/c/K/K queueing model</i>
-----------	---

Description

Returns the mean number of customers in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
L(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the L  
L(o_mmckk)
```

L.o_MMCKM	<i>Returns the mean number of customers in the M/M/c/K/m queueing model</i>
-----------	---

Description

Returns the mean number of customers in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
L(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the L  
L(o_mmckm)
```

L.o_MMInf	Returns the mean number of customers in the M/M/Infinite queueing model
-----------	---

Description

Returns the mean number of customers in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
L(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the mean number of customers in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the L  
L(o_mminf)
```

L.o_MMInfKK	<i>Returns the mean number of customers in the M/M/Infinite/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
L(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the L  
L(o_MMInfKK)
```

L.o_OJN	<i>Returns the mean number of customers of an Open Jackson Network</i>
---------	--

Description

Returns the mean number of customers of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
L(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Returns the mean number of customers of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn <- QueueingModel(i_ojn)
```

L(o_ojn)

Lc	<i>Returns the vector with the mean number of customers of each class in a multiclass queueing network</i>
----	--

Description

Returns the vector with the mean number of customers of each class in a multiclass queueing network

Usage

Lc(x, ...)

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the vector with the mean number of customers of each class in a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Lc.o_MCON](#)
[Lc.o_MCCN](#)
[Lc.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lc(o_mcon1)
```

Lc.o_MCCN	<i>Returns the vector with the mean number of customers of each class in a MultiClass Closed Network</i>
-----------	--

Description

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Lc(x, ...)
```

Arguments

x	a object of class o_MCCN
...	aditional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lc(o_MCCN1)
```

Lc.o_MCMN

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

Description

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lc(x, ...)
```

Arguments

x a object of class o_MCMN
 ... additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lc(o_mcmn1)
```

Lc.o_MCON

*Returns the vector with the mean number of customers of each class
in a MultiClass Open Network*

Description

Returns the vector with the mean number of customers of each class in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lc(x, ...)
```

Arguments

x a object of class o_MCON
... additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON.](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lc(o_mcon1)
```

Lck

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

Usage

Lck(x, ...)

Arguments

x a object of class o_MCON, o_MCCN, o_MCMN
... additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Lck.o_MCON](#)
[Lck.o_MCCN](#)
[Lck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
Lck(o_mcon1)
```

Lck.o_MCCN	<i>Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network</i>
------------	---

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Lck(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```



```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lck(o_MCCN1)
```

Lck.o_MCMN	<i>Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network</i>
------------	--

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lck(o_mcmn1)
```

Lck.o_MCON

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lck(x, ...)
```

Arguments

x a object of class o_MCON
... additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lck(o_mcon1)
```

Lk	<i>Returns the vector with the mean number of customers in each node (server) of a queueing network</i>
----	---

Description

Returns the vector with the mean number of customers in each node (server) of a queueing network

Usage

```
Lk(x, ...)
```

Arguments

x	a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the vector with the mean number of customers in each node (server) of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.

Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Lk.o_OJN](#)

[Lk.o_CJN](#)

[Lk.o_MCON](#)

[Lk.o_MCCN](#)

[Lk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lk(o_mcon1)
```

Lk.o_CJN

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

Description

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'  
Lk(x, ...)
```

Arguments

```
x          a object of class o_CJN  
...       additional arguments
```

Details

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN.](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)  
  
# Define a new input  
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)  
  
# Check the inputs and build the model  
m_cjn1 <- QueueingModel(cjn1)  
  
Lk(m_cjn1)
```

Lk.o_MCCN	Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network
-----------	---

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
Lk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lk(o_MCCN1)
```

Lk.o_MCMN	<i>Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network</i>
-----------	---

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lk(o_mcmn1)
```

Lk.o_MCON

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lk(x, ...)
```

Arguments

x a object of class o_MCON
... additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lk(o_mcon1)
```

Lk.o_OJN

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

Description

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Lk(x, ...)
```

Arguments

x a object of class o_OJN
 ... additional arguments

Details

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn <- QueueingModel(i_ojn)

Lk(o_ojn)
```

Lq	<i>Returns the mean number of customers in the queue in a queueing model</i>
----	--

Description

Returns the mean number of customers in the queue in a queueing model

Usage

```
Lq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	aditional arguments

Details

Returns the mean number of customers in the queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[Lq.o_MM1](#)
[Lq.o_MMC](#)
[Lq.o_MM1K](#)
[Lq.o_MMCK](#)
[Lq.o_MM1KK](#)
[Lq.o_MMCKK](#)
[Lq.o_MMCC](#)
[Lq.o_MMCKM](#)
[Lq.o_MMInfKK](#)
[Lq.o_MMInf](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lq
Lq(o_mm1)
```

Lq.o_MM1

Returns the mean number of customers in the queue in the M/M/1 queueing model

Description

Returns the mean number of customers in the queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Lq(x, ...)
```

Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lq
Lq(o_mm1)
```

Lq.o_MM1K

Returns the mean number of customers in the queue in the M/M/1/K queueing model

Description

Returns the mean number of customers in the queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Lq(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Lq
Lq(o_mm1k)
```

Lq.o_MM1KK	<i>Returns the mean number of customers in the queue in the M/M/1/K/K queueing model</i>
------------	--

Description

Returns the mean number of customers in the queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Lq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Lq
Lq(o_mm1kk)
```

Lq.o_MMC

Returns the mean number of customers in the queue in the M/M/c queueing model

Description

Returns the mean number of customers in the queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Lq(x, ...)
```

Arguments

x a object of class o_MMC
 ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Lq
Lq(o_mmc)
```

Lq.o_MMCC	<i>Returns the mean number of customers in the queue in the M/M/c/c queueing model</i>
-----------	--

Description

Returns the mean number of customers in the queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Lq
Lq(o_mmcc)
```

Lq.o_MMCK	<i>Returns the mean number of customers in the queue in the M/M/c/K queueing model</i>
-----------	--

Description

Returns the mean number of customers in the queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Lq
Lq(o_mmck)
```

Lq.o_MMCKK	<i>Returns the mean number of customers in the queue in the M/M/c/K/K queueing model</i>
------------	--

Description

Returns the mean number of customers in the queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Lq
Lq(o_mmckk)
```

Lq.o_MMCKM	<i>Returns the mean number of customers in the queue in the M/M/c/K/m queueing model</i>
------------	--

Description

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Lq
Lq(o_mmckm)
```

Lq.o_MMInf	<i>Returns the mean number of customers in the queue in the M/M/Infinite queueing model</i>
------------	---

Description

Returns the mean number of customers in the queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Lq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Lq
Lq(o_mminf)
```

Lq.o_MMInfKK	<i>Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model</i>
--------------	---

Description

Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Lq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Lq
Lq(o_MMInfKK)
```

Lqq	<i>Returns the mean number of customers in queue when there is queue in a queueing model</i>
-----	--

Description

Returns the mean number of customers in queue when there is queue in a queueing model

Usage

```
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Lqq.o_MM1](#)
[Lqq.o_MMC](#)
[Lqq.o_MM1K](#)
[Lqq.o_MMCK](#)
[Lqq.o_MM1KK](#)
[Lqq.o_MMCKK](#)
[Lqq.o_MMCC](#)

```
Lqq.o_MMCKM
Lqq.o_MMInfKK
Lqq.o_MMInf
```

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lqq
Lqq(o_mm1)
```

Lqq.o_MM1	<i>Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model</i>
-----------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lqq
Lqq(o_mm1)
```

Lqq.o_MM1K	<i>Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Lq
Lqq(o_mm1k)
```

Lqq.o_MM1KK	<i>Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Lqq
Lqq(o_mm1kk)
```

Lqq.o_MMC	<i>Returns the mean number of customers in queue when there is queue in the M/M/c queueing model</i>
-----------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Lqq
Lqq(o_mmc)
```

Lqq.o_MMCC	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Lqq
Lqq(o_mmcc)
```

Lqq.o_MMCK	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Lqq
Lqq(o_mmck)
```

Lqq.o_MMCKK	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Lqq
Lqq(o_mmckk)
```

Lqq.o_MMCKM	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K/m queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Lqq
Lqq(o_mmckm)
```

Lqq.o_MMInf	<i>Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model</i>
-------------	---

Description

Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Lqq
Lqq(o_mminf)
```

Lqq.o_MMInfKK	<i>Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model</i>
---------------	---

Description

Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Lqq
Lqq(o_MMInfKK)
```

NewInput.BnD

Define the inputs of a new generic Birth and Death process model

Description

Define the inputs of a new generic Birth and Death process model

Usage

```
NewInput.BnD(lambda=NULL, mu=NULL)
```

Arguments

lambda	vectors of arrival rate depending of the number of users in the system. Observe that in R, the vectors starts counting at 1, so lambda[1] is the arrival rate when the system has 0 users on it
mu	vectors of service rate depending of the number of users in the system. Observe that in R, the vectors starts counting at 1, so mu[1] is the arrival rate when the system has 1 users on it

Details

Define the inputs of a new generic Birth and Death process model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_BnD](#)

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)
```

NewInput.CJN

*Define the inputs of a Closed Jackson Network***Description**

Define the inputs of a Closed Jackson Network

Usage

```
NewInput.CJN(prob=NULL, n=0, z=0, operational=FALSE, method=0, tol=0.001, ...)
NewInput2.CJN(prob=NULL, n=0, z=0, operational=FALSE, method=0, tol=0.001, nodes)
NewInput3.CJN(n, z, numNodes, vType, vVisit, vService, vChannel, method=0, tol=0.001)
```

Arguments

prob	It is probability transition matrix or visit ratio vector. That is, the prob[i, j] is the transition probability of node i to node j, or prob[i] is the visit ratio (a probability, that is, a value between 0 and 1) to node i. Also, the visit ratio can express the number of times that a client visits the queueing center, in a more operational point of view. See the parameter operational
n	number of customers in the Network
z	think time of the client
operational	If prob is a vector with the visit ratios, operational equal to FALSE gives to the visit ratio a probability meaning, that is, as the stationary values of the imbedded markov chain. If operational is equal to TRUE, the operational point of view is used: it is the number of visits that the same client makes to a node.
method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used.
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm.
...	a separated by comma list of nodes of i_MM1, i_MMC or i_MMInf class
nodes	A list of nodes of i_MM1, i_MMC or i_MMInf class
numNodes	The number of nodes of the network
vType	A vector with the type of server: "Q" for a queueing node, "D" for a delay node
vVisit	A vector with the visit ratios. It represent visit counts to a center as if the parameter operational were TRUE
vService	A vector with the services time of each node
vChannel	A vector with the number of channels of the node. The type of the server has to be "Q" to be inspected

Details

Define the inputs of a Closed Jackson Network. For a operational use, NewInput3.CJN is recommended. For a more academic use, NewInput.CJN or NewInput2.CJN is recommended. Please, note that the different ways to create the inputs for a Closed Jackson Network are equivalent to each other, and no validation is done at this stage. The validation is done calling CheckInput function.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

## think time = 0
z <- 0

## operational value
operational <- FALSE

## definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

## Not run:
cjn1 <- NewInput2.CJN(prob, n, z, operational, 0, 0.001, list(n1, n2))

## End(Not run)

## using visit ratios and service demands. See [Lazowska84] pag 117.
## E[S] cpu = 0.005, Visit cpu = 121, D cpu = E[S] cpu * Visit cpu = 0.605
cpu <- NewInput.MM1(mu=1/0.005)
```

```

## E[S] disk1 = 0.030, Visit disk1 = 70, D disk1 = E[S] disk1 * Visit disk1 = 2.1
disk1 <- NewInput.MM1(mu=1/0.030)

## E[S] disk2 = 0.027, Visit disk2 = 50, D disk2 = E[S] disk2 * Visit disk2 = 1.35
disk2 <- NewInput.MM1(mu=1/0.027)

## The visit ratios.
vVisit <- c(121, 70, 50)

operational <- TRUE

net <- NewInput.CJN(prob=vVisit, n=3, z=15, operational, 0, 0.001, cpu, disk1, disk2)

## Using the operational creation function
n <- 3
think <- 15
numNodes <- 3
vType <- c("Q", "Q", "Q")
vService <- c(0.005, 0.030, 0.027)
vChannel <- c(1, 1, 1)

net2 <- NewInput3.CJN(n, think, numNodes, vType, vVisit, vService, vChannel, method=0, tol=0.001)

```

NewInput.MCCN

Define the inputs of a MultiClass Closed Network

Description

Define the inputs of a MultiClass Closed Network

Usage

```

NewInput.MCCN(
  classes, vNumber, vThink, nodes, vType, vVisit, vService, method=1, tol=0.01
)

```

Arguments

classes	The number of classes
vNumber	A vector with the number of customers of each class
vThink	A vector with the think time of each class
nodes	The number of nodes in the network
vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j
vService	A matrix[i, j]. The rows represents the different service time for each class i in each node j

method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm

Details

Define the inputs of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

NewInput.MCMN

Define the inputs of a MultiClass Mixed Network

Description

Define the inputs of a MultiClass Mixed Network

Usage

```
NewInput.MCMN(
  classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService, method=0, tol=0.01
)
```

Arguments

classes	The number of classes
vLambda	It is a vector with the rate of arrivals of each class
vNumber	A vector with the number of customers of each class
vThink	A vector with the think time of each class
nodes	The number of nodes in the network
vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j. Take caution about the orden: open classes are defined first and closed classes are defined second
vService	A matrix[i, j]. The rows represents the different service times for each class i in each node j. Take caution about the orden: open classes are defined first and closed classes are defined second.
method	If method is 0, the exact MVA algorith is used. If method is 1, the Bard-Schweitzer approximation algorithm is used
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm

Details

Define the inputs of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4 # A and B are open classes and C and D are closed classes.
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")

# When the visit ratios and vService are set,
# be sure that the open classes are in the first positions
# and the closed classes after the open classes.
vVisit <- matrix(data=1, nrow=4, ncol=2)
```

```

# A and B are open classes:
#   with demand service of 1/4 and 1/2 at the node 1 and 1/2 and 1 at the node 2
# C and D are open classes:
#   with demand service of 1/4 and 1/2 at the node 1 and 1/2 and 1 at the node 2
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

```

NewInput.MCON

Define the inputs of a MultiClass Open Network

Description

Define the inputs of a MultiClass Open Network

Usage

```
NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

Arguments

classes	The number of classes
vLambda	It is a vector with the rate of arrivals of each class
nodes	The number of nodes in the network
vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j
vService	A matrix[i, j]. The rows represents the different service times for each class i in each node j

Details

Define the inputs of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

NewInput.MM1

Define the inputs of a new M/M/1 queueing model

Description

Define the inputs of a new M/M/1 queueing model

Usage

```
NewInput.MM1(lambda=0, mu=0, n=0)
```

Arguments

lambda	arrival rate
mu	server service rate
n	number of customers in the system from which you want to obtain its probabilities. Put n=0 for a idle probability (no customer present in the system or system idle). With n=-1, no probabilities are computed

Details

Define the inputs of a new M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)
```

NewInput.MM1K	<i>Define the inputs of a new M/M/1/K queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/1/K queueing model

Usage

```
NewInput.MM1K(lambda=0, mu=0, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity

Details

Define the inputs of a new M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1K](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)
```

NewInput.MM1KK *Define the inputs of a new M/M/1/K/K queueing model*

Description

Define the inputs of a new M/M/1/K/K queueing model

Usage

```
NewInput.MM1KK(lambda=0, mu=0, k=1, method=3)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms. With method=2, Jain's Method [Jain2007], pag. 26 is used. With method=3, the result that K-n customers up has a truncated poisson distribution is used [Kobayashi2012] pag. 709

Details

Define the inputs of a new M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Jain2007] Joti Lal Jain, Sri Gopal Mohanty, Walter Bohm (2007).

A course on Queueing Models.
Chapman-Hall.

[Kobayashi2012] Hisashi Kobayashi, Brian L. Mark, William Turin (2012).

Probability, Random Processes, and Statistical Analysis: Applications to Communications, Signal Processing, Queueing Theory and Mathematical Finance.
Cambridge University Press.

See Also

[CheckInput.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)
```

NewInput.MMC

Define the inputs of a new M/M/c queueing model

Description

Define the inputs of a new M/M/c queueing model

Usage

```
NewInput.MMC(lambda=0, mu=0, c=1, n=0, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
n	number of customers in the system from which you want to obtain its probabilities. Put n=0 for a idle probability (no customer present in the system or system idle). With n=-1, no probabilities are computed
method	method of computation of the probabilities of n number of customers in the system. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms.

Details

Define the inputs of a new M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)
```

NewInput.MMCC *Define the inputs of a new M/M/c/c queueing model*

Description

Define the inputs of a new M/M/c/c queueing model

Usage

```
NewInput.MMCC(lambda=0, mu=0, c=1, method=1)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
method	with method = 0, the state probabilities are calculated using the formal definition (with overflow problems with factorials; with method = 1 (default), the truncated poisson distribution is used (recomended for professional use)

Details

Define the inputs of a new M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Kobayashi2012] Hisashi Kobayashi, Brian L. Mark, William Turin (2012).
Probability, Random Processes, and Statistical Analysis: Applications to Communications, Signal Processing, Queueing Theory and Mathematical Finance.
Cambridge University Press.

See Also

[CheckInput.i_MMCC](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)
```

NewInput.MMCK	<i>Define the inputs of a new M/M/c/K queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/c/K queueing model

Usage

```
NewInput.MMCK(lambda=0, mu=0, c=1, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity

Details

Define the inputs of a new M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCK](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)
```

NewInput.MMCKK *Define the inputs of a new M/M/c/K/K queueing model*

Description

Define the inputs of a new M/M/c/K/K queueing model

Usage

```
NewInput.MMCKK(lambda=0, mu=0, c=1, k=1, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms. With method=2, Jain's Method [Jain2007], pag. 26 is used

Details

Define the inputs of a new M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Jain2007] Joti Lal Jain, Sri Gopal Mohanty, Walter Bohm (2007).

A course on Queueing Models.
Chapman-Hall.

See Also

[CheckInput.i_MMCKK](#)

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)
```

NewInput.MMCKM

Define the inputs of a new M/M/c/K/m queueing model

Description

Define the inputs of a new M/M/c/K/m queueing model

Usage

```
NewInput.MMCKM(lambda=0, mu=0, c=1, k=1, m=1, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity
m	population size. Please, observe that should be $m \geq k$
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms.

Details

Define the inputs of a new M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKM](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)
```

NewInput.MMInf *Define the inputs of a new M/M/Infinite queueing model*

Description

Define the inputs of a new M/M/Infinite queueing model

Usage

```
NewInput.MMInf(lambda=0, mu=0, n=0)
```

Arguments

lambda	arrival rate
mu	server service rate
n	number of customers in the system from which you want to obtain its probabilities. Put n=0 for a idle probability (no customer present in the system or system idle). With n=-1, no probabilities are computed

Details

Define the inputs of a new M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMInf](#)

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)
```

NewInput.MMInfKK *Define the inputs of a new M/M/Infinite/K/K queueing model*

Description

Define the inputs of a new M/M/Infinite/K/K queueing model

Usage

```
NewInput.MMInfKK(lambda=0, mu=0, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity

Details

Define the inputs of a new M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MMInfKK](#)

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)
```

NewInput.OJN *Define the inputs of an Open Jackson Network*

Description

Define the inputs of an Open Jackson Network

Usage

```
NewInput.OJN(prob=NULL, ...)
NewInput2.OJN(prob=NULL, nodes)
NewInput3.OJN(vLambda, numNodes, vType, vVisit, vService, vChannel)
```

Arguments

prob	It is probability transition matrix or visit ratio vector. That is, the prob[i, j] is the transition probability of node i to node j, or prob[i] is the visit ratio to node i (the visit ratio values doesn't need to be probabilities, that is, a value greater than 1 can be used here. See the examples)
...	a separated by comma list of nodes of i_MM1, i_MMC or i_MMInf class
nodes	A list of nodes of i_MM1, i_MMC or i_MMInf class
vLambda	Vector with the arrivals rates to each node
numNodes	Number of nodes
vType	A vector with the type of server: "Q" for a queueing node, "D" for a delay node
vVisit	A vector with the visit ratios
vService	A vector with the services time of each node
vChannel	A vector with the number of channels of the node. The type of the server has to be "Q" to be inspected

Details

Define the inputs of an Open Jackson Network. For a operational use, NewInput3.OJN is recommended. For a more academic use, NewInput.OJN or NewInput2.OJN is recommended. Please, note that the different ways to create the inputs for a Open Jackson Network are equivalent to each other, and no validation is done at this stage. The validation is done calling CheckInput function.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

## Using function NewInput2
## Not run:
  ojn1 <- NewInput2.OJN(prob, list(n1, n2, n3, n4))

## End(Not run)

## Using visit ratios. Values taken from [Lazowska84], pag. 113.

## E[S] cpu = 0.005, Visit cpu = 121, D cpu = E[S] cpu * Visit cpu = 0.605
cpu <- NewInput.MM1(lambda=0.2, mu=1/0.005)

## E[S] disk1 = 0.030, Visit disk1 = 70, D disk1 = E[S] disk1 * Visit disk1 = 2.1
disk1 <- NewInput.MM1(lambda=0.2, mu=1/0.030)

## E[S] disk2 = 0.027, Visit disk2 = 50, D disk2 = E[S] disk2 * Visit disk2 = 1.35
disk2 <- NewInput.MM1(lambda=0.2, mu=1/0.027)

## In this example, to have the throughput per node, the visit ratios has to be given in this form.
## Please, don't use in the closed Jackson Network
visit <- c(121, 70, 50)
net <- NewInput.OJN(visit, cpu, disk1, disk2)

## Using NewInput3
vLambda <- c(0.2, 0.2, 0.2)
vService <- c(0.005, 0.030, 0.027)
numNodes <- 3
vType <- c("Q", "Q", "Q")
vChannel <- c(1, 1, 1)
net2 <- NewInput3.OJN(vLambda, numNodes, vType, visit, vService, vChannel)
```

Pn	<i>Returns the probabilities of a queueing model (or network)</i>
----	---

Description

Pn returns the probabilities that a queueing model (or network) has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it

Usage

```
Pn(x, ...)  

Qn(x, ...)
```

Arguments

x	For Pn, an object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_BnD. For Qn, an object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Pn returns the system probabilities of a queueing model (or network). Qn returns the probability that an effective arrival see n customers in the system

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Pn.o_MM1](#)
[Qn.o_MM1](#)
[Pn.o_MMC](#)
[Qn.o_MMC](#)
[Pn.o_MM1K](#)
[Qn.o_MM1K](#)
[Pn.o_MMCK](#)
[Qn.o_MMCK](#)
[Pn.o_MM1KK](#)
[Qn.o_MM1KK](#)
[Pn.o_MMCKK](#)
[Qn.o_MMCKK](#)

```

Pn.o_MMCC
Qn.o_MMCC
Pn.o_MMCKM
Qn.o_MMCKM
Pn.o_MMInfKK
Qn.o_MMInfKK
Pn.o_MMInf
Qn.o_MMInf
Pn.o_OJN
Pn.o_BnD

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the probabilities
Pn(o_mm1)

```

Pn.o_BnD

Returns the probabilities of a generic Birth and Death process model

Description

Pn returns the probabilities that a generic Birth and Death process model has n customers.

Usage

```

## S3 method for class 'o_BnD'
Pn(x, ...)

```

Arguments

```

x          a object of class o_BnD
...       additional arguments

```

Details

Pn returns the probabilities that a generic Birth and Death process model has n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_BnD](#).

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)

## Build the model
o_BnD <- QueueingModel(i_BnD)

## Returns the probabilities
Pn(o_BnD)

## Simulating M/M/1
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

pn_bnd_mm1 <- Pn(QueueingModel(NewInput.BnD(lambda=lambda, mu=mu)))
pn_mm1 <- Pn(QueueingModel(NewInput.MM1(lambda=1/4, mu=1/3, n=200)))

## Simulating M/M/2
lambda <- rep(5, 200)
mu <- c(1*10, rep(2*10, 199))

pn_mmc <- Pn(QueueingModel(NewInput.MMC(lambda=5, mu=10, c=2, n=200, method=0)))
pn_bnd_mmc <- Pn(QueueingModel(NewInput.BnD(lambda=lambda, mu=mu)))

## Simulating M/M/1/K/K
lambda <- c(2*0.25, 0.25)
mu <- rep(4, 2)
pn_mm1kk <- Pn(QueueingModel(NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)))
pn_bnd <- Pn(QueueingModel(NewInput.BnD(lambda=lambda, mu=mu)))
```

Pn.o_MM1

Returns the probabilities of a M/M/1 queueing model

Description

Pn returns the probabilities that a M/M/1 queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MM1'  
Pn(x, ...)  
## S3 method for class 'o_MM1'  
Qn(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Pn returns the probabilities that a M/M/1 queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the probabilities  
Pn(o_mm1)  
Qn(o_mm1)
```

Pn.o_MM1K

Returns the probabilities of a M/M/1/K queueing model

Description

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MM1K'  
Pn(x, ...)  
## S3 method for class 'o_MM1K'  
Qn(x, ...)
```

Arguments

x a object of class o_MM1K
... additional arguments

Details

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the probabilities  
Pn(o_mm1k)  
Qn(o_mm1k)
```

Pn.o_MM1KK

Returns the probabilities of a M/M/1/K/K queueing model

Description

Pn returns the probabilities of a M/M/1/K/K queueing model Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MM1KK'
Pn(x, ...)
## S3 method for class 'o_MM1KK'
Qn(x, ...)
```

Arguments

x a object of class o_MM1KK
... additional arguments

Details

Pn returns the probabilities that a M/M/1/K/K queueing model has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)
```



```
## Returns the probabilities  
Pn(o_mm1kk)  
Qn(o_mm1kk)
```

Pn.o_MMC

Returns the probabilities of a M/M/c queueing model

Description

Pn returns the probabilities that a M/M/c queueing model has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMC'  
Pn(x, ...)  
## S3 method for class 'o_MMC'  
Qn(x, ...)
```

Arguments

x a object of class o_MMC
... additional arguments

Details

Pn returns the probabilities that a M/M/c queueing model has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the probabilities
Pn(o_mmc)
Qn(o_mmc)
```

Pn.o_MMCC

Returns the probabilities of a M/M/c/c queueing model

Description

Pn returns the probabilities that a M/M/c/c queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCC'
Pn(x, ...)
## S3 method for class 'o_MMCC'
Qn(x, ...)
```

Arguments

x a object of class o_MMCC
... additional arguments

Details

Pn returns the probabilities that a M/M/c/c queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the probabilities
Pn(o_mmcc)
Qn(o_mmcc)
```

Pn.o_MMCK

Returns the probabilities of a M/M/c/K queueing model

Description

Pn returns the probabilities that a M/M/c/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCK'
Pn(x, ...)
## S3 method for class 'o_MMCK'
Qn(x, ...)
```

Arguments

x a object of class o_MMCK
... additional arguments

Details

Pn returns the probabilities that a M/M/c/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the probabilities
Pn(o_mmck)
Qn(o_mmck)
```

Pn.o_MMCKK

Returns the probabilities of a M/M/c/K/K queueing model

Description

Pn returns the probabilities that a M/M/c/K/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCKK'
Pn(x, ...)
## S3 method for class 'o_MMCKK'
Qn(x, ...)
```

Arguments

x a object of class o_MMCKK
... additional arguments

Details

Pn returns the probabilities that a M/M/c/K/K queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the parameters
Pn(o_mmckk)
Qn(o_mmckk)
```

Pn.o_MMCKM

Returns the probabilities of a M/M/c/K/m queueing model

Description

Pn returns the probabilities that a M/M/c/K/m queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCKM'
Pn(x, ...)
## S3 method for class 'o_MMCKM'
Qn(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Pn returns the probabilities that a M/M/c/K/m queueing model has n customers.

Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the probabilities
Pn(o_mmckm)
Qn(o_mmckm)
```

Pn.o_MMInf

Returns the probabilities of a M/M/Infinite queueing model

Description

Pn returns the probabilities that a M/M/Infinite queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMInf'
Pn(x, ...)
## S3 method for class 'o_MMInf'
Qn(x, ...)
```

Arguments

x a object of class o_MMInf
 ... additional arguments

Details

Pn returns the probabilities that a M/M/Infinite queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the probabilities
Pn(o_mminf)
Qn(o_mminf)
```

Pn.o_MMInfKK

Returns the probabilities of a M/M/Infinite/K/K queueing model

Description

Pn returns the probabilities that a M/M/Infinite/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMInfKK'
Pn(x, ...)
## S3 method for class 'o_MMInfKK'
Qn(x, ...)
```

Arguments

x a object of class o_MMInfKK
 ... additional arguments

Details

Pn returns the probabilities that a M/M/Infinite/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the probabilities
Pn(o_MMInfKK)
Qn(o_MMInfKK)
```

Pn.o_OJN	<i>Returns vector of the probabilities of each node (server) of an Open Jackson Network</i>
----------	---

Description

Returns vector of the probabilities of each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Pn(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Returns vector of the probabilities of each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Pn(o_ojn)
```

```
print.summary.o_BnD     Summary of the results of a generic Birth and Death process model
```

Description

Summary of the results of a generic Birth and Death process model.

Usage

```
## S3 method for class 'summary.o_BnD'
print(x, ...)
```

Arguments

```
x                     a object of class summary.o_BnD
...                    additional arguments
```

Details

Summaries a generic Birth and Death process model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_BnD](#).

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)

## Build the model
o_BnD <- QueueingModel(i_BnD)

## Report the results
print(summary(o_BnD))
```

```
print.summary.o_CJN  Summary of the results of a Closed Jackson Network
```

Description

Summary of the results of a Closed Jackson Network

Usage

```
## S3 method for class 'summary.o_CJN'
print(x, ...)
```

Arguments

```
x          a object of class summary.o_CJN
...        additional arguments
```

Details

Summaries a Closed Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```

## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

print(summary(m_cjn1))

```

```
print.summary.o_MCCN Summary of the results of a MultiClass Closed Network
```

Description

Summary of the results of a MultiClass Closed Network

Usage

```

## S3 method for class 'summary.o_MCCN'
print(x, ...)

```

Arguments

x	a object of class summary.o_MCCN
...	additional arguments

Details

Summaries a MultiClass Closed Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

print(summary(o_MCCN1))
```

```
print.summary.o_MCMN Summary of the results of a MultiClass Mixed Network
```

Description

Summary of the results of a MultiClass Mixed Network

Usage

```
## S3 method for class 'summary.o_MCMN'
print(x, ...)
```

Arguments

```
x          a object of class summary.o_MCMN
...        additional arguments
```

Details

Summaries a MultiClass Mixed Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

print(summary(o_mcmn1))
```

```
print.summary.o_MCON  Summary of the results of a MultiClass Open Network
```

Description

Summary of the results of a MultiClass Open Network

Usage

```
## S3 method for class 'summary.o_MCON'
print(x, ...)
```

Arguments

x a object of class summary.o_MCON
 ... additional arguments

Details

Summaries a MultiClass Open Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON.](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

print(summary(o_mcon1))
```

```
print.summary.o_MM1    Summary of the results of a M/M/1 queueing model
```

Description

Summary of the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'summary.o_MM1'
print(x, ...)
```

Arguments

x a object of class summary.o_MM1
 ... additional arguments

Details

Summaries a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the results
print(summary(o_mm1))
```

print.summary.o_MM1K *Summary of the results of a M/M/1/K queueing model*

Description

Summary of the results of a M/M/1/K queueing model.

Usage

```
## S3 method for class 'summary.o_MM1K'
print(x, ...)
```

Arguments

x a object of class summary.o_MM1K
 ... additional arguments

Details

Summaries a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Report the results
print(summary(o_mm1k))
```

```
print.summary.o_MM1KK Summary of the results of a M/M/1/K/K queueing model
```

Description

Summary of the results of a M/M/1/K/K queueing model.

Usage

```
## S3 method for class 'summary.o_MM1KK'
print(x, ...)
```

Arguments

x	a object of class summary.o_MM1KK
...	aditional arguments

Details

Summaries a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Report the results
print(summary(o_mm1kk))
```

```
print.summary.o_MMC      Summary of the results of a M/M/c queueing model
```

Description

Summary of the results of a M/M/c queueing model.

Usage

```
## S3 method for class 'summary.o_MMC'
print(x, ...)
```

Arguments

x a object of class summary.o_MMC
 ... additional arguments

Details

Summaries a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Report the results
print(summary(o_mmc))
```

```
print.summary.o_MMCC  Summary of the results of a M/M/c/c queueing model
```

Description

Summary of the results of a M/M/c/c queueing model.

Usage

```
## S3 method for class 'summary.o_MMCC'
print(x, ...)
```

Arguments

x	a object of class summary.o_MMCC
...	aditional arguments

Details

Summaries a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Report the results
print(summary(o_mmcc))
```

```
print.summary.o_MMCK  Summary of the results of a M/M/c/K queueing model
```

Description

Summary of the results of a M/M/c/K queueing model.

Usage

```
## S3 method for class 'summary.o_MMCK'
print(x, ...)
```

Arguments

x	a object of class summary.o_MMCK
...	aditional arguments

Details

Summaries a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Report the results
print(summary(o_mmck))
```

```
print.summary.o_MMCKK Summary of the results of a M/M/c/K/K queueing model
```

Description

Summary of the results of a M/M/c/K/K queueing model.

Usage

```
## S3 method for class 'summary.o_MMCKK'
print(x, ...)
```

Arguments

x	a object of class summary.o_MMCKK
...	additional arguments

Details

Summaries a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Report the results
print(summary(o_mmckk))
```

```
print.summary.o_MMCKM Summary of the results of a M/M/c/K/m queueing model
```

Description

Summary of the results of a M/M/c/K/m queueing model.

Usage

```
## S3 method for class 'summary.o_MMCKM'
print(x, ...)
```

Arguments

x	a object of class summary.o_MMCKM
...	aditional arguments

Details

Summaries a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Report the results
print(summary(o_mmckm))
```

```
print.summary.o_MMInf Summary of the results of a M/M/Infinite queueing model
```

Description

Summary of the results of a M/M/Infinite queueing model.

Usage

```
## S3 method for class 'summary.o_MMInf'
print(x, ...)
```

Arguments

x	a object of class summary.o_MMInf
...	additional arguments

Details

Summaries a M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Report the results
print(summary(o_mminf))
```

```
print.summary.o_MMInfKK
```

Reports the results of a M/M/Infinite/K/K queueing model

Description

Reports the results of a M/M/Infinite/K/K queueing model.

Usage

```
## S3 method for class 'summary.o_MMInfKK'
print(x, ...)
```

Arguments

x	a object of class summary.o_MMInfKK
...	additional arguments

Details

Summaries a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Report the results
print(summary(o_MMInfKK))
```

print.summary.o_OJN *Reports the results of an Open Jackson Network*

Description

Reports the results of an Open Jackson Network

Usage

```
## S3 method for class 'summary.o_OJN'
print(x, ...)
```

Arguments

x	a object of class summary.o_OJN
...	additional arguments

Details

Summaries an Open Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

o_ojn <- QueueingModel(i_ojn)

print(summary(o_ojn))
```

QueueingModel

Generic S3 method to build a queueing model (or network)

Description

Generic S3 method to build a queueing model (or network)

Usage

```
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1, i_MMC, i_MM1K, i_MMCK, i_MM1KK, i_MMCKK, i_MMCC, i_MMCKM, i_MMInfKK, i_MMInf, i_OJN, i_MCON
...	aditional arguments

Details

Generic S3 method to build a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

```

QueueingModel.i_MM1
QueueingModel.i_MMC
QueueingModel.i_MM1K
QueueingModel.i_MMCK
QueueingModel.i_MM1KK
QueueingModel.i_MMCKK
QueueingModel.i_MMCC
QueueingModel.i_MMCKM
QueueingModel.i_MMInfKK
QueueingModel.i_MMInf
QueueingModel.i_OJN
QueueingModel.i_MCON

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
QueueingModel(i_mm1)

```

QueueingModel.i_BnD *Builds a a generic Birth and Death process model*

Description

Builds a a generic Birth and Death process model

Usage

```

## S3 method for class 'i_BnD'
QueueingModel(x, ...)

```

Arguments

x	a object of class i_BnD
...	aditional arguments

Details

Build a generic Birth and Death process model. It also checks the input params calling the [Check-Input.i_BnD](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_BnD](#)

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)

## Build the model
o_BnD <- QueueingModel(i_BnD)
```

QueueingModel.i_CJN *Builds one Closed Jackson Network*

Description

Builds one Closed Jackson Network

Usage

```
## S3 method for class 'i_CJN'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_CJN
...	additional arguments

Details

Build one Closed Jackson Network. It also checks the input params calling the [CheckInput.i_CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

m_cjn1
```

QueueingModel.i_MCCN *Builds one MultiClass Closed Network*

Description

Builds one MultiClass Closed Network

Usage

```
## S3 method for class 'i_MCCN'
QueueingModel(x, ...)
```

Arguments

x a object of class i_MCCN
... additional arguments

Details

Build one MultiClass Closed Network. It also checks the input params calling the [CheckInput.i_MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_MCCN1 <- QueueingModel(i_MCCN1)  
  
o_MCCN1
```

QueueingModel.i_MCMN *Builds one MultiClass Mixed Network*

Description

Builds one MultiClass Mixed Network

Usage

```
## S3 method for class 'i_MCMN'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MCMN
...	aditional arguments

Details

Build one MultiClass Mixed Network. It also checks the input params calling the [CheckInput.i_MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.  
  
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=1, nrow=4, ncol=2)  
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)  
  
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcmn1 <- QueueingModel(i_mcmn1)  
  
o_mcmn1
```

QueueingModel.i_MCON *Builds one MultiClass Open Network*

Description

Builds one MultiClass Open Network

Usage

```
## S3 method for class 'i_MCON'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MCON
...	additional arguments

Details

Build one MultiClass Open Network. It also checks the input params calling the [CheckInput.i_MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
o_mcon1
```

QueueingModel.i_MM1 *Builds a M/M/1 queueing model*

Description

Builds a M/M/1 queueing model

Usage

```
## S3 method for class 'i_MM1'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1
...	additional arguments

Details

Build a M/M/1 queueing model. It also checks the input params calling the [CheckInput.i_MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
QueueingModel(i_mm1)
```

QueueingModel.i_MM1K *Builds a M/M/1/K queueing model*

Description

Builds a M/M/1/K queueing model

Usage

```
## S3 method for class 'i_MM1K'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1K
...	additional arguments

Details

Build a M/M/1/K queueing model. It also checks the input params calling the [CheckInput.i_MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
QueueingModel(i_mm1k)
```

QueueingModel.i_MM1KK *Builds a M/M/1/K/K queueing model*

Description

Builds a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'i_MM1KK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1KK
...	additional arguments

Details

Build a M/M/1/K/K queueing model. It also checks the input params calling the [CheckInput.i_MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
QueueingModel(i_mm1kk)
```

QueueingModel.i_MMC *Builds a M/M/c queueing model*

Description

Builds a M/M/c queueing model

Usage

```
## S3 method for class 'i_MMC'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMC
...	additional arguments

Details

Build a M/M/c/ queueing model. It also checks the input params calling the [CheckInput.i_MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
QueueingModel(i_mmc)
```

QueueingModel.i_MMCC *Builds a M/M/c/c queueing model*

Description

Builds a M/M/c/c queueing model

Usage

```
## S3 method for class 'i_MMCC'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCC
...	additional arguments

Details

Build a M/M/c/c queueing model. It also checks the input params calling the [CheckInput.i_MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
QueueingModel(i_mmcc)
```

QueueingModel.i_MMCK *Builds a M/M/c/K queueing model*

Description

Builds a M/M/c/K queueing model

Usage

```
## S3 method for class 'i_MMCK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCK
...	aditional arguments

Details

Build a M/M/c/K queueing model. It also checks the input params calling the [CheckInput.i_MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
QueueingModel(i_mmck)
```

QueueingModel.i_MMCKK *Builds a M/M/c/K/K queueing model*

Description

Builds a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'i_MMCKK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCKK
...	additional arguments

Details

Build a M/M/c/K/K queueing model. It also checks the input params calling the [CheckInput.i_MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
QueueingModel(i_mmckk)
```

QueueingModel.i_MMCKM *Builds a M/M/c/K/m queueing model*

Description

Builds a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'i_MMCKM'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCKM
...	additional arguments

Details

Build a M/M/c/K/m queueing model. It also checks the input params calling the [CheckInput.i_MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKM](#)

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
QueueingModel(i_mmckm)
```

QueueingModel.i_MMInf *Builds a M/M/Infinite queue model*

Description

Builds a M/M/Infinite queue model

Usage

```
## S3 method for class 'i_MMInf'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMInf
...	additional arguments

Details

Build a M/M/Infinite model. It also checks the input params calling the [CheckInput.i_MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMInf](#)

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
QueueingModel(i_mminf)
```

`QueueingModel.i_MMInfKK`*Builds a M/M/Infinite/K/K queueing model*

Description

Builds a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'i_MMInfKK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMInfKK
...	additional arguments

Details

Build a M/M/Infinite/K/K queueing model. It also checks the input params calling the [CheckInput.i_MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MMInfKK](#)

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
QueueingModel(i_MMInfKK)
```

QueueingModel.i_OJN *Builds one Open Jackson Network*

Description

Builds one Open Jackson Network

Usage

```
## S3 method for class 'i_OJN'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_OJN
...	aditional arguments

Details

Build one Open Jackson Network. It also checks the input params calling the [CheckInput.i_OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.  
## create the nodes  
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)  
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)  
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)  
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)  
  
# definition of the transition probabilities  
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)  
  
ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)  
  
m_ojn1 <- QueueingModel(ojn1)
```

m_ojn1

Report

Reports the results of a queueing model

Description

Reports the results of a queueing model.

Usage

Report(x, ...)

Arguments

x i_MM1, i_MMC, i_MM1K, i_MMCK, i_MM1KK, i_MMCKK, i_MMCC, i_MMCKM,
 i_MMInfKK, i_MMInf, i_OJN, i_MCON
... additional arguments

Details

Generic S3 method to report a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Report the results  
Report(o_mm1)
```

`Report.o_BnD`*Reports the results of a M/M/1 queueing model*

Description

Reports the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'o_BnD'  
Report(x, ...)
```

Arguments

```
x          a object of class o_BnD  
...       additional arguments
```

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_BnD](#).

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model  
## create input parameters  
lambda <- rep(1/4, 200)  
mu <- rep(1/3, 200)  
  
i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)  
  
## Build the model  
o_BnD <- QueueingModel(i_BnD)  
  
## Report the results  
Report(o_BnD)
```

Report.o_CJN	<i>Reports the results of a Closed Jackson Network</i>
--------------	--

Description

Reports the results of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'  
Report(x, ...)
```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Generates a report of the queueing network received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)
```

```
# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Report(m_cjn1)
```

Report.o_MCCN

Reports the results of a MultiClass Closed Network

Description

Reports the results of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Report(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
```

```
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Report(o_MCCN1)
```

Report.o_MCMN

Reports the results of a MultiClass Mixed Network

Description

Reports the results of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Report(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Report(o_mcmn1)
```

Report.o_MCON

Reports the results of a MultiClass Open Network

Description

Reports the results of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Report(x, ...)
```

Arguments

x	a object of class o_MCON
...	aditional arguments

Details

Generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Report(o_mcon1)
```

Report.o_MM1

Reports the results of a M/M/1 queueing model

Description

Reports the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'o_MM1'
Report(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the results
Report(o_mm1)
```

Report.o_MM1K

Reports the results of a M/M/1/K queueing model

Description

Reports the results of a M/M/1/K queueing model.

Usage

```
## S3 method for class 'o_MM1K'
Report(x, ...)
```

Arguments

x a object of class o_MM1K
... additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Report the results
Report(o_mm1k)
```

Report.o_MM1KK	<i>Reports the results of a M/M/1/K/K queueing model</i>
----------------	--

Description

Reports the results of a M/M/1/K/K queueing model.

Usage

```
## S3 method for class 'o_MM1KK'
Report(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Report the results
Report(o_mm1kk)
```

Report.o_MMC

Reports the results of a M/M/c queueing model

Description

Reports the results of a M/M/c queueing model.

Usage

```
## S3 method for class 'o_MMC'
Report(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Report the results
Report(o_mmc)
```

Report.o_MMCC

Reports the results of a M/M/c/c queueing model

Description

Reports the results of a M/M/c/c queueing model.

Usage

```
## S3 method for class 'o_MMCC'
Report(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Report the results
Report(o_mmcc)
```

Report.o_MMCK

Reports the results of a M/M/c/K queueing model

Description

Reports the results of a M/M/c/K queueing model.

Usage

```
## S3 method for class 'o_MMCK'
Report(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Report the results
Report(o_mmck)
```

Report.o_MMCKK	<i>Reports the results of a M/M/c/K/K queueing model</i>
----------------	--

Description

Reports the results of a M/M/c/K/K queueing model.

Usage

```
## S3 method for class 'o_MMCKK'
Report(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Report the results
Report(o_mmckk)
```

Report.o_MMCKM	<i>Reports the results of a M/M/c/K/m queueing model</i>
----------------	--

Description

Reports the results of a M/M/c/K/m queueing model.

Usage

```
## S3 method for class 'o_MMCKM'
Report(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Report the results
Report(o_mmckm)
```

Report.o_MMInf	<i>Reports the results of a M/M/Infinite queueing model</i>
----------------	---

Description

Reports the results of a M/M/Infinite queueing model.

Usage

```
## S3 method for class 'o_MMInf'
Report(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Report the results
Report(o_mminf)
```

Report.o_MMInfKK *Reports the results of a M/M/Infinite/K/K queueing model*

Description

Reports the results of a M/M/Infinite/K/K queueing model.

Usage

```
## S3 method for class 'o_MMInfKK'
Report(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Generates a report of the queueing model received as parameter

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Report the results
Report(o_MMInfKK)
```

Report.o_OJN	<i>Reports the results of an Open Jackson Network</i>
--------------	---

Description

Reports the results of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Report(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Generates a report of the queueing network received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

o_ojn <- QueueingModel(i_ojn)

Report(o_ojn)
```

RO

Reports the server use of a queueing model

Description

Reports the server use of a queueing model)

Usage

RO(x, ...)

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	aditional arguments

Details

Reports the server use of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

RO.o_MM1
RO.o_MM2
RO.o_MM1K
RO.o_MMCK
RO.o_MM1KK
RO.o_MMCKK
RO.o_MMCC
RO.o_MMCKM
RO.o_MMInfKK
RO.o_MMInf

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the use of the server
RO(o_mm1)
```

RO.o_MM1	<i>Reports the server use of a M/M/1 queueing model</i>
----------	---

Description

Reports the server use of a M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
RO(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Reports the server use of a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the use of the server
RO(o_mm1)
```

 RO.o_MM1K

Reports the server use of a M/M/1/K queueing model

Description

Reports the server use of a M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
RO(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Reports the server use of a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Report the use of the server
RO(o_mm1k)
```

RO.o_MM1KK

Reports the server use of a M/M/1/K/K queueing model

Description

Reports the server use of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
RO(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Reports the server use of a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Report the use of the server
RO(o_mm1kk)
```

RO.o_MMC

Reports the server use of a M/M/c queueing model

Description

Reports the server use of a M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
RO(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Reports the server use of a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Report the use of the server
RO(o_mmc)
```

RO.o_MMCC

Reports the server use of a M/M/c/c queueing model

Description

Reports the server use of a M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
RO(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Reports the server use of a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Report the use of the server
RO(o_mmcc)
```

RO.o_MMCK

Reports the server use of a M/M/c/K queueing model

Description

Reports the server use of a M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
RO(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Reports the server use of a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Report the use of the server
RO(o_mmck)
```

RO.o_MMCKK

Reports the server use of a M/M/c/K/K queueing model

Description

Reports the server use of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
RO(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Reports the server use of a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Report the use of the server
RO(o_mmckk)
```

RO.o_MMCKM

Reports the server use of a M/M/c/K/m queueing model

Description

Reports the server use of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
RO(x, ...)
```

Arguments

x a object of class o_MMCKM
... additional arguments

Details

Reports the server use of a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Report the use of the server
RO(o_mmckm)
```

RO.o_MMInf	<i>Reports the server use of a M/M/Infinite queueing model</i>
------------	--

Description

Reports the server use of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
RO(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Reports the server use of a M/M/Infinite queueing model. It should be noted that in this model, the RO parameter has a different meaning, its the traffic intensity and it coincides exactly with the average number of customers in the system (L)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#)
[L.o_MMInf](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Report the use of the server
RO(o_mminf)
```

RO.o_MMInfKK

Reports the server use of a M/M/Infinite/K/K queueing model

Description

Reports the server use of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
RO(x, ...)
```

Arguments

x a object of class o_MMInfKK
... additional arguments

Details

Reports the server use of a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Report the use of the server
RO(o_MMInfKK)
```

ROck	<i>Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network</i>
------	--

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network

Usage

```
ROck(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	aditional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos CaballeROk, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial CentROk de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[ROck.o_MCON](#)
[ROck.o_MCCN](#)
[ROck.o_MCMN](#)

Examples

```

## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROck(o_MCCN1)

```

ROck.o_MCCN

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

Usage

```

## S3 method for class 'o_MCCN'
ROck(x, ...)

```

Arguments

x a object of class o_MCCN
... additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROck(o_MCCN1)
```

ROck.o_MCMN

Reports a matrix with the use of class i in each node (server) j in a MultiClass Mixed Network

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
ROck(x, ...)
```

Arguments

x a object of class o_MCMN
 ... additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

ROck(o_mcmn1)
```

ROck.o_MCON

Reports a matrix with the use of class i in each node (server) j in a MultiClass Open Network

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
ROck(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON.](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

ROck(o_mcon1)
```

 ROk

Reports a vector with each node (server) use of a queueing network

Description

Reports a vector with each node (server) use of a queueing network

Usage

```
ROk(x, ...)
```

Arguments

x a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
 ... additional arguments

Details

Reports a vector with each node (server) use of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos CaballeROk, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial CentROk de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[ROk.o_OJN](#)
[ROk.o_CJN](#)
[ROk.o_MCON](#)
[ROk.o_MCCN](#)
[ROk.o_MCMN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROk(o_MCCN1)
```

ROk.o_CJN	<i>Reports a vector with each node (server) use of a Closed Jackson Network</i>
-----------	---

Description

Reports a vector with each node (server) use of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'  
ROk(x, ...)
```

Arguments

x	a object of class o_CJN
...	aditional arguments

Details

Reports a vector with each node (server) use of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)
```

```
# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

ROk(m_cjn1)
```

ROk.o_MCCN	<i>Reports a vector with each node (server) use of a MultiClass Closed Network</i>
------------	--

Description

Reports a vector with each node (server) use of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
ROk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	aditional arguments

Details

Reports a vector with each node (server) use of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROk(o_MCCN1)
```

ROk.o_MCMN	<i>Reports a vector with each node (server) use of a MultiClass Mixed Network</i>
------------	---

Description

Reports a vector with each node (server) use of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
ROk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Reports a vector with each node (server) use of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

ROk(o_mcmn1)
```

ROk.o_MCON

Reports a vector with each node (server) use of a MultiClass Open Network

Description

Reports a vector with each node (server) use of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
ROk(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Reports a vector with each node (server) use of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

ROk(o_mcon1)
```

ROk.o_OJN

Reports a vector with each node (server) use of an Open Jackson Network

Description

Reports a vector with each node (server) use of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
ROk(x, ...)
```

Arguments

x a object of class o_OJN
 ... additional arguments

Details

Reports a vector with each node (server) use of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Deinition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

R0k(o_ojn)
```

 SP

Returns the saturation point of a queueing model

Description

Returns the saturation point of a queueing model

Usage

SP(x, ...)

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

Returns the saturation point of a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[SP.o_MM1KK](#)

Examples

```
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=4, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the saturation point
SP(o_mm1kk)
```

SP.o_MM1KK

Returns the saturation point of a M/M/1/K/K queueing model

Description

Returns the saturation point, or the maximum number of customers that the M/M/1/K/K queueing model can support with no interference or synchronization between themselves

Usage

```
## S3 method for class 'o_MM1KK'
SP(x, ...)
```

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

The value returned is the optimal number of customers of a M/M/1/K/K queueing model. It coincides with the inverse of the serialization parameter of Amdahl's Law. That is, the value which converges the speedup $\text{func}(k) = k/(1 + \text{ser} * (k-1))$. It makes sense, because the saturation point is the maximum value in which no synchronization happens.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=4, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the saturation point
SP(o_mm1kk)
```

summary.o_BnD

Summary of the results of a generic Birth and Death process model

Description

Summary of the results of a generic Birth and Death process model.

Usage

```
## S3 method for class 'o_BnD'
summary(object, ...)
```

Arguments

object	a object of class o_BnD
...	additional arguments

Details

Summaries a generic Birth and Death process model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_BnD](#).

Examples

```
## Generating a generic Birth and Death model with the same lambda and mu vectors as M/M/1 model
## create input parameters
lambda <- rep(1/4, 200)
mu <- rep(1/3, 200)

i_BnD <- NewInput.BnD(lambda=lambda, mu=mu)

## Build the model
o_BnD <- QueueingModel(i_BnD)

## Report the results
summary(o_BnD)
```

summary.o_CJN

Summary of the results of a Closed Jackson Network

Description

Summary of the results of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
summary(object, ...)
```

Arguments

object	a object of class o_CJN
...	additional arguments

Details

Summaries a Closed Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

summary(m_cjn1)
```

summary.o_MCCN

Summary of the results of a MultiClass Closed Network

Description

Summary of the results of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
summary(object, ...)
```

Arguments

object a object of class o_MCCN
 ... additional arguments

Details

Summaries a queueing network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

summary(o_MCCN1)
```

summary.o_MCCN

Summary of the results of a MultiClass Mixed Network

Description

Summary of the results of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'  
summary(object, ...)
```

Arguments

```
object      a object of class o_MCMN  
...        additional arguments
```

Details

Summaries a MultiClass Mixed Network model

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.  
  
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=1, nrow=4, ncol=2)  
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)  
  
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcmn1 <- QueueingModel(i_mcmn1)  
  
summary(o_mcmn1)
```

summary.o_MCON	<i>Summary of the results of a MultiClass Open Network</i>
----------------	--

Description

Summary of the results of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
summary(object, ...)
```

Arguments

object	a object of class o_MCON
...	additional arguments

Details

Summaries a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

summary(o_mcon1)
```

`summary.o_MM1`*Summary of the results of a M/M/1 queueing model*

Description

Summary of the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'o_MM1'  
summary(object, ...)
```

Arguments

```
object      a object of class o_MM1  
...         additional arguments
```

Details

Summaries a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Report the results  
summary(o_mm1)
```

`summary.o_MM1K`*Summary of the results of a M/M/1/K queueing model*

Description

Summary of the results of a M/M/1/K queueing model.

Usage

```
## S3 method for class 'o_MM1K'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MM1K</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Report the results  
summary(o_mm1k)
```

`summary.o_MM1KK`*Summary of the results of a M/M/1/K/K queueing model*

Description

Summary of the results of a M/M/1/K/K queueing model.

Usage

```
## S3 method for class 'o_MM1KK'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MM1KK</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Report the results  
summary(o_mm1kk)
```

`summary.o_MMC`*Summary of the results of a M/M/c queueing model*

Description

Summary of the results of a M/M/c queueing model.

Usage

```
## S3 method for class 'o_MMC'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMC</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Report the results  
summary(o_mmc)
```

`summary.o_MMCC`*Summary of the results of a M/M/c/c queueing model*

Description

Summary of the results of a M/M/c/c queueing model.

Usage

```
## S3 method for class 'o_MMCC'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCC</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Report the results  
summary(o_mmcc)
```

`summary.o_MMCK`*Summary of the results of a M/M/c/K queueing model*

Description

Summary of the results of a M/M/c/K queueing model.

Usage

```
## S3 method for class 'o_MMCK'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCK</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Report the results  
summary(o_mmck)
```

`summary.o_MMCKK`*Summary of the results of a M/M/c/K/K queueing model*

Description

Summary of the results of a M/M/c/K/K queueing model.

Usage

```
## S3 method for class 'o_MMCKK'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCKK</code>
<code>...</code>	aditional arguments

Details

Summaries a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Report the results  
summary(o_mmckk)
```

summary.o_MMCKM	<i>Summary of the results of a M/M/c/K/m queueing model</i>
-----------------	---

Description

Summary of the results of a M/M/c/K/m queueing model.

Usage

```
## S3 method for class 'o_MMCKM'  
summary(object, ...)
```

Arguments

object	a object of class o_MMCKM
...	aditional arguments

Details

Summaries a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Report the results  
summary(o_mmckm)
```

`summary.o_MMInf`*Summary of the results of a M/M/Infinite queueing model*

Description

Summary of the results of a M/M/Infinite queueing model.

Usage

```
## S3 method for class 'o_MMInf'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMInf</code>
<code>...</code>	additional arguments

Details

Summaries a M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Report the results  
summary(o_mminf)
```

summary.o_MMInfKK	<i>Summary of the results of a M/M/Infinite/K/K queueing model</i>
-------------------	--

Description

Summary of the results of a M/M/Infinite/K/K queueing model.

Usage

```
## S3 method for class 'o_MMInfKK'  
summary(object, ...)
```

Arguments

object	a object of class o_MMInfKK
...	additional arguments

Details

Summaries a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Report the results  
summary(o_MMInfKK)
```

`summary.o_OJN`*Summary of the results of an Open Jackson Network*

Description

Summary of the results of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'  
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_OJN</code>
<code>...</code>	aditional arguments

Details

Summaries an Open Jackson Network model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.  
## create the nodes  
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)  
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)  
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)  
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)  
  
# definition of the transition probabilities  
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)  
  
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)  
  
o_ojn <- QueueingModel(i_ojn)
```

summary(o_ojn)

Throughput	<i>Throughput of a queueing model (or network)</i>
------------	--

Description

Returns the throughput of a queueing model (or network)

Usage

Throughput(x, ...)

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the throughput of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughput.o_MM1](#)
[Throughput.o_MMC](#)
[Throughput.o_MM1K](#)
[Throughput.o_MMCK](#)
[Throughput.o_MM1KK](#)
[Throughput.o_MMCKK](#)
[Throughput.o_MMCC](#)
[Throughput.o_MMCKM](#)
[Throughput.o_MMInfKK](#)

```

Throughput.o_MMInf
Throughput.o_OJN
Throughput.o_CJN
Throughput.o_MCON
Throughput.o_MCCN
Throughput.o_MCMN

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Throughput
Throughput(o_mm1)

```

Throughput.o_CJN	<i>Reports the network throughput of a Closed Jackson Network</i>
------------------	---

Description

Reports the network throughput of a Closed Jackson Network

Usage

```

## S3 method for class 'o_CJN'
Throughput(x, ...)

```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Reports the network throughput of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughput(m_cjn1)
```

Throughput.o_MCCN *Reports the throughput of a MultiClass Closed Network*

Description

Reports the throughput of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughput(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports the throughput of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughput(o_MCCN1)
```

Throughput.o_MCMN *Reports the throughput of a MultiClass Mixed Network*

Description

Reports the throughput of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughput(x, ...)
```

Arguments

x a object of class o_MCMN
 ... additional arguments

Details

Reports the throughput of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughput(o_mcmn1)
```

Throughput.o_MCON *Reports the throughput of a MultiClass Open Network*

Description

Reports the throughput of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Throughput(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Reports the throughput of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughput(o_mcon1)
```

Throughput.o_MM1

Throughput of a M/M/1 queueing model

Description

Returns the throughput of a M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Throughput(x, ...)
```

Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the throughput of a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#), [CheckInput.i_MM1](#), [QueueingModel.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Throughput
Throughput(o_mm1)
```

Throughput.o_MM1K *Throughput of a M/M/1/K queueing model*

Description

Returns the throughput of a M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Throughput(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the throughput of a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#), [CheckInput.i_MM1K](#), [QueueingModel.i_MM1K](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mmck <- QueueingModel(i_mm1k)

## Throughput
Throughput(o_mmck)
```

Throughput.o_MM1KK *Throughput of a M/M/1/K/K queueing model*

Description

Returns the throughput of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Throughput(x, ...)
```

Arguments

```
x                    a object of class o_MM1KK
...                   additional arguments
```

Details

Returns the throughput of a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK](#), [CheckInput.i_MM1KK](#), [QueueingModel.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_MM1KKk <- QueueingModel(i_mm1kk)

## Throughput
Throughput(o_MM1KKk)
```

Throughput.o_MMC

Throughput of a M/M/c queueing model

Description

Returns the throughput of a M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Throughput(x, ...)
```

Arguments

x a object of class o_MMC
 ... additional arguments

Details

Returns the throughput of a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC](#), [CheckInput.i_MMC](#), [QueueingModel.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Throughput
Throughput(o_mmc)
```

Throughput.o_MMCC	<i>Throughput of a M/M/c/c queueing model</i>
-------------------	---

Description

Returns the throughput of a M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the throughput of a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC](#), [CheckInput.i_MMCC](#), [QueueingModel.i_MMCC](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Throughput
Throughput(o_mmcc)
```

Throughput.o_MMCK *Throughput of a M/M/c/K queueing model*

Description

Returns the throughput of a M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Throughput(x, ...)
```

Arguments

x a object of class o_MMCK
 ... additional arguments

Details

Returns the throughput of a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#), [CheckInput.i_MMCK](#), [QueueingModel.i_MMCK](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Throughput
Throughput(o_mmck)
```

Throughput.o_MMCKK *Throughput of a M/M/c/K/K queueing model*

Description

Returns the throughput of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Throughput(x, ...)
```

Arguments

x a object of class o_MMCKK
 ... additional arguments

Details

Returns the throughput of a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#), [CheckInput.i_MMCKK](#), [QueueingModel.i_MMCKK](#)

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## build the model
o_mmckk <- QueueingModel(i_mmckk)

## Throughput
Throughput(o_mmckk)
```

Throughput.o_MMCKM *Throughput of a M/M/c/K/m queueing model*

Description

Returns the throughput of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Throughput(x, ...)
```

Arguments

x a object of class o_MMCKM
 ... additional arguments

Details

Returns the throughput of a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#), [CheckInput.i_MMCKM](#), [QueueingModel.i_MMCKM](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Throughput
Throughput(o_mmckm)
```

Throughput.o_MMInf *Throughput of a M/M/Infinite queueing model*

Description

Returns the throughput of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the throughput of a M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#), [CheckInput.i_MMInf](#), [QueueingModel.i_MMInf](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Throughput
Throughput(o_mminf)
```

Throughput.o_MMInfKK *Throughput of a M/M/Infinite/K/K queueing model*

Description

Returns the throughput of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the throughput of a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#), [CheckInput.i_MMInfKK](#), [QueueingModel.i_MMInfKK](#)

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Throughput
Throughput(o_MMInfKK)
```

Throughput.o_OJN	<i>Reports the throughput of an Open Jackson Network</i>
------------------	--

Description

Reports the throughput of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Throughput(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Reports the throughput of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_OJN](#), [QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Throughput(o_ojn)
```

Throughputc	<i>Reports a vector with each class throughput in a multiclass queueing network</i>
-------------	---

Description

Reports a vector with each class throughput in a multiclass queueing network

Usage

```
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Reports a vector with each class throughput in a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputc.o_MCON](#)
[Throughputc.o_MCCN](#)
[Throughputc.o_MCCN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputc(o_mcon1)
```

Throughputc.o_MCCN	<i>Reports a vector with each class throughput in a MultiClass Closed Network</i>
--------------------	---

Description

Reports a vector with each class throughput in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a vector with each class throughput in a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputc(o_MCCN1)
```

Throughputc.o_MCMN	<i>Reports a vector with each class throughput in a MultiClass Mixed Network</i>
--------------------	--

Description

Reports a vector with each class throughput in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughputc(x, ...)
```

Arguments

```
x          a object of class o_MCMN
...        additional arguments
```

Details

Reports a vector with each class throughput in a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputc(o_mcmn1)
```

Throughputc.o_MCON	<i>Reports a vector with each class throughput in a MultiClass Open Network</i>
--------------------	---

Description

Reports a vector with each class throughput in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'  
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each class throughput in a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.
```

```
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)
```

```

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputc(o_mcon1)

```

Throughputck	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network</i>
--------------	--

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network

Usage

```
Throughputck(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN
...	additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputck.o_MCON](#)
[Throughputck.o_MCCN](#)
[Throughputck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputck(o_mcon1)
```

Throughputck.o_MCCN *Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network*

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputck(x, ...)
```

Arguments

x a object of class o_MCCN
 ... additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputck(o_MCCN1)
```

Throughputck.o_MCMN	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network</i>
---------------------	--

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughputck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.

Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputck(o_mcmn1)
```

Throughputck.o_MCON	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network</i>
---------------------	---

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Throughputck(x, ...)
```

Arguments

```
x          a object of class o_MCON
...        additional arguments
```

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputck(o_mcon1)
```

Throughputcn	<i>Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network</i>
--------------	--

Description

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

Usage

```
Throughputcn(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputcn.o_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputcn(o_MCCN1)
```

Throughputcn.o_MCCN *Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network*

Description

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputcn(x, ...)
```

Arguments

x a object of class o_MCCN
... additional arguments

Details

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputcn(o_MCCN1)
```

Throughputk	<i>Reports a vector with each node (server) throughput of a queueing network</i>
-------------	--

Description

Reports a vector with each node (server) throughput of a queueing network

Usage

```
Throughputk(x, ...)
```

Arguments

x	a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Reports a vector with each node (server) throughput of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik

(1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputk.o_OJN](#)
[Throughputk.o_CJN](#)
[Throughputk.o_MCON](#)
[Throughputk.o_MCCN](#)
[Throughputk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputk(o_mcon1)
```

Throughputk.o_CJN	<i>Reports a vector with each node (server) throughput of a Closed Jackson Network</i>
-------------------	--

Description

Reports a vector with each node (server) throughput of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Throughputk(x, ...)
```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Reports a vector with each node (server) throughput of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputk(m_cjn1)
```

Throughputk.o_MCCN	<i>Reports a vector with each node (server) throughput of a MultiClass Closed Network</i>
--------------------	---

Description

Reports a vector with each node (server) throughput of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputk(x, ...)
```

Arguments

```
x          a object of class o_MCCN
...        additional arguments
```

Details

Reports a vector with each node (server) throughput of a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputk(o_MCCN1)
```

Throughputk.o_MCMN	<i>Reports a vector with each node (server) throughput of a MultiClass Mixed Network</i>
--------------------	--

Description

Reports a vector with each node (server) throughput of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'  
Throughputk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a vector with each node (server) throughput of a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.
```

```
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")
```

```

vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputk(o_mcmn1)

```

Throughputk.o_MCON	<i>Reports a vector with each node (server) throughput of a MultiClass Open Network</i>
--------------------	---

Description

Reports a vector with each node (server) throughput of a MultiClass Open Network

Usage

```

## S3 method for class 'o_MCON'
Throughputk(x, ...)

```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each node (server) throughput of a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputk(o_mcon1)
```

Throughputk.o_OJN	<i>Reports a vector with each node (server) throughput of an Open Jackson Network</i>
-------------------	---

Description

Reports a vector with each node (server) throughput of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Throughputk(x, ...)
```

Arguments

x	a object of class o_OJN
...	aditional arguments

Details

Reports a vector with each node (server) throughput of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_OJN](#), [QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Throughputk(o_ojn)
```

Throughputn	<i>Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network</i>
-------------	---

Description

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network

Usage

```
Throughputn(x, ...)
```

Arguments

x	a object of class o_CJN
...	aditional arguments

Details

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Throughputn.o_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputn(m_cjn1)
```

Throughputn.o_CJN	<i>Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network</i>
-------------------	---

Description

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Throughputn(x, ...)
```

Arguments

x a object of class o_CJN
 ... additional arguments

Details

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputn(m_cjn1)
```

VN	Returns the variance of the number of customers in a queueing model (or network)
----	--

Description

Returns the variance of the number of customers in a queueing model (or network)

Usage

```
VN(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in a queueing model (or network)

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[VN.o_MM1](#)
[VN.o_MMC](#)
[VN.o_MMCC](#)
[VN.o_MMInf](#)
[VN.o_MMInfKK](#)
[VN.o_MM1K](#)
[VN.o_MMCK](#)
[VN.o_MM1KK](#)
[VN.o_MMCKK](#)
[VN.o_MMCKM](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)
```

```
## Returns the variance
VN(o_mm1)
```

VN.o_MM1	<i>Returns the variance of the number of customers in the M/M/1 queueing model</i>
----------	--

Description

Returns the variance of the number of customers in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
VN(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance
VN(o_mm1)
```

VN.o_MM1K	<i>Returns the variance of the number of customers in the M/M/1/K queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VN(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VN(o_mm1k)
```

VN.o_MM1KK	<i>Returns the variance of the number of customers in the M/M/1/K/K queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VN(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VN(o_mm1kk)
```

VN.o_MMC	<i>Returns the variance of the number of customers in the M/M/c queueing model</i>
----------	--

Description

Returns the variance of the number of customers in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VN(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance  
VN(o_mmc)
```

VN.o_MMCC	<i>Returns the variance of the number of customers in the M/M/c/c queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VN(o_mmcc)
```

VN.o_MMCK	<i>Returns the variance of the number of customers in the M/M/c/K queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VN(o_mmck)
```

VN.o_MMCKK	<i>Returns the variance of the number of customers in the M/M/c/K/K queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VN(o_mmckk)
```

VN.o_MMCKM	<i>Returns the variance of the number of customers in the M/M/c/K/m queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/c/K/m queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the variance  
VN(o_mmckm)
```

VN.o_MMInf	<i>Returns the variance of the number of customers in the M/M/Infinite queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VN(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VN(o_mminf)
```

VN.o_MMInfKK	<i>Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model</i>
--------------	---

Description

Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the variance  
VN(o_MMInfKK)
```

VNq	<i>Returns the variance of the number of customers in the queue in a queueing model</i>
-----	---

Description

Returns the variance of the number of customers in the queue in a queueing model

Usage

```
VNq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMCC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the queue in a queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[VNq.o_MM1](#)
[VNq.o_MM1](#)
[VNq.o_MMCC](#)
[VNq.o_MMInf](#)
[VNq.o_MMInfKK](#)
[VNq.o_MM1K](#)
[VNq.o_MMCK](#)
[VNq.o_MM1KK](#)
[VNq.o_MMCKK](#)
[VNq.o_MMCKM](#)

Examples

```
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)
```

```
## Returns the variance
VNq(o_mm1)
```

VNq.o_MM1	<i>Returns the variance of the number of customers in the queue in the M/M/1 queueing model</i>
-----------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
VNq(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance
VNq(o_mm1)
```

VNq.o_MM1K	<i>Returns the variance of the number of customers in the queue in the M/M/1/K queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VNq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VNq(o_mm1k)
```

VNq.o_MM1KK	<i>Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VNq(o_mm1kk)
```

VNq.o_MMC	<i>Returns the variance of the number of customers in the queue in the M/M/c queueing model</i>
-----------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance  
VNq(o_mmc)
```

VNq.o_MMCC	<i>Returns the variance of the number of customers in the queue in the M/M/c/c queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VNq(o_mmcc)
```

VNq.o_MMCK	<i>Returns the variance of the number of customers in the queue in the M/M/c/K queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VNq(o_mmck)
```

VNq.o_MMCKK	<i>Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VNq(o_mmckk)
```

VNq.o_MMCKM	<i>Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the variance  
VNq(o_mmckm)
```

VNq.o_MMInf	<i>Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model</i>
-------------	--

Description

Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VNq(o_mminf)
```

VNq.o_MMInfKK	<i>Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model</i>
---------------	--

Description

Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the VNq  
VNq(o_MMInfKK)
```

VT	<i>Returns the variance of the time spend in a queueing model (or network)</i>
----	--

Description

Returns the variance of the time spend in a queueing model (or network)

Usage

```
VT(x, ...)
```

Arguments

x	a object of class <code>o_MM1</code> , <code>o_MMC</code> , <code>o_MM1K</code> , <code>o_MMCK</code> , <code>o_MM1KK</code> , <code>o_MMCKK</code> , <code>o_MMCC</code> , <code>o_MMCKM</code> , <code>o_MMInfKK</code> , <code>o_MMInf</code>
...	additional arguments

Details

Returns the variance of the time spend in a queueing model (or network)

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[VT.o_MM1](#)
[VT.o_MMC](#)
[VT.o_MMCC](#)
[VT.o_MMInf](#)
[VT.o_MMInfKK](#)
[VT.o_MM1K](#)
[VT.o_MM1KK](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in the system
VT(o_mm1)
```

`VT.o_MM1`*Returns the variance of the time spend in the M/M/1 queueing model*

Description

Returns the variance of the time spend in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
VT(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MM1</code>
<code>...</code>	aditional arguments

Details

Returns the variance of the time spend in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the variance of the time spend in the system  
VT(o_mm1)
```

VT.o_MM1K *Returns the variance of the time spend in the M/M/1/K queueing model*

Description

Returns the variance of the time spend in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VT(x, ...)
```

Arguments

x a object of class o_MM1K
... additional arguments

Details

Returns the variance of the time spend in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VT(o_mm1k)
```

VT.o_MM1KK	<i>Returns the variance of the time spend in the M/M/1/K/K queueing model</i>
------------	---

Description

Returns the variance of the time spend in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VT(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the time spend in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VT(o_mm1kk)
```

`VT.o_MMC`*Returns the variance of the time spend in the M/M/c queueing model*

Description

Returns the variance of the time spend in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VT(x, ...)
```

Arguments

`x` a object of class `o_MMC`
`...` additional arguments

Details

Returns the variance of the time spend in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance of the time spend in the system  
VT(o_mmc)
```

`VT.o_MMCC`*Returns the variance of the time spend in the M/M/c/c queueing model*

Description

Returns the variance of the time spend in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VT(x, ...)
```

Arguments

`x` a object of class o_MMCC
`...` additional arguments

Details

Returns the variance of the time spend in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VT(o_mmcc)
```

VT.o_MMInf	<i>Returns the variance of the time spend in the M/M/Infinite queueing model</i>
------------	--

Description

Returns the variance of the time spend in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VT(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the the variance of the time spend in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VT(o_mminf)
```

VT.o_MMInfKK	<i>Returns the variance of the time spend in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the variance of the time spend in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VT(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the variance of the time spend in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the variance  
VT(o_MMInfKK)
```

VTq	<i>Returns the variance of the time spend in queue in a queueing model</i>
-----	--

Description

Returns the variance of the time spend in queue in a queueing model

Usage

```
VTq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMIInfKK, o_MMIInf
...	additional arguments

Details

Returns the variance of the time spend in queue in a queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[VTq.o_MM1](#)
[VTq.o_MMC](#)
[VTq.o_MMCC](#)
[VTq.o_MMIInf](#)
[VTq.o_MMIInfKK](#)
[VTq.o_MM1K](#)
[VTq.o_MMCK](#)
[VTq.o_MM1KK](#)
[VTq.o_MMCKK](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in queue
VTq(o_mm1)
```

VTq.o_MM1	<i>Returns the variance of the time spend in queue in the M/M/1 queueing model</i>
-----------	--

Description

Returns the variance of the time spend in queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the variance of the time spend in queue  
VTq(o_mm1)
```

VTq.o_MM1K	<i>Returns the variance of the time spend in queue in the M/M/1/K queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VTq(o_mm1k)
```

VTq.o_MM1KK	<i>Returns the variance of the time spend in queue in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the variance of the time spend in queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the VTq  
VTq(o_mm1kk)
```

VTq.o_MMC	<i>Returns the variance of the time spend in queue in the M/M/c queueing model</i>
-----------	--

Description

Returns the variance of the time spend in queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance of the time spend in queue  
VTq(o_mmc)
```

VTq.o_MMCC	<i>Returns the variance of the time spend in queue in the M/M/c/c queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VTq(o_mmcc)
```

VTq.o_MMCK	<i>Returns the variance of the time spend in queue in the M/M/c/K queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VTq(o_mmck)
```

VTq.o_MMCKK	<i>Returns the variance of the time spend in queue in the M/M/c/K/K queueing model</i>
-------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VTq(o_mmckk)
```

VTq.o_MMInf	<i>Returns the variance of the time spend in queue in the M/M/Infinite queueing model</i>
-------------	---

Description

Returns the variance of the time spend in queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VTq(o_mminf)
```

VTq.o_MMInfKK	<i>Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model</i>
---------------	---

Description

Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the variance  
VTq(o_MMInfKK)
```

W *Returns the mean time spend in a queueing model (or network)*

Description

Returns the mean time spend in a queueing model (or network)

Usage

$W(x, \dots)$

Arguments

x a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_MCON, o_MCCN, o_MCMN
... additional arguments

Details

Returns the mean time spend in a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[W.o_MM1](#)
[W.o_MMC](#)
[W.o_MM1K](#)
[W.o_MMCK](#)
[W.o_MM1KK](#)
[W.o_MMCKK](#)
[W.o_MMCC](#)
[W.o_MMCKM](#)
[W.o_MMInfKK](#)
[W.o_MMInf](#)
[W.o_OJN](#)
[W.o_MCON](#)
[W.o_MCCN](#)
[W.o_MCMN](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the W
W(o_mm1)
```

W.o_CJN

Returns the mean time spend in a Closed Jackson Network

Description

Returns the mean time spend in a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
W(x, ...)
```

Arguments

x a object of class o_CJN
... additional arguments

Details

Returns the mean time spend in a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```

## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

W(m_cjn1)

```

W.o_MCCN

Returns the mean time spend in a MultiClass Closed Network

Description

Returns the mean time spend in a MultiClass Closed Network

Usage

```

## S3 method for class 'o_MCCN'
W(x, ...)

```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns the mean time spend in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

W(o_MCCN1)
```

W.o_MCMN

Returns the mean time spend in a MultiClass Mixed Network

Description

Returns the mean time spend in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
W(x, ...)
```

Arguments

x a object of class o_MCMN
... additional arguments

Details

Returns the mean time spend in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

W(o_mcmn1)
```

W.o_MCON

Returns the mean time spend in a MultiClass Open Network

Description

Returns the mean time spend in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
W(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Returns the mean time spend in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON.](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

W(o_mcon1)
```

W.o_MMI

Returns the mean time spend in the M/M/1 queueing model

Description

Returns the mean time spend in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MMI'
W(x, ...)
```


Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the mean time spend in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the W
W(o_mm1)
```

W.o_MM1K

Returns the mean time spend in the M/M/1/K queueing model

Description

Returns the mean time spend in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
W(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean time spend in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the W
W(o_mm1k)
```

W.o_MM1KK

Returns the mean time spend in the M/M/1/K/K queueing model

Description

Returns the mean time spend in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
W(x, ...)
```

Arguments

```
x          a object of class o_MM1KK
...        additional arguments
```

Details

Returns the mean time spend in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the W
W(o_mm1kk)
```

W.o_MMC

Returns the mean time spend in the M/M/c queueing model

Description

Returns the mean time spend in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
W(x, ...)
```

Arguments

x a object of class o_MMC
 ... additional arguments

Details

Returns the mean time spend in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the W
W(o_mmc)
```

W.o_MMCC

Returns the mean time spend in the M/M/c/c queueing model

Description

Returns the mean time spend in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
W(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean time spend in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the W
W(o_mmcc)
```

W.o_MMCK

Returns the mean time spend in the M/M/c/K queueing model

Description

Returns the mean time spend in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
W(x, ...)
```

Arguments

x a object of class o_MMCK
... additional arguments

Details

Returns the mean time spend in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the W
W(o_mmck)
```

W.o_MMCKK

Returns the mean time spend in the M/M/c/K/K queueing model

Description

Returns the mean time spend in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
W(x, ...)
```

Arguments

x a object of class o_MMCKK
... additional arguments

Details

Returns the mean time spend in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the W
W(o_mmckk)
```

W.o_MMCKM

Returns the mean time spend in the M/M/c/K/m queueing model

Description

Returns the mean time spend in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
W(x, ...)
```

Arguments

x a object of class o_MMCKM
... additional arguments

Details

Returns the mean time spend in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the W
W(o_mmckm)
```

W.o_MMInf

Returns the time spend in the M/M/Infinite queueing model

Description

Returns the mean time spend in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
W(x, ...)
```

Arguments

x a object of class o_MMInf
... additional arguments

Details

Returns the mean time spend in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the W
W(o_mminf)
```

W.o_MMInfKK	Returns the mean time spend in the M/M/Infinite/K/K queueing model
-------------	--

Description

Returns the mean time spend in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
W(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean time spend in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the W
W(o_MMInfKK)
```

W.o_OJN

Returns the mean time spend in an Open Jackson Network

Description

Returns the mean time spend in an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
W(x, ...)
```

Arguments

x a object of class o_OJN
... additional arguments

Details

Returns the mean time spend in an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

W(o_ojn)
```

Wc	<i>Returns the vector with each class mean time spend on a multiclass queueing network</i>
----	--

Description

Returns the vector with each class mean time spend on a multiclass queueing network

Usage

```
Wc(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the vector with each class mean time spend on a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wc.o_MCON](#)
[Wc.o_MCCN](#)
[Wc.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wc(o_mcon1)
```

Wc.o_MCCN

Returns the vector with each class mean time spend on a MultiClass Closed Network

Description

Returns the vector with each class mean time spend on a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Wc(x, ...)
```

Arguments

x a object of class o_MCCN
... additional arguments

Details

Returns the vector with each class mean time spend on a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Wc(o_MCCN1)
```

Wc.o_MCMN

Returns the vector with each class mean time spend on a MultiClass Mixed Network

Description

Returns the vector with each class mean time spend on a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wc(x, ...)
```

Arguments

x a object of class o_MCMN
 ... additional arguments

Details

Returns the vector with each class mean time spend on a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wc(o_mcmn1)
```

Wc.o_MCON

Returns the vector with each class mean time spend on a MultiClass Open Network

Description

Returns the vector with each class mean time spend on a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'  
Wc(x, ...)
```

Arguments

```
x          a object of class o_MCON  
...       additional arguments
```

Details

Returns the vector with each class mean time spend on a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
Wc(o_mcon1)
```

Wck	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network</i>
-----	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network

Usage

```
Wck(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wck.o_MCON](#)
[Wck.o_MCCN](#)
[Wck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")
```



```

vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wck(o_mcon1)

```

Wck.o_MCCN	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network</i>
------------	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network

Usage

```

## S3 method for class 'o_MCCN'
Wck(x, ...)

```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Wck(o_MCCN1)
```

Wck.o_MCMN	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network</i>
------------	---

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wck(o_mcmn1)
```

Wck.o_MCON	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network</i>
------------	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Wck(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wck(o_mcon1)
```

Wk	<i>Generic S3 method to return the mean time spend in each node (or server) of a network</i>
----	--

Description

Generic S3 method to return the mean time spend in each node (or server) of a network

Usage

```
Wk(x, ...)
```

Arguments

x	a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Generic S3 method to return the mean time spend in each node (or server) of a network

References

- [Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.
- [Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wk.o_OJN](#)
[Wk.o_CJN](#)
[Wk.o_MCON](#)
[Wk.o_MCCN](#)
[Wk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wk(o_mcon1)
```

Wk.o_CJN

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

Description

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Wk(x, ...)
```

Arguments

x a object of class o_CJN
... additional arguments

Details

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)  
  
# Define a new input  
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)  
  
# Check the inputs and build the model  
m_cjn1 <- QueueingModel(cjn1)  
  
Wk(m_cjn1)
```

Wk.o_MCCN	Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network
-----------	--

Description

Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
Wk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_MCCN1 <- QueueingModel(i_MCCN1)
```

```
Wk(o_MCMN1)
```

Wk.o_MCMN	<i>Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network</i>
-----------	--

Description

Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)
```



```
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wk(o_mcmn1)
```

Wk.o_MCON	<i>Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network</i>
-----------	---

Description

Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Wk(x, ...)
```

Arguments

x	a object of class o_MCON
...	aditional arguments

Details

Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wk(o_mcon1)
```

Wk.o_OJN

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

Description

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Wk(x, ...)
```

Arguments

x a object of class o_OJN
... additional arguments

Details

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

m_ojn1 <- QueueingModel(ojn1)

Wk(m_ojn1)
```

Wq

Returns the mean time spend in queue in a queueing model

Description

Returns the mean time spend in queue in a queueing model

Usage

Wq(x, ...)

Arguments

x a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK,
o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
... additional arguments

Details

Returns the mean time spend in queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[Wq.o_MM1](#)
[Wq.o_MM2](#)
[Wq.o_MM1K](#)
[Wq.o_MMCK](#)
[Wq.o_MM1KK](#)
[Wq.o_MMCKK](#)
[Wq.o_MMCC](#)
[Wq.o_MMCKM](#)
[Wq.o_MMInfKK](#)
[Wq.o_MMInf](#)

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wq
Wq(o_mm1)

```

Wq.o_MM1	<i>Returns the mean time spend in queue in the M/M/1 queueing model</i>
----------	---

Description

Returns the mean time spend in queue in the M/M/1 queueing model

Usage

```

## S3 method for class 'o_MM1'
Wq(x, ...)

```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wq
Wq(o_mm1)
```

Wq.o_MM1K

Returns the mean time spend in queue in the M/M/1/K queueing model

Description

Returns the mean time spend in queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Wq(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean time spend in queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Wq
Wq(o_mm1k)
```

Wq.o_MM1KK	<i>Returns the mean time spend in queue in the M/M/1/K/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wq
Wq(o_mm1kk)
```

Wq.o_MMC

Returns the mean time spend in queue in the M/M/c queueing model

Description

Returns the mean time spend in queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Wq(x, ...)
```

Arguments

x a object of class o_MMC
... additional arguments

Details

Returns the mean time spend in queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Wq
Wq(o_mmc)
```

Wq.o_MMCC	<i>Returns the mean time spend in queue in the M/M/c/c queueing model</i>
-----------	---

Description

Returns the mean time spend in queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Wq
Wq(o_mmcc)
```

Wq.o_MMCK

Returns the mean time spend in queue in the M/M/c/K queueing model

Description

Returns the mean time spend in queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Wq
Wq(o_mmck)
```

Wq.o_MMCKK	<i>Returns the mean time spend in queue in the M/M/c/K/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Wq
Wq(o_mmckk)
```

Wq.o_MMCKM	<i>Returns the mean time spend in queue in the M/M/c/K/m queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Wq
Wq(o_mmckm)
```

Wq.o_MMInf	<i>Returns the mean time spend in queue in the M/M/Infinite queueing model</i>
------------	--

Description

Returns the mean time spend in queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Wq
Wq(o_mminf)
```

Wq.o_MMInfKK	<i>Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Wq
Wq(o_MMInfKK)
```

Wq _q	<i>Returns the mean time spend in queue when there is queue in a queueing model</i>
-----------------	---

Description

Returns the mean time spend in queue when there is queue in a queueing model

Usage

```
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Wq_q.o_MM1](#)
[Wq_q.o_MMC](#)
[Wq_q.o_MM1K](#)
[Wq_q.o_MMCK](#)
[Wq_q.o_MM1KK](#)
[Wq_q.o_MMCKK](#)
[Wq_q.o_MMCC](#)

```

Wqq.o_MMCKM
Wqq.o_MMInfKK
Wqq.o_MMInf

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wqq
Wqq(o_mm1)

```

Wqq.o_MM1	<i>Returns the mean time spend in queue when there is queue in the M/M/1 queueing model</i>
-----------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1 queueing model

Usage

```

## S3 method for class 'o_MM1'
Wqq(x, ...)

```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wqq
Wqq(o_mm1)
```

Wqq.o_MM1K	<i>Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Wqq
Wqq(o_mm1k)
```

Wqq.o_MM1KK	<i>Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wqq
Wqq(o_mm1kk)
```

Wqq.o_MMC	<i>Returns the mean time spend in queue when there is queue in the M/M/c queueing model</i>
-----------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Wqq
Wqq(o_mmc)
```

Wqq.o_MMCC	<i>Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Wqq
Wqq(o_mmcc)
```

Wqq.o_MMCK	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Wqq
Wqq(o_mmck)
```

Wqq.o_MMCKK	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Wqq
Wqq(o_mmckk)
```

Wqq.o_MMCKM	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Wq
Wq(o_mmckm)
```

Wq.o_MMInf	<i>Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model</i>
------------	--

Description

Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Wq
Wq(o_mminf)
```

Wq.o_MMInfKK	<i>Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Wqq
Wqq(o_MMInfKK)
```

WVs

Returns the normalized mean response time in a queueing model

Description

Returns the normalized mean response time in a queueing model

Usage

```
WVs(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the normalized mean response time in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[WVs.o_MM1KK](#).

Examples

```
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wws
Wws(o_mm1kk)
```

Wws.o_MM1KK	<i>Returns the normalized mean response time in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the normalized mean response time in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wws(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the normalized mean response time in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the WVs  
WVs(o_mm1kk)
```

Index

- *Topic **B_erlang**
 - B_erlang, 10
- *Topic **BnD**
 - CheckInput.i_BnD, 12
 - L.o_BnD, 49
 - NewInput.BnD, 104
 - Pn.o_BnD, 124
 - print.summary.o_BnD, 137
 - QueueingModel.i_BnD, 154
 - Report.o_BnD, 172
 - summary.o_BnD, 212
- *Topic **C_erlang**
 - C_erlang, 29
- *Topic **Closed Jackson Network**
 - CheckInput.i_CJN, 13
 - Inputs.o_CJN, 32
 - L.o_CJN, 50
 - Lk.o_CJN, 76
 - NewInput.CJN, 105
 - print.summary.o_CJN, 138
 - QueueingModel.i_CJN, 155
 - Report.o_CJN, 173
 - ROk.o_CJN, 205
 - summary.o_CJN, 213
 - Throughput.o_CJN, 230
 - Throughputk.o_CJN, 258
 - Throughputn.o_CJN, 265
 - W.o_CJN, 308
 - Wk.o_CJN, 333
- *Topic **CompareQueueingModels**
 - CompareQueueingModels, 28
- *Topic **Engset**
 - Engset, 30
- *Topic **M/M/1/K/K**
 - CheckInput.i_MM1KK, 19
 - Inputs.o_MM1KK, 39
 - L.o_MM1KK, 57
 - Lq.o_MM1KK, 85
 - Lqq.o_MM1KK, 96
 - NewInput.MM1KK, 113
 - Pn.o_MM1KK, 128
 - print.summary.o_MM1KK, 144
 - QueueingModel.i_MM1KK, 162
 - Report.o_MM1KK, 179
 - RO.o_MM1KK, 191
 - SP, 210
 - SP.o_MM1KK, 211
 - summary.o_MM1KK, 220
 - Throughput.o_MM1KK, 236
 - VN.o_MM1KK, 270
 - VNq.o_MM1KK, 281
 - VT.o_MM1KK, 292
 - VTq.o_MM1KK, 300
 - W.o_MM1KK, 314
 - Wq.o_MM1KK, 342
 - Wqq.o_MM1KK, 353
 - Wws, 361
 - Wws.o_MM1KK, 362
- *Topic **M/M/1/K**
 - CheckInput.i_MM1K, 18
 - Inputs.o_MM1K, 38
 - L.o_MM1K, 56
 - Lq.o_MM1K, 84
 - Lqq.o_MM1K, 95
 - NewInput.MM1K, 112
 - Pn.o_MM1K, 127
 - print.summary.o_MM1K, 143
 - QueueingModel.i_MM1K, 161
 - Report.o_MM1K, 178
 - RO.o_MM1K, 190
 - summary.o_MM1K, 219
 - Throughput.o_MM1K, 235
 - VN.o_MM1K, 269
 - VNq.o_MM1K, 280
 - VT.o_MM1K, 291
 - VTq.o_MM1K, 299
 - W.o_MM1K, 313
 - Wq.o_MM1K, 341

- Wqq.o_MM1K, 352
- *Topic **M/M/1**
 - CheckInput.i_MM1, 17
 - Inputs.o_BnD, 31
 - Inputs.o_MM1, 37
 - L.o_MM1, 55
 - Lq, 82
 - Lq.o_MM1, 83
 - Lqq, 93
 - Lqq.o_MM1, 94
 - NewInput.MM1, 111
 - Pn.o_MM1, 125
 - print.summary.o_MM1, 142
 - QueueingModel.i_MM1, 160
 - Report, 171
 - Report.o_MM1, 177
 - RO.o_MM1, 189
 - summary.o_MM1, 218
 - Throughput.o_MM1, 234
 - VN.o_MM1, 268
 - VNq, 278
 - VNq.o_MM1, 279
 - VT.o_MM1, 290
 - VTq, 297
 - VTq.o_MM1, 298
 - W.o_MM1, 312
 - Wq, 339
 - Wq.o_MM1, 340
 - Wqq, 350
 - Wqq.o_MM1, 351
- *Topic **M/M/Infinite/K/K**
 - CheckInput.i_MMInfFKK, 26
 - Inputs.o_MMInfFKK, 46
 - L.o_MMInfFKK, 64
 - Lq.o_MMInfFKK, 92
 - Lqq.o_MMInfFKK, 103
 - NewInput.MMInfFKK, 120
 - Pn.o_MMInfFKK, 135
 - print.summary.o_MMInfFKK, 151
 - QueueingModel.i_MMInfFKK, 169
 - Report.o_MMInfFKK, 186
 - RO.o_MMInfFKK, 198
 - summary.o_MMInfFKK, 227
 - Throughput.o_MMInfFKK, 243
 - VN.o_MMInfFKK, 277
 - VNq.o_MMInfFKK, 288
 - VT.o_MMInfFKK, 296
 - VTq.o_MMInfFKK, 306
- W.o_MMInfFKK, 321
- Wq.o_MMInfFKK, 349
- Wqq.o_MMInfFKK, 360
- *Topic **M/M/Infinite**
 - CheckInput.i_MMInf, 25
 - Inputs.o_MMInf, 45
 - L.o_MMInf, 63
 - Lq.o_MMInf, 91
 - Lqq.o_MMInf, 102
 - NewInput.MMInf, 119
 - Pn.o_MMInf, 134
 - print.summary.o_MMInf, 150
 - QueueingModel.i_MMInf, 168
 - Report.o_MMInf, 185
 - RO.o_MMInf, 197
 - summary.o_MMInf, 226
 - Throughput.o_MMInf, 242
 - VN.o_MMInf, 276
 - VNq.o_MMInf, 287
 - VT.o_MMInf, 295
 - VTq.o_MMInf, 305
 - W.o_MMInf, 320
 - Wq.o_MMInf, 348
 - Wqq.o_MMInf, 359
- *Topic **M/M/c/K/K**
 - CheckInput.i_MMCKK, 23
 - Inputs.o_MMCKK, 43
 - L.o_MMCKK, 61
 - Lq.o_MMCKK, 89
 - Lqq.o_MMCKK, 100
 - NewInput.MMCKK, 117
 - Pn.o_MMCKK, 132
 - print.summary.o_MMCKK, 148
 - QueueingModel.i_MMCKK, 166
 - Report.o_MMCKK, 183
 - RO.o_MMCKK, 195
 - summary.o_MMCKK, 224
 - Throughput.o_MMCKK, 240
 - VN.o_MMCKK, 274
 - VNq.o_MMCKK, 285
 - VTq.o_MMCKK, 304
 - W.o_MMCKK, 318
 - Wq.o_MMCKK, 346
 - Wqq.o_MMCKK, 357
- *Topic **M/M/c/K/m**
 - CheckInput.i_MMCKM, 24
 - Inputs.o_MMCKM, 44
 - L.o_MMCKM, 62

- Lq.o_MMCKM, [90](#)
- Lqq.o_MMCKM, [101](#)
- NewInput.MMCKM, [118](#)
- Pn.o_MMCKM, [133](#)
- print.summary.o_MMCKM, [149](#)
- QueueingModel.i_MMCKM, [167](#)
- Report.o_MMCKM, [184](#)
- RO.o_MMCKM, [196](#)
- summary.o_MMCKM, [225](#)
- Throughput.o_MMCKM, [241](#)
- VN.o_MMCKM, [275](#)
- VNq.o_MMCKM, [286](#)
- W.o_MMCKM, [319](#)
- Wq.o_MMCKM, [347](#)
- Wqq.o_MMCKM, [358](#)
- *Topic M/M/c/K**
- CheckInput.i_MMCK, [22](#)
- Inputs.o_MMCK, [42](#)
- L.o_MMCK, [60](#)
- Lq.o_MMCK, [88](#)
- Lqq.o_MMCK, [99](#)
- NewInput.MMCK, [116](#)
- Pn.o_MMCK, [131](#)
- print.summary.o_MMCK, [147](#)
- QueueingModel.i_MMCK, [165](#)
- Report.o_MMCK, [182](#)
- RO.o_MMCK, [194](#)
- summary.o_MMCK, [223](#)
- Throughput.o_MMCK, [239](#)
- VN.o_MMCK, [273](#)
- VNq.o_MMCK, [284](#)
- VTq.o_MMCK, [303](#)
- W.o_MMCK, [317](#)
- Wq.o_MMCK, [345](#)
- Wqq.o_MMCK, [356](#)
- *Topic M/M/c**
- CheckInput.i_MMCC, [21](#)
- Inputs.o_MMCC, [41](#)
- L.o_MMCC, [59](#)
- Lq.o_MMCC, [87](#)
- Lqq.o_MMCC, [98](#)
- NewInput.MMCC, [115](#)
- Pn.o_MMCC, [130](#)
- print.summary.o_MMCC, [146](#)
- QueueingModel.i_MMCC, [164](#)
- Report.o_MMCC, [181](#)
- RO.o_MMCC, [193](#)
- summary.o_MMCC, [222](#)
- Throughput.o_MMCC, [238](#)
- VN.o_MMCC, [272](#)
- VNq.o_MMCC, [283](#)
- VT.o_MMCC, [294](#)
- VTq.o_MMCC, [302](#)
- W.o_MMCC, [316](#)
- Wq.o_MMCC, [344](#)
- Wqq.o_MMCC, [355](#)
- *Topic M/M/c**
- CheckInput.i_MMC, [20](#)
- Inputs.o_MMC, [40](#)
- L.o_MMC, [58](#)
- Lq.o_MMC, [86](#)
- Lqq.o_MMC, [97](#)
- NewInput.MMC, [114](#)
- Pn.o_MMC, [129](#)
- print.summary.o_MMC, [145](#)
- QueueingModel.i_MMC, [163](#)
- Report.o_MMC, [180](#)
- RO.o_MMC, [192](#)
- summary.o_MMC, [221](#)
- Throughput.o_MMC, [237](#)
- VN.o_MMC, [271](#)
- VNq.o_MMC, [282](#)
- VT.o_MMC, [293](#)
- VTq.o_MMC, [301](#)
- W.o_MMC, [315](#)
- Wq.o_MMC, [343](#)
- Wqq.o_MMC, [354](#)
- *Topic MultiClass Closed Network**
- CheckInput.i_MCCN, [14](#)
- Inputs.o_MCCN, [34](#)
- L.o_MCCN, [51](#)
- Lc.o_MCCN, [67](#)
- Lck.o_MCCN, [72](#)
- Lk.o_MCCN, [78](#)
- NewInput.MCCN, [107](#)
- print.summary.o_MCCN, [139](#)
- QueueingModel.i_MCCN, [156](#)
- Report.o_MCCN, [174](#)
- ROck.o_MCCN, [200](#)
- ROk.o_MCCN, [206](#)
- summary.o_MCCN, [214](#)
- Throughput.o_MCCN, [231](#)
- Throughputc.o_MCCN, [246](#)
- Throughputck.o_MCCN, [251](#)
- Throughputcn, [255](#)
- Throughputcn.o_MCCN, [256](#)

- Throughputk.o_MCCN, 259
- W.o_MCCN, 309
- Wc.o_MCCN, 324
- Wck.o_MCCN, 329
- Wk.o_MCCN, 335
- *Topic **MultiClass Mixed Network**
 - CheckInput.i_MCMN, 15
 - Inputs.o_MCMN, 35
 - L.o_MCMN, 52
 - Lc.o_MCMN, 68
 - Lck.o_MCMN, 73
 - Lk.o_MCMN, 79
 - NewInput.MCMN, 108
 - print.summary.o_MCMN, 140
 - QueueingModel.i_MCMN, 157
 - Report.o_MCMN, 175
 - ROck.o_MCMN, 201
 - ROk.o_MCMN, 207
 - summary.o_MCMN, 215
 - Throughput.o_MCMN, 232
 - Throughputc.o_MCMN, 247
 - Throughputck.o_MCMN, 252
 - Throughputk.o_MCMN, 261
 - W.o_MCMN, 310
 - Wc.o_MCMN, 325
 - Wck.o_MCMN, 330
 - Wk.o_MCMN, 336
- *Topic **MultiClass Open Network**
 - CheckInput.i_MCON, 16
 - Inputs.o_MCON, 36
 - L.o_MCON, 54
 - Lc.o_MCON, 69
 - Lck.o_MCON, 74
 - Lk.o_MCON, 80
 - NewInput.MCON, 110
 - print.summary.o_MCON, 141
 - QueueingModel.i_MCON, 159
 - Report.o_MCON, 176
 - ROck.o_MCON, 202
 - ROk.o_MCON, 208
 - summary.o_MCON, 217
 - Throughput.o_MCON, 233
 - Throughputc.o_MCON, 249
 - Throughputck.o_MCON, 253
 - Throughputk.o_MCON, 262
 - W.o_MCON, 311
 - Wc.o_MCON, 326
 - Wck.o_MCON, 331
 - Wk.o_MCON, 337
- *Topic **MultiClass Queueing Models**
 - Lck, 70
- *Topic **MultiClass Queueing Networks**
 - ROck, 199
- *Topic **MultiClass Queueing Network**
 - Lc, 66
 - Throughputc, 245
 - Throughputck, 250
 - Wc, 323
 - Wck, 328
- *Topic **Open Jackson Network**
 - CheckInput.i_OJN, 27
 - Inputs.o_OJN, 47
 - L.o_OJN, 65
 - Lk.o_OJN, 81
 - NewInput.OJN, 121
 - Pn.o_OJN, 136
 - print.summary.o_OJN, 152
 - QueueingModel.i_OJN, 170
 - Report.o_OJN, 187
 - ROk.o_OJN, 209
 - summary.o_OJN, 228
 - Throughput.o_OJN, 244
 - Throughputk.o_OJN, 263
 - W.o_OJN, 322
 - Wk.o_OJN, 338
- *Topic **Queueing Models**
 - CheckInput, 11
 - Inputs, 30
 - L, 48
 - Lk, 75
 - Pn, 123
 - QueueingModel, 153
 - RO, 188
 - Throughput, 229
 - VN, 267
 - VT, 289
 - W, 307
- *Topic **Queueing Networks**
 - ROk, 203
- *Topic **Queueing Network**
 - Throughputk, 257
 - Throughputn, 264
 - Wk, 332
- *Topic **queueing**
 - queueing-package, 9

- B_erlang, [10, 29, 30](#)
- C_erlang, [11, 29](#)
- CheckInput, [11](#)
- CheckInput.i_BnD, [12, 104, 154, 155](#)
- CheckInput.i_CJN, [13, 155, 156, 231, 259, 266](#)
- CheckInput.i_MCCN, [14, 157, 232, 247, 252, 256, 260](#)
- CheckInput.i_MCMN, [15, 158, 233, 248, 253, 261](#)
- CheckInput.i_MCON, [16, 159, 234, 249, 254, 262](#)
- CheckInput.i_MM1, [12, 17, 111, 160, 235](#)
- CheckInput.i_MM1K, [12, 18, 112, 161, 236](#)
- CheckInput.i_MM1KK, [12, 19, 113, 162, 237](#)
- CheckInput.i_MMC, [12, 20, 114, 163, 238](#)
- CheckInput.i_MMCC, [12, 21, 115, 164, 239](#)
- CheckInput.i_MMCK, [12, 22, 116, 165, 240](#)
- CheckInput.i_MMCKK, [12, 23, 117, 166, 241](#)
- CheckInput.i_MMCKM, [12, 24, 118, 167, 242](#)
- CheckInput.i_MMInf, [12, 25, 119, 168, 242](#)
- CheckInput.i_MMInfKK, [12, 26, 120, 169, 243](#)
- CheckInput.i_OJN, [12, 27, 170, 244, 264](#)
- CompareQueueingModels, [28](#)
- CompareQueueingModels2
(CompareQueueingModels), [28](#)
- Engset, [30](#)
- Inputs, [30](#)
- Inputs.o_BnD, [31](#)
- Inputs.o_CJN, [31, 32](#)
- Inputs.o_MCCN, [31, 34](#)
- Inputs.o_MCMN, [31, 35](#)
- Inputs.o_MCON, [31, 36](#)
- Inputs.o_MM1, [31, 37](#)
- Inputs.o_MM1K, [31, 38](#)
- Inputs.o_MM1KK, [31, 39](#)
- Inputs.o_MMC, [31, 40](#)
- Inputs.o_MMCC, [31, 41](#)
- Inputs.o_MMCK, [31, 42](#)
- Inputs.o_MMCKK, [31, 43](#)
- Inputs.o_MMCKM, [31, 44](#)
- Inputs.o_MMInf, [31, 45](#)
- Inputs.o_MMInfKK, [31, 46](#)
- Inputs.o_OJN, [31, 47](#)
- L, [48](#)
- L.o_BnD, [49](#)
- L.o_CJN, [49, 50](#)
- L.o_MCCN, [49, 51](#)
- L.o_MCMN, [49, 52](#)
- L.o_MCON, [49, 54](#)
- L.o_MM1, [49, 55](#)
- L.o_MM1K, [49, 56](#)
- L.o_MM1KK, [49, 57](#)
- L.o_MMC, [49, 58](#)
- L.o_MMCC, [49, 59](#)
- L.o_MMCK, [49, 60](#)
- L.o_MMCKK, [49, 61](#)
- L.o_MMCKM, [49, 62](#)
- L.o_MMInf, [49, 63, 197](#)
- L.o_MMInfKK, [49, 64](#)
- L.o_OJN, [49, 65](#)
- Lc, [66](#)
- Lc.o_MCCN, [66, 67](#)
- Lc.o_MCMN, [66, 68](#)
- Lc.o_MCON, [66, 69](#)
- Lck, [70](#)
- Lck.o_MCCN, [71, 72](#)
- Lck.o_MCMN, [71, 73](#)
- Lck.o_MCON, [71, 74](#)
- Lk, [75](#)
- Lk.o_CJN, [76, 76](#)
- Lk.o_MCCN, [76, 78](#)
- Lk.o_MCMN, [76, 79](#)
- Lk.o_MCON, [76, 80](#)
- Lk.o_OJN, [76, 81](#)
- Lq, [82](#)
- Lq.o_MM1, [83, 83](#)
- Lq.o_MM1K, [83, 84](#)
- Lq.o_MM1KK, [83, 85](#)
- Lq.o_MMC, [83, 86](#)
- Lq.o_MMCC, [83, 87](#)
- Lq.o_MMCK, [83, 88](#)
- Lq.o_MMCKK, [83, 89](#)
- Lq.o_MMCKM, [83, 90](#)
- Lq.o_MMInf, [83, 91](#)
- Lq.o_MMInfKK, [83, 92](#)
- Lqq, [93](#)
- Lqq.o_MM1, [93, 94](#)
- Lqq.o_MM1K, [93, 95](#)
- Lqq.o_MM1KK, [93, 96](#)
- Lqq.o_MMC, [93, 97](#)
- Lqq.o_MMCC, [93, 98](#)
- Lqq.o_MMCK, [93, 99](#)

- Lqq.o_MMCKK, 93, 100
- Lqq.o_MMCKM, 94, 101
- Lqq.o_MMInf, 94, 102
- Lqq.o_MMInfKK, 94, 103

- NewInput.BnD, 12, 13, 32, 104
- NewInput.CJN, 13, 14, 33, 105, 259, 266
- NewInput.MCCN, 15, 34, 107, 232, 247, 252, 256, 260
- NewInput.MCMN, 16, 35, 108, 233, 248, 253, 261
- NewInput.MCON, 17, 36, 110, 234, 249, 254, 262
- NewInput.MM1, 18, 37, 38, 111, 235
- NewInput.MM1K, 18, 19, 38, 112, 236
- NewInput.MM1KK, 19, 20, 39, 113, 237
- NewInput.MMC, 20, 40, 114, 238
- NewInput.MMCC, 21, 41, 115, 239
- NewInput.MMCK, 22, 42, 116, 240
- NewInput.MMCKK, 23, 43, 117, 241
- NewInput.MMCKM, 24, 44, 118, 242
- NewInput.MMInf, 25, 45, 119, 242
- NewInput.MMInfKK, 26, 46, 120, 243
- NewInput.OJN, 27, 47, 121, 231, 244, 264
- NewInput2.CJN (NewInput.CJN), 105
- NewInput2.OJN (NewInput.OJN), 121
- NewInput3.CJN (NewInput.CJN), 105
- NewInput3.OJN (NewInput.OJN), 121

- Pn, 123
- Pn.o_BnD, 124, 124
- Pn.o_MM1, 123, 125
- Pn.o_MM1K, 123, 127
- Pn.o_MM1KK, 123, 128
- Pn.o_MMC, 123, 129
- Pn.o_MMCC, 124, 130
- Pn.o_MMCK, 123, 131
- Pn.o_MMCKK, 123, 132
- Pn.o_MMCKM, 124, 133
- Pn.o_MMInf, 124, 134
- Pn.o_MMInfKK, 124, 135
- Pn.o_OJN, 124, 136
- print.summary.o_BnD, 137
- print.summary.o_CJN, 138
- print.summary.o_MCCN, 139
- print.summary.o_MCMN, 140
- print.summary.o_MCON, 141
- print.summary.o_MM1, 142
- print.summary.o_MM1K, 143
- print.summary.o_MM1KK, 144
- print.summary.o_MMC, 145
- print.summary.o_MMCC, 146
- print.summary.o_MMCK, 147
- print.summary.o_MMCKK, 148
- print.summary.o_MMCKM, 149
- print.summary.o_MMInf, 150
- print.summary.o_MMInfKK, 151
- print.summary.o_OJN, 152

- Qn (Pn), 123
- Qn.o_BnD (Pn.o_BnD), 124
- Qn.o_MM1, 123
- Qn.o_MM1 (Pn.o_MM1), 125
- Qn.o_MM1K, 123
- Qn.o_MM1K (Pn.o_MM1K), 127
- Qn.o_MM1KK, 123
- Qn.o_MM1KK (Pn.o_MM1KK), 128
- Qn.o_MMC, 123
- Qn.o_MMC (Pn.o_MMC), 129
- Qn.o_MMCC, 124
- Qn.o_MMCC (Pn.o_MMCC), 130
- Qn.o_MMCK, 123
- Qn.o_MMCK (Pn.o_MMCK), 131
- Qn.o_MMCKK, 123
- Qn.o_MMCKK (Pn.o_MMCKK), 132
- Qn.o_MMCKM, 124
- Qn.o_MMCKM (Pn.o_MMCKM), 133
- Qn.o_MMInf, 124
- Qn.o_MMInf (Pn.o_MMInf), 134
- Qn.o_MMInfKK, 124
- Qn.o_MMInfKK (Pn.o_MMInfKK), 135
- queueing (queueing-package), 9
- queueing-package, 9
- QueueingModel, 28, 153, 171
- QueueingModel.i_BnD, 50, 125, 138, 154, 172, 213
- QueueingModel.i_CJN, 51, 77, 106, 138, 155, 173, 205, 214, 231, 259, 266, 308, 334
- QueueingModel.i_MCCN, 52, 68, 72, 78, 108, 140, 156, 174, 201, 206, 215, 232, 247, 252, 256, 260, 310, 325, 329, 335
- QueueingModel.i_MCMN, 53, 69, 73, 79, 109, 141, 157, 175, 202, 208, 216, 233, 248, 253, 261, 311, 326, 331, 336
- QueueingModel.i_MCON, 54, 70, 75, 81, 110, 142, 154, 159, 177, 203, 209, 217,

- [234, 249, 254, 262, 312, 327, 332, 337](#)
[QueueingModel.i_MM1, 55, 84, 94, 126, 143, 154, 160, 178, 190, 218, 235, 268, 279, 290, 298, 313, 341, 351](#)
[QueueingModel.i_MM1K, 56, 57, 85, 95, 127, 144, 154, 161, 178, 191, 219, 236, 269, 270, 280, 291, 299, 314, 342, 352](#)
[QueueingModel.i_MM1KK, 86, 96, 128, 145, 154, 162, 179, 191, 212, 220, 237, 281, 292, 300, 315, 342, 353, 362](#)
[QueueingModel.i_MMC, 58, 87, 97, 129, 146, 154, 163, 180, 192, 221, 238, 271, 282, 293, 301, 316, 343, 354](#)
[QueueingModel.i_MMCC, 59, 88, 98, 130, 146, 154, 164, 181, 193, 222, 239, 272, 283, 294, 302, 316, 344, 355](#)
[QueueingModel.i_MMCK, 60, 89, 99, 131, 147, 154, 165, 182, 194, 223, 240, 273, 284, 303, 317, 345, 356](#)
[QueueingModel.i_MMCKK, 61, 90, 100, 132, 148, 154, 166, 183, 195, 224, 241, 274, 285, 304, 318, 346, 357](#)
[QueueingModel.i_MMCKM, 62, 91, 101, 133, 149, 154, 167, 184, 196, 225, 242, 275, 286, 319, 347, 358](#)
[QueueingModel.i_MMInf, 63, 91, 102, 134, 150, 154, 168, 185, 197, 226, 242, 276, 287, 295, 305, 320, 348, 359](#)
[QueueingModel.i_MMInfFKK, 64, 92, 103, 135, 151, 154, 169, 186, 198, 227, 243, 277, 288, 296, 306, 321, 349, 360](#)
[QueueingModel.i_OJN, 65, 82, 122, 136, 152, 154, 170, 187, 210, 228, 244, 264, 322, 339](#)
[Report, 171](#)
[Report.o_BnD, 172](#)
[Report.o_CJN, 173](#)
[Report.o_MCCN, 174](#)
[Report.o_MCMN, 175](#)
[Report.o_MCON, 176](#)
[Report.o_MM1, 177](#)
[Report.o_MM1K, 178](#)
[Report.o_MM1KK, 179](#)
[Report.o_MMC, 180](#)
[Report.o_MMCC, 181](#)
[Report.o_MMCK, 182](#)
[Report.o_MMCKK, 183](#)
[Report.o_MMCKM, 184](#)
[Report.o_MMInf, 185](#)
[Report.o_MMInfFKK, 186](#)
[Report.o_OJN, 187](#)
[RO, 188](#)
[RO.o_MM1, 189, 189](#)
[RO.o_MM1K, 189, 190](#)
[RO.o_MM1KK, 189, 191](#)
[RO.o_MMC, 189, 192](#)
[RO.o_MMCC, 189, 193](#)
[RO.o_MMCK, 189, 194](#)
[RO.o_MMCKK, 189, 195](#)
[RO.o_MMCKM, 189, 196](#)
[RO.o_MMInf, 189, 197](#)
[RO.o_MMInfFKK, 189, 198](#)
[ROck, 199](#)
[ROck.o_MCCN, 200, 200](#)
[ROck.o_MCMN, 200, 201](#)
[ROck.o_MCON, 200, 202](#)
[ROk, 203](#)
[ROk.o_CJN, 204, 205](#)
[ROk.o_MCCN, 204, 206](#)
[ROk.o_MCMN, 204, 207](#)
[ROk.o_MCON, 204, 208](#)
[ROk.o_OJN, 204, 209](#)
[SP, 210](#)
[SP.o_MM1KK, 211, 211](#)
[summary.o_BnD, 212](#)
[summary.o_CJN, 213](#)
[summary.o_MCCN, 214](#)
[summary.o_MCMN, 215](#)
[summary.o_MCON, 217](#)
[summary.o_MM1, 218](#)
[summary.o_MM1K, 219](#)
[summary.o_MM1KK, 220](#)
[summary.o_MMC, 221](#)
[summary.o_MMCC, 222](#)
[summary.o_MMCK, 223](#)
[summary.o_MMCKK, 224](#)
[summary.o_MMCKM, 225](#)
[summary.o_MMInf, 226](#)
[summary.o_MMInfFKK, 227](#)
[summary.o_OJN, 228](#)
[Throughput, 229](#)
[Throughput.o_CJN, 230, 230](#)
[Throughput.o_MCCN, 230, 231](#)

- Throughput.o_MCMN, [230](#), [232](#)
 Throughput.o_MCON, [230](#), [233](#)
 Throughput.o_MM1, [229](#), [234](#)
 Throughput.o_MM1K, [229](#), [235](#)
 Throughput.o_MM1KK, [229](#), [236](#)
 Throughput.o_MMC, [229](#), [237](#)
 Throughput.o_MMCC, [229](#), [238](#)
 Throughput.o_MMCK, [229](#), [239](#)
 Throughput.o_MMCKK, [229](#), [240](#)
 Throughput.o_MMCKM, [229](#), [241](#)
 Throughput.o_MMInf, [230](#), [242](#)
 Throughput.o_MMInfKK, [229](#), [243](#)
 Throughput.o_OJN, [230](#), [244](#)
 Throughputc, [245](#)
 Throughputc.o_MCCN, [246](#), [246](#)
 Throughputc.o_MCMN, [247](#)
 Throughputc.o_MCON, [246](#), [249](#)
 Throughputck, [250](#)
 Throughputck.o_MCCN, [250](#), [251](#)
 Throughputck.o_MCMN, [250](#), [252](#)
 Throughputck.o_MCON, [250](#), [253](#)
 Throughputcn, [255](#)
 Throughputcn.o_MCCN, [255](#), [256](#)
 Throughputk, [257](#)
 Throughputk.o_CJN, [258](#), [258](#)
 Throughputk.o_MCCN, [258](#), [259](#)
 Throughputk.o_MCMN, [258](#), [261](#)
 Throughputk.o_MCON, [258](#), [262](#)
 Throughputk.o_OJN, [258](#), [263](#)
 Throughputn, [264](#)
 Throughputn.o_CJN, [265](#), [265](#)
- VN, [267](#)
 VN.o_MM1, [267](#), [268](#)
 VN.o_MM1K, [267](#), [269](#)
 VN.o_MM1KK, [267](#), [270](#)
 VN.o_MMC, [267](#), [271](#)
 VN.o_MMCC, [267](#), [272](#)
 VN.o_MMCK, [267](#), [273](#)
 VN.o_MMCKK, [267](#), [274](#)
 VN.o_MMCKM, [267](#), [275](#)
 VN.o_MMInf, [267](#), [276](#)
 VN.o_MMInfKK, [267](#), [277](#)
 VNq, [278](#)
 VNq.o_MM1, [278](#), [279](#)
 VNq.o_MM1K, [278](#), [280](#)
 VNq.o_MM1KK, [278](#), [281](#)
 VNq.o_MMC, [282](#)
 VNq.o_MMCC, [278](#), [283](#)
- VNq.o_MMCK, [278](#), [284](#)
 VNq.o_MMCKK, [278](#), [285](#)
 VNq.o_MMCKM, [278](#), [286](#)
 VNq.o_MMInf, [278](#), [287](#)
 VNq.o_MMInfKK, [278](#), [288](#)
 VT, [289](#)
 VT.o_MM1, [289](#), [290](#)
 VT.o_MM1K, [289](#), [291](#)
 VT.o_MM1KK, [289](#), [292](#)
 VT.o_MMC, [289](#), [293](#)
 VT.o_MMCC, [289](#), [294](#)
 VT.o_MMInf, [289](#), [295](#)
 VT.o_MMInfKK, [289](#), [296](#)
 VTq, [297](#)
 VTq.o_MM1, [297](#), [298](#)
 VTq.o_MM1K, [297](#), [299](#)
 VTq.o_MM1KK, [297](#), [300](#)
 VTq.o_MMC, [297](#), [301](#)
 VTq.o_MMCC, [297](#), [302](#)
 VTq.o_MMCK, [297](#), [303](#)
 VTq.o_MMCKK, [297](#), [304](#)
 VTq.o_MMInf, [297](#), [305](#)
 VTq.o_MMInfKK, [297](#), [306](#)
- W, [307](#)
 W.o_CJN, [308](#)
 W.o_MCCN, [307](#), [309](#)
 W.o_MCMN, [307](#), [310](#)
 W.o_MCON, [307](#), [311](#)
 W.o_MM1, [307](#), [312](#)
 W.o_MM1K, [307](#), [313](#)
 W.o_MM1KK, [307](#), [314](#)
 W.o_MMC, [307](#), [315](#)
 W.o_MMCC, [307](#), [316](#)
 W.o_MMCK, [307](#), [317](#)
 W.o_MMCKK, [307](#), [318](#)
 W.o_MMCKM, [307](#), [319](#)
 W.o_MMInf, [307](#), [320](#)
 W.o_MMInfKK, [307](#), [321](#)
 W.o_OJN, [307](#), [322](#)
 Wc, [323](#)
 Wc.o_MCCN, [324](#), [324](#)
 Wc.o_MCMN, [324](#), [325](#)
 Wc.o_MCON, [324](#), [326](#)
 Wck, [328](#)
 Wck.o_MCCN, [328](#), [329](#)
 Wck.o_MCMN, [328](#), [330](#)
 Wck.o_MCON, [328](#), [331](#)
 Wk, [332](#)

Wk.o_CJN, 333, 333
Wk.o_MCCN, 333, 335
Wk.o_MCMN, 333, 336
Wk.o_MCON, 333, 337
Wk.o_OJN, 333, 338
Wq, 339
Wq.o_MM1, 340, 340
Wq.o_MM1K, 340, 341
Wq.o_MM1KK, 340, 342
Wq.o_MMC, 340, 343
Wq.o_MMCC, 340, 344
Wq.o_MMCK, 340, 345
Wq.o_MMCKK, 340, 346
Wq.o_MMCKM, 340, 347
Wq.o_MMInf, 340, 348
Wq.o_MMInfKK, 340, 349
Wqq, 350
Wqq.o_MM1, 350, 351
Wqq.o_MM1K, 350, 352
Wqq.o_MM1KK, 350, 353
Wqq.o_MMC, 350, 354
Wqq.o_MMCC, 350, 355
Wqq.o_MMCK, 350, 356
Wqq.o_MMCKK, 350, 357
Wqq.o_MMCKM, 351, 358
Wqq.o_MMInf, 351, 359
Wqq.o_MMInfKK, 351, 360
Wws, 361
Wws.o_MM1KK, 361, 362