

# Package ‘ranger’

March 31, 2017

**Type** Package

**Title** A Fast Implementation of Random Forests

**Version** 0.7.0

**Date** 2017-03-23

**Author** Marvin N. Wright

**Maintainer** Marvin N. Wright <[wright@imbs.uni-luebeck.de](mailto:wright@imbs.uni-luebeck.de)>

**Description** A fast implementation of Random Forests, particularly suited for high dimensional data. Ensembles of classification, regression, survival and probability prediction trees are supported. Data from genome-wide association studies can be analyzed efficiently. In addition to data frames, datasets of class 'gwa.data' (R package 'GenABEL') can be directly analyzed.

**License** GPL-3

**Imports** Rcpp (>= 0.11.2)

**LinkingTo** Rcpp

**Depends** R (>= 3.1)

**Suggests** survival, testthat, GenABEL

**RoxygenNote** 5.0.1

**URL** <https://github.com/imbs-hl/ranger>

**BugReports** <https://github.com/imbs-hl/ranger/issues>

**NeedsCompilation** yes

**Repository** CRAN

**Date/Publication** 2017-03-31 16:19:06 UTC

## R topics documented:

csrf . . . . .	2
getTerminalNodeIDs . . . . .	3
holdoutRF . . . . .	4
importance.ranger . . . . .	5

importance_pvalues . . . . .	5
parse.formula . . . . .	6
predict.ranger . . . . .	7
predict.ranger.forest . . . . .	8
predictions.ranger . . . . .	9
predictions.ranger.prediction . . . . .	10
print.ranger . . . . .	11
print.ranger.forest . . . . .	11
print.ranger.prediction . . . . .	12
ranger . . . . .	12
timepoints.ranger . . . . .	17
timepoints.ranger.prediction . . . . .	18

## Index 19

---

csrf	<i>Case-specific random forests.</i>
------	--------------------------------------

---

### Description

In case-specific random forests (CSRF), random forests are built specific to the cases of interest. Instead of using equal probabilities, the cases are weighted according to their difference to the case of interest.

### Usage

```
csrf(formula, training_data, test_data, params1 = list(), params2 = list())
```

### Arguments

formula	Object of class formula or character describing the model to fit.
training_data	Training data of class data.frame.
test_data	Test data of class data.frame.
params1	Parameters for the proximity random forest grown in the first step.
params2	Parameters for the prediction random forests grown in the second step.

### Details

The algorithm consists of 3 steps:

1. Grow a random forest on the training data
2. For each observation of interest (test data), the weights of all training observations are computed by counting the number of trees in which both observations are in the same terminal node.
3. For each test observation, grow a weighted random forest on the training data, using the weights obtained in step 2. Predict the outcome of the test observation as usual.

In total,  $n+1$  random forests are grown, where  $n$  is the number observations in the test dataset. For details, see Xu et al. (2014).

**Value**

Predictions for the test dataset.

**Author(s)**

Marvin N. Wright

**References**

Xu, R., Nettleton, D. & Nordman, D.J. (2014). Case-specific random forests. *J Comp Graph Stat* 25:49-65. <http://dx.doi.org/10.1080/10618600.2014.983641>.

**Examples**

```
## Split in training and test data
train.idx <- sample(nrow(iris), 2/3 * nrow(iris))
iris.train <- iris[train.idx, ]
iris.test <- iris[-train.idx, ]

## Run case-specific RF
csrf(Species ~ ., training_data = iris.train, test_data = iris.test,
      params1 = list(num.trees = 50, mtry = 4),
      params2 = list(num.trees = 5))
```

---

getTerminalNodeIDs      *Get terminal node IDs (deprecated)*

---

**Description**

This function is deprecated. Please use `predict()` with `type = "terminalNodes"` instead. This function calls `predict()` now.

**Usage**

```
getTerminalNodeIDs(rf, dat)
```

**Arguments**

`rf`                    ranger object.  
`dat`                    New dataset. Terminal node IDs for this dataset are obtained.

**Value**

Matrix with terminal nodeIDs for all observations in dataset and trees.

## Examples

```
library(ranger)
rf <- ranger(Species ~ ., data = iris, num.trees = 5, write.forest = TRUE)
getTerminalNodeIDs(rf, iris)
```

---

holdoutRF

*Hold-out random forests*

---

## Description

Grow two random forests on two cross-validation folds. Instead of out-of-bag data, the other fold is used to compute permutation importance. Related to the novel permutation variable importance by Janitza et al. (2015).

## Usage

```
holdoutRF(...)
```

## Arguments

... All arguments are passed to `ranger()` (except importance, case.weights, replace and holdout.).

## Value

Hold-out random forests with variable importance.

## Author(s)

Marvin N. Wright

## References

Janitza, S., Celik, E. & Boulesteix, A.-L., (2015). A computationally fast variable importance test for random forests for high-dimensional data. *Adv Data Anal Classif* <http://dx.doi.org/10.1007/s11634-016-0276-4>.

## See Also

[ranger](#)

---

importance.ranger      *ranger variable importance*

---

### Description

Extract variable importance of ranger object.

### Usage

```
## S3 method for class 'ranger'  
importance(x, ...)
```

### Arguments

x                      ranger object.  
...                    Further arguments passed to or from other methods.

### Value

Variable importance measures.

### Author(s)

Marvin N. Wright

### See Also

[ranger](#)

---

importance\_pvalues      *ranger variable importance p-values*

---

### Description

Compute variable importance with p-values.

### Usage

```
importance_pvalues(x, method = c("janitza", "altmann"),  
  num.permutations = 100, formula = NULL, data = NULL, ...)
```

**Arguments**

x	ranger or holdoutRF object.
method	Method to compute p-values. Use "janitza" for the method by Janitza et al. (2015) or "altmann" for the non-parametric method by Altmann et al. (2010).
num.permutations	Number of permutations. Used in the "altmann" method only.
formula	Object of class formula or character describing the model to fit. Used in the "altmann" method only.
data	Training data of class data.frame or matrix. Used in the "altmann" method only.
...	Further arguments passed to ranger(). Used in the "altmann" method only.

**Value**

Variable importance and p-values.

**Author(s)**

Marvin N. Wright

**References**

- Janitza, S., Celik, E. & Boulesteix, A.-L., (2015). A computationally fast variable importance test for random forests for high-dimensional data. *Adv Data Anal Classif* <http://dx.doi.org/10.1007/s11634-016-0276-4>.
- Altmann, A., Tolosi, L., Sander, O. & Lengauer, T. (2010). Permutation importance: a corrected feature importance measure, *Bioinformatics* 26(10):1340-1347.

**See Also**

[ranger](#)

---

parse.formula

*Parse formula*

---

**Description**

Parse formula and return dataset containing selected columns. Interactions are supported for numerical columns only. An interaction column is the product of all interacting columns.

**Usage**

```
parse.formula(formula, data)
```

**Arguments**

formula	Object of class formula or character describing the model to fit.
data	Training data of class data.frame.

**Value**

Dataset including selected columns and interactions.

---

predict.ranger	<i>Ranger prediction</i>
----------------	--------------------------

---

**Description**

Prediction with new data and a saved forest from Ranger.

**Usage**

```
## S3 method for class 'ranger'
predict(object, data, predict.all = FALSE,
        num.trees = object$num.trees, type = "response", seed = NULL,
        num.threads = NULL, verbose = TRUE, ...)
```

**Arguments**

object	Ranger ranger object.
data	New test data of class data.frame or gwaab.data (GenABEL).
predict.all	Return individual predictions for each tree instead of aggregated predictions for all trees. Return a matrix (sample x tree) for classification and regression, a 3d array for probability estimation (sample x class x tree) and survival (sample x time x tree).
num.trees	Number of trees used for prediction. The first num.trees in the forest are used.
type	Type of prediction. One of 'response' or 'terminalNodes' with default 'response'. See below for details.
seed	Random seed used in Ranger.
num.threads	Number of threads. Default is number of CPUs available.
verbose	Verbose output on or off.
...	further arguments passed to or from other methods.

**Details**

For type = 'response' (the default), the predicted classes (classification), predicted numeric values (regression), predicted probabilities (probability estimation) or survival probabilities (survival) are returned. For type = 'terminalNodes', the IDs of the terminal node in each tree for each observation in the given dataset are returned.

For classification and predict.all = TRUE, a factor levels are returned as numerics. To retrieve the corresponding factor levels, use rf\$forest\$levels, if rf is the ranger object.

**Value**

Object of class ranger.prediction with elements

predictions	Predicted classes/values (only for classification and regression)
unique.death.times	Unique death times (only for survival).
chf	Estimated cumulative hazard function for each sample (only for survival).
survival	Estimated survival function for each sample (only for survival).
num.trees	Number of trees.
num.independent.variables	Number of independent variables.
treetype	Type of forest/tree. Classification, regression or survival.
num.samples	Number of samples.

**Author(s)**

Marvin N. Wright

**See Also**

[ranger](#)

---

`predict.ranger.forest` *Ranger prediction*

---

**Description**

Prediction with new data and a saved forest from Ranger.

**Usage**

```
## S3 method for class 'ranger.forest'
predict(object, data, predict.all = FALSE,
        num.trees = object$num.trees, type = "response", seed = NULL,
        num.threads = NULL, verbose = TRUE, ...)
```

**Arguments**

object	Ranger <code>ranger.forest</code> object.
data	New test data of class <code>data.frame</code> or <code>gwaa.data</code> (GenABEL).
predict.all	Return individual predictions for each tree instead of aggregated predictions for all trees. Return a matrix (sample x tree) for classification and regression, a 3d array for probability estimation (sample x class x tree) and survival (sample x time x tree).
num.trees	Number of trees used for prediction. The first <code>num.trees</code> in the forest are used.
type	Type of prediction. One of 'response' or 'terminalNodes' with default 'response'. See below for details.
seed	Random seed used in Ranger.
num.threads	Number of threads. Default is number of CPUs available.
verbose	Verbose output on or off.
...	further arguments passed to or from other methods.



**Details**

For type = 'response' (the default), the predicted classes (classification), predicted numeric values (regression), predicted probabilities (probability estimation) or survival probabilities (survival) are returned. For type = 'terminalNodes', the IDs of the terminal node in each tree for each observation in the given dataset are returned.

For classification and predict.all = TRUE, a factor levels are returned as numerics. To retrieve the corresponding factor levels, use rf\$forest\$levels, if rf is the ranger object.

**Value**

Object of class ranger.prediction with elements

predictions	Predicted classes/values (only for classification and regression)
unique.death.times	Unique death times (only for survival).
chf	Estimated cumulative hazard function for each sample (only for survival).
survival	Estimated survival function for each sample (only for survival).
num.trees	Number of trees.
num.independent.variables	Number of independent variables.
treetype	Type of forest/tree. Classification, regression or survival.
num.samples	Number of samples.

**Author(s)**

Marvin N. Wright

**See Also**

[ranger](#)

---

predictions.ranger      *Ranger predictions*

---

**Description**

Extract training data predictions of Ranger object.

**Usage**

```
## S3 method for class 'ranger'
predictions(x, ...)
```

**Arguments**

x                      Ranger object.  
 ...                    Further arguments passed to or from other methods.

**Value**

Predictions: Classes for Classification forests, Numerical values for Regressions forests and the estimated survival functions for all individuals for Survival forests.

**Author(s)**

Marvin N. Wright

**See Also**

[ranger](#)

---

`predictions.ranger.prediction`  
*Ranger predictions*

---

**Description**

Extract predictions of Ranger prediction object.

**Usage**

```
## S3 method for class 'ranger.prediction'  
predictions(x, ...)
```

**Arguments**

<code>x</code>	Ranger prediction object.
<code>...</code>	Further arguments passed to or from other methods.

**Value**

Predictions: Classes for Classification forests, Numerical values for Regressions forests and the estimated survival functions for all individuals for Survival forests.

**Author(s)**

Marvin N. Wright

**See Also**

[ranger](#)

---

print.ranger	<i>Print Ranger</i>
--------------	---------------------

---

**Description**

Print contents of Ranger object.

**Usage**

```
## S3 method for class 'ranger'  
print(x, ...)
```

**Arguments**

x	Object of class 'ranger'.
...	Further arguments passed to or from other methods.

**Author(s)**

Marvin N. Wright

**See Also**

[ranger](#)

---

print.ranger.forest	<i>Print Ranger forest</i>
---------------------	----------------------------

---

**Description**

Print contents of Ranger forest object.

**Usage**

```
## S3 method for class 'ranger.forest'  
print(x, ...)
```

**Arguments**

x	Object of class 'ranger.forest'.
...	further arguments passed to or from other methods.

**Author(s)**

Marvin N. Wright

---

```
print.ranger.prediction
      Print Ranger prediction
```

---

**Description**

Print contents of Ranger prediction object.

**Usage**

```
## S3 method for class 'ranger.prediction'
print(x, ...)
```

**Arguments**

x                    Object of class 'ranger.prediction'.  
 ...                further arguments passed to or from other methods.

**Author(s)**

Marvin N. Wright

---

```
ranger                    Ranger
```

---

**Description**

Ranger is a fast implementation of Random Forest (Breiman 2001) or recursive partitioning, particularly suited for high dimensional data. Classification, regression, and survival forests are supported. Classification and regression forests are implemented as in the original Random Forest (Breiman 2001), survival forests as in Random Survival Forests (Ishwaran et al. 2008).

**Usage**

```
ranger(formula = NULL, data = NULL, num.trees = 500, mtry = NULL,
  importance = "none", write.forest = TRUE, probability = FALSE,
  min.node.size = NULL, replace = TRUE, sample.fraction = ifelse(replace,
  1, 0.632), case.weights = NULL, splitrule = NULL, num.random.splits = 1,
  alpha = 0.5, minprop = 0.1, split.select.weights = NULL,
  always.split.variables = NULL, respect.unordered.factors = NULL,
  scale.permutation.importance = FALSE, keep.inbag = FALSE,
  holdout = FALSE, num.threads = NULL, save.memory = FALSE,
  verbose = TRUE, seed = NULL, dependent.variable.name = NULL,
  status.variable.name = NULL, classification = NULL)
```

**Arguments**

<code>formula</code>	Object of class <code>formula</code> or character describing the model to fit. Interaction terms supported only for numerical variables.
<code>data</code>	Training data of class <code>data.frame</code> , <code>matrix</code> or <code>gwaab.data</code> (GenABEL).
<code>num.trees</code>	Number of trees.
<code>mtry</code>	Number of variables to possibly split at in each node. Default is the (rounded down) square root of the number variables.
<code>importance</code>	Variable importance mode, one of 'none', 'impurity', 'permutation'. The 'impurity' measure is the Gini index for classification and the variance of the responses for regression. For survival, only 'permutation' is available.
<code>write.forest</code>	Save <code>ranger.forest</code> object, required for prediction. Set to FALSE to reduce memory usage if no prediction intended.
<code>probability</code>	Grow a probability forest as in Malley et al. (2012).
<code>min.node.size</code>	Minimal node size. Default 1 for classification, 5 for regression, 3 for survival, and 10 for probability.
<code>replace</code>	Sample with replacement.
<code>sample.fraction</code>	Fraction of observations to sample. Default is 1 for sampling with replacement and 0.632 for sampling without replacement.
<code>case.weights</code>	Weights for sampling of training observations. Observations with larger weights will be selected with higher probability in the bootstrap (or subsampled) samples for the trees.
<code>splitrule</code>	Splitting rule. For classification and probability estimation "gini" or "extratrees" with default "gini". For regression "variance", "extratrees" or "maxstat" with default "variance". For survival "logrank", "extratrees", "C" or "maxstat" with default "logrank".
<code>num.random.splits</code>	For "extratrees" <code>splitrule</code> : Number of random splits to consider for each candidate splitting variable.
<code>alpha</code>	For "maxstat" <code>splitrule</code> : Significance threshold to allow splitting.
<code>minprop</code>	For "maxstat" <code>splitrule</code> : Lower quantile of covariate distribution to be considered for splitting.
<code>split.select.weights</code>	Numeric vector with weights between 0 and 1, representing the probability to select variables for splitting. Alternatively, a list of size <code>num.trees</code> , containing split select weight vectors for each tree can be used.
<code>always.split.variables</code>	Character vector with variable names to be always selected in addition to the <code>mtry</code> variables tried for splitting.
<code>respect.unordered.factors</code>	Handling of unordered factor covariates. One of 'ignore', 'order' and 'partition'. For the "extratrees" <code>splitrule</code> the default is "partition" for all other <code>splitrules</code> 'ignore'. Alternatively TRUE (= 'order') or FALSE (= 'ignore') can be used. See below for details.

<code>scale.permutation.importance</code>	Scale permutation importance by standard error as in (Breiman 2001). Only applicable if permutation variable importance mode selected.
<code>keep.inbag</code>	Save how often observations are in-bag in each tree.
<code>holdout</code>	Hold-out mode. Hold-out all samples with case weight 0 and use these for variable importance and prediction error.
<code>num.threads</code>	Number of threads. Default is number of CPUs available.
<code>save.memory</code>	Use memory saving (but slower) splitting mode. No effect for GWAS data. Warning: This option slows down the tree growing, use only if you encounter memory problems.
<code>verbose</code>	Show computation status and estimated runtime.
<code>seed</code>	Random seed. Default is NULL, which generates the seed from R.
<code>dependent.variable.name</code>	Name of dependent variable, needed if no formula given. For survival forests this is the time variable.
<code>status.variable.name</code>	Name of status variable, only applicable to survival data and needed if no formula given. Use 1 for event and 0 for censoring.
<code>classification</code>	Only needed if data is a matrix. Set to TRUE to grow a classification forest.

## Details

The tree type is determined by the type of the dependent variable. For factors classification trees are grown, for numeric values regression trees and for survival objects survival trees. The Gini index is used as default splitting rule for classification. For regression, the estimated response variances or maximally selected rank statistics (Wright et al. 2016) can be used. For Survival the log-rank test, a C-index based splitting rule (Schmid et al. 2015) and maximally selected rank statistics (Wright et al. 2016) are available. For all tree types, forests of extremely randomized trees (Geurts et al. 2006) can be grown.

With the probability option and factor dependent variable a probability forest is grown. Here, the node impurity is used for splitting, as in classification forests. Predictions are class probabilities for each sample. In contrast to other implementations, each tree returns a probability estimate and these estimates are averaged for the forest probability estimate. For details see Malley et al. (2012).

Note that for classification and regression nodes with size smaller than `min.node.size` can occur, as in original Random Forests. For survival all nodes contain at `min.node.size` samples. Variables selected with `always.split.variables` are tried additionally to the `mtry` variables randomly selected. In `split.select.weights` variables weighted with 0 are never selected and variables with 1 are always selected. Weights do not need to sum up to 1, they will be normalized later. The weights are assigned to the variables in the order they appear in the formula or in the data if no formula is used. Names of the `split.select.weights` vector are ignored. The usage of `split.select.weights` can increase the computation times for large forests.

Unordered factor covariates can be handled in 3 different ways by using `respect.unordered.factors`: For 'ignore' all factors are regarded ordered, for 'partition' all possible 2-partitions are considered for splitting. For 'order' and 2-class classification the factor levels are ordered by their proportion falling in the second class, for regression by their mean response, as described in Hastie et al. (2009), chapter 9.2.4. For multiclass classification and survival outcomes, 'order' is experimental

and should be used with care. The use of 'order' is recommended for 2-class classification and regression, as it is computationally fast and can handle an unlimited number of factor levels. Note that the factors are only reordered once and not again in each split.

For a large number of variables and data frames as input data the formula interface can be slow or impossible to use. Alternatively `dependent.variable.name` (and `status.variable.name` for survival) can be used. Consider setting `save.memory = TRUE` if you encounter memory problems for very large datasets, but be aware that this option slows down the tree growing.

For GWAS data consider combining `ranger` with the `GenABEL` package. See the Examples section below for a demonstration using `Plink` data. All SNPs in the `GenABEL` object will be used for splitting. To use only the SNPs without sex or other covariates from the phenotype file, use `0` on the right hand side of the formula. Note that missing values are treated as an extra category while splitting.

See <https://github.com/imbs-hl/ranger> for the development version.

With recent R versions, multithreading on Windows platforms should just work. If you compile yourself, the new RTools toolchain is required.

## Value

Object of class `ranger` with elements

<code>forest</code>	Saved forest (If <code>write.forest</code> set to <code>TRUE</code> ). Note that the variable IDs in the <code>split.varIDs</code> object do not necessarily represent the column number in R.
<code>predictions</code>	Predicted classes/values, based on out of bag samples (classification and regression only).
<code>variable.importance</code>	Variable importance for each independent variable.
<code>prediction.error</code>	Overall out of bag prediction error. For classification this is the fraction of misclassified samples, for regression the mean squared error and for survival one minus Harrell's c-index.
<code>r.squared</code>	R squared. Also called explained variance or coefficient of determination (regression only). Computed on out of bag data.
<code>confusion.matrix</code>	Contingency table for classes and predictions based on out of bag samples (classification only).
<code>unique.death.times</code>	Unique death times (survival only).
<code>chf</code>	Estimated cumulative hazard function for each sample (survival only).
<code>survival</code>	Estimated survival function for each sample (survival only).
<code>call</code>	Function call.
<code>num.trees</code>	Number of trees.
<code>num.independent.variables</code>	Number of independent variables.
<code>mtry</code>	Value of <code>mtry</code> used.
<code>min.node.size</code>	Value of minimal node size used.

treetype           Type of forest/tree. classification, regression or survival.  
 importance.mode           Importance mode used.  
 num.samples        Number of samples.  
 inbag.counts       Number of times the observations are in-bag in the trees.

### Author(s)

Marvin N. Wright

### References

- Wright, M. N. & Ziegler, A. (2017). ranger: A Fast Implementation of Random Forests for High Dimensional Data in C++ and R. *J Stat Softw* 77:1-17. <http://dx.doi.org/10.18637/jss.v077.i01>.
- Schmid, M., Wright, M. N. & Ziegler, A. (2016). On the use of Harrell's C for clinical risk prediction via random survival forests. *Expert Syst Appl* 63:450-459. <http://dx.doi.org/10.1016/j.eswa.2016.07.018>.
- Wright, M. N., Dankowski, T. & Ziegler, A. (2017). Unbiased split variable selection for random survival forests using maximally selected rank statistics. *Stat Med*. <http://dx.doi.org/10.1002/sim.7212>.
- Breiman, L. (2001). Random forests. *Mach Learn*, 45(1), 5-32. <http://dx.doi.org/10.1023/A:1010933404324>.
- Ishwaran, H., Kogalur, U. B., Blackstone, E. H., & Lauer, M. S. (2008). Random survival forests. *Ann Appl Stat* 2:841-860. <http://dx.doi.org/10.1097/JTO.0b013e318233d835>.
- Malley, J. D., Kruppa, J., Dasgupta, A., Malley, K. G., & Ziegler, A. (2012). Probability machines: consistent probability estimation using nonparametric learning machines. *Methods Inf Med* 51:74-81. <http://dx.doi.org/10.3414/ME00-01-0052>.
- Hastie, T., Tibshirani, R., Friedman, J. (2009). *The Elements of Statistical Learning*. Springer, New York. 2nd edition.
- Geurts, P., Ernst, D., Wehenkel, L. (2006). Extremely randomized trees. *Mach Learn* 63:3-42. <http://dx.doi.org/10.1007/s10994-006-6226-1>.

### See Also

[predict.ranger](#)

### Examples

```
require(ranger)

## Classification forest with default settings
ranger(Species ~ ., data = iris)

## Prediction
train.idx <- sample(nrow(iris), 2/3 * nrow(iris))
iris.train <- iris[train.idx, ]
```



```

iris.test <- iris[-train.idx, ]
rg.iris <- ranger(Species ~ ., data = iris.train, write.forest = TRUE)
pred.iris <- predict(rg.iris, dat = iris.test)
table(iris.test$Species, pred.iris$predictions)

## Variable importance
rg.iris <- ranger(Species ~ ., data = iris, importance = "impurity")
rg.iris$variable.importance

## Survival forest
require(survival)
rg.veteran <- ranger(Surv(time, status) ~ ., data = veteran)
plot(rg.veteran$unique.death.times, rg.veteran$survival[,])

## Alternative interface
ranger(dependent.variable.name = "Species", data = iris)

## Not run:
## Use GenABEL interface to read Plink data into R and grow a classification forest
## The ped and map files are not included
library(GenABEL)
convert.snp.ped("data.ped", "data.map", "data.raw")
dat.gwaa <- load.gwaa.data("data.pheno", "data.raw")
phdata(dat.gwaa)$trait <- factor(phdata(dat.gwaa)$trait)
ranger(trait ~ ., data = dat.gwaa)

## End(Not run)

```

---

timepoints.ranger      *Ranger timepoints*

---

## Description

Extract unique death times of Ranger Survival forest

## Usage

```
## S3 method for class 'ranger'
timepoints(x, ...)
```

## Arguments

x                      Ranger Survival forest object.  
...                     Further arguments passed to or from other methods.

## Value

Unique death times

**Author(s)**

Marvin N. Wright

**See Also**

[ranger](#)

---

`timepoints.ranger.prediction`

*Ranger timepoints*

---

**Description**

Extract unique death times of Ranger Survival prediction object.

**Usage**

```
## S3 method for class 'ranger.prediction'  
timepoints(x, ...)
```

**Arguments**

<code>x</code>	Ranger Survival prediction object.
<code>...</code>	Further arguments passed to or from other methods.

**Value**

Unique death times

**Author(s)**

Marvin N. Wright

**See Also**

[ranger](#)

# Index

csrf, [2](#)

getTerminalNodeIDs, [3](#)

holdoutRF, [4](#)

importance (importance.ranger), [5](#)  
importance.ranger, [5](#)  
importance\_pvalues, [5](#)

parse.formula, [6](#)  
predict.ranger, [7](#), [16](#)  
predict.ranger.forest, [8](#)  
predictions  
    (predictions.ranger.prediction),  
    [10](#)  
predictions.ranger, [9](#)  
predictions.ranger.prediction, [10](#)  
print.ranger, [11](#)  
print.ranger.forest, [11](#)  
print.ranger.prediction, [12](#)

ranger, [4-6](#), [8-11](#), [12](#), [18](#)

timepoints (timepoints.ranger), [17](#)  
timepoints.ranger, [17](#)  
timepoints.ranger.prediction, [18](#)