

Package ‘readODS’

November 26, 2018

Type Package

Title Read and Write ODS Files

Version 1.6.7

Date 2018-11-25

Author Gerrit-Jan Schutten, Chung-hong Chan, Thomas J. Leeper and other contributors

Maintainer Chung-hong Chan <chainsawtiney@gmail.com>

Contact <https://github.com/chainsawriot/readODS/>

Description Import ODS (OpenDocument Spreadsheet) into R as a data frame. Also support writing data frame into ODS file.

Imports xml2 (>= 1.0.0), cellranger, readr, stringi

Suggests dplyr, testthat, datasets

License GPL-3

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2018-11-26 05:40:03 UTC

R topics documented:

get_num_sheet_in_ods	2
ods_sheets	2
read_ods	3
write_ods	4

Index	5
--------------	----------

get_num_sheet_in_ods *get the number of sheets in an ods file*

Description

get the number of sheets in an ods file

Usage

get_num_sheet_in_ods(file)

getNrOfSheetsInODS(file)

Arguments

file the name of the ods file

Author(s)

Chung-hong Chan <chainsawtiney@gmail.com>, Gerrit-Jan Schutten <phonixor@gmail.com>

See Also

use [read_ods](#) to read the data

ods_sheets *List all sheets in an ods file.*

Description

List all sheets in an ods file.

Usage

ods_sheets(path)

Arguments

path Path to the ods file

read_ods	<i>read data from ods files</i>
----------	---------------------------------

Description

read_ods is a function to read a single sheet from an ods file and return a data frame. read.ods always returns a list of data frames with one data frame per sheet. This is a wrapper to read_ods for backward compatibility with previous version of readODS. Please use read_ods if possible.

Usage

```
read_ods(path = NULL, sheet = 1, col_names = TRUE,
         col_types = NULL, na = "", skip = 0, formula_as_formula = FALSE,
         range = NULL)
```

```
read.ods(file = NULL, sheet = NULL, formulaAsFormula = FALSE)
```

Arguments

path	path to the ods file.
sheet	sheet to read. Either a string (the sheet name), or an integer sheet number. The default is 1.
col_names	indicating whether the file contains the names of the variables as its first line.
col_types	Either NULL to guess from the spreadsheet or refer to readr::type_convert to specify cols specification. NA will return a data frame with all columns being "characters".
na	Character vector of strings to use for missing values. By default read_ods converts blank cells to missing data.
skip	the number of lines of the data file to skip before beginning to read data.
formula_as_formula	a switch to display formulas as formulas "SUM(A1:A3)" or as the resulting value "3"... or "8"..
range	selection of rectangle using Excel-like cell range, such as range = "D12:F15" or range = "R1C12:R6C15". Cell range processing is handled by the cellranger package.
file	for read.ods only, path to the ods file.
formulaAsFormula	for read.ods only, a switch to display formulas as formulas "SUM(A1:A3)" or as the resulting value "3"... or "8"..

Value

A data frame (data.frame) containing a representation of data in the ods file.

Note

Currently, ods files that linked to external data source cannot be read. Merged cells cannot be parsed correctly.

Author(s)

Chung-hong Chan <chainsawtiney@gmail.com>, Gerrit-Jan Schutten <phonixor@gmail.com>

write_ods

write data to ods file

Description

Function to write a single data.frame to an ods file and return a data frame.

Usage

```
write_ods(x, path)
```

Arguments

x	a data.frame
path	Path to the ods file to write.

Value

the value of path invisibly.

Author(s)

Thomas J. Leeper <thosjleeper@gmail.com>

Index

cellranger, 3

get_num_sheet_in_ods, 2

getNrOfSheetsInODS

(get_num_sheet_in_ods), 2

ods_sheets, 2

read.ods (read_ods), 3

read_ods, 2, 3

write_ods, 4