

# Package ‘rspm’

December 22, 2022

**Type** Package

**Title** 'RStudio' Package Manager

**Version** 0.3.0

**Description** Enables binary package installations on Linux distributions. Provides access to 'RStudio' public repositories at <https://packagemanager.rstudio.com>, and transparent management of system requirements without administrative privileges. Currently supported distributions are 'CentOS' / 'RHEL' 7-9, and several 'RHEL' derivatives ('Rocky Linux', 'AlmaLinux', 'Oracle Linux', and 'Amazon Linux' 2), 'openSUSE' / 'SLES' 15.3-4, and 'Ubuntu' 18.04, 20.04 and 22.04.

**License** GPL-2 | GPL-3 | MIT + file LICENSE

**Copyright** file COPYRIGHTS

**Encoding** UTF-8

**OS\_type** unix

**Suggests** renv, tinytest

**URL** <https://enchufa2.github.io/rspm/>

**BugReports** <https://github.com/Enchufa2/rspm/issues>

**RoxygenNote** 7.2.2

**NeedsCompilation** no

**Author** Iñaki Ucar [aut, cph, cre] (<<https://orcid.org/0000-0001-6403-5550>>),  
R Core Team [aut, cph]

**Maintainer** Iñaki Ucar <iucar@fedoraproject.org>

**Repository** CRAN

**Date/Publication** 2022-12-22 08:50:16 UTC

## R topics documented:

rspm-package . . . . .	2
integration . . . . .	2
manager . . . . .	3
renv_init . . . . .	4

**Index****5**

---

rspm-package	<b>rspm</b> : <i>RStudio Package Manager</i>
--------------	--

---

**Description**

Enables binary package installations on Linux distributions. Provides access to RStudio public repositories at <https://packagemanager.rstudio.com>, and transparent management of system requirements without administrative privileges. Currently supported distributions are CentOS / RHEL 7-9, and several RHEL derivatives (Rocky Linux, AlmaLinux, Oracle Linux, Amazon Linux 2), openSUSE / SLES 15.3-4, and Ubuntu 18.04, 20.04 and 22.04.

**Author(s)**

Iñaki Ucar

**References**

<https://enchufa2.github.io/rspm/>

**See Also**

[manager](#), [integration](#)

---

integration	<i>Enable/Disable RStudio Package Manager</i>
-------------	---

---

**Description**

Functions to enable or disable RSPM repos as well as the integration of [install\\_sysreqs](#) into `install.packages` and `update.packages`. When enabled, binary packages are installed from RSPM if available, and system requirements are transparently resolved and installed without root privileges.

**Usage**

```
enable()
```

```
disable()
```

**Details**

To enable **rspm** permanently, include the following into your `.Rprofile`:

```
suppressMessages(rspm::enable())
```

**Value**

No return value, called for side effects.

**See Also**

[renv\\_init](#) for **renv** projects.

**Examples**

```
## Not run:
# install 'units' and all its dependencies from the system repos
rspm::enable()
install.packages("units")

# install packages again from CRAN
rspm::disable()
install.packages("errors")

## End(Not run)
```

---

manager

*Manage System Requirements*

---

**Description**

Detect, install and configure system requirements. This function is automatically called when the package is enabled via [enable](#). It can also be called manually at any time to update the system requirements.

**Usage**

```
install_sysreqs()
```

**Value**

No return value, called for side effects.

**Examples**

```
## Not run:
# install 'units' without enabling the integration
install.packages("units")
# then trigger the installation of system requirements manually
rspm::install_sysreqs()

## End(Not run)
```

---

`renv_init`*Initialize an **renv** Project*

---

### Description

Substitutes `renv::init()` to initialize a new **renv** project with **rspm** enabled. This function sets the appropriate infrastructure to activate the integration. Then, packages can be installed normally via `install.packages` and `update.packages`.

### Usage

```
renv_init(...)
```

### Arguments

```
...           Arguments to be passed to renv::init().
```

### Details

Note that, if `renv::install` or `renv::update` are called directly, then `rspm::install_sysreqs()` needs to be called manually.

### Value

The project directory, invisibly. This function is called for its side effects.

### Examples

```
## Not run:
# initialize a new project (with an empty R library)
rspm::renv_init()

# install 'units' and all its dependencies from the system repos
install.packages("units")

# install a specific version and install dependencies manually
renv::install("units@0.8-0")
rspm::install_sysreqs()

## End(Not run)
```

# Index

`disable (integration)`, 2

`enable`, 3

`enable (integration)`, 2

`install_sysreqs`, 2

`install_sysreqs (manager)`, 3

`integration`, 2, 2

`manager`, 2, 3

`renv_init`, 3, 4

`rspm-package`, 2